

# NonLinearSystemNeuralNetworkFMU.jl

October 11, 2022

# Contents

<b>Contents</b>	<b>ii</b>
<b>I Home</b>	<b>1</b>
<b>1 NonLinearSystemNeuralNetworkFMU.jl</b>	<b>2</b>
1.1 Table of Contents . . . . .	2
1.2 Overview . . . . .	2
1.3 Installation . . . . .	3
<b>II Main</b>	<b>4</b>
<b>2 Main Data Generation Routine</b>	<b>5</b>
2.1 Functions . . . . .	5
<b>III Profiling</b>	<b>7</b>
<b>3 Profiling Modelica Models</b>	<b>8</b>
3.1 Functions . . . . .	8
3.2 Structures . . . . .	9
3.3 Examples . . . . .	10
<b>IV Data Generation</b>	<b>11</b>
<b>4 Training Data Generation</b>	<b>12</b>
4.1 Functions . . . . .	12
4.2 Examples . . . . .	14

**Part I**

**Home**

## Chapter 1

# NonLinearSystemNeuralNetworkFMU.jl

Generate Neural Networks to replace non-linear systems inside OpenModelica 2.0 FMUs.

### 1.1 Table of Contents

- [Training Data Generation](#)
  - [Functions](#)
  - [Examples](#)
- [NonLinearSystemNeuralNetworkFMU.jl](#)
  - [Table of Contents](#)
  - [Overview](#)
  - [Installation](#)
- [Main Data Generation Routine](#)
  - [Functions](#)
- [Profiling Modelica Models](#)
  - [Functions](#)
  - [Structures](#)
  - [Examples](#)

### 1.2 Overview

The package generates an FMU from a modelica file in 3 steps (+ 1 user step):

1. Find non-linear equation systems to replace.
  - Simulate and profile Modelica model with OpenModelica using [OMJulia.jl](#).
  - Find slowest equations below given threshold.
  - Find depending variables specifying input and output for every non-linear equation system.
  - Find min-max ranges for input variables by analyzing the simulation results.
2. Generate training data.

- Generate 2.0 Model Exchange FMU with OpenModelica.
  - Add C interface to evaluate single non-linear equation system without evaluating anything else.
  - Re-compile FMU.
  - Initialize FMU using `FMI.jl`.
  - Generate training data for each equation system by calling new interface.
3. Train neural network.
    - Step performed by user.
  4. Integrate neural network into FMU
    - Replace equations with neural network in generated C code.
    - Re-compile FMU.

### 1.3 Installation

Clone this repository to your machine and use the package manager Pkg to develop this package.

```
| (@v1.7) pkg> dev /path/to/NonLinearSystemNeuralNetworkFMU  
| julia> using NonLinearSystemNeuralNetworkFMU
```

**Part II**

**Main**

## Chapter 2

# Main Data Generation Routine

To perform all needed steps for data generation the following functions have to be executed:

1. `profiling`
2. `minMaxValuesReSim`
3. `generateFMU`
4. `addEqInterface2FMU`
5. `generateTrainingData`

These functionalities are bundled in `main`.

### 2.1 Functions

`NonLinearSystemNeuralNetworkFMU.main` - Function.

```
|main(modelName, moFiles; workdir=joinpath(pwd(),modelName), reuseArtifacts=false, N=1000)
```

Main routine to generate training data from Modelica file(s). Generate BSON artifacts and FMUs for each step. Artifacts can be re-used when restarting main routine to skip already performed steps.

Will perform profiling, min-max value compilation, FMU generation and data generation for all non-linear equation systems of `modelName`.

#### Arguments

- `modelName::String`: Name of Modelica model to simulate.
- `moFiles::Array{String}`: Path to .mo file(s).

#### Keywords

- `workingDir::String=pwd()`: Working directory for omc. Defaults to the current directory.
- `reuseArtifacts=false`: Use artifacts to skip already performed steps if true.

-`N=1000::Integer`: Number of data points to generate for each non-linear equation system.

#### Returns

- `csvFiles::Array{String}`: Array of generate CSV files with training data.
- `fmu::String`: Path to unmodified 2.0 ME FMU.
- `profilingInfo::Array{ProfilingInfo}`: Array of profiling information for each non-linear equation system.

See also [profiling](#), [minMaxValuesReSim](#), [generateFMU](#), [addEqInterface2FMU](#), [generateTrainingData](#).

[source](#)



## **Part III**

# **Profiling**

## Chapter 3

# Profiling Modelica Models

### 3.1 Functions

NonLinearSystemNeuralNetworkFMU.profiling - Function.

```
| profiling(modelName, moFiles; pathToOmc, workingDir, threshold = 0.03)
```

Find equations of Modelica model that are slower then threshold.

#### Arguments

- `modelName::String`: Name of the Modelica model.
- `moFiles::Array{String}`: Path to the \*.mo file(s) containing the model.

#### Keywords

- `pathToOmc::String=""`: Path to omc used for simulating the model. Use omc from PATH/OPENMODELICAHOME if nothing is provided.
- `workingDir::String=pwd()`: Working directory for omc. Defaults to the current directory.
- `threshold=0.01`: Slowest equations that need more then threshold of total simulation time.
- `ignoreInit::Bool=true`: Ignore equations from initialization system if true.

#### Returns

- `profilingInfo::Vector{ProfilingInfo}`: Profiling information with non-linear equation systems slower than threshold.

[source](#)

NonLinearSystemNeuralNetworkFMU.minMaxValuesReSim - Function.

```
| minMaxValuesReSim(vars, modelName, moFiles; pathToOmc="" workingDir=pwd())
```

(Re-)simulate Modelica model and find minimum and maximum value each variable has during simulation.

#### Arguments

- `vars::Array{String}`: Array of variables to get min-max values for.
- `modelName::String`: Name of Modelica model to simulate.

- `moFiles::Array{String}`: Path to .mo file(s).

### Keywords

- `pathToOmc::String=""`: Path to OpenModelica Compiler omc.
- `workingDir::String=pwd()`: Working directory for omc. Defaults to the current directory.

### Returns

- `min::Array{Float64}`: Minimum values for each variable listed in vars, minus some small epsilon.
- `max::Array{Float64}`: Maximum values for each variable listed in vars, plus some small epsilon.

See also [profiling](#).

[source](#)

## 3.2 Structures

`NonLinearSystemNeuralNetworkFMU.ProfilingInfo` – Type.

| `ProfilingInfo` <: **Any**

Profiling information for single non-linear equation.

- `eqInfo::EqInfo`  
Non-linear equation
- `iterationVariables::Array{String}`  
Iteration (output) variables of non-linear system
- `innerEquations::Array{Int64}`  
Inner (torn) equations of non-linear system.
- `usingVars::Array{String}`  
Used (input) variables of non-linear system.

[source](#)

`NonLinearSystemNeuralNetworkFMU.EqInfo` – Type.

| `EqInfo` <: **Any**

Equation info struct.

- `id::Int64`  
Unique equation id
- `ncall::Int64`  
Number of calls during simulation
- `time::Float64`  
Total time [s] spend on evaluating this equation.
- `maxTime::Float64`  
Maximum time [s] needed for single evaluation of equation.
- `fraction::Float64`  
Fraction of total simulation time spend on evaluating this equation.

[source](#)

### 3.3 Examples

#### Find Slowest Non-linear Equation Systems

We have a Modelica model SimpleLoop, see [test/simpleLoop.mo](#) with some non-linear equation system

$$r^2 = x^2 + y^2$$

$$rs = x + y$$

We want to see how much simulation time is spend solving this equation. So let's start [profiling](#):

```
julia> using NonLinearSystemNeuralNetworkFMU

julia> modelName = "simpleLoop";

julia> moFiles = [joinpath("test", "simpleLoop.mo")];

julia> profilingInfo = profiling(modelName, moFiles, omc; threshold=0)
ERROR: MethodError: no method matching profiling(::String, ::Vector{String}, ::String; threshold=0)
Closest candidates are:
  profiling(::String, ::Array{String}; pathToOmc, workingDir, threshold, ignoreInit) at
  ↪ ~/work/NonLinearSystemNeuralNetworkFMU.jl/NonLinearSystemNeuralNetworkFMU.jl/src/profiling.jl:331
```

We can see that non-linear equation system 14 is using variables s and r as input and has iteration variable y. x will be computed in the inner equation.

```
julia> profilingInfo[1].usingVars
ERROR: UndefVarError: profilingInfo not defined

julia> profilingInfo[1].iterationVariables
ERROR: UndefVarError: profilingInfo not defined
```

So we can see, that equations 14 is the slowest non-linear equation system. It is called 2512 times and needs around 15% of the total simulation time, in this case that is around 592  $\mu s$ .

If we want to get the minimal and maximal values for the used variables s and r can get we can use [minMaxValuesReSim](#). This will re-simulate the Modelica model and read the simulation results to find the smallest and largest values for each given variable.

```
julia> (min, max) = minMaxValuesReSim(profilingInfo[1].usingVars, modelName, moFiles, omc)
ERROR: UndefVarError: profilingInfo not defined
```

## **Part IV**

# **Data Generation**

## Chapter 4

# Training Data Generation

To generate training data for the slowest non-linear equations found during [Profiling Modelica Models](#) we now simulate the equations multiple time and save in- and outputs.

We will use the [Functional Mock-up Interface \(FMI\)](#) standard to generate FMU that we extend with some function to evaluate single equations without the need to simulate the rest of the model.

### 4.1 Functions

`NonLinearSystemNeuralNetworkFMU.generateFMU` – Function.

```
| generateFMU(modelName, moFiles; [pathToOmc], workingDir=pwd(), clean=false)
```

Generate 2.0 Model Exchange FMU for Modelica model using OMJulia.

#### Arguments

- `modelName::String`: Name of the Modelica model.
- `moFiles::Array{String}`: Path to the \*.mo file(s) containing the model.

#### Keywords

- `pathToOmc::String=""`: Path to omc used for simulating the model. Use omc from PATH/OPENMODELICAHOME if nothing is provided.
- `workingDir::String=pwd()`: Path to temp directory in which FMU will be saved to.
- `clean::Bool=false`: True if workingDir should be removed and re-created before working in it.

#### Returns

- Path to generated FMU `workingDir/<modelName>.fmu`.

See also [addEqInterface2FMU](#), [generateTrainingData](#).

[source](#)

`NonLinearSystemNeuralNetworkFMU.addEqInterface2FMU` – Function.

```
| addEqInterface2FMU(modelName, pathToFmu, eqIndices; workingDir=pwd())
```

Create extendedFMU with special\_interface to evaluate single equations.

### Arguments

- modelName::String: Name of Modelica model to export as FMU.
- pathToFmu::String: Path to FMU to extend.
- eqIndices::Array{Int64}: Array with equation indices to add equation interface for.

### Keywords

- workingDir::String=pwd(): Working directory. Defaults to current working directory.

### Returns

- Path to generated FMU workingDir/<modelName>.interface.fmu.

See also [profiling](#), [generateFMU](#), [generateTrainingData](#).

[source](#)

NonLinearSystemNeuralNetworkFMU.generateTrainingData - Function.

```
generateTrainingData(fmuPath::String,
                    fname::String,
                    eqId::Int64,
                    inputVars::Array{String},
                    min::AbstractVector{<:Number},
                    max::AbstractVector{<:Number},
                    outputVars::Array{String};
                    N::Integer=1000)
```

Generate training data for given equation of FMU.

Generate random inputs between min and max, evaluate equation and compute output. All input-output pairs are saved in fname.

### Arguments

- fmuPath::String: Path to FMU.
- fname::String: File name to save training data to.
- eqId::Int64: Index of equation to generate training data for.
- inputVars::Array{String}: Array with names of input variables.
- min::AbstractVector{<:Number}: Array with minimum value for each input variable.
- max::AbstractVector{<:Number}: Array with maximum value for each input variable.
- outputVars::Array{String}: Array with names of output variables.

### Keywords

- N::Integer = 1000: Number of input-output pairs to generate.

See also [generateFMU](#), [generateFMU](#).

[source](#)

## 4.2 Examples

First we need to create a Model-Exchange 2.0 FMU with OpenModelica.

This can be done directly from OpenModelica or with `generateFMU`:

```
fmu = generateFMU("simpleLoop",
                  ["test/simpleLoop.mo"];
                  pathToOmc = omc,
                  workingDir = "tempDir")
```

```
[ Info: Path to zmq file="/tmp/openmodelica.runner.port.julia.sCRTsA3o9C"
```

Next we need to add non-standard C function

```
fmi2Status myfmi2evaluateEq(fmi2Component c, const size_t eqNumber)
```

that will call `<modelName>_eqFunction_<eqIndex>(DATA* data, threadData_t *threadData)` for all non-linear equations we want to generate data for.

Using `addEqInterface2FMU` this C code will be generated and added to the FMU.

```
interfaceFmu = addEqInterface2FMU("simpleLoop",
                                  fmu,
                                  [14],
                                  workingDir = "tempDir")
rm("tempDir", recursive=true, force=true) #hide
```

Now we can create evaluate equation 14 for random values and save the outputs to generate training data.

```
using CSV
using DataFrames
generateTrainingData(interfaceFmu,
                     "simpleLoop_data.csv",
                     14,
                     ["s", "r"],
                     [0.0, 0.95],
                     [1.5, 3.15],
                     ["y"];
                     N = 10)
df = CSV.File("simpleLoop_data.csv")
rm("simpleLoop_data.csv", force=true) #hide
```