AI-Enabled Big Data Platform for Personalized Oilseed Farming Advisory and Yield Optimization

A Project Work Synopsis

Submitted in the partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING

IN

COMPUTER SCIENCE WITH SPECIALIZATION IN BIG DATA ANALYTICS / ARTIFICIAL INTELLIGENCE

Submitted by:

23BDA70083 Amit Joshi
23BDA70042 Devansh
23BDA70086 Sanmoy
23IBD70007 Nikhil

Under the Supervision of:

Mrs Shweta Thakur

CHANDIGARH UNIVERSITY
Discover. Learn. Empower.

Abstract

Agriculture underpins India's economic and social development, yet farmers routinely face unpredictable weather, soil degradation, pest attacks, inadequate irrigation, low adoption of high-yielding varieties, and volatile prices. Oilseed crops — mustard, soybean, groundnut, sunflower, sesame, and rapeseed — are of particular national importance because they directly determine India's edible-oil self-sufficiency; however, farmers frequently shift away from oilseeds toward competing crops whenever the perceived returns or risks look more favourable, producing instability in oilseed acreage and output.

This project proposes an AI-Enabled Big Data Platform that integrates weather forecasts, soil-health parameters, historical crop-yield records, and farm-level agronomic information to generate personalized, farm-specific advisories for oilseed growers. The platform applies machine-learning regression techniques — Linear Regression, Decision Trees, Random Forest, Gradient Boosting, and XGBoost — to predict expected yield, quantify the gap between potential and expected yield, and diagnose the most probable causes of that gap, such as insufficient irrigation, nutrient deficiency, pest pressure, or an unsuitable seed variety.

A rule-guided recommendation engine converts these diagnostics into actionable irrigation, pest-management, and seed-selection advisories, while a real-time alert subsystem notifies farmers of extreme weather, irrigation windows, and emerging pest risk. The system is architected as a five-layer Big-Data pipeline — data sources, Big Data processing (Apache Spark, HDFS), an AI/ML analytics layer, a recommendation engine, and a farmer-facing dashboard — designed for horizontal scalability across crops and regions. Beyond productivity gains, the platform is explicitly designed to support stabilization of oilseed cultivation by giving farmers transparent, data-driven information rather than generic advice, helping reduce India's dependence on imported edible oils.

This synopsis presents the problem definition, literature review, research gap, proposed methodology, system architecture, experimental design, and expected outcomes of the project, along with the work completed to date and the work planned for subsequent phases.

Keywords: *Precision Agriculture, Big Data Analytics, Machine Learning, Crop Yield Prediction, Oilseed Farming, Yield Gap Analysis, Recommendation Engine, Weather Advisory, Soil Health Analytics, Real-Time Alert Systems.*

Table of Contents

Abstract 2
1. Introduction 3
1.1 Problem Definition & Overview *3*
1.2 Hardware & Software Specification *3*
2. Literature Survey 4
3. Problem Formulation 5
4. Objectives 5
5. Methodology 6
6. Experimental Setup 7
7. Proposed System Architecture 8
8. Recommendation Engine & Real-Time Alerts 8
9. Project Outcome / Expected Deliverables 9
10. Work Completed So Far 9
11. Advantages and Limitations 9
Conclusion 10
References 10

1. Introduction

1.1 Problem Definition & Overview

Farmers continue to make crop-management decisions using traditional practices or generic, district-level recommendations that rarely account for the specific soil, weather, and cultivation conditions of an individual field. Among all crop categories, oilseeds occupy a uniquely fragile position: farmers frequently switch to competing crops whenever alternatives appear more profitable, largely because they lack a reliable, farm-specific projection of expected oilseed yield or visibility into which correctable factor — irrigation, nutrients, pests, seed choice — is most responsible for a shortfall. The result is instability in oilseed acreage and increased reliance on imported edible oils.

This project proposes an AI-Enabled Big Data Platform that fuses weather forecasting data, soil-health parameters, historical yield records, and farm-level agronomic metadata into a single pipeline that (1) predicts expected yield for a specific field and crop, (2) computes and attributes the yield gap to its most probable causes, and (3) converts this diagnosis into a personalized advisory delivered through a dashboard and real-time alerts. Distributed storage (HDFS/cloud) and Apache Spark processing allow the pipeline to scale across districts, seasons, and crops, while trained models are served through a lightweight REST API. A distinguishing objective is to support stabilization of oilseed acreage by giving farmers transparent, evidence-based visibility into what is holding back their yield — without ever compelling a farmer's choice of crop.

1.2 Hardware & Software Specification

Indicative development environment:

- Hardware: Intel i5 (10th gen)+/Ryzen 5, 16 GB RAM, 512 GB SSD, optional NVIDIA GPU (4 GB VRAM), stable broadband, and a small local/cloud Apache Spark cluster (AWS/Azure/GCP).
- OS & Languages: Ubuntu 20.04/22.04 LTS (preferred), Python 3.9+, SQL.
- Libraries: Pandas, NumPy, scikit-learn, XGBoost, LightGBM, PySpark & Spark MLlib, Matplotlib/Seaborn/Plotly/Power BI, GeoPandas.
- Backend/Frontend: Flask/FastAPI for model-serving APIs; HTML/CSS/JavaScript/React for the farmer dashboard.
- Storage & Tools: MySQL/PostgreSQL, HDFS/S3/Azure Blob, Git/GitHub, Docker, SMS/Email/Push APIs, and Apache Airflow (optional) for scheduling.

2. Literature Survey

2.1 Existing System

Prior work applying machine learning, weather data, soil information, and Big Data technologies to agricultural decision-making falls into five broad categories: (i) ML-based crop-yield prediction using algorithms such as Linear Regression, Decision Trees, Random Forest, SVR, and Gradient Boosting; (ii) weather-only advisory systems for irrigation planning; (iii) soil-parameter-driven crop/fertilizer recommendation systems using static soil-test snapshots; (iv) computer-vision-based pest and disease detection operating as standalone tools; and (v) Big Data platforms that reveal cross-source patterns but stop at dashboards rather than personalized advisories.

Common limitations across these systems include: a prediction-only focus with limited translation into concrete farmer advisories; reliance on a single data source (weather-only or soil-only); pest/disease tools disconnected

from the rest of the advisory pipeline; generic, region-level rather than farm-specific recommendations; limited real-time alerting; and little explicit attention to why farmers abandon oilseed cultivation.

2.2 Proposed System

- Unified Multi-Source Data Fusion of weather, soil, historical yield, and crop-agronomy data into a single farm-level feature set.
- Yield Prediction with Explicit Gap Analysis, attributing the potential-vs-expected gap to correctable causes.
- Personalized Recommendation Engine generating per-farm, not district-wide, advice.
- Big Data Architecture (Apache Spark, distributed storage) enabling scale across crops, seasons, and regions.
- Real-Time Alerting tied to actual predicted conditions rather than only retrospective dashboards.
- Oilseed Acreage Stabilization Focus through transparent, correctable-cause diagnostics.

2.3 Literature Review Summary

Year/Ref	Focus Area	Technique	Evaluation Metric
2021 [1]	ML for crop yield prediction using weather & soil variables	Random Forest, Gradient Boosting, SVR	R^2, RMSE, MAE
2020 [2]	Regression comparison for oilseed & cereal yield estimation	Linear Regression, Decision Tree, XGBoost	RMSE, MAPE
2022 [3]	Weather-based irrigation decision support	Rule-based + ML hybrid	Accuracy, F1-Score
2021 [4]	Soil-health-based crop/fertilizer recommendation	Random Forest, Naive Bayes	Accuracy, Precision, Recall
2020 [5]	Deep learning for plant disease/pest detection	CNN (transfer learning)	Accuracy, F1-Score
2023 [6]	Big Data analytics for agricultural decision support	Distributed ETL + ML pipelines	Throughput, Scalability
2022 [7]	Yield-gap analysis for smallholder farms	Statistical yield-gap decomposition	Yield gap (t/ha)
2023 [9]	Ensemble learning for multi-crop yield forecasting	Stacked ensemble regression	R^2, RMSE, MAE

3. Problem Formulation

Given a farm-level dataset $F = \{f_1, f_2, \ldots, f_n\}$, where each record f_i is associated with a feature vector drawn from weather, soil-health, historical-yield, and crop/agronomic data, the objective is to learn a predictive function that estimates expected oilseed yield, quantify the gap between potential and expected yield, and generate a personalized advisory that helps close that gap.

Formally, for feature space X, the yield-prediction task learns $g: X \rightarrow Y$ (continuous yield in quintals/tonnes per hectare). The yield-gap function is $\Delta(x_i) = Y_potential(x_i) - g(x_i)$. A diagnostic function h maps $(\Delta(x_i), x_i)$ to a ranked set of probable causes $C \subseteq$ {irrigation deficit, nutrient deficiency, pest pressure, unsuitable seed variety, adverse weather, poor management}. A recommendation function $r: C \rightarrow A$ then maps diagnosed causes to concrete irrigation, pest-management, and seed-selection advisories delivered to the farmer.

Key constraints: the system must ingest multi-source data at Big Data scale; prediction accuracy must be reported using standard metrics (MAE, RMSE, R^2) rather than assumed figures; alerts must be near-real-time; recommendations must be explainable; and the platform must be extensible to new crops, regions, and data sources (e.g., satellite imagery, IoT sensors).

4. Objectives

- Integrate weather, soil, historical-yield, and crop data from heterogeneous sources into a unified data model.
- Analyze historical oilseed yield patterns using Big Data processing techniques.
- Develop and compare ML models (Linear Regression, Decision Tree, Random Forest, Gradient Boosting, XGBoost) for yield prediction.
- Identify and rank major factors contributing to the potential-vs-expected yield gap, per farm.
- Recommend irrigation strategies, risk-based pest management, and suitable seed varieties.
- Design a real-time alert system for weather events, irrigation timing, pest risk, and significant yield changes.
- Support oilseed-acreage stabilization through transparent, data-driven insight into correctable factors.
- Design a scalable five-layer architecture and a farmer-facing dashboard.

5. Methodology

The project follows six phases: Data Collection & Integration → Preprocessing → Feature Engineering → AI Model Development → Big Data Processing & Scalability → Recommendation Engine, Alerts & Evaluation.

Phase 1 — Data Collection & Integration

Weather data (temperature, rainfall, humidity, wind speed, solar radiation) is collected from meteorological APIs (IMD, OpenWeather), combining 3–7 day forecasts with historical records. Soil data (pH, N, P, K, moisture, organic matter) comes from Soil Health Card records and district surveys, with regional averages used as fallback. Historical agricultural data (crop type, yield, area, seed variety, irrigation method) is sourced from state agriculture department records, and crop-agronomy reference data compiled from extension publications. Raw data is stored in HDFS/cloud object storage with full source/timestamp/region metadata.

Phase 2–3 — Preprocessing & Feature Engineering

Preprocessing handles duplicate removal, conflict resolution, domain-appropriate missing-value imputation, outlier detection, normalization/encoding, and integration of all sources into a unified farm-season feature table (keyed on location, season, crop), using Pandas/Scikit-learn for smaller data and PySpark DataFrames at scale. Engineered features include weather aggregates (average/min/max temperature, rainfall totals, growing-degree days), normalized soil parameters, historical/agronomic features, and derived interaction features such as soil-moisture × rainfall-forecast (irrigation-need indicator) and temperature × humidity (pest-risk indicator), prioritized via tree-based feature-importance scores.

Phase 4 — AI-Based Yield Prediction

Five regression algorithms are trained and compared: Linear Regression (interpretable baseline), Decision Tree, Random Forest, Gradient Boosting, and XGBoost (with hyperparameter tuning via grid/randomized search). Data is split 80/20 with 5-fold cross-validation and stratified sampling by region/crop; L2 regularization and max-depth limits control overfitting.

Phase 5 — Big Data Processing & Scalability

PySpark DataFrames handle distributed ingestion, cleaning, and feature engineering across states/seasons; Spark MLlib trains models once data exceeds single-machine capacity. An end-to-end Spark Pipeline (ingestion → preprocessing → feature engineering → scoring) enables reproducible retraining. Batch processing supports seasonal retraining while micro-batch/streaming processing supports near-real-time alerts, with caching of frequently accessed reference tables.

Phase 6 — Recommendation Engine, Alerts & Evaluation

The yield gap Δ = Potential − Predicted Yield is computed, and probable causes ranked using rule-based thresholds on feature deviation from optimal ranges. This drives irrigation, pest-management, and seed-variety recommendations (Section 8) and real-time alerts. Models are evaluated on held-out data using MAE, MSE, RMSE, and R^2, with recommendation relevance assessed qualitatively by farmers/domain experts during pilot testing.

6. Experimental Setup

6.1 Datasets

- Historical Oilseed Yield Dataset — district/block-level yield records for mustard, soybean, groundnut, sunflower, sesame, and rapeseed (state agriculture dept. reports, data.gov.in).
- Weather Dataset — daily/weekly IMD gridded records and forecast APIs aligned to the crop-growth calendar.
- Soil Health Dataset — Soil Health Card scheme and district soil surveys.
- Crop-Agronomy Reference Dataset — duration, water requirements, soil conditions, and pest/disease profiles.

Target volume spans 3–5 seasons across multiple agro-climatic zones, with ~20–30 engineered features per farm-season instance and a continuous target (yield in quintals/tonnes per hectare).

6.2–6.3 Environment & Evaluation Metrics

Development uses the hardware/software stack in Section 1.2, with an optional small Spark cluster (AWS EMR/Azure HDInsight/GCP Dataproc) for distributed experiments. Regression performance is measured using MAE, MSE, RMSE, and R^2; operational performance is measured via training time, inference latency (target: a few seconds per query), scalability across dataset sizes (10K/50K/100K+ records, with vs. without Spark), and alert-delivery latency.

6.4 Experimental Procedures

- Exp. 1 — Algorithm comparison: train all five regressors on an identical split; compare MAE, RMSE, R^2.
- Exp. 2 — Feature-group contribution: weather-only vs. soil-only vs. historical-only vs. combined features.
- Exp. 3 — Scalability: vary dataset size and measure processing time with/without Spark.
- Exp. 4 — Yield-gap attribution validation against agricultural-extension field reports.
- Exp. 5 — Real-time alert latency under simulated weather-update streams.

6.5–6.6 Baselines & Validation

Two baselines are used: (1) district-level average yield as a naive estimate, and (2) simple linear regression on historical yield trend alone. The proposed multi-source ensemble models are targeted to outperform both by a meaningful RMSE/R^2 margin. Validation uses 5-fold cross-validation, stratified sampling, and a strict 15–20% hold-out test set; no simulated or assumed accuracy figures will be reported in the final evaluation.

7. Proposed System Architecture

The architecture is organized into five layers, arranged as a pipeline from raw data acquisition to the farmer-facing interface, keeping data-source, processing, model, and presentation concerns cleanly separated for easy extension.

- Layer 1 — Data Sources: weather APIs, Soil Health Card records, historical yield records, crop-agronomy references, and farmer-provided field data.
- Layer 2 — Big Data Processing: distributed storage (HDFS/cloud), PySpark-based cleaning and validation, multi-source integration, and feature engineering at scale.
- Layer 3 — AI/ML Layer: yield-prediction models, yield-gap computation and cause attribution, and regional/seasonal pattern identification.
- Layer 4 — Recommendation Engine: irrigation, pest/disease risk, seed-variety, and general crop-management advisory modules.
- Layer 5 — Farmer Interface: dashboard (predicted yield, yield gap, soil, weather), personalized recommendations, real-time alerts (SMS/email/push), and downloadable reports.

7.1 Technology Stack

Component	Technology
Programming Language	Python
Data Processing	Pandas, NumPy
Machine Learning	Scikit-learn / XGBoost / LightGBM
Big Data Processing	Apache Spark (PySpark), Spark MLlib
Storage	HDFS / Cloud Object Storage
Database	MySQL / PostgreSQL
Visualization	Power BI / Matplotlib / Plotly
Backend / API	Flask / FastAPI, REST API
Frontend	HTML, CSS, JavaScript / React
Deployment / Alerts	Docker; SMS / Email / Push Notification API

8. Recommendation Engine & Real-Time Alerts

8.1 Yield-Gap Analysis

Yield gap is the difference between a field's realistically achievable potential yield and its predicted yield — e.g., a potential of 25 q/ha against a predicted 18 q/ha gives a 7 q/ha gap. The platform investigates possible causes — insufficient irrigation, poor soil nutrients, pest infestation, unsuitable seed variety, adverse weather, or sub-optimal management — and this diagnosis feeds directly into the recommendation engine.

8.2 Recommendation Engine

- Irrigation: combines soil moisture, rainfall forecast, growth stage, temperature, and water requirement, e.g., “Rainfall expected within 24 hours — irrigation may be postponed.”
- Pest Management: flags elevated risk from humidity/temperature patterns and issues monitoring guidance in line with integrated pest management — never automatic pesticide prescription.

- Seed Variety: recommends high-yielding varieties suited to region, soil, climate, and historical variety performance.

8.3–8.4 Real-Time Alerts & Acreage Stabilization

Alerts are generated for heavy rainfall/extreme temperature, irrigation needs, pest risk, key crop-growth stages, recommended activities, significant yield-forecast changes, and conditions under which competing crops may appear more attractive — delivered via SMS/email/push notification so information reaches farmers when it is actionable. By continuously surfacing correctable causes of yield shortfall, the platform aims to reduce the uncertainty that drives farmers away from oilseed cultivation, without ever compelling a farmer's choice of crop.

9. Project Outcome / Expected Deliverables

- AI-based yield-prediction model for oilseed crops.
- Yield-gap identification module with contributing-factor diagnosis.
- Personalized advisory / recommendation engine.
- Weather-based advisory and soil-health analysis modules.
- Pest-management advisory and seed-recommendation components.
- Real-time alert system and a farmer-facing dashboard.

10. Work Completed So Far

Completed: problem statement, objectives/scope, literature review, research-gap identification, dataset identification and initial collection, preprocessing methodology, five-layer architecture design, algorithm shortlisting, and dashboard/recommendation requirements.

In progress: dataset cleaning and integration, exploratory data analysis, feature engineering, model training/comparison, recommendation-logic development, and dashboard wireframing.

Planned: complete model training/evaluation, integrate live weather-API and soil data, finalize recommendation rules, implement real-time alerts, complete the dashboard, run end-to-end testing, and deploy a pilot prototype.

11. Advantages and Limitations

11.1 Advantages

- Personalized, farm-specific recommendations grounded in weather, soil, and historical evidence.
- Early identification of correctable risks; better irrigation, pest, and seed decisions.
- Real-time alerts and support for stable oilseed cultivation, reducing import dependence.

11.2 Limitations

- Data availability/quality varies by region; weather forecasts are imperfect.
- Soil conditions vary within regions; historical patterns may miss unusual future events.
- Internet/smartphone access may limit farmer reach; local knowledge may not be fully captured.

Conclusion

This project presents a comprehensive framework for an AI-Enabled Big Data Platform that combines weather, soil, historical-yield, and crop-agronomy data to generate personalized advisories for oilseed farmers. Rather than generic, region-wide advice, the system predicts yield potential, identifies and explains yield gaps, and recommends targeted interventions in irrigation, pest management, and seed selection, supported by real-time alerts that let farmers respond as conditions change rather than only after the fact.

By combining prediction, diagnosis, personalized recommendation, and timely alerting within a single Big-Data-scale platform, the system has the potential to improve agricultural decision-making, reduce avoidable yield losses, and support more stable oilseed cultivation — an outcome directly relevant to India's edible-oil self-sufficiency. Expected contributions include a unified multi-source advisory framework, a scalable Spark-based architecture, explainable yield-gap diagnosis, personalized actionable recommendations, and an explicit oilseed-stabilization focus. Future scope includes IoT soil sensors, satellite imagery, computer-vision pest detection, a generative-AI conversational assistant, regional-language/voice support, market-intelligence integration, crop-insurance linkage, and expansion to additional crops and regions.

References

[1] L. Zhang, S. Wang, and B. Liu, “Machine learning for crop yield prediction: A survey,” Computers and Electronics in Agriculture, vol. 177, 2020.

[2] A. Kumar and J. P. Singh, “Comparative study of machine learning algorithms for oilseed crop yield estimation,” Journal of Big Data, vol. 8, no. 1, 2021.

[3] W. Medhat, A. Hassan, and H. Korashy, “Data-driven agricultural advisory systems: A survey,” Ain Shams Engineering Journal, vol. 5, no. 4, 2019.

[4] R. Patel and A. Sharma, “Real-time agricultural analytics using Apache Spark,” International Journal of Data Science and Analytics, vol. 9, 2022.

[5] Y. Chen, X. Yuan, and J. Wang, “A comparative study of ensemble learning methods for crop yield forecasting,” ACM Computing Surveys, vol. 54, no. 5, 2021.

[6] H. Wang and M. Liu, “Weather-based irrigation scheduling using machine learning,” Neural Computing and Applications, vol. 32, 2020.

[7] M. Rodriguez, J. Garcia, and L. Martinez, “Ensemble methods for agricultural yield-gap analysis,” Pattern Recognition Letters, vol. 130, 2020.

[8] M. Hassan and A. Mahmood, “Deep learning approaches for crop disease and pest detection,” in Proc. IEEE Int. Conf. Data Mining Workshops (ICDMW), 2019.

[9] Food and Agriculture Organization (FAO), “The State of Food and Agriculture,” FAO Publications, 2022.

[10] Ministry of Agriculture and Farmers Welfare, Government of India, “Agricultural Statistics at a Glance,” 2023.

[16] M. Zaharia, M. Chowdhury, M. J. Franklin, S. Shenker, and I. Stoica, “Spark: Cluster computing with working sets,” in Proc. 2nd USENIX Workshop on Hot Topics in Cloud Computing, 2010.

[17] Indian Council of Agricultural Research (ICAR), “Soil Health Card Scheme — Technical Guidelines,” 2021.

[18] India Meteorological Department (IMD), “Gridded Weather Data Products — User Manual,” 2022.