

Logic Design

Tutorial 3

Amr Keleg

Faculty of Engineering, Ain Shams University

July 30, 2020

Contact: amr_mohamed@live.com

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
- 3 Unsigned binary multiplication
- 4 Binary and Gray code

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Assume we have 4 bits to represent numbers on our system.

- We can represent 16 unsigned values $[0, 15]$.

Assume we have 4 bits to represent numbers on our system.

- We can represent 16 unsigned values $[0, 15]$.
- What if we want to represent negative values as well?

Assume we have 4 bits to represent numbers on our system.

- We can represent 16 unsigned values $[0, 15]$.
- What if we want to represent negative values as well?

Table 1.3
Signed Binary Numbers

Decimal	Signed Magnitude
+7	0111
+6	0110
+5	0101
+4	0100
+3	0011
+2	0010
+1	0001
+0	0000
-0	1000
-1	1001
-2	1010
-3	1011
-4	1100
-5	1101
-6	1110
-7	1111
-8	—

Table 1.3
Signed Binary Numbers

Decimal	Signed-2's Complement	Signed Magnitude
+7	0111	0111
+6	0110	0110
+5	0101	0101
+4	0100	0100
+3	0011	0011
+2	0010	0010
+1	0001	0001
+0	0000	0000
-0	—	1000
-1	1111	1001
-2	1110	1010
-3	1101	1011
-4	1100	1100
-5	1011	1101
-6	1010	1110
-7	1001	1111
-8	1000	—

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) =$$

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) = (1110) \text{ which is}$$

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) = (1110) \text{ which is } -2 !!$$

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) = (1110) \text{ which is } -2 !!$$

Therefore we need to have another bit to handle this overflow:

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) = (1110) \text{ which is } -2 !!$$

Therefore we need to have another bit to handle this overflow: $(\mathbf{0}0111) + (\mathbf{0}0111) = \mathbf{0}1110$

How to add two numbers in signed two's complement representation?

Example:

$$(+7) + (+7) = ??$$

$$(0111) + (0111) = (1110) \text{ which is } -2 !!$$

Therefore we need to have another bit to handle this overflow: $(\mathbf{0}0111) + (\mathbf{0}0111) = \mathbf{0}1110$

- The result is positive since the sign bit is equal to zero
- The value is $8 + 4 + 2 = 14$ (Makes sense now)

What about $(-7) + (-7)$?

What about $(-7) + (-7)$?

$$+7 = (00111)$$

$$-7 = (11001)$$

What about $(-7) + (-7)$?

$$+7 = (00111)$$

$$-7 = (11001)$$

$$(11001) + (11001) = 110010 \text{ (Ignore the overflow).}$$

The result is 10010.

What about $(-7) + (-7)$?

$$+7 = (00111)$$

$$-7 = (11001)$$

$$(11001) + (11001) = 110010 \text{ (Ignore the overflow).}$$

The result is 10010.

- The result is negative since the sign bit is equal to one
- Its two's complement is 01110
- The value is $-(8 + 4 + 2) = -14$ (Makes sense now)

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Q17) Convert decimal +49 and +29 to binary, using the signed 2's complement representation and enough digits to accommodate the numbers. Then perform the binary equivalent of $(+29) + (-49)$, $(-29) + (+49)$, and $(-29) + (-49)$. Convert the answers back to decimal and verify that they are correct.

Q17) Convert decimal +49 and +29 to binary, using the signed 2's complement representation and enough digits to accommodate the numbers. Then perform the binary equivalent of $(+29) + (-49)$, $(-29) + (+49)$, and $(-29) + (-49)$. Convert the answers back to decimal and verify that they are correct.

- $49_{10} = 110001_2$
- $29_{10} = \mathbf{0}11101_2$

Q17) Convert decimal +49 and +29 to binary, using the signed 2's complement representation and enough digits to accommodate the numbers. Then perform the binary equivalent of $(+29) + (-49)$, $(-29) + (+49)$, and $(-29) + (-49)$. Convert the answers back to decimal and verify that they are correct.

- $49_{10} = 110001_2$
- $29_{10} = \mathbf{0}11101_2$
- Add two bits, one for sign and one for overflow:
- $49_{10} = \mathbf{00}110001_2$
- $29_{10} = \mathbf{000}11101_2$

Q17) Convert decimal +49 and +29 to binary, using the signed 2's complement representation and enough digits to accommodate the numbers. Then perform the binary equivalent of $(+29) + (-49)$, $(-29) + (+49)$, and $(-29) + (-49)$. Convert the answers back to decimal and verify that they are correct.

- $49_{10} = 110001_2$
- $29_{10} = \mathbf{0}11101_2$
- Add two bits, one for sign and one for overflow:
- $49_{10} = \mathbf{00}110001_2$
- $29_{10} = \mathbf{000}11101_2$
- $-49_{10} = \mathbf{11}001111_2$
- $-29_{10} = \mathbf{111}00011_2$

$$A] (+29) + (-49) = 0001,1101 + 1100,1111$$

$$A] (+29) + (-49) = 0001,1101 + 1100,1111 = 0,1110,1100$$

$$A] (+29) + (-49) = 0001,1101 + 1100,1111 = 0,1110,1100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1110,1100**.

$$A] (+29) + (-49) = 0001,1101 + 1100,1111 = 0,1110,1100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1110,1100**.
- This is a negative value (Sign bit = 1).

$$A] (+29) + (-49) = 0001,1101 + 1100,1111 = 0,1110,1100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1110,1100**.
- This is a negative value (Sign bit = 1).
- Its magnitude is 0001,0100 which is $16 + 4 = 20$

$$A] (+29) + (-49) = 0001,1101 + 1100,1111 = 0,1110,1100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1110,1100**.
- This is a negative value (Sign bit = 1).
- Its magnitude is 0001,0100 which is $16 + 4 = 20$
- The result is $(-20)_{10}$

$$B] (-29) + (49) = 1110,0011 + 0011,0001$$

$$B] (-29) + (49) = 1110,0011 + 0011,0001 = 1,0001,0100$$

$$B] (-29) + (49) = 1110,0011 + 0011,0001 = 1,0001,0100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **0001,0100**.

$$B] (-29) + (49) = 1110,0011 + 0011,0001 = 1,0001,0100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **0001,0100**.
- This is a positive value (Sign bit = 0).

$$B] (-29) + (49) = 1110,0011 + 0011,0001 = 1,0001,0100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **0001,0100**.
- This is a positive value (Sign bit = 0).
- Its magnitude is 0001,0100 which is $16 + 4 = 20$

$$B] (-29) + (49) = 1110,0011 + 0011,0001 = 1,0001,0100$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **0001,0100**.
- This is a positive value (Sign bit = 0).
- Its magnitude is 0001,0100 which is $16 + 4 = 20$
- The result is $(+20)_{10}$

$$C] (-29) + (-49) = 1110,0011 + 1100,1111$$

$$C] (-29) + (-49) = 1110,0011 + 1100,1111 = 1,1011,0010$$

$$C] (-29) + (-49) = 1110,0011 + 1100,1111 = 1,1011,0010$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1011,0010**.

$$C] (-29) + (-49) = 1110,0011 + 1100,1111 = 1,1011,0010$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1011,0010**.
- This is a negative value (Sign bit = 1).

$$C] (-29) + (-49) = 1110,0011 + 1100,1111 = 1,1011,0010$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1011,0010**.
- This is a negative value (Sign bit = 1).
- Its magnitude is 0100,1110 which is $64 + 8 + 4 + 2 = 78$

$$C] (-29) + (-49) = 1110,0011 + 1100,1111 = 1,1011,0010$$

- ALWAYS IGNORE ANY BITS OTHER THAN THE bits that we need (8 bits in this case).
- Result is **1011,0010**.
- This is a negative value (Sign bit = 1).
- Its magnitude is 0100,1110 which is $64 + 8 + 4 + 2 = 78$
- The result is $(-78)_{10}$

Outline

- 1 Two's complement
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
- 4 Binary and Gray code

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Q18) Represent the decimal number 6,248 in:

- a) BCD

Q18) Represent the decimal number 6,248 in:


- a) BCD: Represent each decimal **digit** as a 4-bit binary number.

$$6,248_{10} = 0110, 0010, 0100, 1000_{\text{BCD}}$$

- b) excess3 code

Q18) Represent the decimal number 6,248 in:

- a) BCD: Represent each decimal **digit** as a 4-bit binary number.
 $6,248_{10} = 0110, 0010, 0100, 1000_{\text{BCD}}$
- b) excess3 code: Similar to BCD but add three to each digit before converting to binary
 $6,248_{10} = 1001, 0101, 0111, 1011_{\text{Excess-3 code}}$
- c) 2421 code¹

¹https://en.wikipedia.org/wiki/Aiken_code 

Q18) Represent the decimal number 6,248 in:

- a) BCD: Represent each decimal **digit** as a 4-bit binary number.

$$6,248_{10} = 0110, 0010, 0100, 1000_{\text{BCD}}$$

- b) excess3 code: Similar to BCD but add three to each digit before converting to binary

$$6,248_{10} = 1001, 0101, 0111, 1011_{\text{Excess-3 code}}$$

- c) 2421 code¹: Instead of considering the weights of the 4 bits to be 8, 4, 2, 1 make them 2, 4, 2, 1

$$6,248_{10} = 1100, 0010, 0100, 1110_{2421 \text{ code}}$$

- d) 6311 code

¹https://en.wikipedia.org/wiki/Aiken_code

Q18) Represent the decimal number 6,248 in:

- a) BCD: Represent each decimal **digit** as a 4-bit binary number.

$$6,248_{10} = 0110, 0010, 0100, 1000_{\text{BCD}}$$

- b) excess3 code: Similar to BCD but add three to each digit before converting to binary

$$6,248_{10} = 1001, 0101, 0111, 1011_{\text{Excess-3 code}}$$

- c) 2421 code¹: Instead of considering the weights of the 4 bits to be 8, 4, 2, 1 make them 2, 4, 2, 1

$$6,248_{10} = 1100, 0010, 0100, 1110_{2421 \text{ code}}$$

- d) 6311 code: Instead of considering the weights of the 4 bits to be 8, 4, 2, 1 make them 6, 3, 1, 1

$$6,248_{10} = 1000, 0011, 0101, 1011_{6311 \text{ code}}$$

¹https://en.wikipedia.org/wiki/Aiken_code

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Q1) Convert the following numbers into BCD and hence carry out the BCD addition:

■ b) $(398)_{10} + (198)_{10}$

Q1) Convert the following numbers into BCD and hence carry out the BCD addition:

- b) $(398)_{10} + (198)_{10}$
- $(398)_{10} = (0011, 1001, 1000)_{\text{BCD}}$
- $(198)_{10} = (0001, 1001, 1000)_{\text{BCD}}$

0011 1001 1000

+

0001 1001 1000

0011 1001 1000

+

0001 1001 1000

10000

(result is more than 9, Add 6 to the value)

0011 1001 1000

+

0001 1001 1000

10000

(result is more than 9, Add 6 to the value)

+

0110

0011 1001 1000

+

0001 1001 1000

10000

(result is more than 9, Add 6 to the value)

+

0110

1 0110

$$\begin{array}{r} 1 \\ 0011 1001 1000 \\ + \\ 0001 1001 1000 \\ \hline \end{array}$$

$$\begin{array}{r} 1 \\ 0011 1001 1000 \\ + \\ 0001 1001 1000 \\ \hline 10011 0110 \end{array}$$

(result is more than 9, Add 6 to the value)

$$\begin{array}{r} 1 \\ 0011 1001 1000 \\ + \\ 0001 1001 1000 \\ \hline 10011 0110 \\ \text{(result is more than 9, Add 6 to the value)} \\ 0110 \\ + \\ 0110 \\ \hline \end{array}$$

$$\begin{array}{r}
 1 \\
 0011 1001 1000 \\
 + \\
 0001 1001 1000 \\
 \hline
 10011 0110
 \end{array}$$

(result is more than 9, Add 6 to the value)

$$\begin{array}{r}
 0110 \\
 + \\
 1 1001 0110 \\
 \hline
 1 1001 0110
 \end{array}$$

$$\begin{array}{r} 1 \\ 0011 \quad 1001 \quad 1000 \\ + \\ 0001 \quad 1001 \quad 1000 \\ \hline \end{array}$$

$$\begin{array}{r} 1 \\ 0011 \quad 1001 \quad 1000 \\ + \\ 0001 \quad 1001 \quad 1000 \\ \hline 0101 \quad 1001 \quad 0110 \\ \text{(result is less than 9, Do thing)} \\ \hline \end{array}$$

$$\begin{array}{r} 1 \\ 0011 \quad 1001 \quad 1000 \\ + \\ 0001 \quad 1001 \quad 1000 \\ \hline 0101 \quad 1001 \quad 0110 \\ \text{(result is less than 9, Do thing)} \\ \hline 0101 \quad 1001 \quad 0110 \end{array}$$

Outline

- 1 Two's complement
- 2 BCD and other representations
- 3 Unsigned binary multiplication**
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

How to perform the following **UNSIGNED binary** multiplications:

■ $10011_2 * 1_2 =$

How to perform the following **UNSIGNED binary** multiplications:

■ $10011_2 * 1_2 = 10011_2$

How to perform the following **UNSIGNED binary** multiplications:

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 =$

How to perform the following **UNSIGNED binary** multiplications:

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 10011\mathbf{0}_2$

Explanation:

$$10011_2 = (2^4) + (2^1) + (2^0)$$

$$10_2 = (2^1)$$

How to perform the following **UNSIGNED binary** multiplications:

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 10011\mathbf{0}_2$

Explanation:

$$10011_2 = (2^4) + (2^1) + (2^0)$$

$$10_2 = (2^1)$$

$$10011_2 * 10_2 = ((2^4) + (2^1) + (2^0)) * (2^1) = 2^5 + 2^2 + 2^1$$

- $10011_2 * 100_2 =$

How to perform the following **UNSIGNED binary** multiplications:

■ $10011_2 * 1_2 = 10011_2$

■ $10011_2 * 10_2 = 10011\mathbf{0}_2$

Explanation:

$$10011_2 = (2^4) + (2^1) + (2^0)$$

$$10_2 = (2^1)$$

$$10011_2 * 10_2 = ((2^4) + (2^1) + (2^0)) * (2^1) = 2^5 + 2^2 + 2^1$$

■ $10011_2 * 100_2 = 10011\mathbf{00}_2$

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$
- $10011_2 * 111_2 =$

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$
- $10011_2 * 111_2 =$
 $10011_2 * 1_2 + 10011_2 * 10_2 + 10011_2 * 100_2$

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$
- $10011_2 * 111_2 =$
 $10011_2 * 1_2 + 10011_2 * 10_2 + 10011_2 * 100_2 = 10011 +$
 $100110 + 1001100 = 1000, 0101_2$

- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$
- $10011_2 * 111_2 =$
 $10011_2 * 1_2 + 10011_2 * 10_2 + 10011_2 * 100_2 = 10011 +$
 $100110 + 1001100 = 1000, 0101_2$
- Note: Convert the values to decimal and check that the result is correct.


- $10011_2 * 1_2 = 10011_2$
- $10011_2 * 10_2 = 100110_2$
- $10011_2 * 100_2 = 1001100_2$
- $10011_2 * 111_2 =$
 $10011_2 * 1_2 + 10011_2 * 10_2 + 10011_2 * 100_2 = 10011 +$
 $100110 + 1001100 = 1000, 0101_2$
- Note: Convert the values to decimal and check that the result is correct.

Thus, binary multiplication depends on two operations:
Shift-left (multiplication by 2) and Binary-addition.

Outline


- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

The main blocks are:




Example 1: Allow the user to input two values and check whether they are equal to not.

Example 1: Allow the user to input two values and check whether they are equal to not.



Example 2: Allow the user to input a **Signed 2's complement binary number** and check whether it's positive or negative.

Example 2: Allow the user to input a **Signed 2's complement binary number** and check whether it's positive or negative.



Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Q4) Write an algorithm for unsigned binary numbers multiplication. You can draw a flow chart.

Q4) Write an algorithm for unsigned binary numbers multiplication. You can draw a flow chart.

Note: For binary non-floating numbers:

- A shift left operation adds a zero to the right of the number (e.g: 101 becomes 1010).

Q4) Write an algorithm for unsigned binary numbers multiplication. You can draw a flow chart.

Note: For binary non-floating numbers:


- A shift left operation adds a zero to the right of the number (e.g: 101 becomes 1010).
- A shift right operation drops the least significant bit (e.g: 101 becomes 10).

Q4) Write an algorithm for unsigned binary numbers multiplication. You can draw a flow chart.

Note: For binary non-floating numbers:

- A shift left operation adds a zero to the right of the number (e.g: 101 becomes 1010).
- A shift right operation drops the least significant bit (e.g: 101 becomes 10).

Note: Assume that we want to compute $(A * B)$ where A, B are two binary numbers of the equal length.



Outline

- 1 Two's complement
- 2 BCD and other representations
- 3 Unsigned binary multiplication
- 4 Binary and Gray code**
 - Idea

Outline

- 1 Two's complement
 - Negative values
 - Sheet 1 - Question 17
- 2 BCD and other representations
 - Sheet 1 - Question 18
 - Sheet 2 - Question 1
- 3 Unsigned binary multiplication
 - Idea
 - Quick introduction to flowcharts
 - Sheet 2 - Question 4
- 4 Binary and Gray code
 - Idea

Table 1.6*Gray Code*

Gray Code	Decimal Equivalent
0000	0
0001	1
0011	2
0010	3
0110	4
0111	5
0101	6
0100	7
1100	8
1101	9
1111	10
1110	11
1010	12
1011	13
1001	14
1000	15