


Fix Symbol pin out  
Do not need bypass

Rev: A  
d: 2/17







Note:

1. Review FILT voltage node and adjust current if needed per ap note AND9315-D.PDF
2. Seletec best resitor values after assembly and use one percent resistors to put frequency at 16 MHz.

Symbol Numbers 650 up






While radio transceivers using power amplifiers with topologies such as class-A or class-B may have integrated amplifiers, AX5043 utilizes a class-E amplifier. Because of this, high efficiency power output can be achieved, though external components are required.





AX5043 pins ANTP, ANTN, and ANTP1 are not the PA output; rather, they are the transition between the internal switching transistor and the external resonant components. In the various AX5043 reference designs, LC, CC, CT, LT, and CM actually form the amplifier. For this reason, the output impedance of the ANT pins is not relevant to antenna matching. When the class-E power amplifier has been properly designed, the output impedance will be found at the balun (LB, CB) components, and will be 100 ohms differential, and 50 ohms after the balun. Between the balun and the antenna (or SMA port), filtering and Antenna matching networks can be inserted in series with the RF path.

Another important point is that the output impedance of the internal PA transistor also depends on the output power setting.

Symbol Numbers 150 up

N5BRG  
**AMSAT-NA**  
 Sheet:  
 File: TX\_ax5043.kicad\_sch  
**Title: Radiation Tolerant Internal Housekeeping Unit (IHU)**  
 Size: USLedger | Date: 2023-02-16 | Rev: A  
 KiCad E.D.A. kicad 7.0.0-da2b9df05c-171-ubuntu22.04.1 | Id: 6/17






NOTE: LOAD SWITCHES ARE MAX +5.5V (ABS MAX +6)

Must review this to be sure we have enough power for the board.

We are assuming battery voltage in and regulators for all voltages are included.

Start with 85








Inductors Ref Murata LQW18AN\_00 series

Symbol Numbers 400 up

RECEIVER 3		
N5BRG AMSAT-NA		
Sheet: File: RX_3_ax5043.kicad_sch		
Title: Radiation Tolerant Internal Housekeeping Unit (IHU)		
Size: USLedger	Date: 2023-02-16	Rev: A
KiCad E.D.A. kicad	7.0.0-da2b9df05c-171-ubuntu22.04.1	Id: 9/17







Consider Using this OSC out.

Z. Metzinger

## AMSAT-NA

Sheet:

File: tms570\_cpu.kicad\_sch




**Title: Radiation Tolerant Internal Housekeeping Unit (IHU)**

Size: USLedger | Date: 2019-12-23


KiCad E.D.A. kicad 7.0.0-da2b9df05c~171~ubuntu22.04.1

Rev: 1.1

Id: 12/17







Idd 2.5 uA/600 uA



Start with 25








Memory Chips  
400 uA standby  
11 to 18.5 mA active

Start with 75

Sheet: File: memorg.kicad_sch		
<b>Title:</b>		
Size: A4	Date:	Rev:
KiCad E.D.A. kicad 7.0.0-da2b9df05c-171-ubuntu22.04.1		Id: 17/17





No Battey Charging Implimented  
No remote USB wake implimented

Start with 50

Sheet:		
File: usb_development_io.kicad_sch		
Title:		
Size: A4	Date:	Rev:
KiCad E.D.A. kicad 7.0.0-da2b9df05c~171-ubuntu22.04.1		Id: 18/17