

Installation of MasTer

(FOR Mac OS DISTROS)

Installation guide by:
N. d'Oreye, D. Smittarello, M. Jaspard, G. Celli – ECGS
B. Smets – RMCA

Version 5.0: Aug 31 2023

Preliminary information.....	2
0) Prepare the work.....	4
1) Installing some external components.....	6
2) Installing required tools.....	8
3) Installing MasTer.....	13
4) Directory structure for data, auxiliary data and results.....	16
5) Check installation.....	17
6) Operating with cron jobs.....	20
7) Updates in this manual.....	21

Preliminary information

MasTer tool is a set of mostly shell scripts aiming at processing automatically a large number of interferometric pairs and feeding and running the **MSBAS** processor [Samsonov and d'Oreye, 2012, 2017; Samsonov et al., 2017, 2020] in order to obtain the desired deformation maps and time series in vertical and horizontal components. Geocoded amplitude, coherence, interferometric phase and deformation maps are computed using the **MasTer Engine**, a command line InSAR processor derived from the Centre Spatial de Liege (CSL) InSAR Suite (CIS) [Derauw, 1999; Derauw et al, 2019].

This guide explains the installation procedure for **MasTer (MasTer tool, MasTer Engine, MSBAS)**, on a Mac computer. It does not replace the [manual](#) file provided with the software distribution ([MasTer_Manual_x.x.docx](#)), but rather provide much more details to allow any user with less-advanced knowledge of the Mac environment to properly install the software suite.

The installation procedure has been last tested with the **MasTerEngine_v20231009** package, msbasv3 (20190121), msbasv4 (20201009) and shell scripts dated from Aug 2023.

Sources and codes are available from Github at repositories by ndoreye.

If you are not granted the access to the repositories, please send an email to ndo@ecgs.lu.

Download:

Either from the **distribution repository** (all in one package):

- https://github.com/ndoreye/MasTerToolbox_Distribution

Or from the **development repositories**:

- the documentation and manuals from [ndoreye/DOCS](#)
- the scripts from [ndoreye/SCRIPTS_MT](#)
- the MSBAS sources tuned for MasTer Toolbox from [ndoreye/MSBAS](#) (also available directly from S. Samsonov; see manual)
- the MasTerEngine sources from [ndoreye/_Sources_ME](#) (also available directly from D. Derauw; see manual)

Note: Gitkraken is a convenient interface for Github but is not mandatory.

This installation procedure as been tested on:

- **MacOS Monterey version 12.6**

though former installations were operational already on Mojave (V10.14.6) and former MacOS versions.

It is assumed that the user has the administrator rights on the computer and can provide the root privilege when the “sudo” command is executed in the terminal.

In this installation guide, each command line that has to be written and executed in a terminal is written in *italic blue*. Files names are in [blue](#). Paths are given in [green](#).

Note:

A script exists to assist you making the installation (at least for recent Mac OS X such as Monterey). See

[.../SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT/MasTer_install.sh](#)

(in distribution repository), or

[.../SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT/MasTer_install.sh](#)

(in development repository).

Read carefully all the text and questions displayed by the script.

For older Mac OS versions, you may need to adapt the script or proceed manually by adapting the procedure below.

Note that the ***MasTer_install.sh*** installation script may be run several times (either to correct a problem during the installation or to perform an update of any element at any time). However, if some elements were installed manually (eg Gitkraken, Fiji or QGIS...), the script may not properly detect them as they may have been installed in an expected. This must not be a problem though.

Kind reminder: The software is provided for free. To help us carrying on with the development of the tool, we kindly ask you to cite the **MasTer Toolbox** in publications that contains results produced by the toolbox thanks to at least the most recent references from below:

For MasTer Engine

- Derauw, D., (1999). Phasimétrie par Radar à Synthèse d'Ouverture; théorie et applications. PhD Dissertation, University of Liège, 141 pages.
- Libert, L., Derauw, D., d'Oreye, N., Barbier, C., Orban, A., (2017). Split-band interferometry-assisted phase unwrapping for the phase ambiguities correction. *Remote Sensing*, 9(9), 879.

For MSBAS

- Samsonov, S., d'Oreye, N., (2012). Multidimensional time-series analysis of ground deformation from multiple InSAR data sets applied to Virunga Volcanic Province. *Geophysical Journal International* 191(3), 1095–1108. doi: 10.1111/j.1365-246X.2012.05669.x.
- Samsonov, S., d'Oreye, N., (2017). Multidimensional Small Baseline Subset (MSBAS) for two-dimensional deformation analysis: Case study Mexico City. *Canadian Journal of Remote Sensing* 82(6), 1–12. doi: 10.1080/07038992.2017.1344926
- Samsonov S., W. Feng, A. Peltier, H. Geirsson, N. d'Oreye, KK. F.Tiampo (2017). Multidimensional Small Baseline Subset (MSBAS) for volcano monitoring in two dimensions: opportunities and challenges. Case study Piton de la Fournaise volcano. *Journal of Volcanology and Geothermal Research*, Vol 344, 121-138, <https://doi.org/10.1016/j.jvolgeores.2017.04.017>
- Samsonov, S., A. Dille, O. Dewitte, F. Kervyn, and N. d'Oreye (2020). Satellite interferometry for mapping surface deformation time series in one, two and three dimensions: A new method illustrated on a slow-moving landslide. *Engineering Geology*, (266), 105471, doi:10.1016/j.enggeo.2019.105471.items

For MasTer toolbox

- Derauw, D., N. d'Oreye, M. Jaspard, A. Caselli, and S. Samsonov (2020), Ongoing automated ground deformation monitoring of Domuyo - Laguna del Maule area (Argentina) using Sentinel-1 MSBAS time series: Methodology description and first observations for the period 2015-2020., *Journal of South American Earth Sciences*, 104, 102850, doi:10.1016/j.jsames.2020.102850.
- d'Oreye N., Derauw, D., S. Samsonov, M. Jaspard, and D. Smittarello (2021), MasTer: a full automatic multi-satellite InSAR mass processing tool for rapid incremental 2D ground deformation time series. *Proc. IEEE IGARSS21*, Brussels, July 2021.
- d'Oreye N., Derauw, D., S. Samsonov, M. Jaspard, D. Smittarello, G. Celli (2022), MasTer: InSAR automated Mass processing Toolbox for Multidimensional time series. *Instruction manual V4.0*, Oct. 2022. 191 pp.
- Smittarello, D., d'Oreye, N., Jaspard, M., Derauw, D., & Samsonov, S. (2022). Pair selection optimization for InSAR time series processing. *Journal of Geophysical Research: Solid Earth*, 127, e2021JB022825.

For DORIS

- Kampes, B.M., Hanssen, R.F., Perski, Z., (2003). Radar interferometry with public domain tools. In: *Third International Workshop on ERS SAR Interferometry, FRINGE03*, Frascati, Italy, 1-5 Dec. 2003, 6 pages.

0) Prepare the work

The tools will need the following directories:

- /opt/local/bin
- \$HOME/SAR/EXEC
- \$HOME/SAR/MasTerToolbox/DOC
- \$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older
- \$HOME/SAR/MasTerToolbox/MSBAS
- \$HOME/SAR/MasTerToolbox/SCRIPTS_MT

Where \$HOME/ is obviously your home directory.

It is also advised to source your .barshrc in your **.bash_profile** as all the config will be set in **.bashrc**.

If you do not have these files, create them and ensure you can write and execute them.

If you have old MasTer installation parameters in your **.bashrc**, it is advised to remove them and write new ones based on the instructions below.

1) Installing some external components

The following tools and apps are not mandatory but experience shows that it may greatly help the user.

Macports:

- Download latest version from www.macports.org > Available Downloads:
 - o E.g., for [Monterey](#), take [MacPorts-2.7.2-12-Monterey.pkg](#)
 - o Open and install
 - o And/or:
 - `sudo port selfupdate`
 - `sudo port upgrade outdated`
 - o If your OS is 10.15 or more recent, it is required to change default shell Zsh with bash for scripts compatibility issues:

`chsh -s /bin/bash`

GitKraken :

Although not mandatory, Gitkraken is a useful tool to sync with the last versions of MasTer Toolbox. It requires credentials to access MasTer private repositories on Github (contact ndo@ecgs.lu). GitKraken used to access private repositories requires a license though.

- Download [GitKraken](https://www.gitkraken.com) (from <https://www.gitkraken.com>) and connect e.g. via [Github](#)
- Create profile in GitKraken (may need pay version for accessing private repositories)
- Launch GitKraken
- Clone Repo > Github.com :
 - o Where to Clone: `$HOME/SAR/MasTerToolbox`
 - o Repo to clone: DOC, MSBAS, SCRIPTS_MT
- Clone Repo > Github.com :
 - o Where to Clone: `$HOME/SAR/MasTerToolbox/MasTerEngine`
 - o Repo to clone: `_Sources_ME`
- New tab > Open a Repo > select in Finder `SAR/MasTerToolbox/RepoYouWant`

To display raster figure: XnView, GIMP or Graphic Converter

- my favourite is [Graphic Converter](#) though it is not free...
- To install GIMP:
 - o `sudo port install "gimp2"`

A text editor: BBEdit (not free though)

- Get it from <https://www.barebones.com/products/bbedit/download.html> or any other convenient editor that you like

Cyberduck

- Get it from <https://cyberduck.io> or any other convenient ftp software that you like

gnu fortan (not mandatory):

- Get it from <https://github.com/fxcoudert/gfortran-for-macOS/releases>
- install

GMT and GDAL:

GMT, GDAL and some associated utilities are required for plots, images and GIS manipulations.

- Using MacPorts, at Terminal, type:
 - o `sudo port selfupdate` (to be sure)
 - o `sudo port install gdal +hdf5 +netcdf +openjpeg`
 - o `sudo port install gmt6`
 - o `sudo port install graphicsmagick ffmpeg`
 - o search for installation location: `which gmt6`
 - o link that `gmt6` to `/opt/local/bin/gmt` for portability

Note: if GDAL is crashing (seems to happen with most recent version of OSX ?), try installing `homebrew` version. This however may require to recompile msbas and/or MasTer Engine sources after an OS update as homebrew does not manage libraries the same way as macports.

To display geocoded products: QGIS

- Download latest version from <https://qgis.org/en/site/forusers/download.html>
- note some interesting plugins are:
 - o `point sampling tool`
 - o `PointConnector`
 - o `Profile tool`
 - o `Qdraw`
 - o `QuickMapServices`
 - o `RasterDataPlotting`
 - o `Serval`
 - o `Temporal/Spectral Profile Tool`
 - o `Value Tool`

To quick look scripts with colours when hitting the space bar: QLColorCode

- o `sudo port install QLColorCode`
- o `reboot`

2) Installing required tools

MasTer needs some pre-existing software and libraries to work properly. This is what we call the “dependencies”. So, we first need to install them. These installations are explained here, sorted by type of installation procedure.

bashrc:

- Open Terminal
- Type: `touch .bashrc`
- Type: `nano .bashrc`
- Copy/paste infos from [example_bashrc.txt](#) eg using nano editor
- Adapt to needs (see below)
- Exit nano by Crtl-X > Y
- Create a `.bash_profile` that will use your `.bashrc`. Type: `touch .bash_profile`
- Type: `nano .bash_profile`
- Copy/paste the following lines :


```
if [ -r ~/.bashrc ] ; then
    source ~/.bashrc
fi
```
- Exit nano by Crtl-X > Y
- Type:


```
chmod 700 .bashrc
chmod 700 .bash_profile
```
- Reboot

Note: for recent Mac, default shell is not bash. See here how to get it back to default bash: <https://www.howtogeek.com/444596/how-to-change-the-default-shell-to-bash-in-macos-catalina/>

Xcode:

- Install Xcode (required for compilations below). In Terminal type: `xcode-select --install`

Libraries & modules:

- Install libraries and modules using macports:
 - o `Sudo port install clang-14`
 - o `sudo port install fftw-3-long`
 - o `sudo port install fftw-3-single`
 - o `sudo port install hdf5`

Note: At compilation, a note is displayed reading:
 Mac users may need to set the environment variable "HDF5_USE_FILE_LOCKING" to the five-character string "FALSE" when accessing network mounted files. This is an application run-time setting, not a configure or build setting. Otherwise errors such as "unable to open file" or "HDF5 error" may be encountered.
Not sure what to do out of it yet though...

 - o `sudo port install tiff`
 - o `sudo port install libgeotiff`
 - o `sudo port install libxml2`
 - o `sudo port install lapack`
 - o `sudo port install libomp-devel`
 - o `sudo port install ImageMagick`
 - o `sudo port install gdal +libkml`
 - o `sudo port install parallel`

GNU functions and utilities:

Mac version of some tools such as *sed* or *awk* etc do not have exactly the same syntax as their gnu version. For the sake of portability (and because some options are not available for Mac versions), we use here gnu tools:

- At Terminal:

- o *sudo port install gsed*
- o *sudo port install gawk*

Note: At compilation, a note is displayed reading:

readline support has been removed from gawk. If you need to run gawk interactively, install rlwrap:

sudo port install rlwrap

and run gawk using rlwrap:

rlwrap gawk ...

- o *sudo port install coreutils* (i.e. for gdate, gstat)
- o *sudo port install findutils* (i.e. for find)
- o *sudo port install grep* (i.e. for ggrep)
- o *sudo port install wget* (needed i.e. to download the S1 orbits)
- o *sudo port install curl*

- Check that all these gnu functions are stored in the */opt/local/bin* directory. If not, move them there. That directory MUST be defined as *{PATHGNU}* state variable in your *.bashrc*. At Terminal, type

- o *which gsed*
- o *which gawk*
- o *which gdate*
- o *which gstat*
- o *which gfind*
- o *which ggrep*

If answer to all these lines is not the same as *echo {PATHGNU}*, edit your *.bashrc* and change *{PATHGNU}* state variable. It must be something like

export PATHGNU=/opt/local/bin

Don't forget that a reboot (or source *.bashrc*) is required for changes in *.bashrc* to be taken into account.

Note: ensure that */opt/local/bin* is in your path before the */usr/bin* to ensure that it would in priority take into account your GNU commands in case of doubt.

- Just in case one of these functions would be called without its g-name in a script, it is recommended to have them in *{PATHGNU}* with both names, that is with and without heading g (that is **sed** and **gsed**, **awk** and **gawk**, **grep** and **ggrep**, **date** and **gdate**, **stat** and **gstat**. This can be simply done with a link. In Terminal, type:

- o *cd {PATHGNU}*
- o *ln -s gsed sed*
- o *ln -s gawk awk*
- o *ln -s gdate date*
- o *ln -s gstat stat*
- o *ln -s gfind find*

And to be sure...(I know it is overkill, but one never know...):

- o *ln -s ggrep grep*
- o *ln -s gseq seq*
- o *ln -s guniq uniq*
- o *ln -s greadlink p readlink*
- o *ln -s gdu du*
- o *ln -s gxargs xargs*

Check also that *wget* is *{PATHGNU}*

For some plotting applications: Java

Install it with :

- `sudo port install jdk19`

or manually:

- see <http://www.java.com>
- follow instructions to install Java

Notes:

- if some scripts crash with the following message, re-install java and then re-install Fiji:
The operation couldn't be completed. Unable to locate a Java Runtime that supports (null).
- One may need to define `JAVA_HOME` state variable in the `.bashrc` for some application using it. Check where it is installed by typing:
 - `java -XshowSettings:properties -version 2>&1 > /dev/null | grep 'java.home' | cut -d = -f2- | cut -d " " -f2-`
 and update the `.bashrc` by adding a line with the answer of the line above:
 - `export JAVA_HOME=PATH_FROM_LINE_ABOVE`

Fiji/ImageJ:

- Download latest version from <https://imagej.net/software/fiji/downloads>
- Install
- In Finder, locate `Fiji.app` in your `/Applications` directory. Right click on it and click on "Show Package Contents"
- Navigate in Contents>MacOS and copy the path to executable (must be `ImageJ-macosx`)
- Update `$PATHFIJI` in your `.bashrc`. It must be something like
`export PATHFIJI=/Applications/Fiji.app/Contents/MacOS/`

snaphu:

- Download latest version (e.g. `snaphu-v2.0.5.tar`) from <https://web.stanford.edu/group/radar/softwareandlinks/sw/snaphu/> and store it in in `$HOME/SAR/EXEC`.
- unzip it e.g. using `tar -zxvf`
- edit the Makefile in the `/src` directory to specify your compiler and the optimization flags. Ensure that makefile has no static option in following line
`CFLAGS = -O3 # -D NO_CS2`
- compile: at Terminal in `/src` dir, type `make`
(it seems that you can ignore warnings; most recent compilers are more sensitive)
- Move compiled `snaphu` from `/bin` into `$HOME/SAR/EXEC`
- Download also the `snaphu_man1.txt` if you need more info about snaphu and its configurations.
- Store the installed source e.g. in `$HOME/SAR/EXEC/Sources_Installed`.

cpxfiddle:

Not mandatory, but pretty convenient for creating raster files for quick looking at results.

- Download source from https://github.com/TUDELFTGeodesy/Doris/tree/master/sar_tools
- Cut/paste source in new document with your favorite editor
- Save the file in `$HOME/SAR/EXEC/cpxfiddle.cc`
- In Terminal:
 - `cd $HOME/SAR/EXEC`
 - `make -n cpxfiddle`

- `g++ -O -c -ocpxfiddle.o cpxfiddle.cc` (you can ignore warning)
- `g++ -O cpxfiddle.o -o cpxfiddle`
- Clean sources in `$HOME/SAR/EXEC/cpxfiddle.o`
- Store the installed source `cpxfiddle.cc` e.g. in `$HOME/SAR/EXEC/Sources_Installed`
- Update `$PATHTOCPXFIDDLE` in your `.bashrc`. It must be something like
`export PATHTOCPXFIDDLE=/${HOME}/SAR/EXEC/`

gnuplot:

- At Terminal:
 - `sudo port install gnuplot`
 - `which gnuplot`
- Ensure that the path provided by the former command displays the same path as `$PATHGNU` in your `.bashrc`. It must be something like
`export PATHGNU=/opt/local/bin`

osascript:

- should be by default on your mac. Test at Terminal with : `osascript -h`

python:

- At Terminal:
 - `sudo port install python310`
 - `sudo port select --set python python310` (To make this the default Python or Python 3)
 - `sudo port select --set python3 python310` (To make this the default Python or Python 3)
 - `sudo port install py310-opencv4`
 - `sudo port install py-numpy`
 - `sudo port install py310-scipy`
 - `sudo port install py310-matplotlib`
 - `sudo port install py310-gdal`
- Check which version is used:
 - at Terminal, type: `python -c 'import sys ; print(sys.path)'`
 - It must answer something like:
`"['', '/opt/local/Library/Frameworks/Python.framework/Versions/3.10/lib/python310.zip', '/opt/local/Library/Frameworks/Python.framework/Versions/3.10/lib/python3.10', '/opt/local/Library/Frameworks/Python.framework/Versions/3.10/lib/python3.10/lib-dynload', '/opt/local/Library/Frameworks/Python.framework/Versions/3.10/lib/python3.10/site-packages']"`
 - If a package such as numpy does not load, search where it is stored and check that it is in the same version as your python. For instance, numpy here must be in something like:
`/opt/local/Library/Frameworks/Python.framework/Versions/3.10/lib/python3.10/site-packages/numpy`
 If versions differ, change the default python version with same command as above or try to install an appropriate version of the package.
- Copy python to appropriate directory:
For security reasons recent Mac OS now install python in `/opt/local/bin` instead of `/usr/bin`, and this is a good practice. If for any reason your system did install python in `/usr/bin`, please link it to `/opt/local/bin/python` as that is from where it will be called by all the scripts:
 - `which python3` (To know where it is installed, e.g. `/usr/bin`)
 - `sudo ln -s /usr/bin/python3 /opt/local/bin/python3`
 (To make this the default Python, providing that the path is indeed `/usr/bin`)
 - `sudo ln -s /usr/bin/python3 /opt/local/bin/python`
 (Just in case... i.e. to be sure that it will be called either as python or python3)
- Install `utm` package, which is used in `_LatLong2UTM.py` script:
 - You must get python 3.10 and `pip`. To install `pip`, type at the Terminal:
`curl https://bootstrap.pypa.io/get-pip.py -o get-pip.py`
`python get-pip.py`
 - Check `pip`. Since python is probably not in your PATH, type at the Terminal:

`$HOME/Library/Python/3.10/bin/pip --version`

It must answer something like

pip 22.1.2 from /Users/doris/Library/Python/3.10/lib/python/site-packages/pip (python 3.10)

- Now install it. Type at the Terminal :

`$HOME/Library/Python/3.10/bin/pip install utm`

- Install `pyqt6` package, which is used eg. in **MasterOrganizer.sh** script:
 - `/opt/local/bin/python -m pip install pyqt6`
 - `/opt/local/bin/python -m pip install appscript`
- Add the path to python (`/opt/local/bin/`) in the `$PATH` in your `bashrc`. To avoid any risk of using another version of python if badly called, **add it in the beginning** of the `$PATH`.

3) Installing MasTer

MasTer consists of several packages that need to be obtained or downloaded from different sources:

- **MasTerEngine** (core parts: InSAR and MSBASTools):
 - See **Preliminary information/Sources and codes** above for Github instructions, or
 - To request the code, contact: dderauw@ecgs.lu
 - **MasTer Tool (SCRIPTS_MT: mass processing scripts)**:
 - See **Preliminary information/Sources and codes** above for Github instructions, or
 - To request the code, contact ndo@ecgs.lu
 - **MSBAS** (2D or 3D inversion time series):
 - See **Preliminary information/Sources and codes** above for Github instructions, or
 - Download from: <https://doi.org/10.4095/313749> or
 - Request code tuned for MasTer with a make file adapted to Mac and Linux, contact ndo@ecgs.lu
- In case of problem, contact sergey.samsonov@canada.ca

3.1 Compile **MasTerEngine**:

If executable files were provided (zip file),

- simply unzip it and copy the binaries in `$HOME/SAR/MasTerToolbox/MasTerEngine`
- then store the zipped file in `$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine` where *mostrecent* is the date of the last version, which is in the name of the zip file. This date must be as YYYYMMDD and will be used by some scripts to track (and log) the version used during processing.
- Update `$PATH` in your `.bashrc`. It must be something like `PATH=$PATH:$HOME/SAR/MasTerToolbox/MasTerEngine`

If you were provided with the source code (zip file), simply unzip it in

`$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine`

where *mostrecent* is the date of the last version, which is in the name of the zip file. This date must be as YYYYMMDD and will be used by some scripts to track (and log) the version used during processing. Then,

- In Terminal, in `$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine/MasterEngineYYYYMMDD/InSAR/sources` type: `make`
- Move all files from `$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine/MasterEngineYYYYMMDD/InSAR/bin` in `$HOME/SAR/MasTerToolbox/MasTerEngine`
- In Terminal, in `$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine/MasterEngineYYYYMMDD/MSBASTools/sources` type: `make`
- Move all files from `$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine/MasterEngineYYYYMMDD/MSBASTools/bin` in `$HOME/SAR/MasTerToolbox/MasTerEngine`

- Clean (delete) the decompressed directories; keep only the zip file in:
`$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older/Vmostrecent_MasterEngine`
- Update `$PATH` in your `.bashrc`. It must be something like
`PATH=$PATH:$HOME/SAR/MasTerToolbox/MasTerEngine`

Note that if you are provided with an updated version of MasTer Engine (source code), you can simply update it by copying the zipped file it in `$HOME/SAR/EXEC` and run the script `/$HOME/SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT_Ndo/UpdateMasterEngine.sh` with 2 parameters: the path to the zipped sources file and the date of the version.

3.2 Compile **MSBAS**:

- In Terminal, in `$HOME/SAR/MasTerToolbox/MSBAS/3Dsbas_Archives/msbasv4` decompress `msbas_20201009_wExtract_Unified_20220919_Optimized_v1.1_Gilles.zip`
- In `$HOME/SAR/MasTerToolbox/MSBAS/3Dsbas_Archives/msbasv4/msbas_20201009_wExtract_Unified_20220919_Optimized_v1.1_Gilles`
type: `make all`
(it seems that you can ignore warnings; most recent compilers are more sensitive)
- Move `msbasv4` in: `$HOME/SAR/MasTerToolbox/MSBAS`
- In `$HOME/SAR/MasTerToolbox/MSBAS/3Dsbas_Archives/msbasv4/msbas_20201009_wExtract_Unified_20220919_Optimized_v1.1_Gilles/msbas_extract`
type: `make all`
- Move `msbas_extract` in: `$HOME/SAR/MasTerToolbox/MSBAS`
- Clean (delete) the decompressed directories; keep the sources in `$HOME/SAR/MasTerToolbox/EXEC/Sources_Installed`
- Update `$PATH` in your `.bashrc`. It must be something like
`PATH=$PATH:$HOME/SAR/MasTerToolbox/MSBAS`

3.3 Get the **MasTer Toolbox** scripts at the right place:

- Ensure that the scripts (obtained from Github or from unzipped file) are stored at the right place:
`$HOME/SAR/MasTerToolbox/SCRIPTS_MT`
- Update `$PATH` in your `.bashrc`. It must be something like
`PATH=$PATH:$HOME/SAR/MasTerToolbox/SCRIPTS_MT`
`PATH=$PATH:$HOME/SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT`
`PATH=$PATH:$HOME/SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT_NdO`
`PATH=$PATH:$HOME/SAR/MasTerToolbox/SCRIPTS_MT/_cron_scripts`
`PATH=$PATH:$HOME/SAR/MasTerToolbox/SCRIPTS_MT/MasterOrganizer`
- If scripts were receiver from a zipped file, it can be stored in `$HOME/SAR/MasTerToolbox/EXEC/Sources_Installed`

3.4 Define the environmental variables:

MasTerEngine, MSBAS and MasTer Toolbox requires environmental variables that will be called from the scripts. These are :

`PATH_SCRIPTS=${HOME}/SAR/MasTerToolbox` : path to **SCRIPTS_MT**
(i.e. the directory containing all the scripts)

`PATHGNU=/opt/local/bin` : path to where the **gnu utilities** are stored (better to have it in the **\$PATH** as well)

`PATHFIJI=/Applications/Fiji.app/Contents/MacOS/` : path to where **Fiji** application is

`PATHCONV=/opt/local/bin` : path to where the **convert** command is (from **ImageMagick**)

`PATHTOCPXFIDDLE=${HOME}/SAR/EXEC/` : path to where the **cpxfiddle** command is (from TU Delft)

The path to some disks where data, intermediate results and final results will be stored must also be defined by state variable. At least 5 variables **must be defined**, that is:

PATH_1650, **PATH_3600**, **PATH_3601**, **PATH_3602** and **PATH_DataSAR**.

Names are inherited from architecture at ECGS and will be called throughout the processing. For security reason, it is a good practice to have them pointing to different physical drives, if possible, but this is not mandatory; they can also point toward directories instead of disks, e.g.:

`PATH_1650=/Volumes/hp-1650-Data_Share1` (disk or dir where data or results will be stored)
`PATH_3600=/Volumes /hp-D3600-Data_Share1` (disk or dir where data or results will be stored)
`PATH_3601=/Volumes /hp-D3601-Data_RAID6` (disk or dir where data or results will be stored)
`PATH_3602=/Volumes /hp-D3602-Data_RAID5` (disk or dir where data or results will be stored)
`PATH_DataSAR=/Volumes /DataSAR/` (disk or dir where auxiliary data will be
automatically stored such as orbits, geoid etc...
in a dir named **SAR_AUX_FILES**)

Note also that more disks can be defined and used e.g. for sharing the computation through several disks when intensive computation is required.

When processing ENVISAT or Sentinel 1 data, MasTerEngine will require orbital information. It will usually pick them for you and store them automatically in dedicated directories where it will get them when required. These directories **must be defined** by the following state variable names:

`S1_ORBITS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/ORBITS/S1_ORB`
`ENVISAT_PRECISES_ORBITS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/ORBITS/ENV_ORB/vor_gdr_d`

To create DEM corrected from geoid height, the following state variable must be defined:

`EARTH_GRAVITATIONAL_MODELS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/EGM`

A directory named **EGM96** must exist in that directory and it must contain the geoid file **WW15MGH.DAC**. It can be downloaded from (link checked 05 10 2022):

<https://web.archive.org/web/20130314064801/http://earth-info.nga.mil/GandG/wgs84/gravitymod/egm96/binary/WW15MGH.DAC>

4) Directory structure for data, auxiliary data and results

In addition to the structure of the installation directories, it is important to store your data, auxiliary data (DEM, masks, kml, orbits, geoid, parameters files...), intermediate results and final results in a structure as described below.

MasTer toolbox expects a directory structure similar as what is shown below. Most of the directories where the intermediate and final results are stored will be created by the scripts based on the information provided in the [LaunchMTparameters.txt](#) file.

For those which must be created by the user (in full or based on name provided in the [LaunchMTparameters.txt](#) file), it is required to follow the following architecture and directories naming.

In *italic green* is the information that must be adapted to your satellite(s), orbital mode(s) and region(s). These directories can be located in the disk(s) you want.

Note that, for safety reasons, it is advised to store e.g. raw data and data in csl format (i.e. from MasTerEngine) on different hard drives, or the mass processed results and the msbas results on different hard drives etc....

Names in **red** are mandatory.

Disk 1 (i.e. **PATH_1650**):

PATH_1650/kml	: where to store kml for cropping, or for coherence check
PATH_1650/Param_files_SuperMaster	: where to store your LaunchMTparameters.txt file by <i>/SAT/TRK....</i>
PATH_1650/ SAR_CSL/SAT/TRK/NoCrop	: where data in csl format are stored (incl. crops)
PATH_1650/SAR_SM/AMPLITUDES/ <i>SAT/TRK/Region</i>	: where amplitudes gif will be computed
PATH_1650/ SAR_SM/MSBAS/Region	: where compatible pairs for msbas are computed
PATH_1650/ SAR_SM/RESAMPLED/SAT/TRK	: where data resampled on Super Master are saved

Disk 2 (i.e. **PATH_3600**):

PATH_3600/**SAR_DATA/SAT/...** : where raw data are stored (safer to keep them on a different hard drive than 1650)

Disk 3 (i.e. **PATH_3601**):

PATH_3601/ SAR_MASSPROCESS/SAT/TRK/Crop	: where directories with each pair computation details and results are stored
PATH_3601/ SAR_MASSPROCESS/SAT/TRK/Crop/Geocoded	: where geocoded maps are stored in sub dir Amp, Coh, Defo etc...
PATH_3601/ SAR_MASSPROCESS/SAT/TRK/Crop/GeocodedRasters	: where rasters of geocoded maps (for quick look) are stored

Disk 4 (i.e. **PATH_3602**):

PATH_3602/**MSBAS_RESULTS/Region** : where msbas series are computed

Maybe in one of these disks, or somewhere else where enough storage room is available:

\$PATH_DataSAR/SAR_AUX_FILES/DEM	: where DEMs are stored
\$PATH_DataSAR/SAR_AUX_FILES/EGM96	: where geoid is stored
\$PATH_DataSAR/SAR_AUX_FILES/MASKS/SAT/TRK	: where coherence masks are computed
\$PATH_DataSAR/SAR_AUX_FILES/ORBITS/SAT	: where orbits are stored

Note that **\$PATH_DataSAR** is the state variable defined in .bashrc !!

5) Check installation

5.1 The directory structure

At the end, you should have MasTer installed in a folder named “SAR” as shown in **Fig. 1**.

```

/$HOME/SAR/EXEC
|--Executables...
|--Sources_Installed

/$HOME/SAR/MasTerToolbox
|--DOC
|   |--Biblio
|   |--MasTerEngine
|   |--MasTer_Toolbox
|   |--MSBAS
|
|--MasTerEngine
|   |--_Sources_ME/Older
|       |--[several sources of old versions]
|       |--V20230828_MasTerEngine
|   |--Executables...
|
|--MSBAS
|   |--3Dsbas_Archives
|       |--msbasv4
|   |--Executables...
|
|--SCRIPTS_MT
|   |--_cron_scripts
|   |--MasTerOrganizer
|   |--optimtoolbox
|   |--TemplatesForPlots
|   |--TSCombiFiles
|   |--zz_Uilities_MT
|   |--zz_Uilities_MT_Ndo
|   |--A lot of scripts...

```

Figure 1 – Directory structure required for the proper usage of MasTer Toolbox.

Notes:

- 1) The folders `/$HOME/SAR/MasTerToolbox/MasTerEngine/_Sources_ME/Older` is used to store the archives and the most recent sources of both components of MasTerEngine, that is **InSAR** and **MSBASTools**.

Their latest executable version, when compiled, must be moved to `/$HOME/SAR/MasTerToolbox/MasTerEngine/`.

Hence, when a new version of these packages is available, no need to change the paths of the environmental variables.

- 2) Similarly, the folders `/$HOME/SAR/MasTerToolbox/MSBAS/_3Dsbas_Archives` is used to store the archives and the most recent sources of both components of MSBAS, that is **MSBAS_EXTRACT** and **MSBAS*v*** (where *i* stands for the version). Their latest executable version, when compiled, must be moved to `/$HOME/SAR/MasTerToolbox/MSBAS/`.

Hence, when a new version of these packages is available, no need to change the paths of the environmental variables.

- 3) You can use the script `Check_Installation.sh` to check your installation. See script and manual.

You should also have auxiliary files stored in a folder named “SAR_AUX_FILES” in **DataSAR** as shown in **Fig. 2**.

```
$PATH_DataSAR/SAR_AUX_FILES/
|--DEM
|
|--EGM96
|   |--WW15MGH.DAC
|
|--Masks
|
|--ORBITS
|   |--ENV_ORB
|   |--S1_ORB
```

Figure 2 – Directory structure required for the storage of auxiliary files required by MasTer Toolbox.

Notes:

- 1) The folders `/$PATH_DataSAR/SAR_AUX_FILES/DEM/` is used to store the DEM. It may be associated to a state variable `$EXTERNAL_DEMS_DIR` used automatically by MasTer Engine. However, for the automation with MasTer Toolbox, to avoid possible confusion, the path to the DEM for each run is rather given in the `LaunchMTparameters.txt` file.
- 2) The folders `/$PATH_DataSAR/SAR_AUX_FILES/EGM` **must** contain the geoid file in `EGM96/WW15MGH.DAC`.
- 3) The folders `/$PATH_DataSAR/SAR_AUX_FILES/MASK` is not mandatory, but it is a convenient place to store the mask you would build and used during your processing.
- 3) The folders `/$PATH_DataSAR/SAR_AUX_FILES/ORBITS` **must** contain the orbits for ENVISAT (if required) or Sentinel 1 (if required). These directories must be associated to the state variable `$ENVISAT_PRECISES_ORBITS_DIR` and `$S1_ORBITS_DIR` respectively.

5.2 The environmental variables in .bashrc

At the end, your `./bashrc` must look like:

```
#
# .bashrc
#

[...]
```

```
# User specific environment and startup programs
PATH=/opt/local/bin:$PATH
PATH="$PATH:/usr/local/bin:/usr/bin:/bin:/usr/sbin:/sbin"

BASH_ENV=$HOME/.bashrc
USERNAME=""
LANG=C

# export EDITOR=/usr/bin/edit
export EDITOR=/usr/bin/nano
export PAGER=/usr/bin/less

export USERNAME LANG BASH_ENV PATH

export JAVA_HOME=/Library/Internet\ Plug-Ins/JavaAppletPlugin.plugin/Contents/Home

# MasTer PATHS
#####

PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT/MasTerOrganizer
PATH=$PATH:/Users/YourAccount/SAR/EXEC
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/MSBAS
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/MasTerEngine/_Sources_ME
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/MasTerEngine
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT_Ndo
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT/zz_Uutilities_MT
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT/_cron_scripts
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT
PATH=$PATH:/Users/YourAccount/SAR/MasTerToolbox/SCRIPTS_MT/optimtoolbox

# MasTer VARIABLES
#####

export PATH_HOMEDATA=/Users/YourAccount/
export PATH_3602=/Volumes/hp-D3602-Data_RAID5/
export PATH_3601=/Volumes/hp-D3601-Data_RAID6/
export PATH_3600=/Volumes/hp-D3600-Data_Share1/
export PATH_1650=/Volumes/hp-1650-Data_Share1/
export PATH_DataSAR=/Volumes/DataSAR/

export EARTH_GRAVITATIONAL_MODELS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/EGM
export ENVISAT_PRECISES_ORBITS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/ORBITS/ENV_ORB
export S1_ORBITS_DIR=${PATH_DataSAR}/SAR_AUX_FILES/ORBITS/S1_ORB

export PATH_SCRIPTS=/Users/YourAccount/SAR/MasTerToolbox
export PATHCONV=/opt/local/bin
export PATHFIJI=/Applications/Fiji.app/Contents/MacOS/
export PATHGNU=/opt/local/bin
export PATHTOCPXFIDDLE=/Users/YourAccount/SAR/EXEC/
export PATH=$PATH

#export OMP_NUM_THREADS=10,8,4
#export OMP_NUM_THREADS=4,3,2
```

6) Operating with cron jobs

If you want to operate **MasTer** toolbox from cron jobs, pay attention to the following:

- It is advised to launch scripts by redirecting the messages to /dev/null to avoid filling up the mailbox by ending the command line with

```
> /dev/null 2>&1
```

- If bash is not your default shell (as for the recent Mac OS X) and you want to run scripts from cronjobs, call the scripts in your crontab by calling bash as follow:

```
hh mm * * * /bin/bash YourScript.sh > /dev/null 2>&1
```

Example of .bashrc:

```
# Always end command line launched by cron with > /dev/null 2>&1 to mute output and avoid filling up the mailbox. It will also prevent wrong count of running processes if any...
```

```
## TO GET THE SCRIPTS RUNNING USING CMD LINES AND SCRIPTS STORED IN PATH AVAILABLE IN BASHRC RATHER THAN IN COMMON
```

```
## /user/local/bin FOR INSTANCE, DO NOT FORGET TO SOURCE THE BASHRC AT THE BEGINNING OF THE SCRIPT !!
```

```
# MM HH DoMonth Month DoWeek(0=sunday)
```

```
## *****
## ***** CONGO VVP *****
## *****
```

```
## Step 1: S1 & CSK
```

```
45 04 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_S1_Step1_Read_SMCReg_Pairs.sh > /dev/null 2>&1
```

```
30 12 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_CSK_Step1_Read_SMCReg_Pairs.sh > /dev/null 2>&1
```

```
## Step 2: S1 & CSK
```

```
31 06 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_S1_Step2_Read_MassProc.sh > /dev/null 2>&1
```

```
31 07 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_CSK_Step2_MassProc.sh > /dev/null 2>&1
```

```
## Step 3: S1
```

```
02 21 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_S1_Step3_MSBAS.sh > /dev/null 2>&1
```

```
02 02 * * * /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/VVP_CSK_Step3_MSBAS.sh > /dev/null 2>&1
```

```
## Website Update (once a week)
```

```
00 06 * * 0 /bin/bash /Users/doris/SAR/SCRIPTS_MT/_cron_scripts/rsync_satellite_images_to_virunga_volcanoes.sh > /dev/null 2>&1
```

7) Updates in this manual

V 4.1 (October 26 2022):

- add installation of gnu parallel
- add chapter “7) Updates in this manual”
- correct typo in Version number in header

V 4.3 (April 20 2023):

- Refer to last versions of software and scripts
- Check against installer script

V 5.0 (Aug 30 2023):

- Major changes in dirs and files naming
- Take into account new MasTer Engine V20230828 which is mandatory