WEEK 14

Write a program for congestion control using Leaky bucket algorithm.

```
CODE:
```

```
#include <stdio.h>
#include <stdlib.h> // Include this for the rand() function
int main()
  int buckets, outlets, k = 1, num, remaining;
  printf("Enter Bucket size and outstream size\n");
  scanf("%d %d", &buckets, &outlets);
  remaining = buckets;
  while (k)
  {
     num = rand() % 1000; // Generate a random number between 0 and
999
     if (num < remaining)
     {
       remaining = remaining - num;
       printf("Packet of %d bytes accepted\n", num); // Added missing
variable
     }
     else
       printf("Packet of %d bytes is discarded\n", num);
     if (buckets - remaining > outlets)
       remaining += outlets; // Fixed the calculation
     else
       remaining = buckets;
     printf("Remaining bytes: %d \n", remaining);
```

```
printf("If you want to stop input, press 0, otherwise, press 1\n");
    scanf("%d", &k);
}
while (remaining < buckets) // Fixed the condition
{
    if (buckets - remaining > outlets)
    {
        remaining += outlets; // Fixed the calculation
    }
    else
        remaining = buckets;
    printf("Remaining bytes: %d \n", remaining);
}
return 0; // Added a return statement to indicate successful completion
}
```

OUTPUT:

```
PS D:\VS Code> cd "d:\VS Code\OS\" ; if (\$?) { gcc bucket.c -0 bucket } ; if (\$?) { .\bucket } Enter Bucket size and outstream size
Packet of 41 bytes accepted
Remaining bytes: 2000
If you want to stop input, press 0, otherwise, press 1
Packet of 467 bytes accepted
Remaining bytes: 1633
If you want to stop input, press 0, otherwise, press 1
Packet of 334 bytes accepted
Remaining bytes: 1399
If you want to stop input, press 0, otherwise, press 1
Packet of 500 bytes accepted
Remaining bytes: 999
If you want to stop input, press 0, otherwise, press 1
Packet of 169 bytes accepted
If you want to stop input, press 0, otherwise, press 1
Packet of 724 bytes accepted Remaining bytes: 306
If you want to stop input, press 0, otherwise, press 1
Packet of 478 bytes is discarded
Remaining bytes: 406
If you want to stop input, press 0, otherwise, press 1
Packet of 358 bytes accepted
Remaining bytes: 148
If you want to stop input, press 0, otherwise, press 1
Packet of 962 bytes is discarded
Remaining bytes: 248
If you want to stop input, press 0, otherwise, press 1
```

```
Remaining bytes: 348
Remaining bytes: 448
Remaining bytes: 548
Remaining bytes: 648
Remaining bytes: 748
Remaining bytes: 848
Remaining bytes: 948
Remaining bytes: 1048
Remaining bytes: 1148
Remaining bytes: 1148
Remaining bytes: 1248
Remaining bytes: 1348
Remaining bytes: 1548
Remaining bytes: 1548
Remaining bytes: 1548
Remaining bytes: 1648
Remaining bytes: 1748
Remaining bytes: 1748
Remaining bytes: 1848
Remaining bytes: 1948
```

OBSERVATION:

Agm: vorite a program for congestion control using leaky burker algorithm code : It encudo, < stdrook) # : notude < stdlaboh > int main () ent buckets, pullets, k=1, num, remaining. print (" Enter Bucker sere and The outstream Sq2e"); Scant (" od od", & bucker, 4 outlets); romagning = buckets while CK). hum = rand () % 1000; ? [(num < remaining) remaining = remaining - hum prent (" paints of so byte are accepted" umu). ese prent (" Padent of 16d by to is discorded num);

if Chuckets - remaining > outlets) remaining + = outlets ; else prenty (" Rimaring buckets; old in", remaining telse press 1] scand (" . pd", &K); while Cremaining < buckets) ib chuckets - remaining > outlets) The remaining + = outlets: else print (" Remaining byte : "rid", remaining) geturn 0; Output FATOR Bucket & 5872 and outstream 5872 1000 200

Remainend byter 1000 accepted byou want to stop input press of other Remaining bytu 2733 ab you want to stop input priess o otherwise pres 1 Rackott of 334 bytes are acepted

Remarky bytes 599. 20 30 brove 402002 (1) 0 strel, tagson marros