

ProPath App Summary

Evidence source: React app in /src, seeded data in /public/db.json, and CRA/package scripts in package.json + README.

What It Is

ProPath is a role-based training management web app with separate spaces for administrators, trainers, and trainees. It handles login, cohort and timetable management, announcements, lesson distribution, attendance, and grade tracking in a single React SPA.

Who It's For

Primary persona: a training-center administrator coordinating users, cohorts, announcements, schedules, and reporting, with dedicated trainer and trainee workflows in the same app.

What It Does

- Authenticates users and routes them to admin, trainer, or trainee views based on stored role data.
- Lets admins create, edit, filter, and delete platform users.
- Shows training structure through subjects, groups, and learner counts by group.
- Publishes targeted announcements for all users, trainees, or trainers.
- Uploads and displays timetable images for groups and individual trainers.
- Lets trainers record attendance and enter grades with automatic final-grade calculation.
- Lets trainers upload lesson PDFs, and lets trainees view/download lessons, schedules, absences, and grades.

How It Works

- UI: React 19 single-page app bootstrapped with Create React App; BrowserRouter in App.js controls login and role-based routes.
- Role screens: AdministrationSpace.js, TrainerSpace.js, and stagiereSpace.js + Components.js implement the main workflows.
- Data layer: dataService.js centralizes CRUD, grade helpers, sorting, and audience filtering.
- Flow: UI calls dataService -> tries HTTP API at REACT_APP_API_URL or http://localhost:4000 -> falls back to in-browser local mode if API is unavailable.
- Local mode: seeds from /public/db.json, stores structured data in localStorage, and offloads large payloads/assets to IndexedDB.
- Session state: current user is persisted in localStorage under propath_user.

How To Run

- From repo root: npm install
- Start dev server: npm start
- Open http://localhost:3000 in a browser.
- API setup: Not found in repo. The frontend code falls back to seeded local data if the API is unavailable.