CS2208a Assignment 3

Issued on: Monday, November 11, 2013

Due by: 11:55 pm on Monday, November 18, 2013

For this assignment, only an electronic submission (***attachments***) at owl.uwo.ca is required.

- Attachments must include:
  - ***ONE pdf*** file that has the three flowcharts, program documentations, and any related communications.
  - ***Text*** soft copy of the assembly programs that you wrote for each question (*one program attachment per question*), i.e., ***THREE assembly*** program files in total.
- So, in total, you will submit 1 + 3 = 4 files.
- **Failure to follow the above format may cost you 10% of the total assignment mark.**

Late assignments are strongly discouraged

- 10% will be deducted from a late assignment (up to 24 hours after the due date/time)
- After 24 hours from the due date/time, late assignments will receive a zero grade.

In this assignment, you will use the *micro Vision ARM simulator* by *Keil*, which is an MS Windows based software, to develop the required programs in this assignment. The simulator (version 4) has been installed on all PCs at MC-342 and MC-08 labs.

The simulator may also be installed on your PC. If you have not installed *Keil micro Vision 4 simulator* on your PC yet, you will need to download and install it from https://www.keil.com/download/product/

Note that during this month (October 2013), *Keil* has released a new version of its *MDK-ARM simulator* (*Keil micro Vision 5*). The *MDK-5* installation process has changed from a single monolithic installer to a set of installers.

So, you need to download *MDK-Core Version 5* from https://www.keil.com/download/product/ as well as the *Legacy support for ARM7 & ARM9 devices* from http://www2.keil.com/mdk5/legacy

The author of our text book has provided a *Quick Guide to Using the Keil ARM Simulator*. If you wish, you can access it at http://www.alanclements.org/usingkeilsimulator.html

Programming style is very important in assembly language. It is expected to do the following in your programs:

- Using macros for the constants in your program to make it more readable.
- Applying neat spacing and code organization:
  - Assembly language source code should be arranged in three columns: *label*, *instruction*, and *comments*:
    - the *label* field starts at the beginning of the line,
    - the *instruction* field (opcodes + operands) starts at the next TAB stop, and
    - the *comments* are aligned in a column on the right.
- Using appropriate label names.
- Commenting each assembly line

Great Ways to Lose Marks

- Not grouping your lines into logical ideas
- Not using any whitespace at all
- Not bothering to comment
- Commenting the code by just stating what you're doing, instead of why, e.g.,

```
MOV r0, #5     ;move 5 into r0
```

- Not paying attention to the programming style (see the previous paragraph)
- Handing it in as soon as it assembles without testing and/or trying to break your code

Strings

A string is an array representing a sequence of characters. To store a string of *n* characters in your program, you need to set aside *n+1* bytes of memory. This area of memory will contain the characters in the string, plus one extra special character—the *null* character—to mark the end of the string. The *null* character is a byte whose bits are all zeros (`0x00`). The actual string consists of any group of characters, which none of them can be the *null* character.

QUESTION 1 (25 marks)

Draw a *detailed flowchart* and write an ARM assembly language *program* to concatenate two stings (**`STRING1`** and **`STRING2`**) and store the result in a *null* terminated **`STRING3`**. Assume that the length of **`STRING1`** + the length of **`STRING2`** ≤ 255.

You code should be highly optimized, i.e., use as few number of instructions as possible.

You may want to define the strings as follow:

```
STRING1 DCB "This is a test string1"   ;String1
EoS     DCB 0x00                       ;end of string1
STRING2 DCB "This is a test string2"   ;String
EoS     DCB 0x00                       ;end of string2
STRING3 space 0xFF
```

QUESTION 2 (35 marks)

Draw a *detailed flowchart* and write an ARM assembly language *program* to copy a *null* terminated **`STRING1`** to a *null* terminated **`STRING2`**, after removing any occurrences of the word "***the***" in **`STRING1`**. I.e., if **`STRING1`** is **`"the woman and The man said the"`** then **`STRING2`** would become **`" woman and The man said "`**. However, if **`STRING1`** is **`"and they said another clothe"`** then **`STRING2`** would become **`"and they said another clothe"`** without any change.

You code should be highly optimized, i.e., use as few number of instructions as possible.

You may want to define the strings as follow:

```
STRING1 DCB "and the man said they must go"   ;String1
EoS     DCB 0x00                              ;end of string1
STRING2 space 0xFF
```

QUESTION 3 (40 marks)

Draw a *detailed flowchart* and write an ARM assembly language function (subroutine) that takes a data value stored in register **`r0`** and returns a value in **`r0`** as well. The function returns $y = a \times x^2 + b \times x + c$ where *a*, *b*, and *c* are signed integer parameters built into the function (i.e., they are not passed to it) and are defined in the memory using **`DCD`** instruction. The subroutine also performs clipping, i.e., if the output is greater than a value *d*, it is constrained to *d* (clipped), where *d* is another parameter built into the function defined in the memory using **`DCD`** instruction. The input in **`r0`** is a signed integer ~~positive~~ binary value ~~in the range 0 to 0xFF~~. Apart from **`r0`**, no other registers may be modified by this subroutine, i.e., if you want to use any register as a working register, you have to store its value in a safe place first prior changing it, and to restore this value before returning from the function.

After implementing the function, write an assembly program which stores a value in **`r0`** and calls your function. Once the control is returned back from the function, the program will double the returned value and store this doubled value in **`r1`**.

You code should be highly optimized, i.e., use as few number of instructions as possible.

Example1: if *a = 5, b = 6, c = 7, d = 90*, and **`r0`** = *3*,
then the returned value in **`r0`** should be 70 and the value in **`r1`** will be 140.

Example2: if *a = 5, b = 6, c = 7, d = 50*, and **`r0`** = *3*,
then the returned value in **`r0`** should be 50 and the value in **`r1`** will be 100.

Example3: if *a = -5, b = 6, c = 7, d = 10*, and **`r0`** = *3*,
then the returned value in **`r0`** should be -20 and the value in **`r1`** will be -40.