

This product is no longer manufactured

This product was replaced by **X-SAVE VSR 300 DE**



VR

[Find more details in our online catalogue](#)

Technical parameters

Unit

Frequency	50	Hz
Voltage (nominal)	230	V
Phases	1~	
Recommended fuse	10 A	
Enclosure class	IP24	
Speed regulation	Stepless	

Supply fan

Input power (P1), supply fan	115	W
------------------------------	-----	---

Supply air filter

Filter class, supply air	F7	
--------------------------	----	--

Return fan / Extract fan

Input power (P1), extract fan	115	W
-------------------------------	-----	---

Extract air filter

Filter class, extract air	G3	
---------------------------	----	--

Heater

Heater type	Electric
-------------	----------

Preheater / Reheater

Input power, reheater	1.67	kW
-----------------------	------	----

Exchanger

Heat exchanger	Rotating
----------------	----------

Others

Fan control	CAV, air flow control
Installation type	Horizontal
Supply side	Left;Right

Dimensions and weights

Weight	55.5	kg
--------	------	----

Accessories

- CE/CD-diverting plug 4pin (37367)
- CVVX 160 Combi grille, white (25396)
- JP Junction plug for cable (12428)
- LDC 160-900 Silencer (5193)
- SCD 160 silencer 25mm insulat. (2558)
- TG-K360 Duct sensor 0-60°C (4846)
- ZTR 15-0,4 valve 3-way (9670)
- CVVX 160 Combi grille, black (25394)
- FK 160 Fast clamp (1610)
- LDC 160-600 Silencer (5192)
- RVAZ4 24A Actuator 0-10V (9862)
- TG-A130 Surface sensor 0-30°C (5159)
- VBC 160-2 Water heating batt (5458)

Documents

- 205844 Operation service menu.pdf
- Betriebsanl. VR 400&700 DC-DE.pdf
- Conformity_decl_VM_VX_VR_GB_202665.pdf
- MONT VR 400&700 DC-DE.pdf
- VR_400-700_DC_DCV_Wiring_diagram_205816_en-GB (A004).pdf