

This product is no longer manufactured

This product was replaced by **X-SAVE VTR 500 L**



VR

[Find more details in our online catalogue](#)

Certifications



Ecodesign (ErP) compliant

Complies with stringent EU regulations on energy labelling and Ecodesign for Sustainable Products (ESPR) and Energy-related Products (ErP). Ready to meet future requirements.

Technical parameters

Unit		
Frequency	50	Hz
Voltage (nominal)	230	V
Phases	1~	
Recommended fuse	13 A	
Enclosure class	IP24	
Speed regulation	Stepless	
Supply fan		
Input power (P1), supply fan	230	W
Supply air filter		
Filter class, supply air	F7	

Return fan / Extract fan

Input power (P1), extract fan	230	W
-------------------------------	-----	---

Extract air filter

Filter class, extract air	G3
---------------------------	----

Heater

Heater type	Electric
-------------	----------

Preheater / Reheater

Input power, reheater	1.67	kW
-----------------------	------	----

Exchanger

Heat exchanger	Rotating
----------------	----------

Others

Fan control	CAV, air flow control
-------------	-----------------------

Installation type	Vertical
-------------------	----------

Supply side	Left
-------------	------

Dimensions and weights

Weight	73.4	kg
--------	------	----

ERP

Energy class, Basic unit	B
--------------------------	---

Energy class, Local demand	A
----------------------------	---

ErP ready	ErP 2016;ErP 2018
-----------	-------------------


Ecodesign

Product		
Trade name	Systemair	
Product name	VR 700 DCV /DE	
Basic unit		
ErP compliance	2016/2018	
SEC Average	-30.8	kWh/(m².a)
SEC Cold	-67.3	kWh/(m².a)
SEC Warm	-72	kWh/(m².a)
SEC Class	B	
Unit category	RVU	
Unit type	BVU	
Drive	Integrated VSD	
Heat recovery type	Regenerative	
Temperature ratio	81	%
qv max	554	m³/h
P max	434	W
Sound power (LWA)	51	dB(A)
qv ref	0.108	m³/s
Ps ref	50	Pa
SPI	0.559	W/(m³/h)
CTRL	0.85	
MISC	1.1	
x-value	2	
External Leakage	0.1	%
Internal Leakage	2	%
Type of product	RAHU/AAHE	
AEC average	551	kWh
AEC cold	1088	kWh
AEC warm	506	kWh
AHS Average	4386	kWh/a
AHS Cold	8580	kWh/a
AHS Warm	1983	kWh/a

Units with local demand control		
ErP compliance	2016/2018	
SEC Average	-37.2	kWh/(m ² .a)
SEC Cold	-75	kWh/(m ² .a)
SEC Warm	-13	kWh/(m ² .a)
SEC Class	A	
Unit category	RVU	
Unit type	BVU	
Drive	Integrated VSD	
Heat recovery type	Regenerative	
Temperature ratio	81	%
qv max	554	m ³ /h
P max	434	W
Sound power (LWA)	51	dB(A)
qv ref	0.108	m ³ /s
Ps ref	50	Pa
SPI	0.559	W/(m ³ /h)
CTRL	0.65	
MISC	1.1	
x-value	2	
External Leakage	0.1	%
Internal Leakage	2	%
Type of product	RAHU/AAHE	
AEC average	341	kWh
AEC cold	878	kWh
AEC warm	296	kWh
AHS Average	4507	kWh/a
AHS Cold	8817	kWh/a
AHS Warm	2038	kWh/a

Dimension

- | | |
|---|-------------|
| 1 | Outdoor air |
| 2 | Supply air |
| 3 | Extract air |
| 4 | Exhaust air |



Accessories

- CE/CD-diverting plug 4pin (37367)
- CVVX 200 Combi grille, white (25397)
- JP Junction plug for cable (12428)
- LDC 200-900 Silencer (5195)
- SCD 200 silencer 25mm insulat. (2560)
- TG-K360 Duct sensor 0-60°C (4846)
- VBC 200-2 Water heating batt (5459)
- ZTR 15-1,0 valve 3-way (9672)
- CVVX 200 Combi grille, black (25395)
- FK 200 Fast clamp (1611)
- LDC 200-600 Silencer (5194)
- RVAZ4 24A Actuator 0-10V (9862)
- TG-A130 Surface sensor 0-30°C (5159)
- TUNE-R-200-3-M4 (311970)
- ZTR 15-0,6 valve 3-way (6573)

Documents

- B&V VR 400_700 DCV-DE.pdf
- Conformity_decl_VM_VX_VR_GB_202665.pdf
- MONT VR 400&700 DCV-DE.pdf
- VR_400-700_DC_DCV_Wiring_diagram_205816_en-GB (A004).pdf