



SAVE Air Handling Units

Crisp, fresh, and clean air for every home.

[Find more details in our online catalogue](#)

Unlock even greater efficiency

SAVE AHUs come with different heating and cooling recovery methods. Allowing you to further boost the energy efficiency of your units, wherever they're installed.

Performance you can rely on

Our heat exchanger systems automatically regulates the heat/cool recovery and has automatic defrosting functions. Your SAVE AHUs will keep you comfortable inside, no matter the weather on the outside.

For buildings big and small

Whether you're building a new home or renovating an apartment block, SAVE air handling units are a perfect match for any indoor spaces up to 550m².

Health and safety first

SAVE air handling units are Eurovent certified and ErP compliant, easy to service and maintain. So you can relax – knowing the air you breathe is clean and pure.

Full control, from anywhere

All SAVE units come with SAVE Control – multiple, easy-to-use interfaces that let you communicate with your AHUs wherever you are.

Certifications



Ecodesign (ErP) compliant

Complies with stringent EU regulations on energy labelling and Ecodesign for Sustainable Products (ESPR) and Energy-related Products (ErP). Ready to meet future requirements.

Eurovent Certified Performance

Eurovent Certified Performance is the global benchmark in HVACR certification. The mark guarantees that this product performs as advertised. Check the ongoing validity of our certificates in the Eurovent Certified Products Directory.



Eco Platform: EPD Verified

This product comes with an Environmental Product Declaration (EPD), published by EPD Norway, a global EPD program operator and member of the ECO Platform. Compliant with ISO 14025 and EN 15804, Systemair EPDs support Life Cycle Assessments (LCAs) in all markets where the product is used. Scroll down to download the EPDs.



Green Ventilation

Our proprietary environmental performance benchmark guides you towards the most sustainable solutions within our portfolio. Only products that meet a clear set of verifiable minimum requirements—covering aspects such as energy efficiency, indoor air quality, and safety—are eligible to carry the Green Ventilation™ label.

Technical parameters

Unit		
Frequency	50;60	Hz
Voltage (nominal)	230	V
Phases	1~	
Recommended fuse	13 A	
Enclosure class	IP24	
Speed regulation	Stepless	
Product type	Heat recovery unit	
Temperature	-20 to 40	°C
Supply fan		
Input power (P1), supply fan	170	W
Supply air filter		
Filter class, supply air	ePM1 60%	
Return fan / Extract fan		
Input power (P1), extract fan	170	W
Extract air filter		
Filter class, extract air	ePM10 50%	
Heater		
Heater type	Electric	
Preheater / Reheater		
Input power, reheater	1.67	kW
Voltage (nominal)	230	V
Exchanger		
Heat exchanger rotor drive type	Variable speed	
Heat exchanger	Rotating	

Others

Fan control	Stepless voltage control
Installation type	Horizontal
Supply side	Left;Right

Color casing

Color casing	Galvanized steel
--------------	------------------

Dimensions and weights

Weight	120	kg
--------	-----	----

ERP


Energy class, Basic unit	A
Energy class, Local demand	A+

Performance


⚠ Recommended low airflow is outside valid range

⚠ Recommended high airflow is outside valid range

Supply - Performance curve



Extract - Performance curve



Unit	Supply	Extract
Air density	1.204 kg/m ³	
	Summer	Winter
Supply air temperature	-	-20.0 °C


Ecodesign

Product	
Trade name	Systemair
Product name	SAVE VSR 700

Basic unit		
ErP compliance	2018	
SEC Average	-39.2	kWh/(m ² .a)
SEC Cold	-81.6	kWh/(m ² .a)
SEC Warm	-14.8	kWh/(m ² .a)
SEC Class	A	
Unit category	RVU	
Unit type	BVU	
Drive	Integrated VSD	
Heat recovery type	Regenerative	
Temperature ratio	83	%
qv max	870	m ³ /h
P max	334	W
Sound power (LWA)	44	dB(A)
qv ref	0.169	m ³ /s
Ps ref	50	Pa
SPI	0.232	W/(m ³ /h)
CTRL	0.85	
MISC	1.1	
x-value	2	
External Leakage	3	%
Internal Leakage	Not applicable	
Carry over	4	%
Type of product	RAHU/AARE	
AEC average	210	kWh/a
AEC cold	210	kWh/a
AEC warm	210	kWh/a
AHS Average	4440	kWh/a
AHS Cold	8686	kWh/a
AHS Warm	2008	kWh/a

Units with local demand control		
ErP compliance	2018	
SEC Average	-42.4	kWh/(m ² .a)
SEC Cold	-85.9	kWh/(m ² .a)
SEC Warm	-17.5	kWh/(m ² .a)
SEC Class	A+	
Unit category	RVU	
Unit type	BVU	
Drive	Integrated VSD	
Heat recovery type	Regenerative	
Temperature ratio	83	%
qv max	870	m ³ /h
P max	334	W
Sound power (LWA)	44	dB(A)
qv ref	0.169	m ³ /s
Ps ref	50	Pa
SPI	0.232	W/(m ³ /h)
CTRL	0.65	
MISC	1.1	
x-value	2	
External Leakage	3	%
Internal Leakage	Not applicable	
Carry over	4	%
Type of product	RAHU/AARE	
AEC average	123	kWh/a
AEC cold	123	kWh/a
AEC warm	123	kWh/a
AHS Average	4548	kWh/a
AHS Cold	8898	kWh/a
AHS Warm	2057	kWh/a


Dimension




- 1 Outdoor air
- 2 Supply air
- 3 Extract air
- 4 Exhaust air

Energy class label

std



opt



Accessories

- CAV kit (161100)
- CB 250-6,0 400V/2 Duct heater (5372)
- CB heater connection kit 1 ~ (142852)
- CEC Cable w/plug 12m (24782)
- CVVX 250 Combi grille white (146260)
- CWK 250-3-2,5 Duct cooler,circ (30024)
- Drainage hose VTC 200 kit (209933)
- FK 250 Fast clamp (1612)
- Modbus RTU to TCP gateway (454345)
- OG Ø 250 White (476250)
- PF VSR 700 OPT kit (454340)
- Presence detector/IR24-P (6995)
- PSS20 Transformer 24V (202692)
- RMK-T (153548)
- RS-24V (159484)
- SAVE CONNECT 2.0 (399999)
- SAVE LIGHT White (319118)
- SAVE TOUCH White (138077)
- SCD 250 silencer 25mm insulat. (2561)
- Surface sensor -30-150C (211523)
- Systemair-1 CO2 duct sensor (14906)
- Systemair-E CO2 sensor (14904)
- TUNE-R-250-3-M2 (311951)
- TUNE-R-250-3-M5 (311981)
- VBC 250-2 Water heating batt (5460)
- WHC VSR 700 (462101)
- ZTV 15-1,6 2-way valve (9824)
- CB 250-3,0 230V/1 Duct heater (5385)
- CB 250-9,0 400V/3 Duct heater (5373)
- CB heater connection kit 2/3 ~ (151612)
- CEC Cable w/plug 6m (24783)
- CVVX 250 Combi grille, black (8498)
- Diverting plug 4pin (254978)
- Duct sensor -30-70C (211524)
- LDC 250-900 Silencer (5196)
- OG Ø 250 Black (487200)
- OG Ø 250 Zinc-Magnesium (487700)
- PF VSR 700 STD kit (454339)
- Pressure guard with pitot tube (212987)
- RMK (153549)
- Room sensor 0-50C (211525)
- RVAZ4 24A Actuator 0-10V (9862)
- SAVE LIGHT Black (319119)
- SAVE TOUCH Black (138078)
- SAVE Wall Mounted Kit (140736)
- SPI-250 C Iris damper (6755)
- Surface sensor -30-150C (211523)
- Systemair-E CO2 RH Temperature (211522)
- TUNE-R-250-3-M1 (311941)
- TUNE-R-250-3-M4 (311971)
- VAV/CAV conversion kit (140777)
- VBC 250-3 Water heating batt (9843)
- ZTR 15-1,6 valve 3-way (9673)

Documents

- Commissioning record
- Control panel installation quick guide
- Energy label placement quick guide
- EPD_367449_Systemair_SAVE_VSR_700_json
- EPD_367449_Systemair_SAVE_VSR_700_pdf
- Eurovent Certification Diploma
- Installation manual SAVE CONNECT 2.0
- Installation Operation Maintenance manual
- Modbus variable list
- Schematic layout of components
- Service manual
- Technical fiche

Specification

Filter kits

454339 PF STD kit (F7/ePM1 60% supply and M5/ePM10 50% extract)

454340 PF OPT kit (accessory) (F8/ePM1 70% supply and M5/ePM10 50% extract)

SAVE VSR 700 is perfect for areas up to 500 m².

Take control of your SAVE residential ventilation unit with the user-friendly **SAVE CONNECT** app. Adjust and manage your unit remotely, making home ventilation simpler and more convenient than ever.

Rest assured, the SAVE unit comes with the **SAVE CONNECT** module included, putting remote control firmly in your hands.

MAIN FEATURES

- High energy-efficiency rotary heat exchanger with EC technology fans
- Demand control regulation with the built-in humidity sensor
- Moisture transfer function to minimize condensation in supply air during wintertime
- Remote control via the SAVE CONNECT app
- Built-in electric heater
- Optional SAVE TOUCH and SAVE LIGHT control panels
- Local control and configuration via WEB interface
- Connection board for easy access and connection of accessories
- Modbus communication RS-485 as standard
- Eurovent Certification

EXPAND YOUR CONTROL WITH ADDITIONAL PANELS

You can choose and buy these panels separately, adding more convenience to your setup.

- **SAVE LIGHT** – control panel for basic functions to keep things simple and easy. You can control the airflow, get alerts for general alarms and filter changes.
- **SAVE TOUCH** – Take it up a notch with the SAVE TOUCH panel. It has a touch screen that lets you control everything and mirrors functionality of the SAVE CONNECT app. You can see info like airflow, temperature, and air quality. Each control method is optional and have to be ordered separately as an accessory. A six meter cable for the external control panel connection is already included with the unit.

SIMPLE INSTALLATION

The unit can be simply placed on the leveled floor in the upright position.

Our external connection board comes ready with prewired inputs and outputs, making it a breeze to set up external sensors, heaters, coolers, and more.

Embrace hassle-free installation and harness the power of customization.

KEY COMPONENTS

The unit comes with a built-in electric heater. Water radiator for heating or cooling of the supply air is available as an accessory.

The built-in humidity sensor in extract air can be used for demand control.

The unit features sturdy double-skinned panels. Maintenance is effortless with easily removable components.

The unit is equipped with a high efficiency variable speed rotating heat exchanger and a moisture transfer function that regulates the rotation speed of the rotor. Energy efficient fans with EC motors as well as low-pressure filters reduce the energy consumptions and ensures low SFP factor (Specific Fan Power) and sound level.