

v2.0.0-M7

Value Types

Number Types	byte, Byte, short, Short, int, Integer, long, Long, float, Float, double, Double, BigInteger, BigDecimal
Boolean Types	boolean, Boolean
Text Types	char, Character, String, Password
Markup Types	Markup, AsciiDoc, Markdown
Temporal Types	java.util.Date, java.sql.{Date Timestamp} java.time.{LocalDate LocalDateTime} Joda Time (deprecated) time-of-day types yet not supported by UI, hence not listed
Enum Types	any
Collection Types	Collection<T>, List<T>, Set<T>, Can<T>, T[]
Additional Types	BufferedImage, Blob, Clob, UUID, Url, LocalResourcePath, SSE (ServerSentEvents)

Error & Exception Handling

RecoverableException	anticipated error that results in an UI notification popup
NonRecoverableExeption	error that results in an error page showing the stacktrace

Spring Annotations and Standard API

@SpringBootApplication @SpringBootTest @Configuration @Import @ComponentScan @EntityScan	Bootstrapping
@Component @Service @Repository	Indicates that a class is a "component". Such classes are considered as candidates for auto-detection when using annotation-based configuration and classpath scanning.
@EventListener	Marks a method as a listener for application events. Domain Events .. subscribe using Spring's @EventListener @DomainObject(xxxLifecycleEvent=....) @DomainObjectLayout(xxxUiEvent=....) @Action(domainEvent=....) @Property(domainEvent=...) @Collection(domainEvent=....)
@Nullable (org.springframework.lang)	declares that annotated elements can be null
@javax.inject.Inject @Autowired	Marks a constructor, field, setter method, or config method as to be autowired by Spring's dependency injection facilities.
@PostConstruct	Marks a method to be executed after dependency injection is done to perform any initialization.
@PreDestroy	Marks a method as a listener for notification that the instance is in the process of being removed by the container.

New Programming Style: Parameters as Typed Tuple [2.0.0-M6]

Action parameters can now be collected into an immutable value type say **Parameters**, a typed tuple. The name is arbitrary. Future releases might support Java records. Instances of the **Parameters** type are passed to the various action-support methods, which need to be single-arg, except for **autoComplete**, which is required to be bi-arg.

For regular objects, action-support methods must reference parameters by index (0, 1, 2, ...). However, with *Mixins* it is allowed to reference parameters by name.

Example: *Action Mixin*, with nested class **Parameters**, using parameter references by name.

```
@Action
@RequiredArgsConstructor
public class Customer_placeOrder {

    private final Customer target;

    // typed tuple made of all the action parameters
    @Value @Accessors(fluent = true)
    public static class Parameters {
        Product product;
        int quantity;
    }

    public Customer act(
        @Parameter Product product,
        @Parameter int quantity) {
        // ...
        return target;
    }

    // support methods (no action name reference required)
    public boolean hide() { ... }
    public String disable() { ... }
    public String validate(Parameters params) { ... }

    // parameter support methods (exemplified on first parameter)
    public boolean hideProduct(Parameters params) { ... }
    public String disableProduct(Parameters params) { ... }
    public String validateProduct(Parameters params) { ... }
    public Collection<Product> choicesProduct(Parameters params){ ... }
    // note: additional search parameter required: search
    public Collection<Product> autoCompleteProduct(
        Parameters params, @MinLength(3) String search) { ... }
    public Product defaultProduct(Parameters params) { ... }

    // parameter supporting methods (exemplified on second parameter)
    public boolean hideQuantity(Parameters params) { ... }
    // ...
}
```

Entity and Viewmodel Annotations

JPA Entities (javax.persistence)
@Entity @Table @NamedQueries @Id @Version @Column @Transient
JDO Entities (javax.jdo.annotation)
@PersistenceCapable @DatastoreIdentity @Inheritance @Discriminator @Version @Queries @Uniques @Indices @NotPersistent @Column @PrimaryKey @Join @Element
JAXB View Models (javax.xml.bind.annotation)
@XmlRootElement; @XmlType @XmlAccessorType; @XmlTransient referenced entities: @XmlJavaTypeAdapter(PersistentEntityAdapter.class)