


RoHS Compliant



NOTES:

MATERIAL:

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER(UL94V-0).
2.CONTACT MATERIAL :PHOSPHOR BRONZE T=0.35mm (C5191).
3.PLATING :GOLD PLATING OVER NICKEL.
4.SHIELD: COPPER ALLOY 0.20mm THICKNESS PLATING NI.

ELECTRICAL:


- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :1.5 AMP.
- 3.CONTACT RESISTANCE :50 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC.
- 5.DIELECTRIC WITHSTANDING
RESISTANCE :1000V AC RMS 50Hz. 1MIN.


MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1.STORAGE :-40°C TO +85°C.
2. OPERATION : -20°C TO 70°C.
MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68.SUBPART F.



	NOT SCALED DRAWING	TOLERANCE UNLESS OTHERWISE NOTICE	INCH	MM	DR. Nina	DATE MAY-06-12	HENGLIAN ELECTRONIC TECHNOLOGY CO.,LTD 恒连电子科技有限公司 http://www.chinarj45.com
JACK WITH WIRE	 THIRD ANGLE PROJECTION	LINEAR $\frac{\text{MM}}{\text{INCH}}$.00±0.01 .000±0.005 .0000±0.002	.00±0.25 .000±0.13 .0000±0.05	CK'D Jack	MAY-06-12	
DWG. NO. HL 012052123	$\frac{\text{MM}}{\text{INCH}}$	ANGLE +0° 30'	RADIL	+0.45 -0.15	APP'D Jack	MAY-06-12	