

DOMINO Qi
WIFI 4 THINGS



Licensed under a Creative Commons
Attribution-Share-Alike Unported License.
See creativecommons.org/licenses/by-sa/4.0/

Reference designs are provided "AS IS" and "WITH ALL FAULTS".
Global Marine Networks disclaims all other warranties express or implied,
regarding this product, including but not limited to any implied warranties of
merchantability or fitness for any particular application.

The Domino Team may make changes to specifications and product
descriptions at any time, without notice.


© 2014-2015, The Domino Team
All rights reserved.

Domino Qi Mini

27/01/15 20:44

Sheet: 1/1

Rev.A





Sym	N°	Mils	MM	Qty	Plated
+	1	12	0.30	312	YES
×	2	22	0.55	2	NOT
▣	3	31	0.80	6	NOT
◇	4	40	1.02	44	YES

Class	RF	Type	Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	50 Ohms	26 mils	N/A	6 mils	
Class	USB	Type	Diff Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	90 Ohms	14.5 mils	6 mils	6 mils	
Class	Ethernet	Type	Diff Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	100 Ohms	10 mils	6 mils	6 mils	


1.061 MM +/-10%

LAYER 1 LT TOP ← 18 UM CU + 12.5 UM PLATING (30.5 UM)

CORE ← 1.0 MM CORE FR-4 LG 135 INCLUDING COPPER


LAYER 4 LT BOTTOM ← 18 UM CU + 12.5 UM PLATING (30.5 UM)


1. PRINTED CIRCUIT BOARD MADE FROM NEMA GRADE FR-4 TO 135 EPOXY LAMINATE WITH 18 UM COPPER PLATING AND 1 MM THICKNESS.
2. ALL DIMENSIONS ARE GIVEN IN MILLIMETERS EXCEPT TRACE WIDTH/SPACE.
3. CIRCUIT PATHS ARE FOR REFERENCE ONLY.
4. HOLE SIZES SHOWN ARE FINISHED DIAMETERS AFTER PLATING.
5. BOARD PLATED USING REFLOW OR SIMILAR METHOD.
6. BOARD TO HAVE WHITE SOLDER MASK ON PLATED SURFACES USING WET FILM SR100 OR SR1010 EPOXY.
EQUIVALENT WET OR DRY FILM MAY BE USED.
7. SILKSCREEN BOARD USING BLACK INK. DISTORTION OF SILKSCREEN IS ACCEPTABLE OVER TRACES. EPOXY INK ON PLATED LANDS IS NOT ACCEPTABLE
8. THE FOLLOWING INFORMATION APPLIES TO THIS BOARD:
 - * 2 COPPER LAYERS
 - * 1 MM BOARD THICKNESS
 - * REQUIRES TOP AND BOTTOM SIDE SILKSCREENS



Reference designs are provided "AS IS" and "WITH ALL FAULTS". The Domino Team disclaims all other warranties express or implied, regarding this product, including but not limited to, any implied warranties of merchantability or fitness for any particular application.

Rev. A






DRILL CHART: TOP TO BOTTOM

Sym	N°	Mils	MM	Qty	Plated
+	1	12	0.30	312	YES
×	2	22	0.55	2	NOT
□	3	31	0.80	6	NOT
◇	4	40	1.02	44	YES

LINE WIDTH IMPEDANCE CHART FOR REFERENCE

Class	RF	Type	Coated Coplanar Waveguide With Ground 1B		
Layer	Impedance	Trace Width		Trace Separation	Ground Separation
TOP, BOTTOM	50 Ohms	26 mils		N/A	6 mils
Class	USB	Type	Diff Coated Coplanar Waveguide With Ground 1B		
Layer	Impedance	Trace Width		Trace Separation	Ground Separation
TOP, BOTTOM	90 Ohms	14.5 mils		6 mils	6 mils
Class	Ethernet	Type	Diff Coated Coplanar Waveguide With Ground 1B		
Layer	Impedance	Trace Width		Trace Separation	Ground Separation
TOP, BOTTOM	100 Ohms	10 mils		6 mils	6 mils


STACK-UP FOR REFERENCE



NOTES:

1. PRINTED CIRCUIT BOARD MADE FROM NEMA GRADE FR-4 TG 135 EPOXY LAMINATE WITH 16 UM COPPER PLATING AND 1 MM THICKNESS.
2. ALL DIMENSIONS ARE GIVEN IN MILLIMETERS EXCEPT TRACE WIDTH/SPACE.
3. CIRCUIT PATHS ARE FOR REFERENCE ONLY.
4. HOLE SIZES SHOWN ARE FINISHED DIAMETERS AFTER PLATING.
5. BOARD PLATED USING REFLOW OR SIMILAR METHOD.
6. BOARD TO HAVE WHITE SOLDER MASK ON PLATED SURFACES USING WET FILM SR100 OR SR1010 EPOXY. EQUIVALENT WET OR DRY FILM MAY BE USED.
7. SILKSCREEN BOARD USING BLACK INK. DISTORTION OF SILKSCREEN IS ACCEPTABLE OVER TRACES. EPOXY INK ON PLATED LANDS IS NOT ACCEPTABLE.
8. THE FOLLOWING INFORMATION APPLIES TO THIS BOARD:
 - * 2 COPPER LAYERS
 - * 1 MM BOARD THICKNESS
 - * REQUIRES TOP AND BOTTOM SIDE SILKSCREENS

DOMINO Qi
WIFI 4 THINGS



Licensed under a Creative Commons Attribution-Share-Alike Unported License. See creativecommons.org/licenses/by-sa/4.0/

Reference designs are provided "AS IS" and "WITH ALL FAULTS". The Domino Team disclaims all other warranties express or implied, regarding this product, including but not limited to, any implied warranties of merchantability or fitness for any particular application.

The Domino Team may make changes to specifications and product descriptions at any time, without notice.

© 2014-2015, The Domino Team. All rights reserved.

Domino Qi Mini

not saved!

Silk screen SOL (.PLS)

Rev. A



1234

A

LAYER-STACK

Sym	N°	Mils	MM	Qty	Plated
+	1	12	0.30	312	YES
×	2	22	0.55	2	NOT
□	3	31	0.80	6	NOT
◇	4	40	1.02	44	YES

B

LINE WIDTH IMPEDANCE CHART FOR REFERENCE

Class	RF	Type	Coated Coplanar Waveguide With Ground 1B	
Layer	Impedance	Trace Width	Trace Separation	Ground Separation
TOP, BOTTOM	50 Ohms	26 mils	N/A	6 mils

Class	USB	Type	Diff Coated Coplanar Waveguide With Ground 1B	
Layer	Impedance	Trace Width	Trace Separation	Ground Separation
TOP, BOTTOM	90 Ohms	14.5 mils	6 mils	6 mils

Class	Ethernet	Type	Diff Coated Coplanar Waveguide With Ground 1B	
Layer	Impedance	Trace Width	Trace Separation	Ground Separation
TOP, BOTTOM	100 Ohms	10 mils	6 mils	6 mils

STACK-UP FOR REFERENCE

1.061 MM +/-10%

LAYER 1 LT TOP

CORE

LAYER 4 LT6 BOTTOM

← 18 UM CU + 12.5 UM PLATING (30.5 UM)

← 1.0 MM CORE FR-4 LG 135 INCLUDING COPPER

← 18 UM CU + 12.5 UM PLATING (30.5 UM)

C

NOTES:

1. PRINTED CIRCUIT BOARD MADE FROM NEMA GRADE FR-4 TG 135 EPOXY LAMINATE WITH 18 UM COPPER PLATING AND 1 MM THICKNESS.

2. ALL DIMENSIONS ARE GIVEN IN MILLIMETERS EXCEPT TRACE WIDTH/SPACE

3. CIRCUIT PATHS ARE FOR REFERENCE ONLY.

4. HOLE SIZES SHOWN ARE FINISHED DIAMETERS AFTER PLATING.

5. BOARD PLATED USING REFLOW OR SIMILAR METHOD.

6. BOARD TO HAVE WHITE SOLDER MASK ON PLATED SURFACES USING WET FILM SR100 OR SR1010 EPOXY. EQUIVALENT WET OR DRY FILM MAY BE USED.

7. SILKSCREEN BOARD USING BLACK INK. DISTORTION OF SILKSCREEN IS ACCEPTABLE OVER TRACES. EPOXY INK ON PLATED LANDS IS NOT ACCEPTABLE

8. THE FOLLOWING INFORMATION APPLIES TO THIS BOARD:

* 2 COPPER LAYERS

* 1 MM BOARD THICKNESS

* REQUIRES TOP AND BOTTOM SIDE SILKSCREENS

D

Licensed under a Creative Commons Attribution-Share-Alike Unported License. See creativecommons.org/licenses/by-sa/4.0/

Reference designs are provided "AS IS" and "WITH ALL FAULTS". The Domino Team disclaims all other warranties express or implied, regarding this product, including but not limited to, any implied warranties of merchantability or fitness for any particular application.

The Domino Team may make changes to specifications and product descriptions at any time, without notice.

© 2014-2015, The Domino Team. All rights reserved.

Domino Qi Mini

not saved!


Solder stop mask SOL (.STS)

Rev. A

1234









Sym	N°	Mils	MM	Qty	Plated
+	1	12	0.30	312	YES
×	2	22	0.55	2	NOT
▣	3	31	0.80	6	NOT
◇	4	40	1.02	44	YES

Class	RF	Type	Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	50 Ohms	26 mils	N/A	6 mils	
Class	USB	Type	Diff Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	90 Ohms	14.5 mils	6 mils	6 mils	
Class	Ethernet	Type	Diff Coated Coplanar Waveguide With Ground 1B		
LAYER	Impedance	Trace Width	Trace Separation	Ground Separation	
TOP, BOTTOM	100 Ohms	10 mils	6 mils	6 mils	

1.061 MM +/- 10%

LAYER 1 LT TOP

18 UM CU + 12.5 UM PLATING (30.5 UM)


CORE

1.0 MM CORE FR-4 LG 135 INCLUDING COPPER

LAYER 4 LT6 BOTTOM

18 UM CU + 12.5 UM PLATING (30.5 UM)

1. PRINTED CIRCUIT BOARD MADE FROM NEMA GRADE FR-4 TO 135 EPOXY LAMINATE WITH 18 UM COPPER PLATING AND 1 MM THICKNESS.
2. ALL DIMENSIONS ARE GIVEN IN MILLIMETERS EXCEPT TRACE WIDTH/SPACE.
3. CIRCUIT PATHS ARE FOR REFERENCE ONLY.
4. HOLE SIZES SHOWN ARE FINISHED DIAMETERS AFTER PLATING.
5. BOARD PLATED USING REFLOW OR SIMILAR METHOD.
6. BOARD TO HAVE WHITE SOLDER MASK ON PLATED SURFACES USING WET FILM SR100 OR SR1010 EPOXY.
EQUIVALENT WET OR DRY FILM MAY BE USED.
7. SILKSCREEN BOARD USING BLACK INK. DISTORTION OF SILKSCREEN IS ACCEPTABLE OVER TRACES. EPOXY INK ON PLATED LANDS IS NOT ACCEPTABLE
8. THE FOLLOWING INFORMATION APPLIES TO THIS BOARD:
 - * 2 COPPER LAYERS
 - * 1 MM BOARD THICKNESS
 - * REQUIRES TOP AND BOTTOM SIDE SILKSCREENS



Reference designs are provided "AS IS" and "WITH ALL FAULTS". The Domino Team disclaims all other warranties express or implied, regarding this product, including but not limited to, any implied warranties of merchantability or fitness for any particular application.

© 2014-2015, The Domino Team.
All rights reserved.

Domino Qi Mini

not saved!

Component Assembly SOL (.ASS) Rev. A

1



