


P. C. B LAYOUT



1. Electronic Characteristics:

Contact Resistance	: $\leq 30m\Omega$
Insulation Resistance	: $\geq 100M\Omega$
Rating Value	: DC 30V 0.3A
Actuating Force	: 0.7 \sim 4kg
Withstand Voltage	: AC500V (50Hz)/min
Life	: 10,000 Cycles

2. Environmental:

Operating Temperature Range -30 $^{\circ}$ C to +70 $^{\circ}$ C


3. Material:

Housing : Thermoplastics UL94V-0
Terminal: Copper Alloy, T=0.25mm
Shell : Copper/Iron, T=0.30mm

4. Finish:

Contact : Plated Gold in Mating Area;
Tin On Solder Tails
Shell : Nickel Plating

NO:	PARTICULAR	BY	DATE
1	REVISIONS		



SZJUSTWELL ELECTRONICS CO., LTD

MODEL: USB AF-002W	GENERAL TOLERANCE:	DRAWN BY : Leiqin 99.04.27
TITLE: USB JACK	WITHIN: 1.5mm \pm 0.1mm OVER : 1.5mm \pm 0.2mm	CHECKED BY : Liwei 99.04.30
SCALE: 4:1	UNIT: mm	APPROVED BY: Wuxin 99.04.30