


Recap

30 June 2023

19:26




What is Multiclass Classification

30 June 2023 14:16

	cgpa	iq	placement	
{	9	90	4	→ <u>3 classes</u>
	6	60	N	
	7	70	OPT	
	<div><div>6.5</div><div>65</div></div>			

n classes



How to Logistic Regression handles Multiclass Classification Problems

30 June 2023 17:12

binary classification


- OVR (one vs rest) → OVA (one vs all)
- Multinomial LR → Softmax Reg

$\hookrightarrow k \text{ models} \rightarrow k \text{ prob} \rightarrow \text{normalize}$



OVR Approach

30 June 2023 17:13

train \rightarrow prediction \rightarrow code




Prediction $\{6.5, 65\} \rightarrow Y, N, 0$



\rightarrow efficient \rightarrow large dataset
low high num

$n =$



efficient large number
has high number
of classes

Code

30 June 2023 17:13

Sigmoid function

Softmax LR

$$\underline{\sigma}(\underline{z})_i = \frac{e^{z_i}}{\sum_{j=1}^K e^{z_j}}$$

z₁ z₂ z₃

$$\sigma(z_1) = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + e^{z_3}}$$

$$\sigma(z_1) + \sigma(z_2) + \sigma(z_3) = \textcircled{1}$$

↓
multiclass

$$\sigma(z_2) = \frac{e^{z_2}}{e^{z_1} + e^{z_2} + e^{z_3}}$$


$$\sigma(z_3) = \frac{e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3}}$$

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

← binary

prob

0-1



training \rightarrow prediction \rightarrow code

one

cgpa	iq	placement = Y	plac = N	plac = 0
-	-x	1	0	0
-	-N	0	1	0
-	-0	0	0	1

loss function \rightarrow

binary

$$L = -\frac{1}{n} \sum_{i=1}^n y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)$$

$K=2$

3 parameters

$K=3$

$$L = -\frac{1}{n} \sum_{i=1}^n \sum_{k=1}^K y_i^k \log \hat{y}_i^k$$

general

$K = \# \text{ classes } (Y, N, 0)$

$\# \text{ classes} \rightarrow 2 \rightarrow \textcircled{C}$

softmax LR

minimize

9 parameters

3 classes

2 in ph

$$\sum_{k=1}^K y^k \log \hat{y}^k = \log \hat{y}^{yes} +$$

cgpa	iq	plac = Y	plac = N	plac = 0
-	-	1	0	0
-	-	0	1	0
-	-	0	0	1

$\eta = 1$

3 rows

1000

$i=1$

$$y^{yes} \log \hat{y}^{yes} + y^{no} \log \hat{y}^{no} + y^{opt} \log \hat{y}^{opt}$$

$$\log(\hat{y}^{yes}) + 0 + 0$$

$$\log \hat{y}^{opt}$$

$$\log \hat{y}^{no}$$

1000 $\log \hat{y}_3^{opt}$

① $\beta_0 \beta_1 \beta_2$

$-\frac{1}{n} \sum_{i=1}^n \sum_{k=1}^K y_i^k \log(\hat{y}_i^k)$

minimize $L = \log(\hat{y}_1) + \log(\hat{y}_2) + \log(\hat{y}_3)$

row number y -value

3 random lines

random \rightarrow sigmoid $\rightarrow 0, 1$

\hat{y}_i \rightarrow output of logistic

$\hat{y}_1^{yes}, \hat{y}_2^{no}, \hat{y}_3^{opt}$

$-y_i \log(\hat{y}_i)$

$z_i = \beta_0 + \beta_1 x_{i1} + \beta_2 x_{i2}$

$\hat{y}_1^{yes} = \sigma(z_i) = \frac{e^{z_{yes}}}{e^{z_{yes}} + e^{z_{no}} + e^{z_{opt}}}$

$\hat{y}_2^{no} = \frac{e^{z_{no}}}{e^{z_{yes}} + e^{z_{no}} + e^{z_{opt}}}$

$\hat{y}_3^{opt} = \frac{e^{z_{opt}}}{e^{z_{yes}} + e^{z_{no}} + e^{z_{opt}}}$

$z_{yes} = 8$

$z_{no} = 8$

$z_{opt} = 8$

$\beta_0 + \beta_1 8 + \beta_2 80$

$\beta_0^{(2)} + \beta_1^{(2)} 8 + \beta_2^{(2)} 80$

$\beta_0^{(3)} + \beta_1^{(3)} 8 + \beta_2^{(3)} 80$

$\beta_0' = \beta_0 - \eta \frac{\partial L}{\partial \beta_0}$

9 different

1,0

$\eta \leq \dots \leq 1$

multipl
1000

$$\frac{\partial L}{\partial \beta_0^1} = -\frac{1}{n} \sum_{i=1}^n \sum_{k=1}^K y_i^k \log(\hat{y}_i^k) \quad \xrightarrow{k=2} \text{binary cross entropy}$$

$$= -\frac{1}{n} \sum_{i=1}^n y_i^1 \log(\hat{y}_i^1) + y_i^0 \log(\hat{y}_i^0)$$

$\hat{y}_i^0 = (1 - \hat{y}_i^1)$

$$\begin{bmatrix} y_i^1 & y_i^0 \end{bmatrix}$$

n, y

cgpa | iq | placement

$$\underline{1} \rightarrow y_i^1 = 1 \quad y_i^0 = 0$$

$$\underline{0} \rightarrow y_i^0 = 1 \quad y_i^1 = 0$$

$$\uparrow \quad 1 - 1 = 0$$

$$\hat{y}_i = 0.37 \rightarrow p(1) = 0.37$$

$p(0) = 0.63$

$$= -\frac{1}{n} \sum_{i=1}^n y_i^1 \log(\hat{y}_i^1) + \underbrace{(1 - y_i^1) \log(1 - \hat{y}_i^1)}$$

$$= -\frac{1}{n} \sum_{i=1}^n y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)$$

binary cross

gradients

$\mu_1 \rightarrow$	$\beta_0^1 \quad \beta_1^1 \quad \beta_2^1$
$\mu_2 \rightarrow$	$\beta_0^2 \quad \beta_1^2 \quad \beta_2^2$
$\mu_3 \rightarrow$	$\beta_0^3 \quad \beta_1^3 \quad \beta_2^3$

predict $\{6.5, 65\}$

$$\rightarrow z_1 = \beta_0^1 + 6.5 \beta_1^1 + 65 \beta_2^1$$

$$\rightarrow z_2 = \beta_0^2 + 6.5 \beta_1^2 + 65 \beta_2^2$$

$$\rightarrow z_3 = \beta_0^3 + 6.5 \beta_1^3 + 65 \beta_2^3$$

Prediction

Softmax $\rightarrow \sigma(z_1) = \frac{e^{z_1}}{e^{z_1} + e^{z_2} + e^{z_3}} = 0.3$

$$\sigma(z_3) = \frac{e^{z_3}}{e^{z_1} + e^{z_2} + e^{z_3}} = \underline{0.5}$$

$$\sigma(z_2) = \frac{e^{z_2}}{e^{z_1} + e^{z_2} + e^{z_3}} = 0.2$$

Code

30 June 2023 17:13

When to use what?


30 June 2023 17:13

Use One-vs-Rest (OVR) when:

1. **Classes are Non-Mutually Exclusive:** OVR is appropriate if an instance can belong to more than one class, as each classifier provides an independent probability for each class.
2. **Dealing with Imbalanced Data:** OVR might perform better when class distribution is highly imbalanced since each class gets a dedicated model.

Use Multinomial Logistic Regression (SoftMax Regression) when:

1. **Computational Efficiency is Required:** Softmax Regression is generally more efficient for large datasets and a high number of classes.
2. **Classes are Mutually Exclusive:** SoftMax Regression is a good choice when each instance can only belong to one class. The SoftMax function provides a set of probabilities that sum to 1, fitting well with mutually exclusive classes.
3. **Interpretability is Important:** The probabilities output by SoftMax Regression are more interpretable than those from OVR, as they always sum to 1. This can make model predictions easier to explain.



Tasks

30 June 2023 18:19

1. Derive sigmoid from softmax
2. Derive binary cross entropy from categorical cross entropy
3. Find the derivative of Softmax Function ←
4. Find the gradients of cross entropy error

$$\sigma(z) = \sigma(z) (1 - \sigma(z))$$

↑

