

```

// Initialize Time
configTime(19800, 0, "pool.ntp.org"); // IST: GMT+5:30
while(!time(nullptr)) delay(1000);

// Initialize BLE
BLEDevice::init("");
pBLEScan = BLEDevice::getScan();
pBLEScan->setActiveScan(true);
pBLEScan->setInterval(97);
pBLEScan->setWindow(37);
}

void loop() {
    checkDailyReset();
    processBLEScan();
    checkForExits();
    delay(2000);
}

void processBLEScan() {
    BLEScanResults* scanResults = pBLEScan->start(SCAN_TIME, false); // Fixed pointer declaration
    time_t now;
    time(&now);

    if (scanResults) {
        for(int i = 0; i < scanResults->getCount(); i++) { // Use -> operator
            BLEAdvertisedDevice device = scanResults->getDevice(i);
            String devName = device.getName().c_str();

            for(auto &emp : employees) {
                if(devName == emp.beaconName) {
                    if (!emp.isActive) { // Entry event
                        emp.isActive = true;
                        emp.entryTime = now;
                        logFirebaseEvent(emp.empID, "entry", now);
                    }
                    emp.lastSeen = now; // Update last seen time
                }
            }
        }
        pBLEScan->clearResults();
    }
}

void checkForExits() {
    time_t now;
    time(&now);

    for (auto &emp : employees) {
        if (emp.isActive && (now - emp.lastSeen > EXIT_TIMEOUT)) {
            emp.isActive = false;
            emp.dailyTotal += (now - emp.entryTime);
            logFirebaseEvent(emp.empID, "exit", now);
            Firebase.setDouble(fbdo, getFirebasePath(emp.empID) + "/total", emp.dailyTotal);
        }
    }
}

```