

The Derivatives Service Bureau (DSB)

REST Rules of Engagement

Author: The Derivatives Service Bureau (DSB), Technical support team

Email: <u>technical.support@anna-dsb.com</u>

Date: 3 November 2017

Version: 3.01 RC1

Designation: Rules of Engagement

© 2017 The Derivatives Service Bureau (DSB) Limited. All Rights Reserved.

No part of this document may be photocopied, reproduced, stored in a retrieval system, or transmitted, in any form or by any means whether, electronic, mechanical, or otherwise without the prior written permission of The Derivatives Service Bureau (DSB) Limited London UK.

No warranty of accuracy is given concerning the contents of the information contained in this publication.



Proprietary Information

Derivatives Service Bureau (DSB) provides this publication "as is" without warranty of any kind, either express or implied, including but not limited to warranties of merchantability. Occasionally, the author may apply changes to the information within this document and these changes will be incorporated to subsequent revisions of this document. These periodic changes may include revisions to typographical errors and technical inaccuracies.

Copyright Derivatives Service Bureau (DSB) © 2017

All company, product, and service names are hereby acknowledged



Contents

Pı	roprieta	ry Information	2
Pı	reface		5
	Change	e History	5
1	Intro	oduction	5
	1.1	Document Purpose	5
	1.2	Intended Audience	5
	1.3	Scope	5
	1.4	Contact Information	5
	1.5	Functional Summary	5
	1.6	Activity Diagram Summary	6
	1.7	Document Structure	7
2	Site	Preparation	7
	2.1	Introduction	7
	2.2	JSON Product Definitions Representation as JSON Schema	9
	2.3	MiFiD II Data (ToTV)	11
3	REST	Γ API methods	12
	3.1	Introduction	12
	3.2	Obtain JSON schemas	12
	3.3	Retrieve or Create ISIN Record by Attribute	13
	3.4	Retrieve ISIN Record by Attribute	14
	3.5	Retrieve ISIN or ToTV Record by ISIN	15
	3.6	Search for ISIN or ToTV Records by attributes	16
	3.7	Download historical ISINs	18
4	Met	hods Reference	19
	4.1	Introduction	19
	4.2	Obtain schema names	19
	4.3	Obtain single schema	19
	4.4	Retrieve or Create ISIN Record by Attribute Retrieve ISIN Record by Attribute	20
	4.5	Retrieve ISIN or ToTV Record by ISIN	21
	4.6	Search for ISIN or ToTV Records by attributes	22
	4.7	Download Historical ISINs	23
5	RES	Γ Methods Samples	24
	5.1	Introduction	24
	5.2	Obtain schema names	24



	5.3	Obtain single schema	. 24
	5.4	Retrieve or Create ISIN Record by Attribute	. 25
	5.5	Retrieve ISIN Record by Attribute	. 26
	5.6	Retrieve ISIN Record by ISIN	. 27
	5.7	Retrieve ToTV Record by ISIN	. 28
	5.8	Search for ISIN Records by attributes	.30
	5.9	Download Historical ISIN records	.31
Α	bout De	erivatives Service Bureau (DSB)	.32



Preface

Change History

Date	Change	Version	Author	Revision Details
7 June 2017	Creation	1.00 RC1	Yuval Cohen	Initial Version
26 June 2017	Additions	1.01 RC1	Yuval Cohen	Added: File download workflows
18 July 2017	Corrections and amendments	1.02 RC1	Yuval Cohen	Titles of section 5.4 and 5.5 got mismatched. Update /search to be a GET method Added clarifications in section 3 and 4
27 July 2017	Additions	2.00 RC1	Yuval Cohen	Clarification about token Added workflow: Test for ISIN existence
3 August 2017	Additions	2.01 RC1	Yuval Cohen	Clarifications about status codes and maintenance schedule
20 September 2017	Additions	3.00 RC1	Yuval Cohen	Additions for MiFiD II (ToTV) workflows
3 November 2017	Additions	3.01 RC1	Yuval Cohen	Added ToTV example

1 Introduction

1.1 Document Purpose

This specification defines the implementation of the Representational State Transfer (REST or RESTful) Web Service by the Derivatives Service Bureau (DSB) Limited for determining the ISIN for a financial instrument. In doing so it aims to provide a comprehensive reference guide to any such institutions who wish to automate the usage of the DSB REST API Web service.

1.2 Intended Audience

Anyone with an interest in creating or querying ISINs for financial OTC derivatives instruments using an automated REST API web service.

1.3 Scope

This document focuses on the use of the DSB REST API to define and query for ISINs for OTC derivative financial products.

1.4 Contact Information

Please direct your questions on the REST API via email technical.support@anna-dsb.com

1.5 Functional Summary

The DSB REST API provides a near real time service to determine ISINs for OTC derivative financial instruments. Each financial instrument supported by the DSB service is defined by a unique set of attributes verified by industry.



1.6 Activity Diagram Summary

The following diagram illustrates, the DSB REST API Web service:




Diagram 1: Activity Diagram



1.7 Document Structure

This document contains the following sections:

Section Number	Title	Description
Section 1	Introduction	A brief introduction to this document providing background to the purpose of the document and the DSB REST API Web service.
Section 2 Site Preparation Provides details of the REST API implementation and the trequired to use the service.		
Section 3	REST API methods	Provides details of the methods and workflows that are supported DSB.
Section 4	REST API methods Reference	Contains the definitions of the methods that are supported by the DSB REST API service including possible arguments and expected response codes.
Section 5	Methods samples	Some sample methods that illustrate the possible contents of the methods as well as their response.

2 Site Preparation

2.1 Introduction

The following preparation is required to use the DSB REST API Web Service:

- Users should follow and adhere to the <u>REST architectural constraints</u> called RESTful APIs.
- Web service methods are transmitted over the internet using HTTPS (HTTP secure over SSL) protocol through port 443
- DSB operations will provide authentication parameters: username and password
 - Users should attach the authentication parameters to each of the REST methods' header with:

```
key = "Authorization"
value = base64(username + ":" + password)
```

The username and password are concatenated with a colon separator and encoded in <u>base64</u>.

- Access to the DSB Web Service is by default restricted to a throughput of one message per minute. Users wishing to increase this throughput rate may ask DSB operations to provide a DSB-Token for use with the REST API. The token increases the message rate for Power Users as per the DSB Acceptable User Policy (currently set at 60 messages per minute).
 - Users should attach the DSB-token to each of the REST methods' header with: key = "DSB-Token" value = <token>

DSB Web Service responds with status code 429 (too many request) when a client exceeds its rate limit.

- Users should make any network/firewall configuration changes required to enable connectivity to the base DSB websites (below) over port 443
- The default Base URL for REST methods (except file-download see <u>Download Historical ISINs</u>) are:
 - o Production environment: https://prod.anna-dsb.com/api



- UAT environment: https://uat.anna-dsb.com/api
- The response to all methods in the REST API contains "responseCode" which follows the HTTP status codes.
 - o In case of either client errors (4XX) or Server errors (5XX) the response will contain indicative (human readable) "message".
- The DSB Web Service schedule weekly maintenance periods which currently commence on Saturday 12:00:00 and finish on Sunday 12:00:00 [mid-day] UTC. During these hours, all REST methods are expected to be responded to with HTTP status code 503 (Service unavailable).
- Common HTTP status codes:
 - o 200: OK, Success.
 - o 401: Unauthorized
 - 429: too many request [The user has sent too many requests in a given amount of time. Intended for use with rate-limiting schemes]
 - 503: Service unavailable: [The server is currently unavailable because it is down for maintenance]

Additional HTTP status codes are listed in section 4.



2.2 JSON Product Definitions Representation as JSON Schema

2.2.1 Product Definitions

The DSB Product Committee defines the set of Product Definitions for all OTC derivatives in scope and any future changes or additions will be made under the advisement of the Product Committee. Each Product Definition can be identified by:

- Asset Class
- Instrument Type
- Product (Use case)
- Leve

Further information about the Product Definition will be available on our web-site.

2.2.2 JSON and JSON Schema

JSON is a text format that is completely language independent but uses conventions that are familiar to programmers of the C-family of languages, including C, C++, C#, Java, JavaScript, Perl, Python, and many others. JSON Schema describe existing data format in a clear, human and machine readable documentation and provides complete structural validation which is useful to validate the client submitted data.

JSON standards are available in <u>ECMA-404</u> as well as in <u>RFC-7159</u>.

JSON Schema standards are available in: JSON-SCHEMA-04

2.2.3 Product Definition as JSON Schema

The Product Definitions are formatted in a machine readable format in a set of JSON schema files, which are made available by the DSB system. Users are expected to use these JSON schema when requesting an ISIN via the RESTful API.

For each Product Definition there are two JSON schema files:

1	File: Request schema file
	Description : a schema that defines the attributes in order to request a new ISIN
	Naming Convention: Request. <assetclass>.<instrumenttype>.<product>.<level>.json</level></product></instrumenttype></assetclass>
	Example of a name: _Request.Rate.Swap.FixedFloatPlainVanilla.InstRefDataReporting.json
2	File: Record schema file
	Description : a schema that defines the attributes in the ISIN Record which is returned from the DSB
	Naming Convention: <assetclass>.<instrumenttype>.<product>.<level>.<version>.json</version></level></product></instrumenttype></assetclass>
	Example of a name: Rate.Swap.FixedFloatPlainVanilla.InstRefDataReporting.V1.json

The example for the name above is for a Product Definition where:

- Asset Class = Rate
- Instrument Type = Swap
- Product (Use Case) = FixedFloatPlainVanilla
- Level = InstRefDataReporting

The (Template) Version is added for backwords compatibility to the record file only

• Template Version = V1



2.2.4 Using JSON Schema

This subsection lists some of the main tasks and procedures to interact with the DSB system

- 1. User needs to obtain the up-to-date JSON schema
 - I. Users can download JSON schema using REST API (see Obtain JSON schemas)
 - II. JSON schema are available to download from the DSB web-site (in the file-download section)
 - III. JSON schema are also available through GitHub in: https://github.com/ANNA-DSB
- 2. To request for a new ISIN, user needs to:
 - I. Select a 'Request' JSON schema which matches their needs. Each Request JSON Schema can be uniquely identified by four attributes:
 - Asset Class
 - Instrument Type
 - Product (Use Case)
 - Level
 - II. Format the required instrument and supply its attributes as a valid *JSON request for* an instrument record based on the Request JSON Schema
 - III. Embed the JSON request for an instrument record within a POST /records (see Request the ISIN for a financial instrument) method
- 3. In case the responseCode is continue (100) or successful (200) the response contains a *JSON* instrument record
- 4. To parse the JSON instrument record, the user needs to:
 - I. Extract the TemplateVersion attribute and Header which contains:
 - Asset Class
 - Instrument Type
 - Product (Use Case)
 - Level
 - II. Select the relevant JSON record schema that matches above attribute
 - III. Continue to parse additional attributes in the *JSON instrument record* as it must be a valid record based on the schema found above



2.3 MiFiD II Data (ToTV)

The DSB provides access to a composite instruments records that are available in <u>FiRDS reference</u> <u>data</u> or in <u>FiRDS transparency data</u>

The business requirements as well as the methodology to create and update these records are available in: https://github.com/ANNA-DSB/ToTV-uToTV

The ToTV records are reported as JSON records based on the JSON schema that is available in: https://github.com/ANNA-DSB/ToTV-uToTV

The ToTV records contain:

- The entire ISIN record, if such is available in the DSB
- All the reference data that was reported in FiRDS aggregated by MIC
- The transparency thresholds like pre-trade and post-trade 'large in scale' (LIS) and 'instrument size specific' (SSTI) and others.
- Derived flags like the ToTV and uToTV flag.
- The last modified date of the record

Users can indicate in the REST API if they would like to receive DSB ISIN records or ToTV records.



3 REST API methods

3.1 Introduction

This section looks at the methods that will be supported by DSB REST API.

All the DSB REST methods are HTTP based RESTful methods that adhere to the REST architectural constraints.

The HTTP Status codes in the response adhere to the standard HTTP/1.1 (RFC 7231).

3.2 Obtain JSON schemas

To obtain the JSON schemas user needs to invoke GET /schemas?names that will return the list of schema names. Using each of these names the user may invoke GET

/schemas?SchemaName=<NAME> that will return the JSON schema for that name.




Diagram 2: Obtain JSON schema



3.3 Retrieve or Create ISIN Record by Attribute

The POST /records method is used to create the ISIN record for a financial instrument or return the existing record if the ISIN record already exists. The financial instrument is defined by a *JSON instrument request* object provided in the "record" within the body of the request.

The input JSON record must contain a "record" component where the financial instrument is provided. The input may also contain a "requestContext" which will be echoed back in the response and may help users to identify their request.

The REST API service will first search for an existing ISIN that has identical attributes as the record (up to normalization, see section 6 in: <u>DSB UAT Product Definition.pdf</u>) and if such an ISIN exists, the result record will contain the ISIN.

If such an ISIN does not exist, the DSB will allocate a new ISIN for this request.

In both cases, provided the request is valid, the resulting record will contain an ISIN. The client will not be able to tell if the ISIN was just allocated or if it existed prior to this call.




Diagram 3: Retrieve or Create ISIN Record by Attribute



3.4 Retrieve ISIN Record by Attribute

The POST /records method that is described in the previous section, can be used with additional parameter: POST /records?create=false

The additional parameter: create=false guarantees that no new record will be added to the system.

For the input JSON record see the previous section.

The REST API service will search for an existing ISIN that has identical attributes as the supplied record (up to normalization, see section 6 in: DSB UAT Product Definition.pdf) and if such an ISIN exists, the result record will contain the ISIN record.

If such an ISIN does not exist, the DSB will not allocate a new ISIN, instead the system will calculate all derived values and the output record will contain all attributes except of the ISIN value.

This method can be used to resolve the derived attributes (e.g. CFI code, and FISN) of the record without the need to create the associated ISIN.




Diagram 4: Retrieve ISIN Record by Attribute



3.5 Retrieve ISIN or ToTV Record by ISIN

The $\mbox{GET /records/<ISIN>}$ method is used to return the ISIN record for an existing ISIN. The ISIN is specified in <ISIN>.

By default, the user retrieves an ISIN record. To receive the ToTV record, user needs to add to the request the parameter: ToTV=true




Diagram 5: Retrieve ISIN or ToTV Record by ISIN



3.6 Search for ISIN or ToTV Records by attributes

The GET /search/ method can be used to search for ISIN records that match the supplied criteria.

The user must specify the following arguments:

- query: (i.e. a query string). Please refer to DSB Search Query Syntax document.
- pageSize: which is the maximum number of results that are returned in each page
- pageNum: see explanation below
- requestContext: a valid JSON record that may help to identify the query

To retrieve the first 100 records, the user should specify:

"pageSize": 100 "pageNum": 1

To retrieve the next 100 records, the user should invoke the GET /search/ method again, with the same query but using:

"pageSize": 100 "pageNum": 2

A valid response contains all the above arguments (in a JSON record) together with:

- Records: which contains the result records
- totalResults: The number of total records that matches the query criteria
- responseCode: Matches the HTTP status code

By default, the user retrieves ISIN records. To receive the ToTV records, user needs to add to the request the parameter: ToTV=true






Diagram 6: Search for ISIN Records by attributes



3.7 Download historical ISINs

The GET /file-download/<YYYYMMDD>/<ASSET-CLASS>/<ASSET-CLASS>-<YYYYMMDD>.records method is used to download historical ISINs.

The <YYYYMMDD> stands for a valid date when ISINs where created.

<ASSET-CLASS> is one of:

- Credit
- Commodities
- Equity
- Foreign_Exchange
- Rates

The response contains instrument records separated by newline (\n') that were either allocated or modified on the YYYYMMDD date. Each record is a valid JSON instrument record.

See section 4.6 below for the base URL of this method.




Diagram 7: Download historical ISINs



4 Methods Reference

4.1 Introduction

This section details the REST API methods that are used by DSB Web service.

4.2 Obtain schema names

Method	1ethod Request		Required authorization	
GET	/schemas		×	
Request arguments				
Argument name	Datatype	Required	Note	
names	-	✓	No content	
Response arguments				
Output JSON record components	Datatype	Required	Note	
responseCode	Integer	✓	Matches the HTTP status code: success = 200 Error code = 4XX or 5XX	
message	String	×	Available only if response code indicates an error Contains indicative error message	
names	Array of strings	×	Conditionally required if responseCode=200 Each string indicates a single schema name	

4.3 Obtain single schema

Method GET	Request /schemas		Required authorization
Request arguments	/ scriemas		,
Argument name	Datatype	Required	Note
schemaName	String	✓	Content is expected to be a valid schema name
Response arguments			
Output JSON record components	Datatype	Required	Note
responseCode	Integer	✓	Matches the HTTP status code: success = 200 Schema Name does not exist = 404 Error code = 4XX or 5XX
message	String	×	Available only if response code indicates an error Contains indicative error message
schemas	JSON record	×	Conditionally required if responseCode=200 Contains the name of the schema (as key) and the JSON schema as value.



4.4 Retrieve or Create ISIN Record by Attribute Retrieve ISIN Record by Attribute

Method Request Requir		Required authorization			
POST	/records		✓		
Request arguments	lequest arguments				
Argument name	Datatype	Required	Note		
create	Boolean	×	The default is: create=true When create=false, the system will not allocate a new ISIN, and the output will not include ISIN.		
Input JSON record components	Datatype	Required	Note		
record	JSON record	✓	Content of an <i>Instrument Request</i> JSON record which is valid to an <i>Instrument Request schema</i>		
requestContext	JSON record	×	User may place here any information that will help to identify the request		
Response arguments					
Output JSON record components	Datatype	Required	Note		
responseCode	Integer	✓	Matches the HTTP status code: success = 200 Authorization failed: 401 Invalid record (invalid per schema): 400 Invalid JSON syntax: 500		
Message	String	×	Available only if response code indicates an error Contains indicative error message		
Record	JSON record	×	Available is responseCode=200 Contains a valid <i>instrument JSON record</i> .		
requestContext	JSON record	×	Echo the user input Conditionally required if requestContext was provided and responseCode is one of: - 200 (Success) - 400 (invalid record) - 401 (authorization failed) Note: requestContext is not available if responseCode is 500		



4.5 Retrieve ISIN or ToTV Record by ISIN

Method	Request		Required authorization	
GET	/records/ <isin></isin>		✓	
Request arguments		ı		
Argument name	Datatype	Required	Note	
ToTV	TV Boolean *		When ToTV=false, the returned record is a valid ISIN record. When ToTV=true, the returned record is a valid ToTV record. The default is: ToTV=false.	
Response arguments				
Output JSON record components	Datatype	Required	Note	
responseCode	Integer	✓	Matches the HTTP status code: success = 200 Authorization failed: 401 No such ISIN: 404	
message	String	×	Contains indicative error message Contains: "Success" in case responseCode = 200	
record	JSON record	×	Conditionally required if responseCode=200 Contains a valid <i>instrument JSON record</i> .	



4.6 Search for ISIN or ToTV Records by attributes

Method	Method Request Required authorization		
GET	/search		✓
Request arguments			
Argument name	Datatype	Required	Note
ToTV	Boolean	×	When ToTV=false, the returned records are valid ISIN record. When ToTV=true, the returned record are valid ToTV records The default is: ToTV=false
query	String	✓	Query string. refer to: DSB Search Query Syntax document.
pageSize	Positive Integer	×	The maximum number of records that return in each page Default and the maximum values are 1000
pageNum	Positive Integer	×	The page number Default to 1
requestContext	JSON record	×	User may place here any information that will help to identify the request
Response arguments			
Output JSON record components	Datatype	Required	Note
responseCode	Integer	✓	Matches the HTTP status code: success = 200 pageSize exceeds maximum = 403 Note: The responseCode does not indicate the case where user is not authorized, instead, in such a case, the totalResults is 0.
message	String	×	Available only if response code indicates an error Contains indicative error message
totalResults	Integer	×	Conditionally required if responseCode=200 Indicate the total number of records that match the query
query	String	×	Echo the user input Conditionally required if responseCode=200
pageSize	Positive Integer	×	Echo the user input Conditionally required if responseCode=200
pageNum	Positive Integer	×	Echo the user input Conditionally required if responseCode=200
records	Array of JSON	×	Conditionally required if responseCode=200
	record		Contains a valid <i>instrument JSON records</i> that matches the query.



Conditionally required if requestContext was
provided and responseCode is 200 (Success)

4.7 Download Historical ISINs

Method	Request	Required authorization						
GET	/file-download/isin/ <yyyymmdd>/<asset-class>/<asset-class>- <yyyymmdd>.records</yyyymmdd></asset-class></asset-class></yyyymmdd>	✓						
Request notes								
YYYYMMDD – st	ands for a valid date							
 Credit Commodity Foreign Rates The base url for	Asset Class – is one of: Credit Commodities Equity Foreign_Exchange							
	Production environment: https://prod.anna-dsb.com UAT environment: https://uat.anna-dsb.com							
Response notes	Response notes							
-	The response is a content of file which contains ISIN records The records are separated by new line							



5 REST Methods Samples

5.1 Introduction

This section contains REST method samples.

Some of the responses are <truncated>

5.2 Obtain schema names

```
Response

{
    "names": [
        "Credit.Swap.CDX_Risky_Zero_Tranche.InstRefDataReporting.V1",
        "Credit.Option.iTraxx_Europe_Swaption.InstRefDataReporting.V1",
        "Credit.Swap.Singapore_Corporate.InstRefDataReporting.V1",
        "Credit.Swap.Standard_LCDS_Bullet.InstRefDataReporting.V1",
        "Cruncated>
        "Request.Credit.Swap.Asia_Corporate.InstRefDataReporting"
    ],
        "responseCode": 200
}
```

5.3 Obtain single schema

GET /schemas?schemaName=<NAME>

GET /schemas?schemaName=Credit.Swap.PO.InstRefDataReporting.V1

Response

```
"schemas": {
    "Credit.Swap.PO.InstRefDataReporting.V1": {
        "$schema": "http://json-schema.org/draft-04/schema#",
        "title": "Credit.Swap.PO.InstRefDataReporting.V1",
        "description": "Record template for Credit.Swap.PO",

<truncated>
    },
    "responseCode": 200
}
```



5.4 Retrieve or Create ISIN Record by Attribute

```
POST
                           /records
POST /records
      "record": {
             "Header":{
                   "AssetClass": "Credit",
                   "InstrumentType": "Swap",
                   "UseCase": "ABX Tranche",
                   "Level": "InstRefDataReporting"
             "Attributes":{
                   "NotionalCurrency": "EUR",
                   "ExpiryDate": "20170503",
                   "UnderlyingIndexName": "ABXHE",
                   "DebtSeniority": "Senior",
                   "IndexSeries":4, "IndexVersion":5
             }
      },
      "requestContext":{
             "user": "username@email.com",
             "requestID":"ID1",
             "additional information": "blob"
      }
Response
        "record": {
                "Header": {
<truncated>
                "Attributes": {
<truncated>
                "ISIN": {
                        "ISIN": "EZ0000000SB1",
                        "Status": "New"
<truncated>
                "TemplateVersion": 1,
                "Derived": {
<truncated>
                }
        "responseCode": 200,
        "requestContext": {
                "user": "username@email.com",
                "requestID": "ID1",
                "additional information": "blob"
        }
```



5.5 Retrieve ISIN Record by Attribute

```
/records
POST
POST /records&create=false
      "record": {
             "Header":{
                   "AssetClass": "Credit",
                   "InstrumentType": "Swap",
                   "UseCase": "ABX Tranche",
                   "Level": "InstRefDataReporting"
             "Attributes":{
                   "NotionalCurrency": "EUR",
                   "ExpiryDate": "20170503",
                   "UnderlyingIndexName": "ABXHE",
                   "DebtSeniority": "Senior",
                   "IndexSeries":4, "IndexVersion":5
             }
      },
      "requestContext":{
             "user": "username@email.com",
             "requestID":"ID1",
             "additional information": "blob"
      }
Response
        "record": {
                "Header": {
<truncated>
                "Attributes": {
<truncated>
                "ISIN": {
                        "ISIN": "",
                        "Status": "New"
<truncated>
                "TemplateVersion": 1,
                "Derived": {
<truncated>
                }
        "responseCode": 200,
        "requestContext": {
                "user": "username@email.com",
                "requestID": "ID1",
                "additional information": "blob"
        }
```



5.6 Retrieve ISIN Record by ISIN

GET /records/<ISIN>

"CFI": "JTAXFC"

"responseCode": 200,
"message": "Success"

}
},

GET /records/EZ000001HT00

```
Response
{
  "record": {
    "Header": {
     "AssetClass": "Commodities",
      "InstrumentType": "Forward",
      "UseCase": "Commodities_Forward",
      "Level": "InstRefDataReporting"
    "Attributes": {
     "NotionalCurrency": "GBP",
      "ExpiryDate": "24170228",
      "ReturnPayout": "Forward price of underlying instrument",
      "DeliveryType": "Cash",
      "BaseProduct": "AGRI",
      "TransactionType": "OTHR",
      "FinalPriceType": "OTHR",
      "SubProduct": "SOFT",
      "AdditionalSubProduct": "ROBU"
    } ,
    "ISIN": {
      "ISIN": "EZ000001HT00",
      "Status": "New"
    "TemplateVersion": 1,
    "Derived": {
      "Issuer": "NA",
      "PriceMultiplier": 1,
      "CommoditiesDerivativesIndicator": "TRUE",
      "UnderlyingAssetType": "Agriculture",
      "LongName": "Commodities Forward AGRI ROBU GBP 24170228",
      "FISN": "NA/Fwd AGRI ROBU GBP 24170228",
```



5.7 Retrieve ToTV Record by ISIN

GET /records/<ISIN>&totv=true

GET /records/EZ8JND56HJK5&totv=true

```
Response
{
  "record": {
        "ToTV-record": {
                "Header": {
                        "ISIN": "EZ8JND56HJK5",
                        "LastModifiedDate": "2017-10-22",
                        "LastCompletedProcessingDate": "2017-10-30",
                        "CFI-Category": "S",
                        "CFI-Group": "R"
                "DSB-ISIN":{
                        "Header":{
                                "AssetClass": "Rates",
                                "InstrumentType": "Swap",
                                "UseCase": "Fixed Float",
                                "Level": "InstRefDataReporting"
                        "Attributes":{
                                "NotionalCurrency": "USD",
                                "ExpiryDate": "2048-03-21",
                                "ReferenceRate": "USD-LIBOR-BBA",
                                "ReferenceRateTermValue":3,
                                "ReferenceRateTermUnit": "MNTH",
                                "NotionalSchedule": "Constant",
                                "DeliveryType":"PHYS",
                                "PriceMultiplier":1
                        "ISIN":{
                                "ISIN": "EZ8JND56HJK5",
                                "Status": "New",
                                "StatusReason":"",
                                "LastUpdateDateTime":"2017-10-22T14:00:40"
                        "TemplateVersion":1,
                        "Derived":{
                                "ISOReferenceRate": "LIBO",
                                "CommodityDerivativeIndicator": "FALSE",
                                "UnderlyingAssetType":"Fixed - Floating",
                                "SingleorMultiCurrency": "Single Currency",
        "IssuerorOperatoroftheTradingVenueIdentifier": "NA",
                                "FullName": "Rates Swap Fixed Float USD-
LIBOR-BBA 3 MNTH 20480321",
                                "ShortName": "NA/Swap Fxd Flt USD 20480321",
                                "ClassificationType": "SRCCSP"
                        }
                "Derived": {
                        "ToTV": false,
                        "uToTV": false
                }
        }
  "responseCode": 200,
```



"message": "Success"
}



5.8 Search for ISIN Records by attributes

Search for Rates instruments that contains Libor

```
/records
GET
GET /search?query=LIBOR AND
Rates&pageSize=5&pageNum=3&requestContext={"requestID":"ID1"}
Response
{
          "query": "LIBOR AND Rates",
          "pageNum": 3,
          "pageSize": 5,
          "totalResults": 59,
         "records": [
<truncated> },
        <truncated> }, <truncated> }, <truncated> }, <truncated> }, <truncated> },
         <truncated> },
          "responseCode": 200,
          "requestContext": {
                    "requestID": "ID1"
```



5.9 Download Historical ISIN records



About Derivatives Service Bureau (DSB)

The Association of National Numbering Agencies ("ANNA"), is founding the Derivatives Service Bureau (DSB), for the issuance and maintenance of International Securities Identification Numbers (ISINs) for OTC Derivatives. The DSB will rely on an automated platform capable of allocating ISINs in near real-time.