

# TINA: Supplementary Proofs and Numerical Details

Scott Moeller

Bhaskar Krishnamachari

September 2026

Supplement to *A Theory of Information Architecture for Networked Decisions: Freshness, Locality, and Coordination*, revision d of arXiv v2. Unqualified references to main-paper results and equations use the accompanying paper’s numbering.

## S1 Aggregate-coupling calculations

This section supplies the matrix arithmetic for Proposition 1 in the main paper. For  $Q = qI + \gamma \mathbf{1}\mathbf{1}^\top$ ,

$$Q^{-1} = \frac{1}{q} \left( I - \frac{\gamma}{q + \gamma n} \mathbf{1}\mathbf{1}^\top \right).$$

*Proof.* Recall the coupled normal equations (24):

$$Q_{ii}u_i + \sum_{j \neq i} Q_{ij}\mathbb{E}[u_j \mid \mathcal{G}_i] = \mathbb{E}[b_i(\theta_t) \mid \mathcal{G}_i].$$

Here  $Q_{ii} = q + \gamma$ ,  $Q_{ij} = \gamma$  for  $j \neq i$ , and  $b_i(\theta) = \theta_i$ . Let  $\mu_j = \mathbb{E}[u_j]$ . For  $j \neq i$ , the policy  $u_j$  is a function of  $\theta_{j,t}$ , which is independent of  $\theta_{i,t}$ , so

$$\mathbb{E}[u_j \mid \mathcal{G}_{i,t}^{\text{loc}}] = \mathbb{E}[u_j] = \mu_j,$$

while  $\theta_{i,t}$  is  $\mathcal{G}_{i,t}^{\text{loc}}$ -measurable. The conditional normal equation (24) therefore gives

$$(q + \gamma)u_i + \gamma \sum_{j \neq i} \mu_j - \theta_{i,t} = 0.$$

Taking expectations yields

$$q\mu_i + \gamma \sum_j \mu_j = 0.$$

Summing over  $i$  implies  $\sum_j \mu_j = 0$ , hence every  $\mu_i = 0$  and  $u_i = \theta_{i,t}/(q + \gamma)$ , which proves (45). This argument uses independence, zero means, square integrability, and strict convexity; Gaussianity is not required for the local-policy formula.

*Open-loop regret.* Here  $B = I$  and  $\Sigma_\infty = \sigma^2 I$ , so by (39),  $R_\infty = \frac{\sigma^2}{2} \text{tr}(Q^{-1})$ . From the Sherman–Morrison formula above,

$$\text{tr}(Q^{-1}) = \frac{1}{q} \left( n - \frac{\gamma n}{q + \gamma n} \right) = \frac{n(q + \gamma(n - 1))}{q(q + \gamma n)},$$

which gives (46).

*Local regret.* By the Pythagorean form of Lemma 1 (the orthogonality identity after Lemma 1, with both  $x^\star$  and  $u^{\text{loc}}$  mean zero),  $2R_{\text{loc}} = \|x^\star\|_Q^2 - \|u^{\text{loc}}\|_Q^2 = 2R_\infty - \|u^{\text{loc}}\|_Q^2$ . Since  $u^{\text{loc}} = \theta/(q+\gamma)$  and  $\text{tr}(Q) = n(q+\gamma)$ ,

$$\|u^{\text{loc}}\|_Q^2 = \frac{\sigma^2 \text{tr}(Q)}{(q+\gamma)^2} = \frac{n\sigma^2}{q+\gamma}.$$

Therefore

$$R_{\text{loc}} = \frac{n\sigma^2}{2} \left[ \frac{q+\gamma(n-1)}{q(q+\gamma n)} - \frac{1}{q+\gamma} \right] = \frac{n\sigma^2}{2} \cdot \frac{(q+\gamma(n-1))(q+\gamma) - q(q+\gamma n)}{q(q+\gamma)(q+\gamma n)}.$$

The numerator reduces to  $\gamma^2(n-1)$ , which gives (47).

*Share.* Dividing (47) by (46), the factors  $n\sigma^2/2$  and  $q(q+\gamma n)$  cancel, leaving (48). □

## S2 Canonical spatial omission: detailed calculation

We expand the proof of Lemma 3 in the main paper, including the equal-inverse-length case in the variance integral.

*Proof.* By spatial stationarity, take  $z = 0$  and suppress the time argument. Write  $\beta_c \triangleq 1/\ell_c$  and  $\beta_s \triangleq 1/\ell_s$  for the inverse lengths, so  $w(u) = \frac{\beta_c}{2} e^{-\beta_c|u|}$  and  $\text{Cov}(\theta(u), \theta(u')) = \sigma^2 e^{-\beta_s|u-u'|}$ .

**Step 0 (omission is a variance ratio).** With  $Q = qI$  the optimal policy given  $\mathcal{O}_r$  is  $\mathbb{E}[x^\star(0) \mid \mathcal{O}_r]$ . Its expected loss is  $\frac{q}{2} \mathbb{E}[\text{Var}(x^\star(0) \mid \mathcal{O}_r)]$ . For a Gaussian field the conditional variance is a deterministic number: it does not depend on the observed values (companion Section 1.3). Since  $R_\infty = \frac{q}{2} \text{Var}(x^\star(0))$ ,

$$\eta_S(r) = \frac{\text{Var}(x^\star(0) \mid \mathcal{O}_r)}{\text{Var}(x^\star(0))}.$$

**Step 1 (split into observed middle and two tails).** Write  $x^\star(0) = M_r + T_r^+ + T_r^-$ , where

$$M_r = \int_{-r}^r w(u)\theta(u) du, \quad T_r^+ = \int_r^\infty w(u)\theta(u) du, \quad T_r^- = \int_{-\infty}^{-r} w(u)\theta(u) du.$$

The middle  $M_r$  is computed from observed values, so it contributes no conditional variance.

**Step 2 (rewrite the right tail).** Substituting  $u = r + s$ ,

$$T_r^+ = \frac{\beta_c}{2} e^{-\beta_c r} Y_r, \quad Y_r \triangleq \int_0^\infty e^{-\beta_c s} \theta(r+s) ds.$$

**Step 3 (spatial Markov property).** By Section 4, the field is Markov in  $z$ . Given the observed segment  $[-r, r]$ , the right tail  $\{\theta(u) : u > r\}$  and the left tail  $\{\theta(u) : u < -r\}$  are conditionally independent, and each depends on the segment only through its adjacent endpoint  $\theta(r)$  or  $\theta(-r)$ . Therefore

$$\text{Var}(T_r^+ \mid \mathcal{O}_r) = \text{Var}(T_r^+ \mid \theta(r)), \quad \text{Var}(T_r^- \mid \mathcal{O}_r) = \text{Var}(T_r^- \mid \theta(-r)), \quad \text{Cov}(T_r^+, T_r^- \mid \mathcal{O}_r) = 0.$$

**Step 4 (the tail variance does not depend on  $r$ ).** Define  $C \triangleq \text{Var}(Y_0 \mid \theta(0))$ . Shifting the field by  $r$  does not change its law, so  $\text{Var}(Y_r \mid \theta(r)) = C$  for every  $r$ . By reflection symmetry (the covariance depends only on  $|u - u'|$ ), the left tail gives the same value. Hence

$$\text{Var}(x^*(0) \mid \mathcal{O}_r) = 2 \left( \frac{\beta_c}{2} \right)^2 e^{-2\beta_c r} C = \frac{\beta_c^2}{2} e^{-2\beta_c r} C.$$

At  $r = 0$  the same argument applies with  $\mathcal{O}_0 = \sigma(\theta(0))$  and  $M_0 = 0$ , giving  $\text{Var}(x^*(0) \mid \theta(0)) = \frac{\beta_c^2}{2} C$ . Dividing,  $\eta_S(r) = \eta_S(0) e^{-2\beta_c r} = \eta_S(0) e^{-2r/\ell_c}$ . The unknown constant  $C$  cancels, so it never has to be computed.

**Step 5 (the constant  $\eta_S(0)$ ).** Conditioning on the single Gaussian variable  $\theta(0)$  gives  $\text{Var}(x^*(0) \mid \theta(0)) = \text{Var}(x^*(0))(1 - \text{Corr}(x^*(0), \theta(0))^2)$  (companion Section 1.3), so  $\eta_S(0) = 1 - \text{Corr}^2$ . Two moments are needed.

*Covariance with the local value:*

$$\text{Cov}(x^*(0), \theta(0)) = \int_{\mathbb{R}} w(u) \sigma^2 e^{-\beta_s |u|} du = \frac{\sigma^2 \beta_c}{2} \int_{\mathbb{R}} e^{-(\beta_c + \beta_s)|u|} du = \frac{\sigma^2 \beta_c}{\beta_c + \beta_s}.$$

*Variance of the target:*  $\text{Var}(x^*(0)) = \frac{\sigma^2 \beta_c^2}{4} I$ , where  $I \triangleq \iint e^{-\beta_c(|u|+|v|) - \beta_s|u-v|} du dv$ .

To evaluate  $I$ , define the inner integral  $h(u) \triangleq \int_{\mathbb{R}} e^{-\beta_c|v|} e^{-\beta_s|u-v|} dv$ . Then  $h$  is even, so  $I = 2 \int_0^\infty e^{-\beta_c u} h(u) du$ . For  $u \geq 0$ , split the  $v$ -integral at 0 and  $u$ :

$$h(u) = \underbrace{\frac{e^{-\beta_s u}}{\beta_c + \beta_s}}_{v < 0} + \underbrace{\frac{e^{-\beta_c u} - e^{-\beta_s u}}{\beta_s - \beta_c}}_{0 \leq v \leq u} + \underbrace{\frac{e^{-\beta_c u}}{\beta_c + \beta_s}}_{v > u}.$$

(The middle term is read as  $u e^{-\beta_c u}$  when  $\beta_s = \beta_c$ .) Multiply by  $e^{-\beta_c u}$  and integrate over  $u \geq 0$  term by term:

$$\frac{1}{(\beta_c + \beta_s)^2}, \quad \frac{1}{\beta_s - \beta_c} \left( \frac{1}{2\beta_c} - \frac{1}{\beta_c + \beta_s} \right) = \frac{1}{2\beta_c(\beta_c + \beta_s)}, \quad \frac{1}{2\beta_c(\beta_c + \beta_s)}.$$

Summing and doubling,

$$I = 2 \left[ \frac{1}{(\beta_c + \beta_s)^2} + \frac{1}{\beta_c(\beta_c + \beta_s)} \right] = \frac{2(2\beta_c + \beta_s)}{\beta_c(\beta_c + \beta_s)^2}, \quad \text{Var}(x^*(0)) = \frac{\sigma^2 \beta_c (2\beta_c + \beta_s)}{2(\beta_c + \beta_s)^2}. \quad (\text{S1})$$

*Combine.* With  $\text{Var}(\theta(0)) = \sigma^2$ ,

$$\text{Corr}^2 = \frac{(\sigma^2 \beta_c / (\beta_c + \beta_s))^2}{\sigma^2 \cdot \sigma^2 \beta_c (2\beta_c + \beta_s) / (2(\beta_c + \beta_s)^2)} = \frac{2\beta_c}{2\beta_c + \beta_s}, \quad \eta_S(0) = \frac{\beta_s}{2\beta_c + \beta_s} = \frac{\ell_c}{\ell_c + 2\ell_s}.$$

□

### S3 Numerical reproducibility details

This section records settings, estimators, grids, normalization conventions, and diagnostics for the six experiments in Section 6 of the main paper, which reports the findings and their interpretation. Each calculation evaluates architecture regret under the corresponding information structure: a common delayed snapshot in Experiment 1, the exact fresh-local rule in Experiment 2, scalar composition in Experiments 3–4, and agentwise Gaussian conditioning with  $Q = I$  in Experiments 5–6. Normalized losses use the analytical open-loop regret  $R_\infty$ ; Experiment 2 instead estimates

its boundary from paired sample means. Pointwise Monte Carlo means have 95% normal intervals  $\bar{L} \pm 1.96s_L/\sqrt{N}$ , with sample standard deviation  $s_L$ . Conditioning uses linear solves rather than explicit matrix inverses.

Table 1: Reference numerical settings. The shared-resource sweep fixes  $q = 1$ ; graph covariances in Experiments 5–6 are scaled to average marginal variance one. Quantities not being swept retain the experiment-specific values in the configuration files.

| Experiment            | principal sweep                               | fixed setting/size                          | evaluation       |
|-----------------------|-----------------------------------------------|---------------------------------------------|------------------|
| 1. Temporal pairs     | $\tau/T \in [0, 3]$ (25 points)               | A–D; $n = 8, 20, 50, 32$                    | 20,000/point     |
| 2. Local–global       | 9 $\gamma/q$ values in $[0, 10]$              | $n = 5, 10, 25, 100$ ; $q = 1$              | 30,000/setting   |
| 3. Scalar radius      | $r/\ell_c \in [0, 2]$ (1,001 points)          | 3 regimes; $D/\ell_c = 2$                   | 50,000/point     |
| 4. Canonical map      | $(vT/\ell_c, \ell_s/\ell_c)$ ; $72 \times 68$ | $r/\ell_c \in [0, 4]$ ; $\Delta r = 0.0016$ | direct scalar    |
| 5. Decision relevance | $\ell_c = 0.7, 2, 6$                          | 64-node ring; $T = 6$                       | 12,000/check     |
| 6. General graphs     | path, ring, grid, geometric                   | 64 nodes; $T = 5$                           | exact covariance |

**1. Temporal scaling.** At each of 25 equally spaced  $\rho = \tau/T \in [0, 3]$ , each system uses 20,000 independent stationary OU pairs:  $\theta_t = e^{-\rho}\theta_{t-\tau} + \sqrt{1 - e^{-2\rho}}\varepsilon$ , where  $\theta_{t-\tau}$  and  $\varepsilon$  are independent  $\mathcal{N}(0, \Sigma_S)$  draws. Systems A–D have dimensions 8, 20, 50, and 32 and respectively identity, Toeplitz, ring-Laplacian, and geometric-graph covariances; their matrices are archived in `numerics/results/raw/exp01_system_matrices.npz`. The known optimal delayed-snapshot action is evaluated in each system’s  $Q$ -metric; no time stepping or burn-in is needed.

**2. Fresh-local/stale-global crossover.** We fix  $q = 1$  and use  $n \in \{5, 10, 25, 100\}$ . The nine coupling ratios are  $\gamma/q \in \{0, 0.05, 0.1, 0.2, 0.5, 1, 2, 5, 10\}$ . At each setting, 30,000 independent current-state draws give paired open-loop and fresh-local losses, using  $u_i = \theta_i/(q + \gamma)$ . Writing their means as  $o = \hat{R}_\infty$  and  $l = \hat{R}_{\text{loc}}$ , the estimator is  $\hat{\rho}^* = \frac{1}{2} \log[o/(o - l)]$ . Its 95% delta-method interval is  $\hat{\rho}^* \pm 1.96\sqrt{g^\top Cg/N}$ , where  $C$  is the sample covariance of the paired losses and

$$g = \left( -\frac{l}{2o(o-l)}, \frac{1}{2(o-l)} \right)^\top.$$

The paired covariance is retained;  $o - l \leq 0$  is rejected rather than clipped. The zero-coupling boundary is zero and is omitted from the logarithmic plot.

**3. Three radius regimes.** The scalar calculation uses  $\eta_S(r) = \eta_0 e^{-2r/\ell_c}$ ,  $\tau(r) = r/v$ ,  $\ell_c = 1$ , and  $D = 2$ , with  $(\eta_0, vT) = (0.25, 0.2), (0.7, 4), (0.9, 100)$ . The radius grid has spacing 0.002. At each point, 50,000 pairs of independent standard normals are scaled by the square roots of the normalized components  $R_T/R_\infty$  and  $R_S/R_\infty$  in (73)–(74), then added and squared. This checks scalar variance composition; it does not simulate a spatial field.

**4. Canonical regime map.** The logarithmic parameter grid has  $72 \times 68$  points over  $vT/\ell_c \in [0.1, 20]$  and  $\ell_s/\ell_c \in [0.05, 5]$ . At every point, direct scalar evaluation of (65) uses the same radius grid  $r/\ell_c = 0.0016j$ ,  $j = 0, \dots, 2500$ , without an adaptive radius range or covariance simulation. The maximum grid-versus-closed-form error is  $8.00 \times 10^{-4}$ ; five zero/positive classifications disagree adjacent to the threshold, where the continuous optimum is below the first positive grid point.

**5. Decision relevance.** The graph and covariance are fixed on a 64-node ring, with  $T = 6$  and latency 0.12 per hop. For  $\ell_c \in \{0.7, 2, 6\}$  the operator is  $K_{ij} = e^{-d_G(i,j)/\ell_c} / \|e^{-d_G(i,\cdot)/\ell_c}\|_2$ . With  $Q = I$ , exact Gaussian conditioning gives spatial omission; 12,000-sample checks evaluate selected radii. Each operator has its own analytical  $R_\infty = \frac{1}{2} \text{tr}(K \Sigma_S K^\top)$ . Raw state correlation is computed separately from the fixed covariance.

**6. Finite graphs.** One 64-node path, ring, grid, and geometric graph is used, with geometric-graph seed 20260839. For both graph experiments,  $\Sigma_S \propto (\kappa_s^2 I + L_G)^{-\nu}$  is scaled to average marginal variance one;  $(\kappa_s, \nu) = (0.75, 1.5)$  in Experiment 5 and  $(0.8, 1.5)$  here. The reference setting uses  $Q = I$ ,  $T = 5$ ,  $\ell_c = 2$ , and latency 0.12 per hop. Exact Gaussian conditioning evaluates every integer radius through the graph diameter, with no canonical-line fit or graph-ensemble averaging. Neighbor regret differences and parameter sweeps are archived in `numerics/results/processed/exp06_general_graphs.csv` and `numerics/results/processed/exp06_comparative_statics.csv`.

**Reproduction and audit.** The public TINA repository contains `numerics/config/experiment_01.yaml` through `experiment_06.yaml`, with seeds 20260823 through 20260828, and run metadata in `numerics/results/metadata/`. The archive includes selected raw arrays, not every random draw. `docs/numerical_method.md` and `docs/experiment_parameters.md` specify system construction, conditioning safeguards, sweeps, and environment versions; `numerics/README.md` gives reproduction commands.