

A Theory of Information Architecture for Networked Decisions: Freshness, Locality, and Coordination

Scott Moeller

Independent Researcher, Portsmouth, RI, USA

`scott.h.moeller@gmail.com`

Bhaskar Krishnamachari

University of Southern California

`bkrishna@usc.edu`

September 2026

Abstract

Networked systems face a tradeoff between the scope of the information behind a decision and its freshness: a broader view of the system supports better coordination, but assembling and communicating it takes time, so it arrives older. We study this tradeoff for a team of agents that repeatedly choose actions to minimize a shared quadratic cost driven by an environment that evolves on its own, unaffected by the agents' actions. An information architecture specifies what each agent observes, from where, and with what delay; we measure an architecture by the cost it loses relative to a decision made with complete, current information. We first compare fresh local observations with a complete but delayed global view. For affine full-information decisions in a common-rate Gauss–Markov environment, this comparison reduces to a closed-form threshold on the ratio of delay to coherence time. We then study intermediate architectures in which each agent acts on a time-aligned, and therefore older, snapshot of a wider neighborhood. An interior optimal neighborhood radius satisfies a balance between the marginal value of added scope and the marginal cost of lost freshness. In a canonical spatial model, this radius is set by the spatial-correlation, decision-relevance, and temporal-propagation lengths. Throughout, architecture performance is governed by the predictability of the optimal decision rather than of the raw state.

1 Introduction

Many networked systems must repeatedly make coupled decisions using information that is distributed across space and changes over time. A wireless transmitter may know its current local channel state but not the current interference conditions elsewhere in the network; an edge server may observe its own workload immediately while a system-wide view is available only after telemetry has been collected and disseminated; and a distributed sensing system may have fresh measurements from nearby sensors while observations from distant sensors arrive with greater latency. In each case, broad information can improve coordination, but obtaining it takes time. The resulting design choice is not simply between centralized and distributed control, but between *information architectures* that differ simultaneously in spatial scope and temporal freshness.

This tension appears in several literatures under different performance models. Work on stale information in distributed systems shows that old global state can lose much of its value [1], and Age of Information formalizes freshness as a system resource [2]. Distributed optimization studies computation under communication constraints [3], organizational economics studies adaptation to local information versus coordination [4], and networked-control work examines how communication scope, topology, and propagation delay interact with closed-loop performance.

Distributed-control work establishes controller localization and models finite-speed or distance-dependent communication [5–8]. Most directly, Ballotta, Jovanović, and Schenato show that scope-dependent delay can make sparse feedback outperform all-to-all control [9]; Section 7.2 develops the comparison with this literature.

The distinction pursued here is the decision problem and the resulting analytical object. The environment evolves exogenously, and each epoch is a static team decision. Dynamic feedback control, in which the controller changes future plant state, lies outside this setting. For a fixed information architecture, performance is the Q -weighted loss in reproducing the current full-information decision, where Q is the cost’s Hessian, defined in Section 2.1. We then vary spatial scope and information age jointly. Under a model in which every component of the environment decorrelates at the same exponential rate (the common-rate model), this prediction-theoretic formulation yields an exact composition identity for spatial omission and temporal staleness, a fresh-local versus stale-global crossover in terms of decision-relevant predictability, and a marginal-balance characterization of the synchronized-snapshot radius. In the canonical field model, these quantities produce an explicit radius law involving temporal coherence, spatial correlation, decision-relevance length, and propagation speed.

This paper develops a theory for this tradeoff. We consider a collection of agents operating in an exogenously evolving stochastic environment $\theta_t = (\theta_{1,t}, \dots, \theta_{n,t})$. At each decision epoch the agents select a joint action $x_t = (x_{1,t}, \dots, x_{n,t})$ that incurs a common cost $f(x_t, \theta_t)$. An *information architecture* specifies the information available to each agent when this decision is made. Thus a fresh-local architecture may allow agent i to condition on the current $\theta_{i,t}$, a neighborhood architecture may provide the states of agents within a given spatial radius, and a global architecture may provide the entire state vector only after a delay τ . Each of these architectures uses a synchronized snapshot of current or delayed state. More generally, an architecture specifies *who knows what, from where, and at what age*.

Our analysis uses the classical fixed-information framework of static team decision theory initiated by Radner [10]: a static team has multiple decision makers sharing one objective, each acting on its own information, whose actions do not affect what anyone later observes. In the quadratic model considered here, whose Hessian Q is constant and state-independent, completing the square reduces optimization under any fixed information architecture to a Hilbert-space approximation problem: the team-optimal policy under any fixed architecture is the Q -orthogonal projection of the full-information action, and architecture regret is the squared projection distance (Section 2.4). We study an outer design problem: comparison and selection within a structured family in which information scope and age vary jointly. Classical team and information-structure work has also treated information and organizational networks as design objects [11, 12]. The narrower question pursued here is how scope-dependent age changes the value of a synchronized-snapshot radius family when information is evaluated through prediction error of the full-information decision.

Our first result answers the two extreme points of this tradeoff. We compare a *fresh-local* architecture, in which each agent observes its current local state, against a *stale-global* architecture, in which every agent has access to the complete system state with delay τ . In general, the loss from staleness is governed by the prediction error of the current decision-relevant state from information τ units old. For a Gauss–Markov environment with temporal coherence time T , and for an affine full-information decision, stale-global regret grows as $1 - e^{-2\tau/T}$ toward the open-loop regret. Fresh-local information is preferred once this temporal loss exceeds the share of decision-relevant variation not captured locally. In a canonical shared-resource quadratic model, where τ is the global-information delay, T is the temporal coherence time, q is local stiffness, and γ is coordination strength, the

large-system threshold is

$$\left(\frac{\tau}{T}\right)^* = \frac{1}{2} \log \left(1 + \frac{\gamma}{q}\right), \quad (1)$$

making explicit how stronger decision coupling increases the amount of staleness that is worth tolerating in exchange for global coordination.

The local–global comparison concerns two pure benchmark regimes. Our second result considers agents embedded in a graph or spatial domain and a synchronized-snapshot family in which each agent bases its decision on a time-aligned neighborhood snapshot of radius r . Increasing r replaces a narrower, fresher snapshot by a broader snapshot of greater age $\tau(r)$. The resulting architecture faces two competing sources of error: a *spatial omission error*, caused by excluding decision-relevant state beyond radius r , and a *temporal staleness error*, caused by the delay required to acquire the broader information.

We characterize this tradeoff using the spatial and temporal predictability of the underlying stochastic field. In a canonical model, the optimal radius is determined jointly by spatial correlation, temporal coherence, the scope–delay relation, and the coupling structure of the decision objective. The result yields comparative statics with direct architectural interpretations: faster temporal variation favors smaller and fresher information radii; faster information propagation supports broader coordination; and stronger long-range decision coupling increases the value of larger information scope. Spatial smoothness determines how rapidly additional spatial observations become redundant and hence how much information radius is needed to approximate global decisions. Under tractable spatio-temporal covariance and propagation models, these effects combine into dimensionless scaling laws for r^* .

The framework separates information architecture from the algorithm used to implement it. It consequently complements canonical distributed-optimization formulations, where the communication structure is specified first and the principal question is how to compute efficiently over it [3]. We study a structured outer comparison over a scope–age family. Similarly, unlike freshness metrics that assign value to an update primarily through its age [2], the value of an observation here depends on how much it changes the downstream decision. This perspective also suggests extensions to heterogeneous information radii, sparse long-range information “shortcuts,” low-dimensional global summaries, and budget-constrained information acquisition.

Our model is restricted to *static* information structures: the stochastic environment may be temporally and spatially correlated, but agents’ current actions do not alter the information subsequently observed by other agents. This boundary is consequential. Once actions influence future observations, they act simultaneously as control actions and implicit signals; Witsenhausen’s counterexample [13] shows that this interaction breaks the projection structure our analysis relies on. This theory is most directly applicable to repeated networked optimization against an exogenously evolving environment, for example, stylized quadratic or locally quadratic models of rate, power, compute, or sensing decisions driven by changing demand, channel, or resource conditions. Fully constrained engineering formulations, controlled queueing, and decentralized Markov decision processes lie beyond this baseline.

In summary, this paper makes two technical contributions and one conceptual contribution:

1. We derive an exact *fresh-local versus stale-global crossover law* for two pure information regimes, expressed through decision-relevant temporal predictability and the share of decision variation captured locally.
2. For a synchronized-snapshot radius family under the common-rate model, we derive an exact spatio-temporal prediction-error composition law and use it to characterize the optimal radius

by a marginal balance between spatial-information gain and freshness loss. In a canonical field model, this yields an explicit scaling law in the spatial-correlation, decision-relevance, and temporal-propagation lengths.

3. We show that, within the analyzed framework, architecture performance is governed by *decision-relevant predictability*, not raw state predictability. The desired architecture depends jointly on environmental statistics, decision sensitivity and coupling, information geometry, and freshness; the communication graph and decision geometry therefore need not coincide.

To situate the contribution precisely: scope-dependent communication delay and optimal architectures of intermediate sparsity both appear in prior networked-control work [9, 14–16]. What is new here is the decision problem and the resulting analytical object: an exogenous environment, a stagewise team decision, and an architecture valued by its prediction error for the full-information decision. This formulation yields the composition identity between spatial omission and temporal staleness, the fresh-local versus stale-global crossover, and the coordination-radius laws that follow.

Section 2 formalizes architectures and regret. Section 3 compares the fresh-local and stale-global endpoints, and Sections 4–5 develop the radius family and its optimal coordination scale. Section 6 reports numerical checks, Section 7 situates the work, and Section 8 concludes.

2 Networked Decisions and Information Architectures

We consider a network of decision-making agents operating in a stochastic environment whose state is distributed across the network and evolves over time. Our formulation separates three distinct objects: the *network geometry*, which defines relationships and distances among agents; the *decision problem*, which determines how their actions and states interact in the objective; and the *information architecture*, which determines what information is available to each agent and with what delay. These three structures need not coincide.

The environment evolves exogenously: agents react to the state but their current actions do not alter the law governing its future evolution. The model therefore describes repeated information-constrained decisions against an exogenous environment. Under the fixed-information static-team formulation, the quadratic model used here has a constant, state-independent Hessian and admits the projection characterization developed below.

Table 1 collects the principal notation used throughout the paper; we introduce each object in context below.

2.1 Network, Environment, and Decision Model

There are n decision-making agents indexed by

$$V = \{1, \dots, n\},$$

represented as the vertices of a graph

$$G = (V, E). \tag{2}$$

The graph provides a notion of network or spatial proximity. We write $d_G(i, j)$ for the graph distance between nodes i and j , and define the radius- r neighborhood of node i as

$$\mathcal{N}_r(i) \triangleq \{j \in V : d_G(i, j) \leq r\}. \tag{3}$$

Depending on the application, G may represent a physical communication network, a geographic neighborhood relation, or another structure governing the cost or latency of obtaining nonlocal information.¹

Let

$$\theta = \{\theta_t\}_{t \in \mathbb{T}}$$

be a stochastic process defined on a probability space $(\Omega, \mathcal{F}, \mathbb{P})$, where $\mathbb{T}$ may be discrete or continuous. At time t , the environment state is

$$\theta_t = (\theta_{1,t}, \dots, \theta_{n,t}) \in \mathbb{R}^m, \quad \theta_{i,t} \in \mathbb{R}^{m_i}, \quad \sum_{i=1}^n m_i = m. \quad (4)$$

The component $\theta_{i,t}$ denotes the state locally associated with node i . Depending on the application, it may represent a local channel condition, workload or demand, sensing quality, resource availability, or another externally evolving quantity relevant to the decision.

For the basic results in this section, we assume that θ_t is stationary and square-integrable:

$$\mathbb{E}\|\theta_t\|^2 < \infty. \quad (5)$$

No independence, Gaussianity, Markov property, or specific form of spatial or temporal correlation is required. More structured stochastic models will be introduced later when we derive explicit architecture laws.

Agent i chooses an action

$$x_{i,t} \in \mathbb{R}^{d_i},$$

and the joint action is

$$x_t = (x_{1,t}, \dots, x_{n,t}) \in \mathbb{R}^d, \quad d = \sum_{i=1}^n d_i. \quad (6)$$

The agents share a common per-stage cost

$$f(x, \theta) = \frac{1}{2}x^\top Qx - b(\theta)^\top x + c(\theta), \quad (7)$$

where $Q \in \mathbb{R}^{d \times d}$ is symmetric and positive definite, $b : \mathbb{R}^m \rightarrow \mathbb{R}^d$ is measurable, and $c : \mathbb{R}^m \rightarrow \mathbb{R}$ is an additive state-dependent term. We assume

$$\mathbb{E}\|b(\theta_t)\|^2 < \infty, \quad \mathbb{E}|c(\theta_t)| < \infty. \quad (8)$$

The matrix Q describes coupling among the agents' actions. If Q is partitioned according to $x = (x_1, \dots, x_n)$, an off-diagonal block Q_{ij} captures direct interaction between the decisions of agents i and j . The mapping $b(\theta)$ provides another form of coupling: the preferred action of agent i may depend on states associated with other agents.

We emphasize that this decision coupling is distinct from the graph G . The graph describes network proximity and information propagation, whereas Q and $b(\cdot)$ determine which states and actions are relevant to one another in the objective. Nearby agents need not be strongly coupled, and strong decision coupling may exist between distant nodes.

¹The graph model is adopted for concreteness. The framework can more generally be formulated for agents embedded in a metric space, or for any collection of agents equipped with a meaningful notion of neighborhoods and information-propagation cost.

If the complete current state θ_t is available without information constraints, the unique optimal joint action is

$$x_t^* \triangleq x^*(\theta_t) = Q^{-1}b(\theta_t). \quad (9)$$

We call x_t^* the *clairvoyant* or *full-information* decision.

For the affine specializations used to obtain closed forms, we write

$$b(\theta) = B\theta + b_0, \quad B \in \mathbb{R}^{d \times m}, \quad b_0 \in \mathbb{R}^d, \quad K \triangleq Q^{-1}B \in \mathbb{R}^{d \times m}. \quad (10)$$

The matrix B maps state into the linear term of the objective, while K is the resulting decision-sensitivity operator. The general projection results do not require this affine form.

Completing the square in (7) gives

$$f(x, \theta) - f(x^*(\theta), \theta) = \frac{1}{2} (x - x^*(\theta))^\top Q (x - x^*(\theta)). \quad (11)$$

Hence, for the quadratic model, excess decision cost is exactly a weighted squared error in reproducing the full-information action.

2.2 Information Architectures

An *information architecture* specifies what information is available to each agent when its decision is made. At a fixed decision epoch, let

$$\mathcal{G}_i \subseteq \mathcal{F}$$

denote the σ -algebra representing the information available to agent i . An information architecture is the tuple

$$\mathcal{A} = (\mathcal{G}_1, \dots, \mathcal{G}_n). \quad (12)$$

A decision rule for agent i is admissible only if it is measurable with respect to $\mathcal{G}_i$.

This abstraction accommodates information patterns that differ in spatial scope, temporal freshness, and degree of aggregation.

Fresh-local information. Agent i observes its own current state:

$$\mathcal{G}_{i,t}^{\text{loc}} = \sigma(\theta_{i,t}). \quad (13)$$

This architecture has minimal spatial scope and no imposed information delay.

Stale-global information. Every agent has access to the complete state snapshot at time $t - \tau$:

$$\mathcal{G}_{i,t}^{\text{glob}}(\tau) = \sigma(\theta_{t-\tau}), \quad i = 1, \dots, n. \quad (14)$$

This architecture has maximal spatial scope but potentially substantial staleness.

Radius- r information. More generally, agent i may obtain state information from nodes within graph distance r :

$$\mathcal{G}_{i,t}^{(r)} = \sigma(\theta_{j,t-\tau(r)} : j \in \mathcal{N}_r(i)). \quad (15)$$

The radius family studied below is a synchronized-snapshot architecture. At radius r , the decision is formed from a time-aligned neighborhood snapshot whose age is $\tau(r)$; increasing r replaces, rather than augments, the fresher narrow snapshot. This restriction models applications requiring

temporal consistency or a common decision epoch. If fresh local and delayed remote information can instead be freely combined, the resulting hybrid architecture contains more information and weakly dominates either source alone; such mixed-age architectures are outside the principal family analyzed here.

A closely related common-delay-by-scope abstraction appears in Ballotta, Jovanović, and Schenato [9]; see Section 7.2.

Here $\tau(r)$ denotes the latency required to acquire information over radius r . We focus on systems for which

$$r_2 \geq r_1 \implies \tau(r_2) \geq \tau(r_1), \quad (16)$$

so that broader information is systematically less fresh.

With $\tau(0) = 0$, the synchronized-snapshot radius family interpolates between its fresh-local and stale-global endpoints by definition. At the smallest radius, each decision relies on a narrow, rapidly available snapshot. As r increases, that snapshot is replaced by a broader but older view. When r reaches the diameter of a finite connected graph, (15) is the stale-global snapshot in (14).

Local information plus a global summary. An architecture need not transport raw remote state. Agent i may instead combine fresh-local information with a low-dimensional statistic

$$z_t = h(\theta_t)$$

of the global state:

$$\mathcal{G}_{i,t}^{\text{hyb}} = \sigma(\theta_{i,t}) \vee \sigma(z_{t-\tau_z}). \quad (17)$$

Examples include congestion prices, aggregate load indicators, or other summaries intended to communicate the globally decision-relevant portion of the state. The hybrid always contains the fresh-local information set. It dominates the stale-global benchmark only if the delayed summary preserves all delayed global information; an arbitrary low-dimensional summary need not.

For a given architecture $\mathcal{A}$, define the admissible joint-policy set

$$\mathcal{S}(\mathcal{A}) \triangleq \{u = (u_1, \dots, u_n) : u_i \in L^2, u_i \text{ is } \mathcal{G}_i\text{-measurable, } i = 1, \dots, n\}. \quad (18)$$

Thus an information architecture constrains the information on which each decision may depend; it does not prescribe a specific algorithm for computing that decision.

The sets $\mathcal{G}_i$ are exogenously specified: current actions neither change the law of θ_t nor other agents' information, as discussed in Section 1.

2.3 Architecture Regret

We evaluate an architecture by the best expected performance achievable under its information restrictions. Define

$$J(\mathcal{A}) \triangleq \inf_{u \in \mathcal{S}(\mathcal{A})} \mathbb{E}[f(u, \theta_t)], \quad (19)$$

and let

$$J^* \triangleq \mathbb{E}[f(x_t^*, \theta_t)] \quad (20)$$

denote the expected full-information cost.

The *architecture regret* is

$$R(\mathcal{A}) \triangleq J(\mathcal{A}) - J^*. \quad (21)$$

Here “regret” denotes a static expected performance gap after optimizing over all policies admissible under the architecture, distinct from cumulative regret in sequential decision making or online learning.

Because the environment is stationary, this expected per-stage regret is independent of the particular decision epoch, and the expected finite-horizon average equals the same one-stage expectation. Almost-sure convergence of sample-path time averages additionally requires ergodicity.

At this stage, $R(\mathcal{A})$ measures only the decision-quality consequence of an information restriction. We do not separately charge for communication, sensing, or computation. The physical cost of obtaining broader information enters through the feasible architecture and, in particular, through the scope–latency relation $\tau(r)$.

If two architectures $\mathcal{A}$ and $\mathcal{A}'$ satisfy

$$\mathcal{G}_i \subseteq \mathcal{G}'_i, \quad i = 1, \dots, n, \quad (22)$$

then every policy feasible under $\mathcal{A}$ is also feasible under $\mathcal{A}'$, and therefore

$$R(\mathcal{A}') \leq R(\mathcal{A}). \quad (23)$$

Thus additional information cannot hurt when it is available with the same freshness. The interesting architectural tradeoff arises because increasing spatial scope generally also increases information age.

2.4 Fixed-Architecture Quadratic Projection

The classical fixed-information static-team formulation supplies coupled person-by-person optimality conditions [10]. In this quadratic model, completing the square turns those conditions into the projection characterization below. We use this fixed-architecture result as the inner optimization primitive for the outer scope–age comparison. Related affine-gain projection formulations appear in Krainak, Speyer, and Marcus [17].

Let

$$\mathcal{H} = L^2(\Omega, \mathcal{F}, \mathbb{P}; \mathbb{R}^d) \quad (24)$$

and equip $\mathcal{H}$ with the weighted inner product

$$\langle u, v \rangle_Q \triangleq \mathbb{E} \left[u^\top Q v \right], \quad \|u\|_Q^2 \triangleq \langle u, u \rangle_Q. \quad (25)$$

Since $Q \succ 0$, the induced norm is equivalent to the ordinary L^2 norm.

Lemma 1 (Fixed-architecture quadratic projection; Radner-type specialization). *For any static information architecture $\mathcal{A}$, the admissible policy set $\mathcal{S}(\mathcal{A})$ defined in (18) is a closed linear subspace of $\mathcal{H}$. Under the quadratic cost (7), the unique optimal policy implementable under $\mathcal{A}$ is*

$$u_{\mathcal{A}}^* = \Pi_{\mathcal{S}(\mathcal{A})} x_t^*, \quad (26)$$

where $\Pi_{\mathcal{S}(\mathcal{A})}$ denotes orthogonal projection with respect to (25). Consequently,

$$R(\mathcal{A}) = \frac{1}{2} \|x_t^* - \Pi_{\mathcal{S}(\mathcal{A})} x_t^*\|_Q^2. \quad (27)$$

This identity specializes the classical static-team formulation [10] to the quadratic model used here.

Proof. Linearity of $\mathcal{S}(\mathcal{A})$ follows because $\mathcal{G}_i$ -measurability is preserved under linear combinations. Closedness follows because an L^2 limit of $\mathcal{G}_i$ -measurable random variables admits a $\mathcal{G}_i$ -measurable version.

For any admissible policy u , (11) gives

$$\begin{aligned}\mathbb{E}[f(u, \theta_t) - f(x_t^*, \theta_t)] &= \frac{1}{2} \mathbb{E}[(u - x_t^*)^\top Q(u - x_t^*)] \\ &= \frac{1}{2} \|u - x_t^*\|_Q^2.\end{aligned}\tag{28}$$

Minimizing this expression over the closed subspace $\mathcal{S}(\mathcal{A})$ is the standard Hilbert-space projection problem, yielding (26) and (27). $\square$

Corollary 1 (Coupled conditional normal equations). *The unique team optimum in Lemma 1 satisfies*

$$\boxed{\mathbb{E}[(Qu_A^* - b(\theta_t))_i \mid \mathcal{G}_i] = 0, \quad i = 1, \dots, n.}\tag{29}$$

With Q partitioned into action blocks, this is equivalently

$$Q_{ii}u_i^* + \sum_{j \neq i} Q_{ij} \mathbb{E}[u_j^* \mid \mathcal{G}_i] = \mathbb{E}[b_i(\theta_t) \mid \mathcal{G}_i].\tag{30}$$

These are the coupled person-by-person stationarity equations associated with the classical static-team formulation [10]. Strict convexity makes them sufficient for the unique team optimum here. With heterogeneous information and off-diagonal Q , one generally does not have $u_i^ = \mathbb{E}[x_i^* \mid \mathcal{G}_i]$. When all components share a common information sigma-algebra, deterministic Q makes the joint solution the ordinary vector conditional expectation.*

Remark 1 (Scope of the projection identity). *The fixed-architecture projection identity requires square integrability, a deterministic positive-definite matrix Q , unconstrained Euclidean actions, and a closed linear space of admissible policies. It does not require Gaussianity, an affine map $b(\theta)$, Markov dynamics, temporal stationarity, or independent observations. Those stronger assumptions enter only in later closed-form prediction and composition results.*

Lemma 1 turns an information architecture into a geometric object. The full-information policy x_t^* specifies what the system would ideally do if the current global state were known. The architecture restricts the system to the policy subspace $\mathcal{S}(\mathcal{A})$, and its regret is precisely the squared distance from the ideal policy to the closest rule implementable using the available information.

This interpretation also identifies the relevant notion of environmental predictability. An architecture need not reconstruct the complete state θ_t . It need only provide enough information to predict the components that affect x_t^* . Section 4.4 develops the corresponding notion of decision-relevant predictability.

The radius-dependent architecture in (15) makes the central tradeoff clear. Increasing r provides each agent with a broader view of the network and, if freshness were fixed, could only improve performance. In a physical network, however, larger r generally also increases $\tau(r)$. The architecture family

$$\{\mathcal{A}_{r, \tau(r)}\}_{r \geq 0}\tag{31}$$

therefore trades spatial information against temporal freshness.

We first study the two endpoints of this tradeoff: fresh-local information and stale-global information. We then ask the more general architecture-design question: what information radius

minimizes regret when the value of broader spatial knowledge must be balanced against the additional delay required to obtain it?

The notation admits a direct networked interpretation through illustrative mappings. The component θ_i may represent an externally evolving local condition, for example, channel quality, demand, workload intensity, sensing conditions, or resource availability, while x_i is a corresponding continuous decision such as rate, power, compute allocation, or sensing effort. The matrices Q and B , or equivalently the decision-sensitivity operator $K = Q^{-1}B$, encode how other agents' decisions and remote state affect the desired action; this coupling structure need not coincide with the physical or information graph over which observations travel. The essential boundary is exogeneity. An external arrival or workload process may be modeled as part of θ , whereas a queue length whose evolution depends on earlier service decisions is not exogenous in the sense required here.

Table 1: Core notation. Quantities labeled as shares are normalized by R_∞ .

Symbol	Meaning	Symbol	Meaning
n	number of agents	$G = (V, E)$	network or geometry graph
θ_t	exogenous environment state	x_t	joint action
Q	positive-definite action-coupling matrix	B	affine state-to-objective map
$K = Q^{-1}B$	decision-sensitivity operator	x_t^*	full-information decision
$\mathcal{A}$	information architecture	$R(\mathcal{A})$	architecture regret; includes R_{loc} and $R_{\text{glob}}(\tau)$
R_∞	open-loop regret	$\eta_S(0)$	fresh-local omission share
$\eta_T(\tau)$	temporal unpredictability	$\eta_S(r)$	radius- r zero-delay spatial omission
$\eta_{ST}(r, \tau)$	normalized joint spatio-temporal regret	T	temporal coherence time
$\tau(r)$	information latency at radius r	v	effective propagation speed
ℓ_s	spatial correlation length	ℓ_c	decision-relevance length
$L_T = vT$	temporal propagation length	r^*	optimal synchronized-snapshot radius

3 Fresh-Local versus Stale-Global Information

We begin with the two endpoints of the freshness–scope tradeoff introduced in Section 2. A *fresh-local* architecture gives each agent immediate access to its own state but no current information about remote states. A *stale-global* architecture gives every agent complete system-wide information, but only after a delay τ .

This section compares two pure regimes; as noted in Section 2.2, an architecture free to combine both information sources would weakly dominate either one.

If both architectures had the same delay, global information could only help: the corresponding information sets would contain the local ones. The comparison becomes nontrivial precisely because spatial scope and freshness move in opposite directions. This section characterizes that tradeoff first for an arbitrary stationary environment through a temporal prediction-error function, and then obtains an exact crossover law under a Gauss–Markov model.

3.1 Two Benchmark Architectures

At decision time t , the *fresh-local* architecture is

$$\mathcal{A}_{\text{loc}} = (\mathcal{G}_{1,t}^{\text{loc}}, \dots, \mathcal{G}_{n,t}^{\text{loc}}), \quad \mathcal{G}_{i,t}^{\text{loc}} = \sigma(\theta_{i,t}). \quad (32)$$

Its regret is

$$R_{\text{loc}} \triangleq R(\mathcal{A}_{\text{loc}}). \quad (33)$$

Because this information is current, R_{loc} does not depend on the global information delay τ . Its magnitude instead reflects how much of the full-information decision can be inferred from local information alone.

The *stale-global* architecture at delay τ is

$$\mathcal{A}_{\text{glob}}(\tau) = (\mathcal{G}_t^\tau, \dots, \mathcal{G}_t^\tau), \quad \mathcal{G}_t^\tau \triangleq \sigma(\theta_{t-\tau}). \quad (34)$$

All agents therefore share the same complete but delayed snapshot of the environment. We denote its regret by

$$R_{\text{glob}}(\tau) \triangleq R(\mathcal{A}_{\text{glob}}(\tau)). \quad (35)$$

On a finite connected graph of diameter D , these are the $r = 0$ and $r = D$ members of the synchronized-snapshot family in Section 4, with delays zero and τ , respectively.

For reference, define also the *open-loop* architecture, whose decision is the best constant, state-independent action. Its optimal action is $\mathbb{E}[x_t^*]$, and its regret is

$$R_\infty \triangleq \frac{1}{2} \|x_t^* - \mathbb{E}[x_t^*]\|_Q^2. \quad (36)$$

Throughout the normalized comparisons below we assume $R_\infty > 0$, excluding the trivial case in which the clairvoyant decision is deterministic.

Since all agents share the global snapshot, stale-global regret is one-half the minimum Q -weighted mean-square error of predicting x_t^* from $\theta_{t-\tau}$ (Corollary 1). Define the two loss shares as regret ratios:

$$\eta_T(\tau) \triangleq \frac{R_{\text{glob}}(\tau)}{R_\infty}, \quad 0 \leq \eta_T(\tau) \leq 1, \quad (37)$$

and

$$\eta_S(0) \triangleq \frac{R_{\text{loc}}}{R_\infty}, \quad 0 \leq \eta_S(0) \leq 1. \quad (38)$$

The quantity $\eta_S(0)$ measures what is lost by restricting information spatially, while $\eta_T(\tau)$ measures what is lost by allowing global information to age. The captured local share is $1 - \eta_S(0)$. At zero delay, $\eta_T(0) = 0$ because the complete current state determines x_t^* . If remote snapshots become uninformative in the mean-square sense that $\mathbb{E}[x_t^* | \theta_{t-\tau}] \rightarrow \mathbb{E}[x_t^*]$ in L^2 , then $\eta_T(\tau) \rightarrow 1$; this holds, for example, under strong mixing. Snapshots at different delays are not generally nested. For a Markov environment, the prediction-error data-processing inequality makes η_T nondecreasing; the OU formula below shows this explicitly.

Dividing by $R_\infty > 0$ gives the crossover observation

$$R_{\text{loc}} < R_{\text{glob}}(\tau) \iff \eta_T(\tau) > \eta_S(0). \quad (39)$$

Fresh-local information is preferable precisely when the temporal information lost by waiting for a global view exceeds the decision-relevant information unavailable locally.

3.2 Gauss–Markov Temporal Model

We now specialize the temporal unpredictability function to obtain a closed form. Suppose the environment follows the stationary multivariate Ornstein–Uhlenbeck process

$$d\theta_t = -\frac{1}{T} (\theta_t - \bar{\theta}) dt + \sqrt{\frac{2}{T}} \Sigma_\infty^{1/2} dW_t, \quad (40)$$

where $T > 0$ is the temporal coherence time, $\bar{\theta}$ is the stationary mean, and Σ_∞ is the stationary covariance matrix. The process may exhibit arbitrary instantaneous cross-correlation among agents through Σ_∞ ; the simplifying assumption is that all temporal modes share the same decay time T .

Assume further that

$$b(\theta) = B\theta + b_0, \quad (41)$$

so that the full-information decision is affine:

$$x^*(\theta) = Q^{-1}B\theta + Q^{-1}b_0. \quad (42)$$

Let

$$\rho \triangleq \frac{\tau}{T} \quad (43)$$

denote the dimensionless staleness ratio.

The OU transition law [18, eqs. (8)–(10), (14)] gives the innovation decomposition

$$\theta_t - \bar{\theta} = e^{-\rho}(\theta_{t-\tau} - \bar{\theta}) + \varepsilon_{t,\tau}, \quad \mathbb{E}[\varepsilon_{t,\tau} \mid \theta_{t-\tau}] = 0. \quad (44)$$

For the OU process, the innovation is Gaussian and independent of the past. Writing the centered full-information decision as

$$\bar{x}^* \triangleq \mathbb{E}[x_t^*], \quad X_t \triangleq x_t^* - \bar{x}^*, \quad (45)$$

the affine decision inherits the same split:

$$X_t = e^{-\rho}X_{t-\tau} + K\varepsilon_{t,\tau}, \quad K = Q^{-1}B. \quad (46)$$

Because constants are admissible under every architecture, subtracting $\bar{x}^*$ from both the target and the policy leaves regret unchanged. We use the L^2 norm $\|Y\|_Q^2 = \mathbb{E}[Y^\top QY]$ defined in (25).

Lemma 2 (Innovation split). *Under (40)–(41), every square-integrable $\mathbb{R}^d$ -valued function u of $\theta_{t-\tau}$ satisfies*

$$\|X_t - u\|_Q^2 = \|e^{-\rho}X_{t-\tau} - u\|_Q^2 + (1 - e^{-2\rho}) 2R_\infty. \quad (47)$$

Proof. The error is the sum of $e^{-\rho}X_{t-\tau} - u$ and $K\varepsilon_{t,\tau}$. The first term is a function of the old snapshot, so the conditional mean in (44) makes their Q -inner product zero. Applying the same orthogonality with $u = 0$ and using stationarity gives

$$\|K\varepsilon_{t,\tau}\|_Q^2 = \|X_t\|_Q^2 - e^{-2\rho}\|X_{t-\tau}\|_Q^2 = (1 - e^{-2\rho}) 2R_\infty.$$

Adding the two orthogonal error costs proves (47). $\square$

The first term is the error in reproducing the predictable old decision; the second is the fresh innovation that the old snapshot cannot predict. For global information, the first error can be eliminated entirely.

Theorem 1 (Exact stale-global regret). *Under (40)–(41),*

$$\boxed{R_{\text{glob}}(\tau) = \left(1 - e^{-2\tau/T}\right) R_{\infty}}, \quad (48)$$

where

$$R_{\infty} = \frac{1}{2} \text{tr} \left(B^{\top} Q^{-1} B \Sigma_{\infty} \right). \quad (49)$$

Equivalently,

$$\boxed{\eta_T(\tau) = 1 - e^{-2\tau/T}}. \quad (50)$$

Proof. The global snapshot can implement the centered policy $u = e^{-\rho} X_{t-\tau}$, making the first term in Lemma 2 zero. Dividing the remaining term by two gives (48); the trace identity (49) follows from $\text{Cov}(x_t^*) = K \Sigma_{\infty} K^{\top}$. $\square$

Generality of the innovation argument. The proof uses only stationarity, an affine decision, and a common scalar decay factor with a conditionally mean-zero innovation. It therefore also applies to stationary linear AR(1) processes with non-Gaussian innovations: for $\theta_t - \bar{\theta} = a(\theta_{t-1} - \bar{\theta}) + \varepsilon_t$, $0 < a < 1$, independent mean-zero innovations give the same identity at lag k with $e^{-\rho}$ replaced by a^k .

The result has a simple interpretation. When $\tau \ll T$, the environment changes little over the information delay and

$$R_{\text{glob}}(\tau) = 2 \frac{\tau}{T} R_{\infty} + o\left(\frac{\tau}{T}\right). \quad (51)$$

When $\tau \gg T$, the delayed global snapshot becomes essentially uninformative about the current decision and

$$R_{\text{glob}}(\tau) \rightarrow R_{\infty}.$$

Staleness therefore matters relative to the timescale on which decision-relevant state changes. For any fixed $\tau > 0$, the same identity gives $R_{\text{glob}}(\tau) \rightarrow R_{\infty}$ as $T \downarrow 0$ and $R_{\text{glob}}(\tau) \rightarrow 0$ as $T \rightarrow \infty$.

3.3 Fresh-Local versus Stale-Global Crossover

Combining the observation (39) with (50) yields the first main architectural result.

Theorem 2 (Fresh-local versus stale-global crossover). *Under the Gauss–Markov and affine-decision assumptions of Theorem 1, suppose $0 \leq \eta_S(0) < 1$. Fresh-local information strictly outperforms stale-global information if and only if*

$$\boxed{\frac{\tau}{T} > \frac{1}{2} \log \frac{1}{1 - \eta_S(0)}}. \quad (52)$$

Equivalently, defining

$$\rho^* \triangleq \frac{1}{2} \log \frac{1}{1 - \eta_S(0)}, \quad (53)$$

we have

$$R_{\text{loc}} < R_{\text{glob}}(\tau) \iff \rho > \rho^*. \quad (54)$$

For $\eta_S(0) = 1$, define $\rho^* = +\infty$ in the extended-real sense; fresh-local information then never strictly outperforms stale-global information at a finite delay.

Proof. By (39), fresh-local wins exactly when

$$1 - e^{-2\rho} > \eta_S(0).$$

Equivalently,

$$e^{-2\rho} < 1 - \eta_S(0),$$

which gives (52). □

The limiting cases are informative. If

$$\eta_S(0) = 0,$$

fresh-local information is sufficient to reproduce the full-information decision, and the fresh-local architecture dominates for every $\tau > 0$. If

$$\eta_S(0) = 1,$$

local information provides no improvement over open loop, and stale-global information is never strictly worse at any finite delay.

More generally, Theorem 2 identifies two dimensionless determinants of the architecture choice. The staleness ratio τ/T measures the loss of temporal relevance incurred by global information, while $\eta_S(0)$ measures the share of decision-relevant variation omitted locally. Within the comparison of the two pure benchmarks, fresh-local has lower regret precisely when the two loss fractions cross.

3.4 Role of Decision Coupling

The fresh-local omission share $\eta_S(0)$ depends jointly on the spatial statistics of the environment and on the coupling structure of the decision problem. To isolate the role of decision coupling, consider a symmetric shared-resource model with $n \geq 2$ scalar actions,

$$f(x, \theta) = \sum_{i=1}^n \left(\frac{q}{2} x_i^2 - \theta_i x_i \right) + \frac{\gamma}{2} \left(\sum_{i=1}^n x_i \right)^2, \quad q > 0, \gamma \geq 0. \quad (55)$$

Here q determines the local curvature or stiffness of each decision, while γ determines the strength of the shared coordination penalty. In the notation of Section 2,

$$Q = qI + \gamma \mathbf{1}\mathbf{1}^\top, \quad b(\theta) = \theta. \quad (56)$$

Assume that the state components θ_i are independent, mean-zero stationary OU processes with common variance σ^2 and common coherence time T .

The full-information action is

$$x_i^* = \frac{\theta_i}{q} - \frac{\gamma}{q(q + \gamma n)} \sum_{j=1}^n \theta_j. \quad (57)$$

Thus, even though the linear reward $\theta_i x_i$ is local, coupling through the common resource makes agent i 's optimal action depend on the states of all other agents.

Proposition 1 (Local explainability under aggregate coupling). *For the model (55), the optimal fresh-local policy is*

$$u_i^{\text{loc}} = \frac{\theta_i}{q + \gamma}, \quad (58)$$

and

$$R_\infty = \frac{n\sigma^2(q + \gamma(n - 1))}{2q(q + \gamma n)}, \quad (59)$$

$$R_{\text{loc}} = \frac{n\sigma^2\gamma^2(n - 1)}{2q(q + \gamma)(q + \gamma n)}. \quad (60)$$

Consequently, the fresh-local omission share is

$$\eta_S(0) = \frac{\gamma^2(n - 1)}{(q + \gamma)(q + \gamma(n - 1))}. \quad (61)$$

Proof. Let $\mu_j = \mathbb{E}[u_j]$. For $j \neq i$, the policy u_j is a function of $\theta_{j,t}$, which is independent of $\theta_{i,t}$, so

$$\mathbb{E}[u_j \mid \mathcal{G}_{i,t}^{\text{loc}}] = \mathbb{E}[u_j] = \mu_j,$$

while $\theta_{i,t}$ is $\mathcal{G}_{i,t}^{\text{loc}}$ -measurable. The conditional normal equation (30) therefore gives

$$(q + \gamma)u_i + \gamma \sum_{j \neq i} \mu_j - \theta_{i,t} = 0.$$

Taking expectations yields

$$q\mu_i + \gamma \sum_j \mu_j = 0.$$

Summing over i implies $\sum_j \mu_j = 0$, hence every $\mu_i = 0$ and $u_i = \theta_{i,t}/(q + \gamma)$, which proves (58). This argument uses independence, zero means, square integrability, and strict convexity; Gaussianity is not required for the local-policy formula.

The expressions (59) and (60) follow by substituting the full-information and local policies into the quadratic regret expression (27). Substituting them into (38) and simplifying yields (61). $\square$

Combining Proposition 1 with Theorem 2 gives an explicit threshold:

$$\rho^*(\gamma, n) = \frac{1}{2} \log \left[\frac{(q + \gamma)(q + \gamma(n - 1))}{q(q + \gamma n)} \right]. \quad (62)$$

Therefore

$$R_{\text{loc}} < R_{\text{glob}}(\tau) \iff \frac{\tau}{T} > \rho^*(\gamma, n). \quad (63)$$

As $n \rightarrow \infty$,

$$\rho^*(\gamma, n) \longrightarrow \frac{1}{2} \log \left(1 + \frac{\gamma}{q} \right). \quad (64)$$

The local–global architecture choice therefore collapses, in the large-system limit, to a comparison between two dimensionless quantities:

$$\underbrace{\frac{\tau}{T}}_{\text{information staleness}} \quad \text{and} \quad \underbrace{\frac{1}{2} \log \left(1 + \frac{\gamma}{q} \right)}_{\text{value of coordination}}. \quad (65)$$

When $\gamma = 0$, the decisions decouple and $\eta_S(0) = 0$: current local information is sufficient, so any positive global delay makes the fresh-local architecture preferable. As γ increases, each agent’s optimal action depends more strongly on remote states, $\eta_S(0)$ increases, and the crossover moves to larger τ/T . Thus stronger coordination coupling makes the system willing to tolerate increasingly stale-global information before abandoning global coordination in favor of fresh-local decisions.

The result provides the first endpoint characterization of the broader freshness–scope problem. The next sections move beyond the binary local–global comparison by allowing the information radius itself to vary, and ask how spatial predictability and temporal staleness jointly determine the optimal coordination scale.

4 Spatial and Temporal Predictability

We now introduce intermediate architectures in which each agent observes a synchronized snapshot within radius r . Temporal predictability determines the freshness loss, while decision-relevant spatial predictability determines the omission loss.

4.1 Spatial Structure of the Environment

We first describe the spatial statistics that determine what nearby observations reveal about remote state.

For simplicity of exposition, first suppose that each node has a scalar local state, so that

$$\theta_t = (\theta_{1,t}, \dots, \theta_{n,t})^\top.$$

The vector-valued case follows by replacing scalar covariances with block covariances.

Let

$$\bar{\theta} \triangleq \mathbb{E}[\theta_t], \quad \Sigma_S \triangleq \text{Cov}(\theta_t) \succeq 0 \quad (66)$$

denote the stationary mean and spatial covariance. The entry $(\Sigma_S)_{ij}$ measures the instantaneous statistical dependence between the states associated with nodes i and j .

On a path, line, or Euclidean spatial domain, a canonical covariance model is

$$\text{Cov}(\theta_{i,t}, \theta_{j,t}) = \sigma^2 \exp\left(-\frac{d_G(i, j)}{\ell_s}\right), \quad (67)$$

where $\ell_s > 0$ is a spatial correlation length. Larger ℓ_s means that states remain strongly correlated over greater network distance. In one spatial dimension, (67) is the exponential, or Ornstein–Uhlenbeck, covariance model [19].

4.2 Temporal Structure

We use the common-rate model (40) with $\Sigma_\infty = \Sigma_S$. Its stationary space-time covariance is

$$\text{Cov}(\theta_t, \theta_s) = e^{-|t-s|/T} \Sigma_S. \quad (68)$$

Thus Σ_S specifies instantaneous spatial dependence and T specifies a common temporal coherence time; general nonseparable models need not have this factorization [20].

4.3 Snapshot Architectures

For radius r , define the zero-delay information available to agent i at time t as

$$\mathcal{I}_{i,t}^{(r)} \triangleq \sigma(\theta_{j,t} : j \in \mathcal{N}_r(i)). \quad (69)$$

The corresponding zero-delay radius- r architecture is

$$\mathcal{A}_{r,0} \triangleq (\mathcal{I}_{1,t}^{(r)}, \dots, \mathcal{I}_{n,t}^{(r)}). \quad (70)$$

A delayed synchronized-snapshot radius- r architecture provides the same type of information, shifted backward by τ :

$$\mathcal{A}_{r,\tau} \triangleq (\mathcal{I}_{1,t-\tau}^{(r)}, \dots, \mathcal{I}_{n,t-\tau}^{(r)}). \quad (71)$$

Such common-time snapshots arise, for example, when a coordinated optimizer requires a temporally consistent system estimate at a common decision epoch, or when asynchronous measurements cannot be combined without explicit time alignment into a coherent state vector. Define the normalized zero-delay spatial omission function

$$\eta_S(r) \triangleq \frac{R(\mathcal{A}_{r,0})}{R_\infty}. \quad (72)$$

The quantity $\eta_S(r)$ is the fraction of decision-relevant variation that cannot be captured using current information within radius r .

Since zero-delay radius architectures are nested,

$$r_2 \geq r_1 \implies \mathcal{S}(\mathcal{A}_{r_1,0}) \subseteq \mathcal{S}(\mathcal{A}_{r_2,0}), \quad (73)$$

and therefore

$$0 \leq \eta_S(r_2) \leq \eta_S(r_1) \leq 1. \quad (74)$$

If radius zero observes precisely the local current component, then

$$\eta_S(0) = \frac{R_{\text{loc}}}{R_\infty}. \quad (75)$$

On a finite connected graph with diameter D , complete current state is available at $r = D$, so

$$\eta_S(D) = 0. \quad (76)$$

4.4 Decision-Relevant Smoothness

Suppose, as in (10), that

$$b(\theta) = B\theta + b_0. \quad (77)$$

Then

$$x_t^\star = K\theta_t + k_0, \quad K \triangleq Q^{-1}B, \quad k_0 \triangleq Q^{-1}b_0. \quad (78)$$

The matrix K is the decision-sensitivity operator: its block K_{ij} describes how the state at node j influences the full-information decision at node i .

The covariance of the clairvoyant decision is

$$\Sigma_x \triangleq \text{Cov}(x_t^\star) = K\Sigma_S K^\top. \quad (79)$$

The function $\eta_S(r)$ therefore depends on the decision operator K and cost metric Q , as well as the state covariance and observation geometry:

$$\boxed{\text{state spatial statistics} \quad + \quad \begin{array}{c} \text{decision sensitivity} \\ \text{and cost geometry} \end{array} \quad + \quad \text{information geometry.}} \quad (80)$$

A spatial correlation length alone does not determine regret. Modes in the null space of K do not affect the desired decision, while uncertainty in strongly amplified modes can dominate it. Experiment 5 illustrates this dependence on decision relevance with the covariance held fixed.

Theorem 3 (Spatio-temporal predictability composition law). *Suppose the environment follows (40) with $\Sigma_\infty = \Sigma_S$, and the full-information decision is affine as in (78). For the snapshot family (71), every radius r and finite delay $\tau \geq 0$ satisfy*

$$\boxed{R(\mathcal{A}_{r,\tau}) = \left(1 - e^{-2\tau/T}\right) R_\infty + e^{-2\tau/T} R(\mathcal{A}_{r,0}).} \quad (81)$$

Equivalently,

$$\boxed{\frac{R(\mathcal{A}_{r,\tau})}{R_\infty} = 1 - e^{-2\tau/T} (1 - \eta_S(r)).} \quad (82)$$

In terms of the temporal unpredictability $\eta_T(\tau) = 1 - e^{-2\tau/T}$,

$$\boxed{\eta_{ST}(r, \tau) = \eta_T(\tau) + (1 - \eta_T(\tau)) \eta_S(r),} \quad (83)$$

where

$$\eta_{ST}(r, \tau) \triangleq \frac{R(\mathcal{A}_{r,\tau})}{R_\infty}.$$

Proof. Subtract $\bar{x}^*$ from the target and each admissible policy, which preserves agentwise measurability because constants are admissible. Every centered-target policy $u \in \mathcal{S}(\mathcal{A}_{r,\tau})$ is a function of $\theta_{t-\tau}$, so Lemma 2 gives

$$\|X_t - u\|_Q^2 = \|e^{-\rho} X_{t-\tau} - u\|_Q^2 + (1 - e^{-2\rho}) 2R_\infty.$$

The substitution $u = e^{-\rho} v$ maps the admissible linear space onto itself and preserves each agent's measurability. Hence the minimum of the first term is $e^{-2\rho}$ times the minimum of $\|X_{t-\tau} - v\|_Q^2$. This is the zero-delay radius- r problem posed at $t - \tau$, whose minimum is $2R(\mathcal{A}_{r,0})$ by stationarity. Dividing by two proves (81) and its normalized forms. $\square$

Theorem 1 is the case $r = D$ on a finite connected graph, where $\eta_S(D) = 0$. The temporal term $(1 - e^{-2\tau/T})R_\infty$ is the innovation that the delayed snapshot cannot predict. The remaining spatial omission is discounted by $e^{-2\tau/T}$, so broader information helps only with the part of the current decision that remains temporally predictable.

Generality of the composition law. The same proof holds under the conditionally mean-zero, common-rate innovation structure of Lemma 2, without Gaussianity. Gaussianity is used below to compute the spatial prediction errors from covariances in the canonical model and Experiments 5–6, where the cost is separable across actions. Coupled Q still requires the team projection of Section 2.4.

5 Optimal Coordination Scale

We now make information radius an architectural design variable. For each r , an agent may base its action on observations available within radius r , but those observations arrive after latency $\tau(r)$. The objective is to select the spatial scope that minimizes architecture regret.

On a graph, admissible radii are generally integers. We first analyze the continuous relaxation $r \in [0, D]$, where D is the maximum allowed information radius. On a finite graph, the exact optimizer is obtained by minimizing over the admissible integer radii. Rounding the continuous optimum to a neighboring integer is justified only when the interpolated regret curve is unimodal.

5.1 Radius Family and Marginal Balance

We now formalize the radius family and the latency law that couples scope to age.

Let

$$\tau : [0, D] \rightarrow [0, \infty) \quad (84)$$

be a nondecreasing information-propagation law satisfying

$$\tau(0) = 0. \quad (85)$$

Architecture $\mathcal{A}_{r, \tau(r)}$ provides each agent with information from a synchronized radius- r snapshot delayed by $\tau(r)$.

By information monotonicity (23), nested information cannot produce a strict interior minimum without an explicit acquisition cost. The synchronized-snapshot family is generally non-nested: increasing radius replaces a fresher narrow snapshot with an older broad one.

Define

$$R(r) \triangleq R(\mathcal{A}_{r, \tau(r)}). \quad (86)$$

By Theorem 3,

$$\boxed{R(r) = R_\infty \left[1 - e^{-2\tau(r)/T} (1 - \eta_S(r)) \right]}. \quad (87)$$

On a finite graph, moving from radius r to $r + 1$ strictly improves performance exactly when

$$e^{-2\tau(r+1)/T} (1 - \eta_S(r+1)) > e^{-2\tau(r)/T} (1 - \eta_S(r)), \quad (88)$$

or, provided $1 - \eta_S(r) > 0$, equivalently

$$\log \left(\frac{1 - \eta_S(r+1)}{1 - \eta_S(r)} \right) > \frac{2(\tau(r+1) - \tau(r))}{T}. \quad (89)$$

The multiplicative comparison (88) remains the primary statement when $1 - \eta_S(r) = 0$. Increasing the radius by one hop is beneficial precisely when the discrete proportional gain in decision-relevant spatial information exceeds the freshness loss incurred over that hop.

At radius zero,

$$R(0) = R_\infty \eta_S(0) = R_{\text{loc}}. \quad (90)$$

On a finite graph, if $D = \text{diam}(G)$ and radius D provides the entire state, then

$$R(D) = R_\infty \left(1 - e^{-2\tau(D)/T} \right) = R_{\text{glob}}(\tau(D)). \quad (91)$$

Equation (87) can be written as

$$R(r) = R_T(r) + R_S(r), \quad (92)$$

where

$$R_T(r) \triangleq \left(1 - e^{-2\tau(r)/T}\right) R_\infty, \quad (93)$$

$$R_S(r) \triangleq e^{-2\tau(r)/T} \eta_S(r) R_\infty. \quad (94)$$

The temporal term increases with information radius whenever $\tau(r)$ does. The zero-delay spatial omission fraction $\eta_S(r)$ decreases with radius, although its contribution is discounted by the temporal relevance factor $e^{-2\tau(r)/T}$.

To characterize the optimum, define the marginal temporal decay rate

$$m_T(r) \triangleq \frac{2\tau'(r)}{T} \quad (95)$$

and the proportional marginal spatial information gain

$$m_S(r) \triangleq -\frac{\eta'_S(r)}{1 - \eta_S(r)}. \quad (96)$$

The latter quantity is the rate at which the spatially explained share $1 - \eta_S(r)$ grows:

$$m_S(r) = \frac{d}{dr} \log(1 - \eta_S(r)). \quad (97)$$

Proposition 2 (Continuous marginal-balance characterization). *Under the assumptions of Theorem 3, additionally assume that $\tau(r)$ and $\eta_S(r)$ are continuously differentiable on $[0, D]$, with*

$$\tau'(r) \geq 0, \quad \eta'_S(r) \leq 0, \quad 0 \leq \eta_S(r) < 1.$$

Then

$$R'(r) = R_\infty e^{-2\tau(r)/T} (1 - \eta_S(r)) [m_T(r) - m_S(r)]. \quad (98)$$

Consequently, every interior optimal radius $r^ \in (0, D)$ satisfies*

$$\boxed{-\frac{\eta'_S(r^*)}{1 - \eta_S(r^*)} = \frac{2\tau'(r^*)}{T}}. \quad (99)$$

Proof. Differentiating (87) gives

$$\frac{R'(r)}{R_\infty} = e^{-2\tau(r)/T} \left[\frac{2\tau'(r)}{T} (1 - \eta_S(r)) + \eta'_S(r) \right].$$

Factoring $1 - \eta_S(r) > 0$ yields (98). At an interior minimum the derivative vanishes, giving (99). $\square$

If m_S is strictly decreasing and m_T is nondecreasing, their difference crosses at most once: the optimum is at zero when $m_S(0) \leq m_T(0)$, at D when $m_S(D) \geq m_T(D)$, and otherwise at the unique crossing. Under these conditions, increasing T or raising m_S pointwise moves the optimum outward, while scaling latency upward or lowering m_S pointwise moves it inward; the latter spatial changes are conditions on decision-relevant predictability, not automatic consequences of raw covariance parameters. Concave latency laws can make m_T decrease and break uniqueness.

The resulting design principle is to expand information radius while the marginal spatial value exceeds the marginal freshness loss, stopping at their balance when the optimum is interior.

5.2 Canonical Line Model and Closed-Form Radius

We now derive the spatial omission function and the optimal radius from a concrete stochastic field and decision model. Consider a dense one-dimensional network, represented by locations $z \in \mathbb{R}$. This is also the continuum approximation of a sufficiently long path graph away from its boundaries.

Let $\theta(z, t)$ be a zero-mean Gaussian field with covariance

$$\mathbb{E} [\theta(z, t)\theta(z', s)] = \sigma^2 \exp\left(-\frac{|z - z'|}{\ell_s}\right) \exp\left(-\frac{|t - s|}{T}\right). \quad (100)$$

The parameter ℓ_s is the spatial correlation length, and T is the temporal coherence time.

Suppose the full-information decision at location z is the exponentially weighted spatial aggregate

$$x^*(z, t) = \int_{-\infty}^{\infty} w_{\ell_c}(u) \theta(z + u, t) du, \quad (101)$$

where

$$w_{\ell_c}(u) \triangleq \frac{1}{2\ell_c} \exp\left(-\frac{|u|}{\ell_c}\right). \quad (102)$$

The decision-relevance length ℓ_c controls how broadly remote states influence the desired local action.

For example, (101) is generated pointwise by the quadratic tracking-loss density

$$f_z(x, \theta) = \frac{q}{2} [x(z) - x^*(z, \theta)]^2, \quad q > 0. \quad (103)$$

We measure regret per unit length as the expected pointwise tracking loss; with $Q = qI$, the pointwise optimizer is the conditional mean and $R_\infty = (q/2) \text{Var}(x^*(z, t))$. Thus the canonical model places nonlocal decision dependence in $b(\theta)$. Direct action coupling changes the form of $\eta_S(r)$ but not the general composition law or Proposition 2.

At zero delay, the radius- r observation at location z is

$$\mathcal{O}_r(z, t) \triangleq \sigma(\theta(z + u, t) : |u| \leq r). \quad (104)$$

Lemma 3 (Exponential omission by self-similarity). *For the field (100), decision (101), and observation (104), the normalized zero-delay spatial omission error is*

$$\boxed{\eta_S(r) = \frac{\ell_c}{\ell_c + 2\ell_s} \exp\left(-\frac{2r}{\ell_c}\right)}. \quad (105)$$

In particular,

$$\eta_0 = \eta_S(0) = \frac{\ell_c}{\ell_c + 2\ell_s}. \quad (106)$$

Proof. By spatial stationarity, take $z = 0$ and suppress the time argument. Set $\kappa = 1/\ell_c$ and $\lambda = 1/\ell_s$. The Gaussian field with exponential covariance is Markov in the spatial coordinate [19, 21]. Split $x^*(0)$ into its observed middle over $[-r, r]$ and its two tails. Given the observed segment, the two tails are conditionally independent, and each depends on the segment only through its adjacent boundary value. The right tail is

$$\frac{\kappa}{2} e^{-\kappa r} \int_0^\infty e^{-\kappa s} \theta(r + s) ds.$$

By Gaussianity its conditional variance given $\theta(r)$ is independent of the observed value, and by stationarity the integral has the same conditional variance C at every r . Reflection symmetry gives the same variance for the left tail. Consequently,

$$\text{Var}(x^*(0) \mid \mathcal{O}_r) = \frac{\kappa^2}{2} e^{-2\kappa r} C = e^{-2\kappa r} \text{Var}(x^*(0) \mid \mathcal{O}_0).$$

This includes $r = 0$, where the observed middle has zero integral and the two tails are conditionally independent given $\theta(0)$. The exponential form follows from the spatial Markov property and the exponential decision weight.

To determine the constant, Gaussian conditioning on the scalar $\theta(0)$ gives $\eta_S(0) = 1 - \text{Corr}(x^*(0), \theta(0))^2$. The required covariance is

$$\text{Cov}(x^*(0), \theta(0)) = \frac{\sigma^2 \kappa}{2} \int_{\mathbb{R}} e^{-(\kappa+\lambda)|u|} du = \frac{\sigma^2 \kappa}{\kappa + \lambda},$$

and the target variance is

$$\begin{aligned} \text{Var}(x^*(0)) &= \frac{\sigma^2 \kappa^2}{4} \int_{\mathbb{R}} \int_{\mathbb{R}} e^{-\kappa(|u|+|v|)-\lambda|u-v|} du dv \\ &= \frac{\sigma^2 \kappa (2\kappa + \lambda)}{2(\kappa + \lambda)^2}. \end{aligned} \tag{107}$$

Using $\text{Var}(\theta(0)) = \sigma^2$ yields $\eta_S(0) = \lambda/(2\kappa + \lambda) = \ell_c/(\ell_c + 2\ell_s)$, which proves both claims. $\square$

Assume information propagates at effective speed $v > 0$, so

$$\tau(r) = r/v, \tag{108}$$

and define the temporal propagation length

$$L_T \triangleq vT. \tag{109}$$

This is the distance information can travel during one coherence time. We write $[z]_+ \triangleq \max\{z, 0\}$.

Theorem 4 (Optimal synchronized-snapshot radius in the canonical model). *Suppose the state field obeys (100), the full-information decision is given by (101), the loss is (103), and the latency is (108). Then the unique optimal radius on the infinite line satisfies the dimensionless law*

$$\boxed{\frac{r^*}{\ell_c} = \frac{1}{2} \left[\log \left(\frac{1 + L_T/\ell_c}{1 + 2\ell_s/\ell_c} \right) \right]_+}. \tag{110}$$

Equivalently,

$$\boxed{r^* = \frac{\ell_c}{2} \left[\log \left(\frac{\ell_c + L_T}{\ell_c + 2\ell_s} \right) \right]_+}. \tag{111}$$

The optimal radius is strictly positive if and only if

$$\boxed{L_T > 2\ell_s}. \tag{112}$$

Within the interior regime, r^* :

1. increases with the temporal coherence time T ;
2. increases with the information-propagation speed v ;
3. decreases with the spatial correlation length ℓ_s ; and
4. increases with the decision-relevance length ℓ_c .

Proof. For any omission law $\eta_S(r) = \eta_0 e^{-2r/\ell_c}$ with $0 < \eta_0 < 1$, minimizing (87) under linear delay is equivalent to maximizing

$$g(r) = e^{-2r/L_T} - \eta_0 e^{-2r(1/L_T + 1/\ell_c)}.$$

Differentiation gives

$$g'(r) = 2e^{-2r/L_T} \left[\eta_0 \left(\frac{1}{L_T} + \frac{1}{\ell_c} \right) e^{-2r/\ell_c} - \frac{1}{L_T} \right].$$

The bracket is strictly decreasing and has a negative limit, so g' changes sign at most once, from positive to negative. If its value at zero is nonpositive, radius zero is the unique optimum; otherwise the unique stationary point is the optimum. Thus the general exponential law gives

$$r^* = \frac{\ell_c}{2} \left[\log \left(\eta_0 \left(1 + \frac{L_T}{\ell_c} \right) \right) \right]_+, \quad (113)$$

and a maximum allowed radius D gives

$$r_D^* = \min\{D, r^*\}. \quad (114)$$

Substituting $\eta_0 = \ell_c/(\ell_c + 2\ell_s)$ gives (110)–(112). The cap restricts observation radius on the same infinite-line model; it does not turn that model into a finite graph.

In the positive-radius regime, $\partial r^*/\partial L_T = \ell_c/[2(\ell_c + L_T)] > 0$ and $\partial r^*/\partial \ell_s = -\ell_c/(\ell_c + 2\ell_s) < 0$. Since $L_T = vT$, these establish the first three comparative statics. Finally, when $L_T > 2\ell_s$,

$$r^* = \frac{1}{2} \int_{2\ell_s}^{L_T} \frac{\ell_c}{\ell_c + s} ds. \quad (115)$$

The integrand is strictly increasing in ℓ_c , proving that r^* increases with the range over which remote state affects the desired decision. $\square$

Theorem 4 identifies three physical length scales:

$$\boxed{\underbrace{\ell_s}_{\text{spatial correlation}} \quad \underbrace{\ell_c}_{\text{decision relevance}} \quad \underbrace{L_T = vT}_{\text{temporal propagation}}}. \quad (116)$$

Three consequences clarify how these lengths determine the optimum. At radius zero, $m_S(0) = 1/\ell_s$ and $m_T = 2/L_T$, so the first increment of radius pays off exactly when $L_T > 2\ell_s$, independently of ℓ_c . In this positive-radius regime, a long decision range $\ell_c \gg L_T, \ell_s$ gives $r^* \approx (L_T - 2\ell_s)/2$, half the excess propagation length. A short decision range $\ell_c \ll \ell_s, L_T$ gives $r^* \approx (\ell_c/2) \log(L_T/(2\ell_s))$; outside the positive-radius regime, the optimum remains zero.

On a finite graph, Theorem 3 and minimization over integer radii remain exact, with the one-hop comparison (88)–(89) as the discrete form of marginal balance; Eq. (111) is the closed-form counterpart on the homogeneous line.

6 Numerical Consistency Checks and Finite-Graph Illustrations

This section checks the implementations against the closed-form predictions and then shows how the same quantities behave on finite graphs. Experiments 1 and 2 check temporal prediction and the fresh-local-stale-global endpoints; Experiments 3 and 4 isolate and sweep the continuous radius tradeoff; Experiment 5 separates state statistics from decision-relevant omission; and Experiment 6 evaluates exact integer radii on several noncanonical graph instances.

6.1 Numerical Methodology and Synthetic Environments

The numerical objects are architecture regrets, so each calculation uses the same information structure as its analytical counterpart. We work with an exogenous common-rate Gaussian-affine environment: actions do not alter later states. For $x^* = K\theta + k_0$, with $K = Q^{-1}B$, we evaluate

$$R(\mathcal{A}) = \frac{1}{2} \|x^* - u_{\mathcal{A}}^*\|_Q^2$$

from conditional covariance and, where appropriate, from independently sampled quadratic losses. The solvers respect the information structure: the common delayed snapshot in Experiment 1 permits a joint conditional mean even for non-diagonal Q ; Experiment 2 uses the exact fresh-local rule; Experiments 3 and 4 evaluate the scalar composition; and Experiments 5 and 6 use $Q = I$ so agentwise Gaussian conditional variances are exact. Experiment 5 holds the graph and covariance fixed while changing decision sensitivity. The graph covariances are scaled to average marginal variance one.

For an arbitrary graph, a convenient alternative is to define the covariance spectrally through the graph Laplacian L_G . For example,

$$\Sigma_S = \sigma^2 (\kappa_s^2 I + L_G)^{-\nu}, \quad \kappa_s > 0, \quad \nu > 0, \quad (117)$$

is positive semidefinite and places more state energy in low graph-frequency modes. Such constructions are closely related to graph signal smoothness and Gaussian Markov random-field models [21, 22].

Pointwise Monte Carlo means use 95% normal confidence intervals. The Experiment 2 boundary intervals apply the delta method to the paired fresh-local/open-loop regret means, so their uncertainty reflects that the two regrets use the same draws.

Table 2 summarizes the reference settings. The repository stores fixed configurations, processed tables, selected raw arrays, and graph covariance/distance inputs where applicable, together with run metadata and diagnostics; it is not a complete archive of every random draw. The exact system construction, graph seeds, conditioning safeguards, boundary conventions, radius grids, crossover estimator, and interval calculation are specified in the reproduction documentation. Robustness beyond the common-rate Gaussian-affine model is discussed in Section 8.

Table 2: Reference numerical settings. The shared-resource sweep fixes $q = 1$; graph covariances in Experiments 5–6 are scaled to average marginal variance one. Quantities not being swept retain the experiment-specific values in the configuration files.

Experiment	principal sweep	fixed setting/size	evaluation
1. Temporal pairs	$\tau/T \in [0, 3]$ (25 points)	A–D; $n = 8, 20, 50, 32$	20,000/point
2. Local–global	9 γ/q values in $[0, 10]$	$n = 5, 10, 25, 100$; $q = 1$	30,000/setting
3. Scalar radius	$r/\ell_c \in [0, 2]$ (1,001 points)	3 regimes; $D/\ell_c = 2$	50,000/point
4. Canonical map	$(vT/\ell_c, \ell_s/\ell_c)$; 72×68	$r/\ell_c \in [0, 4]$; $\Delta r = 0.0016$	direct scalar
5. Decision relevance	$\ell_c = 0.7, 2, 6$	64-node ring; $T = 6$	12,000/check
6. General graphs	path, ring, grid, geometric	64 nodes; $T = 5$	exact covariance

6.2 Temporal Scaling and the Local–Global Crossover

The first two experiments test two different consequences of common-rate temporal predictability: the exact stale-global law (48), and the endpoint crossover threshold (62).

Experiment 1 asks whether the normalized regret of a delayed global snapshot depends only on $\rho = \tau/T$, even when spatial covariance, objective coupling, and the decision operator change. We used the four systems in Table 2 and drew 20,000 exact stationary OU pairs $(\theta_{t-\tau}, \theta_t)$ at each of 25 values of ρ . The first member has covariance Σ_S and the second is generated as $e^{-\rho}\theta_{t-\tau} + (1 - e^{-2\rho})^{1/2}\varepsilon$, with an independent innovation ε of covariance Σ_S . For each pair, the optimal delayed-snapshot action was evaluated with the known common-rate coefficient and the quadratic loss was computed in the system’s Q metric.

Across the 100 system–parameter combinations, the Monte Carlo curves collapse onto $1 - e^{-2\rho/T}$ (Fig. 1). The largest absolute normalized deviation was 0.0155 and the root-mean-square deviation was 0.00471. This supports the exact temporal scaling for these stationary common-rate pairs.

Experiment 2 asks whether the finite- n threshold in Eq. (62) describes the point at which fresh local information becomes preferable to a stale global snapshot. We used the shared-resource model $Q = qI + \gamma\mathbf{1}\mathbf{1}^\top$, $q = 1$, with independent OU components. For each of 36 $(n, \gamma/q)$ settings, the fresh-local and open-loop regrets were evaluated on the same 30,000 current-state draws. The empirical boundary was then inferred by inserting these two estimates into the OU temporal law,

$$\hat{\rho}^* = \frac{1}{2} \log \left(\frac{\hat{R}_\infty}{\hat{R}_\infty - \hat{R}_{\text{loc}}} \right).$$

Accordingly, Fig. 2 reports the temporal-law boundary inferred from paired local/open-loop losses.

The mean absolute boundary error was 0.00111 and the maximum was 0.00557. Finite size matters most under strong coupling: at $n = 5$ and $\gamma/q = 10$, the exact threshold is 0.109 below the large-system limit. As n grows, the inferred boundary approaches $\frac{1}{2} \log(1 + \gamma/q)$. Stronger decision coupling therefore makes older global information worth tolerating in this independent-component model.

6.3 Emergence of an Optimal Coordination Radius

Experiment 3 illustrates why expanding the information radius can help at first and hurt later: reduced spatial omission competes with increasing staleness. We used $\eta_S(r) = \eta_0 e^{-2r/\ell_c}$ and $\tau(r) = r/v$ on $0 \leq r \leq D = 2$, with local $(\eta_0, vT) = (0.25, 0.2)$, interior $(0.7, 4)$, and maximum allowed radius $(0.9, 100)$ regimes (all with $\ell_c = 1$). At each radius, independent standard-normal draws




Figure 1: Temporal scaling collapse from exact stationary OU pairs. Markers are Monte Carlo estimates for four systems with different dimensions, spatial covariances, objective matrices, and decision operators; bars are 95% confidence intervals. The solid curve is the exact law $1 - e^{-2\tau/T}$. Normalization by R_∞ removes system-specific scale.

were scaled by the two prescribed component variances and added before squaring. This is a scalar loss check: no spatial field, graph, or neighborhood conditional distribution is sampled.

The grid minima were 0, 0.626, and 2; the corresponding analytical minima after imposing the cap were 0, 0.62638, and 2. At the interior grid minimum, the marginal-slope gap was $|m_S(\hat{r}^*) - m_T(\hat{r}^*)| = 4.77 \times 10^{-4}$, and the largest Monte Carlo deviation from the prescribed scalar curve was about 0.020. The maximum allowed radius case is not a global endpoint: its unconstrained minimizer lies beyond D , while $\eta_S(D) = \eta_0 e^{-2D/\ell_c} > 0$. Thus the cap still omits decision-relevant state. The three curves distinguish immediate dominance of staleness, an interior balance, and a benefit from expansion throughout the allowed range.

6.4 Scaling Laws and Regime Map

Experiment 4 asks whether the canonical closed form predicts both the zero-radius region and the interior radius over a two-parameter sweep, rather than only at selected examples. We swept 4,896 points over $vT/\ell_c \in [0.1, 20]$ and $\ell_s/\ell_c \in [0.05, 5]$, using $\ell_c = 1$ as the unit of length. Independently of the closed form, every point was minimized by direct scalar evaluation of Eq. (82) on the same fixed grid $r_j = 0.0016j$, $j = 0, \dots, 2500$, so $r \in [0, 4]$ for every parameter pair. No covariance simulation or adaptive radius range was used. Separate one-dimensional sweeps tested the four comparative statics.

The gray region in Fig. 4 selects fresh local information; above the threshold $vT = 2\ell_s$, positive




Figure 2: Fresh-local versus stale-global crossover. Left: the phase map uses the exact finite- $n = 100$ boundary (solid) and the large- n limit (dashed), Eqs. (62) and (64). Upper right: exact theory curves and inferred Monte Carlo boundaries (crosses) for four system sizes, with paired delta-method 95% intervals. Lower right: empirical minus theoretical boundary, on a scale that reveals the sampling differences and their uncertainty. The zero-coupling setting is evaluated at $\rho^* = 0$ but omitted from the logarithmic positive-coupling axes.

scope becomes worthwhile. Moving upward increases the distance information can travel within a coherence time and raises the preferred radius. Moving right increases spatial correlation, making remote observations more redundant and lowering the preferred radius. The slices show these changes as ordinary radius curves. The mean absolute grid-versus-closed-form error was 2.25×10^{-4} and the maximum was 8.00×10^{-4} , below the 0.0016 grid step. Ordinary grid error occurs throughout the positive-radius interior because the minimizer is discretized; it is not confined to the threshold. There were five zero/positive classification disagreements, all adjacent to the threshold where the continuous optimum fell below the first positive grid point. The one-dimensional sweeps were monotone in all four predicted directions: r^* increased with T , v , and ℓ_c , and decreased with ℓ_s . This validates the scalar search and canonical scaling within the stated range.

6.5 State Predictability versus Decision-Relevant Predictability

Experiment 5 asks whether the architecture depends on which state modes affect the decision, rather than only on raw state correlation. We held a 64-node ring, its Laplacian covariance, $T = 6$, and the latency law (0.12 time units per hop) fixed, and changed only the decision-sensitivity operator $K_{ij} = e^{-d_G(i,j)/\ell_c} / \|e^{-d_G(i,\cdot)/\ell_c}\|_2$, using $\ell_c \in \{0.7, 2, 6\}$ and $Q = I$. Exact Gaussian conditioning gives the decision-weighted omission $\eta_S(r)$ at every graph radius. The raw state-correlation statistic was computed separately from the fixed covariance; it is not the same quantity as $\eta_S(r)$. Each curve is normalized by its own $R_\infty = \frac{1}{2} \text{tr}(K \Sigma_S K^\top)$, so normalized regrets compare unexplained fractions rather than equal absolute cost scales.

Increasing ℓ_c from 0.7 to 2 to 6 increased $\eta_S(0)$ from 0.0460 to 0.258 to 0.572 and moved the discrete optimum from 1 to 2 to 5 hops, even though the raw state correlation was identical.




Figure 3: Emergence of local, interior, and maximum allowed radius optima under $\eta_S(r) = \eta_0 e^{-2r/\ell_c}$ and $\tau(r) = r/v$. Curves show total regret and its temporal and residual-spatial terms from Eq. (92); open markers with 95% intervals are independent scalar-innovation estimates. Dash-dotted lines and crosses mark the analytical constrained and grid minimizers. At the maximum allowed radius, positive omission remains: $\eta_S(D) > 0$.

Independent 12,000-sample conditioning checks differed from the exact omission by at most 2.39×10^{-3} (the largest pointwise standard error was 3.20×10^{-3}). Thus changing only decision sensitivity in a fixed environment produced substantially different preferred architectures.

6.6 Finite Graphs beyond the Canonical Geometry

Experiment 6 asks whether the conditional-variance construction and discrete radius comparison remain usable when the geometry is not the homogeneous line assumed by the canonical formula. We considered one 64-node graph of each of a path, ring, two-dimensional grid, and random geometric type; the geometric graph uses the fixed configured seed. For each instance we formed the covariance (117), scaled it to average marginal variance one, and computed every $\eta_S(r)$ directly from the Gaussian conditional covariance of the desired action given the radius- r neighborhood. The reference setting uses $Q = I$, $T = 5$, $\ell_c = 2$, and latency 0.12 per hop. No exponential omission fit or canonical line formula was used, and no graph ensemble average was taken.

Under the reference setting, Fig. 6 gives exact integer optima of 2, 2, 3, and 2 hops for the path, ring, grid, and geometric instance, respectively. In these four sampled instances, increasing T over the configured values 1.5, 2.5, 4, 6, 9, 14 changed the optimum from 1 to 3 hops on the path and ring, from 1 to 4 on the grid, and from 1 to 3 on the geometric graph. The sampled ℓ_c sweep from 0.7 to 6 moved the optima from (0, 0, 1, 1) to (5, 5, 5, 3) in the same graph order. Increasing per-hop latency weakly decreased the optimum, as did decreasing κ_s , which increases spatial smoothness after variance normalization. These comparative statics describe the four specified graph instances. Since radii are integer-valued, the appropriate comparison is the one-hop regret difference in Eq. (88). For example, the geometric graph’s three-hop regret exceeds its two-hop minimum by only $0.00362R_\infty$; the archived neighbor differences quantify such shallow minima.




Figure 4: Dimensionless optimal-radius law from direct scalar minimization. Left: the numerical map, with the numerical zero-radius region shown in gray and the dashed curve marking the theoretical transition $vT = 2\ell_s$. Upper right: selected ℓ_s/ℓ_c slices comparing grid minimizers with the closed form in Eq. (110). Lower right: the histogram of $(\hat{r}^* - r^*)/\Delta r$ over all 4,896 points; its zero spike includes local-regime points and the remaining grid errors are of order a half-step.




Figure 5: Decision relevance with the graph and state covariance held fixed. The decision-weighted omission and normalized composed regret are shown for three row- ℓ_2 -normalized operators with $Q = I$. Raw state correlation is shown in a separate context panel and is identical across operators; it is not an omission estimate. Each regret is normalized by its operator-specific R_∞ , and the minimizing integer radius is marked. Changing only the decision-relevance range moves the optimum from 1 to 5 hops.




Figure 6: Finite noncanonical graphs. Top: $\eta_S(r)$ computed from exact Gaussian conditional covariances and the resulting regret under one common normalized setting; lines join integer-radius evaluations. Bottom: exact integer optima at the sampled coherence times and decision ranges; no transition locations between those settings are inferred. Distinct marker shapes identify coincident graph results. The canonical line closed form is not used.

7 Related Work

We organize the closest literatures around three distinctions: iterative computation versus information architecture, controlled dynamics versus an exogenous environment, and age-based freshness versus decision-relevant value. These distinctions frame the more specific connections developed below.

7.1 Static Team Decision Theory

Radner established foundational optimality conditions for static teams, in which decision makers share a common objective but act on different information [10]. Under appropriate convexity and regularity conditions, the resulting stationarity conditions are sufficient for global team optimality; in the quadratic Gaussian specialization, the optimal decision rules are affine [10, 11]. In the deterministic-Hessian quadratic model used here, these fixed-information optimality conditions admit the equivalent Hilbert-space formulation developed in Section 2.4: for a fixed information architecture $\mathcal{A}$, the team-optimal policy is the Q -orthogonal projection of the full-information action onto the closed subspace $\mathcal{S}(\mathcal{A})$ of implementable policies. This projection identity specializes the classical static-team framework to our quadratic model; Radner’s theorem is not stated in this literal form. Krainak, Speyer, and Marcus subsequently relaxed the sufficient conditions associated with Radner’s stationarity result and extended the theory to an exponential-quadratic criterion with jointly Gaussian state and observations [23]. In a companion paper, they formulated affine linear-quadratic-Gaussian and linear-exponential-Gaussian team problems as constrained parameter optimizations and represented optimal team gains as projections of the corresponding centralized gains [17].

Classical team theory also treated information itself as an organizational design object. Marschak and Radner analyzed the value of information, delayed information and the tradeoff between timeliness and completeness, and formulated team organization in terms of optimal networks [11]. More recently, Summers, Li, and Kamgarpour formulated information-structure design as the selection of additional measurements or communication links jointly with the corresponding team decision strategies [12]. Afshari and Mahajan characterized quadratic Gaussian static teams whose observations decompose into information common to all agents and agent-specific local information [24]. They subsequently applied this decomposition to team-optimal decentralized filtering over communication graphs with delayed information sharing, where sufficiently old measurements constitute common information while more recent measurements remain local [25]. Rusmevichientong and Van Roy studied large teams in which each agent observes the local cost structure only within a graph radius, using centralized performance as a benchmark [26]. Gamarnik, Goldberg, and Weber studied decentralized decisions based on local information in random decision networks and related their near-optimality to a correlation-decay, or long-range-independence, property [27].

Relative to these works, the distinctive object studied here is a structured family of information architectures in which spatial scope and temporal freshness are coupled through the scope–latency relation $\tau(r)$. Each spatial scope induces an acquisition delay, and the resulting architecture is valued through its prediction error for the full-information decision. This coupling yields the freshness–locality crossover and coordination-scale laws developed in Sections 3 and 5.

7.2 Distributed Optimization, Communication Constraints, and Scope

Distributed optimization studies how agents compute a common solution using local computation and message exchange. Classical asynchronous gradient methods allow delayed interprocessor

communication while retaining convergence guarantees under suitable boundedness conditions [28], while distributed subgradient methods establish convergence when agents exchange information locally over time-varying network topologies [3]. In these canonical formulations, the communication process constrains an iterative computation of an optimizer. Our setting separates that computational question from information architecture: the full-information decision at each epoch is the benchmark, and the object of design is the information available when that decision must be made.

Networked and decentralized control place communication restrictions directly in the feedback loop, including sampling, packet loss, communication topology, and delay [29]. For spatially invariant plants, early work showed that optimal controllers can exhibit inherent spatial localization [5], while subsequent work imposed explicit finite-speed communication structure. Arbelaiz, Bamieh, Hosoi, and Jadbabaie characterize the spatial decay of optimal estimator gains, using the decay rate as a proxy for the distance over which measurements are useful in a spatially distributed dynamic estimation problem [30]. Voulgaris, Bianchini, and Bamieh studied H_2 control under delayed communication requirements [6]; Bamieh and Voulgaris formulated distance-dependent information propagation through funnel causality [7]; and Fardad and Jovanović developed state-space models for distributed controllers with finite communication speed [8]. These works are important antecedents to our use of spatial scope and propagation time, but they optimize dynamic feedback for controlled plants rather than information-constrained stage decisions in an exogenous environment.

Communication structure has also been treated as a design variable. Langbort and Gupta study interconnection topology when communication is assigned a topology-dependent cost [31], and Matni co-designs communication-delay structure and H_2 control using regularization [32]. In wireless consensus, Vanka, Gupta, and Haenggi explicitly trade communication radius against interference-induced delay and show that the preferred connectivity depends on network geometry [15]. Most directly, Ballotta, Jovanović, and Schenato parameterize control architectures by communication scope: each agent receives measurements from nodes within a chosen number of communication hops, with an architecture-dependent delay that increases with that scope. After optimizing the feedback gains for each scope, they show that sparse architectures can outperform all-to-all feedback [9]. Ballotta and Gupta obtain an analogous conclusion when maximizing consensus convergence speed under hop-dependent communication delay [14]. These results establish that scope-dependent delay can itself induce a sparse or intermediate optimal control architecture.

Our setting differs in the decision problem: an exogenous-state static team, with the current full-information action as the benchmark and an architecture valued by the prediction error it induces for that action. This yields the decision-relevant spatial omission function $\eta_S(r)$, temporal unpredictability $\eta_T(\tau)$, their exact common-rate composition law, and the fresh-local versus stale-global and coordination-radius laws derived above. Ballotta, Arbelaiz, Gupta, Schenato, and Jovanović study a different but complementary question for spatially invariant dynamic plants: how delayed measurements from different spatial locations alter the spatial locality of the optimal feedback kernel [16]. Their results operate through closed-loop plant dynamics and controller localization, whereas ours operate through prediction of an exogenously varying full-information decision.

7.3 Freshness and Age of Information

Age of Information (AoI) formalizes the timeliness of status information through the age of the freshest received update, $\Delta(t) = t - u(t)$. Seminal work showed that minimizing AoI is distinct from maximizing throughput or minimizing packet delay and initiated a large literature on update generation, queueing, and scheduling [2, 33]. Subsequent work generalized linear age to application-specific nonlinear age penalties [34]. Connections to remote estimation make the distinction between

age and task loss explicit: for a Gauss–Markov Ornstein–Uhlenbeck process, estimation error under signal-agnostic sampling is a nonlinear function of age, whereas signal-aware sampling can exploit the realized estimation error and outperform age-optimal policies [18].

More recent work has pushed freshness metrics toward task-aware objectives. Shisher et al. showed that remote-inference loss can be nonmonotonic in age and designed communication policies around inference performance [35]; subsequent work considers correlated sources for which inference penalties depend jointly on multiple sources’ ages [36]. Li et al. go further toward decision-aware freshness by jointly optimizing sampling and remote decision making under stale observations [37]. Those works optimize when or which updates reach a fixed remote receiver; we instead choose the information architecture available to a decentralized team: what is observed, from what spatial scope, and at what age. Because broader scope itself incurs greater acquisition delay, spatial omission and temporal staleness are coupled by the architecture. This leads to the fresh-local versus stale-global crossover and optimal coordination-scale results developed here.

7.4 Centralization, Delegation, and Organizational Economics

A closely related organizational-economics literature asks how dispersed information, communication constraints, and decision rights determine organizational form. Aoki compares hierarchical and horizontal information structures when local conditions are uncertain and central monitoring or response is limited [38]. In the information-processing tradition, Radner studies organizations of limited-capacity processors trading off processing resources against decision delay [39]; Bolton and Dewatripont derive communication networks from processing and communication costs [40]; and Van Zandt studies real-time decentralized processing in which computational delay constrains the use of recent information [41]. Dessein and Santos likewise study adaptation to local information versus coordination under imperfect communication [42].

A complementary delegation literature makes decision rights endogenous when information and objectives are dispersed. Aghion and Tirole distinguish formal from real authority [43], while Dessein studies delegation as an alternative to strategic communication [44]. Most closely related to our centralization framing, Alonso, Dessein, and Matouschek compare centralized and decentralized coordination when managers privately observe local conditions [4]. Our model abstracts from incentive conflicts and endogenous information acquisition: agents share a common objective and the environment evolves exogenously. The tradeoff studied here is spatio-temporal: broader synchronized snapshots can improve coordination but arrive older. This yields a pure-benchmark crossover and, in the canonical spatial model, an interior optimum within the synchronized-snapshot family.

7.5 Spatial Statistics and Graph Signal Processing

Spatial statistics provides the closest statistical antecedent to our spatial-predictability model. Kriging casts spatial prediction as an optimal linear prediction problem under spatial dependence [45]. For lattice data, Besag’s conditional formulation represents spatial dependence through local Markov neighborhoods [46]; Lindgren, Rue, and Lindström later connect Matérn Gaussian fields to sparse Gaussian Markov random fields through stochastic partial differential equation representations [21]. Space–time statistics treats separability as an optional modeling restriction: Gneiting constructs broad classes of stationary nonseparable covariance functions [20]. These works provide the statistical context for our covariance-based spatial model and its separable and non-separable distinction.

Graph signal processing extends analogous ideas to irregular domains. Shuman et al. use graph-Laplacian eigenvectors to define a graph Fourier domain and associate low graph frequencies with

signals that vary slowly over the graph [22]. Graph-sampling theory asks when bandlimited graph signals can be exactly recovered from partial observations [47], while stationary graph signal processing gives spectral descriptions and Wiener-type estimators for random graph signals [48]. Our objective is different: we do not value accurate reconstruction of θ_t per se. A radius- r architecture is evaluated by its loss in reproducing the full-information decision x_t^* , and increasing r also increases information age through $\tau(r)$. Thus spatial omission and temporal staleness are priced jointly, and graph-smooth modes matter only insofar as they are decision-relevant.

8 Discussion and Conclusions

What the theory establishes. The central constraint in networked decision making is that information breadth and freshness generally cannot be chosen independently. Nearby observations can be used quickly but may omit remote state needed for coordination; a broader view can improve coordination but loses predictive value while it is collected and disseminated. Architecture regret measures this loss relative to the full-information decision after optimizing over every policy implementable under the architecture.

Theorem 2 characterizes the fresh-local versus stale-global endpoints. Proposition 2 gives the interior marginal-balance condition for the synchronized-snapshot radius, and Theorem 4 gives its closed-form scaling law in the canonical model. Normalization by open-loop regret separates the overall scale of the decision problem from the fraction of decision-relevant variation preserved by an architecture, enabling comparisons across modeled systems.

Why decision-relevant predictability matters. Raw state predictability is not the correct design criterion. Architecture regret depends on predicting the full-information decision x^* , not on reconstructing every component of θ . A remote state component can be hard to predict but architecturally unimportant when it has little influence on the desired action. Conversely, a small residual uncertainty can matter when the decision-sensitivity operator K strongly amplifies that mode. The relevant predictability therefore combines environmental statistics, decision sensitivity and coupling, information geometry, and freshness (Section 6.5).

This distinction also separates physical communication geometry from decision geometry. Graph distance determines which observations can be acquired and their age on arrival; Q , B , and K determine whether those observations change the desired joint action. Two nearby nodes may be weakly coupled, while distant nodes may interact strongly through a shared constraint or common decision mode. An architecture based only on physical distance can therefore communicate extensively about irrelevant variation while omitting a remote mode with high decision value.

Scope and limitations. The paper establishes an exogenous-state, static-team baseline. Environmental state may be correlated across space and time, but current actions neither alter its future law nor change what another agent later observes. Within this boundary, the fixed-architecture quadratic projection gives an exact benchmark for each fixed information pattern, and the paper’s new results compare a structured scope-age family using that benchmark. The principal radius family uses synchronized snapshots; history-based and mixed-age variants lie outside this principal family. The fixed-epoch projection does not require stationarity, although stationarity makes expected performance time-invariant and ergodicity is needed for sample-path long-run averages.

The projection identity assumes quadratic costs, a deterministic positive-definite Hessian, and unconstrained Euclidean actions. The explicit stale-global and composition laws additionally require affine full-information decisions and a stationary common-rate innovation structure with

conditionally mean-zero innovations. Gaussianity is used to evaluate spatial prediction errors from covariances in the canonical model and Experiments 5–6; the canonical radius formula further uses a separable homogeneous field and linear propagation delay. Nonquadratic or discrete decisions, state-dependent Hessians, and feasibility constraints such as nonnegativity, capacity, or simplex restrictions require different analytical tools. Outside the stated assumptions, one should work directly with decision-relevant prediction-error functions or suitable bounds rather than assume the same factorization.

The experiments do not probe temporal-rate heterogeneity, nonseparable covariance, non-Gaussian evolution, nonlinear decisions, or mixed-age architectures; each remains an extension.

Finally, the common-rate assumption suppresses possible alignment between temporal coherence, spatial scale, and decision relevance. If long-range decision-relevant modes evolve more slowly than local modes, a scalar common-rate approximation may understate the value of broad delayed information; the reverse alignment may overstate it. There is no universal direction of bias without specifying the mode weights and the procedure used to select an effective coherence time. With heterogeneous temporal modes, the scalar composition law generally gives way to a joint spatio-temporal decision-prediction error.

Most important extensions. A first extension is to price information acquisition explicitly. The present model represents communication and sensing constraints mainly through the feasible scope–delay relationship. Adding an acquisition cost or budget could produce sparse, nonuniform topologies and compressed summaries that preserve decision-relevant modes with less latency.

A second extension is adaptation to unknown or nonstationary statistics. Temporal coherence, spatial predictability, and decision sensitivity may need to be estimated online while the architecture changes on a slower timescale than operational decisions. The challenge is to account for estimation uncertainty while retaining a stable architecture-selection rule.

The most important extension is action-dependent state evolution and dynamic teams, where actions alter future state and may signal information to other agents. Extending information-architecture design beyond the exogenous-state baseline is therefore not a routine modification. Witsenhausen’s counterexample [13] explains why: once control and signaling interact, the fixed-subspace projection characterization generally no longer solves the team problem.

Design implication. Taken together, the theory yields a practical design heuristic: expand information scope as long as the marginal decision value of broader information exceeds the predictive value lost in obtaining it.

AI Use Statement. The development of this paper made substantial use of AI tools, including Claude Code, ChatGPT/Codex, Gemini, and Grok, for drafting and revising text, developing code and figures, mathematical formulation and proofs. The human authors formulated the original problem, made substantial contributions throughout the paper’s development, reviewed the manuscript, and accept full responsibility for its contents.

Code and Data Availability. The manuscript source, numerical code, experiment configurations, processed reference results, and figure-generation pipeline are available in the public TINA repository at <https://github.com/ANRGUSC/TINA> [49].

References

- [1] M. Mitzenmacher, “How useful is old information?” *IEEE Transactions on Parallel and Distributed Systems*, vol. 11, no. 1, pp. 6–20, Jan. 2000.
- [2] S. Kaul, R. Yates, and M. Gruteser, “Real-time status: How often should one update?” in *2012 Proceedings IEEE INFOCOM*. IEEE, 2012, pp. 2731–2735.
- [3] A. Nedic and A. Ozdaglar, “Distributed subgradient methods for multi-agent optimization,” *IEEE Transactions on Automatic Control*, vol. 54, no. 1, pp. 48–61, 2009.
- [4] R. Alonso, W. Dessein, and N. Matouschek, “When does coordination require centralization?” *American Economic Review*, vol. 98, no. 1, pp. 145–179, 2008.
- [5] B. Bamieh, F. Paganini, and M. A. Dahleh, “Distributed control of spatially invariant systems,” *IEEE Transactions on Automatic Control*, vol. 47, no. 7, pp. 1091–1107, Jul. 2002.
- [6] P. G. Voulgaris, G. Bianchini, and B. Bamieh, “Optimal H2 controllers for spatially invariant systems with delayed communication requirements,” *Systems & Control Letters*, vol. 50, no. 5, pp. 347–361, Dec. 2003.
- [7] B. Bamieh and P. G. Voulgaris, “A convex characterization of distributed control problems in spatially invariant systems with communication constraints,” *Systems & Control Letters*, vol. 54, no. 6, pp. 575–583, Jun. 2005.
- [8] M. Fardad and M. R. Jovanović, “Design of optimal controllers for spatially invariant systems with finite communication speed,” *Automatica*, vol. 47, no. 5, pp. 880–889, May 2011.
- [9] L. Ballotta, M. R. Jovanović, and L. Schenato, “Can decentralized control outperform centralized? the role of communication latency,” *IEEE Transactions on Control of Network Systems*, vol. 10, no. 3, pp. 1629–1640, Sep. 2023.
- [10] R. Radner, “Team decision problems,” *The Annals of Mathematical Statistics*, vol. 33, no. 3, pp. 857–881, 1962.
- [11] J. Marschak and R. Radner, *Economic Theory of Teams*, ser. Cowles Foundation Monographs. New Haven, CT: Yale University Press, 1972, no. 22.
- [12] T. Summers, C. Li, and M. Kamgarpour, “Information structure design in team decision problems,” *IFAC-PapersOnLine*, vol. 50, no. 1, pp. 2530–2535, 2017.
- [13] H. S. Witsenhausen, “A counterexample in stochastic optimum control,” *SIAM Journal on Control*, vol. 6, no. 1, pp. 131–147, 1968.
- [14] L. Ballotta and V. Gupta, “Faster consensus via a sparser controller,” *IEEE Control Systems Letters*, vol. 7, pp. 1459–1464, 2023.
- [15] S. Vanka, V. Gupta, and M. Haenggi, “Power-delay analysis of consensus algorithms on wireless networks with interference,” *International Journal of Systems, Control and Communications*, vol. 2, no. 1/2/3, pp. 256–274, 2010.
- [16] L. Ballotta, J. Arbelaz, V. Gupta, L. Schenato, and M. R. Jovanović, “The role of communication delays in the optimal control of spatially invariant systems,” *IEEE Transactions on Automatic Control*, vol. 71, no. 2, pp. 978–993, Feb. 2026.

- [17] J. C. Krainak, J. Speyer, and S. I. Marcus, “Static team problems—part II: Affine control laws, projections, algorithms, and the LEGT problem,” *IEEE Transactions on Automatic Control*, vol. 27, no. 4, pp. 848–859, 1982.
- [18] T. Z. Ornee and Y. Sun, “Sampling and remote estimation for the Ornstein–Uhlenbeck process through queues: Age of information and beyond,” *IEEE/ACM Transactions on Networking*, vol. 29, no. 5, pp. 1962–1975, 2021.
- [19] C. E. Rasmussen and C. K. Williams, *Gaussian Processes for Machine Learning*. MIT press Cambridge, MA, 2006.
- [20] T. Gneiting, “Nonseparable, stationary covariance functions for space–time data,” *Journal of the American Statistical Association*, vol. 97, no. 458, pp. 590–600, 2002.
- [21] F. Lindgren, H. Rue, and J. Lindström, “An explicit link between Gaussian fields and Gaussian Markov random fields: the stochastic partial differential equation approach,” *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, vol. 73, no. 4, pp. 423–498, 2011.
- [22] D. I. Shuman, S. K. Narang, P. Frossard, A. Ortega, and P. Vandergheynst, “The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains,” *IEEE Signal Processing Magazine*, vol. 30, no. 3, pp. 83–98, 2013.
- [23] J. C. Krainak, J. Speyer, and S. I. Marcus, “Static team problems—part i: Sufficient conditions and the exponential cost criterion,” *IEEE Transactions on Automatic Control*, vol. 27, no. 4, pp. 839–848, 1982.
- [24] M. Afshari and A. Mahajan, “Static teams with common information,” *IFAC-PapersOnLine*, vol. 50, no. 1, pp. 11 926–11 931, 2017.
- [25] —, “Team optimal decentralized state estimation,” in *2018 IEEE Conference on Decision and Control (CDC)*. IEEE, 2018, pp. 5044–5050.
- [26] P. Rusmevichientong and B. Van Roy, “Decentralized decision-making in a large team with local information,” *Games and Economic Behavior*, vol. 43, no. 2, pp. 266–295, 2003.
- [27] D. Gamarnik, D. A. Goldberg, and T. Weber, “Correlation decay in random decision networks,” *Mathematics of Operations Research*, vol. 39, no. 2, pp. 229–261, 2014.
- [28] J. N. Tsitsiklis, D. P. Bertsekas, and M. Athans, “Distributed asynchronous deterministic and stochastic gradient optimization algorithms,” *IEEE Transactions on Automatic Control*, vol. 31, no. 9, pp. 803–812, Sep. 1986.
- [29] J. P. Hespanha, P. Naghshtabrizi, and Y. Xu, “A survey of recent results in networked control systems,” *Proceedings of the IEEE*, vol. 95, no. 1, pp. 138–162, Jan. 2007.
- [30] J. Arbelaz, B. Bamieh, A. E. Hosoi, and A. Jadbabaie, “Optimal estimation in spatially distributed systems: How far to share measurements from?” *IEEE Transactions on Automatic Control*, vol. 70, no. 5, pp. 3226–3239, 2025. [Online]. Available: <https://doi.org/10.1109/TAC.2024.3504257>
- [31] C. Langbort and V. Gupta, “Minimal interconnection topology in distributed control design,” *SIAM Journal on Control and Optimization*, vol. 48, no. 1, pp. 397–413, 2009.

- [32] N. Matni, “Communication delay co-design in $\mathcal{H}_2$ -distributed control using atomic norm minimization,” *IEEE Transactions on Control of Network Systems*, vol. 4, no. 2, pp. 267–278, Jun. 2017.
- [33] R. D. Yates, Y. Sun, D. R. Brown, S. K. Kaul, E. Modiano, and S. Ulukus, “Age of information: An introduction and survey,” *IEEE Journal on Selected Areas in Communications*, vol. 39, no. 5, pp. 1183–1210, 2021.
- [34] Y. Sun, E. Uysal-Biyikoglu, R. D. Yates, C. E. Koksal, and N. B. Shroff, “Update or wait: How to keep your data fresh,” *IEEE Transactions on Information Theory*, vol. 63, no. 11, pp. 7492–7508, 2017.
- [35] M. K. C. Shisher, Y. Sun, and I.-H. Hou, “Timely communications for remote inference,” *IEEE/ACM Transactions on Networking*, vol. 32, no. 5, pp. 3824–3839, 2024.
- [36] M. K. C. Shisher, V. Tripathi, M. Chiang, and C. G. Brinton, “AoI-based scheduling of correlated sources for timely inference,” *IEEE Transactions on Networking*, vol. 34, pp. 2181–2195, 2026.
- [37] A. Li, S. Wu, G. C. F. Lee, and S. Sun, “From freshness to effectiveness: Goal-oriented sampling for remote decision making,” *IEEE Transactions on Information Theory*, vol. 72, no. 4, pp. 2237–2276, Apr. 2026. [Online]. Available: <https://doi.org/10.1109/TIT.2026.3663678>
- [38] M. Aoki, “Horizontal vs. vertical information structure of the firm,” *The American Economic Review*, vol. 76, no. 5, pp. 971–983, 1986.
- [39] R. Radner, “The organization of decentralized information processing,” *Econometrica: Journal of the Econometric Society*, vol. 61, no. 5, pp. 1109–1146, 1993.
- [40] P. Bolton and M. Dewatripont, “The firm as a communication network,” *The Quarterly Journal of Economics*, vol. 109, no. 4, pp. 809–839, 1994.
- [41] T. Van Zandt, “Real-time decentralized information processing as a model of organizations with boundedly rational agents,” *The Review of Economic Studies*, vol. 66, no. 3, pp. 633–658, 1999.
- [42] W. Dessein and T. Santos, “Adaptive organizations,” *Journal of Political Economy*, vol. 114, no. 5, pp. 956–995, 2006.
- [43] P. Aghion and J. Tirole, “Formal and real authority in organizations,” *Journal of Political Economy*, vol. 105, no. 1, pp. 1–29, 1997.
- [44] W. Dessein, “Authority and communication in organizations,” *The Review of Economic Studies*, vol. 69, no. 4, pp. 811–838, 2002.
- [45] N. Cressie, “The origins of kriging,” *Mathematical Geology*, vol. 22, no. 3, pp. 239–252, 1990.
- [46] J. Besag, “Spatial interaction and the statistical analysis of lattice systems,” *Journal of the Royal Statistical Society: Series B (Methodological)*, vol. 36, no. 2, pp. 192–225, 1974.
- [47] S. Chen, R. Varma, A. Sandryhaila, and J. Kovačević, “Discrete signal processing on graphs: Sampling theory,” *IEEE Transactions on Signal Processing*, vol. 63, no. 24, pp. 6510–6523, 2015.

- [48] N. Perraudin and P. Vandergheynst, “Stationary signal processing on graphs,” *IEEE Transactions on Signal Processing*, vol. 65, no. 13, pp. 3462–3477, Jul. 2017.
- [49] S. Moeller and B. Krishnamachari, “TINA: Reproduction package for “a theory of information architecture for networked decisions”,” GitHub repository, 2026, source code, data, figures, and manuscript materials. [Online]. Available: <https://github.com/ANRGUSC/TINA>