Banksy: Evidence-Gated Repair of Garbled Text in AI-Generated Videos

Anonymous CVPR submission

Paper ID *****




Figure 1. **Repairing garbled text in generated videos.** A generative video text editor rewrites the text region and often produces plausible but wrong characters (a, b) or breaks text that was already correct (c). Banksy edits only when evidence supports it, writes the target string deterministically, and leaves everything outside the text untouched. Below each crop: the transcription of frame 24 by the evaluation reader (✓ correct, ✗ wrong). Right: headline numbers on our 526-clip benchmark (Sec. 5.1). Examples (a, b) were chosen among clips where SteerVTE fails and Banksy succeeds; (c) is the only clip among the 46 that Banksy leaves untouched which SteerVTE breaks.

Abstract

Text-to-video generators still render garbled text on signs, screens and posters. We study repair*: given a generated clip, a target string and a hint box, make the text read correctly and leave everything else as it was. Generative video text editors produce natural glyphs but keep or invent wrong characters, rewrite text that was already correct, and re-render the background. Banksy is a training-free, correctness-first pipeline built around three evidence gates: a preservation gate leaves a clip untouched when multi-frame OCR already reads the target; a localization gate lays the new text out on the old glyph instance when the evidence is strong and falls back to the tracked box otherwise; and an appearance gate enables a non-parametric source appearance transport (SAT) that carries glow and material from the old glyphs to the new ones only where it measurably helps. The target is rendered deterministically, so its spelling cannot drift, and only pixels inside the text region change. On 526 generated clips over seven carrier materials in English and Chinese, Banksy reaches 91.4% readability against 84.0% for the state-of-the-art editor SteerVTE (198 vs. 159 net repairs; a pre-registered second reader confirms the advantage) and keeps the background intact (42.5 vs. 36.5 dB PSNR outside the text). Raters preferred SAT over plain pasting for material fidelity in 87% of non-tied judgements. We report, with pre-registered criteria, what did not work—a learned 1.3B refiner, two appear-*

ance modules, a glyph-locked material generator and reconstruction without any source glyph—and characterise the appearance gap to generative editing that remains.

1. Introduction

Text-to-video models such as Wan [29], CogVideoX [39] and VACE [15] synthesise convincing street scenes, shop fronts and screens, yet the text inside them is often garbled: a record shop reads ROCRDS, a convenience store reads 便刻台 (Fig. 1). In our benchmark of generated clips, only 53.8% of the target strings are rendered correctly. Wherever the text carries meaning, a single wrong character is a hard failure, and re-generating the clip until the text comes out right is expensive and changes the shot. We therefore study *repair*: keep the generated clip, and make its text read correctly.

The natural tool is a generative video text editor, which regenerates the text region conditioned on rendered glyphs and the source style. On generated videos we observe three systematic problems. Such editors write characters that look plausible but are wrong—FRESY BREAD, 小心坍滑—and the strongest of them, SteerVTE [40], still leaves 16% of our clips unreadable. They rewrite text that was already correct (FRESH BREAD → FRECH BREAD, Fig. 1c). And because the whole clip passes through the generator, the background changes too: PSNR outside the text region drops to 36.5 dB.

We argue that repair should be correctness-first and minimal: do not change what is already right; when a change is needed, change only the text; and recover the material of the old text only when there is evidence that this helps. Banksy implements this order with three evidence gates (Sec. 4). A preservation gate returns the clip unchanged when OCR on many frames already reads the target. A localization gate decides whether the new text can be laid out on the old glyph instance—its size, colour and baseline—or must fall back to filling the tracked box. An appearance gate decides whether to apply source appearance transport (SAT), a non-parametric operator that carries glow and material from the old glyphs to the new ones. Between the gates the target is rendered deterministically from a matched font and warped with carrier homographies, so its spelling cannot drift, and only pixels inside the text region are composited. Nothing is trained.

On 526 generated clips covering seven carrier materials in English and Chinese, Banksy raises readability from 53.8% to 91.4% (SteerVTE: 84.0%), with 198 net repairs against 159, and keeps the background intact (42.5 dB). We are equally explicit about what it does not do: its glyphs are rendered, not generated, and where both methods repair a clip, SteerVTE's text is closer to the original appearance in 70% of the cases. We trace this gap to its causes and report the alternatives we tried and rejected under pre-registered criteria.

Our contributions are: **(i)** a repair task, a 526-clip benchmark and a protocol whose metrics separate repairs from breakages, measure background fidelity and temporal stability, and are complemented by blind human studies and a pre-registered second reader; **(ii)** Banksy, a training-free, evidence-gated pipeline with deterministic rendering anchored to the tracked carrier and SAT behind an appearance gate; **(iii)** an analysis with negative results—a learned 1.3B refiner, two appearance modules, a glyph-locked material generator and a carrier-grounded branch for inputs without any source glyph, each judged by criteria fixed before the run—and a verified selection between Banksy and SteerVTE that reaches 96.4% readability with 0 broken clips (Sec. 5.6). The full experimental record, including every pre-registration and all audits, is in the supplementary material.

2. Related work

Scene text editing. Early editors decompose a text image into background, style and content and re-synthesise it with GANs [16, 25, 26, 34]; diffusion models brought text rendering and editing to arbitrary images through glyph conditioning [4, 14, 20, 30–32, 38, 41, 46]. Their glyphs are natural, but spelling remains a sampling outcome, and frame-wise application to video flickers. A related line renders text first and harmonises it afterwards [35, 42]; our learned refiner (Sec. 5.5) belongs to it.

Text in generated and edited videos. Text-to-video models render legible text only occasionally [11, 12, 33, 43, 48]; generation-time remedies condition on glyphs [18] or fine-tune on text-rich clips [21] but do not repair a given clip. For editing, SteerVTE [40] injects glyph features and a VLM style embedding into a frozen VACE backbone trained on a million triplets; VidScribe [45] and ViTeX-Bench [5] evaluate video text editing, including commercial models, and find edits that corrupt text that should not change. A concurrent editor [44] warps rendered target glyphs into the text box of every frame as a per-frame reference for a video diffusion model and supervises it with a frozen recognizer, and releases VTEdit, 288 real clips for text replacement and addition; like SteerVTE it regenerates the text region, whereas we place rendered glyphs deterministically on the tracked carrier and gate every edit on evidence. All of these regenerate the text region. We repair generated text with a training-free pipeline that leaves correct text untouched, writes the target deterministically and changes only the text region, and compare against SteerVTE as the strongest editor.

Text effects, inpainting, evaluation. Example-based text effects transfer keys appearance on the distance to the glyph boundary [24, 36, 37]; SAT fits such an operator on the old glyphs of the same video and gates its use on measured gain. We remove the old text with LaMa [28] once per clip and propagate along the tracked carrier rather than inpainting every frame [3, 47], and we test a carrier-anchored attention bias in the spirit of flow-guided attention [6, 10] on the refiner. Text is scored by OCR [1, 7, 27] and, increasingly, by vision-language models [2]; we use a VLM reader for evaluation and a separate OCR inside the pipeline.

3. Task, benchmark and metrics

Task. The input is a generated clip V, a target string s and a hint box b marking where the text is; in our benchmark s is the quoted sign text of the generation prompt and b comes from OCR localisation and tracking of the generated text, and the same box is given to every method (SteerVTE uses it as its editing mask). The output is a clip $\hat{V}$ of the same size and length in which the text inside b reads s and nothing else has changed. Unlike scene text editing, the source text is a near miss produced by the generator, and in about half of the clips it is already correct, so "do nothing" is often the right answer.

Benchmark. We generated clips of street scenes, shop fronts and screens with VACE-14B [15] from 120 prompts that ask for a specific sign text on one of seven carrier materials, ten seeds each (832×464, 49 frames, 15 fps). From 1,178 usable clips an OCR screen selected 526 as garbled; the screen is stricter than our evaluation reader, which judges 53.8% of them correct, so the benchmark contains both repair and do-nothing cases. The clips cover 40 target strings (20 English, 20 Chinese) and seven materials: neon (93), signboard (86), paper (96), glass (76), screen (65), metal (56) and wood (54); 295 are English and 231 Chinese. Forty clips inspected during development are listed in the supplement and excluded in a separate report.

3.1. Metrics

Readability. A vision-language reader, Qwen2.5-VL-7B [2], transcribes the text inside the hint box on 5 frames; a clip is *correct* if at least 4 transcriptions match the target exactly (after normalising whitespace, case and traditional/simplified Chinese). The reader is independent of Banksy, whose gates use a different OCR. All compared outputs are read in one job and one software environment, and a second reader from another model family re-reads the main comparison (Sec. 5.1). **Repairs and breakages.** We count *fixed* (garbled → correct) and *broken* (correct → wrong) clips and their difference, the *net* repairs. **Locality.** *BG PSNR* is computed outside the dilated hint box over all frames; *collateral change* is the grey-level change inside the text neighbourhood but outside both the old and the new glyphs (it needs the method's glyph mask, so it is reported for Banksy only). **Appearance.** On three frames we compare, in CIELAB, the ink colour, ink–ground contrast, halo, edge softness and stroke shading of each output with those of the original glyphs, each normalised by its median over the evaluation run; lower is closer, values are comparable only within one run, and the unseeded ink segmentation gives a test–retest noise of 0.47 per clip, so we interpret only differences well above it. **Temporal stability.** With the carrier motion estimated once on the original and applied to every output, *flicker* is the motion-compensated grey-level change inside the box, *jitter* the same for gradient magnitudes, and *boundary jump* the change at the chunk boundaries of a chunked model. **Human judgements** come from blind pairwise studies with the original shown between two versions in random order and separate questions per quality (supplement). Full definitions are in the supplementary material, Sec. A.

4. Banksy

Banksy takes a clip $V = \{I_t\}_{t=1}^{T}$, a target s and a hint box b and returns a clip that differs from V only inside the text region (Fig. 2). All components are classical or pre-trained; nothing is trained for the task. Thresholds and implementation details are in the supplementary material, Sec. A.

Reading the text and tracking its carrier. An off-the-shelf OCR system (EasyOCR [13]: CRAFT [1], CRNN [27]) runs on every frame; boxes overlapping b are grouped into rows, and the frame whose rows best match s becomes the reference frame $t^{\star}$. The text sits on a physical *carrier*—a sign, a poster, a screen—so we track the carrier rather than the glyphs: SIFT keypoints [22] around the reference quad are matched to every frame and a RANSAC homography H_t [9] is estimated, with the quad-to-quad homography of the OCR boxes as fallback. Everything placed on the carrier later—erased background, glyphs, masks—is placed once in $I_{t^{\star}}$ and carried to frame t by H_t, which removes the per-frame jitter of OCR boxes from the output.

Preservation gate. Generated text is often already correct, and an edit can only make such a clip worse. The gate returns $\hat{V} = V$ when the pipeline's OCR reads the complete target in at least 85% of the frames, inside the hint box, with wrong readings in at most 5% of the frames and with the concatenated reading of all boxes inside the box equal to s (which prevents skipping when the target appears next to other, garbled text). It never consults the evaluation reader, and it trades recall for safety: in the final run it skips 46 of the 526 clips, all confirmed correct by the independent




Figure 2. **Banksy framework and the scope of this paper.** Text analysis reads and tracks the text and its carrier; the preservation gate returns the clip unchanged when the text already reads the target; otherwise the evidence available decides between repairing the existing text (B1) and glyph-free reconstruction (G); local erasure and a region-constrained compositor keep every edit inside the allowed region. *Status:* every result reported in this paper is produced by the frozen B1 path, whose only appearance step is the non-parametric source appearance transport; nothing is trained. G (v4.1) is under a sealed cross-generator test and is not part of the reported results; the trainable material synthesis (M) is a negative result (Sec. 5.5); the semantic evidence module (S), the evidence router and the verification loop are planned.

reader.

Localization gate and layout. If the old glyphs can be localised reliably, the new text inherits their size, colour and baseline. We estimate a glyph *instance* in the reference frame—ink mask, ink and ground colours, letter height, number of letters, letter band—and accept it only with at least three letters (two for Chinese), an ink–ground contrast above 40 in CIELAB, a letter height between 0.3 and 1.0 of the OCR box height and a regular row grouping. Otherwise the clip takes the *box layout*, which fills the tracked box with legible text; in the final run, 168 of the 480 edited clips (35%) do. With an accepted instance the target is laid out on the letter band at the measured letter height, in the string's natural aspect ratio, centred on the old text; stacked text keeps its rows.

Erasure and deterministic rendering. The old glyphs are removed once, in the reference frame: the ink mask (extended by the bright pixels of glowing text) is dilated, flat grounds are pre-filled with their median colour, and the hole is inpainted with LaMa [28]; the erased background is carried to every frame by H_t with a per-frame gain fitted on a ring around the hole, so exposure changes follow without inpainting flicker. The font is chosen from a library of 33 Latin and 8 Chinese families by comparing stroke statistics of the warped old ink mask with each candidate rendered in the same layout, and the target is drawn by a font rasteriser, so its spelling is exact by construction. Its colour follows the per-frame ink colour of the old text modulated by a low-frequency shading field estimated from the old strokes; glowing text receives a soft halo; the canvas is warped to every frame with H_t and composited over the erased background.

Appearance gate and source appearance transport. On emissive carriers—neon, lightboxes, screens—the old glyphs carry glow, bloom and inner structure that a flat fill cannot reproduce. SAT transports this appearance from the old glyphs to the new ones without regenerating the region. Let B be the erased background, I the reference frame and $d(x)$ the signed distance of pixel x to the boundary of the old glyphs in units of the letter height. On the old text we fit, per distance bin k and per channel, a multiplicative-plus-additive light-transport operator

$$I(x) \approx m_k\, B(x) + a_k, \qquad k = k(d(x)), \tag{1}$$

over the support $d \leq 0.6$, and apply it to the new glyphs with their own distance field, $\hat{I}(x) = m_{k(\hat{d}(x))}B(x) + a_{k(\hat{d}(x))}$. On the old text this family reconstructs the source better than an additive-only operator, a distance-indexed replacement or a flat fill (cross-validated CIELAB error 17.2 vs. 25.9, 27.6 and 29.7; supplement). SAT is applied only behind an *appearance gate*: the text must be emissive and the operator must generalise across the text—fitted on one half and tested on the other, in both directions, with an error below 0.75 of the flat-fill error. In the final run SAT is enabled on 50 clips (10%), never on box-layout clips.

Compositing. The output differs from the input only where the erasure mask or the new glyphs (with halo) are non-zero; elsewhere the input pixels are copied, so the only residual outside the text region is the re-encoding of the video.

5. Experiments

Protocol. Table 1 and every number in Secs. 5.1, 5.2 and 5.5 come from one front-end pass over the 526 clips with the final system and its registered variants, read together with the original clips and SteerVTE's outputs in one evaluation job (Sec. 3.1). Every other table comes from its own pass and its own evaluation run; because the appearance distance is normalised within a run, it is compared only within a table. Paired differences carry 95% bootstrap CIs over clips (10,000 resamples) [8] and readability differences exact McNemar tests [23]. Table 1 reports all clips and, separately, the 486 clips never inspected during development. **Baseline.** SteerVTE [40], the strongest published video text editor (glyph and style conditioning on a frozen VACE-14B backbone, one million training triplets), is run with the hint box as editing mask and the target as text at the input's resolution and length.

5.1. Main results

Banksy makes 91.4% of the clips readable, 7.4 points more than SteerVTE (70 clips correct only with Banksy, 31 only with SteerVTE; $p = 1.3 \times 10^{-4}$), and repairs 210 of the 243 garbled clips. It breaks 12 of the 283 originally correct clips where SteerVTE breaks 6, so its advantage in net repairs (198 vs. 159) is smaller than in repairs alone; the picture is unchanged outside the development set (91.2% vs. 84.4%). The two methods trade different qualities: Banksy leaves the background intact (PSNR 6.0 dB higher, 95% CI [5.8, 6.3]) and its strokes jitter less (7.86 vs. 8.30), because every glyph is placed once on the tracked carrier; SteerVTE's region flickers less and, above all, its text looks more like the original (appearance distance 1.83 vs. 2.57), a gap we analyse in Sec. 6. Banksy is ahead on all seven materials, most on signboards (+15.1 points) and neon (+8.6), least on metal (+1.8) and wood (+1.9), and reaches 91.5% on English and 91.3% on Chinese clips (SteerVTE: 84.1%, 84.0%). Figure 3 shows random examples, including two failures of Banksy.

A second reader. Readability depends on the reader, so we registered a re-reading of the outputs by readers from other model families with identical crops, frames, prompt, decoding and scoring, and a rule fixed in advance: the advantage counts as reader-robust only if InternVL2.5-8B finds Banksy more readable than SteerVTE with $p < 0.05$. It does: 84.8% against 78.7% (74 vs. 42 discordant clips, $p = 3.8 \times 10^{-3}$), with a smaller margin that is significant for Chinese ($p = 0.02$) but not for English alone. A third reader, Pixtral-12B, cannot read Chinese and finds no advantage on the English clips (77.6% vs. 80.3%); most of its errors on Banksy's outputs are correct transcriptions followed by invented text, which exact matching counts as wrong. Full tables are in the supplement, Sec. B.

Edit locality. SteerVTE's difference to the original covers the entire frame, including edges far from the text; Banksy's is confined to the text region, with a residual of 1–2 grey levels elsewhere from re-encoding. Inside the text neighbourhood, the collateral change outside both old and new glyphs is 1.68 grey levels on the 480 clips Banksy edits.

5.2. The evidence gates

Preservation gate. The gate skips 46 clips, all confirmed correct by the reader (no false skip; the registered limit was 2%). In the selective-editing pass (Sec. 5.4) it is the only difference between B0 and B1: it restores 2 of the 16 originally correct clips that B0 breaks and loses none. Its recall is low by design: the pipeline's OCR rarely reads stylised originals—neon italics, extruded or condensed letters—consistently enough, and all 12 clips Banksy breaks are such cases (Sec. 6).

Carrier anchoring, font matching, localization gate. Pasting the target into the per-frame OCR box makes the text readable but nearly doubles flicker (3.12 vs. 1.98 for the original), because OCR boxes jitter; anchoring everything on the tracked carrier brings it to the level of SteerVTE (1.67 vs. 1.66) with lower jitter (7.12 vs. 8.30) and unchanged readability. Matching the font to the old strokes adds 2.6 points of readability ($p = 0.044$) once candidates are rendered in the layout of the original. Laying the text out on the glyph instance leaves half as much of the old ink visible as the box layout (residual 0.21 vs. 0.42) but, with a confidence-based tracker, cost 5.5 points of readability; carrier tracking recovers most of it, and the localization gate routes the unreliable instances to the box layout, giving a front end as readable as the box layout (91.1 vs. 90.7) with

Table 1. **Main results** (526 clips; one front-end pass and one evaluation job for every row). Readability: share of clips whose text the reader transcribes exactly in at least 4 of 5 frames. Fixed / broken: garbled → correct and correct → wrong transitions relative to the original as read in the same job; net = fixed − broken. Appearance: glyph-agnostic material distance to the original text (normalised within this run; lower is closer). BG PSNR: outside the dilated text region. Flicker and jitter: motion-compensated, inside the text box (grey levels). The lower block excludes the 40 clips inspected while developing the selective-editing components.

	Readability ↑	Fixed ↑	Broken ↓	Net ↑	NED sim. ↑	Appearance ↓	BG PSNR ↑	Flicker ↓	Jitter ↓
All 526 clips									
Original (generated)	53.8	–	–	–	0.820	–	–	1.98	9.18
SteerVTE [40]	84.0	165	**6**	159	0.946	**1.83**	36.49	**1.66**	8.30
Banksy	**91.4**	**210**	12	**198**	**0.959**	2.57	**42.52**	1.79	**7.86**
486 clips outside the development set									
Original (generated)	54.7	–	–	–	0.822	–	–	1.97	9.12
SteerVTE [40]	84.4	150	**6**	144	0.945	**1.85**	36.40	**1.65**	8.24
Banksy	**91.2**	**189**	12	**177**	**0.958**	2.60	**42.50**	1.79	**7.86**




Figure 3. **Qualitative comparison on randomly sampled clips** (two of the four materials of the full figure in the supplement, Sec. B) (one English and one Chinese clip per material, drawn with a fixed seed among garbled originals outside the development set; not curated). Each cell is the same crop of frame 24; below it, the reader's transcription (✓ correct, ✗ wrong). SteerVTE produces more natural glyphs but frequently keeps or invents wrong characters; Banksy writes the target but its glyphs often look pasted (see Sec. 6).

the instance path's lower residual and lowest jitter. Two re-readings of the same outputs differ by about one point, so we claim parity, not superiority (supplement, Sec. B).

5.3. Source appearance transport

The appearance gate enables SAT on 53 clips of the analysed pass (23 neon, 11 screen, 9 signboard, 8 metal, 2 wood); most rejections are clips without an accepted instance, non-emissive text, or no cross-validated gain. On the enabled clips SAT reduces the appearance distance by a third (-1.02; better on 42 of 53 clips) for every material—screens 3.02→1.33, neon 3.03→2.02, wood 4.12→2.21—without hurting readability or the background, at a cost in temporal stability (flicker $+0.15$, jitter $+0.81$). Because the distance is only a proxy, we ran a blind study on all 53 clips: raters saw the original between the paste-only and the SAT version in random order and answered three separate questions. With four raters (one excluded by a rule fixed after seeing the data; results with all five are reported too), SAT was judged closer to the original material in 158 of 182 non-tied judgements (win rate 0.87, 95% CI [0.77, 0.94]; 48 vs. 3 clips by majority) and as having fewer artifacts in 147 of 191 (0.77 [0.66, 0.87]). The measured flicker increase was not perceived. The six clips raters judged worse show a bright rectangular plate behind the new letters, which we traced to the canvas truncating the halo's distance field; the fix was diagnosed on these clips and is therefore not part of the evaluated system (supplement, Sec. B and F).

5.4. Selective, structure-preserving editing

The most frequent problem of an early Banksy was not missing material but changing things it should not have. We therefore tested, with criteria fixed before the run, three components added to B0 (Banksy without the preservation gate): the preservation gate (B1), glyph-only erasure (B2) and a carrier-fit check that declares a target layout-infeasible (B3). In one front-end pass and one evaluation run, the preservation gate meets its criteria (no false skip, two fewer broken clips, readability not lower) and is adopted, which makes B1 the Banksy of Tab. 1. Glyph-only erasure reduces collateral change on all clips (-0.090, 95% CI $[-0.16, -0.02]$) but not significantly outside the devel-

opment clips, and costs 7.6 points of readability because the instance ink mask is not a complete glyph mask; of 24 clips flagged infeasible, inspection confirmed 5. B2 and B3 are rejected (supplement, Sec. B).

5.5. What did not pass

We report the alternatives we built and rejected; each was judged by criteria fixed before its run, and all details are in the supplement, Sec. C and D.

A learned refiner. A video diffusion transformer initialised from Wan2.1-T2V-1.3B [29], trained as a flow-matching bridge [17, 19] from the pasted clip to the target on Blender renders, 562 real pairs and up to 1.15 million image pairs, does not improve on the paste it starts from: refiners trained with 0, 10k, 100k and 1M image pairs reach 75–78% readability on a garbled subset against 80.7% for the paste, and a diagnostic on 1,500 held-out pairs shows that they move away from the original even on the task they were trained for, because the paste's font and the generator's glyphs make the supervision inconsistent. Glyph-consistent supervision recovers most of the image-domain loss but still does not exceed the paste on video. On the full benchmark the best refiner costs 3.5 points of readability, adds flicker, jitter and chunk seams, and leaves the appearance distance unchanged (-0.035, 95% CI $[-0.21, 0.19]$). The result is specific to our scale (1.3B parameters, a few hundred real video pairs), but at this scale a learned harmoniser trades the guarantee that motivates rendering for a gain we could not measure.

Two appearance modules. Baseline-aligned layout with glyph-matched fonts (B1f) changes the output in 157 and 25 clips respectively and leaves readability unchanged, but its appearance difference ($+0.052$ [$+0.002$, $+0.106$]) fails the registered criterion; the appearance distance is glyph-agnostic, so it cannot see what B1f changes, and we report the criterion unchanged rather than amend it. Reuse of the correctly generated source glyphs (R1), which keeps the right letters in place with their own material and renders only the missing ones, applies to only 7 of the 526 clips with our current segmentation, matching and gating, too few to evaluate. Neither module is part of Banksy.

A glyph-locked material generator. A conditional U-Net in the carrier's UV space, trained on 2,000 Blender counterfactual pairs that differ only in the text, closes 0.48 of the gap between a flat paste and the rendered truth on held-out pairs (registered gate 0.50; a model with 1.8× the parameters, the one registered capacity test, closes 0.498). Applied zero-shot to 129 benchmark clips it fails every registered criterion (appearance distance 3.06 vs. 1.99 for Banksy; 20 readings lost). Under our registered protocol, increasing capacity did not close the synthetic-domain criterion and zero-shot transfer to generated video degraded both appearance and readability; a photometric ablation attributes part of the transfer loss to the renders' photometry and leaves the rest unexplained by it.

Table 2. **Verified selection between Banksy and SteerVTE** (526 clips, one evaluation run; the full table with ablations is in the supplement, Sec. B). Banksy-V keeps the clip when the preservation gate fires, otherwise takes a SteerVTE output whose text an independent verifier (InternVL2.5-8B) reads as the target, composited locally into the original, and falls back to Banksy. W/L: clips correct only with the system / only with Banksy.

	Read. ↑	Broken ↓	Net ↑	W/L	Appear. ↓	BG PSNR ↑
Banksy (B1)	91.8	12	201	–	3.34	42.52
SteerVTE	84.0	5	160	29/70	2.37	36.49
Banksy-V (verified, local)	96.4	0	225	30/6	2.67	41.74
Oracle selection (upper bound)	98.1	0	234	34/1	2.70	41.74

Reconstruction without source glyphs. Banksy's gating assumes that some glyph survives. Classifying the benchmark with the frozen localiser, 455 clips have readable matches, 71 have detectable but unreadable pseudo-text (which Banksy handles through its detection-box fallback at 90.1% readability; SteerVTE: 76.1%), and none lacks a detectable text-like region. To test the case the benchmark does not contain, we registered a branch that lays the target out from the tracked carrier alone and evaluated it on the 455 clips with their glyphs erased: it reads 92.1% of the locatable clips where the frozen code's static-hint fallback reads 81.6% and the deployed configuration writes nothing, but it misses the registered geometry and stability criteria (3 of 6), so the registered verdict is a failure. On the 71 natural pseudo-text clips, an amendment registered after the classes were known reads 98.6% against Banksy's 90.1% ($p = 0.07$) with no clip broken, but the appearance distance rises from 1.56 to 3.06; routing these clips to the branch would raise readability on the benchmark by about one point at that cost. The branch shows a readability gain on inputs that defeat the deployed system; it has not shown that it keeps the material and the stability of Banksy, and it is not part of Banksy.

5.6. Verified selection between Banksy and SteerVTE

The two systems fail on different clips, so a system that could tell which output is right would inherit the readability of both. We registered one before running it, with no tunable threshold: *Banksy-V* keeps the clip when the preservation gate fires; otherwise it runs SteerVTE (seed 1, then a second seed) and accepts an output whose text an independent verifier—InternVL2.5-8B with the reading protocol of Sec. 3.1—transcribes as the target in at least 4 of 5

frames, composited back into the original around the text box with a feathered boundary and a colour match; otherwise it falls back to Banksy. The verifier never scores. In one run over every row (Tab. 2), Banksy-V reads correctly in 96.4% of the clips (30 vs. 6 discordant against Banksy, $p = 7.0 \times 10^{-5}$) with 0 broken clips and 225 net repairs; its appearance distance lies between SteerVTE's and Banksy's, because SteerVTE's text is used wherever it reads correctly, and the background stays local (41.74 dB). It meets five of six registered criteria and misses the temporal one by a margin that we trace to the re-encoding of the composited output (supplement, Sec. B). Banksy-V is a system combination—its material from SteerVTE, its correctness from verification, its locality and fallback from Banksy—and it runs SteerVTE up to twice per clip plus a 7B verifier; a registered blind study of its naturalness against SteerVTE is in progress and is not reported here.

5.7. External benchmarks

On SteerVTE's own VTE-Bench Real (100 real clips whose correct text is to be changed), the frozen Banksy is clearly behind SteerVTE (73.0% vs. 92.0%), partly because its front end does not locate 8 of the source texts and ships those clips unchanged: on correct, well-formed text the gates that make Banksy safe for repair have nothing to protect. On the 29 replacement and translation clips of VidScribe [45] that OCR can locate, Banksy reads 37.9%, ahead of the strongest of seven commercial models (31.0%) without significance and significantly ahead of 3 of them, with the background kept (36.2 dB against 16.7–28.0 dB). We report both to delimit the claim: Banksy is a repair method for garbled generated text, not a general video text editor (supplement, Sec. B).

6. Analysis and limitations

Where Banksy fails. Banksy breaks 12 of the 283 originally correct clips (SteerVTE: 6). In all of them the evaluation reader transcribes the original correctly while the pipeline's OCR reads it in at most 2% of the frames (neon italics, extruded or condensed letters), so the preservation gate cannot fire; the outputs then show new text larger than its sign (4 clips), old text left visible next to the new text (5), wrong colour or contrast on lightboxes (2) or a misread stacked text (1). The more common failure does not affect readability: erasure leaves a visible patch, or the new glyphs are flat where the old ones were outlined, extruded or glowing. These cases explain the appearance distance in Tab. 1.

The appearance gap to generative editing. Among the 145 garbled clips that both methods repair, SteerVTE's text is closer to the original in 70%, so the gap is not an artefact of SteerVTE leaving garbled text untouched. Four causes, in decreasing order of visibility: Banksy renders instead of generating, so it cannot reproduce extrusion, bevels, tube geometry or texture inside the strokes; its font library is small (3 Chinese families are ever selected, and Noto Sans SC alone renders 67% of the edited Chinese clips); its layout inherits the axis-aligned orientation of the OCR quad, so on tilted carriers the text can look skewed; and LaMa's fill is visible as a patch on textured carriers. Two observations suggest that the gap is closable without giving up correctness: the garbled source already contains a median of 88% of the target's letters (Chinese: 67%), so reusing them would extend "change only what is wrong" from words to characters once letter segmentation is reliable; and the two methods fail on different clips (at least one repairs 97.3%), which the verified selection of Sec. 5.6 exploits.

Other limitations. The benchmark comes from one family of generators and asks for short sign texts; long texts are out of scope. Readability is measured by VLM readers, which favour large, high-contrast text and can transcribe a garbled original as the intended word; the second reader confirms the advantage over SteerVTE with a smaller margin, and the third finds the methods level on English once its invented additions are discounted, so we report all of them. The appearance distance is glyph-agnostic and noisy at the clip level; it supports large differences such as the gap to SteerVTE and the effect of SAT, not small ones, and it rewards a constant colour, which is why a flat paste scores well on it. The SAT study used four raters; the blind comparison of Banksy-V with SteerVTE is in progress. The frozen front end is bit-exact within one software environment but not across OpenCV and CUDA versions, where its font matcher and a few OCR decisions diverge (about 3 readability points and 1.4 dB of background PSNR on 71 clips); every comparison in this paper is therefore made within one environment and one evaluation run (supplement, Sec. G). Outside repair, on editing correct text, the frozen system is clearly behind SteerVTE (Sec. 5.7).

7. Conclusion

Repairing garbled text in generated videos is not the same problem as editing text: the source is a near miss, it is often already right, and everything around it should survive. Banksy treats repair as a sequence of evidence-gated decisions—leave the clip alone, lay the text out on the old glyphs or on the tracked box, transport the old appearance or not—around a rendering step whose spelling cannot drift. This makes it more reliable than the strongest generative editor on our benchmark and confines its changes to the text, but its glyphs still look rendered. Our negative results delimit what closing that gap requires: an appearance measure that sees glyph shape and orientation, letter segmentation reliable enough to reuse the characters

the generator drew correctly, and generative edits accepted only when they can be verified—the step that verified selection takes, repairing more clips than either system and breaking none, at the cost of running the generative editor.

References

[1] Youngmin Baek, Bado Lee, Dongyoon Han, Sangdoo Yun, and Hwalsuk Lee. Character region awareness for text detection. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9357–9366, 2019. 3

[2] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, et al. Qwen2.5-VL technical report. arXiv preprint arXiv:2502.13923, 2025. 3

[3] Yuxuan Bian, Zhaoyang Zhang, Xuan Ju, Mingdeng Cao, Liangbin Xie, Ying Shan, and Qiang Xu. VideoPainter: Any-length video inpainting and editing with plug-and-play context control. In *Proceedings of the Special Interest Group on Computer Graphics and Interactive Techniques Conference Conference Papers (SIGGRAPH Conference Papers '25)*. Association for Computing Machinery, 2025. 3

[4] Jingye Chen, Yupan Huang, Tengchao Lv, Lei Cui, Qifeng Chen, and Furu Wei. TextDiffuser: Diffusion models as text painters. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 9353–9387, 2023. 2

[5] Xinghao Chen, Xiangbo Gao, Jiongze Yu, Yuheng Wu, and Zhengzhong Tu. ViTeX-Bench: Benchmarking high-fidelity video scene text editing. arXiv preprint arXiv:2609.40356, 2026. 2

[6] Yuren Cong, Mengmeng Xu, Christian Simon, Shoufa Chen, Jiawei Ren, Yanping Xie, Juan-Manuel Perez-Rua, Bodo Rosenhahn, Tao Xiang, and Sen He. FLATTEN: optical FLow-guided ATTENtion for consistent text-to-video editing. In *International Conference on Learning Representations (ICLR)*, 2024. 3

[7] Yuning Du, Chenxia Li, Ruoyu Guo, Xiaoting Yin, Weiwei Liu, Jun Zhou, Yifan Bai, Zilin Yu, Yehua Yang, Qingqing Dang, and Haoshuang Wang. PP-OCR: A practical ultra lightweight OCR system. arXiv preprint arXiv:2009.09941, 2020. 3

[8] Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman and Hall/CRC, 1994. 5

[9] Martin A. Fischler and Robert C. Bolles. Random sample consensus: A paradigm for model fitting with applications to image analysis and automated cartography. *Communications of the ACM*, 24(6):381–395, 1981. 3

[10] Michal Geyer, Omer Bar-Tal, Shai Bagon, and Tali Dekel. TokenFlow: Consistent diffusion features for consistent video editing. In *International Conference on Learning Representations (ICLR)*, 2024. 3

[11] Xuyang Guo, Jiayan Huo, Zhenmei Shi, Zhao Song, Jiahao Zhang, and Jiale Zhao. T2VTextBench: A human evaluation benchmark for textual control in video generation models. arXiv preprint arXiv:2505.04946, 2025. 2

[12] Yu Huang, Jungang Li, Zhiyuan Wang, Yonghua Hei, Song Dai, Jiayu Yang, Deyuan Liu, Xiang Zheng, Xiaoshuang Shi, Hao Cheng, and Kaidi Xu. VTR-Bench: A systematic benchmark for evaluating visual text rendering in video generation. arXiv preprint arXiv:2610.01499, 2026. 2

[13] JaidedAI. EasyOCR. `https://github.com/JaidedAI/EasyOCR`, 2020. 3

[14] Jiabao Ji, Guanhua Zhang, Zhaowen Wang, Bairu Hou, Zhifei Zhang, Brian L. Price, and Shiyu Chang. Improving diffusion models for scene text editing with dual encoders. *Transactions on Machine Learning Research*, 2024. 2

[15] Zeyinzi Jiang, Zhen Han, Chaojie Mao, Jingfeng Zhang, Yulin Pan, and Yu Liu. VACE: All-in-one video creation and editing. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 17191–17202, 2025. 2, 3

[16] Praveen Krishnan, Rama Kovvuri, Guan Pang, Boris Vassilev, and Tal Hassner. TextStyleBrush: Transfer of text aesthetics from a single example. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(7):9122–9134, 2023. 2

[17] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. In *International Conference on Learning Representations (ICLR)*, 2023. 7

[18] Lin Liu, Quande Liu, Shengju Qian, Yuan Zhou, Wengang Zhou, Houqiang Li, Lingxi Xie, and Qi Tian. Text-Animator: Controllable visual text video generation. arXiv preprint arXiv:2406.17777, 2024. 2

[19] Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. In *International Conference on Learning Representations (ICLR)*, 2023. 7

[20] Zeyu Liu, Weicong Liang, Zhanhao Liang, Chong Luo, Ji Li, Gao Huang, and Yuhui Yuan. Glyph-ByT5: A customized text encoder for accurate visual text rendering. In *Computer Vision – ECCV 2024*, pages 361–377. Springer Nature Switzerland, 2024. 2

[21] Ziyang Liu, Kevin Valencia, and Justin Cui. Video text preservation with synthetic text-rich videos. arXiv preprint arXiv:2511.05573, 2025. 2

[22] David G. Lowe. Distinctive image features from scale-invariant keypoints. *International Journal of Computer Vision*, 60(2):91–110, 2004. 3

[23] Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947. 5

[24] Yifang Men, Zhouhui Lian, Yingmin Tang, and Jianguo Xiao. DynTypo: Example-based dynamic text effects transfer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 5863–5872, 2019. 3

[25] Yadong Qu, Qingfeng Tan, Hongtao Xie, Jianjun Xu, Yuxin Wang, and Yongdong Zhang. Exploring stroke-level modifications for scene text editing. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, pages 2119–2127, 2023. 2

[26] Prasun Roy, Saumik Bhattacharya, Subhankar Ghosh, and Umapada Pal. STEFANN: Scene text editor using font

adaptive neural network. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13225–13234, 2020. 2

[27] Baoguang Shi, Xiang Bai, and Cong Yao. An end-to-end trainable neural network for image-based sequence recognition and its application to scene text recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 39(11):2298–2304, 2017. 3

[28] Roman Suvorov, Elizaveta Logacheva, Anton Mashikhin, Anastasia Remizova, Arsenii Ashukha, Aleksei Silvestrov, Naejin Kong, Harshith Goka, Kiwoong Park, and Victor Lempitsky. Resolution-robust large mask inpainting with Fourier convolutions. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 2149–2159, 2022. 3, 4

[29] Team Wan, Ang Wang, Baole Ai, Bin Wen, Chaojie Mao, Chen-Wei Xie, et al. Wan: Open and advanced large-scale video generative models. arXiv preprint arXiv:2503.20314, 2025. 2, 7

[30] Yuxiang Tuo, Yifeng Geng, and Liefeng Bo. AnyText2: Visual text generation and editing with customizable attributes. arXiv preprint arXiv:2411.15245, 2024. 2

[31] Yuxiang Tuo, Wangmeng Xiang, Jun-Yan He, Yifeng Geng, and Xuansong Xie. AnyText: Multilingual visual text generation and editing. In *International Conference on Learning Representations (ICLR)*, 2024.

[32] Tong Wang, Ting Liu, Xiaochao Qu, Chengjing Wu, Luoqi Liu, and Xiaolin Hu. GlyphMastero: A glyph encoder for high-fidelity scene text editing. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 28523–28532, 2025. 2

[33] Junfeng Wu, Dongliang Luo, Weizhi Zhao, Zhihao Xie, Yuanhao Wang, Junyi Li, Xudong Xie, Yuliang Liu, and Xiang Bai. TokBench: Evaluating your visual tokenizer before visual generation. arXiv preprint arXiv:2505.18142, 2025. 2

[34] Liang Wu, Chengquan Zhang, Jiaming Liu, Junyu Han, Jingtuo Liu, Errui Ding, and Xiang Bai. Editing text in the wild. In *Proceedings of the 27th ACM International Conference on Multimedia*, pages 1500–1508. Association for Computing Machinery, 2019. 2

[35] Zexuan Yan, Jiarui Jin, Yue Ma, Shijian Wang, Jiahui Hu, Wenxiang Jiao, Yuan Lu, and Linfeng Zhang. GlyphBanana: Advancing precise text rendering through agentic workflows. arXiv preprint arXiv:2603.12155, 2026. 2

[36] Shuai Yang, Jiaying Liu, Zhouhui Lian, and Zongming Guo. Awesome typography: Statistics-based text effects transfer. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2886–2895, 2017. 3

[37] Shuai Yang, Jiaying Liu, Wenjing Wang, and Zongming Guo. TET-GAN: Text effects transfer via stylization and destylization. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, pages 1238–1245, 2019. 3

[38] Yukang Yang, Dongnan Gui, Yuhui Yuan, Weicong Liang, Haisong Ding, Han Hu, and Kai Chen. GlyphControl: Glyph conditional control for visual text generation. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 44050–44066, 2023. 2

[39] Zhuoyi Yang, Jiayan Teng, Wendi Zheng, Ming Ding, Shiyu Huang, Jiazheng Xu, Yuanming Yang, Wenyi Hong, Xiaohan Zhang, Guanyu Feng, Da Yin, Yuxuan Zhang, Weihan Wang, Yean Cheng, Bin Xu, Xiaotao Gu, Yuxiao Dong, and Jie Tang. CogVideoX: Text-to-video diffusion models with an expert transformer. In *International Conference on Learning Representations (ICLR)*, 2025. 2

[40] Kai Zeng, Moran Li, Zhengwei Wang, Yingchen Yu, Yiheng Lin, Ruichuan An, Ming Lu, Qi She, and Wentao Zhang. SteerVTE: Seamless video text editing with style and glyph control. arXiv preprint arXiv:2606.23254, 2026. 1, 2, 5, 6

[41] Weichao Zeng, Yan Shu, Zhenhang Li, Dongbao Yang, and Yu Zhou. TextCtrl: Diffusion-based scene text editing with prior guidance control. In *Advances in Neural Information Processing Systems (NeurIPS)*, pages 138569–138594, 2024. 2

[42] Fangneng Zhan, Hongyuan Zhu, and Shijian Lu. Spatial fusion GAN for image synthesis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3648–3657, 2019. 2

[43] Ruiqiang Zhang, Hengyi Wang, Chang Liu, Guanjie Wang, Zehua Ma, and Weiming Zhang. TextVBench: Evaluating text rendering and preservation in video generation. arXiv preprint arXiv:2610.13412, 2026. 2

[44] Shulian Zhang, Xiangyu Shu, Wenbo Li, Jian Chen, and Yong Guo. Enhanced video text editing with trajectory-aligned glyph rendering, 2026. arXiv:2609.34178. 2

[45] Ziying Zhang, Litao Li, Junchao Liao, Tianyi Zeng, Siyu Zhu, Long Qin, and Zhenghao Zhang. Beyond legibility: Benchmarking visual text rendering and in-place editing in unified video generation. arXiv preprint arXiv:2609.36598, 2026. 2, 8

[46] Yiming Zhao and Zhouhui Lian. UDiffText: A unified framework for high-quality text synthesis in arbitrary images via character-aware diffusion models. In *Computer Vision – ECCV 2024*, pages 217–233. Springer Nature Switzerland, 2024. 2

[47] Shangchen Zhou, Chongyi Li, Kelvin C. K. Chan, and Chen Change Loy. ProPainter: Improving propagation and transformer for video inpainting. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 10477–10486, 2023. 3

[48] Ziwei Zhou, Zeyuan Lai, Rui Wang, Yifan Yang, Yuqing Yang, Qi Dai, Lili Qiu, and Chong Luo. AVGen-Bench: A task-driven benchmark for multi-granular evaluation of text-to-audio-video generation. In *Proceedings of the 43rd International Conference on Machine Learning (ICML)*, pages 165095–165114. PMLR, 2026. 2

LLM usage statement

Large language models were used as assistants for writing and editing the text of this paper, for drafting experiment scripts, and for summarising evaluation outputs. The task definition, the method, the pre-registered criteria, the experiments and their interpretation are the authors' own; every number in the paper is generated from the evaluation

files of the stated runs, and the authors verified the claims against those files. Vision-language models are also used as components of the evaluation (readers) and of the verified-selection system, as described in the paper.