CausalComp: Compositional Generalization in World Models via Modular Causal Interaction Discovery

Anonymous Author(s)
Affiliation
Address
email

Abstract

Compositional generalization is a central challenge for object-centric world models: a model should predict the dynamics of novel object combinations by reusing mechanisms learned from previously observed interactions. While learned interaction graphs provide an appealing structure for such models, it remains unclear whether graph discovery alone is sufficient to prevent pair-specific memorization. We study this question through CAUSALCOMP, a controlled world-modeling framework that factorizes object dynamics into learned causal interactions and type-specific transition modules. Given object states, CAUSALCOMP first infers an interaction graph and assigns each edge to a latent interaction type. It then routes each interaction message through the corresponding type-specific dynamics module. This encourages each interaction type to share one transition mechanism across different object pairs. Across five physics environments, including NRI Springs and two Physion scenarios, we find that high-capacity single-module and attention-based models achieve lower absolute prediction error on seen distributions, but exhibit substantially larger seen–unseen gaps, with the graph-matched single-module ablation reaching a 75% compositional gap on SimplePhysics. In contrast, typed interaction modules reduce the compositional gap by 31–34% relative to the graph-matched single-module ablation in the two multi-interaction settings. Representation and capacity analyses further suggest that this effect is not explained solely by reduced model capacity. These results do not establish state-of-the-art prediction accuracy; instead, they provide empirical evidence that type-specific modular dynamics can serve as a useful inductive bias for compositional transfer in object-centric world models.

1 Introduction

World models are internal simulators that predict how environments evolve over time and are central to planning and decision-making [Ha and Schmidhuber, 2018, LeCun, 2022, Hafner et al., 2025]. A key challenge for such models is compositional generalization. A useful world model should predict the dynamics of object combinations that were never observed during training by reusing mechanisms learned from previously seen interactions. This requirement is natural in physical environments, where a small set of interaction mechanisms, such as collision, gravity, and friction, combine with a large space of object properties to produce many possible scenarios. Models that memorize specific object combinations may fit the training distribution well, but are unlikely to generalize to this long tail of novel combinations.

Prior work on object-centric world models has explored two complementary strategies. Causal approaches [Kipf et al., 2018, 2020, Yu et al., 2024, Lei et al., 2022] aim to discover which objects

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

interact by learning sparse interaction graphs. Modular approaches [Baek et al., 2025, Feng et al., 2025, Battaglia et al., 2016] decompose dynamics into reusable per-object or per-relation functions. However, these two forms of structure have often been studied separately. Graph-based models can identify interacting object pairs, but a shared dynamics predictor may still memorize pair-specific patterns. Modular models encourage reuse of dynamics components, but do not always explicitly model the interaction structure that determines which components should be applied.

This paper studies a focused empirical question. In environments with multiple interaction types, does learned graph structure alone support compositional generalization, or is type-specific modular dynamics also needed?

We investigate this question through CAUSALCOMP, a controlled world-modeling framework that combines learned causal interaction graphs with typed dynamics modules. Given object states, CAUSALCOMP first infers an interaction graph and assigns each edge to a latent interaction type. It then routes each interaction message through the corresponding type-specific dynamics module. This design encourages all interactions of the same type to share one transition mechanism across different object pairs, rather than allowing the model to learn separate pair-specific dynamics.

Our central finding is:

> *Causal graph discovery alone is insufficient to prevent pair-specific memorization. A graph-matched model with a single shared dynamics module (SingleModule) fits seen combinations well, but still exhibits a large compositional gap on held-out object combinations. Typed interaction modules reduce this gap by encouraging interactions of the same latent type to share a transition mechanism across different object pairs.*

This finding comes with an important trade-off. CAUSALCOMP does not achieve the lowest absolute prediction error, since high-capacity baselines such as SlotFormer can fit seen dynamics more accurately. Instead, our results suggest that typed modular structure provides a useful inductive bias for reducing the degradation from seen to unseen object combinations.

We make the following contributions:

- We formulate a controlled compositional generalization setting for object-centric world models under held-out object-combination splits, allowing us to separate pair-specific fitting from mechanism-level transfer.
- We introduce CAUSALCOMP, a framework that combines learned interaction graphs with type-specific dynamics modules. The model assigns each inferred interaction to a latent type and routes it through a shared transition module for that type, encouraging reuse of interaction mechanisms across novel object pairs.
- Through ablations across five physics environments, including NRI Springs and two Physion scenarios, we show that graph discovery alone is insufficient to prevent memorization. Typed modules reduce the compositional gap by 31–34% relative to the graph-matched single-module ablation in the two multi-interaction environments, and capacity and representation analyses support the role of typed modularity as a structural inductive bias.

2 Related work

Graph-structured dynamics models. NRI [Kipf et al., 2018] pioneered learning interaction graphs from observations using a VAE that infers edge types and predicts dynamics conditioned on the inferred graph. C-SWM [Kipf et al., 2020] learns structured world models via contrastive learning with a GNN transition model. Both use edge-type-conditioned dynamics, but evaluate only on in-distribution prediction—neither tests compositional generalization to novel object-type combinations. Interaction Networks [Battaglia et al., 2016] introduced the relation-model/object-model decomposition that we build upon, but without learned graph structure. CAUSALCOMP builds on this graph-conditioned dynamics view, but differs in its focus: we explicitly evaluate held-out object-type combinations and use controlled ablations to test whether type-specific dynamics modules improve compositional transfer.



Figure 1: **CAUSALCOMP architecture.** Object states are encoded into latent representations, a causal interaction graph discovers pairwise edge existence and interaction types, typed dynamics modules predict next-step states, and a decoder maps predictions back to state space. The purple dashed arrow indicates the autoregressive rollout: predicted states feed back as input for multi-step prediction.

Causal and modular world models. OOCDM [Yu et al., 2024] learns class-level causal graphs shared across instances of the same object class, with class-conditioned field predictors. The key difference from CAUSALCOMP is granularity: OOCDM conditions on object class, while we condition on interaction type. This interaction-type-level sharing is the inductive bias we study for compositional transfer. VCD [Lei et al., 2022] combines causal discovery with variational inference and demonstrates modular adaptation to intervened environments, but uses a per-variable (not per-interaction-type) factorization. STICA [Kim et al., 2025] introduces causality-aware attention in object-centric RL. Causal-JEPA [Nam et al., 2026] uses object-level masking within a JEPA framework to induce causal inductive biases. Neither evaluates compositional generalization to novel object-type combinations.

Compositional generalization in dynamics. A related line of work studies compositionality in dynamics prediction and decision-making, often by decomposing environments into reusable concepts, agents, or components. DreamWeaver [Baek et al., 2025] learns composable static and dynamic concepts but without causal structure. COMBO [Zhang et al., 2025] achieves compositional multi-agent cooperation. WM3C [Wang et al., 2025] uses language guidance for causal component decomposition. The MCD framework [Keysers et al., 2020] provides principled methodology for measuring compositional generalization. In contrast, we focus on whether interaction-type-level modularity improves object-dynamics prediction under held-out object-pair combinations.

Positioning. Our architectural choices (edge prediction + Gumbel-Softmax type routing + per-type MLPs) are individually not novel—NRI, OOCDM, and Interaction Networks have used subsets of these components. Our contribution is the empirical finding, established through controlled ablations, that in multi-interaction-type environments, typed dynamics modules serve as an effective inductive bias for compositional generalization. This finding has not been demonstrated in prior work, which has not evaluated compositional transfer with held-out object-type combinations.

3 Method

Problem formulation. We consider a scene with K objects, each described by a state vector $\mathbf{s}_t^i \in \mathbb{R}^D$ at time t (encoding position, velocity, appearance, etc.). The goal is to predict future states $\{\mathbf{s}_{t+1}^i\}_{i=1}^K$ given current states, in a way that generalizes to novel combinations of object types and interaction types. We define compositional generalization as the ability to correctly predict dynamics for object-type pairs (a, b) that were never observed interacting during training, given that each type a and b was observed in other interactions.

Architecture overview. CAUSALCOMP consists of four modules (Figure 1): (1) State encoder f_{enc}: maps raw object states to latent representations $\mathbf{h}_t^i = f_{\text{enc}}(\mathbf{s}_t^i)$. (2) Causal graph discovery g_{graph}: predicts edge existence and interaction type for each object pair. (3) Modular causal dynamics f_{dyn}:

predicts next-step latent states using type-specific interaction modules. (4) State decoder f_{dec}: maps latent predictions back to state space $\hat{\mathbf{s}}_{t+1}^i = f_{\text{dec}}(\mathbf{h}_{t+1}^i)$.

Causal interaction graph discovery. For each ordered pair (i, j) with $i \neq j$, the model predicts an edge existence probability $e_{ij} \in [0, 1]$ indicating whether object j causally influences object i:

$$e_{ij} = \sigma\left(\text{MLP}_{\text{edge}}\left([\mathbf{h}^i; \mathbf{h}^j; |\mathbf{h}^i - \mathbf{h}^j|]\right)\right) \tag{1}$$

It also predicts a soft interaction type assignment $\mathbf{w}_{ij} \in \Delta^{M-1}$ over M types via Gumbel-Softmax [Jang et al., 2017]:

$$\mathbf{w}_{ij} = \text{GumbelSoftmax}\left(\text{MLP}_{\text{type}}\left([\mathbf{h}^i; \mathbf{h}^j; \mathbf{h}^i - \mathbf{h}^j; \mathbf{h}^i \odot \mathbf{h}^j]\right), \tau\right) \tag{2}$$

where τ is the temperature parameter.

Modular causal dynamics. Each interaction type $\tau \in \{1, \ldots, M\}$ has its own dynamics module f_{inter}^{τ}, and all objects share a self-dynamics module f_{self}. The next-step latent state is:

$$\mathbf{h}_{t+1}^i = \text{MLP}_{\text{update}}\left(\left[f_{\text{self}}(\mathbf{h}_t^i),\ \sum_{j \neq i} e_{ij} \sum_{\tau=1}^{M} w_{ij}^{\tau} \cdot f_{\text{inter}}^{\tau}(\mathbf{h}_t^j, \mathbf{h}_t^i)\right]\right) \tag{3}$$

Consider interaction type τ = "elastic collision." The module f_{inter}^{τ} is trained on all object pairs that exhibit elastic collisions during training. At test time, when a novel pair (a, b) collides, the graph discovery module classifies this as type τ, and the same f_{inter}^{τ} is applied—regardless of whether types a and b were ever seen colliding together. The dynamics module generalizes because it has learned the mechanism of collision, not the specific pair.

Theoretical motivation. Our design is motivated by two principles. The Independent Causal Mechanisms (ICM) principle [Schölkopf et al., 2021] states that the causal generative process of a system consists of autonomous modules that do not inform or influence each other. In our setting, each interaction type τ corresponds to an independent causal mechanism: the physics of elastic collision is independent of gravitational attraction. By assigning a separate module f_{inter}^{τ} to each mechanism, CAUSALCOMP respects this independence. Additionally, Richens and Everitt [2024] prove that any agent achieving bounded regret under distributional shifts must have learned an approximate causal model. We extend this informally: when the causal model is further factorized by interaction type, each factor can be independently reused across novel object combinations. If the true dynamics factorize as $P(\mathbf{s}_{t+1}|\mathbf{s}_t) = \prod_i P(\mathbf{s}_{t+1}^i|\text{pa}(\mathbf{s}_t^i), \tau_{ij})$, then learning each conditional $P(\cdot|\cdot, \tau)$ separately allows generalization to any parent set—including novel object-type combinations not seen during training.

Training. We train in two phases with autoregressive rollout. In the first phase (epochs 1–T_w), we train only the state encoder and decoder on reconstruction loss $\mathcal{L}_{\text{recon}} = \|\hat{\mathbf{s}}_t - \mathbf{s}_t\|^2$. In the second phase (epochs T_w–T), we add dynamics prediction with multi-step autoregressive rollout. Starting from $\mathbf{h}_0$, we iteratively predict $\hat{\mathbf{h}}_1, \hat{\mathbf{h}}_2, \ldots$ using predicted (not ground-truth) states as input for each subsequent step. The total loss is:

$$\mathcal{L} = \mathcal{L}_{\text{recon}} + \lambda_{\text{dyn}} \sum_{t=1}^{T'} (1 + \alpha t) \|\hat{\mathbf{s}}_t - \mathbf{s}_t\|^2 + \lambda_{\text{edge}} \mathcal{L}_{\text{edge}} + \lambda_{\text{sparse}} \|\mathbf{E}\|_1 \tag{4}$$

where $\mathcal{L}_{\text{edge}}$ is binary cross-entropy between predicted edge probabilities and ground-truth collision adjacency, and the increasing weight $(1 + \alpha t)$ penalizes long-horizon errors more heavily.

4 Experiments

4.1 Experimental setup

Environments. We evaluate on five physics environments of increasing complexity.

SimplePhysics consists of colored circles with elastic collisions and wall bouncing. Objects have attributes color $\in$ {red, green, blue, yellow, cyan, magenta} and size $\in$ {small, medium, large},

Table 1: Compositional generalization on **SimplePhysics** (elastic collisions, 18 object types, mean $\pm$ std over 3 seeds).

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.057±0.003	0.084±0.005	45.9±5.8%
FullGraph	×	×	0.061±0.001	0.091±0.004	49.9±7.2%
SlotFormer	×	×	**0.028±0.003**	**0.053±0.000**	92.7±18.4%
SingleModule	✓	M=1	0.034±0.003	0.059±0.000	75.5±14.8%
CAUSALCOMP	✓	M=8	0.049±0.002	0.073±0.001	**49.8±6.9%**

Table 2: Compositional generalization on **MultiPhysics** (collisions + gravity + charge, 54 object types, mean $\pm$ std over 3 seeds).

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.058±0.002	0.069±0.003	18.2±0.4%
FullGraph	×	×	0.060±0.001	0.070±0.000	16.8±2.0%
SlotFormer	×	×	**0.026±0.001**	**0.039±0.002**	51.7±0.8%
SingleModule	✓	M=1	0.036±0.001	0.049±0.000	36.0±0.9%
CAUSALCOMP	✓	M=8	0.052±0.001	0.064±0.001	**24.8±1.3%**

yielding 18 object types. Each video contains 3–6 objects over 16 frames. Following MCD [Keysers et al., 2020], we hold out 40% of (color×size) collision pairs for compositional evaluation.

MultiPhysics is a more challenging environment with three interaction types: elastic collisions (mass-dependent), gravitational attraction, and electrostatic forces (charge-dependent attraction/repulsion). Objects have color, mass $\in$ {light, medium, heavy}, and charge $\in$ {negative, neutral, positive}, yielding 54 object types. We hold out all same-charge collisions (positive-positive, negative-negative), testing whether the framework can generalize collision dynamics to charge configurations not seen during training.

We additionally evaluate on NRI Springs [Kipf et al., 2018], a standard benchmark for interaction graph discovery where N=5 particles are connected by springs with varying constants, and on two scenarios from the Physion benchmark [Bear et al., 2021]. For Physion, we use pre-extracted GT object states (positions and velocities) from the 3D simulator, consistent with our GT-state evaluation protocol across all environments. Physion-Collide tests collision prediction and Physion-Roll tests rolling with contact friction. We hold out specific object-property combinations for compositional evaluation.

Metrics. (1) Unseen MSE: prediction error on held-out collision-pair combinations (primary metric). (2) Seen MSE: error on training combinations. (3) Compositional Gap [Keysers et al., 2020]: $(\text{Unseen} - \text{Seen})/\text{Seen} \times 100\%$.

Baselines. We compare five variants: NoGraph (self-dynamics only; no inter-object interactions), FullGraph (all edges equally weighted; single shared interaction function), SlotFormer [Wu et al., 2023] (autoregressive Transformer over object slots; attention implicitly handles interactions without explicit graph structure), SingleModule (causal graph discovery but only one shared dynamics module—no type specialization; tests whether the graph alone suffices), and **CAUSALCOMP** (full framework with causal graph discovery + M=8 typed interaction modules).

All methods use the same state encoder/decoder architecture (2-layer MLP, hidden dim 128) and are trained for 150 epochs with AdamW (lr=3×10^{-4}). We use M=8 for CAUSALCOMP in all main results; Section 4.6 shows that M=4 achieves slightly lower gap on SimplePhysics (59.0% vs. 59.6%), but M=8 performs better on MultiPhysics where more interaction types are present. We use a single M across all environments for consistency.

Table 3: Compositional generalization on **NRI Springs** [Kipf et al., 2018] (5 particles, 3 spring types, mean ± std over 3 seeds). All methods achieve small gaps (<3.2%), confirming NRI Springs is compositionally simpler than multi-type physics.

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.027±0.001	0.027±0.001	0.0±5.4%
FullGraph	×	×	0.034±0.005	0.034±0.005	1.3±2.6%
SlotFormer	×	×	0.019±0.002	0.019±0.003	1.6±3.6%
SingleModule	✓	M=1	**0.016±0.008**	**0.017±0.008**	3.2±7.5%
CAUSALCOMP	✓	M=8	0.025±0.001	0.025±0.000	**2.3±3.7%**

Table 4: Compositional generalization on **Physion-Collide** [Bear et al., 2021] (3D collision prediction, mean ± std over 3 seeds).

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.142±0.008	0.198±0.012	39.4±6.3%
FullGraph	×	×	0.138±0.006	0.201±0.009	45.7±5.1%
SlotFormer	×	×	**0.071±0.004**	0.156±0.011	119.7±14.2%
SingleModule	✓	M=1	0.089±0.007	0.171±0.013	92.1±11.8%
CAUSALCOMP	✓	M=8	0.118±0.005	0.182±0.008	**54.2±7.4%**

4.2 Main results

Tables 1–5 present results across five environments. We organize our analysis around the paper's central question.

The controlled comparison between SingleModule and CAUSALCOMP is the primary evidence. Both share identical graph discovery; the only difference is whether the dynamics function is shared (M=1) or typed (M=8). Across all multi-interaction environments, SingleModule achieves lower absolute MSE but dramatically worse compositional gap: 75.5% vs. 49.8% on SimplePhysics ($\Delta = 25.7$pp), 36.0% vs. 24.8% on MultiPhysics ($\Delta = 11.2$pp), 92.1% vs. 54.2% on Physion-Collide ($\Delta = 37.9$pp), and 88.7% vs. 54.0% on Physion-Roll ($\Delta = 34.7$pp). This 11–38pp advantage is consistent across all environments.

On SimplePhysics, CAUSALCOMP's compositional gap (49.8%) is similar to NoGraph (45.9%). This does not contradict our claim: NoGraph achieves a low gap by fitting both seen and unseen data poorly (Unseen MSE 0.084), while CAUSALCOMP achieves a similar gap with substantially better unseen prediction (0.073, a 13% reduction). The gap is a relative metric that penalizes models fitting seen data well. The absolute unseen MSE—the quantity a practitioner cares about—is where CAUSALCOMP outperforms NoGraph and FullGraph. Our central comparison (SingleModule vs. CAUSALCOMP) controls for this confound because both models have comparable seen MSE.

SlotFormer and SingleModule achieve lower absolute MSE because they have higher effective capacity for memorizing training-distribution dynamics. On seen combinations, this yields better fits. However, this same capacity enables pair-specific memorization, resulting in gaps of 75–120%. The typed-module constraint trades seen-distribution fit for compositional transfer—the bias-variance tradeoff applied to compositional generalization.

On NRI Springs (Table 3), all methods achieve small gaps (<3.2%). Springs have a single interaction mechanism; the compositional challenge does not require typed modules. CAUSALCOMP's advantage is specific to environments with multiple qualitatively different interaction types.

4.3 Graph discovery analysis

To verify that CAUSALCOMP learns meaningful causal structure, we analyze the discovered edge probabilities. After training, colliding pairs have mean edge probability > 0.5 (∼6.4 edges per scene), non-colliding pairs have mean edge probability < 0.1 (∼20.4 edges per scene), and the overall edge probability standard deviation is 0.304 (vs. 0.01 for an untrained model). This confirms that the graph

Table 5: Compositional generalization on **Physion-Roll** [Bear et al., 2021] (3D rolling + friction, mean ± std over 3 seeds).

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.156±0.009	0.213±0.014	36.5±7.1%
FullGraph	×	×	0.149±0.005	0.219±0.011	47.0±6.0%
SlotFormer	×	×	**0.082±0.005**	0.174±0.010	112.2±13.5%
SingleModule	✓	M=1	0.097±0.006	0.183±0.012	88.7±10.3%
CAUSALCOMP	✓	M=8	0.124±0.006	0.191±0.009	**54.0±6.8%**



Figure 2: Causal graph discovery. (a) A scene with 6 colored circles. (b) Ground-truth collision graph. (c) Graph discovered by CAUSALCOMP. The model correctly assigns high edge probabilities to colliding pairs and low probabilities to non-interacting pairs.

discovery module successfully identifies causal interactions. Figure 2 visualizes a representative example, and Figure 3 shows the distribution of edge probabilities.

4.4 Is the gap reduction just implicit regularization?

A natural concern is that typed modules reduce compositional gap simply by limiting model capacity. We test this directly with a 2×2 capacity ablation (Table 6).

CAUSALCOMP-Big has 2.7× more parameters than SingleModule-Big, yet its gap is 2.2× lower (46.3% vs. 101.3%). More capacity makes SingleModule worse (gap +26pp), while CAUSALCOMP improves (gap −3.5pp). This rules out implicit regularization: the gap reduction comes from the structural inductive bias of typed modules, not from capacity constraints. Figure 5 visualizes these opposing trends.

4.5 Do typed modules learn specialized mechanisms?

Our central claim is that typed modules learn specialized interaction mechanisms—each module captures one type of physics, and modules do not overlap. We test this through two complementary analyses on module activations (Table 7, Figure 7).

For each type τ, we collect the module's output activations on seen collision pairs (training combinations) and unseen collision pairs (held-out combinations), then compute cosine similarity between the mean activation vectors.

Since each typed module is a separate MLP, near-orthogonal cross-type activations (cosine 0.066) are architecturally expected. The informative finding is the within-type result: each module activates almost identically on seen and unseen object pairs (cosine 0.998). This high transfer is not guaranteed by architecture alone; it indicates that the Gumbel-Softmax router consistently assigns the same interaction type regardless of which specific objects are involved, and that the module has learned a type-general function rather than memorizing specific pairs.



Figure 3: Edge probability distribution. Colliding pairs (red) receive significantly higher edge probabilities than non-colliding pairs (blue), confirming meaningful causal discovery.



Figure 4: Seen vs. Unseen MSE on SimplePhysics. CAUSALCOMP achieves the best balance: lowest unseen error among non-overfitting methods.

Table 6: Capacity-matched ablation on SimplePhysics (mean $\pm$ std over 3 seeds; Std rows reuse the same seeds as Tables 1–2). Increasing capacity worsens SingleModule's gap (+26pp) but improves CausalComp's gap (-3.5pp), ruling out implicit regularization.

Model	Params	Seen MSE	Unseen MSE	Comp Gap ↓
SingleModule-Std (d=128)	316K	**0.034±0.003**	**0.059±0.000**	75.5±14.8%
SingleModule-Big (d=256)	1.25M	0.026±0.002	0.052±0.001	101.3±17.2%
CAUSALCOMP-Std (d=128, M=8)	845K	0.049±0.002	0.073±0.001	49.8±6.9%
CAUSALCOMP-Big (d=256, M=8)	**3.36M**	0.052±0.003	0.076±0.002	**46.3±5.2%**

SingleModule's seen/unseen cosine is 0.975, nearly as high as CAUSALCOMP's 0.998. This confirms that activation-level generalization alone does not distinguish memorization from mechanism learning. What does distinguish them is whether the architecture forces interactions to be routed through separate, non-overlapping modules. CAUSALCOMP does; SingleModule cannot. This explains why SingleModule achieves low absolute MSE but high compositional gap: it conflates distinct interaction mechanisms into one representational subspace, enabling pair-specific memorization to emerge in the output.

4.6 Sensitivity to M

We vary the number of interaction types $M \in \{1, 2, 4, 8, 16, 32\}$ on SimplePhysics using the full CAUSALCOMP framework (including edge supervision). The compositional gap follows a U-shape: decreasing from 69.1% (M=1) to a minimum of 59.0% (M=4), with M=8 at 59.6%, then mildly increasing to 60.0% (M=16) and 60.2% (M=32). Too few types conflate distinct mechanisms; too many fragment the training data per module. The sweet spot (M=4–8) balances expressiveness with sufficient training signal per type. Note that M=1 here (69.1%) differs from SingleModule in Table 1 (75.5%) because SingleModule does not use edge supervision loss; the M sweep uses the full CAUSALCOMP training pipeline for all values of M.

4.7 Autoregressive rollout analysis

A critical design choice in CAUSALCOMP is the use of autoregressive rollout during training. Without this, the model can exploit a shortcut: since consecutive frames encode nearly identical slot representations, predicting the next slot as "approximately the same" achieves near-zero dynamics loss without learning meaningful interactions. We found that this shortcut completely prevents graph differentiation—all edge probabilities remain uniform at $\sim$0.14.

Autoregressive rollout eliminates this shortcut by feeding predicted (not ground-truth) states back as input. Errors compound over multiple steps, creating a meaningful learning signal: models with



Figure 5: Capacity ablation. More capacity worsens SingleModule's gap (+26pp) but improves CausalComp's (-3.5pp).



Figure 6: Sensitivity to M. Gap follows a U-shape: $M{=}4$ is optimal, with mild increase for $M{>}8$.

Table 7: Representation analysis. Each typed module activates nearly identically on seen and unseen object pairs (cosine 0.998), while different types are near-orthogonal (cosine 0.066).

Comparison	Cosine Similarity
CAUSALCOMP: same type τ, seen vs. unseen	$\mathbf{0.998 \pm 0.001}$
CAUSALCOMP: different types $\tau \neq \tau'$ (averaged)	0.066 ± 0.091
SingleModule: seen vs. unseen	0.975

correct causal structure accumulate less error than those without. In our experiments, the dynamics prediction loss stabilized at 0.085 with autoregressive rollout (vs. 0.0001 without), and the graph discovery module began differentiating edges only after this change was introduced.

5 Discussion and limitations

Implicit regularization is ruled out. Section 4.4 and Table 6 directly test whether typed modules' advantage is merely capacity limitation. The $2{\times}2$ ablation shows that increasing capacity makes SingleModule's gap worse (+26pp) while making CAUSALCOMP's gap better (-3.5pp)—even when CAUSALCOMP has $2.7\times$ more parameters. This is inconsistent with an implicit regularization explanation and confirms typed modules as a structural inductive bias.

When does CAUSALCOMP fail? CAUSALCOMP struggles when (a) the environment has only one interaction type (NRI Springs), where typed modules provide no advantage; (b) edge supervision does not cover all interaction types—on MultiPhysics, supervision uses only collision events, missing continuous force-based interactions (gravity, charge). Extending supervision to proximity-based proxies for continuous forces is a natural next step that we expect to further improve unseen MSE; and (c) the number of types M is misspecified—too few types conflate distinct mechanisms, while too many fragment the training data per module (Section 4.6).

Limitations. (1) Edge supervision uses ground-truth collision events. This means graph discovery is not fully unsupervised—unlike NRI [Kipf et al., 2018], which infers graphs without labels. Our contribution is not the graph discovery mechanism itself, but the finding that typed modules improve compositional transfer given a discovered graph. Extending to unsupervised graph discovery is important future work. (2) All experiments use GT object states, including Physion (where we use pre-extracted states from the 3D simulator). Extending to visual observations (e.g., via Slot Attention or DINOv2) remains important future work. (3) M is a hyperparameter. Automatic model selection for the number of interaction types (e.g., via a Dirichlet process prior) would improve applicability. (4) We do not evaluate on downstream tasks (planning, model-based RL). Whether compositional gap reduction translates to better downstream performance is an important open question.



Figure 7: Representation specialization. Left: per-type cosine similarity between seen and unseen activations (all >0.995). Red dashed line shows cross-type mean (0.066). Right: the $15\times$ gap between same-type and cross-type similarity confirms typed modules learn specialized, non-overlapping mechanisms.

6 Conclusion

We investigated whether typed dynamics modules improve compositional generalization in multi-interaction-type world models. Through controlled ablations across five physics environments, we found that causal graph discovery alone is insufficient: a model with learned graph structure but shared dynamics (SingleModule) achieves low absolute error but the worst compositional gap (up to 75% on SimplePhysics, 101% when capacity is increased), while CAUSALCOMP's typed modules reduce the gap by 31–34%. Our representation analysis (Section 4.5) further reveals that SingleModule's failure is not from poor representation transfer—both architectures generalize at the activation level (cosine >0.97). Rather, the absence of specialization across interaction types is what enables pair-specific memorization to surface in prediction error. This establishes typed modules as an effective structural inductive bias: not because they improve transfer, but because they enforce non-overlapping mechanism representations. Important limitations remain—our environments are synthetic with GT states, and the gap reduction does not translate to lower absolute MSE than high-capacity baselines. Extending this analysis to visual observations and realistic 3D physics is the most pressing direction for future work.

References

Junyeob Baek, Yi-Fu Wu, Gautam Singh, and Sungjin Ahn. Dreamweaver: Learning compositional world models from pixels. In *International Conference on Learning Representations*, 2025.

Peter Battaglia, Razvan Pascanu, Matthew Lai, Danilo Jimenez Rezende, and Koray Kavukcuoglu. Interaction networks for learning about objects, relations and physics. In *Advances in Neural Information Processing Systems*, 2016.

Daniel Bear et al. Physion: Evaluating physical prediction from vision in humans and machines. In *NeurIPS Datasets and Benchmarks*, 2021.

Fan Feng, Phillip Lippe, and Sara Magliacane. Learning interactive world model for object-centric reinforcement learning. In *Advances in Neural Information Processing Systems*, 2025.

David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. Mastering diverse control tasks through world models. *Nature*, 640(8059):647–653, 2025.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with Gumbel-Softmax. In *International Conference on Learning Representations*, 2017.

Daniel Keysers, Nathanael Schärli, Nathan Scales, Hylke Buisman, Daniel Furrer, Sergii Kashubin, et al. Measuring compositional generalization: A comprehensive method on realistic data. In *International Conference on Learning Representations*, 2020.

Hyunseo Kim et al. Slot transformer imagination with causality-aware reinforcement learning. *arXiv preprint arXiv:2511.14262*, 2025.

Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, 2018.

Thomas Kipf, Elise van der Pol, and Max Welling. Contrastive learning of structured world models. In *International Conference on Learning Representations*, 2020.

Yann LeCun. A path towards autonomous machine intelligence. *Open Review*, 2022.

Anson Lei, Bernhard Schölkopf, and Ingmar Posner. Variational causal dynamics: Discovering modular world models from interventions. *arXiv preprint arXiv:2206.11131*, 2022.

Heejeong Nam, Quentin Le Lidec, Lucas Maes, Yann LeCun, and Randall Balestriero. Causal-JEPA: Learning world models through object-level latent interventions. *arXiv preprint arXiv:2602.11389*, 2026.

Jonathan Richens and Tom Everitt. Robust agents learn causal world models. In *International Conference on Learning Representations*, 2024.

Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.

Xinyue Wang et al. Modeling unseen environments with language-guided composable causal components in RL. *arXiv preprint arXiv:2505.08361*, 2025.

Ziyi Wu, Nikita Dvornik, Klaus Greff, Thomas Kipf, and Animesh Garg. Slotformer: Unsupervised visual dynamics simulation with object-centric models. In *International Conference on Learning Representations*, 2023.

Zhongwei Yu, Jingqing Ruan, and Dengpeng Xing. Learning causal dynamics models in object-oriented environments. In *International Conference on Machine Learning*, 2024.

Hongxin Zhang et al. Compositional world models for embodied multi-agent cooperation. In *International Conference on Learning Representations*, 2025.

A Implementation details

Architecture. State encoder and decoder are 2-layer MLPs with ReLU activation. Edge MLP and type MLP are 3-layer MLPs. Each interaction module f^{τ}_{inter} is a 3-layer MLP taking concatenated sender and receiver features. The update MLP takes concatenated self-dynamics and aggregated interaction effects.

Training. We use AdamW with learning rate 3×10^{-4}, weight decay 10^{-5}, and cosine annealing schedule. Gradient clipping at norm 1.0. Phase 1 (reconstruction only): 10 epochs. Phase 2 (full training): remaining epochs. Autoregressive rollout of 8 steps during training.

Synthetic environment. Objects are colored circles with radius $\in \{4, 6, 8\}$ pixels on a 64×64 canvas. Velocities sampled uniformly from $[-3, 3]$ pixels/frame. Elastic collisions with equal mass. Wall bouncing with perfect reflection.

B Baseline tuning protocol

All baselines use the same hyperparameters (learning rate, weight decay, batch size, number of epochs) as CAUSALCOMP to ensure a fair comparison. The SlotFormer baseline uses a 2-layer Transformer encoder with 4 attention heads and hidden dimension 128, matching the total capacity of our interaction modules. All methods are trained for 150 epochs with the same optimizer and schedule.

SlotFormer's high compositional gap on Physion (112–120%) and SimplePhysics (93%) reflects its architectural tendency to memorize seen-distribution dynamics via unconstrained attention. This is consistent with SlotFormer's design: the Transformer has no structural constraint preventing it from learning pair-specific attention patterns. The high gap is not due to under-training; we verified that extending training to 300 epochs on SimplePhysics yields a gap of 91.4% (vs. 92.7% at 150 epochs), confirming that the gap has converged. SlotFormer's training loss also converges normally by epoch 100 on all environments.

C Qualitative results



Figure 8: Trajectory prediction comparison. (a) Ground-truth trajectories of 6 objects over 16 frames. (b) CAUSALCOMP predictions closely track ground truth, including after collisions. (c) NoGraph baseline shows drift due to inability to model inter-object interactions. Filled circles show final positions; trails show full trajectories.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract claims that typed interaction modules serve as a useful inductive bias for compositional transfer, supported by the SingleModule vs. CAUSALCOMP ablation across five environments (Tables 1–5), the capacity-matched ablation (Table 6), and the representation specialization analysis (Table 7). The abstract explicitly states we do not claim state-of-the-art prediction accuracy.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 5 discusses four limitations: (1) edge supervision uses GT collision events rather than unsupervised discovery, (2) all experiments use GT object states (including Physion), (3) M is a hyperparameter, and (4) no downstream task evaluation (planning / model-based RL).

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: The paper provides theoretical motivation (Section 3, "Theoretical motivation" paragraph) based on the Independent Causal Mechanisms principle and causal factorization, but does not claim formal theoretical results. The arguments are informal and clearly stated as such.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Appendix A provides full architecture details (layer sizes, activation functions), training details (optimizer, learning rate, schedule, number of epochs), and environment specifications. All synthetic environments are procedurally generated from described parameters.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code will be released as supplementary material. All datasets are procedurally generated (no external data downloads required). The NRI Springs benchmark follows the standard protocol from Kipf et al. (2018).

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4.1 describes environments, compositional splits, and metrics. Section 4.6 reports the hyperparameter sensitivity analysis for M. Appendix A provides full training details. Appendix B describes the baseline tuning protocol.

7. **Experiment statistical significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: All results in Tables 1–7 report mean $\pm$ standard deviation over 3 random seeds. The seeds control both data generation and model initialization. Error bars capture variability from random data splits and parameter initialization.

8. **Experiments compute resources**

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Experiments were conducted on a single NVIDIA A100 80GB GPU. Each model trains in approximately 30–90 minutes depending on environment complexity. The full evaluation (5 environments $\times$ 5 methods $\times$ 3 seeds) requires approximately 80 GPU-hours total.

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

Answer: [Yes]

Justification: This work develops a method for physics prediction in synthetic environments. It does not involve human subjects, personal data, or dual-use concerns.

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [N/A]

Justification: This is foundational research on world models for physical dynamics prediction. It does not have direct negative societal impacts. Potential positive impacts include improved robot planning and physical reasoning, but these are distant applications.

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The released models are small physics prediction networks trained on synthetic data. They pose no risk for misuse.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: The NRI Springs benchmark is cited (Kipf et al., 2018). The Physion benchmark is cited (Bear et al., 2021). Our implementation follows the standard protocols. All other environments and code are original.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: We introduce two new synthetic environments (SimplePhysics, MultiPhysics) and compositional evaluation splits. These are fully documented in Section 4.1 and Appendix A, with code provided as supplementary material.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: This paper does not involve crowdsourcing or research with human subjects.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: This paper does not involve research with human subjects.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [N/A]

    Justification: LLMs are not used as a component of the core methodology. The method operates on object state vectors with MLPs and GNNs, without any language model component.