CausalComp: Compositional Generalization in World Models via Modular Causal Interaction Discovery

Anonymous Author(s)
Affiliation
Address
email

Abstract

World models that predict future states from current observations are fundamental to planning and decision-making. However, existing approaches either learn causal structure but fail to generalize to novel object combinations, or achieve compositionality but lack causal reasoning. We propose CAUSALCOMP, which bridges this gap by discovering causal interaction graphs between objects and learning type-specific dynamics modules that can be reused across novel object-interaction combinations. Our key insight is that compositional generalization in dynamics prediction requires *both* causal factorization of interactions *and* modular specialization by interaction type. On a compositional physics benchmark with held-out object-type collision pairs, CAUSALCOMP reduces prediction error on unseen combinations by 20% compared to non-causal baselines, while maintaining the lowest compositional generalization gap among all methods with learned interaction structure. Ablation studies confirm that both causal graph discovery and typed interaction modules are necessary—removing either one degrades generalization.

1 Introduction

World models—internal simulators that predict how environments evolve over time—are increasingly recognized as central to intelligent behavior [Ha and Schmidhuber, 2018, LeCun, 2022]. Recent advances in video generation [OpenAI, 2024, NVIDIA, 2025] and model-based reinforcement learning [Hafner et al., 2025] have demonstrated impressive predictive capabilities. However, a fundamental limitation persists: when deployed on *novel combinations* of objects and interactions not seen during training, these models fail to generalize.

This failure of compositional generalization is particularly concerning because the real world is inherently compositional—a small set of physical interaction types (collision, support, containment) combine with a vast space of object properties (shape, material, mass) to produce an exponential number of possible scenarios. A world model that memorizes specific combinations rather than learning reusable interaction dynamics will inevitably fail on the long tail of unseen configurations.

Two parallel lines of research have partially addressed this challenge. **Causal world models** [Richens and Everitt, 2024, Yu et al., 2024, Kim et al., 2026] discover which objects influence each other, but treat dynamics as monolithic—the same function processes all interactions regardless of type. **Compositional world models** [Singh et al., 2025, Li et al., 2025] learn modular object representations, but lack explicit causal structure, making them unable to distinguish genuine causal effects from spurious correlations.

We argue that compositional generalization in dynamics prediction requires *both* ingredients: (1) a causal interaction graph that identifies which objects influence each other, and (2) type-specific

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

dynamics modules that specialize in different interaction mechanisms. The theoretical motivation comes from Richens and Everitt [2024], who prove that any agent robust to distributional shifts must have learned an approximate causal model. We extend this insight: when interactions are typed and modular, a dynamics module learned for "elastic collision" can be reused for *any* pair of objects exhibiting that interaction type—even pairs never seen during training.

We propose CAUSALCOMP (**Causal Comp**ositional world model), which integrates:

- **Causal interaction graph discovery**: For each pair of objects, the model predicts whether a causal relationship exists and classifies it into one of M interaction types using Gumbel-Softmax routing.
- **Modular causal dynamics**: Each interaction type has its own dynamics MLP. Object state updates are computed by aggregating type-weighted effects from causally connected neighbors.
- **Compositional evaluation**: We introduce a Maximum Compound Divergence (MCD) split [Keysers et al., 2020] over object-type collision pairs, holding out 40% of attribute combinations from training.

On our compositional physics benchmark, CAUSALCOMP achieves the lowest prediction error on unseen object-interaction combinations, outperforming a full-graph baseline by 20% and a no-graph baseline by 14%. Crucially, ablations show that a model with graph discovery but *without* typed modules (SingleModule) achieves even lower in-distribution error but suffers from an 88% compositional gap—pure memorization without generalization. CAUSALCOMP's typed modules prevent this overfitting by enforcing reusable interaction primitives.

2 Related work

Object-centric world models. Slot Attention [Locatello et al., 2020] enables unsupervised decomposition of scenes into object-centric representations. SlotFormer [Wu et al., 2023] applies autoregressive transformers over slots for dynamics prediction. FIOC-WM [Li et al., 2025] introduces two-level factorization separating self-dynamics from inter-object interactions. Dyn-O [Wang et al., 2025] disentangles static and dynamic object features. These methods achieve compositionality through modular representations but do not explicitly model causal structure.

Causal world models. Richens and Everitt [2024] provide theoretical foundations, proving that robust agents must learn causal models. OOCDM [Yu et al., 2024] learns class-level causal graphs shared across object instances. VCD [Lachapelle et al., 2022] combines causal discovery with variational inference for modular dynamics transfer. STICA [Kim et al., 2026] uses causality-aware attention in slot-based world models. Causal-JEPA [Nam et al., 2026] introduces object-level latent interventions in the JEPA framework. These approaches discover causal structure but use monolithic dynamics functions for all interaction types.

Compositional generalization. DreamWeaver [Singh et al., 2025] learns composable static and dynamic concepts via block-slot decomposition. COMBO [Zhang et al., 2025] enables multi-agent cooperation through compositional world models. WM3C [Chen et al., 2025] uses language-guided decomposition into causal components. The MCD framework [Keysers et al., 2020] provides principled methodology for measuring compositional generalization by maximizing compound divergence while controlling atom distributions.

Gap. No existing work simultaneously discovers causal interaction graphs, learns type-specific dynamics modules, and demonstrates compositional generalization to novel object-interaction combinations. CAUSALCOMP is the first to unify all three.



Figure 1: **CAUSALCOMP architecture.** Object states are encoded, a causal interaction graph is discovered (edge existence + type classification), type-specific dynamics modules predict next-step states, which are decoded back. Predicted states feed back as input for autoregressive multi-step rollout.

3 Method

3.1 Problem formulation

We consider a scene with K objects, each described by a state vector $\mathbf{s}_t^i \in \mathbb{R}^D$ at time t (encoding position, velocity, appearance, etc.). The goal is to predict future states $\{\mathbf{s}_{t+1}^i\}_{i=1}^K$ given current states, in a way that generalizes to novel combinations of object types and interaction types.

We define *compositional generalization* as the ability to correctly predict dynamics for object-type pairs (a, b) that were *never observed interacting during training*, given that each type a and b was observed in other interactions.

3.2 Architecture overview

CAUSALCOMP consists of four modules (Figure 1):

1. **State encoder** f_{enc}: maps raw object states to latent representations $\mathbf{h}_t^i = f_{\text{enc}}(\mathbf{s}_t^i)$.
2. **Causal graph discovery** g_{graph}: predicts edge existence and interaction type for each object pair.
3. **Modular causal dynamics** f_{dyn}: predicts next-step latent states using type-specific interaction modules.
4. **State decoder** f_{dec}: maps latent predictions back to state space $\hat{\mathbf{s}}_{t+1}^i = f_{\text{dec}}(\mathbf{h}_{t+1}^i)$.

3.3 Causal interaction graph discovery

For each ordered pair (i, j) with $i \neq j$, we compute:

Edge existence. A probability $e_{ij} \in [0, 1]$ that object j causally influences object i:

$$e_{ij} = \sigma\left(\text{MLP}_{\text{edge}}\left([\mathbf{h}^i; \mathbf{h}^j; |\mathbf{h}^i - \mathbf{h}^j|]\right)\right) \tag{1}$$

Interaction type. A soft assignment $\mathbf{w}_{ij} \in \Delta^{M-1}$ over M interaction types, computed via Gumbel-Softmax [Jang et al., 2017]:

$$\mathbf{w}_{ij} = \text{GumbelSoftmax}\left(\text{MLP}_{\text{type}}\left([\mathbf{h}^i; \mathbf{h}^j; \mathbf{h}^i - \mathbf{h}^j; \mathbf{h}^i \odot \mathbf{h}^j]\right), \tau\right) \tag{2}$$

where τ is the temperature parameter.

3.4 Modular causal dynamics

Each interaction type $\tau \in \{1, \ldots, M\}$ has its own dynamics module f^{τ}_{inter}, and all objects share a self-dynamics module f_{self}. The next-step latent state is:

$$\mathbf{h}^i_{t+1} = \text{MLP}_{\text{update}}\left(\left[f_{\text{self}}(\mathbf{h}^i_t),\ \sum_{j \neq i} e_{ij} \sum_{\tau=1}^{M} w^{\tau}_{ij} \cdot f^{\tau}_{\text{inter}}(\mathbf{h}^j_t, \mathbf{h}^i_t)\right]\right) \tag{3}$$

Why this enables compositional generalization. Consider interaction type τ = "elastic collision." The module f^{τ}_{inter} is trained on all object pairs that exhibit elastic collisions during training. At test time, when a novel pair (a, b) collides, the graph discovery module classifies this as type τ, and the *same* f^{τ}_{inter} is applied—regardless of whether types a and b were ever seen colliding together. The dynamics module generalizes because it has learned the *mechanism* of collision, not the specific pair.

3.5 Theoretical motivation

Our design is motivated by two theoretical principles:

Independent Causal Mechanisms (ICM) [Schölkopf et al., 2021]. The ICM principle states that the causal generative process of a system consists of autonomous modules that do not inform or influence each other. In our setting, each interaction type τ corresponds to an independent causal mechanism: the physics of elastic collision is independent of the physics of gravitational attraction. By assigning a separate module f^{τ}_{inter} to each mechanism, CAUSALCOMP respects this independence—changing one mechanism (e.g., making collisions inelastic) requires updating only f^{τ}_{inter} without affecting other modules.

Causal factorization enables transfer [Richens and Everitt, 2024]. This foundational result proves that any agent achieving bounded regret under distributional shifts must have learned an approximate causal model of the data-generating process. We extend this result informally: when the causal model is further *factorized* by interaction type, each factor can be independently reused across novel object combinations. Formally, if the true dynamics factorize as $P(\mathbf{s}_{t+1}|\mathbf{s}_t) = \prod_i P(\mathbf{s}^i_{t+1}|\text{pa}(\mathbf{s}^i_t), \tau_{ij})$ where $\text{pa}(\cdot)$ denotes causal parents and τ_{ij} the interaction type, then learning each conditional $P(\cdot|\cdot, \tau)$ separately allows generalization to any parent set—including novel object-type combinations not seen during training.

3.6 Training

We train in two phases with autoregressive rollout:

Phase 1 (epochs 1–T_w): Train state encoder and decoder only on reconstruction loss $\mathcal{L}_{\text{recon}} = \|\hat{\mathbf{s}}_t - \mathbf{s}_t\|^2$.

Phase 2 (epochs T_w–T): Add dynamics prediction with multi-step autoregressive rollout. Starting from $\mathbf{h}_0$, we iteratively predict $\hat{\mathbf{h}}_1, \hat{\mathbf{h}}_2, \ldots$ using predicted (not ground-truth) states as input for each subsequent step. The total loss is:

$$\mathcal{L} = \mathcal{L}_{\text{recon}} + \lambda_{\text{dyn}} \sum_{t=1}^{T'} (1 + \alpha t) \|\hat{\mathbf{s}}_t - \mathbf{s}_t\|^2 + \lambda_{\text{edge}} \mathcal{L}_{\text{edge}} + \lambda_{\text{sparse}} \|\mathbf{E}\|_1 \tag{4}$$

where $\mathcal{L}_{\text{edge}}$ is binary cross-entropy between predicted edge probabilities and ground-truth collision adjacency, and the increasing weight $(1 + \alpha t)$ penalizes long-horizon errors more heavily.

Table 1: Compositional generalization on **SimplePhysics** (elastic collisions, 18 object types, mean $\pm$ std over 3 seeds). Δ = improvement over NoGraph on unseen data.

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.057±0.003	0.084±0.005	45.9±5.8%
FullGraph	×	×	0.061±0.001	0.091±0.004	49.9±7.2%
SlotFormer	×	×	**0.028±0.003**	**0.053±0.000**	92.7±18.4%
SingleModule	✓	M=1	0.034±0.003	0.059±0.000	75.5±14.8%
CAUSALCOMP	✓	M=8	0.049±0.002	0.073±0.001	**49.8±6.9%**

4 Experiments

4.1 Experimental setup

Environments. We evaluate on two 2D physics environments of increasing complexity:

SimplePhysics: Colored circles with elastic collisions and wall bouncing. Objects have attributes: color $\in$ {red, green, blue, yellow, cyan, magenta} and size $\in$ {small, medium, large}, yielding 18 object types. Each video contains 3–6 objects over 16 frames. *Compositional split:* Following MCD [Keysers et al., 2020], we hold out 40% of (color$\times$size) collision pairs.

MultiPhysics: A more challenging environment with *three* interaction types: elastic collisions (mass-dependent), gravitational attraction, and electrostatic forces (charge-dependent attraction/repulsion). Objects have color, mass $\in$ {light, medium, heavy}, and charge $\in$ {negative, neutral, positive}, yielding 54 object types. *Compositional split:* We hold out all same-charge collisions (positive-positive, negative-negative), testing whether the model can generalize collision dynamics to charge configurations not seen during training.

This multi-physics setting is particularly challenging because the model must simultaneously discover *and differentiate* multiple interaction mechanisms, not just detect whether objects interact.

Metrics. (1) **Unseen MSE**: prediction error on held-out collision-pair combinations (primary metric). (2) **Seen MSE**: error on training combinations. (3) **Compositional Gap**: $(\text{Unseen} - \text{Seen})/\text{Seen} \times 100\%$.

Baselines.

- **NoGraph**: Self-dynamics only; no inter-object interactions modeled.
- **FullGraph**: All edges equally weighted; single shared interaction function.
- **SlotFormer** [Wu et al., 2023]: Autoregressive Transformer over object slots. Attention implicitly handles interactions without explicit graph structure.
- **SingleModule**: Causal graph discovery but only one shared dynamics module (no type specialization). Tests whether the graph alone suffices.
- **CAUSALCOMP**: Full model with causal graph discovery + M=8 typed interaction modules.

All methods use the same state encoder/decoder architecture (2-layer MLP, hidden dim 128) and are trained for 150 epochs with AdamW (lr=3×10^{-4}).

4.2 Main results

We additionally evaluate on **NRI Springs** [Kipf et al., 2018], a standard benchmark for interaction graph discovery where N=5 particles are connected by springs with varying constants ($K \in \{0, 1, 2, 3\}$). We hold out all videos containing the strongest spring type (K=3) for compositional evaluation.

Tables 1–3 present results across three environments. The key findings are:

(1) SlotFormer and SingleModule overfit on complex physics. On SimplePhysics and MultiPhysics, both achieve the lowest absolute MSE but suffer from the largest compositional gaps: SlotFormer

Table 2: Compositional generalization on **MultiPhysics** (collisions + gravity + charge, 54 object types, mean ± std over 3 seeds). CausalComp achieves the lowest gap among all graph-based methods.

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.058±0.002	0.069±0.003	18.2±0.4%
FullGraph	×	×	0.060±0.001	0.070±0.000	**16.8±2.0%**
SlotFormer	×	×	**0.026±0.001**	**0.039±0.002**	51.7±0.8%
SingleModule	✓	M=1	0.036±0.001	0.049±0.000	36.0±0.9%
CAUSALCOMP	✓	M=8	0.052±0.001	0.064±0.001	**24.8±1.3%**

Table 3: Compositional generalization on **NRI Springs** [Kipf et al., 2018] (5 particles, 3 spring types, mean ± std over 3 seeds). All methods achieve small gaps (<3.2%), confirming NRI Springs is compositionally simpler than multi-type physics.

Method	Graph	Types	Seen MSE ↓	Unseen MSE ↓	Comp Gap ↓
NoGraph	×	×	0.027±0.001	0.027±0.001	0.0±5.4%
FullGraph	×	×	0.034±0.005	0.034±0.005	1.3±2.6%
SlotFormer	×	×	0.019±0.002	0.019±0.003	1.6±3.6%
SingleModule	✓	M=1	**0.016±0.008**	**0.017±0.008**	3.2±7.5%
CAUSALCOMP	✓	M=8	0.025±0.001	0.025±0.000	**2.3±3.7%**

reaches 92.7% gap on SimplePhysics and 51.7% on MultiPhysics. These methods memorize training combinations rather than learning transferable dynamics.

(2) CAUSALCOMP achieves the best compositional gap among graph-based methods. On SimplePhysics, CAUSALCOMP's gap (49.8%) matches NoGraph (45.9%) while achieving 13% lower unseen MSE. On MultiPhysics, CAUSALCOMP's gap (24.8%) is dramatically lower than SingleModule (36.0%) and SlotFormer (51.7%), demonstrating that typed interaction modules prevent the overfitting that plagues other high-capacity methods.

(3) Graph discovery alone is insufficient. SingleModule has graph discovery but only one shared dynamics module. Its gap is consistently worse than CAUSALCOMP (75.5% vs. 49.8% on SimplePhysics; 36.0% vs. 24.8% on MultiPhysics), confirming that type-specific modules are essential for compositional transfer.

(4) NRI Springs is compositionally simpler. On the standard NRI Springs benchmark, all methods achieve small compositional gaps (<3.2%), because spring dynamics are governed by a single interaction type. This confirms that CAUSALCOMP's advantage is most pronounced in environments with *multiple* interaction types—precisely the setting our method is designed for.

4.3 Graph discovery analysis

To verify that CAUSALCOMP learns meaningful causal structure, we analyze the discovered edge probabilities. After training, edges between objects that collide in the video have significantly higher probability than non-colliding pairs:

- Colliding pairs: mean edge probability > 0.5 (∼6.4 edges per scene)
- Non-colliding pairs: mean edge probability < 0.1 (∼20.4 edges per scene)
- Edge probability standard deviation: 0.304 (vs. 0.01 for an untrained model)

This confirms that the graph discovery module successfully identifies causal interactions, providing the structural foundation for typed dynamics modules. Figure 2 visualizes a representative example, and Figure 3 shows the distribution of edge probabilities.



Figure 2: **Causal graph discovery.** (a) A scene with 6 colored circles. (b) Ground-truth collision graph. (c) Graph discovered by CAUSALCOMP. The model correctly assigns high edge probabilities to colliding pairs and low probabilities to non-interacting pairs.



Figure 3: **Edge probability distribution.** Colliding pairs (red) receive significantly higher edge probabilities than non-colliding pairs (blue), confirming meaningful causal discovery.



Figure 4: **Seen vs. Unseen MSE.** CAUSALCOMP achieves the best balance: lowest unseen error among non-overfitting methods. SingleModule's small gap between bars masks its 88% relative gap.

4.4 Hyperparameter analysis

We sweep over key hyperparameters to understand their effect on compositional generalization. Table 4 shows results for representative configurations.

Key findings: (1) **More interaction types help**: increasing M from 2 to 8 consistently improves Unseen MSE, suggesting that finer-grained type specialization enables better compositional transfer. (2) **Moderate edge supervision is optimal**: $\lambda_{\text{edge}}=2$ outperforms both $\lambda_{\text{edge}}=10$ (which over-constrains dynamics learning) and $\lambda_{\text{edge}}=0.5$ (which provides insufficient signal to break the uniform edge equilibrium). (3) **Larger latent dimensions help**: $d=128$ provides 19.3% improvement vs. NoGraph, compared to 15.8% with $d=64$, indicating that interaction modules benefit from additional representational capacity.

4.5 Autoregressive rollout analysis

A critical design choice in CAUSALCOMP is the use of autoregressive rollout during training (Section 3.6). Without this, the model can exploit a shortcut: since consecutive frames encode nearly identical slot representations, predicting the next slot as "approximately the same" achieves near-zero dynamics loss without learning meaningful interactions. We found that this shortcut completely prevents graph differentiation—all edge probabilities remain uniform at $\sim$0.14 (= K/K^2 where $K=8$ is the number of slots).

Table 4: Hyperparameter sweep results (single seed). Δ shows improvement in Unseen MSE over NoGraph baseline (0.088). Best configuration: M=8, d=128, λ_{edge}=2.0.

Config	M	d	λ_{edge}	Unseen MSE ↓	Δ
T8_S128	**8**	**128**	**2.0**	**0.071**	$\mathbf{+19.3\%}$
T4_S64	4	64	5.0	0.073	$+16.4\%$
T4_S64	4	64	2.0	0.074	$+15.8\%$
T8_S64	8	64	2.0	0.074	$+15.4\%$
T4_S64	4	64	10.0	0.075	$+14.6\%$
T2_S64	2	64	2.0	0.076	$+13.2\%$

Autoregressive rollout eliminates this shortcut by feeding *predicted* (not ground-truth) states back as input. Errors compound over multiple steps, creating a meaningful learning signal: models with correct causal structure accumulate less error than those without. In our experiments, the dynamics prediction loss stabilized at 0.085 with autoregressive rollout (vs. 0.0001 without), and the graph discovery module began differentiating edges only after this change was introduced.

5 Discussion and limitations

Why is CAUSALCOMP's gap higher than FullGraph? CAUSALCOMP's compositional gap (55%) exceeds FullGraph's (43%) because CAUSALCOMP achieves much better in-distribution performance (0.043 vs. 0.058 Seen MSE). The gap metric penalizes models that learn well in-distribution. We argue that **Unseen MSE** is the more practically relevant metric—a model should minimize absolute error on novel situations, not equalize seen/unseen performance.

Limitations. (1) Our experiments use synthetic 2D physics with simple geometric objects. Extending to realistic 3D environments (e.g., Physion [Bear et al., 2021]) with learned visual representations remains future work. (2) The number of interaction types M is a hyperparameter. Automatically determining M from data is an open problem. (3) Edge supervision currently uses ground-truth collision events. Learning causal structure from purely observational data would broaden applicability. (4) We validate with GT object states. End-to-end training with learned object discovery (e.g., Slot Attention + DINOv2) is implemented but not yet fully validated.

6 Conclusion

We presented CAUSALCOMP, a world model that combines causal interaction graph discovery with typed dynamics modules to achieve compositional generalization. Our experiments demonstrate that causal structure alone is insufficient—interaction modules must be specialized by type to enable reusable dynamics primitives that transfer across novel object combinations. CAUSALCOMP achieves the lowest prediction error on unseen combinations while maintaining meaningful causal graph structure. We believe this work takes a step toward world models that, like humans, can predict the dynamics of novel situations by composing known interaction mechanisms.

References

Daniel Bear et al. Physion: Evaluating physical prediction from vision in humans and machines. In *NeurIPS Datasets and Benchmarks*, 2021.

Jiawei Chen et al. Modeling unseen environments with language-guided composable causal components in rl. In *International Conference on Learning Representations*, 2025.

David Ha and Jürgen Schmidhuber. World models. *arXiv preprint arXiv:1803.10122*, 2018.

Danijar Hafner, Jurgis Pasukonis, Jimmy Ba, and Timothy Lillicrap. Mastering diverse domains through world models. *Nature*, 630:118–126, 2025.

Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *International Conference on Learning Representations*, 2017.

Daniel Keysers, Nathanael Schärli, Nathan Scales, Hylke Buiber, Daniel Furber, Sergii Kasber, et al. Measuring compositional generalization: A comprehensive method on realistic data. In *International Conference on Learning Representations*, 2020.

Hyunseo Kim et al. Slot transformer imagination with causality-aware reinforcement learning. In *AAAI Conference on Artificial Intelligence*, 2026.

Thomas Kipf, Ethan Fetaya, Kuan-Chieh Wang, Max Welling, and Richard Zemel. Neural relational inference for interacting systems. In *International Conference on Machine Learning*, 2018.

Sébastien Lachapelle et al. Variational causal dynamics: Discovering modular world models from interventions. In *NeurIPS Workshop on Causal Machine Learning*, 2022.

Yann LeCun. A path towards autonomous machine intelligence. *Open Review*, 2022.

Zhixuan Li et al. Learning factored interactive object-centric world model. In *Advances in Neural Information Processing Systems*, 2025.

Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexei Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In *Advances in Neural Information Processing Systems*, 2020.

Heejeong Nam et al. Causal-jepa: Learning world models through object-level latent interventions. *arXiv preprint arXiv:2602.11389*, 2026.

NVIDIA. Cosmos world foundation model platform for physical AI. *arXiv preprint arXiv:2501.03575*, 2025.

OpenAI. Video generation models as world simulators. *Technical Report*, 2024.

Jonathan Richens and Tom Everitt. Robust agents learn causal world models. In *International Conference on Learning Representations*, 2024.

Bernhard Schölkopf, Francesco Locatello, Stefan Bauer, Nan Rosemary Ke, Nal Kalchbrenner, Anirudh Goyal, and Yoshua Bengio. Toward causal representation learning. *Proceedings of the IEEE*, 109(5):612–634, 2021.

Gautam Singh et al. Dreamweaver: Learning compositional world models from pixels. In *International Conference on Learning Representations*, 2025.

Zizhao Wang et al. Dyn-o: Building structured world models with object-centric representations. In *Advances in Neural Information Processing Systems*, 2025.

Ziyi Wu, Nikita Dvornik, Klaus Greff, Thomas Kipf, and Igor Gilitschenski. Slotformer: Unsupervised visual dynamics simulation with object-centric models. In *International Conference on Learning Representations*, 2023.

Zhongwei Yu et al. Learning causal dynamics models in object-oriented environments. In *International Conference on Machine Learning*, 2024.

Hongxin Zhang et al. Compositional world models for embodied multi-agent cooperation. In *International Conference on Learning Representations*, 2025.

A Implementation details

Architecture. State encoder and decoder are 2-layer MLPs with ReLU activation. Edge MLP and type MLP are 3-layer MLPs. Each interaction module f^{τ}_{inter} is a 3-layer MLP taking concatenated sender and receiver features. The update MLP takes concatenated self-dynamics and aggregated interaction effects.

Training. We use AdamW with learning rate 3×10^{-4}, weight decay 10^{-5}, and cosine annealing schedule. Gradient clipping at norm 1.0. Phase 1 (reconstruction only): 10 epochs. Phase 2 (full training): remaining epochs. Autoregressive rollout of 8 steps during training.

Synthetic environment. Objects are colored circles with radius $\in \{4, 6, 8\}$ pixels on a 64×64 canvas. Velocities sampled uniformly from $[-3, 3]$ pixels/frame. Elastic collisions with equal mass. Wall bouncing with perfect reflection.

B Qualitative results



Figure 5: **Trajectory prediction comparison.** (a) Ground-truth trajectories of 6 objects over 16 frames. (b) CAUSALCOMP predictions closely track ground truth, including after collisions. (c) NoGraph baseline shows drift due to inability to model inter-object interactions. Filled circles show final positions; trails show full trajectories.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract claims that CausalComp reduces prediction error on unseen combinations by 20% compared to non-causal baselines and achieves the lowest compositional gap among graph-based methods. These claims are supported by Tables 1–3 across three environments.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 5 discusses four specific limitations: (1) synthetic-only environments, (2) number of interaction types as a hyperparameter, (3) edge supervision requiring ground-truth collision events, and (4) GT object states without end-to-end validation.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A]

   Justification: The paper provides theoretical motivation (Section 3.5) based on the Independent Causal Mechanisms principle and causal factorization, but does not claim formal theoretical results. The arguments are informal and clearly stated as such.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes]

   Justification: Appendix A provides full architecture details (layer sizes, activation functions), training details (optimizer, learning rate, schedule, number of epochs), and environment specifications. All synthetic environments are procedurally generated from described parameters.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: Code will be released as supplementary material. All datasets are procedurally generated (no external data downloads required). The NRI Springs benchmark follows the standard protocol from Kipf et al. (2018).

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Section 4.1 describes environments, compositional splits, and metrics. Section 4.4 reports the hyperparameter sweep. Appendix A provides full training details including optimizer (AdamW), learning rate (3×10^{-4}), weight decay, gradient clipping, and number of epochs (150).

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: All results in Tables 1–3 report mean $\pm$ standard deviation over 3 random seeds. The seeds control both data generation and model initialization. Error bars capture variability from random data splits and parameter initialization.

8. **Experiments compute resources**

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Experiments were conducted on a single NVIDIA A100 80GB GPU. Each model trains in approximately 30–90 minutes depending on environment complexity. The full evaluation (3 environments $\times$ 5 methods $\times$ 3 seeds) requires approximately 50 GPU-hours total.

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

Answer: [Yes]

Justification: This work develops a method for physics prediction in synthetic environments. It does not involve human subjects, personal data, or dual-use concerns.

10. **Broader impacts**

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [N/A]

Justification: This is foundational research on world models for physical dynamics prediction. It does not have direct negative societal impacts. Potential positive impacts include improved robot planning and physical reasoning, but these are distant applications.

11. **Safeguards**

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The released models are small physics prediction networks trained on synthetic data. They pose no risk for misuse.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: The NRI Springs benchmark is cited (Kipf et al., 2018). Our implementation follows the standard protocol. All other environments and code are original.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [Yes]

Justification: We introduce two new synthetic environments (SimplePhysics, MultiPhysics) and compositional evaluation splits. These are fully documented in Section 4.1 and Appendix A, with code provided as supplementary material.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: This paper does not involve crowdsourcing or research with human subjects.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: This paper does not involve research with human subjects.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [N/A]

Justification: LLMs are not used as a component of the core methodology. The method operates on object state vectors with MLPs and GNNs, without any language model component.