

ans =

10-Feb-2015 10:30:12

Torsion Suspension (suspTorsion.m)

- torsion suspension wire material: Tungsten
- torsion suspension wire loss angle: $1e-07$
- torsion suspension wire temperature: 293 K
- torsion wire diameter (single wire, multiplied safety factor 1.5x): 466.0401

um

- torsion suspension wire length: 0.6 m
- torsion spring constant (2 wire): 0.028786 Nm/rad
- torsion bar inertia: $0.62492\text{kg}\cdot\text{m}^2$
- torsion resonance: 0.034158 Hz

You are not injecting squeezing..loozer!

- Seismic Isolator: MinusK
- Seismic Ground Motion: LL0
- Seismic Isolator: MinusK
- Seismic Ground Motion: LL0

Laser Power: 0.010 Watt

SRM Detuning: 0.00 degree

SRM transmission: 1.0000

ITM transmission: 0.0213

PRM transmission: 1.0000

Finesse: 294.71

Power Recycling Factor: 1.00

Arm power: 0.00 kW

Power on beam splitter: 0.01 W

Thermal load on ITM: 0.000 W

Thermal load on BS: 0.000 W

Required TCS efficiency: 1.000(estimate, see IFOModel.m for definition)

BNS Inspiral Range: 0.000 Mpc

BBH Inspiral Range: 0.002 Mpc

Stochastic Omega: $5e+01$ Universes

New Nebulous Range: 0.990 Mpc

TORPEDO Configuration (nomm_anu_pType1.m)

- Bar length and diameter: 0.6 m x 0.06 m. (dumbell)
- Bar material: Aluminium
- Bar material loss angle: $1.13e+06$
- Bar temperature: 293 K
- Bar mass: 13.911 kg