

ans =

16-Feb-2015 15:30:50

Torsion Suspension (suspTorsion.m)

- torsion suspension wire material: Tungsten
- torsion suspension wire loss angle: $1e-07$
- torsion suspension wire temperature: 293 K
- torsion wire diameter (single wire, multiplied safety factor 1.5x): 1015.4936 μm
- torsion suspension wire length: 1.2 m
- torsion spring constant (2 wire): 0.068337 Nm/rad
- torsion bar inertia: 12.1592 kg*m²
- torsion resonance: 0.011932 Hz

You are not injecting squeezing..loozer!

- Seismic Isolator: CMG3T
- Seismic Ground Motion: LL0
- Seismic Isolator: CMG3T
- Seismic Ground Motion: LL0

Laser Power: 0.100 Watt
SRM Detuning: 0.00 degree
SRM transmission: 1.0000
ITM transmission: 0.0213
PRM transmission: 1.0000
Finesse: 294.71

Power Recycling Factor: 1.00
Arm power: 0.01 kW
Power on beam splitter: 0.10 W
Thermal load on ITM: 0.000 W
Thermal load on BS: 0.000 W
Required TCS efficiency: 1.000 (estimate, see IFOModel.m for definition)
BNS Inspiral Range: 0.000 Mpc
BBH Inspiral Range: 0.002 Mpc
Stochastic Omega: 2e+01 Universes

New Nebulous Range: 0.936 Mpc

TORPEDO Configuration (nomm_anu_pType1.m)

- Bar length and diameter: 1.2 m x 0.08 m. (dumbell)
- Bar material: Aluminium
- Bar material loss angle: 1.13e+06
- Bar temperature: 293 K
- Bar mass: 66.049 kg