

ans =

11-Apr-2015 21:58:19

Torsion Suspension (suspTorsion.m)

- torsion suspension wire material: Silica
- torsion suspension wire loss angle: $4.1e-10$
- torsion suspension wire temperature: 293 K
- torsion wire diameter (single wire, multiplied safety factor 1.5x): 1568.3193 μm
- torsion suspension wire length: 0.6 m
- torsion spring constant (2 wire): 0.027166 Nm/rad
- torsion bar inertia: $0.6392\text{kg}\cdot\text{m}^2$
- torsion resonance: 0.03281 Hz

You are not injecting squeezing..loozer!

- Seismic Isolator: MultiSAS
- Seismic Ground Motion: LLO
- Seismic Isolator: MultiSAS
- Seismic Ground Motion: LLO

Laser Power: 0.100 Watt
SRM Detuning: 0.00 degree
SRM transmission: 1.0000
ITM transmission: 0.0213
PRM transmission: 1.0000
Finesse: 294.71
Power Recycling Factor: 1.00
Arm power: 0.01 kW
Power on beam splitter: 0.10 W
Thermal load on ITM: 0.000 W
Thermal load on BS: 0.000 W
Required TCS efficiency: 1.000 (estimate, see IFOModel.m for definition)
BNS Inspiral Range: 0.000 Mpc
BBH Inspiral Range: 0.003 Mpc
Stochastic Omega: 7 Universes

New Nebulous Range: 1.320 Mpc

TORPEDO Configuration (nomm_anu_pType1.m)

- Reference Cavity Length: 6.2 m
- Arm Lengths: 0.368 m
- Bar length and diameter: 0.6 m x 0.06 m.
- Bar material: Aluminium
- Bar material loss angle: $1.13e+06$
- Bar temperature: 293 K
- Bar mass: 13.128 kg

