

ans =

26-Jan-2015 17:22:26

Torsion Suspension (suspTorsion.m)

- torsion suspension wire material: Silicon
- torsion suspension wire loss angle: $1e-09$
- torsion suspension wire temperature: 120 K
- torsion wire diameter (single wire, multiplied safety factor 15x): 41.9824 μm
- torsion suspension wire length: 0.4 m
- torsion spring constant (2 wire): 0.0004088 Nm/rad
- torsion bar inertia: $0.00035559\text{kg}\cdot\text{m}^2$
- torsion resonance: 0.17065 Hz

You are not injecting squeezing..loozer!

- Seismic Isolator: MinusK
- Seismic Ground Motion: LL0
- Seismic Isolator: MinusK
- Seismic Ground Motion: LL0

Laser Power: 0.010 Watt

SRM Detuning: 0.00 degree

SRM transmission: 1.0000

ITM transmission: 0.0140

PRM transmission: 1.0000

Finesse: 448.16

Power Recycling Factor: 1.00

Arm power: 0.00 kW

Power on beam splitter: 0.01 W

Thermal load on ITM: 0.000 W

Thermal load on BS: 0.000 W

Required TCS efficiency: 1.000 (estimate, see IFOModel.m for definition)

BNS Inspiral Range: 0.000 Mpc

BBH Inspiral Range: 0.001 Mpc

Stochastic Omega: $4e+02$ Universes

New Nebulous Range: 0.508 Mpc

TORPEDO Configuration

- Bar length and diameter: 0.18 m x 0.02 m.
- Bar material: Silicon
- Bar material loss angle: $1e+09$
- Bar temperature: 120 K
- Bar mass: 0.1317 kg