Optimal Spring Sizing

Landon Wright

January 24, 2018

Summary

0.1 Design variable values

The optimal cost was found to be $400,140. The determined optimum values for the design variables are as follows:

Table 1: Optimum values for design

Variable	**Value**
Velocity	$7.8161\frac{ft}{s}$
Pipe Diameter	$0.1816ft$
Particle Size	$0.0005ft$
Water Flow Rate	$0.1128\frac{ft^3}{s}$
Volumetric Concentration	0.4
Slurry Density	$104.84\frac{lbm}{ft^3}$

0.2 Design function values

Table 2: Values of design functions at optimum

Design Function	**Value**
Maximize F_0	$6.4541lbs$
$h_S + 0.05 \leq h_{def}$	$0.60in \leq 0.60in$
$\tau_a \leq \frac{s_e}{s_f}$	$18352psi \leq 30000psi$
$\tau_a + \tau_m \leq \frac{s_y}{s_f}$	$70576psi \leq 70576psi$
$4 \geq \frac{D}{d} \leq 16$	$4in \leq 9.359in \leq 16in$
$D + d \leq 0.75$	$0.75in \leq 0.75in$
$\tau_{solid} \leq s_y$	$75165psi \leq 105860psi$

0.3 Binding Constraints

The binding constraints are:

- $h_S + 0.05 \leq h_{def}$
- $D + d \leq 0.75$
- $\tau_a + \tau_m \leq \frac{s_y}{s_f}$

1 Setup

1.1 Variable Mapping

Table 3: My caption

Analysis Variables	**Design Variables**
Wire Diameter	Wire Diameter
Coil Diameter	Coil Diameter
Number of Coils	Number of Coils
Free height	Free height
Preload Height	
Preload Deflection	
Shear Modulus	
Safety Factor	
Endurance Limit	

Analysis Functions	**Design Functions**
Force	Maximize
Spring Stiffness	Solid Height $\leq$ Deflected height
Whal Factor	Alternating Stress $\leq \frac{s_e}{s_f}$
Solid Height	Alternating and Mean Stress $\leq \frac{s_y}{s_f}$
Alternating Stress	$4 \leq$ Coil to Wire Ratio ≤ 16
Mean Stress	Solid Stress $\leq s_y$
Yield Strength	
Coil to Wire Ratio	
Spring Diameter	
Deflected Height	

2 Results

2.1 Optimum values of variables and functions

Table 4: Optimum Values of Variables and Functions (binding functions are highlighted)

Variable/Function	**Value**
Wire Diameter	0.0724 in
Coil Diameter	0.6776 in
Number Coils	0.5928
Free Height	1.3691
Preload Height	1.0 in
δ_0	0.4 in
h_{def}	0.6 in
h_s	0.55in
F_0	6.454 lbs
k	17.4853 lbs/in
K	1.1561
τ_{max}	70576 psi
τ_{min}	33871 psi
τ_a	18353 psi
τ_m	52224 psi
$\tau_a + \tau_m$	70576 psi
$\frac{S_e}{S_f}$	30000 psi
$\frac{S_y}{S_f}$	70576 psi
$\frac{D}{d}$	9.3539
$D + d$	0.75

2.2 Starting points and obtained values

Table 5: Optimized Values from Given Starting Point

	Initial Values				**Optimized Values**			
Trial	Wire Diameter	Coil Diameter	Number of Coils	Free Height	Wire Diameter	Coil Diameter	Number of Coils	Free Height
1	0.04735309758	0.2632045077	13.47275949	1.525959964	0.07243674785	0.6775631377	7.592829475	1.369115417
2	0.07681530634	0.6400386081	12.94948955	1.594751247	0.07243674785	0.6775631377	7.592829475	1.369115417
3	0.1842667961	0.2857953622	15.87240389	1.778356185	0.07243674785	0.6775631377	7.592829475	1.369115417
4	0.08228471093	0.4690840665	4.289522923	1.148555107	0.07243674785	0.6775631377	7.592829475	1.369115417
5	0.1108515351	0.6064586996	18.87818163	1.216915588	0.07243674785	0.6775631377	7.592829475	1.369115417
6	0.1180764956	0.4051039167	3.202335182	1.40341038	0.07243674785	0.6775631377	7.592829475	1.369115417
7	0.04081463856	0.6162849514	8.290655715	1.575679822	0.07243674785	0.6775631377	7.592829475	1.369115417
8	0.0414732586	0.4912882619	7.470511837	1.688671189	0.07243674785	0.6775631377	7.592829475	1.369115417
9	0.1409507556	0.5862985353	10.65920717	1.17543924	0.07243674785	0.6775631377	7.592829475	1.369115417
10	0.05350562406	0.693669285	5.590426322	1.84323528	0.07243674785	0.6775631377	7.592829475	1.369115417

2.3 Design space contour plot



Figure 1: Contour plot showing the design space

2.4 Feasible design space contour plot



Figure 2: Contour plot showing the feasible design space

3 Discussion

As can be seen in figure 1 the design space for this problem is quite restricted. There are several contraints and the feasible design space is quite small compared to the total design space, at least when viewed on a contour plot of wire diameter and spring diameter. Due to the fact that the contours shown in Figure 1 are quite linear and that the various initial values tried all converged to the same value as shown in Table 5 I conclude that we have found a global optimum for the spring given the applied constraints. It is also of interest that the optimum appears to be bound by three constraints, meaning that if we wanted to increase the increase the rate of the spring by only changing the spring or wire diameter we would need to either relax the alternating and mean stress constraint(ie. find a stronger material), or we would need to relax both the solid height and spring size constraints. It is important to remember that Figures 1 and 2 are only showing a portion of the design space and other options should also be considered

4 Appendix

4.1 Matlab files

4.1.1 Optmization code

4.1.2 Plotting Code