

to pass, return to station in rear. If the Loco Pilot is not able to find anything doubtful, subsequent trains shall be dispatched with a speed restriction of 10 kilometres per hour over the suspected track length until the track is certified to be safe by engineering officials. If the condition as reported earlier is confirmed by the Loco Pilot, then no train movement shall be allowed till the track is certified to be safe by engineering officials.

Obstruction on adjacent track

If Loco Pilot and / or Guard notices any obstruction or any other unsafe condition, on or near the track adjacent to the line over which his train has passed, they shall immediately switch on the flasher light of loco and inform the Station Master(s) concerned through the available means of communication. Concurrently, the Loco pilot and Guard shall also stop their train and proceed with danger hand signals to protect the obstructed line. If there are trains on run towards the obstructed track that cannot be stopped by the Station Master, in electrified section, OHE shall be immediately switched off from the Traction Power Control.

Once it is ensured that there are no trains that are on run towards the affected spot, they shall continue journey to the next station cautiously keeping flasher light on and be prepared to stop any incoming train approaching on the affected line by exhibiting danger hand signal or any other available means of communication like walkie talkie. On arrival at the next station, he/she shall inform the Station Master through a written memo about the occurrence. On receipt of such information, the Station Master shall take action as per SR 6.07.1(c) to (f).

Patrolman not turned up in time

When patrolling is in force, if a Patrolman does not turn up within 15 minutes of his/her scheduled arrival, the Station Master shall stop run through trains proceeding into the block section and issue a Caution Order to all trains proceeding into the block section advising the Loco Pilot to be alert and specify a speed restriction of 40 KMPH. The Station Master shall also immediately advise the Station Master at the other end of the block section to take similar action and advise the SCOR, the concerned section Gangmate and the PWI. The Caution Orders shall continue to be issued till the Patrolman arrives and report that the line is safe for passage of trains.

Unusals in a running train

Hot Axle

Hot Axle is a condition where the axle of the wheel gets heated up because of reasons like faulty bearings, insufficient greasing etc. that leads to excess friction during wheel rotation. If the condition continues, it can result in seizure of axle and derailment.