

Semi-Auto Chemistry Analyzer

ACCUCHEM-100



Features

Compact design

User-friendly software

Perfect balance of efficiency and flexibility

Convenient operation through touch screen

Intelligent & humanized software

6 Interfaces, more suitable for 5 USB interfaces + ethernet port.

Powerful inner core, huge storage

Windows embedded compact 7 smart operation system

Technical specifications

Test method	1 point end, 2 point end (sample blank), Kinetics, Fixed-time
Optics	7 Standard filters: 340nm, 405nm, 450nm, 505nm, 546nm, 578nm, 630nm, 2 more for optional
Display	7" TFT-LCD color touch screen, 800 X 480 pixels, friendly user interface, convenient operation.
Lamp house	Long-life tungsten halogen lamp (6V/10W), auto sleep function
Printer	Build-in thermal printer, 57mm printer paper
Temperature	25, 30, 37°C and room temperature. By means of peltier elements
Flow cell capacity & optical path	32μL, 10mm
Resolution	0.0001 Abs
Photometric range	0.0000 – 4.0000 Abs
CPU	ARM Cortex-A8, 800MHz
Memory (storage)	4 GB Over 300 programs, 200000 results can be stored
Interface	4 USB Hosts, 1 USB Slave, 1 Ethernet port USB port (host) for keyboard, mouse, printer, U disk, barcode reader etc. USB port (slave) for PC connection (support PC software control function)
Operational environment	Temperature: 10°C~30°C, Humidity: 30% - 80%
Power requirement	Wide power supply AC 100-240V, 50/60Hz
Dimension	380 X 280 X 180 mm (L X W X H)
Weight	4.1 Kg

Contact Us

Lab-Care Diagnostics (India) Pvt. Ltd.,
16 A, 'A' Wing, Sita Estate, 1st Floor, Aziz Baug,
Mahul Road, Chembur, Mumbai-400074, India.
Email: exports@labcarediagnostics.com