

ST-200CC[®]

Ultra Smart



ABGEM Blood Gas Analyzer



Analyzer's Advantages

-  Minimal Maintenance
-  Easy to Operate
-  Economical
-  Accurate Results

SENSA[®]CORE

Sensa Core Medical Instrumentation Pvt. Ltd.
Plot No: 3, Export Promotion Industrial Park, Pashamylaram, Sangareddy (Dist) - 502307.
Hyderabad, Telangana, INDIA. Tel: +91 8455 - 223400

www.sensacore.com


info@sensacore.com



Toll Free No: 1800 212 2880


SENSA[®]CORE

- Aspirate 1 sample and acquire 27 different results.
Blood gas : pH, pCO₂, pO₂, Hct.
Electrolytes : Na, K, iCa, Li, pH, Cl.
Metabolites : GLU, LAC.
Calculated Parameters : Hb, HCO₃, BE, BE-B, BE-ECF, TCO₂, AG, AG(K), O₂ Sat, O₂ Ct, SBC, nCa, TCa, pO₂%, A, AaDO₂, a/A.
- Levey-Jennings chart for NABL and seamless integration to LIS (Lab information system).
- Numeric & alpha numeric input option with 15 digit operator and patient ID.
- Self probe wiping facility with 3 different aspiration modes (sample tube, sample syringe & capillary).
- The result can be recalled by Date, Patient ID, Patient name, by parameters etc.
- External mouse & keypad interfacing option.
- 10 inch high definition LCD with capacitive touch screen.
- Single Reagent pack for all 16 combinations.
- Integrated Parameter conversion functionality.
- Single touch calibration for new reagent pack.
- Maximum 1,00,000 sample storage capacity.
- Optional battery backup & much more.
- Internal barcode scanner.
- Excellent precision and reliability.
- USB output port. (USB 2.0)
- Extremely low cost per test.
- Multilingual support.





Specifications



- Principle : Direct measurement with ion selective electrode (ISE), Impedence (Hct) and Amperometry (pO₂, GLU, LAC).
- Reading time : 60 seconds.
- Parameters : This functionality allows the change of analytes.
- Sample Type : Whole blood, serum, plasma, CSF and diluted urine.
- Conditioning : Temperature: 10°C - 30°C, <85% moisture.
- Display : 10 inch high definition LCD with capacitive touch.
- Print : 2 inch 24 column thermal printer.
- Input voltage : 100/115-V AC, 50-60 Hz (or) 220V AC, 50-60 Hz, 0.75 amp.
- Dimensions : 12.8" W x 17.3" H x 10.6" D, Weight: 7.55 kg.
- OS : Android.
- Analysis Speed : 60 Seconds.
- Sample volume : 100µL (Capillary/Micro Mode).
- Battery : Optional support for 4 hours.
- Storage : 1,00,000

ABGEM	ABCM	ABGE	ABC	ELECTROLYTE															
BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD	BD
pO ₂ Hct	pO ₂ Hct	pO ₂ Hct	pO ₂ Hct	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
K	K	K	B	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K
Na	Na	Na	B	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na	Na
iCa	iCa	iCa	B	B	iCa	iCa	iCa	iCa	iCa	iCa	iCa	iCa	iCa	iCa	iCa	iCa	B	B	B
pH	pH	pH	pH	pH	pH	Li	Li	pH	Li	pH	pH	Li	B	B	B	B	B	B	B
pCO ₂	pCO ₂	pCO ₂	pCO ₂	HCO ₃	HCO ₃	pH	B	B	pH	B	B	B	B	B	B	B	B	B	B
Cl	Cl	Cl	Cl	Cl	Cl	Cl	Cl	Cl	B	B	B	Cl	B	Cl	B	Cl	B	Cl	B
GLU LAC	LAC	③	④	⑤	⑥	⑦	⑧	⑨	⑩	⑪	⑫	⑬	⑭	⑮	⑯	⑰	⑱	⑲	⑲
①	②			Parameter Combinations															

Parameter	Measuring Range Blood	Measuring Range Urine
Na+	20.0 - 250.0 mmol/L	25.0 - 1000.0 mmol/L
K+	0.20 - 40.0 mmol/L	1.0 - 500.0 mmol/L
Cl-	25.0 - 200.0 mmol/L	25.0 - 500.0 mmol/L
iCa++	1.0 - 20.0 mg/dL	***
Li+	0.2 - 5.0 mmol/L	***
pH	5 - 9	***
pO ₂	10 - 750 mmHg	***
pCO ₂	5 - 120 mmHg	***
TCO ₂	5 - 50 mmol/L	***
Hct	10 - 70 %	***
HCO ₃	5 - 50 mmol/L	***
GLU	20 - 800 mg/dL	***
LAC	0.1 - 24 mmol/L	***