

# God in Coq: Modal Logic in Coq and Scott's Version of Gödel's Proof of God's Existence

(Rough Diamond Proof Pearl)

Christoph Benz Müller<sup>1\*</sup> and Bruno Woltzenlogel Paleo<sup>2</sup>

<sup>1</sup> Dahlem Center for Intelligent Systems, Freie Universität Berlin, Germany  
c.benzmueller@gmail.com

<sup>2</sup> Theory and Logic Group, Vienna University of Technology, Austria  
bruno@logic.at

## 1 Introduction

Gödel's proof of God's existence is challenging to formalize and verify because it requires an expressive logical language with modal operators ( $\Diamond$  and  $\Box$ ) and higher-order quantifiers. Specialized modal logic tools lack higher-order capabilities, while higher-order provers lack built-in support for modalities. However, by embedding modal logics into higher-order logic, it is in principle possible to use standard higher-order automated and interactive theorem provers for reasoning about and within modal logics [4, 3]. To realize this potential, formalizations [26] of Gödel's proof in TPTP THF [25], Coq [8] and Isabelle [21] have been completed so far, in this order. This paper focuses on the formalization in Coq. The implementation of the embedding is discussed in detail in Section 2 and Scott's version of Gödel's proof is shown in Section 3.

## 2 Modal Logic in Coq

A crucial aspect of modal logics [9] is that the so-called *necessitation rule* allows  $\Box A$  to be derived if  $A$  is a theorem, but  $A \rightarrow \Box A$  is not necessarily a theorem. Naive attempts to define the modal operators  $\Box$  and  $\Diamond$  may easily be unsound in this respect. To avoid this issue, the *possible world semantics* of modal logics can be explicitly embedded into higher-order logics [4, 3]. The embedding is related to labeling techniques [16]. However, the expressiveness of higher-order logic is exploited here to encode the labels within the logic language itself. To this aim, a type for worlds must be declared and modal propositions should be not of type **Prop** but of a lifted type that depends on possible worlds. Possible worlds are connected by an accessibility relation.

```
Parameter i: Type. (* Type for worlds *)
Parameter u: Type. (* Type for individuals *)
Definition o := i -> Prop. (* Type of modal propositions *)
Parameter r: i -> i -> Prop. (* Accessibility relation for worlds *)
```

All modal connectives are simply lifted versions of the usual logical connectives. Notations are used to allow the modal connectives to be used as similarly as possible as the usual connectives. The prefix “m” is used to distinguish the modal connectives: if  $\odot$  is a connective on type **Prop**, **m** $\odot$  is a connective on the lifted type **o** of modal propositions.

```
Definition mequal (x y: u) := fun w: i => x = y.
Notation "x m= y" := (mequal x y) (at level 99, right associativity).
```

```
Definition mnot (p: o)(w: i) := ~ (p w).
Notation "m~ p" := (mnot p) (at level 74, right associativity).
```

---

\* This work has been supported by the German Research Foundation (DFG) under grant BE2501/9-1.

**Definition** `mand (p q:o)(w: i) := (p w) /\ (q w).`  
**Notation** `"p m/\ q" := (mand p q) (at level 79, right associativity).`

**Definition** `mor (p q:o)(w: i) := (p w) \/ (q w).`  
**Notation** `"p m\/ q" := (mor p q) (at level 79, right associativity).`

**Definition** `mimplies (p q:o)(w:i) := (p w) -> (q w).`  
**Notation** `"p m-> q" := (mimplies p q) (at level 99, right associativity).`

**Definition** `mequiv (p q:o)(w:i) := (p w) <-> (q w).`  
**Notation** `"p m<-> q" := (mequiv p q) (at level 99, right associativity).`

Likewise, modal quantifiers are lifted versions of the usual quantifiers.

**Definition** `A t: Type(p: t -> o) := fun w => forall x, p x w.`  
**Notation** `"'mforall' x , p" := (A (fun x => p))`  
(at level 200, x ident, right associativity) : type\_scope.  
**Notation** `"'mforall' x : t , p" := (A (fun x:t => p))`  
(at level 200, x ident, right associativity,  
format `"[' 'mforall' '/' ' x : t , '/' ' p ']"`)  
: type\_scope.

**Definition** `E t: Type(p: t -> o) := fun w => exists x, p x w.`  
**Notation** `"'mexists' x , p" := (E (fun x => p))`  
(at level 200, x ident, right associativity) : type\_scope.  
**Notation** `"'mexists' x : t , p" := (E (fun x:t => p))`  
(at level 200, x ident, right associativity,  
format `"[' 'mexists' '/' ' x : t , '/' ' p ']"`)  
: type\_scope.

The modal operators  $\Diamond$  (*possibly*) and  $\Box$  (*necessarily*) are defined accordingly to their meanings in the possible world semantics.

**Definition** `box (p: o) := fun w => forall w1, (r w w1) -> (p w1).`  
**Definition** `dia (p: o) := fun w => exists w1, (r w w1) /\ (p w1).`

To maximally preserve user intuition in interactive modal logic theorem proving, the embedding via the possible world semantics should be as transparent as possible to the user. Fortunately, basic Coq tactics such as `intro`, `apply` and `split` automatically unfold the modal definitions. They can thus be used with modal connectives and quantifiers just as they are used with the usual connectives and quantifiers. For the modal operators, however, the following simple tactics have been implemented, in order to allow the user to work with the concepts of *necessity* and *possibility* without having to unfold the definitions of modal operators and think in terms of possible worlds.

**Ltac** `box_i := let w := fresh "w" in let R := fresh "R"`  
`in (intro w at top; intro R at top).`

**Ltac** `box_elim H w1 H1 := match type of H with`  
`((box ?p) ?w) => cut (p w1); [intros H1 | (apply (H w1); try assumption)] end.`

**Ltac** `box_e H H1:= match goal with | [ |- (_ ?w) ] => box_elim H w H1 end.`

**Ltac** `dia_e H := let w := fresh "w" in let R := fresh "R"`  
`in (destruct H as [w [R H]]; move w at top; move R at top).`

**Ltac** `dia_i w := (exists w; split; [assumption | idtac]).`

Validity of a modal proposition is validity of its grounding on any world. A non-intrusive notation and a tactic that grounds the proposition to an arbitrary world are provided.

```

Definition V (p: o) := forall w, p w.
Notation "[ p ]" := (V p).
Ltac mv := match goal with [|- (V _)] => intro end.

```

The following lemmas are quite convenient. The first is a kind of modus ponens applicable to formulas under the scope of a modal operator. The second allows pushing negations inside modalities.

```

Lemma mp_dia: [mforall p, mforall q, (dia p) m-> (box (p m-> q)) m-> (dia q)].
Proof. mv. intros p q H1 H2. dia_e H1. dia_i w0. box_e H2 H3. apply H3. exact H1. Qed.

```

```

Lemma not_dia_box_not: [mforall p, (m~ (dia p)) m-> (box (m~ p))].
Proof. mv. intro p. intro H. box_i. intro H2. apply H. dia_i w0. exact H2. Qed.

```

The most well-known modal logics can be distinguished by their acceptance of the following reachability axioms. **S5** is the modal logic that accepts all three.

```

Axiom reflexivity: forall w, r w w.
Axiom transitivity: forall w1 w2 w3, (r w1 w2) -> (r w2 w3) -> (r w1 w3).
Axiom symmetry: forall w1 w2, (r w1 w2) -> (r w2 w1).

```

Modal logic “axioms” can be derived from the reachability axioms.

```

Theorem K: [ mforall p, mforall q, (box (p m-> q)) m-> (box p) m-> (box q) ].
Proof. mv. intros p q H1 H2. box_i. box_e H1 H3. apply H3. box_e H2 H4. exact H4. Qed.

```

```

Theorem T: [ mforall p, (box p) m-> p ].
Proof. mv. intro p. intro H. box_e H H1. exact H1. apply reflexivity. Qed.

```

In strong modal logics, such as S5, iterations of modal operators can be collapsed. This is a controversial principle used in Gödel’s and Scott’s versions of the proof.

```

Theorem dia_box_to_box: [ mforall p, (dia (box p)) m-> (box p) ].
Proof. mv. intro p. intro H1. dia_e H1. box_i. box_e H1 H2. exact H2. eapply transitivity.
  apply symmetry. exact R.
  exact R0.
Qed.

```

### 3 Gödel’s Proof of God’s Existence

Attempts to prove the existence (or non-existence) of God by means of abstract ontological arguments are an old tradition in philosophy and theology. Gödel’s proof [17, 18] is a modern culmination of this tradition, following particularly the footsteps of Leibniz. Various slightly different versions of axioms and definitions have been considered by Gödel and by several philosophers who commented on his proof (cf. [24, 2, 15, 1, 14]). The formalization shown in this section aims at being as similar as possible to Dana Scott’s version of the proof [23]. The formulation and numbering of axioms, definitions and theorems is the same as in Scott’s notes. Even the Coq proof scripts follow all the steps in Scott’s notes. Scott’s assertions are emphasized with comments. In contrast to the formalization in Isabelle [?], where automation via Metis [20] and Sledgehammer [10] using tools such as Nitpick [11], LEO-II [5] and Satallax [13] has been successfully employed, the formalization in Coq used no automation. This was a deliberate choice, mainly because it allowed a qualitative evaluation of the convenience of the possible world semantic embedding approach for *interactive* theorem proving. Moreover, in order to formalize precisely Scott’s version and not another automatically found version, automation would have to be heavily limited anyway. Furthermore, the deliberate preference for simple tactics (mostly *intro*, *apply* and the modal tactics described in the previous section) results in proof scripts that could be read as natural deduction proofs. This hopefully makes the formalization more accessible to those who are not experts in Coq’s tactics but are nevertheless interested in Gödel’s proof.

```

Require Import Coq.Logic.Classical Coq.Logic.Classical_Pred_Type Modal.

Ltac proof_by_contradiction H := apply NNPP; intro H.

(* Constant predicate that distinguishes positive properties *)
Parameter Positive: (u -> o) -> o.

(* Axiom A1: either a property or its negation is positive, but not both *)
Axiom axiom1a : [ mforall p, (Positive (fun x: u => m~(p x))) m-> (m~ (Positive p)) ].
Axiom axiom1b : [ mforall p, (m~ (Positive p)) m-> (Positive (fun x: u => m~ (p x))) ].

(* Axiom A2: a property necessarily implied by a positive property is positive *)
Axiom axiom2: [ mforall p, mforall q,
  Positive p m/\ (box (mforall x, (p x) m-> (q x) )) m-> Positive q ].

(* Theorem T1: positive properties are possibly exemplified *)
Theorem theorem1: [ mforall p, (Positive p) m-> dia (mexists x, p x) ].
Proof. mv.
intro p. intro H1. proof_by_contradiction H2. apply not_dia_box_not in H2.
assert (H3: ((box (mforall x, m~ (p x))) w)). (* Scott *)
  box_i. intro x. assert (H4: ((m~ (mexists x : u, p x)) w0)).
    box_e H2 G2. exact G2.
  clear H2 R H1 w. intro H5. apply H4. exists x. exact H5.
  assert (H6: ((box (mforall x, (p x) m-> m~ (x m= x))) w)). (* Scott *)
  box_i. intro x. intros H7 H8. box_elim H3 w0 G3. eapply G3. exact H7.
  assert (H9: ((Positive (fun x => m~ (x m= x))) w)). (* Scott *)
    apply (axiom2 w p (fun x => m~ (x m= x))). split.
      exact H1.
      exact H6.
  assert (H10: ((box (mforall x, (p x) m-> (x m= x))) w)). (* Scott *)
  box_i. intros x H11. reflexivity.
  assert (H11 : ((Positive (fun x => (x m= x))) w)). (* Scott *)
    apply (axiom2 w p (fun x => x m= x)). split.
      exact H1.
      exact H10.
  apply axiom1a in H9. contradiction.
Qed.

(* Definition D1: God: a God-like being possesses all positive properties *)
Definition G(x: u) := mforall p, (Positive p) m-> (p x).

(* Axiom A3: the property of being God-like is positive *)
Axiom axiom3: [ Positive G ].

(* Corollary C1: possibly, God exists *)
Theorem corollary1: [ dia (mexists x, G x) ].
Proof. mv. apply theorem1. apply axiom3. Qed.

(* Axiom A4: positive properties are necessarily positive *)
Axiom axiom4: [ mforall p, (Positive p) m-> box (Positive p) ].

(* Definition D2: essence: an essence of an individual is a property possessed by it
and necessarily implying any of its properties *)
Definition Essence(p: u -> o)(x: u) := (p x) m/\ mforall q,
  ((q x) m-> box (mforall y, (p y) m-> (q y))).
Notation "p 'ess' x" := (Essence p x) (at level 69).

(* Theorem T2: being God-like is an essence of any God-like being *)

```

```

Theorem theorem2: [ mforall x, (G x) m-> (G ess x) ].
Proof. mv. intro g. intro H1. unfold Essence. split.
  exact H1.
  intro q. intro H2. assert (H3: ((Positive q) w)).
    proof_by_contradiction H4. unfold G in H1. apply axiom1b in H4. apply H1 in H4.
      contradiction.
  cut (box (Positive q) w). (* Scott *)
    apply K. box_i. intro H5. intro y. intro H6. unfold G in H6. apply (H6 q). exact H5.
    apply axiom4. exact H3.
Qed.

(* Definition D3: necessary existence: necessary existence of an individual
is the necessary exemplification of all its essences *)
Definition NE(x: u) := mforall p, (p ess x) m-> box (mexists y, (p y)).

(* Axiom A5: necessary existence is a positive property *)
Axiom axiom5: [ Positive NE ].

Lemma lemma1: [ (mexists z, (G z)) m-> box (mexists x, (G x)) ].
Proof. mv. intro H1. destruct H1 as [g H2]. cut ((G ess g) w). (* Scott *)
  assert (H3: (NE g w)). (* Scott *)
    unfold G in H2. apply (H2 NE). apply axiom5.
    unfold NE in H3. apply H3.
  apply theorem2. exact H2.
Qed.

Lemma lemma2: [ dia (mexists z, (G z)) m-> box (mexists x, (G x)) ].
Proof. mv. intro H. cut (dia (box (mexists x, G x)) w). (* Scott *)
  apply dia_box_to_box.
  apply (mp_dia w (mexists z, G z)).
  exact H.
  box_i. apply lemma1.
Qed.

(* Theorem T3: necessarily, a God exists *)
Theorem theorem3: [ box (mexists x, (G x)) ].
Proof. mv. apply lemma2. apply corollary1. Qed.

(* Corollary C2: There exists a god *)
Theorem corollary2: [ mexists x, (G x) ].
Proof. mv. apply T. apply theorem3. Qed.

```

## 4 Conclusions

The successful formalization of Scott's version of Gödel's proof of God's existence indicates that the *embedding* of modal logics into higher-order logics via the *possible world semantics* is a viable approach for interactive theorem proving within modal logics. The minimalistic implementation of the embedding (Section 2) takes special care to hide the underlying possible world machinery from the user. An inspection of the proof scripts in Section 3 shows that this goal has been achieved. The user does not have to explicitly bother about worlds and their mutual reachability; the provided tactics for modalities do the job for him. Moreover, for subgoals that do not involve modalities, the user has all the usual interactive tactics at his/her disposal.

The theological implications of the verified correctness of this proof certainly depend on a critical discussion of the underlying concepts, definitions and axioms, which is beyond the scope of this paper. What can be said though is that our work presents further evidence that theism is at least not (obviously) irrational.

Related work includes formalizations of Anselm’s argument by Rushby [22], and by Oppenheimer and Zalta [12]. Clearly, the application of theorem proving technology to the domain of theoretical philosophy can — as already pictured by Leibniz — be very fruitful for both areas. In fact, new results of philosophical interest have been obtained by our work [7]. Moreover a first, basic infrastructure for interactive and automated reasoning in higher-order modal logics has been created and will be further improved in the future.

*Acknowledgements:* Thanks to Cedric Auger and Laurent Théry, for their answers to our newbie questions about Ltac in the Coq-Club mailing-list.

## References

1. R.M. Adams. Introductory note to \*1970. In *Kurt Gödel: Collected Works Vol. 3: Unpublished Essays and Letters*. Oxford University Press, 1995.
2. A.C. Anderson and M. Gettings. Gödel ontological proof revisited. In *Gödel’96: Logical Foundations of Mathematics, Computer Science, and Physics: Lecture Notes in Logic 6*. Springer, 1996.
3. C. Benz Müller and L.C. Paulson. Exploring properties of normal multimodal logics in simple type theory with LEO-II. In *Festschrift in Honor of Peter B. Andrews on His 70th Birthday*, pages 386–406. College Publications.
4. C. Benz Müller and L.C. Paulson. Quantified multimodal logics in simple type theory. *Logica Universalis (Special Issue on Multimodal Logics)*, 7(1):7–20, 2013.
5. C. Benz Müller, F. Theiss, L. Paulson, and A. Fietzke. LEO-II - a cooperative automatic theorem prover for higher-order logic. In *Proc. of IJCAR 2008*, volume 5195 of *LNAI*, pages 162–170. Springer, 2008.
6. C. Benz Müller and B. Woltzenlogel Paleo, Formalization, Mechanization and Automation of Gödel’s Proof of God’s Existence. *arXiv:1308.4526*, 2013.
7. C. Benz Müller and B. Woltzenlogel Paleo, Gödel’s God in Isabelle/HOL. *Archive of Formal Proofs*, 2013.
8. Y. Bertot and P. Casteran. *Interactive Theorem Proving and Program Development*. Springer, 2004.
9. P. Blackburn, J.v. Benthem, and F. Wolter (eds.), *Handbook of Modal Logic*. Elsevier, 2006.
10. J.C. Blanchette, S. Böhme, and L.C. Paulson. Extending Sledgehammer with SMT solvers. *Journal of Automated Reasoning*, 51(1):109–128, 2013.
11. J.C. Blanchette and T. Nipkow. Nitpick: A counterexample generator for higher-order logic based on a relational model finder. In *Proc. of ITP 2010*, no. 6172 in *LNCS*, pages 131–146. Springer, 2010.
12. P.E. Oppenheimer and E.N. Zalta. A Computationally-Discovered Simplification of the Ontological Argument. *Australasian Journal of Philosophy*, 89(2):333–349, 2011.
13. C.E. Brown. Satallax: An automated higher-order prover. In *Proc. of IJCAR 2012*, number 7364 in *LNAI*, pages 111 – 117. Springer, 2012.
14. R. Corazzon. Contemporary bibliography on the ontological proof (<http://www.ontology.co/biblio/ontological-proof-contemporary-biblio.htm>).
15. M. Fitting. *Types, Tableaux and Gödel’s God*. Kluwer Academic Press, 2002.
16. D.M. Gabbay. *Labelled Deductive Systems*. Clarendon Press, 1996.
17. K. Gödel. Ontological proof. In *Kurt Gödel: Collected Works Vol. 3: Unpublished Essays and Letters*. Oxford University Press, 1970.
18. K. Gödel. *Appendix A. Notes in Kurt Gödel’s Hand*, pages 144–145. In [24], 2004.
19. A.P. Hazen. On gödel’s ontological proof. *Australasian Journal of Philosophy*, 76:361–377, 1998.
20. J. Hurd. First-order proof tactics in higher-order logic theorem provers. In *Design and Application of Strategies/Tactics in Higher Order Logics, NASA Tech. Rep. NASA/CP-2003-212448*, 2003.
21. T. Nipkow, L.C. Paulson, and M. Wenzel. *Isabelle/HOL: A Proof Assistant for Higher-Order Logic*. Number 2283 in *LNCS*. Springer, 2002.
22. J. Rushby. The Ontological Argument in PVS. In *Proc. of CAV Workshop “Fun With Formal Methods”*, St. Petersburg, Russia, 2013.
23. D. Scott. *Appendix B. Notes in Dana Scott’s Hand*, pages 145–146. In [24], 2004.
24. J.H. Sobel. *Logic and Theism: Arguments for and Against Beliefs in God*. Cambridge U. Press, 2004.
25. G. Sutcliffe and C. Benz Müller. Automated reasoning in higher-order logic using the TPTP THF infrastructure. *Journal of Formalized Reasoning*, 3(1):1–27, 2010.
26. B. Woltzenlogel Paleo and C. Benz Müller. Formal theology repository (<https://github.com/FormalTheology/GoedelGod>).