Daniel Alejandro Osornio López 0244685@up.edu.mx

Resultados



Assessment Items	Status	Points	Component(s)	Feedback
Network				
PC1				
Ports				
FastEthernet0				
IP Address	Correct	15	IPv4 Host Addre…	
Subnet Mask	Correct	2	IPv4 Host Addre…	
PC2				
Ports				
FastEthernet0				
IP Address	Correct	15	IPv4 Host Addre…	
Subnet Mask	Correct	2	IPv4 Host Addre…	
S1				
Banner MOTD	Correct	1	Basic Security C…	
Console Line				
Login	Correct	1	Basic Security C…	
Password	Correct	1	Basic Security C…	
Enable Secret	Correct	1	Basic Security C…	
Host Name	Correct	1	Hostname Confi…	
Ports				
Vlan1				
IP Address	Correct	5	IPv4 Host Addre…	
Port Status	Correct	10	IPv4 Host Addre…	
Subnet Mask	Correct	5	IPv4 Host Addre…	
Startup Config	Correct	2	Configuration M…	
S2				
Banner MOTD	Correct	1	Basic Security C…	
Console Line				
Login	Correct	1	Basic Security C…	
Password	Correct	1	Basic Security C…	
Enable Secret	Correct	1	Basic Security C…	
Host Name	Correct	1	Hostname Confi…	
Ports				
Vlan1				
IP Address	Correct	5	IPv4 Host Addre…	
Port Status	Correct	10	IPv4 Host Addre…	
Subnet Mask	Correct	5	IPv4 Host Addre…	
Startup Config	Correct	2	Configuration M…	

Preguntas

Parte 1

Paso 3

1. ¿Cómo puede verificar que ambas contraseñas se configuraron correctamente?

   A: Mostrando los contenidos de `running-config` con el comando `show running-config`

Paso 4

2. ¿Qué comando emite para realizar este paso?

   A: `copy run start`

Parte 2

Paso 2

1. ¿Tuvo éxito (al hacer `ping` al switch `S1`)? Explique.

   A: No, porque no tienen una dirección IP configurada.

   Si vamos a inspeccionar y vemos los estados de los puertos podemos ver que `vlan` esta `Down`:

   ```
   Vlan1               Down    1       <not set>          0002.1714.2963
   ```

Parte 3

Paso 1

1. ¿Por qué ingresa el comando `no shutdown`?

   A: Para encender la interfaz `vlan 1`, ahora en la tabla en `Inspect > Port Summary` se ve:

```
  Vlan1                  Up      1       192.168.1.253/24   0002.1714.2963
```

2. El ping funciona a `S1`, `S2` y `PC2`