



AP[®] Computer Science A 2012 Free-Response Questions

About the College Board

The College Board is a mission-driven not-for-profit organization that connects students to college success and opportunity. Founded in 1900, the College Board was created to expand access to higher education. Today, the membership association is made up of more than 5,900 of the world's leading educational institutions and is dedicated to promoting excellence and equity in education. Each year, the College Board helps more than seven million students prepare for a successful transition to college through programs and services in college readiness and college success — including the SAT[®] and the Advanced Placement Program[®]. The organization also serves the education community through research and advocacy on behalf of students, educators, and schools.

© 2012 The College Board. College Board, Advanced Placement Program, AP, AP Central, SAT, and the acorn logo are registered trademarks of the College Board. Admitted Class Evaluation Service and inspiring minds are trademarks owned by the College Board. All other products and services may be trademarks of their respective owners. Visit the College Board on the Web: www.collegeboard.org. Permission to use copyrighted College Board materials may be requested online at: www.collegeboard.org/inquiry/cbpermit.html.

Visit the College Board on the Web: www.collegeboard.org.

AP Central is the official online home for the AP Program: apcentral.collegeboard.org.



2012 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

4. A grayscale image is represented by a 2-dimensional rectangular array of pixels (picture elements). A pixel is an integer value that represents a shade of gray. In this question, pixel values can be in the range from 0 through 255, inclusive. A black pixel is represented by 0, and a white pixel is represented by 255.

The declaration of the `GrayImage` class is shown below. You will write two unrelated methods of the `GrayImage` class.

```
public class GrayImage
{
    public static final int BLACK = 0;
    public static final int WHITE = 255;

    /** The 2-dimensional representation of this image. Guaranteed not to be null.
     * All values in the array are within the range [BLACK, WHITE], inclusive.
     */
    private int[][] pixelValues;

    /** @return the total number of white pixels in this image.
     * Postcondition: this image has not been changed.
     */
    public int countWhitePixels()
    { /* to be implemented in part (a) */ }

    /** Processes this image in row-major order and decreases the value of each pixel at
     * position (row, col) by the value of the pixel at position (row + 2, col + 2) if it exists.
     * Resulting values that would be less than BLACK are replaced by BLACK.
     * Pixels for which there is no pixel at position (row + 2, col + 2) are unchanged.
     */
    public void processImage()
    { /* to be implemented in part (b) */ }
}
```

- (a) Write the method `countWhitePixels` that returns the number of pixels in the image that contain the value `WHITE`. For example, assume that `pixelValues` contains the following image.

	0	1	2	3	4
0	255	184	178	84	129
1	84	255	255	130	84
2	78	255	0	0	78
3	84	130	255	130	84

A call to `countWhitePixels` method would return 5 because there are 5 entries (shown in boldface) that have the value `WHITE`.

2012 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `countWhitePixels` below.

```
/** @return the total number of white pixels in this image.  
 *   Postcondition: this image has not been changed.  
 */  
public int countWhitePixels()
```

Part (b) begins on page 20.

2012 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

- (b) Write the method `processImage` that modifies the image by changing the values in the instance variable `pixelValues` according to the following description. The pixels in the image are processed one at a time in row-major order. Row-major order processes the first row in the array from left to right and then processes the second row from left to right, continuing until all rows are processed from left to right. The first index of `pixelValues` represents the row number, and the second index represents the column number.

The pixel value at position (row, col) is decreased by the value at position (row + 2, col + 2) if such a position exists. If the result of the subtraction is less than the value `BLACK`, the pixel is assigned the value of `BLACK`. The values of the pixels for which there is no pixel at position (row + 2, col + 2) remain unchanged. You may assume that all the original values in the array are within the range [`BLACK`, `WHITE`], inclusive.

The following diagram shows the contents of the instance variable `pixelValues` before and after a call to `processImage`. The values shown in boldface represent the pixels that could be modified in a grayscale image with 4 rows and 5 columns.

Before Call to <code>processImage</code>						After Call to <code>processImage</code>					

2012 AP[®] COMPUTER SCIENCE A FREE-RESPONSE QUESTIONS

Complete method `processImage` below.

```
/** Processes this image in row-major order and decreases the value of each pixel at
 * position (row, col) by the value of the pixel at position (row + 2, col + 2) if it exists.
 * Resulting values that would be less than BLACK are replaced by BLACK.
 * Pixels for which there is no pixel at position (row + 2, col + 2) are unchanged.
 */
public void processImage()
```

STOP

END OF EXAM