



Day07 Machine Learning Using Python

Day07 Objectives

Classification models - 2

- Decision Tree Regressor
- Random Forest Algorithm

Regression

Finding the relationship between the Inputs/features/predictors and Output/targets/predicted


In [1]:

```
import matplotlib.pyplot as plt
import numpy as np

x = np.arange(1, 100)
y = np.arange(5, 104)
plt.scatter(x, y)
```

Out[1]:

<matplotlib.collections.PathCollection at 0x1d82b6dc9a0>




In [2]:

```
plt.scatter(x, x**4)
```

Out[2]:

<matplotlib.collections.PathCollection at 0x1d82b759a00>



```
tot_marks = 750
if tot_marks > 700:
    print('A')
elif tot_marks < 700 and tot_marks > 600:
    print('B')
```

```
tot_marks = 750
if tot_marks > 700 :
    print('A')
elif tot_marks < 700 and tot_marks > 600:
    print('B')
```

price real state example

Distancecity, Locality, Resources, CRIM, Polution, Transporation

50, good, 5, 7.5, 0.5, 5.5, 7500

40, good, 5, 8.0, 0.5, 7, 7700

100, ok, 6, 8.5, 0.7, 6, 7300

distance < 50:

7300

Metrics for regression

- R^2 score
- RMSE - Root Mean Squarred Error
- MSE - Mean Squarred Error
- MAE - Mean Absolute Error
- ME - Mean error

Actual	predicited	Error
20	10	10
120	110	10
120	130	-10
150	160	-10
140	140	0
160	160	0
ME		- 0/4 - 0 100% Accuracy
MAE		- 40/6
MSE		- 1600/6
RMSE		- sqrt(1600/6)

Decsion Tree as Regressor

In [5]:

```
from sklearn.datasets import load_boston
```

In [6]:

```
data = load_boston()
```

In [7]:

```
type(data)
```

Out[7]:

```
sklearn.utils.Bunch
```

In [8]:

```
data.keys()
```

Out[8]:

```
dict_keys(['data', 'target', 'feature_names', 'DESCR', 'filename'])
```

In [9]:



```
data.data
```

Out[9]:

```
array([[6.3200e-03, 1.8000e+01, 2.3100e+00, ..., 1.5300e+01, 3.9690e+02,
        4.9800e+00],
       [2.7310e-02, 0.0000e+00, 7.0700e+00, ..., 1.7800e+01, 3.9690e+02,
        9.1400e+00],
       [2.7290e-02, 0.0000e+00, 7.0700e+00, ..., 1.7800e+01, 3.9283e+02,
        4.0300e+00],
       ...,
       [6.0760e-02, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9690e+02,
        5.6400e+00],
       [1.0959e-01, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9345e+02,
        6.4800e+00],
       [4.7410e-02, 0.0000e+00, 1.1930e+01, ..., 2.1000e+01, 3.9690e+02,
        7.8800e+00]])
```

In [10]:



```
data.target
```

Out[10]:

```
array([24. , 21.6, 34.7, 33.4, 36.2, 28.7, 22.9, 27.1, 16.5, 18.9, 15. ,
       18.9, 21.7, 20.4, 18.2, 19.9, 23.1, 17.5, 20.2, 18.2, 13.6, 19.6,
       15.2, 14.5, 15.6, 13.9, 16.6, 14.8, 18.4, 21. , 12.7, 14.5, 13.2,
       13.1, 13.5, 18.9, 20. , 21. , 24.7, 30.8, 34.9, 26.6, 25.3, 24.7,
       21.2, 19.3, 20. , 16.6, 14.4, 19.4, 19.7, 20.5, 25. , 23.4, 18.9,
       35.4, 24.7, 31.6, 23.3, 19.6, 18.7, 16. , 22.2, 25. , 33. , 23.5,
       19.4, 22. , 17.4, 20.9, 24.2, 21.7, 22.8, 23.4, 24.1, 21.4, 20. ,
       20.8, 21.2, 20.3, 28. , 23.9, 24.8, 22.9, 23.9, 26.6, 22.5, 22.2,
       23.6, 28.7, 22.6, 22. , 22.9, 25. , 20.6, 28.4, 21.4, 38.7, 43.8,
       33.2, 27.5, 26.5, 18.6, 19.3, 20.1, 19.5, 19.5, 20.4, 19.8, 19.4,
       21.7, 22.8, 18.8, 18.7, 18.5, 18.3, 21.2, 19.2, 20.4, 19.3, 22. ,
       20.3, 20.5, 17.3, 18.8, 21.4, 15.7, 16.2, 18. , 14.3, 19.2, 19.6,
       23. , 18.4, 15.6, 18.1, 17.4, 17.1, 13.3, 17.8, 14. , 14.4, 13.4,
       15.6, 11.8, 13.8, 15.6, 14.6, 17.8, 15.4, 21.5, 19.6, 15.3, 19.4,
       17. , 15.6, 13.1, 41.3, 24.3, 23.3, 27. , 50. , 50. , 50. , 22.7,
       25. , 50. , 23.8, 23.8, 22.3, 17.4, 19.1, 23.1, 23.6, 22.6, 29.4,
       23.2, 24.6, 29.9, 37.2, 39.8, 36.2, 37.9, 32.5, 26.4, 29.6, 50. ,
       32. , 29.8, 34.9, 37. , 30.5, 36.4, 31.1, 29.1, 50. , 33.3, 30.3,
       34.6, 34.9, 32.9, 24.1, 42.3, 48.5, 50. , 22.6, 24.4, 22.5, 24.4,
       20. , 21.7, 19.3, 22.4, 28.1, 23.7, 25. , 23.3, 28.7, 21.5, 23. ,
       26.7, 21.7, 27.5, 30.1, 44.8, 50. , 37.6, 31.6, 46.7, 31.5, 24.3,
       31.7, 41.7, 48.3, 29. , 24. , 25.1, 31.5, 23.7, 23.3, 22. , 20.1,
       22.2, 23.7, 17.6, 18.5, 24.3, 20.5, 24.5, 26.2, 24.4, 24.8, 29.6,
       42.8, 21.9, 20.9, 44. , 50. , 36. , 30.1, 33.8, 43.1, 48.8, 31. ,
       36.5, 22.8, 30.7, 50. , 43.5, 20.7, 21.1, 25.2, 24.4, 35.2, 32.4,
       32. , 33.2, 33.1, 29.1, 35.1, 45.4, 35.4, 46. , 50. , 32.2, 22. ,
       20.1, 23.2, 22.3, 24.8, 28.5, 37.3, 27.9, 23.9, 21.7, 28.6, 27.1,
       20.3, 22.5, 29. , 24.8, 22. , 26.4, 33.1, 36.1, 28.4, 33.4, 28.2,
       22.8, 20.3, 16.1, 22.1, 19.4, 21.6, 23.8, 16.2, 17.8, 19.8, 23.1,
       21. , 23.8, 23.1, 20.4, 18.5, 25. , 24.6, 23. , 22.2, 19.3, 22.6,
       19.8, 17.1, 19.4, 22.2, 20.7, 21.1, 19.5, 18.5, 20.6, 19. , 18.7,
       32.7, 16.5, 23.9, 31.2, 17.5, 17.2, 23.1, 24.5, 26.6, 22.9, 24.1,
       18.6, 30.1, 18.2, 20.6, 17.8, 21.7, 22.7, 22.6, 25. , 19.9, 20.8,
       16.8, 21.9, 27.5, 21.9, 23.1, 50. , 50. , 50. , 50. , 50. , 13.8,
       13.8, 15. , 13.9, 13.3, 13.1, 10.2, 10.4, 10.9, 11.3, 12.3, 8.8,
       7.2, 10.5, 7.4, 10.2, 11.5, 15.1, 23.2, 9.7, 13.8, 12.7, 13.1,
       12.5, 8.5, 5. , 6.3, 5.6, 7.2, 12.1, 8.3, 8.5, 5. , 11.9,
       27.9, 17.2, 27.5, 15. , 17.2, 17.9, 16.3, 7. , 7.2, 7.5, 10.4,
       8.8, 8.4, 16.7, 14.2, 20.8, 13.4, 11.7, 8.3, 10.2, 10.9, 11. ,
       9.5, 14.5, 14.1, 16.1, 14.3, 11.7, 13.4, 9.6, 8.7, 8.4, 12.8,
       10.5, 17.1, 18.4, 15.4, 10.8, 11.8, 14.9, 12.6, 14.1, 13. , 13.4,
       15.2, 16.1, 17.8, 14.9, 14.1, 12.7, 13.5, 14.9, 20. , 16.4, 17.7,
       19.5, 20.2, 21.4, 19.9, 19. , 19.1, 19.1, 20.1, 19.9, 19.6, 23.2,
       29.8, 13.8, 13.3, 16.7, 12. , 14.6, 21.4, 23. , 23.7, 25. , 21.8,
       20.6, 21.2, 19.1, 20.6, 15.2, 7. , 8.1, 13.6, 20.1, 21.8, 24.5,
       23.1, 19.7, 18.3, 21.2, 17.5, 16.8, 22.4, 20.6, 23.9, 22. , 11.9])
```

In [11]:



```
data.feature_names
```

Out[11]:

```
array(['CRIM', 'ZN', 'INDUS', 'CHAS', 'NOX', 'RM', 'AGE', 'DIS', 'RAD',  
      'TAX', 'PTRATIO', 'B', 'LSTAT'], dtype='<U7')
```

In [12]:



```
print(data.DESCR)
```

```
.. _boston_dataset:
```

Boston house prices dataset

****Data Set Characteristics:****

:Number of Instances: 506

:Number of Attributes: 13 numeric/categorical predictive. Median Value (attribute 14) is usually the target.

:Attribute Information (in order):

- CRIM per capita crime rate by town
- ZN proportion of residential land zoned for lots over 25,000 sq.ft.
- INDUS proportion of non-retail business acres per town
- CHAS Charles River dummy variable (= 1 if tract bounds river; 0 otherwise)
- NOX nitric oxides concentration (parts per 10 million)
- RM average number of rooms per dwelling
- AGE proportion of owner-occupied units built prior to 1940
- DIS weighted distances to five Boston employment centres
- RAD index of accessibility to radial highways
- TAX full-value property-tax rate per \$10,000
- PTRATIO pupil-teacher ratio by town
- B $1000(Bk - 0.63)^2$ where Bk is the proportion of blacks by town
- LSTAT % lower status of the population
- MEDV Median value of owner-occupied homes in \$1000's

:Missing Attribute Values: None

:Creator: Harrison, D. and Rubinfeld, D.L.

This is a copy of UCI ML housing dataset.

<https://archive.ics.uci.edu/ml/machine-learning-databases/housing/> (<https://archive.ics.uci.edu/ml/machine-learning-databases/housing/>)

This dataset was taken from the StatLib library which is maintained at Carnegie Mellon University.

The Boston house-price data of Harrison, D. and Rubinfeld, D.L. 'Hedonic prices and the demand for clean air', J. Environ. Economics & Management, vol.5, 81-102, 1978. Used in Belsley, Kuh & Welsch, 'Regression diagnostics ...', Wiley, 1980. N.B. Various transformations are used in the table on pages 244-261 of the latter.

The Boston house-price data has been used in many machine learning papers that address regression problems.

```
.. topic:: References
```

- Belsley, Kuh & Welsch, 'Regression diagnostics: Identifying Influential Data and Sources of Collinearity', Wiley, 1980. 244-261.
- Quinlan,R. (1993). Combining Instance-Based and Model-Based Learning. In Proceedings on the Tenth International Conference of Machine Learning, 236-243, University of Massachusetts, Amherst. Morgan Kaufmann.

In [13]:

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

df = pd.DataFrame(data.data, columns = data.feature_names)
```

In [14]:

```
df.head()
```

Out[14]:

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS	RAD	TAX	PTRATIO	B	LS
0	0.00632	18.0	2.31	0.0	0.538	6.575	65.2	4.0900	1.0	296.0	15.3	396.90	4
1	0.02731	0.0	7.07	0.0	0.469	6.421	78.9	4.9671	2.0	242.0	17.8	396.90	5
2	0.02729	0.0	7.07	0.0	0.469	7.185	61.1	4.9671	2.0	242.0	17.8	392.83	4
3	0.03237	0.0	2.18	0.0	0.458	6.998	45.8	6.0622	3.0	222.0	18.7	394.63	5
4	0.06905	0.0	2.18	0.0	0.458	7.147	54.2	6.0622	3.0	222.0	18.7	396.90	5

In [15]:

```
df['MEDV'] = data.target
df.head()
```

Out[15]:

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS	RAD	TAX	PTRATIO	B	LS
0	0.00632	18.0	2.31	0.0	0.538	6.575	65.2	4.0900	1.0	296.0	15.3	396.90	4
1	0.02731	0.0	7.07	0.0	0.469	6.421	78.9	4.9671	2.0	242.0	17.8	396.90	5
2	0.02729	0.0	7.07	0.0	0.469	7.185	61.1	4.9671	2.0	242.0	17.8	392.83	4
3	0.03237	0.0	2.18	0.0	0.458	6.998	45.8	6.0622	3.0	222.0	18.7	394.63	5
4	0.06905	0.0	2.18	0.0	0.458	7.147	54.2	6.0622	3.0	222.0	18.7	396.90	5

In [16]:



```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 506 entries, 0 to 505
Data columns (total 14 columns):
 #   Column      Non-Null Count  Dtype  
---  -
 0   CRIM        506 non-null   float64
 1   ZN          506 non-null   float64
 2   INDUS       506 non-null   float64
 3   CHAS        506 non-null   float64
 4   NOX         506 non-null   float64
 5   RM          506 non-null   float64
 6   AGE         506 non-null   float64
 7   DIS         506 non-null   float64
 8   RAD         506 non-null   float64
 9   TAX         506 non-null   float64
10  PTRATIO     506 non-null   float64
11  B           506 non-null   float64
12  LSTAT       506 non-null   float64
13  MEDV        506 non-null   float64
dtypes: float64(14)
memory usage: 55.5 KB
```

Finding the relationship value between variables


- visualation - scatterplot
- math - correlation

In [17]:

```
sns.pairplot(df)
```

Out[17]:

<seaborn.axisgrid.PairGrid at 0x1d83483c730>



In [18]:



```
df.corr()
```

Out[18]:

	CRIM	ZN	INDUS	CHAS	NOX	RM	AGE	DIS
CRIM	1.000000	-0.200469	0.406583	-0.055892	0.420972	-0.219247	0.352734	-0.379670
ZN	-0.200469	1.000000	-0.533828	-0.042697	-0.516604	0.311991	-0.569537	0.664408
INDUS	0.406583	-0.533828	1.000000	0.062938	0.763651	-0.391676	0.644779	-0.708027
CHAS	-0.055892	-0.042697	0.062938	1.000000	0.091203	0.091251	0.086518	-0.099176
NOX	0.420972	-0.516604	0.763651	0.091203	1.000000	-0.302188	0.731470	-0.769230
RM	-0.219247	0.311991	-0.391676	0.091251	-0.302188	1.000000	-0.240265	0.205246
AGE	0.352734	-0.569537	0.644779	0.086518	0.731470	-0.240265	1.000000	-0.747881
DIS	-0.379670	0.664408	-0.708027	-0.099176	-0.769230	0.205246	-0.747881	1.000000
RAD	0.625505	-0.311948	0.595129	-0.007368	0.611441	-0.209847	0.456022	-0.494588
TAX	0.582764	-0.314563	0.720760	-0.035587	0.668023	-0.292048	0.506456	-0.534432
PTRATIO	0.289946	-0.391679	0.383248	-0.121515	0.188933	-0.355501	0.261515	-0.232471
B	-0.385064	0.175520	-0.356977	0.048788	-0.380051	0.128069	-0.273534	0.291512
LSTAT	0.455621	-0.412995	0.603800	-0.053929	0.590879	-0.613808	0.602339	-0.496996
MEDV	-0.388305	0.360445	-0.483725	0.175260	-0.427321	0.695360	-0.376955	0.249929




In [26]:

```
plt.figure(figsize=(14, 8))
corr_matrix = df.corr().round(2)
sns.heatmap(data=corr_matrix, cmap='coolwarm', annot=True)
```

Out[26]:

<matplotlib.axes._subplots.AxesSubplot at 0x1d83ec69970>



Correlation between independent variable and dependent variable:

In order for our regression model to perform well, we ideally need to select those features that are highly correlated with our dependent variable (MEDV).

We observe that both RM , PTRATIO and LSTAT are correlated with MEDV with a correlation score of 0.66, 0.51 and 0.74 respective. This can also be illustrated via the scatter plot .



In [19]:




```
X = df[['RM', 'PTRATIO', 'LSTAT']]
Y = df['MEDV']
```

In [20]:

```
for feature in X:  
    plt.figure(figsize = (14, 7))  
    plt.scatter(df[feature], Y)  
    plt.xlabel(feature)  
    plt.ylabel('MEDV')  
    plt.show()
```





In [21]:

```
from sklearn.tree import DecisionTreeRegressor
```

In [22]:

```
model = DecisionTreeRegressor()
```

In [23]:

```
model.fit(X, Y)
```

Out[23]:

```
DecisionTreeRegressor()
```

In [24]:

```
pred = model.predict(X)
```

In [25]:

```
from sklearn.metrics import r2_score, mean_squared_error

print('R2 Score', r2_score(Y, pred))
print('RMSE', mean_squared_error(Y, pred) ** 0.5)
```

```
R2 Score 1.0
RMSE 0.0
```

Random Forest Algorithm

Random Forest Classifier Intution

- m1 - +ve
- m2 - -ve
- m3 - +ve
- m4 - +ve
- m5 - +ve
- m6 - +ve
- m7 - -ve

PowerFulModel - **+ve** - MajorityVoting - +ve

Random Forest Regressor Intution

- m1 - 5.5
- m2 - 6.5
- m3 - 5.7
- m4 - 6.2
- m5 - 5.4
- m6 - 6.2
- m7 - 5.5

PowerFulModel - **+ve** - MajorityVoting - +ve