

Fully Dressed Use Case Specification for NOVUS: Smart Editorial and Publishing Platform

Project Documentation Submitted to the Faculty of the
School of Computing and Information Technologies
Asia Pacific College

In Partial Fulfillment of the Requirements for
System Analysis and Detailed Design
MSYADD1

Submitted by:

Galido, Rei Khalil S. (Team Leader)

Albania, Roman Rico B. (Member)

Clavero, Joshmar L. (Member)

Concepcion, Joshua (Member)

Submitted to:

Mr. Jose Eugenio L. Quesada

Course Instructor

October 2026

1st Term

A.Y. 2026 – 2027

Module 1 — Editorial Production

Commissioning an article, writing it, assessing it and reaching an editorial decision on it.

Use Case Name: Commission an Article

Use Case ID:	UC-1.1																									
Author	Rei Khalil S. Galido																									
Purpose	Enable an Editor to place a piece of work with a Writer, giving them the topic, the angle and the date it is wanted.																									
Related Use Case	None																									
Priority	High																									
Preconditions	• The system is available • The Editor is authenticated in the Editor role • At least one active Writer exists in the directory																									
Postconditions	• An article record exists in the assigned state • The brief, the deadline and the commissioning Editor are recorded • The Writer is notified and the work appears on their dashboard • Any deadline is reflected in deadline tracking and on the calendar																									
Actors	• Editor • Writer (recipient)																									
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Editor selects Assign article from the dashboard.</td><td>1.1 System displays the assignment form.</td></tr> <tr> <td></td><td></td><td>1.2 System lists the active Writers available to receive the work.</td></tr> <tr> <td>2</td><td>Editor enters the working title, category, editorial brief and deadline, and selects the Writer.</td><td></td></tr> <tr> <td>3</td><td>Editor confirms the commission.</td><td>3.1 System validates that a title and a Writer have been supplied.</td></tr> <tr> <td></td><td></td><td>3.2 System creates the article in the Assigned state with its brief, deadline and commissioning Editor.</td></tr> <tr> <td></td><td></td><td>3.3 System notifies the Writer.</td></tr> <tr> <td>4</td><td>Writer opens their dashboard.</td><td>4.1 System lists the commission under To write, with its brief and deadline.</td></tr> </table> ALTERNATE FLOW A1 (No Deadline Set) 1. The Editor confirms the commission without a deadline. 2. The system accepts it, as a deadline is optional. 3. The system states that the work will not appear in deadline tracking or on the calendar.		Step	Actor Action	System Response	1	Editor selects Assign article from the dashboard.	1.1 System displays the assignment form.			1.2 System lists the active Writers available to receive the work.	2	Editor enters the working title, category, editorial brief and deadline, and selects the Writer.		3	Editor confirms the commission.	3.1 System validates that a title and a Writer have been supplied.			3.2 System creates the article in the Assigned state with its brief, deadline and commissioning Editor.			3.3 System notifies the Writer.	4	Writer opens their dashboard.	4.1 System lists the commission under To write, with its brief and deadline.
Step	Actor Action	System Response																								
1	Editor selects Assign article from the dashboard.	1.1 System displays the assignment form.																								
		1.2 System lists the active Writers available to receive the work.																								
2	Editor enters the working title, category, editorial brief and deadline, and selects the Writer.																									
3	Editor confirms the commission.	3.1 System validates that a title and a Writer have been supplied.																								
		3.2 System creates the article in the Assigned state with its brief, deadline and commissioning Editor.																								
		3.3 System notifies the Writer.																								
4	Writer opens their dashboard.	4.1 System lists the commission under To write, with its brief and deadline.																								

	4. A deadline may be added later by amending the assignment. ALTERNATE FLOW A2 (Assignment Transferred) 1. The Editor moves an unstarted assignment to a different Writer. 2. The system verifies that the work has not been submitted. 3. The system transfers the assignment, retaining the brief and the deadline. 4. The system notifies both the previous and the new Writer. ALTERNATE FLOW A-VALID (Incomplete or Invalid Input) 1. The actor submits an assignment. 2. The system validates every required field before committing anything. 3. The system detects that one or more required items are missing or malformed. 4. The system identifies each item and displays corrective guidance beside it. 5. The system prevents the incomplete operation from changing the workflow state. 6. The actor corrects the input and retries. 7. The system revalidates before continuing. EXCEPTION FLOW E1 (Work Already Submitted) 1. The Editor attempts to transfer or cancel an assignment that has been submitted. 2. The system detects that the copy has entered review. 3. The system refuses the change. 4. The system explains that submitted copy belongs to its author and must be decided upon rather than reassigned. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Produce an Article

Use Case ID:	UC-1.2
Author	Roman Rico Albania
Purpose	Enable a Writer to take a commission from an empty page to a submission the Editor can act on, including any revision the Editor asks for.

Related Use Case	«include» UC-1.2.1 (Evaluate a Submitted Article)		
Priority	High		
Preconditions	• The system is available • The Writer is authenticated in the Writer role • The article is commissioned to this Writer under UC-1.1, or was started by them		
Postconditions	• The copy, standfirst and photography are stored • On submission, an immutable version snapshot is recorded • On submission, an assessment is attached and the article routed by it • The article is no longer directly editable once submitted		
Actors	• Writer		
Flow of Actions	BASIC FLOW		
	Step	Actor Action	System Response
	1	Writer opens the commissioned work.	1.1 System displays the composer with the brief and the deadline in view.
	2	Writer enters the headline, standfirst and body copy.	2.1 System saves the work at intervals and reports the save state.
			2.2 System reports the word count and reading time as they change.
	3	Writer attaches the hero image and any photography within the body.	3.1 System stores each image against the article.
	4	Writer submits the article for review.	4.1 System checks that the draft is ready to be assessed.
			4.2 System records an immutable version snapshot of the submitted copy.
			4.3 System invokes UC-1.2.1 to assess the article and routes it by the verdict.
	ALTERNATE FLOW		
	A1 (Article Returned for Revision)		
	1. The article is returned by the Editor or by pre-screening. 2. The system displays the revision notes beside the copy, so each point can be addressed without leaving the passage it concerns. 3. The Writer revises the copy and resubmits. 4. The system records a further version rather than replacing the previous one. 5. The system obtains a fresh assessment and routes the article again.		
	ALTERNATE FLOW		
	A2 (No Photography Supplied)		
	1. The Writer completes the copy without attaching a hero image. 2. The system accepts the submission, as photography is optional. 3. The system states that the article will run as text only. 4. The Editor may supply photography during their review.		
ALTERNATE FLOW			
A3 (Session Lapses While Writing)			
1. The Writer's session expires during composition. 2. The system exchanges the renewal credential for a fresh session.			

	3. The system retries the pending save. 4. The work is preserved and the Writer continues uninterrupted. 5. Where renewal fails, the system warns the Writer before any work is lost. ALTERNATE FLOW A4 (Article Written by an Editor) 1. The author holds the Editor role. 2. The system obtains the assessment as normal. 3. On a passing verdict the article is routed to the Publisher rather than to the Editor's own queue. 4. The article is decided under UC-1.5, because no person signs off their own copy. ALTERNATE FLOW A5 (Quick Fixes Applied) 1. The article was returned in the Revise band with quick fixes attached. 2. The system shows each fix as the original passage struck through beside its replacement, with a one-line reason, and a count of fixes resolved. 3. The Writer applies or dismisses each fix. 4. Before applying, the system saves any unsaved edits and locks the editor for the request, so no pending change can overwrite the corrected copy. 5. The system applies the fix to the saved copy, inside text only, records the decision, and reloads the corrected copy into the editor. 6. Where the Writer has since changed that passage, the system marks the fix as no longer applicable rather than forcing it in. 7. The score is unchanged; the Writer resubmits under the basic flow to have the article assessed again. EXCEPTION FLOW E1 (Draft Not Ready for Assessment) 1. The Writer submits a draft that is unfinished in some mechanical way. 2. The system checks the word count against the configured floor, unresolved placeholder markers, an absent headline or standfirst, and whether the copy has changed since it was last assessed. 3. The system refuses the submission and returns every reason together. 4. No version is recorded and no assessment is requested. 5. The Writer corrects the draft and resubmits. EXCEPTION FLOW E2 (Assessment Rate Limited) 1. The Writer resubmits within the cooldown following a previous assessment. 2. The system refuses and states how long remains. 3. Where the Writer has reached the daily ceiling, the system says so and notes that an Editor may review the article without an assessment. 4. The cooldown is waived once every quick fix from the previous assessment has been resolved, since resubmitting straight afterwards is the intended path; the daily ceiling still applies. 5. No assessment is requested and the article stays with the Writer. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW
--	---

	<i>E-AUTH (Authorization or Session Failure)</i> 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Use Case Name: Evaluate a Submitted Article

Use Case ID:	UC-1.2.1
Author	Roman Rico Albania
Purpose	Assess a submitted article for grammar, readability and structure, and route it according to whether it meets the publication's minimum standard.
Related Use Case	Included by UC-1.2 (Produce an Article)
Priority	High
Preconditions	• The system is available • An article has been submitted for review under UC-1.2 • The evaluation service is reachable and holds a valid credential
Postconditions	• An assessment is attached to the article with its scores and summary • Suggestions are recorded in a form the revision composer can consume • The article is routed by the verdict against the passing mark • The producing model and the usage are recorded against the assessment • Where the verdict is revise, quick fixes are recorded against the assessment; otherwise none are kept
Actors	• Writer • AI Evaluation Service • Editor (recipient)

Flow of Actions	BASIC FLOW		
	Step	Actor Action	System Response
	1	Writer submits an article under UC-1.2.	1.1 System assembles the headline, standfirst and body into an assessment request.
			1.2 System sends the request to the AI Evaluation Service.
	2	AI Evaluation Service returns scores, a summary and suggestions.	2.1 System validates the response structure before accepting it.
			2.2 System stores the assessment with the producing model and the usage recorded.
			2.3 System compares the overall score against the passing mark and finds it met.
			2.4 System places the article in the Editor's review queue and notifies the Editor.
	3	Editor opens the review queue.	3.1 System shows the article with its assessment attached.
	ALTERNATE FLOW A1 (Revise: Between the Rewrite Mark and the Passing Mark) 1. The overall score is below the passing mark but at or above the rewrite mark. 2. The system records each suggestion as a revision note with no authoring Editor. 3. The system keeps the quick fixes whose passages appear exactly once in the copy. 4. The system returns the article to its Writer and notifies them, stating how many quick fixes were suggested. 5. The Writer revises, applying or dismissing fixes, under UC-1.2. ALTERNATE FLOW A2 (Rewrite: Below the Rewrite Mark) 1. The overall score is below the rewrite mark. 2. The system records the suggestions as revision notes and keeps no quick fixes, since line edits would not carry the draft over the mark. 3. The system returns the article to its Writer and notifies them that it needs rework rather than line edits. 4. The Writer reworks the draft under UC-1.2. ALTERNATE FLOW A3 (Malformed Assessment) 1. The service returns a response that does not match the expected structure. 2. The system attempts to recover the scored fields from the payload. 3. Where recovery is not possible, the system treats the assessment as unobtained. 4. The system retains the raw response for diagnosis. 5. The article proceeds to manual review rather than being held. ALTERNATE FLOW A4 (Editor-Authored Article Passes) 1. The author holds the Editor role and the article meets the mark. 2. The system routes the article to the Publisher rather than to the Editor's queue. 3. The system notifies the Publisher that copy awaits sign-off.		

	EXCEPTION FLOW E1 (Service Unavailable or Credential Refused) 1. Where no evaluation credential is configured, the system treats the assessment as unobtainable rather than recording a score of zero, which would fail every draft. 2. The system submits the assessment request. 3. The service does not respond within the configured timeout, or refuses the credential. 4. The system does not retry indefinitely and does not block the Writer. 5. The system records that no assessment was obtained. 6. The article is routed to the Editor with the absence stated explicitly, so a missing assessment is never mistaken for a passing one. 7. The integration status is visible to an Administrator under UC-5.4. 8. An article written by an Editor goes to the Publisher for sign-off, not to its author's own review queue.
--	---

Use Case Name: Communicate About an Article

Use Case ID:	UC-1.3																
Author	Joshmar Clavero																
Purpose	Enable staff to hold the conversation an article needs in the place the article lives, rather than across separate messaging applications.																
Related Use Case	«extend» UC-1.3.1 (Decide on a Submitted Article)																
Priority	Medium																
Preconditions	• The system is available • The actor is authenticated and the article falls within their scope																
Postconditions	• The message is recorded against the article • The other participants are notified, subject to their preferences • The article's state is unchanged																
Actors	• Writer • Editor																
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Writer or Editor opens the correspondence on an article.</td><td>1.1 System displays the messages in order with their authors and times.</td></tr> <tr> <td>2</td><td>Writer or Editor writes a message and sends it.</td><td>2.1 System records the message against the article.</td></tr> <tr> <td></td><td></td><td>2.2 System notifies the other party, subject to their preferences.</td></tr> <tr> <td>3</td><td>The other party opens the article.</td><td>3.1 System shows the new message in the thread.</td></tr> </table> ALTERNATE FLOW A1 (Recipient Has Muted This Notice) 1. A participant has muted correspondence notifications. 2. The system records the message as normal.		Step	Actor Action	System Response	1	Writer or Editor opens the correspondence on an article.	1.1 System displays the messages in order with their authors and times.	2	Writer or Editor writes a message and sends it.	2.1 System records the message against the article.			2.2 System notifies the other party, subject to their preferences.	3	The other party opens the article.	3.1 System shows the new message in the thread.
Step	Actor Action	System Response															
1	Writer or Editor opens the correspondence on an article.	1.1 System displays the messages in order with their authors and times.															
2	Writer or Editor writes a message and sends it.	2.1 System records the message against the article.															
		2.2 System notifies the other party, subject to their preferences.															
3	The other party opens the article.	3.1 System shows the new message in the thread.															

	3. The system does not notify that participant. 4. The message remains visible on the article, so nothing is lost by muting. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Use Case Name: Decide on a Submitted Article

Use Case ID:	UC-1.3.1							
Author	Joshmar Clavero							
Purpose	Enable an Editor to reach and record a decision on submitted copy: to accept it, to return it for revision, to accept it against the assessment, or to remove it from the pipeline.							
Related Use Case	Extended by UC-1.3 (Communicate About an Article)							
Priority	High							
Preconditions	• The system is available • The Editor is authenticated in the Editor role • The article has been submitted and assessed under UC-1.2.1, or is recorded as having no assessment							
Postconditions	• The article is approved, returned for revision, or withdrawn • The deciding Editor and the time of the decision are recorded • Where the assessment was overridden, the justification is recorded against it • The Writer is notified of the outcome • An approved article becomes eligible for scheduling into an issue							
Actors	• Editor • Writer (notified)							
Flow of Actions	BASIC FLOW <table border="1"> <thead> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> </thead> <tbody> <tr> <td></td><td></td><td></td></tr> </tbody> </table>		Step	Actor Action	System Response			
Step	Actor Action	System Response						

	1	Editor opens an article from the review queue.	1.1 System displays the copy with its assessment and version history.
			1.2 System displays the status timeline and the correspondence beside it.
			1.3 System lists any AI-suggested fixes the Writer accepted, showing the original and the replacement.
	2	Editor reads the copy and the assessment.	
	3	Editor replaces or captions the photography where the article needs it.	3.1 System stores the change and records the uploading user.
	4	Editor selects to approve the article.	4.1 System validates that the article is under review.
			4.2 System validates that no assessment stands against it unoverridden.
			4.3 System records the approval and the deciding Editor.
			4.4 System notifies the Writer and makes the article eligible for scheduling.
	5	Writer opens their dashboard.	5.1 System shows the article as approved.
	ALTERNATE FLOW A1 (Revision Requested) 1. The Editor selects to return the article. 2. The system presents the note composer, prefilled from the assessment suggestions where these exist. 3. The Editor amends, removes or adds notes, each carrying a section, type and priority. 4. The system validates that at least one note carries an instruction. 5. The system records the notes, returns the article to its Writer and notifies them.		
	ALTERNATE FLOW A2 (Assessment Overridden) 1. The assessment returned the article and the Editor judges it publishable. 2. The Editor selects to override and enters an editorial justification. 3. The system validates that a justification of sufficient length is supplied. 4. The system marks the assessment overridden and records the justification, the Editor and the time. 5. The system approves the article and displays the justification against the assessment for anyone who later reads it.		
	ALTERNATE FLOW A3 (Article Withdrawn) 1. The Editor determines that the article should not run. 2. The Editor selects to withdraw it and enters a reason. 3. The system removes the article from any issue and corrects that issue's readiness. 4. The system records the withdrawal and its reason. 5. Where the issue had been closed, the system notifies the Publisher, since the layout was planned around those contents.		
	ALTERNATE FLOW A4 (No Assessment Obtained)		

	1. The article carries no assessment because the service was unavailable. 2. The system states the absence plainly on the review screen. 3. The Editor decides on editorial judgement alone. 4. No override is required, because no verdict stands against the article. EXCEPTION FLOW E1 (Article Not Under Review) 1. The Editor attempts to decide on an article in another state. 2. The system validates the current state before acting. 3. The system refuses the decision and names the article's actual position. 4. No state change is committed, so the assessment cannot be bypassed by acting on a draft. EXCEPTION FLOW E2 (Justification Absent or Insufficient) 1. The Editor confirms an override without an adequate justification. 2. The system validates the justification before committing the override. 3. The system refuses the override and leaves the verdict unchanged. 4. The system explains that a written justification is required for audit. 5. The Editor supplies one and retries. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Correct an Editorial Decision

Use Case ID:	UC-1.4
Author	Joshua Concepcion
Purpose	Enable an Editor or Publisher to return an approved article to review, so that an early or mistaken approval can be corrected without destroying the work.
Related Use Case	None
Priority	Medium
Preconditions	• The system is available • The actor is authenticated in the Editor or Publisher role

	• The article was approved under UC-1.3.1 and has not been published • Where the article is scheduled into an issue, the actor holds the Publisher role
Postconditions	• The article returns to the review queue • The reason is recorded as a revision note against the article • Any issue the article belonged to has its readiness corrected • The Writer is notified
Actors	• Editor • Publisher • Writer (notified)
Flow of Actions	Step Actor Action System Response 1 Editor or Publisher opens an approved article and selects to return it to review. 1.1 System presents a reason field. 1.2 System states that the article will leave any issue it belongs to. 2 Editor or Publisher enters the reason and confirms. 2.1 System validates the actor's authority against the article's scheduling. 2.2 System removes the article from any issue and corrects that issue's readiness. 2.3 System returns the article to review and records the reason as a revision note. 2.4 System notifies the Writer, and the Publisher where an issue was affected. 3 Writer opens their dashboard. 3.1 System shows the article back with the editor, with the reason attached as a revision note. ALTERNATE FLOW A1 (Editor Acts on a Scheduled Article) 1. An Editor attempts to correct a decision on an article already placed in an issue. 2. The system detects the scheduling. 3. The system refuses the action and leaves the issue untouched. 4. The system explains that the Publisher is planning around those contents and must authorise the removal. 5. The Editor raises the matter with the Publisher. EXCEPTION FLOW E1 (Reason Absent) 1. The actor confirms without an adequate reason. 2. The system validates the reason before committing. 3. The system refuses the correction and leaves the approval standing. 4. The actor supplies a reason and retries. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change.

	- The system validates the requested transition. - The system attempts to persist the change to the authoritative store. - The persistence operation fails or times out. - The system retains the last confirmed state and does not report success. - The system records the failure and displays a controlled retry message. - The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) - The actor initiates the protected operation. - The system validates the current session and the required role or ownership permission immediately before the state-changing action. - The system detects an expired session or an absent permission. - The system blocks the state change and does not partially commit it. - The system records the denied attempt where security policy requires it. - The system redirects to authentication or displays access denied. - After authorization is restored, the actor may retry.
--	--

Use Case Name: Sign Off Editor-Authored Copy

Use Case ID:	UC-1.5																
Author	Joshua Concepcion																
Purpose	Enable a Publisher to provide the second reading that editorial practice requires on articles written by an Editor.																
Related Use Case	None																
Priority	Medium																
Preconditions	- The system is available - The Publisher is authenticated in the Publisher role - The article was written by an Editor and has passed assessment																
Postconditions	- The article is approved and the signing Publisher recorded as its editor of record - The author is notified - The article becomes eligible for scheduling into an issue																
Actors	- Publisher - Editor (as author)																
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Publisher opens the sign-off queue.</td><td>1.1 System lists the articles awaiting sign-off with their assessment scores.</td></tr> <tr> <td>2</td><td>Publisher reads an article in the preview panel.</td><td></td></tr> <tr> <td>3</td><td>Publisher confirms the sign-off.</td><td>3.1 System validates that the article awaits sign-off.</td></tr> <tr> <td></td><td></td><td>3.2 System approves the article and records the Publisher as its editor of record.</td></tr> </table>		Step	Actor Action	System Response	1	Publisher opens the sign-off queue.	1.1 System lists the articles awaiting sign-off with their assessment scores.	2	Publisher reads an article in the preview panel.		3	Publisher confirms the sign-off.	3.1 System validates that the article awaits sign-off.			3.2 System approves the article and records the Publisher as its editor of record.
Step	Actor Action	System Response															
1	Publisher opens the sign-off queue.	1.1 System lists the articles awaiting sign-off with their assessment scores.															
2	Publisher reads an article in the preview panel.																
3	Publisher confirms the sign-off.	3.1 System validates that the article awaits sign-off.															
		3.2 System approves the article and records the Publisher as its editor of record.															

		3.3 System notifies the author and makes the article eligible for scheduling.
	4	Editor opens their own article. 4.1 System shows it approved, with the Publisher recorded as editor of record.
ALTERNATE FLOW A1 (Returned to the Author) 1. The Publisher judges that the copy needs work. 2. The Publisher returns it with notes. 3. The system records the notes and returns the article to its author. 4. The author revises and resubmits under UC-1.2. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.		

Module 2 — Issue Production and Publication

Assembling an issue from approved copy, laying it out, fixing its contents and releasing it.

Use Case Name: Schedule Articles into an Issue

Use Case ID:	UC-2.1																			
Author	Rei Khalil S. Galido																			
Purpose	Enable an Editor to determine which approved articles form a given issue, and on what terms readers may see each of them.																			
Related Use Case	None																			
Priority	High																			
Preconditions	• The system is available • The Editor is authenticated in the Editor role • The article is approved • The target issue exists and remains open • The article has been approved under UC-1.3.1																			
Postconditions	• The article belongs to the issue and carries a position within it • The article's reader access is recorded • The issue's readiness reflects the change • The article becomes visible to the Graphic Designer																			
Actors	• Editor • Graphic Designer (recipient)																			
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Editor opens the publishing panel on an approved article.</td><td>1.1 System lists the issues open for scheduling with their current contents and planned counts.</td></tr> <tr> <td>2</td><td>Editor selects an issue.</td><td>2.1 System places the article in the issue and marks it subscriber-only.</td></tr> <tr> <td>3</td><td>Editor sets the reader access, overriding the default where the piece is to run free.</td><td>3.1 System records the access level and applies it to the reader portal.</td></tr> <tr> <td></td><td></td><td>3.2 System updates the issue's readiness and makes the article visible for layout.</td></tr> <tr> <td>4</td><td>Graphic Designer opens the workspace.</td><td>4.1 System lists the article under its issue in Ready for layout.</td></tr> </table> ALTERNATE FLOW A1 (Left as a Standalone Article) 1. The Editor chooses not to place the article in an issue. 2. The system clears any existing issue and marks the article free to read, since it no longer forms part of the paid product. 3. The article becomes eligible for standalone release by the Publisher. 4. The article does not appear in the Designer's queue, because a web-only piece has no print layout.		Step	Actor Action	System Response	1	Editor opens the publishing panel on an approved article.	1.1 System lists the issues open for scheduling with their current contents and planned counts.	2	Editor selects an issue.	2.1 System places the article in the issue and marks it subscriber-only.	3	Editor sets the reader access, overriding the default where the piece is to run free.	3.1 System records the access level and applies it to the reader portal.			3.2 System updates the issue's readiness and makes the article visible for layout.	4	Graphic Designer opens the workspace.	4.1 System lists the article under its issue in Ready for layout.
Step	Actor Action	System Response																		
1	Editor opens the publishing panel on an approved article.	1.1 System lists the issues open for scheduling with their current contents and planned counts.																		
2	Editor selects an issue.	2.1 System places the article in the issue and marks it subscriber-only.																		
3	Editor sets the reader access, overriding the default where the piece is to run free.	3.1 System records the access level and applies it to the reader portal.																		
		3.2 System updates the issue's readiness and makes the article visible for layout.																		
4	Graphic Designer opens the workspace.	4.1 System lists the article under its issue in Ready for layout.																		

	ALTERNATE FLOW A2 (Issue Below Its Planned Count) 1. The issue holds fewer articles than it was planned for. 2. The system states the shortfall alongside the issue. 3. Scheduling proceeds, as the planned count is an intention rather than a limit. 4. The issue continues to report itself as not yet ready. EXCEPTION FLOW E1 (Issue Closed) 1. The Editor attempts to schedule an article into a closed issue. 2. The system detects that the table of contents is fixed. 3. The system refuses the change and leaves the issue untouched. 4. The system explains that the Publisher may reopen the issue. 5. The Editor requests a reopening or selects a different issue. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Use Case Name: Produce a Magazine Layout

Use Case ID:	UC-2.2
Author	Rei Khalil S. Galido
Purpose	Enable a Graphic Designer to lay out an issue and submit the edition readers will receive.
Related Use Case	None
Priority	High
Preconditions	• The system is available • The Graphic Designer is authenticated in the Graphic Designer role • The issue holds at least one approved article
Postconditions	• A versioned edition is recorded against the issue • The edition is held in protected storage and is not publicly addressable

	• The cover image is recorded for the public archive • The Editor is notified that an edition awaits review																														
Actors	• Graphic Designer • Editor (notified)																														
Flow of Actions	BASIC FLOW <table><tr><th>Step</th><th>Actor Action</th><th>System Response</th></tr><tr><td>1</td><td>Graphic Designer opens the workspace.</td><td>1.1 System lists each issue awaiting layout with the articles scheduled into it.</td></tr><tr><td>2</td><td>Graphic Designer reads the approved copy and produces the layout outside the system.</td><td></td></tr><tr><td>3</td><td>Graphic Designer selects the issue, enters the version label, and attaches the edition PDF, the cover image and any notes for the Editor.</td><td>3.1 System previews the cover image.</td></tr><tr><td>4</td><td>Graphic Designer submits the layout for editor review.</td><td>4.1 System confirms the issue is open, that no version is already under review, and that the version label is unused.</td></tr><tr><td></td><td></td><td>4.2 System issues a signed instruction permitting one transfer to storage, valid briefly.</td></tr><tr><td></td><td></td><td>4.3 System transfers the edition from the browser directly to storage and reports the progress.</td></tr><tr><td></td><td></td><td>4.4 System verifies with storage that the edition arrived and matches what was declared.</td></tr><tr><td></td><td></td><td>4.5 System records the layout as a new version awaiting review and notifies the Editor.</td></tr><tr><td>5</td><td>Editor opens their dashboard.</td><td>5.1 System shows the layout awaiting review.</td></tr></table> ALTERNATE FLOW A1 (Corrected Version Submitted) 1. The Editor has returned the edition with notes. 2. The Designer reads the notes and submits a corrected edition under a new version label. 3. The system validates that the label is unique within the issue. 4. The system records the new version and retains the previous one. 5. The system notifies the Editor. EXCEPTION FLOW E1 (Version Already Under Review) 1. The Designer submits while a version for this issue awaits the Editor. 2. The system detects the pending version before permitting any transfer. 3. The system refuses the submission and names the version already with the Editor. 4. The system explains that the Editor's response comes first. 5. Nothing is transferred and no record is created. EXCEPTION FLOW	Step	Actor Action	System Response	1	Graphic Designer opens the workspace.	1.1 System lists each issue awaiting layout with the articles scheduled into it.	2	Graphic Designer reads the approved copy and produces the layout outside the system.		3	Graphic Designer selects the issue, enters the version label, and attaches the edition PDF, the cover image and any notes for the Editor.	3.1 System previews the cover image.	4	Graphic Designer submits the layout for editor review.	4.1 System confirms the issue is open, that no version is already under review, and that the version label is unused.			4.2 System issues a signed instruction permitting one transfer to storage, valid briefly.			4.3 System transfers the edition from the browser directly to storage and reports the progress.			4.4 System verifies with storage that the edition arrived and matches what was declared.			4.5 System records the layout as a new version awaiting review and notifies the Editor.	5	Editor opens their dashboard.	5.1 System shows the layout awaiting review.
Step	Actor Action	System Response																													
1	Graphic Designer opens the workspace.	1.1 System lists each issue awaiting layout with the articles scheduled into it.																													
2	Graphic Designer reads the approved copy and produces the layout outside the system.																														
3	Graphic Designer selects the issue, enters the version label, and attaches the edition PDF, the cover image and any notes for the Editor.	3.1 System previews the cover image.																													
4	Graphic Designer submits the layout for editor review.	4.1 System confirms the issue is open, that no version is already under review, and that the version label is unused.																													
		4.2 System issues a signed instruction permitting one transfer to storage, valid briefly.																													
		4.3 System transfers the edition from the browser directly to storage and reports the progress.																													
		4.4 System verifies with storage that the edition arrived and matches what was declared.																													
		4.5 System records the layout as a new version awaiting review and notifies the Editor.																													
5	Editor opens their dashboard.	5.1 System shows the layout awaiting review.																													

	E2 (Transfer Incomplete) 1. The transfer to storage is interrupted or abandoned. 2. The system asks storage whether the object arrived rather than trusting the client's report. 3. Storage confirms nothing is there. 4. The system creates no record, so nothing claims a file that does not exist. 5. Any partial object is removed by the retention sweep. EXCEPTION FLOW E3 (Working File Submitted) 1. The Designer submits a working file rather than an exported PDF. 2. The system validates the file type before storing anything. 3. The system refuses the submission. 4. The system explains that the file becomes the edition subscribers read, and must therefore be exported. 5. The Designer exports the layout and retries. EXCEPTION FLOW A-VALID (Incomplete or Invalid Input) 1. The actor submits an edition. 2. The system validates every required field before committing anything. 3. The system detects that one or more required items are missing or malformed. 4. The system identifies each item and displays corrective guidance beside it. 5. The system prevents the incomplete operation from changing the workflow state. 6. The actor corrects the input and retries. 7. The system revalidates before continuing. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Approve a Magazine Layout

Use Case ID:	UC-2.3
Author	Roman Rico Albania
Purpose	Enable an Editor to accept a laid-out edition, or to return it with the changes required.

Related Use Case	None		
Priority	High		
Preconditions	• The system is available • The Editor is authenticated in the Editor role • An edition version awaits review • An edition version submitted under UC-2.2 awaits review		
Postconditions	• The edition is accepted or returned with notes • On acceptance, the reviewing Editor and the time are recorded • On acceptance, every other version for the issue is retired • The version becomes the issue's edition, released to subscribers when the issue is published		
Actors	• Editor • Graphic Designer (notified)		
Flow of Actions	BASIC FLOW		
	Step	Actor Action	System Response
	1	Editor opens the layout awaiting review.	1.1 System displays the version, the Graphic Designer's notes and a link to open the file.
	2	Editor opens and examines the edition.	
	3	Editor approves it.	3.1 System records the approval with the Editor and the time.
			3.2 System retires every other version for the issue, whether approved earlier, awaiting review, or returned.
			3.3 System notifies the Graphic Designer.
	4	Graphic Designer opens the workspace.	4.1 System shows the version as approved and lists the retired versions under Earlier versions.
	ALTERNATE FLOW		
	A1 (Returned for Revision)		
1. The Editor judges that the edition needs work. 2. The Editor records notes describing the changes required. 3. The system validates that notes have been supplied. 4. The system returns the version to the Designer and notifies them. 5. The Designer submits a corrected version under UC-2.2.			
EXCEPTION FLOW			
E-SAVE (Persistence Failure)			
1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery.			

	EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Close an Issue

Use Case ID:	UC-2.4																			
Author	Joshmar Clavero																			
Purpose	Enable a Publisher to fix the table of contents of an issue, so that its layout can be finalised without the contents shifting beneath it.																			
Related Use Case	None																			
Priority	High																			
Preconditions	• The system is available • The Publisher is authenticated in the Publisher role • The issue holds at least one scheduled article																			
Postconditions	• The issue's contents are fixed and further scheduling is refused • The closing Publisher and the time are recorded • Editors and Designers are notified that the contents are settled • The issue becomes eligible for publication																			
Actors	• Publisher • Editor (notified) • Graphic Designer (notified)																			
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Publisher opens an issue in preparation.</td><td>1.1 System displays the issue's contents, readiness and anything blocking it.</td></tr> <tr> <td>2</td><td>Publisher selects to close the issue.</td><td>2.1 System presents a confirmation naming the article count and the consequences.</td></tr> <tr> <td>3</td><td>Publisher confirms.</td><td>3.1 System validates that the issue holds at least one article.</td></tr> <tr> <td></td><td></td><td>3.2 System fixes the contents and records the closing Publisher and the time.</td></tr> <tr> <td></td><td></td><td>3.3 System notifies Editors and</td></tr> </table>		Step	Actor Action	System Response	1	Publisher opens an issue in preparation.	1.1 System displays the issue's contents, readiness and anything blocking it.	2	Publisher selects to close the issue.	2.1 System presents a confirmation naming the article count and the consequences.	3	Publisher confirms.	3.1 System validates that the issue holds at least one article.			3.2 System fixes the contents and records the closing Publisher and the time.			3.3 System notifies Editors and
Step	Actor Action	System Response																		
1	Publisher opens an issue in preparation.	1.1 System displays the issue's contents, readiness and anything blocking it.																		
2	Publisher selects to close the issue.	2.1 System presents a confirmation naming the article count and the consequences.																		
3	Publisher confirms.	3.1 System validates that the issue holds at least one article.																		
		3.2 System fixes the contents and records the closing Publisher and the time.																		
		3.3 System notifies Editors and																		

		Designers that the contents are settled.
	4	Editor or Graphic Designer opens the issues overview. 4.1 System shows the issue as closed, with its contents fixed.
ALTERNATE FLOW A1 (Issue Reopened) 1. A late story warrants admission to a closed issue. 2. The Publisher selects to reopen it and enters the reason. 3. The system validates that a reason of sufficient length is supplied. 4. The system reopens the issue and records the reason against it. 5. Editors may schedule into the issue once more. ALTERNATE FLOW A2 (Issue Below Its Planned Count) 1. The issue holds fewer articles than planned. 2. The system states the shortfall in the confirmation. 3. The Publisher may close regardless, as the planned count is an intention. 4. The issue continues to report itself as not yet ready until the count is met or the plan revised. EXCEPTION FLOW E1 (Empty Issue) 1. The Publisher attempts to close an issue holding no articles. 2. The system validates the article count before committing. 3. The system refuses the closure. 4. The system explains that an empty issue has no contents to fix. EXCEPTION FLOW E2 (Reason Absent on Reopening) 1. The Publisher confirms a reopening without an adequate reason. 2. The system validates the reason before committing. 3. The system refuses and leaves the issue closed. 4. The Publisher supplies a reason and retries. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.		

Use Case Name: Publish an Issue

Use Case ID:	UC-2.5																									
Author	Joshmar Clavero																									
Purpose	Release an issue and every article within it to readers, as a single indivisible act.																									
Related Use Case	None																									
Priority	High																									
Preconditions	• The system is available • The Publisher is authenticated in the Publisher role • The issue is closed • Every scheduled article is approved • The issue meets its planned article count • An edition has been accepted for the issue • The issue has been closed under UC-2.4																									
Postconditions	• The issue and every article within it are released to readers • The release time and the releasing Publisher are recorded • Subscribers are notified that a new issue is available • The digital edition is available where an accepted edition exists																									
Actors	• Publisher • Reader (recipient) • Scheduler																									
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Publisher opens a closed issue and selects to publish.</td><td>1.1 System confirms the issue is closed, holds an approved edition, and that every article in it is approved.</td></tr> <tr> <td></td><td></td><td>1.2 System presents a confirmation naming every article that will be released.</td></tr> <tr> <td>2</td><td>Publisher confirms.</td><td>2.1 System releases the issue and all its articles in a single transaction.</td></tr> <tr> <td></td><td></td><td>2.2 System records the release time and the releasing Publisher.</td></tr> <tr> <td></td><td></td><td>2.3 System removes superseded layout versions from storage, keeping their records.</td></tr> <tr> <td></td><td></td><td>2.4 System notifies subscribers that a new issue is available.</td></tr> <tr> <td>3</td><td>Reader opens the reader portal.</td><td>3.1 System presents the new issue and its articles.</td></tr> </table> ALTERNATE FLOW A1 (Standalone Article Released) 1. The Publisher selects an approved article belonging to no issue.		Step	Actor Action	System Response	1	Publisher opens a closed issue and selects to publish.	1.1 System confirms the issue is closed, holds an approved edition, and that every article in it is approved.			1.2 System presents a confirmation naming every article that will be released.	2	Publisher confirms.	2.1 System releases the issue and all its articles in a single transaction.			2.2 System records the release time and the releasing Publisher.			2.3 System removes superseded layout versions from storage, keeping their records.			2.4 System notifies subscribers that a new issue is available.	3	Reader opens the reader portal.	3.1 System presents the new issue and its articles.
Step	Actor Action	System Response																								
1	Publisher opens a closed issue and selects to publish.	1.1 System confirms the issue is closed, holds an approved edition, and that every article in it is approved.																								
		1.2 System presents a confirmation naming every article that will be released.																								
2	Publisher confirms.	2.1 System releases the issue and all its articles in a single transaction.																								
		2.2 System records the release time and the releasing Publisher.																								
		2.3 System removes superseded layout versions from storage, keeping their records.																								
		2.4 System notifies subscribers that a new issue is available.																								
3	Reader opens the reader portal.	3.1 System presents the new issue and its articles.																								

	2. The system confirms that the article publishes on its own. 3. The system releases the single article without reference to any issue. 4. The article appears on the reader portal as a web piece with no edition. ALTERNATE FLOW A2 (Release Scheduled) 1. The Publisher sets a future release time rather than publishing at once. 2. The system validates that the time lies ahead and the issue is ready. 3. The system records the scheduled release. 4. At the appointed time the scheduler releases the issue as in the basic flow. 5. The Publisher is notified that the release has occurred. EXCEPTION FLOW E1 (No Accepted Edition) 1. The Publisher attempts to release an issue with no accepted edition. 2. The system detects that nothing has been accepted for the issue. 3. The system refuses publication and names the requirement. 4. The system explains that the Designer must submit the edition and an Editor accept it. 5. Nothing is published. EXCEPTION FLOW E2 (Issue Not Closed) 1. The Publisher attempts to release an issue still open for scheduling. 2. The system detects that the contents are not fixed. 3. The system refuses publication and names the closure requirement. 4. The Publisher closes the issue and retries. EXCEPTION FLOW E3 (Unapproved Article Present) 1. One or more scheduled articles have not been approved. 2. The system evaluates readiness before beginning the transaction. 3. The system refuses publication and names each blocking article. 4. No article is released, since a partially published issue is not an issue. EXCEPTION FLOW E4 (Scheduled Release Cannot Proceed) 1. An article is withdrawn after the issue has been scheduled for release. 2. At the appointed time the system finds the issue no longer ready. 3. The system cancels the release rather than publishing an incomplete issue. 4. The system notifies the Publisher that intervention is required. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it.
--	--

	5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Use Case Name: Retire an Issue

Use Case ID:	UC-2.6													
Author	Joshua Concepcion													
Purpose	Enable a Publisher to move a completed issue out of the active publishing list while readers keep access to it.													
Related Use Case	None													
Priority	Low													
Preconditions	• The system is available • The Publisher is authenticated in the Publisher role • The issue has been published • The issue has been published under UC-2.5													
Postconditions	• The issue no longer appears among issues in preparation • The issue and its articles remain readable on the reader portal • The issue remains searchable in the published archive													
Actors	• Publisher													
Flow of Actions	BASIC FLOW <table border="1"> <thead> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> </thead> <tbody> <tr> <td>1</td><td>Publisher opens a published issue and selects to retire it.</td><td>1.1 System presents a confirmation stating that readers keep access.</td></tr> <tr> <td>2</td><td>Publisher confirms.</td><td>2.1 System retires the issue from the active publishing list.</td></tr> <tr> <td></td><td></td><td>2.2 System leaves the issue and its articles available to readers and searchable in the archive.</td></tr> </tbody> </table> EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission.		Step	Actor Action	System Response	1	Publisher opens a published issue and selects to retire it.	1.1 System presents a confirmation stating that readers keep access.	2	Publisher confirms.	2.1 System retires the issue from the active publishing list.			2.2 System leaves the issue and its articles available to readers and searchable in the archive.
Step	Actor Action	System Response												
1	Publisher opens a published issue and selects to retire it.	1.1 System presents a confirmation stating that readers keep access.												
2	Publisher confirms.	2.1 System retires the issue from the active publishing list.												
		2.2 System leaves the issue and its articles available to readers and searchable in the archive.												

	4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Module 3 — Editorial and Issue Oversight

Knowing where work stands, how the publication is performing, and what it has already run.

Use Case Name: Review Publication Performance

Use Case ID:	UC-3.1																			
Author	Roman Rico Albania																			
Purpose	Enable an Editor, Publisher or Administrator to understand how the publication is performing: what is moving, how long it takes, how the assessment is behaving, and what the subscriber base is worth.																			
Related Use Case	None																			
Priority	Medium																			
Preconditions	• The system is available • The actor is authenticated in the Editor, Publisher or Administrator role • Revenue reporting additionally requires the Publisher or Administrator role																			
Postconditions	• The requested report is presented for the chosen period • The basis of any derived figure is stated • No state change occurs																			
Actors	• Editor • Publisher • Administrator																			
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Editor, Publisher or Administrator opens the reports area and selects a report.</td><td></td></tr> <tr> <td>2</td><td>Editor, Publisher or Administrator sets the period to report on.</td><td>2.1 System aggregates the underlying records for that period.</td></tr> <tr> <td></td><td></td><td>2.2 System presents the report with its figures and their basis.</td></tr> <tr> <td></td><td></td><td>2.3 System accompanies each chart with a textual description, so the figures are available to anyone who cannot read the chart.</td></tr> <tr> <td>3</td><td>Editor, Publisher or Administrator changes the period or moves to another report.</td><td></td></tr> </table> ALTERNATE FLOW A1 (No Data in Period) 1. The chosen period holds no records of the kind reported. 2. The system states that no data exists for the period. 3. The system offers a wider period. 4. No empty chart is drawn, since an empty chart reads as zero rather than absent.		Step	Actor Action	System Response	1	Editor, Publisher or Administrator opens the reports area and selects a report.		2	Editor, Publisher or Administrator sets the period to report on.	2.1 System aggregates the underlying records for that period.			2.2 System presents the report with its figures and their basis.			2.3 System accompanies each chart with a textual description, so the figures are available to anyone who cannot read the chart.	3	Editor, Publisher or Administrator changes the period or moves to another report.	
Step	Actor Action	System Response																		
1	Editor, Publisher or Administrator opens the reports area and selects a report.																			
2	Editor, Publisher or Administrator sets the period to report on.	2.1 System aggregates the underlying records for that period.																		
		2.2 System presents the report with its figures and their basis.																		
		2.3 System accompanies each chart with a textual description, so the figures are available to anyone who cannot read the chart.																		
3	Editor, Publisher or Administrator changes the period or moves to another report.																			

	ALTERNATE FLOW A2 (Demonstration Data Present) 1. Some assessments in the period were produced for demonstration rather than by the evaluation service. 2. The system identifies them in the report. 3. The figures are presented with that qualification rather than suppressed. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Monitor Editorial Progress

Use Case ID:	UC-3.2													
Author	Joshmar Clavero													
Purpose	Enable staff to see what needs their attention, what is sitting with somebody else, and what is at risk of being late.													
Related Use Case	None													
Priority	High													
Preconditions	• The system is available • The actor is authenticated in a staff role													
Postconditions	• Work is presented grouped by whether the actor can act on it • Overdue work is identified • Deadline warnings have been delivered to those responsible • No state change occurs													
Actors	• Writer • Editor • Publisher • Scheduler													
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Staff member signs in and arrives at their dashboard.</td><td>1.1 System determines the actor's role and assembles the queues relevant to it.</td></tr> <tr> <td></td><td></td><td>1.2 System groups the work by whether the actor can act on it now or is waiting on another party.</td></tr> <tr> <td></td><td></td><td>1.3 System identifies overdue work and</td></tr> </table>		Step	Actor Action	System Response	1	Staff member signs in and arrives at their dashboard.	1.1 System determines the actor's role and assembles the queues relevant to it.			1.2 System groups the work by whether the actor can act on it now or is waiting on another party.			1.3 System identifies overdue work and
Step	Actor Action	System Response												
1	Staff member signs in and arrives at their dashboard.	1.1 System determines the actor's role and assembles the queues relevant to it.												
		1.2 System groups the work by whether the actor can act on it now or is waiting on another party.												
		1.3 System identifies overdue work and												

		offers a filtered view of it.
	2	Staff member opens the calendar to see deadlines and release targets across the month. 2.1 System displays the month, distinguishing overdue work, work in hand and settled work.
	3	Staff member selects an item and acts on it.
ALTERNATE FLOW A1 (Deadline Sweep) 1. The scheduler invokes the deadline sweep at its appointed time. 2. The system authenticates the request against the scheduler credential. 3. The system identifies open work whose deadline is approaching or has passed. 4. The system notifies each Writer, and the commissioning Editor for overdue work. 5. The system records the outcome of the sweep. ALTERNATE FLOW A2 (Nothing Outstanding) 1. A queue or a month holds no items. 2. The system explains what would appear there and how it arrives. 3. The actor is directed to the action that would populate it. 4. No empty chart or blank panel is drawn, since an empty display reads as zero rather than as absent. EXCEPTION FLOW E1 (Unauthenticated Sweep Request) 1. A request to run the deadline sweep arrives without a valid credential. 2. The system refuses it and produces no notifications. 3. The system records the refusal, since an unauthenticated call to a scheduled endpoint may indicate probing. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.		

Use Case Name: Consult the Published Archive

Use Case ID:	UC-3.3
Author	Joshua Concepcion
Purpose	Enable staff to find anything the publication has run, so that past work informs present decisions.
Related Use Case	None
Priority	Medium
Preconditions	• The system is available

	• The actor is authenticated in a staff role															
Postconditions	• The matching published work is presented • No state change occurs															
Actors	• Writer • Editor • Publisher • Graphic Designer															
Flow of Actions	BASIC FLOW <table><thead><tr><th>Step</th><th>Actor Action</th><th>System Response</th></tr></thead><tbody><tr><td>1</td><td>Staff member opens the archive.</td><td>1.1 System presents everything published, grouped by the month it ran.</td></tr><tr><td>2</td><td>Staff member searches a term, or filters by issue, category or year.</td><td>2.1 System presents the matching work with its issue and its reader access.</td></tr><tr><td>3</td><td>Staff member opens an article.</td><td>3.1 System opens a read-only preview with the full text, the photography and the article's publication details.</td></tr><tr><td></td><td></td><td>3.2 System offers a link to the article's page on the public site.</td></tr></tbody></table> ALTERNATE FLOW A1 (No Matches) 1. The search or filter returns nothing. 2. The system states that nothing matched. 3. The system offers to clear the filters. 4. The total published count remains visible, so the absence is understood as a narrow search rather than an empty archive. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.	Step	Actor Action	System Response	1	Staff member opens the archive.	1.1 System presents everything published, grouped by the month it ran.	2	Staff member searches a term, or filters by issue, category or year.	2.1 System presents the matching work with its issue and its reader access.	3	Staff member opens an article.	3.1 System opens a read-only preview with the full text, the photography and the article's publication details.			3.2 System offers a link to the article's page on the public site.
Step	Actor Action	System Response														
1	Staff member opens the archive.	1.1 System presents everything published, grouped by the month it ran.														
2	Staff member searches a term, or filters by issue, category or year.	2.1 System presents the matching work with its issue and its reader access.														
3	Staff member opens an article.	3.1 System opens a read-only preview with the full text, the photography and the article's publication details.														
		3.2 System offers a link to the article's page on the public site.														

Module 4 — Reader Engagement

What a reader can do with the publication, and what a subscription adds.

Use Case Name: Read Published Content

Use Case ID:	UC-4.1																
Author	Rei Khalil S. Galido																
Purpose	Enable anyone to read the publication, and to understand what a subscription would give them.																
Related Use Case	None																
Priority	High																
Preconditions	• The system is available • At least one article has been published																
Postconditions	• The requested content is presented within the reader's entitlement • No state change occurs																
Actors	• Anonymous Visitor • Reader																
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Visitor opens the reader portal.</td><td>1.1 System presents the lead article and the most recent published work.</td></tr> <tr> <td>2</td><td>Visitor filters by category or opens an article.</td><td>2.1 System determines the visitor's entitlement.</td></tr> <tr> <td></td><td></td><td>2.2 System presents the article in full where it is freely available.</td></tr> <tr> <td>3</td><td>Visitor passes the article to somebody else.</td><td>3.1 System offers the device's sharing options, or copies the address where these are unavailable.</td></tr> </table> ALTERNATE FLOW A1 (Subscriber-only Article) 1. The requested article is reserved for subscribers. 2. The system presents the standfirst and the opening passage. 3. The system presents the subscription notice beneath the extract. 4. The remainder is withheld. 5. A subscriber receives the article in full without interruption. EXCEPTION FLOW E1 (Platform Under Maintenance) 1. Maintenance has been enabled by an Administrator. 2. The system returns the maintenance notice to public requests. 3. No article content is served. 4. Authenticated staff continue to work normally, since a maintenance mode that locked out the people performing the maintenance would defeat itself.		Step	Actor Action	System Response	1	Visitor opens the reader portal.	1.1 System presents the lead article and the most recent published work.	2	Visitor filters by category or opens an article.	2.1 System determines the visitor's entitlement.			2.2 System presents the article in full where it is freely available.	3	Visitor passes the article to somebody else.	3.1 System offers the device's sharing options, or copies the address where these are unavailable.
Step	Actor Action	System Response															
1	Visitor opens the reader portal.	1.1 System presents the lead article and the most recent published work.															
2	Visitor filters by category or opens an article.	2.1 System determines the visitor's entitlement.															
		2.2 System presents the article in full where it is freely available.															
3	Visitor passes the article to somebody else.	3.1 System offers the device's sharing options, or copies the address where these are unavailable.															

Use Case Name: Save Articles for Later

Use Case ID:	UC-4.2													
Author	Roman Rico Albania													
Purpose	Enable a reader to keep articles and return to them.													
Related Use Case	None													
Priority	Medium													
Preconditions	• The system is available • The reader is authenticated • The article has been published													
Postconditions	• The article appears in the reader's saved list • Saving the same article twice produces no duplicate													
Actors	• Reader													
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Reader selects the save control on an article.</td><td>1.1 System records the article against the reader and confirms.</td></tr> <tr> <td>2</td><td>Reader opens their saved list.</td><td>2.1 System presents the saved articles, most recently saved first.</td></tr> <tr> <td>3</td><td>Reader removes an article from the list.</td><td>3.1 System removes the record and the article leaves the list.</td></tr> </table> ALTERNATE FLOW A1 (Visitor Not Signed In) 1. An anonymous visitor selects the save control. 2. The system records nothing. 3. The system explains that saving requires an account and offers to sign in. 4. The visitor is not navigated away, so their place in the article is kept. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied.		Step	Actor Action	System Response	1	Reader selects the save control on an article.	1.1 System records the article against the reader and confirms.	2	Reader opens their saved list.	2.1 System presents the saved articles, most recently saved first.	3	Reader removes an article from the list.	3.1 System removes the record and the article leaves the list.
Step	Actor Action	System Response												
1	Reader selects the save control on an article.	1.1 System records the article against the reader and confirms.												
2	Reader opens their saved list.	2.1 System presents the saved articles, most recently saved first.												
3	Reader removes an article from the list.	3.1 System removes the record and the article leaves the list.												

	7. After authorization is restored, the actor may retry.
--	--

Use Case Name: Subscribe to BOSS Magazine

Use Case ID:	UC-4.3
Author	Joshmar Clavero
Purpose	Enable a reader to purchase access to the publication's paid content.
Related Use Case	«include» UC-4.3.1 (Read Subscriber-Only Content)
Priority	High
Preconditions	• The system is available • The reader holds an account • The payment provider is reachable
Postconditions	• A subscription exists and the reader holds the subscriber tier • The transaction is recorded with its amount, currency and outcome • The provider's customer reference is recorded • No card detail is held by this system
Actors	• Reader • Payment Gateway

	3. The system records the rejected confirmation. 4. An administrator is alerted, since a failed signature may indicate an attempted forgery. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery.
--	---

Use Case Name: Read Subscriber-Only Content

Use Case ID:	UC-4.3.1																									
Author	Joshmar Clavero																									
Purpose	Enable a subscriber to read the laid-out magazine, in the browser or as a file they keep.																									
Related Use Case	Included by UC-4.3 (Subscribe to BOSS Magazine)																									
Priority	High																									
Preconditions	• The system is available • The reader is authenticated and holds a subscription • The issue has been published and carries an accepted edition • The issue has been published and carries an edition accepted under UC-2.3																									
Postconditions	• A time-limited address for the edition is issued to the reader • The address expires shortly after issue • The reader's page-turn preference is retained																									
Actors	• Reader (subscriber)																									
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Subscriber opens a subscriber-only article.</td><td>1.1 System verifies the subscription.</td></tr> <tr> <td></td><td></td><td>1.2 System presents the article in full.</td></tr> <tr> <td>2</td><td>Subscriber opens a published issue and selects to read it.</td><td>2.1 System confirms that an approved edition exists.</td></tr> <tr> <td></td><td></td><td>2.2 System issues a time-limited address for the edition.</td></tr> <tr> <td></td><td></td><td>2.3 System renders the first page and reports the page count.</td></tr> <tr> <td>3</td><td>Subscriber turns pages by control, keyboard or slider.</td><td>3.1 System renders each page at the size the display allows.</td></tr> <tr> <td>4</td><td>Subscriber downloads the edition, or</td><td>4.1 System retains the page-turn</td></tr> </table>		Step	Actor Action	System Response	1	Subscriber opens a subscriber-only article.	1.1 System verifies the subscription.			1.2 System presents the article in full.	2	Subscriber opens a published issue and selects to read it.	2.1 System confirms that an approved edition exists.			2.2 System issues a time-limited address for the edition.			2.3 System renders the first page and reports the page count.	3	Subscriber turns pages by control, keyboard or slider.	3.1 System renders each page at the size the display allows.	4	Subscriber downloads the edition, or	4.1 System retains the page-turn
Step	Actor Action	System Response																								
1	Subscriber opens a subscriber-only article.	1.1 System verifies the subscription.																								
		1.2 System presents the article in full.																								
2	Subscriber opens a published issue and selects to read it.	2.1 System confirms that an approved edition exists.																								
		2.2 System issues a time-limited address for the edition.																								
		2.3 System renders the first page and reports the page count.																								
3	Subscriber turns pages by control, keyboard or slider.	3.1 System renders each page at the size the display allows.																								
4	Subscriber downloads the edition, or	4.1 System retains the page-turn																								

	adjusts the page-turn treatment.	preference for subsequent readings.
ALTERNATE FLOW A1 (<i>Reduced Motion Requested</i>) 1. The reader's device requests reduced motion. 2. The system defaults the page-turn treatment to none without being asked. 3. Pages change without animation. 4. The reader may still choose an animated treatment explicitly. ALTERNATE FLOW A2 (<i>No Edition for the Issue</i>) 1. The issue has been published but carries no accepted edition. 2. The system states that no digital edition is available. 3. The articles remain readable on the reader portal. 4. An edition accepted later becomes available without republication. EXCEPTION FLOW E1 (<i>Reader Not a Subscriber</i>) 1. A free or anonymous reader requests the edition. 2. The system verifies the entitlement and finds none. 3. The system refuses the request and issues no address. 4. The system explains that the edition is available to subscribers. 5. The file itself remains unreachable, since it is not publicly addressable. EXCEPTION FLOW E2 (<i>Edition Cannot Be Rendered</i>) 1. The system obtains the edition but cannot render it in the browser. 2. The system states that the edition could not be opened. 3. The system offers the download as an alternative. 4. The failure is recorded for diagnosis. EXCEPTION FLOW E-AUTH (<i>Authorization or Session Failure</i>) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.		

Use Case Name: Manage a Subscription

Use Case ID:	UC-4.4
Author	Joshua Concepcion
Purpose	Enable a subscriber to see what they are paying for, change how they pay, or stop paying.
Related Use Case	None
Priority	Medium
Preconditions	• The system is available

	• The reader is authenticated and holds a subscription • A subscription exists, obtained under UC-4.3																		
Postconditions	• The subscription reflects the reader's instruction • Access continues to the end of any period already paid for • No card detail is held by this system																		
Actors	• Reader (subscriber) • Payment Gateway																		
Flow of Actions	BASIC FLOW<table><tr><th>Step</th><th>Actor Action</th><th>System Response</th></tr><tr><td>1</td><td>Subscriber opens their subscription details.</td><td>1.1 System presents the plan, the renewal date and the payment method as the Payment Gateway describes it.</td></tr><tr><td>2</td><td>Subscriber selects to cancel.</td><td>2.1 System states the date to which access will continue.</td></tr><tr><td>3</td><td>Subscriber confirms.</td><td>3.1 System sends the cancellation to the Payment Gateway.</td></tr><tr><td>4</td><td>Payment Gateway confirms the cancellation takes effect at the end of the paid period.</td><td>4.1 System records the date access ends.</td></tr><tr><td></td><td></td><td>4.2 System returns the Reader to the free tier at that date.</td></tr></table> ALTERNATE FLOW A1 (Payment Method Updated) 1. The subscriber selects to update their payment method. 2. The system directs them to the provider's interface. 3. The subscriber updates the method with the provider. 4. The system reflects the change on their return. ALTERNATE FLOW A2 (Cancellation Reversed) 1. The subscriber resumes before the paid period expires. 2. The system reinstates the subscription with the provider. 3. No gap in access occurs. 4. The system records the reinstatement. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action.	Step	Actor Action	System Response	1	Subscriber opens their subscription details.	1.1 System presents the plan, the renewal date and the payment method as the Payment Gateway describes it.	2	Subscriber selects to cancel.	2.1 System states the date to which access will continue.	3	Subscriber confirms.	3.1 System sends the cancellation to the Payment Gateway.	4	Payment Gateway confirms the cancellation takes effect at the end of the paid period.	4.1 System records the date access ends.			4.2 System returns the Reader to the free tier at that date.
Step	Actor Action	System Response																	
1	Subscriber opens their subscription details.	1.1 System presents the plan, the renewal date and the payment method as the Payment Gateway describes it.																	
2	Subscriber selects to cancel.	2.1 System states the date to which access will continue.																	
3	Subscriber confirms.	3.1 System sends the cancellation to the Payment Gateway.																	
4	Payment Gateway confirms the cancellation takes effect at the end of the paid period.	4.1 System records the date access ends.																	
		4.2 System returns the Reader to the free tier at that date.																	

	3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Module 5 — Accounts and Platform Administration

Getting into the system, looking after your own account, and looking after everybody else's.

Use Case Name: Register and Authenticate

Use Case ID:	UC-5.1	
Author	Rei Khalil S. Galido	
Purpose	Enable a person to obtain an account and to prove who they are on each return.	
Related Use Case	None	
Priority	High	
Preconditions	The system is available	
Postconditions	- An account exists, or a session is established and scoped to the account's role - The actor is directed to the interface appropriate to their role - Consent to the terms is recorded at registration	
Actors	User (Reader, Writer, Editor, Publisher or Graphic Designer)	
Flow of Actions	BASIC FLOW	
	Step	Actor Action
		System Response
	1	User opens the registration page and enters their name, email address and a password.
		1.1 System indicates the strength of the password as it is entered.
	2	User consents to the terms and submits.
		2.1 System validates the email format, the password strength and the uniqueness of the address.
		2.2 System creates the account, records the consent and establishes a session.
	3	On a later visit, the User enters their email address and password.
		3.1 System validates the credentials and confirms the account is active.
		3.2 System issues an access credential and a renewal credential, and directs the User to the interface for their role.
ALTERNATE FLOW		
A1 (Session Renewed Transparently)		
- The access credential expires while the actor is working. - The system exchanges the renewal credential for a fresh access credential. - The system retries the interrupted request. - The actor continues without interruption and without losing work. - Where the renewal credential has also expired, the system ends the session and says so plainly.		
ALTERNATE FLOW		
A2 (Staff Account at the Reader Sign-in)		
- A staff account signs in through the reader portal. - The system authenticates the credentials successfully. - The system ends the session and directs the actor to the staff portal. - The two portals serve different audiences and are kept distinct.		

	ALTERNATE FLOW A3 (Address Already Registered) 1. The submitted address already belongs to an account. 2. The system refuses the registration. 3. The system directs the visitor to sign in instead. 4. The system discloses nothing beyond what the visitor already supplied. EXCEPTION FLOW E1 (Credentials Not Recognised) 1. The actor submits an incorrect address or password. 2. The system finds no match and refuses the sign-in. 3. The system does not state which field was wrong, since doing so would confirm which addresses hold accounts. 4. The system records the failed attempt. 5. Repeated failures are surfaced to the actor as a caution. EXCEPTION FLOW E2 (Account Suspended) 1. The credentials are correct but the account has been suspended. 2. The system refuses the sign-in and establishes no session. 3. The system states that the account is not currently active and directs the actor to an administrator. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery.
--	--

Use Case Name: Manage Own Account

Use Case ID:	UC-5.2
Author	Roman Rico Albania
Purpose	Enable a person to keep their own details current, control their password, and choose what the system tells them about.
Related Use Case	None
Priority	Medium
Preconditions	• The system is available • The actor is authenticated, except where recovering a forgotten password
Postconditions	• The account reflects the actor's changes • A changed password is stored as a hash and other sessions are ended • Notification preferences govern subsequent notifications • Security and account notices continue to be delivered regardless of preference
Actors	• User (Reader, Writer, Editor, Publisher or Graphic Designer)

Flow of Actions	BASIC FLOW		
	Step	Actor Action	System Response
	1	User opens their account settings.	1.1 System presents the current name and sign-in address.
	2	User amends their details.	2.1 Where the sign-in address has changed, System asks for the current password.
	3	User supplies the password and saves.	3.1 System verifies the password and the uniqueness of the new address.
			3.2 System stores the changes and confirms them.
	ALTERNATE FLOW		
	A1 (Name Change Only)		
	1. The actor amends their name without touching the sign-in address. 2. The system requires no password. 3. The system stores the change immediately.		
	ALTERNATE FLOW		
	A2 (Password Changed While Signed In)		
	1. The actor changes their password from account settings. 2. The system requires the current password and validates the strength of the new one. 3. The system stores the new hash and retains the current session. 4. Other sessions for the account are ended.		
	ALTERNATE FLOW		
	A3 (Password Forgotten)		
	1. The actor requests recovery for their address. 2. The system dispatches a single-use, time-limited recovery link. 3. The actor follows the link and sets a new password. 4. The system validates the link's authenticity and expiry, then the new password's strength. 5. The system stores the new hash and ends existing sessions.		
	ALTERNATE FLOW		
	A4 (Recovery for an Unregistered Address)		
	1. The submitted address belongs to no account. 2. The system displays the same confirmation as for a valid address. 3. No recovery message is dispatched. 4. Account existence is not inferable from the response.		
	ALTERNATE FLOW		
	A5 (Notifications Adjusted)		
	1. The actor mutes a kind of notification they no longer want. 2. The system records the preference and applies it to subsequent notifications. 3. The underlying events continue to occur and remain visible on the dashboard, so nothing is lost by muting. 4. Security and account notices are delivered regardless.		
	EXCEPTION FLOW		
	E1 (Password Not Correct)		
	1. The actor supplies an incorrect current password for a protected change. 2. The system verifies before committing anything. 3. The system refuses the change and leaves the account unaltered. 4. The actor retries.		

	EXCEPTION FLOW E2 (Address Already in Use) 1. The new sign-in address already belongs to another account. 2. The system detects the collision before committing. 3. The system refuses the change and states that the address is unavailable, without disclosing whose account holds it. EXCEPTION FLOW E3 (Recovery Link Expired or Used) 1. The actor follows a recovery link after it has expired or been redeemed. 2. The system finds the link invalid and refuses the change. 3. The system offers to send a fresh link. 4. The existing password remains in force. EXCEPTION FLOW E-SAVE (Persistence Failure) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (Authorization or Session Failure) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	---

Use Case Name: Administer User Accounts

Use Case ID:	UC-5.3
Author	Joshmar Clavero
Purpose	Enable an Administrator to control who has access to the system and what each person may do.
Related Use Case	None
Priority	High
Preconditions	• The system is available • The Administrator is authenticated with administration access
Postconditions	• The account reflects the change • A role change takes effect on the account's next request • A suspended account is refused regardless of the role it holds • The account's articles, versions and history are retained in every case

Actors	• Administrator		
Flow of Actions	BASIC FLOW		
	Step	Actor Action	System Response
	1	Administrator opens the user directory.	1.1 System lists the accounts with their role, status and last sign-in.
	2	Administrator searches or filters to find an account.	
	3	Administrator changes the account's role, suspends it, or grants a subscription tier.	3.1 System validates the change against the roles and tiers it recognises.
			3.2 System stores the change and applies it on the account's next request.
			3.3 System retains the account's articles, versions and history in every case.
	ALTERNATE FLOW		
	A1 (Account Holds Outstanding Work)		
	1. The account holds articles commissioned under its previous role. 2. The system does not reassign or withdraw that work. 3. The system stores the role change. 4. The Administrator reassigns outstanding work where the change makes it unreachable to its holder.		
	ALTERNATE FLOW		
	A2 (Subscription Granted Directly)		
	1. A reader is to receive a subscription without passing through payment. 2. The Administrator sets the tier directly. 3. The system records the tier and the start date. 4. Access is granted on exactly the same terms as a purchased subscription, since the entitlement checks do not distinguish between the two routes.		
	EXCEPTION FLOW		
	E-SAVE (Persistence Failure)		
1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery.			
EXCEPTION FLOW			
E-AUTH (Authorization or Session Failure)			
1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.			

Use Case Name: Configure the Platform

Use Case ID:	UC-5.4																			
Author	Joshua Concepcion																			
Purpose	Enable an Administrator to set how the publication presents itself, to see whether its external services are working, and to hold public traffic during an update.																			
Related Use Case	None																			
Priority	Medium																			
Preconditions	- The system is available - The Administrator is authenticated in the Administrator role																			
Postconditions	- The configuration is stored and takes effect without redeployment - The updating Administrator is recorded - Where maintenance is enabled, public traffic receives the notice and staff continue working																			
Actors	Administrator																			
Flow of Actions	BASIC FLOW <table> <tr> <th>Step</th><th>Actor Action</th><th>System Response</th></tr> <tr> <td>1</td><td>Administrator opens platform settings.</td><td>1.1 System presents the current configuration and the status of each external service.</td></tr> <tr> <td>2</td><td>Administrator amends the publication name, tagline, accent colour or page size.</td><td>2.1 System validates the values, including the colour format.</td></tr> <tr> <td></td><td></td><td>2.2 System stores the configuration, records the Administrator, and applies it without redeployment.</td></tr> <tr> <td>3</td><td>Administrator enables maintenance and sets the notice before an update.</td><td>3.1 System returns the notice to unauthenticated public requests while continuing to serve staff.</td></tr> <tr> <td>4</td><td>Administrator disables maintenance once the update is complete.</td><td></td></tr> </table> ALTERNATE FLOW A1 (Service Not Configured) 1. An external service holds no credential. 2. The system reports it as unconfigured. 3. The system states the consequence — what the system does instead in its absence. 4. No credential is ever displayed, since the interface does not hold them. EXCEPTION FLOW A-VALID (Incomplete or Invalid Input) 1. The actor submits a configuration value. 2. The system validates every required field before committing anything. 3. The system detects that one or more required items are missing or malformed. 4. The system identifies each item and displays corrective guidance beside it. 5. The system prevents the incomplete operation from changing the workflow state. 6. The actor corrects the input and retries.		Step	Actor Action	System Response	1	Administrator opens platform settings.	1.1 System presents the current configuration and the status of each external service.	2	Administrator amends the publication name, tagline, accent colour or page size.	2.1 System validates the values, including the colour format.			2.2 System stores the configuration, records the Administrator, and applies it without redeployment.	3	Administrator enables maintenance and sets the notice before an update.	3.1 System returns the notice to unauthenticated public requests while continuing to serve staff.	4	Administrator disables maintenance once the update is complete.	
Step	Actor Action	System Response																		
1	Administrator opens platform settings.	1.1 System presents the current configuration and the status of each external service.																		
2	Administrator amends the publication name, tagline, accent colour or page size.	2.1 System validates the values, including the colour format.																		
		2.2 System stores the configuration, records the Administrator, and applies it without redeployment.																		
3	Administrator enables maintenance and sets the notice before an update.	3.1 System returns the notice to unauthenticated public requests while continuing to serve staff.																		
4	Administrator disables maintenance once the update is complete.																			

	7. The system revalidates before continuing. EXCEPTION FLOW E-SAVE (<i>Persistence Failure</i>) 1. The actor confirms the requested change. 2. The system validates the requested transition. 3. The system attempts to persist the change to the authoritative store. 4. The persistence operation fails or times out. 5. The system retains the last confirmed state and does not report success. 6. The system records the failure and displays a controlled retry message. 7. The actor retries after service recovery. EXCEPTION FLOW E-AUTH (<i>Authorization or Session Failure</i>) 1. The actor initiates the protected operation. 2. The system validates the current session and the required role or ownership permission immediately before the state-changing action. 3. The system detects an expired session or an absent permission. 4. The system blocks the state change and does not partially commit it. 5. The system records the denied attempt where security policy requires it. 6. The system redirects to authentication or displays access denied. 7. After authorization is restored, the actor may retry.
--	--