

# RPKI Engine

## 1.0

Generated by Doxygen 1.6.1

Tue Jan 12 02:46:40 2010

## Contents

1	RPKI Engine Reference Manual	1
2	Further Reading	1
3	Installation Guide	2
4	Operation Guide	5
4.1	rpkid.py . . . . .	6
4.2	pubd.py . . . . .	7
4.3	rootd.py . . . . .	8
4.4	irdbd.py . . . . .	10
4.5	irbe_cli.py . . . . .	11
4.6	cross_certify.py . . . . .	13
4.7	irbe-setup.py con g le. . . . .	13
4.8	cronjob.py . . . . .	14
4.9	testbed.py: . . . . .	15
4.10	testpoke.py . . . . .	17
5	Left-right protocol	18
5.1	Terminology. . . . .	18
5.2	initiated by the IRBE. . . . .	19
5.2.1	<self/> object . . . . .	19
5.2.2	<bsc/> object . . . . .	21
5.2.3	<parent/> object . . . . .	22
5.2.4	<child/> object . . . . .	23
5.2.5	<repository/> object . . . . .	24
5.2.6	<route_origin/> object. . . . .	25
5.3	Operations initiated by the RPKI engine. . . . .	26
5.3.1	<list_resources/ messages . . . . .	26
5.4	Error handling . . . . .	27
6	Publication protocol	28

6.1	Terminology . . . . .	28
6.2	Publication control subprotocol . . . . .	28
6.2.1	<con g/> object . . . . .	29
6.2.2	<client/> object . . . . .	29
6.3	Publication subprotocol . . . . .	30
6.3.1	<certi cate/> object . . . . .	30
6.3.2	<crl/> object . . . . .	30
6.3.3	<manifest/> object . . . . .	30
6.3.4	<roa/> object . . . . .	30
6.4	Error handling . . . . .	30
6.5	Additional access control considerations . . . . .	31
7	SQL database schemas . . . . .	32
7.1	rpkid SQL schema . . . . .	34
7.2	pubd SQL Schema . . . . .	38
7.3	irdbd SQL Schema . . . . .	40
8	BPKI model . . . . .	42
9	Namespace Documentation . . . . .	45
9.1	Package irbe_cli . . . . .	45
9.1.1	Detailed Description . . . . .	46
9.1.2	Function Documentation . . . . .	46
9.1.3	Variable Documentation . . . . .	47
9.2	Package irdbd . . . . .	49
9.2.1	Detailed Description . . . . .	49
9.2.2	Function Documentation . . . . .	50
9.2.3	Variable Documentation . . . . .	51
9.3	Package pubd . . . . .	53
9.3.1	Detailed Description . . . . .	53
9.3.2	Function Documentation . . . . .	54
9.3.3	Variable Documentation . . . . .	54

9.4	Package rootd . . . . .	55
9.4.1	Detailed Description . . . . .	56
9.4.2	Function Documentation . . . . .	57
9.4.3	Variable Documentation . . . . .	58
9.5	Package rpkg . . . . .	62
9.6	Package rpkg.async . . . . .	63
9.6.1	Detailed Description . . . . .	63
9.6.2	Function Documentation . . . . .	64
9.6.3	Variable Documentation . . . . .	65
9.7	Package rpkg.conf . . . . .	65
9.7.1	Detailed Description . . . . .	65
9.8	Package rpkg.exceptions . . . . .	66
9.8.1	Detailed Description . . . . .	67
9.9	Package rpkg.https . . . . .	68
9.9.1	Detailed Description . . . . .	69
9.9.2	Function Documentation . . . . .	69
9.9.3	Variable Documentation . . . . .	70
9.10	Package rpkg.ipaddr . . . . .	72
9.10.1	Detailed Description . . . . .	72
9.11	Package rpkg.left_right . . . . .	73
9.11.1	Detailed Description . . . . .	73
9.11.2	Variable Documentation . . . . .	74
9.12	Package rpkg.log . . . . .	74
9.12.1	Detailed Description . . . . .	75
9.12.2	Function Documentation . . . . .	75
9.12.3	Variable Documentation . . . . .	76
9.13	Package rpkg.manifest . . . . .	77
9.13.1	Detailed Description . . . . .	77
9.14	Package rpkg.oids . . . . .	78
9.14.1	Detailed Description . . . . .	78
9.14.2	Variable Documentation . . . . .	79

9.15 Package rpkgi.publication . . . . .	80
9.15.1 Detailed Description . . . . .	80
9.16 Package rpkgi.relaxng . . . . .	81
9.16.1 Variable Documentation . . . . .	81
9.17 Package rpkgi.resource_set . . . . .	81
9.17.1 Detailed Description . . . . .	82
9.17.2 Function Documentation . . . . .	83
9.17.3 Variable Documentation . . . . .	84
9.18 Package rpkgi.roa . . . . .	84
9.18.1 Detailed Description . . . . .	84
9.19 Package rpkgi.rpkgi_engine . . . . .	85
9.19.1 Detailed Description . . . . .	86
9.20 Package rpkgi.sql . . . . .	86
9.20.1 Detailed Description . . . . .	86
9.21 Package rpkgi.sundial . . . . .	87
9.21.1 Detailed Description . . . . .	87
9.21.2 Function Documentation . . . . .	88
9.22 Package rpkgi.up_down . . . . .	89
9.22.1 Detailed Description . . . . .	89
9.22.2 Variable Documentation . . . . .	90
9.23 Package rpkgi.x509 . . . . .	90
9.23.1 Detailed Description . . . . .	91
9.23.2 Function Documentation . . . . .	92
9.24 Package rpkgi.xml_utils . . . . .	92
9.24.1 Detailed Description . . . . .	92
9.25 Package rpkgid . . . . .	93
9.25.1 Detailed Description . . . . .	93
9.25.2 Function Documentation . . . . .	94
9.25.3 Variable Documentation . . . . .	94
10 Class Documentation . . . . .	95

10.1	<a href="#">async_chat Class Reference</a>	95
10.2	<a href="#">dispatcher Class Reference</a>	95
10.3	<a href="#">Exception Class Reference</a>	95
10.4	<a href="#">irbe_cli.bsc_elt Class Reference</a>	95
10.4.1	<a href="#">Detailed Description</a>	96
10.4.2	<a href="#">Member Function Documentation</a>	96
10.4.3	<a href="#">Member Data Documentation</a>	96
10.5	<a href="#">irbe_cli.caller Class Reference</a>	97
10.5.1	<a href="#">Detailed Description</a>	97
10.5.2	<a href="#">Member Function Documentation</a>	98
10.5.3	<a href="#">Member Data Documentation</a>	98
10.6	<a href="#">irbe_cli.certificate_elt Class Reference</a>	99
10.6.1	<a href="#">Detailed Description</a>	99
10.7	<a href="#">irbe_cli.child_elt Class Reference</a>	99
10.7.1	<a href="#">Detailed Description</a>	99
10.8	<a href="#">irbe_cli.client_elt Class Reference</a>	99
10.8.1	<a href="#">Detailed Description</a>	100
10.9	<a href="#">irbe_cli.cmd_elt_mixin Class Reference</a>	100
10.9.1	<a href="#">Detailed Description</a>	101
10.9.2	<a href="#">Member Function Documentation</a>	101
10.9.3	<a href="#">Member Data Documentation</a>	102
10.10	<a href="#">irbe_cli.cmd_msg_mixin Class Reference</a>	104
10.10.1	<a href="#">Detailed Description</a>	104
10.10.2	<a href="#">Member Function Documentation</a>	104
10.11	<a href="#">irbe_cli.config_elt Class Reference</a>	104
10.11.1	<a href="#">Detailed Description</a>	105
10.11.2	<a href="#">Member Function Documentation</a>	105
10.11.3	<a href="#">Member Data Documentation</a>	105
10.12	<a href="#">irbe_cli.crl_elt Class Reference</a>	105
10.12.1	<a href="#">Detailed Description</a>	105
10.13	<a href="#">irbe_cli.left_right_cmds_msg Class Reference</a>	105

10.13.1 Detailed Description . . . . .	106
10.13.2 Member Data Documentation . . . . .	106
10.14irbe_cli.left_right_msg Class Reference. . . . .	106
10.14.1 Detailed Description . . . . .	106
10.14.2 Member Data Documentation . . . . .	106
10.15irbe_cli.left_right_sax_handler Class Reference. . . . .	107
10.15.1 Detailed Description . . . . .	107
10.15.2 Member Data Documentation . . . . .	107
10.16irbe_cli.list_published_objects_elt Class Reference. . . . .	107
10.16.1 Detailed Description . . . . .	108
10.16.2 Member Data Documentation . . . . .	108
10.17irbe_cli.manifest_elt Class Reference. . . . .	108
10.17.1 Detailed Description . . . . .	108
10.18irbe_cli.parent_elt Class Reference . . . . .	108
10.18.1 Detailed Description . . . . .	109
10.19irbe_cli.publication_cms_msg Class Reference . . . . .	109
10.19.1 Detailed Description . . . . .	109
10.19.2 Member Data Documentation . . . . .	109
10.20irbe_cli.publication_msg Class Reference . . . . .	109
10.20.1 Detailed Description . . . . .	110
10.20.2 Member Data Documentation . . . . .	110
10.21irbe_cli.publication_sax_handler Class Reference. . . . .	110
10.21.1 Detailed Description . . . . .	110
10.21.2 Member Data Documentation . . . . .	110
10.22irbe_cli.reply_elt_mixin Class Reference . . . . .	111
10.22.1 Detailed Description . . . . .	111
10.22.2 Member Function Documentation. . . . .	111
10.22.3 Member Data Documentation . . . . .	112
10.23irbe_cli.report_error_elt Class Reference. . . . .	112
10.23.1 Detailed Description . . . . .	112
10.24irbe_cli.repository_elt Class Reference . . . . .	112

10.24.1 Detailed Description . . . . .	112
10.25irbe_cli.roa_elt Class Reference . . . . .	112
10.25.1 Detailed Description . . . . .	113
10.26irbe_cli.self_elt Class Reference . . . . .	113
10.26.1 Detailed Description . . . . .	113
10.27irbe_cli.UsageWrapper Class Reference . . . . .	113
10.27.1 Detailed Description . . . . .	113
10.27.2 Member Function Documentation. . . . .	113
10.28long Class Reference . . . . .	114
10.29object Class Reference . . . . .	114
10.30pubd.pubd_context Class Reference . . . . .	114
10.30.1 Detailed Description . . . . .	115
10.30.2 Member Function Documentation. . . . .	115
10.30.3 Member Data Documentation . . . . .	116
10.31datetime Class Reference . . . . .	118
10.32timedelta Class Reference . . . . .	118
10.33rootd.cms_msg Class Reference . . . . .	118
10.33.1 Detailed Description . . . . .	118
10.33.2 Member Data Documentation . . . . .	119
10.34rootd.issue_pdu Class Reference . . . . .	119
10.34.1 Detailed Description . . . . .	119
10.34.2 Member Function Documentation. . . . .	119
10.35rootd.list_pdu Class Reference . . . . .	119
10.35.1 Detailed Description . . . . .	120
10.35.2 Member Function Documentation. . . . .	120
10.36rootd.message_pdu Class Reference. . . . .	120
10.36.1 Detailed Description . . . . .	120
10.36.2 Member Function Documentation. . . . .	121
10.36.3 Member Data Documentation . . . . .	121
10.37rootd.revoke_pdu Class Reference . . . . .	121
10.37.1 Detailed Description . . . . .	122



10.37.2 Member Function Documentation . . . . .	122
10.38rootd.sax_handler Class Reference . . . . .	122
10.38.1 Detailed Description . . . . .	122
10.38.2 Member Data Documentation . . . . .	122
10.39rpki.async.gc_summary Class Reference . . . . .	123
10.39.1 Detailed Description . . . . .	123
10.39.2 Member Function Documentation. . . . .	123
10.39.3 Member Data Documentation . . . . .	124
10.40rpki.async.iterator Class Reference . . . . .	124
10.40.1 Detailed Description . . . . .	124
10.40.2 Member Function Documentation. . . . .	125
10.40.3 Member Data Documentation . . . . .	126
10.41rpki.async.sync_wrapper Class Reference . . . . .	126
10.41.1 Detailed Description . . . . .	127
10.41.2 Member Function Documentation. . . . .	127
10.41.3 Member Data Documentation . . . . .	128
10.42rpki.async.timer Class Reference . . . . .	128
10.42.1 Detailed Description . . . . .	129
10.42.2 Member Function Documentation. . . . .	130
10.42.3 Member Data Documentation . . . . .	132
10.43rpki.con g.parser Class Reference. . . . .	133
10.43.1 Detailed Description . . . . .	134
10.43.2 Member Function Documentation. . . . .	134
10.43.3 Member Data Documentation . . . . .	136
10.44rpki.exceptions.BadClassNameSyntax Class Reference . . . . .	137
10.44.1 Detailed Description . . . . .	137
10.45rpki.exceptions.BadClientURL Class Reference . . . . .	137
10.45.1 Detailed Description . . . . .	137
10.46rpki.exceptions.BadContactURL Class Reference. . . . .	137
10.46.1 Detailed Description . . . . .	138
10.47rpki.exceptions.BadExtension Class Reference . . . . .	138

10.47.1 Detailed Description . . . . .	138
10.48rpki.exceptions.BadIRDBReply Class Reference . . . . .	138
10.48.1 Detailed Description . . . . .	138
10.49rpki.exceptions.BadIssueResponse Class Reference. . . . .	138
10.49.1 Detailed Description . . . . .	139
10.50rpki.exceptions.BadPKCS10 Class Reference. . . . .	139
10.50.1 Detailed Description . . . . .	139
10.51rpki.exceptions.BadPublicationReply Class Reference . . . . .	139
10.51.1 Detailed Description . . . . .	139
10.52rpki.exceptions.BadQuery Class Reference . . . . .	139
10.52.1 Detailed Description . . . . .	140
10.53rpki.exceptions.BadSender Class Reference. . . . .	140
10.53.1 Detailed Description . . . . .	140
10.54rpki.exceptions.BadStatusCode Class Reference . . . . .	140
10.54.1 Detailed Description . . . . .	140
10.55rpki.exceptions.BadURISyntax Class Reference. . . . .	140
10.55.1 Detailed Description . . . . .	141
10.56rpki.exceptions.BSCNotFound Class Reference. . . . .	141
10.56.1 Detailed Description . . . . .	141
10.57rpki.exceptions.BSCNotReady Class Reference. . . . .	141
10.57.1 Detailed Description . . . . .	141
10.58rpki.exceptions.ChildNotFound Class Reference . . . . .	141
10.58.1 Detailed Description . . . . .	142
10.59rpki.exceptions.ClassNameMismatch Class Reference. . . . .	142
10.59.1 Detailed Description . . . . .	142
10.60rpki.exceptions.ClassNameUnknown Class Reference . . . . .	142
10.60.1 Detailed Description . . . . .	142
10.61rpki.exceptions.ClientNotFound Class Reference . . . . .	142
10.61.1 Detailed Description . . . . .	143
10.62rpki.exceptions.CMSContentNotSet Class Reference. . . . .	143
10.62.1 Detailed Description . . . . .	143

10.63rpki.exceptions.CMSCRLNotSet Class Reference . . . . .	143
10.63.1 Detailed Description . . . . .	143
10.64rpki.exceptions.CMSVerificationFailed Class Reference . . . . .	143
10.64.1 Detailed Description . . . . .	144
10.65rpki.exceptions.DBConsistencyError Class Reference . . . . .	144
10.65.1 Detailed Description . . . . .	144
10.66rpki.exceptions.DERObjectConversionError Class Reference . . . . .	144
10.66.1 Detailed Description . . . . .	144
10.67rpki.exceptions.DuplicateObject Class Reference . . . . .	144
10.67.1 Detailed Description . . . . .	145
10.68rpki.exceptions.EmptyPEM Class Reference . . . . .	145
10.68.1 Detailed Description . . . . .	145
10.69rpki.exceptions.EmptyROAPre xList Class Reference . . . . .	145
10.69.1 Detailed Description . . . . .	145
10.70rpki.exceptions.ForbiddenURI Class Reference . . . . .	145
10.70.1 Detailed Description . . . . .	146
10.71rpki.exceptions.HandleTranslationError Class Reference . . . . .	146
10.71.1 Detailed Description . . . . .	146
10.72rpki.exceptions.HTTPRequestFailed Class Reference . . . . .	146
10.72.1 Detailed Description . . . . .	146
10.73rpki.exceptions.HTTPSBadVersion Class Reference . . . . .	146
10.73.1 Detailed Description . . . . .	147
10.74rpki.exceptions.HTTPSCientAborted Class Reference . . . . .	147
10.74.1 Detailed Description . . . . .	147
10.75rpki.exceptions.HTTPSUnexpectedState Class Reference . . . . .	147
10.75.1 Detailed Description . . . . .	147
10.76rpki.exceptions.MissingCMSCRL Class Reference . . . . .	147
10.76.1 Detailed Description . . . . .	148
10.77rpki.exceptions.MissingCMSEECert Class Reference . . . . .	148
10.77.1 Detailed Description . . . . .	148
10.78rpki.exceptions.MultipleTLSEECert Class Reference . . . . .	148

10.78.1 Detailed Description . . . . .	148
10.79rpki.exceptions.MustBePre x Class Reference. . . . .	148
10.79.1 Detailed Description . . . . .	149
10.80rpki.exceptions.NoActiveCA Class Reference . . . . .	149
10.80.1 Detailed Description . . . . .	149
10.81rpki.exceptions.NoCoveringCertForROA Class Reference . . . . .	149
10.81.1 Detailed Description . . . . .	149
10.82rpki.exceptions.NoObjectAtURI Class Reference . . . . .	149
10.82.1 Detailed Description . . . . .	150
10.83rpki.exceptions.NotACertificateChain Class Reference . . . . .	150
10.83.1 Detailed Description . . . . .	150
10.84rpki.exceptions.NotFound Class Reference . . . . .	150
10.84.1 Detailed Description . . . . .	150
10.85rpki.exceptions.NotImplementedYet Class Reference. . . . .	150
10.85.1 Detailed Description . . . . .	151
10.86rpki.exceptions.NotInDatabase Class Reference . . . . .	151
10.86.1 Detailed Description . . . . .	151
10.87rpki.exceptions.ReceivedTLSCACert Class Reference . . . . .	151
10.87.1 Detailed Description . . . . .	151
10.88rpki.exceptions.RPKI_Exception Class Reference. . . . .	151
10.88.1 Detailed Description . . . . .	152
10.89rpki.exceptions.ServerShuttingDown Class Reference . . . . .	152
10.89.1 Detailed Description . . . . .	152
10.90rpki.exceptions.SKIMismatch Class Reference . . . . .	153
10.90.1 Detailed Description . . . . .	153
10.91rpki.exceptions.SubprocessError Class Reference . . . . .	153
10.91.1 Detailed Description . . . . .	153
10.92rpki.exceptions.TLSValidationError Class Reference . . . . .	153
10.92.1 Detailed Description . . . . .	153
10.93rpki.exceptions.UnexpectedCMSCerts Class Reference . . . . .	154
10.93.1 Detailed Description . . . . .	154

10.94rpki.exceptions.UnexpectedCMSCRLs Class Reference . . . . .	154
10.94.1 Detailed Description . . . . .	154
10.95rpki.exceptions.UnparsableCMSDER Class Reference. . . . .	154
10.95.1 Detailed Description . . . . .	154
10.96rpki.exceptions.UpstreamError Class Reference. . . . .	155
10.96.1 Detailed Description . . . . .	155
10.97rpki.exceptions.WrongEContentType Class Reference . . . . .	155
10.97.1 Detailed Description . . . . .	155
10.98rpki.https.http_client Class Reference. . . . .	155
10.98.1 Detailed Description . . . . .	156
10.98.2 Member Function Documentation. . . . .	156
10.98.3 Member Data Documentation . . . . .	158
10.99rpki.https.http_listener Class Reference . . . . .	160
10.99.1 Detailed Description . . . . .	160
10.99.2 Member Function Documentation. . . . .	160
10.99.3 Member Data Documentation . . . . .	161
10.100rpki.https.http_message Class Reference . . . . .	162
10.100.1 Detailed Description . . . . .	162
10.100.2 Member Function Documentation. . . . .	163
10.100.3 Member Data Documentation . . . . .	164
10.101rpki.https.http_queue Class Reference . . . . .	164
10.101.1 Detailed Description . . . . .	165
10.101.2 Member Function Documentation. . . . .	165
10.101.3 Member Data Documentation . . . . .	166
10.102rpki.https.http_request Class Reference . . . . .	167
10.102.1 Detailed Description . . . . .	167
10.102.2 Member Function Documentation. . . . .	168
10.102.3 Member Data Documentation . . . . .	168
10.103rpki.https.http_response Class Reference . . . . .	169
10.103.1 Detailed Description . . . . .	169
10.103.2 Member Function Documentation. . . . .	169

10.103.3Member Data Documentation . . . . .	170
10.104pk.https.http_server Class Reference . . . . .	170
10.104.1Detailed Description . . . . .	171
10.104.2Member Function Documentation. . . . .	171
10.104.3Member Data Documentation . . . . .	172
10.105pk.https.http_stream Class Reference. . . . .	173
10.105.1Detailed Description . . . . .	174
10.105.2Member Function Documentation. . . . .	175
10.105.3Member Data Documentation . . . . .	178
10.106pk.ipaddrs.v4addr Class Reference . . . . .	179
10.106.1Detailed Description . . . . .	179
10.106.2Member Function Documentation. . . . .	180
10.106.3Member Data Documentation . . . . .	180
10.107pk.ipaddrs.v6addr Class Reference . . . . .	181
10.107.1Detailed Description . . . . .	181
10.107.2Member Function Documentation. . . . .	181
10.107.3Member Data Documentation . . . . .	182
10.108pk.left_right.bsc_elt Class Reference . . . . .	182
10.108.1Detailed Description . . . . .	183
10.108.2Member Function Documentation. . . . .	183
10.108.3Member Data Documentation . . . . .	184
10.109pk.left_right.child_elt Class Reference. . . . .	186
10.109.1Detailed Description . . . . .	187
10.109.2Member Function Documentation. . . . .	187
10.109.3Member Data Documentation . . . . .	188
10.110pk.left_right.cms_msg Class Reference. . . . .	190
10.110.1Detailed Description . . . . .	190
10.110.2Member Data Documentation . . . . .	191
10.111pk.left_right.data_elt Class Reference. . . . .	191
10.111.1Detailed Description . . . . .	192
10.111.2Member Function Documentation. . . . .	192

10.111.3	Member Data Documentation . . . . .	194
10.112	pkc.left_right.left_right_namespace Class Reference . . . . .	194
10.112.1	Detailed Description . . . . .	194
10.112.2	Member Data Documentation . . . . .	195
10.113	pkc.left_right.list_published_objects_elt Class Reference . . . . .	195
10.113.1	Detailed Description . . . . .	196
10.113.2	Member Function Documentation . . . . .	196
10.113.3	Member Data Documentation . . . . .	196
10.114	pkc.left_right.list_resources_elt Class Reference . . . . .	197
10.114.1	Detailed Description . . . . .	198
10.114.2	Member Function Documentation . . . . .	198
10.114.3	Member Data Documentation . . . . .	198
10.115	pkc.left_right.list_roa_requests_elt Class Reference . . . . .	199
10.115.1	Detailed Description . . . . .	200
10.115.2	Member Function Documentation . . . . .	200
10.115.3	Member Data Documentation . . . . .	200
10.116	pkc.left_right.msg Class Reference . . . . .	201
10.116.1	Detailed Description . . . . .	202
10.116.2	Member Function Documentation . . . . .	202
10.116.3	Member Data Documentation . . . . .	202
10.117	pkc.left_right.parent_elt Class Reference . . . . .	203
10.117.1	Detailed Description . . . . .	203
10.117.2	Member Function Documentation . . . . .	204
10.117.3	Member Data Documentation . . . . .	205
10.118	pkc.left_right.report_error_elt Class Reference . . . . .	207
10.118.1	Detailed Description . . . . .	208
10.118.2	Member Function Documentation . . . . .	208
10.118.3	Member Data Documentation . . . . .	208
10.119	pkc.left_right.repository_elt Class Reference . . . . .	209
10.119.1	Detailed Description . . . . .	210
10.119.2	Member Function Documentation . . . . .	210

10.119.3	Member Data Documentation . . . . .	211	
10.120	10.120.1	10.120.2	10.120.3
10.120	10.120.1	10.120.2	10.120.3
10.120	10.120.1	10.120.2	10.120.3
10.121	10.121.1	10.121.2	10.121.3
10.121	10.121.1	10.121.2	10.121.3
10.121	10.121.1	10.121.2	10.121.3
10.122	10.122.1	10.122.2	10.122.3
10.122	10.122.1	10.122.2	10.122.3
10.122	10.122.1	10.122.2	10.122.3
10.123	10.123.1	10.123.2	10.123.3
10.123	10.123.1	10.123.2	10.123.3
10.123	10.123.1	10.123.2	10.123.3
10.124	10.124.1	10.124.2	10.124.3
10.124	10.124.1	10.124.2	10.124.3
10.124	10.124.1	10.124.2	10.124.3
10.125	10.125.1	10.125.2	10.125.3
10.125	10.125.1	10.125.2	10.125.3
10.125	10.125.1	10.125.2	10.125.3
10.126	10.126.1	10.126.2	10.126.3
10.126	10.126.1	10.126.2	10.126.3
10.126	10.126.1	10.126.2	10.126.3
10.127	10.127.1	10.127.2	10.127.3
10.127	10.127.1	10.127.2	10.127.3
10.127	10.127.1	10.127.2	10.127.3
10.128	10.128.1	10.128.2	10.128.3
10.128	10.128.1	10.128.2	10.128.3
10.128	10.128.1	10.128.2	10.128.3



10.128.1	Detailed Description . . . . .	230
10.128.2	Member Data Documentation . . . . .	230
10.129	pkcpublication.cong_elt Class Reference . . . . .	231
10.129.1	Detailed Description . . . . .	231
10.129.2	Member Function Documentation . . . . .	232
10.129.3	Member Data Documentation . . . . .	233
10.130	pkcpublication.control_elt Class Reference . . . . .	234
10.130.1	Detailed Description . . . . .	234
10.130.2	Member Function Documentation . . . . .	234
10.131	pkcpublication.crl_elt Class Reference . . . . .	235
10.131.1	Detailed Description . . . . .	235
10.131.2	Member Data Documentation . . . . .	235
10.132	pkcpublication.manifest_elt Class Reference . . . . .	235
10.132.1	Detailed Description . . . . .	236
10.132.2	Member Data Documentation . . . . .	236
10.133	pkcpublication.msg Class Reference . . . . .	236
10.133.1	Detailed Description . . . . .	237
10.133.2	Member Function Documentation . . . . .	237
10.133.3	Member Data Documentation . . . . .	237
10.134	pkcpublication.publication_namespace Class Reference . . . . .	238
10.134.1	Detailed Description . . . . .	238
10.134.2	Member Data Documentation . . . . .	238
10.135	pkcpublication.publication_object_elt Class Reference . . . . .	239
10.135.1	Detailed Description . . . . .	239
10.135.2	Member Function Documentation . . . . .	240
10.135.3	Member Data Documentation . . . . .	241
10.136	pkcpublication.report_error_elt Class Reference . . . . .	242
10.136.1	Detailed Description . . . . .	243
10.136.2	Member Function Documentation . . . . .	243
10.136.3	Member Data Documentation . . . . .	243
10.137	pkcpublication.roa_elt Class Reference . . . . .	245

10.137.1	Detailed Description . . . . .	245
10.137.2	Member Data Documentation . . . . .	245
10.138	rpki.publication.sax_handler Class Reference . . . . .	245
10.138.1	Detailed Description . . . . .	246
10.138.2	Member Data Documentation . . . . .	246
10.139	rpki.resource_set.resource_bag Class Reference . . . . .	246
10.139.1	Detailed Description . . . . .	247
10.139.2	Member Function Documentation . . . . .	247
10.139.3	Member Data Documentation . . . . .	249
10.140	rpki.resource_set.resource_range Class Reference . . . . .	250
10.140.1	Detailed Description . . . . .	250
10.140.2	Member Function Documentation . . . . .	251
10.140.3	Member Data Documentation . . . . .	251
10.141	rpki.resource_set.resource_range_as Class Reference . . . . .	251
10.141.1	Detailed Description . . . . .	252
10.141.2	Member Function Documentation . . . . .	252
10.141.3	Member Data Documentation . . . . .	252
10.142	rpki.resource_set.resource_range_ip Class Reference . . . . .	253
10.142.1	Detailed Description . . . . .	253
10.142.2	Member Function Documentation . . . . .	254
10.143	rpki.resource_set.resource_range_ipv4 Class Reference . . . . .	254
10.143.1	Detailed Description . . . . .	255
10.143.2	Member Data Documentation . . . . .	255
10.144	rpki.resource_set.resource_range_ipv6 Class Reference . . . . .	255
10.144.1	Detailed Description . . . . .	255
10.144.2	Member Data Documentation . . . . .	256
10.145	rpki.resource_set.resource_set Class Reference . . . . .	256
10.145.1	Detailed Description . . . . .	257
10.145.2	Member Function Documentation . . . . .	257
10.145.3	Member Data Documentation . . . . .	259
10.146	rpki.resource_set.resource_set_as Class Reference . . . . .	259

10.146.1	Detailed Description . . . . .	260
10.146.2	Member Function Documentation. . . . .	260
10.146.3	Member Data Documentation. . . . .	261
10.147	pk resource_set.resource_set_ip Class Reference . . . . .	261
10.147.1	Detailed Description . . . . .	262
10.147.2	Member Function Documentation. . . . .	262
10.147.3	Member Data Documentation. . . . .	262
10.148	pk resource_set.resource_set_ipv4 Class Reference . . . . .	263
10.148.1	Detailed Description . . . . .	263
10.148.2	Member Data Documentation. . . . .	263
10.149	pk resource_set.resource_set_ipv6 Class Reference . . . . .	264
10.149.1	Detailed Description . . . . .	264
10.149.2	Member Data Documentation. . . . .	264
10.150	pk resource_set.roa_pre x Class Reference . . . . .	265
10.150.1	Detailed Description . . . . .	265
10.150.2	Member Function Documentation. . . . .	265
10.150.3	Member Data Documentation. . . . .	267
10.151	pk resource_set.roa_pre x_ipv4 Class Reference . . . . .	267
10.151.1	Detailed Description . . . . .	268
10.151.2	Member Data Documentation. . . . .	268
10.152	pk resource_set.roa_pre x_ipv6 Class Reference . . . . .	268
10.152.1	Detailed Description . . . . .	268
10.152.2	Member Data Documentation. . . . .	269
10.153	pk resource_set.roa_pre x_set Class Reference. . . . .	269
10.153.1	Detailed Description . . . . .	269
10.153.2	Member Function Documentation. . . . .	269
10.154	pk resource_set.roa_pre x_set_ipv4 Class Reference. . . . .	271
10.154.1	Detailed Description . . . . .	271
10.154.2	Member Data Documentation. . . . .	271
10.155	pk resource_set.roa_pre x_set_ipv6 Class Reference. . . . .	272
10.155.1	Detailed Description . . . . .	272

10.155.2Member Data Documentation . . . . .	272
10.156rpki.roa.ROAIPAddress Class Reference . . . . .	273
10.156.1Detailed Description . . . . .	273
10.156.2Member Function Documentation. . . . .	273
10.156.3Member Data Documentation . . . . .	273
10.157rpki.roa.ROAIPAddresses Class Reference . . . . .	274
10.157.1Detailed Description . . . . .	274
10.157.2Member Function Documentation. . . . .	274
10.158rpki.roa.ROAIPAddressFamilies Class Reference . . . . .	274
10.158.1Detailed Description . . . . .	275
10.158.2Member Function Documentation. . . . .	275
10.159rpki.roa.ROAIPAddressFamily Class Reference . . . . .	275
10.159.1Detailed Description . . . . .	275
10.159.2Member Function Documentation. . . . .	275
10.159.3Member Data Documentation . . . . .	276
10.160rpki.roa.RouteOriginAttestation Class Reference . . . . .	276
10.160.1Detailed Description . . . . .	276
10.160.2Member Function Documentation. . . . .	276
10.160.3Member Data Documentation . . . . .	277
10.161rpki.rpki_engine.ca_detail_obj Class Reference . . . . .	277
10.161.1Detailed Description . . . . .	278
10.161.2Member Function Documentation. . . . .	279
10.161.3Member Data Documentation . . . . .	283
10.162rpki.rpki_engine.ca_obj Class Reference . . . . .	285
10.162.1Detailed Description . . . . .	286
10.162.2Member Function Documentation. . . . .	287
10.162.3Member Data Documentation . . . . .	290
10.163rpki.rpki_engine.child_cert_obj Class Reference . . . . .	291
10.163.1Detailed Description . . . . .	292
10.163.2Member Function Documentation. . . . .	292
10.163.3Member Data Documentation . . . . .	294

10.164	<a href="#">rpk_i.rpki_engine.publication_queue Class Reference</a> . . . . .	295
10.164.1	<a href="#">Detailed Description</a> . . . . .	296
10.164.2	<a href="#">Member Function Documentation</a> . . . . .	296
10.164.3	<a href="#">Member Data Documentation</a> . . . . .	297
10.165	<a href="#">rpk_i.rpki_engine.revoked_cert_obj Class Reference</a> . . . . .	298
10.165.1	<a href="#">Detailed Description</a> . . . . .	298
10.165.2	<a href="#">Member Function Documentation</a> . . . . .	298
10.165.3	<a href="#">Member Data Documentation</a> . . . . .	299
10.166	<a href="#">rpk_i.rpki_engine.roa_obj Class Reference</a> . . . . .	300
10.166.1	<a href="#">Detailed Description</a> . . . . .	301
10.166.2	<a href="#">Member Function Documentation</a> . . . . .	301
10.166.3	<a href="#">Member Data Documentation</a> . . . . .	304
10.167	<a href="#">rpk_i.rpki_engine.rpkid_context Class Reference</a> . . . . .	306
10.167.1	<a href="#">Detailed Description</a> . . . . .	307
10.167.2	<a href="#">Member Function Documentation</a> . . . . .	307
10.167.3	<a href="#">Member Data Documentation</a> . . . . .	309
10.168	<a href="#">rpk_i.sql.session Class Reference</a> . . . . .	312
10.168.1	<a href="#">Detailed Description</a> . . . . .	313
10.168.2	<a href="#">Member Function Documentation</a> . . . . .	313
10.168.3	<a href="#">Member Data Documentation</a> . . . . .	315
10.169	<a href="#">rpk_i.sql.sql_persistent Class Reference</a> . . . . .	316
10.169.1	<a href="#">Detailed Description</a> . . . . .	317
10.169.2	<a href="#">Member Function Documentation</a> . . . . .	317
10.169.3	<a href="#">Member Data Documentation</a> . . . . .	321
10.170	<a href="#">rpk_i.sql.template Class Reference</a> . . . . .	322
10.170.1	<a href="#">Detailed Description</a> . . . . .	322
10.170.2	<a href="#">Member Function Documentation</a> . . . . .	323
10.170.3	<a href="#">Member Data Documentation</a> . . . . .	323
10.171	<a href="#">rpk_i.sundial.datetime Class Reference</a> . . . . .	324
10.171.1	<a href="#">Detailed Description</a> . . . . .	325
10.171.2	<a href="#">Member Function Documentation</a> . . . . .	325

10.171.3Member Data Documentation . . . . .	328
10.172pkisundial.timedelta Class Reference . . . . .	329
10.172.1Detailed Description . . . . .	329
10.172.2Member Function Documentation. . . . .	330
10.172.3Member Data Documentation. . . . .	332
10.173pkisup_down.base_elt Class Reference . . . . .	332
10.173.1Detailed Description . . . . .	333
10.173.2Member Function Documentation. . . . .	333
10.174pkisup_down.certicate_elt Class Reference. . . . .	335
10.174.1Detailed Description . . . . .	335
10.174.2Member Function Documentation. . . . .	335
10.174.3Member Data Documentation . . . . .	336
10.175pkisup_down.class_elt Class Reference . . . . .	337
10.175.1Detailed Description . . . . .	337
10.175.2Member Function Documentation. . . . .	338
10.175.3Member Data Documentation . . . . .	339
10.176pkisup_down.class_response_syntax Class Reference . . . . .	340
10.176.1Detailed Description . . . . .	340
10.176.2Member Function Documentation. . . . .	341
10.176.3Member Data Documentation . . . . .	341
10.177pkisup_down.cms_msg Class Reference . . . . .	341
10.177.1Detailed Description . . . . .	342
10.177.2Member Data Documentation . . . . .	342
10.178pkisup_down.error_response_pdu Class Reference . . . . .	342
10.178.1Detailed Description . . . . .	343
10.178.2Member Function Documentation. . . . .	343
10.178.3Member Data Documentation . . . . .	344
10.179pkisup_down.issue_pdu Class Reference . . . . .	345
10.179.1Detailed Description . . . . .	345
10.179.2Member Function Documentation. . . . .	346
10.179.3Member Data Documentation . . . . .	347

10.180	<a href="#">pki.up_down.issue_response_pdu Class Reference</a> . . . . .	348
10.180.1	<a href="#">Detailed Description</a> . . . . .	348
10.180.2	<a href="#">Member Function Documentation</a> . . . . .	348
10.181	<a href="#">pki.up_down.list_pdu Class Reference</a> . . . . .	348
10.181.1	<a href="#">Detailed Description</a> . . . . .	349
10.181.2	<a href="#">Member Function Documentation</a> . . . . .	349
10.182	<a href="#">pki.up_down.list_response_pdu Class Reference</a> . . . . .	349
10.182.1	<a href="#">Detailed Description</a> . . . . .	350
10.183	<a href="#">pki.up_down.message_pdu Class Reference</a> . . . . .	350
10.183.1	<a href="#">Detailed Description</a> . . . . .	351
10.183.2	<a href="#">Member Function Documentation</a> . . . . .	351
10.183.3	<a href="#">Member Data Documentation</a> . . . . .	352
10.184	<a href="#">pki.up_down.multi_uri Class Reference</a> . . . . .	354
10.184.1	<a href="#">Detailed Description</a> . . . . .	354
10.184.2	<a href="#">Member Function Documentation</a> . . . . .	354
10.185	<a href="#">pki.up_down.revoke_pdu Class Reference</a> . . . . .	355
10.185.1	<a href="#">Detailed Description</a> . . . . .	355
10.185.2	<a href="#">Member Function Documentation</a> . . . . .	355
10.185.3	<a href="#">Member Data Documentation</a> . . . . .	356
10.186	<a href="#">pki.up_down.revoke_response_pdu Class Reference</a> . . . . .	356
10.186.1	<a href="#">Detailed Description</a> . . . . .	357
10.187	<a href="#">pki.up_down.revoke_syntax Class Reference</a> . . . . .	357
10.187.1	<a href="#">Detailed Description</a> . . . . .	357
10.187.2	<a href="#">Member Function Documentation</a> . . . . .	357
10.187.3	<a href="#">Member Data Documentation</a> . . . . .	358
10.188	<a href="#">pki.up_down.sax_handler Class Reference</a> . . . . .	358
10.188.1	<a href="#">Detailed Description</a> . . . . .	358
10.188.2	<a href="#">Member Data Documentation</a> . . . . .	359
10.189	<a href="#">pki.x509.CMS_object Class Reference</a> . . . . .	359
10.189.1	<a href="#">Detailed Description</a> . . . . .	360
10.189.2	<a href="#">Member Function Documentation</a> . . . . .	361

10.189.3	Member Data Documentation . . . . .	362
10.190	pkix509.CRL Class Reference . . . . .	364
10.190.1	Detailed Description . . . . .	365
10.190.2	Member Function Documentation. . . . .	365
10.190.3	Member Data Documentation . . . . .	367
10.191	pkix509.DeadDrop Class Reference. . . . .	368
10.191.1	Detailed Description . . . . .	368
10.191.2	Member Function Documentation. . . . .	368
10.191.3	Member Data Documentation . . . . .	369
10.192	pkix509.DER_CMS_object Class Reference . . . . .	369
10.192.1	Detailed Description . . . . .	369
10.192.2	Member Function Documentation. . . . .	370
10.192.3	Member Data Documentation . . . . .	370
10.193	pkix509.DER_object Class Reference. . . . .	370
10.193.1	Detailed Description . . . . .	371
10.193.2	Member Function Documentation. . . . .	372
10.193.3	Member Data Documentation . . . . .	376
10.194	pkix509.PEM_converter Class Reference. . . . .	377
10.194.1	Detailed Description . . . . .	377
10.194.2	Member Function Documentation. . . . .	378
10.194.3	Member Data Documentation . . . . .	378
10.195	pkix509.PKCS10 Class Reference. . . . .	379
10.195.1	Detailed Description . . . . .	379
10.195.2	Member Function Documentation. . . . .	380
10.195.3	Member Data Documentation . . . . .	381
10.196	pkix509.ROA Class Reference . . . . .	382
10.196.1	Detailed Description . . . . .	382
10.196.2	Member Function Documentation. . . . .	382
10.196.3	Member Data Documentation . . . . .	382
10.197	pkix509.RSA Class Reference . . . . .	383
10.197.1	Detailed Description . . . . .	384



10.197.2	Member Function Documentation	384
10.197.3	Member Data Documentation	385
10.198	pkix509.RSAPublic Class Reference	386
10.198.1	Detailed Description	387
10.198.2	Member Function Documentation	387
10.198.3	Member Data Documentation	387
10.199	pkix509.SignedManifest Class Reference	388
10.199.1	Detailed Description	389
10.199.2	Member Function Documentation	389
10.199.3	Member Data Documentation	390
10.200	pkix509.X509 Class Reference	390
10.200.1	Detailed Description	391
10.200.2	Member Function Documentation	391
10.200.3	Member Data Documentation	394
10.201	pkix509.XML_CMS_object Class Reference	395
10.201.1	Detailed Description	396
10.201.2	Member Function Documentation	396
10.201.3	Member Data Documentation	397
10.202	pkixml_utils.base_elt Class Reference	398
10.202.1	Detailed Description	399
10.202.2	Member Function Documentation	399
10.202.3	Member Data Documentation	401
10.203	pkixml_utils.data_elt Class Reference	402
10.203.1	Detailed Description	402
10.203.2	Member Function Documentation	403
10.204	pkixml_utils.msg Class Reference	406
10.204.1	Detailed Description	406
10.204.2	Member Function Documentation	407
10.204.3	Member Data Documentation	408
10.205	pkixml_utils.sax_handler Class Reference	409
10.205.1	Detailed Description	409

10.205.2	Member Function Documentation . . . . .	409
10.205.3	Member Data Documentation . . . . .	411
10.206	rpki.xml_utils.text_elt Class Reference . . . . .	412
10.206.1	Detailed Description . . . . .	412
10.206.2	Member Function Documentation . . . . .	412
10.206.3	Member Data Documentation . . . . .	413
10.207	Sequence Class Reference . . . . .	413
10.208	SequenceOf Class Reference . . . . .	413
10.209	TextWrapper Class Reference . . . . .	413
10.210	ContentHandler Class Reference . . . . .	414
11	File Documentation . . . . .	414
11.1	__init__.py File Reference . . . . .	414
11.2	async.py File Reference . . . . .	414
11.3	con g.py File Reference . . . . .	415
11.4	exceptions.py File Reference . . . . .	415
11.5	https.py File Reference . . . . .	416
11.6	ipaddrs.py File Reference . . . . .	417
11.7	irbe_cli.py File Reference . . . . .	418
11.8	irdbd.py File Reference . . . . .	419
11.9	left_right.py File Reference . . . . .	420
11.10	log.py File Reference . . . . .	420
11.11	manifest.py File Reference . . . . .	421
11.12	oids.py File Reference . . . . .	421
11.13	pubd.py File Reference . . . . .	422
11.14	publication.py File Reference . . . . .	422
11.15	relaxng.py File Reference . . . . .	423
11.16	resource_set.py File Reference . . . . .	423
11.17	roa.py File Reference . . . . .	424
11.18	rootd.py File Reference . . . . .	425
11.19	rpki_engine.py File Reference . . . . .	426

<a href="#">11.20rpkid.py File Reference</a> . . . . .	427
<a href="#">11.21sql.py File Reference</a> . . . . .	427
<a href="#">11.22sundial.py File Reference</a> . . . . .	427
<a href="#">11.23up_down.py File Reference</a> . . . . .	428
<a href="#">11.24x509.py File Reference</a> . . . . .	428
<a href="#">11.25xml_utils.py File Reference</a> . . . . .	429

## 1 RPKI Engine Reference Manual

This collection of Python modules implements a prototype of the RPKI Engine. This is a work in progress.

See <http://viewvc.hactrn.net/subvert-rpki.hactrn.net/> for code, design documents, a text mirror of portions of APNIC's Wiki, etc.

The RPKI Engine is an implementation of the production-side tools for generating certificates, CRLs, and ROAs. The [relying party tools](#) are a separate (and much simpler) package.

The Subversion repository for the entire project is available for (read-only) anonymous access at <http://subvert-rpki.hactrn.net/>.

The documentation you're reading is generated automatically by Doxygen from comments and documentation [in the code](#) .

Besides the automatically-generated code documentation, this manual also includes documentation of the overall package:

- The [installation instructions](#)
- The [operation instructions](#)
- A description of the [left-right protocol](#)
- A description of the [publication protocol](#)
- A description of the [RPKI model](#) used to secure the up-down, left-right, and publication protocols
- A description of the several [SQL database schemas](#)
- Some suggestions for [further reading](#)

This work was funded from 2006 through 2008 [by ARIN](#), in collaboration with the other Regional Internet Registries. Current work is funded by DHS.

## 2 Further Reading

If you're interested in this package you might also be interested in:

- [The rcynic validation tool](#)
- [A live sample of rcynic's summary output](#)
- [APNIC's Wiki](#)
- [APNIC's project Trac instance](#)

## 3 Installation Guide

Preliminary installation instructions for [rpki](#) et al.

These are the production-side RPKI tools, for Internet Registries (RIRs, LIRs, etc). See the "rcynic" program for relying party tools.

[rpki](#) is a set of Python modules supporting generation and maintenance of resource certificates. Most of the code is in the `rpki/rpki/` directory. [rpki](#) itself is a relatively small program that calls the library modules. There are several other programs that make use of the same libraries, as well as a collection of test programs.

At present the package is intended to be run out of its build directory. Setting up proper installation in a system area using the Python distutils package would likely not be very hard but has not yet been done.

Note that initial development of this code has been on FreeBSD, so installation will probably be easiest on FreeBSD.

Before attempting to build the package, you need to install any missing prerequisites. Note that the Python code requires Python version 2.5. [rpki](#) et al are mostly self-contained, but do require a small number of external packages to run.

- If your Python installation does not already include the sources files needed to compile new Python extension modules, you will need to install whatever package does include those source files. The need for and name of this package varies from system to system. On FreeBSD, the base Python interpreter package includes the development sources; on at least some Linux distributions, you have to install a separate "python-devel" package or something similar. If you get compilation errors trying to build the POW code (below) and the error message says something about the file "Python.h" being missing, this is almost certainly your problem.
- <http://codespeak.net/lxml/> . lxml in turn requires the Gnome LibXML2 C libraries.

- FreeBSD: /usr/ports/devel/py-lxml
- Fedora: python-lxml.i386
- Ubuntu: python-lxml
- <http://sourceforge.net/projects/mysql-python/> . MySQLdb  
in turn requires MySQL client and server [rpkid](#) et al have been tested with  
MySQL 5.0 and 5.1.
  - FreeBSD: /usr/ports/databases/py-MySQLdb
  - Fedora: MySQL-python.i386
  - Ubuntu: python-mysqldb

[rpkid](#) et al also make heavy use of a modified copy of the Python OpenSSL Wrappers (POW) package, but this copy has enough modifications and additions that it's included in the subversion tree.

The next step is to build the OpenSSL and POW binaries. At present the OpenSSL code is just a snapshot of the OpenSSL development sources, compiled with special options to enable RFC 3779 support that ISC wrote under previous contract to ARIN. The POW (Python OpenSSL Wrapper) library is an extended copy of the stock POW release.

To build these, cd to the top-level directory in the distribution and type "make".

```
$ cd $top
$ make
```

This should automatically build everything, in the right order, including statically linking the POW extension module with the OpenSSL library to provide RFC 3779 support. If you get errors building POW, see the above discussion of Python development sources.

You will also need a MySQL installation. This code was developed using MySQL 5.1 and has been tested with MySQL 5.0 and 5.1.

The architecture is intended to support hardware signing modules (HSMs), but the code to support them has not been written.

At this point, you should have all the necessary software installed. You will probably want to test it. All tests should be run from the `rpkid/` directory. The test suite requires a few more external packages, only one of which is Python code.

- <http://pyyaml.org/> . testpoke.py (an up-down protocol command line test client) and testbed.py (a test harness) use PyYAML.
  - FreeBSD: /usr/ports/devel/py-yaml
  - Ubuntu: python-yaml

- <http://xmlsoft.org/XSLT/> . Some of the test code uses xsltproc, from the Gnome LibXSLT package.
  - FreeBSD: /usr/ports/textproc/libxslt
  - Ubuntu: xsltproc
- <http://w3m.sourceforge.net/> . testbed.py uses w3m to display the summary output from rcynic. Nothing terrible will happen if w3m isn't available, testbed.py will just complain about it being missing and won't display rcynic's output.
  - FreeBSD: /usr/ports/www/w3m
  - Ubuntu: w3m

Some of the tests require MySQL databases to store their data. To set up all the databases that the tests will need, run the SQL commands in rpkid/testbed.setup.sql. The MySQL command line client is usually the easiest way to do this, eg:

```
$ cd $top/rpkid
$ mysql -u root -p <testbed.setup.sql
```

To run the tests, run "make all-tests":

```
$ cd $top/rpkid
$ make all-tests
```

If nothing explodes, your installation is probably ok. Any Python backtraces in the output indicate a problem.

There's a last set of tools that only developers should need, as they're only used when modifying schemas or regenerating the documentation. These tools are listed here for completeness.

- <http://www.doxygen.org/> . Doxygen in turn pulls in several other tools, notably Graphviz, pdfLaTeX, and Ghostscript.
  - FreeBSD: /usr/ports/devel/doxygen
  - Ubuntu: doxygen
- <http://lynx.isc.org/current/> . The documentation build process uses xsltproc and Lynx to dump at text versions of a few critical documentation pages.
  - FreeBSD: /usr/ports/www/lynx
  - Ubuntu: lynx

- <http://www.thaiopensource.com/relaxng/trang.html> . Trang is used to convert RelaxNG schemas from the human-readable "compact" form to the XML form that LibXML2 understands. Trang in turn requires Java.
  - FreeBSD: /usr/ports/textproc/trang
- <http://search.cpan.org/dist/SQL-Translator/> . SQL-Translator, also known as "SQL Fairy", includes code to parse an SQL schema and dump a description of it as Graphviz input. SQL Fairy in turn requires Perl.
  - FreeBSD: /usr/ports/databases/p5-SQL-Translator

## 4 Operation Guide

Preliminary operation instructions for [rpki](#) et al.

These are the production-side RPKI tools, for Internet Registries (RIRs, LIRs, etc). See rcynic/README for relying party tools.

Warning:

[rpki](#) is still in development, and the code changes more often than the hand-maintained portions of this documentation. The following text was reasonably accurate at the time it was written but may be obsolete by the time you read it.

At present the package is intended to be run out of [rpki/](#) directory.

In addition to the library routines in the [rpki/rpki/](#) directory, the package includes the following programs:

- [rpkid.py](#) : The main RPKI engine daemon.
- [pubd.py](#) : The [publication](#) engine daemon.
- [rootd.py](#) : A separate daemon for handling the root of an RPKI certificate tree. This is essentially a stripped down version of [rpkid](#) with no SQL database, no left-right protocol implementation, and only the parent side of the up-down protocol. It's separate because the root is a special case in several ways and it was simpler to keep the special cases out of the main daemon.
- [irdbd.py](#) : A sample implementation of an IR database daemon. [rpkid](#) calls into this to perform lookups via the left-right protocol.
- [irbe\\_cli.py](#) : A command-line client for the left-right control protocol.

- `cross_certify.py`: A BPKI cross-certification tool.
- `irbe-setup.py`: An example of a script to set up the mappings between the IRDB and rpkiid's own database, using the left-right control protocol.
- `cronjob.py`: A trivial HTTP client used to drive rpkiid cron events.
- `testbed.py`: A test tool for running a collection of rpkiid and irdb instances under common control, driven by a unified test script.
- `testpoke.py`: A simple client for the up-down protocol, mostly compatible with APNIC's `rpki_poke.pl` tool.

Most of these programs take configuration files in a common format similar to that used by the OpenSSL command line tool. The test programs also take input in YAML format to drive the tests. Runs of the `testbed.py` test tool will generate a fairly complete set of configuration files which may be useful as examples.

Basic operation consists of creating the appropriate MySQL databases, starting `pubd`, `rootd`, and `irdbd`, using the left-right control protocol to set up rpkiid's internal state, and setting up a cron job to invoke rpkiid's cron action at regular intervals. All other operations should occur either as a result of cron events or as a result of incoming left-right and up-down protocol requests.

Note that the full event-driven model for rpkiid hasn't yet been implemented. The design is intended to allow an arbitrary number of hosted RPKI engines to run in a single rpkiid instance, but without the event-driven tasking model one must set up a separate rpkiid instance for each hosted RPKI engine.

At present the daemon programs all run in foreground, that is, if one wants them to run in background one must do so manually, eg, using Bourne shell syntax:

```
$ python whatever.py &
$ echo >whatever.pid "$!"
```

All of the daemons use syslog. At present they all set LOG\_PERROR, so all logging also goes to stderr.

## 4.1 rpkiid.py

rpkiid is the main RPKI engine daemon. Configuration of rpkiid is a two step process: a config file to bootstrap rpkiid to the point where it can speak using the left-right protocol, followed by dynamic configuration via the left-right protocol. In production use the latter stage would be handled by the IRBE stub; for test and development purposes it's handled by the `irbe_cli.py` command line interface or by the `testbed.py` test framework.



rpkiid stores dynamic data in an SQL database, which must have been created for it, as explained in the [installation guide](#).

The default configuration file is rpkiid.conf, start rpkiid with "-c filename" to choose a different configuration file. All options are in the section "[rpkiid]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Configuration options:

- startup-message : String to log on startup, useful when debugging a collection of rpkiid instances at once.
- sql-username : Username to hand to MySQL when connecting to rpkiid's database.
- sql-database : MySQL's database name for rpkiid's database.
- sql-password : Password to hand to MySQL when connecting to rpkiid's database.
- bpki-ta : Name of file containing BPKI trust anchor. All BPKI certificate verification within rpkiid traces back to this trust anchor.
- rpkiid-cert : Name of file containing rpkiid's own BPKI EE certificate.
- rpkiid-key : Name of file containing RSA key corresponding to rpkiid-cert.
- irbe-cert : Name of file containing BPKI certificate used by IRBE when talking to rpkiid.
- irdb-cert : Name of file containing BPKI certificate used by irdbd.
- irdb-url : Service URL for irdbd. Must be a https:// URL.
- server-host : Hostname or IP address on which to listen for HTTPS connections. Current default is INADDR\_ANY (IPv4 0.0.0.0); this will need to be hacked to support IPv6 for production.
- server-port : TCP port on which to listen for HTTPS connections.

## 4.2 pubd.py

`pubd` is the `publication` daemon. It implements the server side of the `publication` protocol, and is used by `rpkid` to publish the certificates and other objects that `rpkid` generates.

`pubd` is separate from `rpkid` for two reasons:

- The hosting model allows entities which choose to run their own copies of `rpkid` to publish their output under a common `publication` point. In general, encouraging shared `publication` services where practical is a good thing for relying parties, as it will speed up recursive synchronization time.
- The `publication` server has to run on (or at least close to) the `publication` point itself, which in turn must be on a publically reachable server to be useful. `rpkid`, on the other hand, need only be reachable by the IRBE and its children in the RPKI tree. `rpkid` is a much more complex piece of software than `pubd`, so in some situations it might make sense to wrap tighter firewall constraints around `rpkid` than would be practical if `rpkid` and `pubd` were a single program.

`pubd` stores dynamic data in an SQL database, which must have been created for it, as explained in the installation guide. `pubd` also stores the published objects themselves as files in a configurable location which should correspond to an appropriate module definition in `rsync.conf`.

The default configuration file is `pubd.conf`, start `pubd` with `"-c filename"` to choose a different configuration file. All options are in the section "[pubd]". Certificates, keys, and trust anchors may be either DER or PEM format.

Configuration options:

- `sql-username` : Username to hand to MySQL when connecting to `pubd`'s database.
- `sql-database` : MySQL's database name for `pubd`'s database.
- `sql-password` : Password to hand to MySQL when connecting to `pubd`'s database.
- `bpki-ta` : Name of file containing master BPKI trust anchor for `pubd`. All BPKI validation in `pubd` traces back to this trust anchor.
- `irbe-cert` : Name of file containing BPKI certificate used by IRBE when talking to `pubd`.
- `pubd-cert` : Name of file containing BPKI certificate used by `pubd`.

- `pubd-key` : Name of file containing RSA key corresponding to `pubd-cert`.
- `server-host` : Hostname or IP address on which to listen for HTTPS connections. Current default is `INADDR_ANY` (IPv4 0.0.0.0); this will need to be hacked to support IPv6 for production.
- `server-port` : TCP port on which to listen for HTTPS connections.
- `publication-base` : Path to base of filesystem tree where `pubd` should store publishable objects. Default is "publication/".

### 4.3 rootd.py

`rootd` is a stripped down implementation of (only) the server side of the up-down protocol. It's a separate program because the root certificate of an RPKI certificate tree requires special handling and may also require a special handling policy. `rootd` is a simple implementation intended for test use, it's not suitable for use in a production system. All configuration comes via the config file.

The default config file is `rootd.conf`, start `rootd` with `"-c filename"` to choose a different config file. All options are in the section "[rootd]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `bpki-ta` : Name of file containing BPKI trust anchor. All BPKI certificate validation in `rootd` traces back to this trust anchor.
- `rootd-bpki-cert` : Name of file containing rootd's own BPKI certificate.
- `rootd-bpki-key` : Name of file containing RSA key corresponding to `rootd-bpki-cert`.
- `rootd-bpki-crl` : Name of file containing BPKI CRL that would cover `rootd-bpki-cert` had it been revoked.
- `child-bpki-cert` : Name of file containing BPKI certificate for rootd's one and only child (RPKI engine to which `rootd` issues an RPKI certificate).
- `server-host` : Hostname or IP address on which to listen for HTTPS connections. Default is `localhost`.
- `server-port` : TCP port on which to listen for HTTPS connections.

- `rpki-root-key` : Name of file containing RSA key to use in signing resource certificates.
- `rpki-root-cert` : Name of file containing self-signed root resource certificate corresponding to `rpki-root-key`.
- `rpki-root-dir` : Name of directory where `rootd` should write RPKI subject certificate, `manifest` and CRL.
- `rpki-subject-cert` : Name of file that `rootd` should use to save the one and only certificate it issues. Default is "Subroot.cer".
- `rpki-root-crl` : Name of file to which `rootd` should save its RPKI CRL. Default is "Root.crl".
- `rpki-root-manifest` : Name of file to which `rootd` should save its RPKI `manifest`. Default is "Root.mnf".
- `rpki-subject-pkcs10` : Name of file that `rootd` should use when saving a copy of the received PKCS #10 request for a resource certificate. This is only used for debugging. Default is not to save the PKCS #10 request.

#### 4.4 irdbd.py

`irdbd` is a sample implementation of the server side of the IRDB callback subset of the left-right protocol. In production use this service is a function of the IRBE `irdbd` may be suitable for production use in simple cases, but an IR with a complex IRDB may need to extend or rewrite `irdbd`.

`irdbd` requires a pre-populated database to represent the IR's custom `irdbd` expects this database to use the SQL schema defined in `rpkid/irdbd.sql`. Once this database has been populated, the IRBE stub needs to create the appropriate objects in `rpkid`'s database via the control subset of the left-right protocol, and store the linkage IDs (foreign keys into `rpkid`'s database, basically) in the IRDB. The `irbe-setup.py` program shows an example of how to do this.

`irdbd`'s default config file is `irdbd.conf`, start `irdbd` with "-c filename" to choose a different config file. All options are in the section "[irdbd]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `startup-message` : String to log on startup, useful when debugging a collection of `irdbd` instances at once.

- `sql-username` : Username to hand to MySQL when connecting to irdbd's database.
- `sql-database` : MySQL's database name for irdbd's database.
- `sql-password` : Password to hand to MySQL when connecting to irdbd's database.
- `bpki-ta` : Name of file containing BPKI trust anchor. All BPKI certificate validation in `irdbd` traces back to this trust anchor.
- `irdbd-cert` : Name of file containing irdbd's own BPKI certificate.
- `irdbd-key` : Name of file containing RSA key corresponding to `irdbd-cert`.
- `rpki-cert` : Name of file containing certificate used the one and only by `rpki` instance authorized to contact `irdbd` instance.
- `https-url` : Service URL for `irdbd`. Must be a `https://` URL.

## 4.5 irbe\_cli.py

`irbe_cli` is a simple command line client for the control subsets of `left-right` and `publication` protocols. In production use this functionality would be part of the IRBE stub.

Basic configuration of `irbe_cli` is handled via a config file. The specific action or actions to be performed are specified on the command line, and map closely to the protocols themselves.

At present the user is assumed to be able to read the (XML) left-right `publication` protocol messages, and with one exception, `irdbd-cli` makes no attempt to interpret the responses other than to check for signature and syntax errors. The one exception is that, if the `--pem_out` option is specified on the command line, any PKCS #10 requests received from `rpki` will be written in PEM format to that file; this makes it easier to hand these requests off to the business PKI (BPKI) in order to issue signing certs corresponding to newly generated business keys.

Command line IR back-end control program for `rpki` and `pubd`.

\$Id: irbe\_cli.py 2799 2009-09-30 02:33:36Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any

purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Usage:

# Top-level options:

--config= --help --pem\_out= --quiet --verbose

# left-right protocol:

parent --action= --tag= --self\_handle= --parent\_handle= --bsc\_handle=  
 --repository\_handle= --peer\_contact\_uri= --sia\_base=  
 --sender\_name= --recipient\_name= --bpki\_cms\_cert= --bpki\_cms\_glue=  
 --bpki\_https\_cert= --bpki\_https\_glue= --rekey --reissue --revoke  
 --revoke\_forgotten  
 repository --action= --tag= --self\_handle= --repository\_handle=  
 --bsc\_handle= --peer\_contact\_uri= --bpki\_cert= --bpki\_glue=  
 self --action= --tag= --self\_handle= --crl\_interval= --regen\_margin=  
 --bpki\_cert= --bpki\_glue= --rekey --reissue --revoke --run\_now  
 --publish\_world\_now --revoke\_forgotten  
 child --action= --tag= --self\_handle= --child\_handle= --bsc\_handle=  
 --bpki\_cert= --bpki\_glue= --reissue  
 list\_published\_objects --self\_handle= --tag=  
 bsc --action= --tag= --self\_handle= --bsc\_handle= --key\_type=  
 --hash\_alg= --key\_length= --signing\_cert= --signing\_cert\_crl=  
 --generate\_keypair

# publication protocol:

certificate --action= --tag= --client\_handle= --uri=  
 roa --action= --tag= --client\_handle= --uri=  
 manifest --action= --tag= --client\_handle= --uri=  
 client --action= --tag= --client\_handle= --base\_uri= --bpki\_cert=  
 --bpki\_glue=  
 config --action= --tag= --bpki\_crl=  
 crl --action= --tag= --client\_handle= --uri=

Global options (`--config` , `--help` , `--pem_out` ) come first, then zero or more commands (`parent` , `repository` , `self` , `child` , `bsc` , `config` , `client` ), each followed by its own set of options. The commands map to elements in the protocols, and the command-specific options map to attributes or subelements for those commands.

`--tag` is an optional arbitrary tag (think IMAP) to simplify matching up replies with batched queries.

-- \*\_handle options refer to object primary keys.

The remaining options are specific to the particular commands, and follow directly from the protocol specifications.

A trailing "=" in the above option summary indicates that an option takes a value, eg, "--action create" or "--action=create". Options without a trailing "=" correspond to boolean control attributes.

The default config file for `irbe_cli` is `irbe_cli.conf`, start `irbe_cli` with "-c filename" (or "--config filename") to choose a different config file. All options are in the section "[irbe\_cli]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Config file options:

- `rpkid-bpki-ta` : Name of file containing BPKI trust anchor to use when authenticating messages from `rpkid`.
- `rpkid-irbe-cert` : Name of file containing BPKI certificate `irbe_cli` should use when talking to `rpkid`.
- `rpkid-irbe-key` : Name of file containing RSA key corresponding to `rpkid-irbe-cert`.
- `rpkid-cert` : Name of file containing `rpkid`'s BPKI certificate.
- `rpkid-url` : Service URL for `rpkid`. Must be a https:// URL.
- `pubd-bpki-ta` : Name of file containing BPKI trust anchor to use when authenticating messages from `pubd`.
- `pubd-irbe-cert` : Name of file containing BPKI certificate `irbe_cli` should use when talking to `pubd`.
- `pubd-irbe-key` : Name of file containing RSA key corresponding to `pubd-irbe-cert`.
- `pubd-cert` : Name of file containing `pubd`'s BPKI certificate.
- `pubd-url` : Service URL for `pubd`. Must be a https:// URL.

## 4.6 cross\_certify.py

cross\_certify.py is a small tool to extract certain fields from an existing X.509 certificate and generate issue a new certificate that can be used as part of a cross-certification chain. cross\_certify doesn't take any file, all of its arguments are specified on the command line.

```
python cross_certify.py { -i | --in      } input_cert
                        { -c | --ca      } issuing_cert
                        { -k | --key     } issuing_cert_key
                        { -s | --serial } serial_filename
                        [ { -h | --help } ]
                        [ { -o | --out   } filename ]
                        [ { -l | --lifetime } timedelta ]
```

## 4.7 irbe-setup.py configuration

Warning:

irbe-setup is old code, not currently used, kept in case it is useful at some later date. It may not work properly or at all. If you don't understand what it does, you don't need it. You have been warned.

The default configuration file is irbe.conf, start rpkid with "-c filename" to choose a different configuration file. Most options are in the section "[irbe\_cli]", but a few are in the section "[irbdb]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Options in the "[irbe\_cli]" section:

- bпки-ta : Name of file containing BPKI trust anchor.
- irbe-cert : Name of file containing BPKI certificate irbe-setup should use.
- irbe-key : Name of file containing RSA key corresponding to irbe-cert.
- rpkid-cert : Name of file containing rpkid's BPKI certificate.
- https-url : Service URL for rpkid. Must be a https:// URL.

Options in the "[irbdb]" section:

- sql-username : Username to hand to MySQL when connecting to irbdb's database.
- sql-database : MySQL's database name for irbdb's database.



- `sql-password` : Password to hand to MySQL when connecting to irdbd's database.

## 4.8 cronjob.py

This is a trivial program to trigger a cron run with `rpkid`. Once `rpkid` has been converted to the planned event-driven model, this function will be handled internally, but for now it has to be triggered by an external program. For pseudo-production use one would run this program under the system cron daemon. For scripted testing it happens to be useful to be able to control when cron cycles occur, so at the current stage of code development use of an external trigger is a useful feature.

The default configuration file is `cronjob.conf`, start cronjob with "`-c filename`" to choose a different configuration file. All options are in the section "[cronjob]". Certificates, keys, and trust anchors may be in either DER or PEM format.

Configuration options:

- `bpki-ta` : Name of file containing BPKI trust anchor.
- `irbe-cert` : Name of file containing cronjob.py's BPKI certificate.
- `https-key` : Name of file containing RSA key corresponding to `irbe-cert`.
- `rpkid-cert` : Name of file containing `rpkid`'s BPKI certificate.
- `https-url` : Service URL for `rpkid`. Must be a `https://` URL.

## 4.9 testbed.py:

testbed is a test harness to set up and run a collection of `rpkid` and `irdbd` instances under scripted control. testbed is a very recent addition to the toolset and is still evolving rapidly.

Unlike the programs described above, testbed takes two configuration files in different languages. The first configuration file uses the same syntax as the above configuration files but is completely optional. The second configuration file is the test script, which is encoded using the YAML serialization language (<http://www.yaml.org/> for more information on YAML). The YAML script is not optional, as it describes the test layout. testbed is designed to support running a fairly wide set of test configurations as canned scripts without writing any new control code. The intent is to make it possible to write meaningful regression tests.

All of the options in the first (optional) configuration file are just overrides for wired-in default values. In most cases the defaults will suffice, and the set of options is still

in `ux`, so only a few of the options are described here. The default name for this configuration file is `testbed.conf`, run `testbed` with `"-c filename"` to change it.

`testbed.conf` options:

- `testbed_dir`: Working directory into which `testbed` should write the (many) files it generates. Default is `"testbed.dir"`.
- `irdb_db_pass`: MySQL password for the `"irdb"` user. Default is `"fnord"`. You may want to override this.
- `rpki_db_pass`: MySQL password for the `"rpki"` user. Default is `"fnord"`. You may want to override this.
- `rootd_sia`: `rsync` URI naming a (perhaps fictitious) directory to use as the `id-ad-caRepository` SIA value in the generated root resource certificate. Default is `"rsync://wombat.invalid/"`. You may want to override this if you intend to run an `rsync` server and test against the generated results using `rcynic`. This default will likely change if and when `testbed` learns how to run `rcynic` itself as part of the test suite.

The second configuration file is named `testbed.yaml` by default, run `testbed` with `"-y filename"` to change it. The YAML file contains multiple YAML "documents". The first document describes the initial test layout and resource allocations, subsequent documents describe modifications to the initial allocations and other parameters. Resources listed in the initial layout are aggregated automatically, so that a node in the resource hierarchy automatically receives the resources it needs to issue whatever its children are listed as holding. Actions in the subsequent documents are modifications to the current resource set, modifications to validity dates or other non-resource parameters, or special commands like `"sleep"`. The details are still evolving, but here's an example of current usage:

```
name: RIR
valid_for: 2d
sia_base: "rsync://wombat.invalid/"
kids:
  - name: LIR0
    kids:
      - name: Alice
        ipv4: 192.0.2.1-192.0.2.33
        asn: 64533
    ---
  - name: Alice
    valid_add: 10
  ---
  - name: Alice
    add_as: 33
    valid_add: 2d
```

```

---
- name: Alice
  valid_sub: 2d
---
- name: Alice
  valid_for: 10d

```

This specifies an initial layout consisting of an RPKI engine named "RIR", with one child "LIR0", which in turn has one child "Alice". Alice has a set of assigned resources, and all resources in the system are initially set to be valid for two days from the time at which the test is started. The first subsequent document adds ten seconds to the validity interval for Alice's resources and makes no other modifications. The second subsequent document grants Alice additional resources and adds another two days to the validity interval for Alice's resources. The next document subtracts two days from the validity interval for Alice's resources. The final document sets the validity interval for Alice's resources to ten days.

Operators in subsequent (update) documents:

- `add_as` , `add_v4` , `add_v6`: These add ASN, IPv4, or IPv6 resources, respectively.
- `sub_as` , `sub_v4` , `sub_v6`: These subtract resources.
- `valid_until`: Set an absolute expiration date.
- `valid_for`: Set a relative expiration date.
- `valid_add` , `valid_sub`: Add to or subtract from validity interval.
- `sleep [interval]`: Sleep for specified interval, or until testbed receives a SIGALRM signal.

Absolute timestamps should be in the form shown (UTC timestamp format as used in XML).

Intervals (`valid_add` , `valid_sub` , `valid_for` , `sleep` ) are either integers, in which case they're interpreted as seconds, or are a string of the form "wD xH yM zS" where w, x, y, and z are integers and D, H, M, and S indicate days, hours, minutes, and seconds. In the latter case all of the fields are optional, but at least one must be specified. For example, "3D4H" means "three days plus four hours".

## 4.10 testpoke.py

This is a command-line client for the up-down protocol. Unlike all of the above programs, testpoke does not accept a config file in OpenSSL-compatible format at all. Instead, it is configured exclusively by a YAML script. testpoke's design was constrained

by a desire to have it be compatible with APNIC's `rpki_poke.pl` tool, so that the two tools could use a common configuration language to simplify scripted testing. There are minor variations due to slightly different feature sets, but YAML files intended for one program will usually work with the other.

README for APNIC's tool describing the input language can be found at <http://mirin.apnic.net/svn/rpki-engine/branches/gary-poker/client/poke/README>.

`testpoke.py` takes a simplified command line and uses only one YAML input file.

```
Usage: python testpoke.py [ { -y | --yaml }      configfile ]
                        [ { -r | --request } requestname ]
                        [ { -h | --help } ]
```

Default configuration file is `testpoke.yaml`, override with `--yaml` option.

The `--request` option specifies the specific command within the YAML file to execute.

Sample configuration file:

```
---
# Sample YAML configuration file for testpoke.py

version: 1
posturl: https://localhost:4433/up-down/1
recipient-id: wombat
sender-id: "1"

cms-cert-file: biz-certs/Frank-EE.cer
cms-key-file: biz-certs/Frank-EE.key
cms-ca-cert-file: biz-certs/Bob-Root.cer
cms-cert-chain-file: [ biz-certs/Frank-CA.cer ]

ssl-cert-file: biz-certs/Frank-EE.cer
ssl-key-file: biz-certs/Frank-EE.key
ssl-ca-cert-file: biz-certs/Bob-Root.cer

requests:
  list:
    type: list
    issue:
      type: issue
      class: 1
      sia: [ "rsync://bandicoot.invalid/some/where/" ]
      revoke:
        type: revoke
        class: 1
        ski: "CB5K6APY-4KcGAW9jaK_cVPXKX0"
```

`testpoke` adds one extension to the language described in APNIC's README: the `cms-cert-chain` and `ssl-cert-chain` options, which allow one to specify a chain of

intermediate certificates to be presented in the CMS or TLS protocol. APNIC's initial implementation required direct knowledge of the issuing certificate (ie, it supported a maximum chain length of one); subsequent APNIC code changes have probably relaxed this restriction, and with luck APNIC has copied testpoke's syntax to express chains of intermediate certificates.

## 5 Left-right protocol

The left-right protocol is really two separate client/server protocols over separate channels between the RPKI engine and the IR back end (IRBE).

The IRBE is the client for one of the subprotocols, the RPKI engine is the client for the other.

## 5.1 Terminology

- IRBE: Internet Registry Back End
- IRDB: Internet Registry Data Base
- BPKI: Business PKI
- RPKI: Resource PKI

## 5.2 initiated by the IRBE

This part of the protocol uses a kind of message-passing. Each object that the RPKI engine knows about takes five messages: "create", "set", "get", "list", and "destroy". Actions which are not just data operations on objects are handled via an SNMP-like mechanism, as if they were fields to be set. For example, to generate a keypair one "sets" the "generate-keypair" field of a BSC object, even though there is no such field in the object itself as stored in SQL. This is a bit of a kludge, but the reason for doing it as if these were variables being set is to allow composite operations such as creating a BSC, populating all of its data fields, and generating a keypair, all as a single operation. With this model, that's trivial, otherwise it's at least two round trips.

Fields can be set in either "create" or "set" operations, the difference just being whether the object already exists. A "get" operation returns all visible elds of the object. A "list" operation returns a list containing what "get" would have returned on each of those objects.

Left-right protocol objects are encoded as signed CMS messages containing XML as eContent and using an eContentType OID of `ct-xml`.

(1.2.840.113549.1.9.16.1.28). These CMS messages are in turn passed as the data for HTTPS POST operations, with an HTTP content type of "application/x-rpki" for both the POST data and the response data.

All operations allow an optional "tag" attribute which can be any alphanumeric token. The main purpose of the tag attribute is to allow batching of multiple requests into a single PDU.

### 5.2.1 <self/> object

A <self/> object represents one virtual RPKI engine. In simple cases where the RPKI engine operator operates the engine only on their own behalf, there will only be one <self/> object, representing the engine operator's organization, but in environments where the engine operator hosts other entities, there will be one <self/> object per hosted entity (probably including the engine operator's own organization, considered as a hosted customer of itself).

Some of the RPKI engine's configured parameters and data are shared by all hosted entities, but most are tied to a specific <self/> object. Data which are shared by all hosted entities are referred to as "per-engine" data, data which are specific to a particular <self/> object are "per-self" data.

Since all other RPKI engine objects refer to a <self/> object via a "self\_handle" value, one must create a <self/> object before one can usefully configure any other left-right protocol objects.

Every <self/> object has a self\_handle attribute, which must be specified for the "create", "set", "get", and "destroy" actions.

Payload data which can be configured in a <self/> object:

- use\_hsm (attribute): Whether to use a Hardware Signing Module. At present this option has no effect, as the implementation does not yet support HSMs.
- crl\_interval (attribute): Positive integer representing the planned lifetime of an RPKI CRL for this <self/>, measured in seconds.
- regen\_margin (attribute): Positive integer representing how long before expiration of an RPKI certificate a new one should be generated, measured in seconds. At present this only affects the one-off EE certificates associated with ROAs.
- bpki\_cert (element): BPKI CA certificate for this <self/>. This is used as part of the certificate chain when validating incoming TLS and CMS messages, and should be the issuer of cross-certification BPKI certificates used in <repository/>, <parent/>, and <child/> objects. If the bpki\_glue certificate is in use (below), the bpki\_cert certificate should be issued by the

bpki\_glue certificate; otherwise, the bpki\_cert certificate should be issued by the per-engine bpki\_ta certificate.

- bpki\_glue (element): Another BPKI CA certificate for thisself/ >, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the bpki\_glue certificate should be the issuer of the bpki\_cert certificate and should be issued by the per-engine bpki\_ta certificate; if not needed, the bpki\_glue certificate should be left unset.

Control attributes that can be set to "yes" to force actions:

- rekey: Start a key rollover for every RPKI CA associated with every <parent/ > object associated with thisself/ > object. This is the first phase of a key rollover operation.
- revoke: Revoke any remaining certificates for any expired key associated with any RPKI CA for any <parent/ > object associated with thisself/ > object. This is the second (cleanup) phase for a key rollover operation; it's separate from the first phase to leave time for new RPKI certificates to propagate and be installed.
- reissue: Not implemented, may be removed from protocol. Original theory was that this operation would force reissuance of any object with a changed key, but as that happens automatically as part of the key rollover mechanism this operation seems unnecessary.
- run\_now: Force immediate processing for all tasks associated with this <self/ > object that would ordinarily be performed under cron. Not currently implemented.
- publish\_world\_now: Force (re)publication of every publishable object for this <self/ > object. Not currently implemented. Intended to aid in recovery if RPKI engine and publication engine somehow get out of sync.

### 5.2.2 <bsc/> object

The <bsc/ > ("business signing context") object represents all the BPKI data needed to sign outgoing CMS or HTTPS messages. Various other objects include pointers to a <bsc/ > object. Whether a particularself/ > uses only one <bsc/ > or multiple is a configuration decision based on external requirements: the RPKI engine code doesn't care, it just cares that, for any object representing a relationship for which it must sign messages, there be a <bsc/ > object that it can use to produce that signature.

Every `<bsc/ >` object has a `bsc_handle`, which must be specified for the "create", "get", "set", and "destroy" actions. Every `<bsc/ >` also has a `self_handle` attribute which indicates the `<self/ >` object with which this `<bsc/ >` object is associated.

Payload data which can be configured in `<bsc/ >` object:

- `signing_cert` (element): BPKI certificate to use when generating a signature.
- `signing_cert_crl` (element): CRL which would list `signing_cert` if it had been revoked.

Control attributes that can be set to "yes" to force actions:

- `generate_keypair`: Generate a new BPKI keypair and return a PKCS #10 certificate request. The resulting certificate, once issued, should be configured as this `<bsc/ >` object's `signing_cert`.

Additional attributes which may be specified when specifying "generate\_keypair":

- `key_type`: Type of BPKI keypair to generate. "rsa" is both the default and, at the moment, the only allowed value.
- `hash_alg`: Cryptographic hash algorithm to use with this keypair. "sha256" is both the default and, at the moment, the only allowed value.
- `key_length`: Length in bits of the keypair to be generated. "2048" is both the default and, at the moment, the only allowed value.

Replies to "create" and "set" actions that specify "generate-keypair" include a `pkcs10/ >` element, as do replies to "get" and "list" actions for `<bsc/ >` object for which a "generate-keypair" command has been issued. The RPKI engine stores the PKCS #10 request, which allows the IRBE to reuse the request if and when it needs to reissue the corresponding BPKI signing certificate.

### 5.2.3 `<parent/ >` object

The `<parent/ >` object represents the RPKI engine's view of a particular parent of the current `<self/ >` object in the up-down protocol. Due to the way that the resource hierarchy works, a given `<self/ >` may obtain resources from multiple parents, but it will always have at least one; in the case of IANA or an RIR, the parent RPKI engine may be a trivial stub.

Every `<parent/ >` object has a `parent_handle`, which must be specified for the "create", "get", "set", and "destroy" actions. Every `<parent/ >` also has a `self_handle`



attribute which indicates the `<self/>` object with which this `<parent/>` object is associated, a `bsc_handle` attribute indicating the `<bsc/>` object to be used when signing messages sent to this parent, and a `repository_handle` indicating the `<repository/>` object to be used when publishing issued by the certificate issued by this parent.

Payload data which can be configured in a `<parent/>` object:

- `peer_contact_uri` (attribute): HTTPS URI used to contact this parent.
- `sia_base` (attribute): The leading portion of an rsync URI that the RPKI engine should use when composing the publication URI for objects issued by the RPKI certificate issued by this parent.
- `sender_name` (attribute): Sender name to use in the up-down protocol when talking to this parent. The RPKI engine doesn't really care what this value is, but other implementations of the up-down protocol do care.
- `recipient_name` (attribute): Recipient name to use in the up-down protocol when talking to this parent. The RPKI engine doesn't really care what this value is, but other implementations of the up-down protocol do care.
- `bpki_cms_cert` (element): BPKI CMS CA certificate for this `<parent/>`. This is used as part of the certificate chain when validating incoming CMS messages. If the `bpki_cms_glue` certificate is in use (below), the `bpki_cms_cert` certificate should be issued by the `bpki_cms_glue` certificate; otherwise, the `bpki_cms_cert` certificate should be issued by the `bpki_cert` certificate in the `<self/>` object.
- `bpki_cms_glue` (element): Another BPKI CMS CA certificate for this `<parent/>`, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the `bpki_cms_glue` certificate should be the issuer of the `bpki_cms_cert` certificate and should be issued by the `bpki_cert` certificate in the `<self/>` object; if not needed, the `bpki_cms_glue` certificate should be left unset.
- `bpki_https_cert` (element): BPKI HTTPS CA certificate for this `<parent/>`. This is like the `bpki_cms_cert` object, only used for validating incoming TLS messages rather than CMS.
- `bpki_https_glue` (element): Another BPKI HTTPS CA certificate for this `<parent/>`, usually not needed. This is like the `bpki_cms_glue` certificate, only used for validating incoming TLS messages rather than CMS.

Control attributes that can be set to "yes" to force actions:

- rekey: This is like the rekey command in the `<self/>` object, but limited to RPKI CAs under this parent.
- reissue: This is like the reissue command in the `<self/>` object, but limited to RPKI CAs under this parent.
- revoke: This is like the revoke command in the `<self/>` object, but limited to RPKI CAs under this parent.

#### 5.2.4 `<child/>` object

The `<child/>` object represents the RPKI engine's view of particular child of the current `<self/>` in the up-down protocol.

Every `<child/>` object has a `child_handle`, which must be specified for the "create", "get", "set", and "destroy" actions. Every `<child/>` also has a `self_handle` attribute which indicates the `<self/>` object with which this `<child/>` object is associated.

Payload data which can be configured in `<child/>` object:

- `bpki_cert` (element): BPKI CA certificate for this `<child/>`. This is used as part of the certificate chain when validating incoming TLS and CMS messages. If the `bpki_glue` certificate is in use (below), the `bpki_cert` certificate should be issued by the `bpki_glue` certificate; otherwise, the `bpki_cert` certificate should be issued by the `bpki_cert` certificate in the `<self/>` object.
- `bpki_glue` (element): Another BPKI CA certificate for this `<child/>`, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the `bpki_glue` certificate should be the issuer of the `bpki_cert` certificate and should be issued by the `bpki_cert` certificate in the `<self/>` object; if not needed, the `bpki_glue` certificate should be left unset.

Control attributes that can be set to "yes" to force actions:

- reissue: Not implemented, may be removed from protocol.

#### 5.2.5 `<repository/>` object

The `<repository/>` object represents the RPKI engine's view of a particular `publication` repository used by the current `<self/>` object.

Every `<repository/>` object has a `repository_handle`, which must be specified for the "create", "get", "set", and "destroy" actions. Every `<repository/>` also

has a `self_handle` attribute which indicates the `self/` object with which this `<repository/` object is associated.

Payload data which can be configured in a `repository/` object:

- `peer_contact_uri` (attribute): HTTPS URI used to contact this repository.
- `bpki_cms_cert` (element): BPKI CMS CA certificate for this `<repository/` object. This is used as part of the certificate chain when validating incoming CMS messages. If the `bpki_cms_glue` certificate is in use (below), the `bpki_cms_cert` certificate should be issued by the `bpki_cms_glue` certificate; otherwise, the `bpki_cms_cert` certificate should be issued by the `bpki_cert` certificate in the `self/` object.
- `bpki_cms_glue` (element): Another BPKI CMS CA certificate for this `<repository/` object, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the `bpki_cms_glue` certificate should be the issuer of the `bpki_cms_cert` certificate and should be issued by the `bpki_cert` certificate in the `self/` object; if not needed, the `bpki_cms_glue` certificate should be left unset.
- `bpki_https_cert` (element): BPKI HTTPS CA certificate for this `<repository/` object. This is like the `bpki_cms_cert` object, only used for validating incoming TLS messages rather than CMS.
- `bpki_https_glue` (element): Another BPKI HTTPS CA certificate for this `<repository/` object, usually not needed. This is like the `bpki_cms_glue` certificate, only used for validating incoming TLS messages rather than CMS.

At present there are no control attributes for `repository/` objects.

### 5.2.6 `<route_origin/` object

This section is out-of-date. The `route_origin/` object has been replaced by the `<list_roa_requests/` IRDB query, but the documentation for that hasn't been written yet.

The `<route_origin/` object is a kind of prototype for a ROA. It contains all the information needed to generate a ROA once the RPKI engine obtains the appropriate RPKI certificates from its parent(s).

Note that a `<route_origin/` object represents a ROA to be generated on behalf of `<self/`, not on behalf of a `<child/`. Thus, a hosted entity that has no children but which does need to generate ROAs would be represented by a hosted `<self/` with no `<child/` objects but one or more `route_origin/` objects. While lumping ROA generation in with the other RPKI engine activities may

seem a little odd at first, it's a natural consequence of the design requirement that the RPKI daemon never transmit private keys across the network in any form; given this requirement, the RPKI engine that holds the private keys for an RPKI certificate must also be the engine which generates any ROAs that derive from that RPKI certificate.

The precise content of the `route_origin/` object has changed over time as the underlying ROA specification has changed. The current implementation as of this writing matches what we expect to see in draft-ietf-sidr-roa-format-03, once it is issued. In particular, note that the `exactMatch` boolean from the -02 draft has been replaced by the `pre_x` and `maxLength` encoding used in the -03 draft.

Payload data which can be configured in a `route_origin/` object:

- `asn` (attribute): Autonomous System Number (ASN) to place in the generated ROA. A single ROA can only grant authorization to a single ASN; multiple ASNs require multiple ROAs, thus multiple `route_origin/` objects.
- `ipv4` (attribute): List of IPv4 `pre_x` and `maxLength` values, see below for format.
- `ipv6` (attribute): List of IPv6 `pre_x` and `maxLength` values, see below for format.

Control attributes that can be set to "yes" to force actions:

- `suppress_publication`: Not implemented, may be removed from protocol.

The lists of IPv4 and IPv6 `pre_x` and `maxLength` values are represented as comma-separated text strings, with no whitespace permitted. Each entry in such a string represents a single `pre_x`/`maxLength` pair.

ABNF for these address lists:

```
<ROAIPAddress> ::= <address> "/" <prefixlen> [ "-" <max_prefixlen> ]
                  ; Where <max_prefixlen> defaults to the same
                  ; value as <prefixlen>.

<ROAIPAddressList> ::= <ROAIPAddress> * ( "," <ROAIPAddress> )
```

For example, `"10.0.1.0/24-32,10.0.2.0/24"`, which is a shorthand form of `"10.0.1.0/24-32,10.0.2.0/24-24"`.

### 5.3 Operations initiated by the RPKI engine

The left-right protocol also includes queries from the RPKI engine back to the IRDB. These queries do not follow the message-passing pattern used in the IRBE-initiated part of the protocol. Instead, there's a single query back to the IRDB, with a corresponding response. The CMS and HTTPS encoding are the same as in the rest of the protocol, but the BPKI certificates will be different as the back-queries and responses form a separate communication channel.

#### 5.3.1 <list\_resources> messages

The <list\_resources/> query and response allow the RPKI engine to ask the IRDB for information about resources assigned to a particular child. The query must include both a "self\_handle" attribute naming the self/> that is making the request and also a "child\_handle" attribute naming the child that is the subject of the query. The query and response also allow an optional "tag" attribute of the same form used elsewhere in this protocol, to allow batching.

A <list\_resources/> response includes the following attributes, along with the tag (if specified), self\_handle, and child\_handle copied from the request:

- **valid\_until:** A timestamp indicating the date and time at which certificates generated by the RPKI engine for these data should expire. The timestamp is expressed as an `XML:dateTime`, must be expressed in UTC, and must carry the "Z" suffix indicating UTC.
- **asn:** A list of autonomous sequence numbers, expressed as a comma-separated sequence of decimal integers with no whitespace.
- **ipv4:** A list of IPv4 address prefixes and ranges, expressed as a comma-separated list of prefixes and ranges with no whitespace. See below for format details.
- **ipv6:** A list of IPv6 address prefixes and ranges, expressed as a comma-separated list of prefixes and ranges with no whitespace. See below for format details.

Entries in a list of address prefixes and ranges can be either prefixes, which are written in the usual address/prefix notation, or ranges, which are expressed as a pair of addresses denoting the beginning and end of the range, written in ascending order separated by a single "-" character. This format is superficially similar to the format used for prefix and maxLength values in the `route_origin/>` object, but the semantics differ: note in particular that `route_origin/>` objects don't allow ranges, while `<list_resources/>` messages don't allow a maxLength specification.

## 5.4 Error handling

Error in this protocol are handled at two levels.

Since all messages in this protocol are conveyed over HTTPS connections, basic errors are indicated via the HTTP response code. 4xx and 5xx responses indicate that something bad happened. Errors that make it impossible to decode a query or encode a response are handled in this way.

Where possible, errors will result in a `<report_error/ >` message which takes the place of the expected protocol response message. `<report_error/ >` messages are CMS-signed XML messages like the rest of this protocol, and thus can be archived to provide an audit trail.

`<report_error/ >` messages only appear in replies, never in queries. The `<report_error/ >` message can appear on either the "forward" (IRBE as client of RPKI engine) or "back" (RPKI engine as client of IRDB) communication channel.

The `<report_error/ >` message includes an optional "tag" attribute to assist in matching the error with a particular query when using batching, and also includes a "self\_handle" attribute indicating the `<self/ >` that issued the error.

The error itself is conveyed in the `error_code` (attribute). The value of this attribute is a token indicating the specific error that occurred. At present this will be the name of a Python exception; the production version of this protocol will nail down the allowed error tokens here, probably in the RelaxNG schema.

The body of the `<report_error/ >` element itself is an optional text string; if present, this is debugging information. At present this capability is not used, debugging information goes to syslog.

## 6 Publication protocol

The publication protocol is really two separate client/server protocols, between different parties.

The first is a configuration protocol for an IRBE to use to configure a publication engine, the second is the interface by which authorized clients request publication of specific objects.

Much of the architecture of the publication protocol is borrowed from [left-right protocol](#): like the left-right protocol, the publication protocol uses CMS-wrapped XML over HTTPS with the same eContentType OID and the same HTTPS content-type, and the overall style of the XML messages is very similar to the left-right protocol. All operations allow an optional "tag" attribute to allow batching.

The publication engine operates a single HTTPS server which serves both of these subprotocols. The two subprotocols share a single server port, but use distinct URLs to allow demultiplexing.

## 6.1 Terminology

- IRBE: Internet Registry Back End
- IRDB: Internet Registry Data Base
- BPKI: Business PKI
- RPKI: Resource PKI

## 6.2 Publication control subprotocol

The control subprotocol reuses the message-passing design of the left-right protocol. Configured objects support the "create", "set", "get", "list", and "destroy" actions, or a subset thereof when the full set of actions doesn't make sense.

### 6.2.1 <con g/> object

The <con g/> object allows configuration of data that apply to the entire publication server rather than a particular client.

There is exactly one <con g/> object in the publication server, and it only supports the "set" and "get" actions -- it cannot be created or destroyed.

Payload data which can be configured in a <con g/> object:

- `bpki_crl` (element): This is the BPKI CRL used by the publication server when signing the CMS wrapper on responses in the publication subprotocol. As the CRL must be updated at regular intervals, it's not practical to restart the publication server when the BPKI CRL needs to be updated. The BPKI model doesn't require use of a BPKI CRL between the IRBE and the publication server, so we can use the publication control subprotocol to update the BPKI CRL.

### 6.2.2 <client/> object

The <client/> object represents one client authorized to use the publication server.

The <client/> object supports the full set of "create", "set", "get", "list", and "destroy" actions. Each client has a "client\_handle" attribute, which is used in responses and must be specified in "create", "set", "get", or "destroy" actions.

Payload data which can be configured in a <client/> object:

- `base_uri` (attribute): This is the base URI below which this client is allowed to publish data. The publication server may impose additional constraints in the case of a child publishing beneath its parent.

- `bpki_cert` (element): BPKI CA certificate for this<client/>. This is used as part of the certificate chain when validating incoming TLS and CMS messages. If the `bpki_glue` certificate is in use (below), the `bpki_cert` certificate should be issued by the `bpki_glue` certificate; otherwise, the `bpki_cert` certificate should be issued by the publication engine's `bpki_ta` certificate.
- `bpki_glue` (element): Another BPKI CA certificate for this<client/>, usually not needed. Certain pathological cross-certification cases require a two-certificate chain due to issuer name conflicts. If used, the `bpki_glue` certificate should be the issuer of the `bpki_cert` certificate and should be issued by the publication engine's `bpki_ta` certificate; if not needed, the `bpki_glue` certificate should be left unset.

### 6.3 Publication subprotocol

The publication subprotocol is structured somewhat differently from the publication control protocol. Objects in the publication subprotocol represent objects to be published or objects to be withdrawn from publication. Each kind of object supports two actions: "publish" and "withdraw". In each case the XML element representing the object to be published or withdrawn has a "uri" attribute which contains the publication URI. For "publish" actions, the XML element body contains the DER object to be published, encoded in Base64; for "withdraw" actions, the XML element body is empty.

In theory, the detailed access control for each kind of object might be different. In practice, as of this writing, access control for all objects is a simple check that the client's "base\_uri" is a leading substring of the publication URI. Details of why access control might need to become more complicated are discussed in a later section.

#### 6.3.1 <certificate/> object

The<certificate/> object represents an RPKI certificate to be published or withdrawn.

#### 6.3.2 <crl/> object

The<crl/> object represents an RPKI CRL to be published or withdrawn.

#### 6.3.3 <manifest/> object

The<manifest/> object represents an RPKI publication manifest to be published or withdrawn.



Note that part of the reason for the batching support in the publication protocol is because every publication or withdrawal action requires a new manifest, thus every publication or withdrawal action will involve at least two objects.

#### 6.3.4 <roa/> object

The <roa/> object represents a ROA to be published or withdrawn.

### 6.4 Error handling

Error in this protocol are handled at two levels.

Since all messages in this protocol are conveyed over HTTPS connections, basic errors are indicated via the HTTP response code. 4xx and 5xx responses indicate that something bad happened. Errors that make it impossible to decode a query or encode a response are handled in this way.

Where possible, errors will result in a ~~<report\_error/>~~ message which takes the place of the expected protocol response message. ~~<report\_error/>~~ messages are CMS-signed XML messages like the rest of this protocol, and thus can be archived to provide an audit trail.

~~<report\_error/>~~ messages only appear in replies, never in queries. ~~<report\_error/>~~ message can appear in both the control and publication subprotocols.

The ~~<report\_error/>~~ message includes an optional "tag" attribute to assist in matching the error with a particular query when using batching.

The error itself is conveyed in the ~~error\_code~~ (attribute). The value of this attribute is a token indicating the specific error that occurred. At present this will be the name of a Python exception; the production version of this protocol will nail down the allowed error tokens here, probably in the RelaxNG schema.

The body of the ~~<report\_error/>~~ element itself is an optional text string; if present, this is debugging information. At present this capability is not used, debugging information goes to syslog.

### 6.5 Additional access control considerations.

As detailed above, the publication protocol is trivially simple. This glosses over two bits of potential complexity:

- In the case where parent and child are sharing a repository, we'd like to nest child under parent, because testing has demonstrated that even on relatively slow hardware the delays involved in setting up separate rsync connections tend to dominate synchronization time for relying parties.

- The repository operator might also want to do some checks to assure itself that what it's about to allow the RPKI engine to publish is not dangerous toxic waste.

The up-down protocol includes a mechanism by which a parent can suggest a publication URI to each of its children. The children are not required to accept this hint, and the children must make separate arrangements with the repository operator (who might or might not be the same as the entity that hosts the children's RPKI engine operations) to use the suggested publication point, but if everything works out, this allows children to nest cleanly under their parents publication points, which helps reduce synchronization time for relying parties.

In this case, one could argue that the publication server is responsible for preventing one of its clients (the child in the above description) from stomping on data published by another of its clients (the parent in the above description). This goes beyond the basic access check and requires the publication server to determine whether the parent has given its consent for the child to publish under the parent. Since the RPKI certificate profile requires the child's publication point to be indicated in an SIA extension in a certificate issued by the parent to the child, the publication engine can infer this permission from the parent's issuance of a certificate to the child. Since, by definition, the parent also uses this publication server, this is an easy check, as the publication server should already have the parent's certificate available by the time it needs to check the child's certificate.

The previous paragraph only covers a "publish" action for a certificate object. For "publish" actions on other objects, the publication server would need to trace permission back to the certificate issued by the parent; for "withdraw" actions, the publication server would have to perform the same checks it would perform for a "publish" action, using the current published data before withdrawing it. The latter in turn implies an ordering constraint on "withdraw" actions in order to preserve the data necessary for these access control decisions; as this may prove impractical, the publication server may probably need to make periodic sweeps over its published data looking for orphaned objects, but that's probably a good idea anyway.


Note that, in this publication model, any agreement that the repository makes to publish the RPKI engine's output is conditional upon the object to be published passing whatever access control checks the publication server imposes.

## 7 SQL database schemas

- [rpkid database schema](#)
- [pubd database schema](#)
- [irdbd database schema](#)



## 7.1 rpkiid SQL schema



```

-- $Id: rpkiid.sql 2906 2009-12-23 06:31:32Z sra $

-- Copyright (C) 2007-2008 American Registry for Internet Numbers ("ARIN")
--
-- Permission to use, copy, modify, and distribute this software for any
-- purpose with or without fee is hereby granted, provided that the above
-- copyright notice and this permission notice appear in all copies.
--
-- THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
-- REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
-- AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
-- INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
-- LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
-- OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
-- PERFORMANCE OF THIS SOFTWARE.

-- SQL objects needed by the RPKI engine (rpkiid.py).

-- DROP TABLE commands must be in correct (reverse dependency) order
-- to satisfy FOREIGN KEY constraints.

DROP TABLE IF EXISTS roa_prefix;
DROP TABLE IF EXISTS roa;
DROP TABLE IF EXISTS revoked_cert;
DROP TABLE IF EXISTS child_cert;
DROP TABLE IF EXISTS child;
DROP TABLE IF EXISTS ca_detail;
DROP TABLE IF EXISTS ca;
DROP TABLE IF EXISTS parent;
DROP TABLE IF EXISTS repository;
DROP TABLE IF EXISTS bsc;
DROP TABLE IF EXISTS self;

CREATE TABLE self (
    self_id          SERIAL NOT NULL,
    self_handle      VARCHAR(255) NOT NULL,
    use_hsm          BOOLEAN NOT NULL DEFAULT FALSE,
    srl_interval     BIGINT UNSIGNED,
    regen_margin     BIGINT UNSIGNED,
    bpkc_cert        LONGBLOB,
    bpkc_glue        LONGBLOB,
    PRIMARY KEY      (self_id),
    UNIQUE           (self_handle)
) ENGINE=InnoDB;

CREATE TABLE bsc (
    bsc_id          SERIAL NOT NULL,
    bsc_handle      VARCHAR(255) NOT NULL,
    private_key_id   LONGBLOB,
    pkcs10_request   LONGBLOB,
    hash_alg         ENUM ('sha256'),
    signing_cert     LONGBLOB,
    signing_cert_srl LONGBLOB,
    self_id         BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY      (bsc_id),
    CONSTRAINT       bsc_self_id
    FOREIGN KEY      (self_id) REFERENCES self (self_id) ON DELETE CASCADE,

```

```

        UNIQUE                                (self_id, bsc_handle)
    ) ENGINE=InnoDB;

CREATE TABLE repository (
    repository_id SERIAL NOT NULL,
    repository_handle VARCHAR(255) NOT NULL,
    peer_contact_uri TEXT,
    bpki_cert LONGBLOB,
    bpki_glue LONGBLOB,
    bsc_id BIGINT UNSIGNED NOT NULL,
    self_id BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY (repository_id),
    CONSTRAINT repository_self_id FOREIGN KEY (self_id) REFERENCES self (self_id) ON DELETE CASCADE,
    CONSTRAINT repository_bsc_id FOREIGN KEY (bsc_id) REFERENCES bsc (bsc_id) ON DELETE CASCADE,
    UNIQUE (self_id, repository_handle)
) ENGINE=InnoDB;

CREATE TABLE parent (
    parent_id SERIAL NOT NULL,
    parent_handle VARCHAR(255) NOT NULL,
    bpki_cms_cert LONGBLOB,
    bpki_cms_glue LONGBLOB,
    bpki_https_cert LONGBLOB,
    bpki_https_glue LONGBLOB,
    peer_contact_uri TEXT,
    sia_base TEXT,
    sender_name TEXT,
    recipient_name TEXT,
    self_id BIGINT UNSIGNED NOT NULL,
    bsc_id BIGINT UNSIGNED NOT NULL,
    repository_id BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY (parent_id),
    CONSTRAINT parent_repository_id FOREIGN KEY (repository_id) REFERENCES repository (repository_id) ON DELETE CASCADE,
    CONSTRAINT parent_bsc_id FOREIGN KEY (bsc_id) REFERENCES bsc (bsc_id) ON DELETE CASCADE,
    CONSTRAINT parent_self_id FOREIGN KEY (self_id) REFERENCES self (self_id) ON DELETE CASCADE,
    UNIQUE (self_id, parent_handle)
) ENGINE=InnoDB;

CREATE TABLE ca (
    ca_id SERIAL NOT NULL,
    last_crl_sn BIGINT UNSIGNED NOT NULL,
    last_manifest_sn BIGINT UNSIGNED NOT NULL,
    next_manifest_update DATETIME,
    next_crl_update DATETIME,
    last_issued_sn BIGINT UNSIGNED NOT NULL,
    sia_uri TEXT,
    parent_resource_class TEXT,
    parent_id BIGINT UNSIGNED,
    PRIMARY KEY (ca_id),
    CONSTRAINT ca_parent_id FOREIGN KEY (parent_id) REFERENCES parent (parent_id) ON DELETE CASCADE
) ENGINE=InnoDB;

```

```

CREATE TABLE ca_detail (
  ca_detail_id      SERIAL NOT NULL,
  public_key        LONGBLOB,
  private_key_id    LONGBLOB,
  latest_crl        LONGBLOB,
  crl_published     DATETIME,
  latest_ca_cert    LONGBLOB,
  manifest_private_key_id LONGBLOB,
  manifest_public_key LONGBLOB,
  latest_manifest_cert LONGBLOB,
  latest_manifest   LONGBLOB,
  manifest_published DATETIME,
  state            ENUM ('pending', 'active', 'deprecated', 'revoked') NOT NULL,
  ca_cert_uri      TEXT,
  ca_id            BIGINT UNSIGNED NOT NULL,
  PRIMARY KEY      (ca_detail_id),
  CONSTRAINT       ca_detail_ca_id
  FOREIGN KEY      (ca_id) REFERENCES ca (ca_id) ON DELETE CASCADE
) ENGINE=InnoDB;

CREATE TABLE child (
  child_id          SERIAL NOT NULL,
  child_handle      VARCHAR(255) NOT NULL,
  bpki_cert         LONGBLOB,
  bpki_glue         LONGBLOB,
  self_id           BIGINT UNSIGNED NOT NULL,
  bsc_id            BIGINT UNSIGNED NOT NULL,
  PRIMARY KEY      (child_id),
  CONSTRAINT       child_bsc_id
  FOREIGN KEY      (bsc_id) REFERENCES bsc (bsc_id) ON DELETE CASCADE,
  CONSTRAINT       child_self_id
  FOREIGN KEY      (self_id) REFERENCES self (self_id) ON DELETE CASCADE,
  UNIQUE          (self_id, child_handle)
) ENGINE=InnoDB;

CREATE TABLE child_cert (
  child_cert_id     SERIAL NOT NULL,
  cert              LONGBLOB NOT NULL,
  published         DATETIME,
  ski              TINYBLOB NOT NULL,
  child_id          BIGINT UNSIGNED NOT NULL,
  ca_detail_id      BIGINT UNSIGNED NOT NULL,
  PRIMARY KEY      (child_cert_id),
  CONSTRAINT       child_cert_ca_detail_id
  FOREIGN KEY      (ca_detail_id) REFERENCES ca_detail (ca_detail_id) ON DELETE CASCADE,
  CONSTRAINT       child_cert_child_id
  FOREIGN KEY      (child_id) REFERENCES child (child_id) ON DELETE CASCADE
) ENGINE=InnoDB;

CREATE TABLE revoked_cert (
  revoked_cert_id   SERIAL NOT NULL,
  serial            BIGINT UNSIGNED NOT NULL,
  revoked           DATETIME NOT NULL,
  expires           DATETIME NOT NULL,
  ca_detail_id      BIGINT UNSIGNED NOT NULL,
  PRIMARY KEY      (revoked_cert_id),

```

```

CONSTRAINT
FOREIGN KEY
) ENGINE=InnoDB;

CREATE TABLE roa (
  roa_id
  asn
  cert
  roa
  published
  self_id
  ca_detail_id
  PRIMARY KEY
  CONSTRAINT
  FOREIGN KEY
  CONSTRAINT
  FOREIGN KEY
) ENGINE=InnoDB;

revoked_cert_ca_detail_id
(ca_detail_id) REFERENCES ca_detail (ca_detail_id) ON DELETE CASCADE

SERIAL NOT NULL,
BIGINT UNSIGNED,
LONGBLOB,
LONGBLOB,
DATETIME,
BIGINT UNSIGNED NOT NULL,
BIGINT UNSIGNED NOT NULL,
(roa_id),
roa_self_id
(self_id) REFERENCES self (self_id) ON DELETE CASCADE,
roa_ca_detail_id
(ca_detail_id) REFERENCES ca_detail (ca_detail_id) ON DELETE CASCADE

CREATE TABLE roa_prefix (
  prefix
  prefixlen
  max_prefixlen
  version
  roa_id
  PRIMARY KEY
  CONSTRAINT
  FOREIGN KEY
) ENGINE=InnoDB;

VARCHAR(40) NOT NULL,
TINYINT NOT NULL,
TINYINT NOT NULL,
TINYINT NOT NULL,
BIGINT UNSIGNED NOT NULL,
(roa_id, prefix, prefixlen, max_prefixlen),
roa_prefix_roa_id
(roa_id) REFERENCES roa (roa_id) ON DELETE CASCADE

-- Local Variables:
-- indent-tabs-mode: nil
-- End:

```

## 7.2 pubd SQL Schema




Figure 2: Diagram of pubd.sql



```
-- $Id: pubd.sql 2502 2009-06-08 03:56:26Z sra $

-- Copyright (C) 2008 American Registry for Internet Numbers ("ARIN")
--
-- Permission to use, copy, modify, and distribute this software for any
-- purpose with or without fee is hereby granted, provided that the above
-- copyright notice and this permission notice appear in all copies.
--
-- THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
-- REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
-- AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
-- INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
-- LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
-- OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
-- PERFORMANCE OF THIS SOFTWARE.

-- SQL objects needed by pubd.py.

-- The config table is weird because we're really only using it
-- to store one BPKI CRL, but putting this here lets us use a lot of
-- existing machinery and the alternatives are whacky in other ways.

DROP TABLE IF EXISTS client;
DROP TABLE IF EXISTS config;

CREATE TABLE config (
    config_id SERIAL NOT NULL,
    bpki_crl LONGBLOB,
    PRIMARY KEY (config_id)
) ENGINE=InnoDB;

CREATE TABLE client (
    client_id SERIAL NOT NULL,
    client_handle VARCHAR(255) NOT NULL,
    base_uri TEXT,
    bpki_cert LONGBLOB,
    bpki_glue LONGBLOB,
    PRIMARY KEY (client_id),
    UNIQUE (client_handle)
) ENGINE=InnoDB;

-- Local Variables:
-- indent-tabs-mode: nil
-- End:
```

## 7.3 irdbd SQL Schema




Figure 3: Diagram of irdbd.sql

```

-- $Id: irdbd.sql 2906 2009-12-23 06:31:32Z sra $

-- Copyright (C) 2007-2008 American Registry for Internet Numbers ("ARIN")
--
-- Permission to use, copy, modify, and distribute this software for any
-- purpose with or without fee is hereby granted, provided that the above
-- copyright notice and this permission notice appear in all copies.
--
-- THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH
-- REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
-- AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT,
-- INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
-- LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
-- OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
-- PERFORMANCE OF THIS SOFTWARE.

-- SQL objects needed by irdbd.py. You only need this if you're using
-- irdbd.py as your IRDB; if you have a "real" backend you can do
-- anything you like so long as you implement the relevant portion of
-- the left-right protocol.

```

```
-- DROP TABLE commands must be in correct (reverse dependency) order
-- to satisfy FOREIGN KEY constraints.
```

```
DROP TABLE IF EXISTS roa_request_prefix;
DROP TABLE IF EXISTS roa_request;
DROP TABLE IF EXISTS registrant_net;
DROP TABLE IF EXISTS registrant_asn;
DROP TABLE IF EXISTS registrant;
```

```
CREATE TABLE registrant (
    registrant_id          SERIAL NOT NULL,
    registrant_handle      VARCHAR(255) NOT NULL,
    registrant_name        TEXT,
    registry_handle        VARCHAR(255),
    valid_until            DATETIME NOT NULL,
    PRIMARY KEY            (registrant_id),
    UNIQUE                 (registry_handle, registrant_handle)
) ENGINE=InnoDB;
```

```
CREATE TABLE registrant_asn (
    registrant_asn_id      SERIAL NOT NULL,
    start_as               BIGINT UNSIGNED NOT NULL,
    end_as                 BIGINT UNSIGNED NOT NULL,
    registrant_id          BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY            (registrant_asn_id),
    CONSTRAINT             registrant_asn_registrant_id
    FOREIGN KEY            (registrant_id) REFERENCES registrant (registrant_id) ON DELETE CASCADE
) ENGINE=InnoDB;
```

```
CREATE TABLE registrant_net (
    registrant_net_id      SERIAL NOT NULL,
    start_ip               VARCHAR(40) NOT NULL,
    end_ip                 VARCHAR(40) NOT NULL,
    version                TINYINT UNSIGNED NOT NULL,
    registrant_id          BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY            (registrant_net_id),
    CONSTRAINT             registrant_net_registrant_id
    FOREIGN KEY            (registrant_id) REFERENCES registrant (registrant_id) ON DELETE CASCADE
) ENGINE=InnoDB;
```

```
CREATE TABLE roa_request (
    roa_request_id         SERIAL NOT NULL,
    roa_request_handle     VARCHAR(255) NOT NULL,
    asn                   BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY            (roa_request_id)
) ENGINE=InnoDB;
```

```
CREATE TABLE roa_request_prefix (
    prefix                 VARCHAR(40) NOT NULL,
    prefixlen              TINYINT NOT NULL,
    max_prefixlen          TINYINT NOT NULL,
    version                TINYINT NOT NULL,
    roa_request_id         BIGINT UNSIGNED NOT NULL,
    PRIMARY KEY            (roa_request_id, prefix, prefixlen, max_prefixlen),
    CONSTRAINT             roa_request_prefix_roa_request_id
    FOREIGN KEY            (roa_request_id) REFERENCES roa_request (roa_request_id) ON DELETE CASCADE
```

```
) ENGINE=InnoDB;
-- Local Variables:
-- indent-tabs-mode: nil
-- End:
```

## 8 BPKI model

The "business PKI" (BPKI) is the PKI used to authenticate communication on the up-down, left-right, and publication protocols.

BPKI certificates are not resource PKI (RPKI) certificates. The BPKI is a separate PKI that represents relationships between the various entities involved in the production side of the RPKI system. In most cases the BPKI tree will follow existing business relationships, hence the name "BPKI".


Setup of the BPKI is handled by the back end; for the most `rpkid` and `pubd` just use the result. The one place where the engines are directly involved in creation of new BPKI certificates is in the production of end-entity certificates for use by the engines.

There are a few design principals that underly the chosen BPKI model:

- Each engine should rely on a single BPKI trust anchor which is controlled by the back end entity that runs the engine; all other trust material should be cross-certified into the engine's BPKI tree.
- Private keys must never transit the network.
- Except for end entity certificates, the engine should only have access to the BPKI certificates; in particular, the private key for the BPKI trust anchor should not be accessible to the engine.
- The number of BPKI keys and certificates that the engine has to manage should be no larger than is necessary.

`rpkid`'s hosting model adds an additional constraint: `rpkid`'s BPKI trust anchor belongs to the entity operating `rpkid`, but the entities hosted by `rpkid` should have control of their own BPKI private keys. This implies the need for an additional layer of BPKI certificate hierarchy within `rpkid`.

Here is a simplified picture of what the BPKI might look like for `rpkid` operator that hosts two entities, "Alice" and "Ellen":



Black objects belong to the hosting entity, blue objects belong to the hosted entities, red objects are cross-certified objects from the hosted entities' peers. The arrows indicate certificate issuance: solid arrows are the ones that will be used for validation, dotted arrows show the origin of the EE certificates that `pubd` uses to sign CMS and TLS messages.


There's one nasty bit where the model had to bend to fit the current state of the underlying protocols: it's not possible to use exactly the same BPKI keys and certificates for HTTPS and CMS. The reason for this is simple: each hosted entity has its own BPKI, as does the hosting entity, but the HTTPS listener is shared. The only ways to avoid sharing the HTTPS server certificate would be to use separate listeners for each hosted entity, which scales poorly, or to rely on the TLS "Server Name Indication" extension (RFC 4366 3.1) which is not yet widely implemented.

The certificate tree looks complicated, but the set of certificates needed to build any particular validation chain is obvious, again excepting the HTTPS server case, where the client certificate is the first hint that the engine has of the client's identity, so the server must be prepared to accept any current client certificate.

Detailed instructions on how to build a BPKI are beyond the scope of this document, but one can handle simple cases using the OpenSSL command line tool and `cross-certify.py`; the latter is a tool designed specifically for the purpose of generating the cross-certification certificates needed to splice foreign trust material into a BPKI tree.

The BPKI tree for `pubd` instance is similar to the BPKI tree for `rpkiid` instance, but is a bit simpler, as `pubd` does not provide hosting in the same sense that `rpkiid` does: `pubd` is a relatively simple server that publishes objects as instructed by its clients.

Here's a simplified picture of what the BPKI might look like for `pubd` operator that serves two clients, "Alice" and "Bob":



While it is likely that RIRs (at least) will operate both `pkid` and `pubd` instances, the two functions are conceptually separate. As far as `pubd` is concerned, it doesn't matter who operates the `pkid` instance; `pubd` just has clients, each of which has trust material that has been cross-certified into `pubd`'s BPKI. Similarly, `pkid` doesn't really care who operates a `pubd` instance that it's been configured to use, it just treats `pubd` as a foreign BPKI whose trust material has to be cross-certified into its own BPKI. Cross-certification itself is done by the back end operator, using `cross_certify` or some equivalent tool; the resulting BPKI certificates are configured into `pkid` and `pubd` via the left-right protocol and the control subprotocol of the `publication` protocol, respectively.

Because the BPKI tree is almost entirely controlled by the operating entity, CRLs are not necessary for most of the BPKI. The one exception to this is the EE certificates issued under the cross-certification points. These EE certificates are generated by the peer, not the local operator, and thus require CRLs. Because of this, `pkid` and `pubd` require regular updates of certain BPKI CRLs, again via the left-right and `publication` control protocols.

Because the left-right protocol and the `publication` control subprotocol are used to configure BPKI certificates and CRLs, they cannot themselves use certificates and CRLs configured in this way. This is why the configuration files for `pkid` and `pubd` require static configuration of the left-right and `publication` control certificates.

## 9 Namespace Documentation

### 9.1 Package irbe\_cli

#### Classes

- class [bsc\\_elt](#)
- class [caller](#)
- class [certificate\\_elt](#)
- class [child\\_elt](#)
- class [client\\_elt](#)
- class [cmd\\_elt\\_mixin](#)
- class [cmd\\_msg\\_mixin](#)
- class [config\\_elt](#)
- class [crl\\_elt](#)
- class [left\\_right\\_cms\\_msg](#)
- class [left\\_right\\_msg](#)
- class [left\\_right\\_sax\\_handler](#)
- class [list\\_published\\_objects\\_elt](#)
- class [manifest\\_elt](#)
- class [parent\\_elt](#)
- class [publication\\_cms\\_msg](#)
- class [publication\\_msg](#)
- class [publication\\_sax\\_handler](#)
- class [reply\\_elt\\_mixin](#)
- class [report\\_error\\_elt](#)
- class [repository\\_elt](#)
- class [roa\\_elt](#)
- class [self\\_elt](#)
- class [UsageWrapper](#)

#### Functions

- def [usage](#)

#### Variables

- list [argv](#) = sys.argv[1:]
- tuple [call\\_pubd](#)
- tuple [call\\_rpkid](#)
- tuple [cfg](#) = [rpki.config.parse\(cfg\\_file, "irbe\\_cli"\)](#)
- string [cfg\\_file](#) = "irbe.conf"

- `pem_out= None`
- `q_msg= q_msg_left_right`
- `tuple q_msg_left_right= left_right_msg.query()`
- `tuple q_msg_publication= publication_msg.query()`
- `list q_pdu= left_right_msg.pdu[argv[0]]`
- `list top_opts= ["con g=", "help", "pem_out", "quiet", "verbose"]`
- `tuple usage_1l = UsageWrapper(subsequent_indent = "*" 4)`
- `verbose= True`

### 9.1.1 Detailed Description

Command line IR back-end control program for rpkid and pubd.

\$Id: irbe\_cli.py 2799 2009-09-30 02:33:36Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.1.2 Function Documentation

#### 9.1.2.1 `def irbe_cli.usage (code= 1)`

Definition at line 275 of file `irbe_cli.py`.



### 9.1.3 Variable Documentation

#### 9.1.3.1 tuple irbe\_cli::argv = sys.argv[1:]

Definition at line 294 of file irbe\_cli.py.

#### 9.1.3.2 tuple irbe\_cli.call\_pubd

Initial value:

```
rpki.async.sync_wrapper(caller(
    cms_class = publication_cms_msg,
    client_key = rpki.x509.RSA( Auto_file = cfg.get("pubd-irbe-key")),
    client_cert = rpki.x509.X509(Auto_file = cfg.get("pubd-irbe-cert")),
    server_ta = rpki.x509.X509(Auto_file = cfg.get("pubd-bpki-ta")),
    server_cert = rpki.x509.X509(Auto_file = cfg.get("pubd-cert")),
    url = cfg.get("pubd-url")))
```

Definition at line 349 of file irbe\_cli.py.

#### 9.1.3.3 tuple irbe\_cli.call\_rpkid

Initial value:

```
rpki.async.sync_wrapper(caller(
    cms_class = left_right_cms_msg,
    client_key = rpki.x509.RSA( Auto_file = cfg.get("rpkid-irbe-key")),
    client_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-irbe-cert")),
    server_ta = rpki.x509.X509(Auto_file = cfg.get("rpkid-bpki-ta")),
    server_cert = rpki.x509.X509(Auto_file = cfg.get("rpkid-cert")),
    url = cfg.get("rpkid-url")))
```

Definition at line 337 of file irbe\_cli.py.

#### 9.1.3.4 tuple irbe\_cli.cfg = rpki.config.parser(cfg\_file, "irbe\_cli")

Definition at line 318 of file irbe\_cli.py.

#### 9.1.3.5 irbe\_cli.cfg\_file = "irbe.conf"

Definition at line 299 of file irbe\_cli.py.

9.1.3.6 `irbe_cli.pem_out = None`

Definition at line 39 of file `irbe_cli.py`.

9.1.3.7 `irbe_cli.q_msg = q_msg_left_right`

Definition at line 326 of file `irbe_cli.py`.

9.1.3.8 `tuple irbe_cli.q_msg_left_right = left_right_msg.query()`

Definition at line 320 of file `irbe_cli.py`.

9.1.3.9 `tuple irbe_cli.q_msg_publication = publication_msg.query()`

Definition at line 321 of file `irbe_cli.py`.

9.1.3.10 `list irbe_cli::q_pdu = left_right_msg.pdus[argv[0]]`

Definition at line 325 of file `irbe_cli.py`.

9.1.3.11 `list irbe_cli.top_opts = ["con g=", "help", "pem_out=", "quiet",  
"verbose"]`

Definition at line 273 of file `irbe_cli.py`.

9.1.3.12 `tuple irbe_cli.usage_II = UsageWrapper(subsequent_indent = " * 4)`

Definition at line 87 of file `irbe_cli.py`.

## 9.1.3.13 irbe\_cli.verbose = True

Definition at line 300 of file irbe\_cli.py.

## 9.2 Package irdbd

### Functions

- def `handle_list_resources`
- def `handle_list_roa_requests`
- def `handler`

### Variables

- tuple `bpki_ta` = `rpki.x509.X509`(`Auto_le` = `cfg.get("bpki-ta")`)
- tuple `cfg` = `rpki.config.parse(cfg_le, "irdbd")`
- string `cfg_le` = "irdbd.conf"
- tuple `client_ta` = (`bpki_ta`, `rpkid_cert`)
- tuple `cur` = `db.cursor()`
- tuple `db`
- dictionary `handle_dispatch`
- tuple `handlers` = ((`u.path`, `handler`),)
- string `host` = "localhost"
- tuple `irdbd_cert` = `rpki.x509.X509`(`Auto_le` = `cfg.get("irdbd-cert")`)
- tuple `irdbd_key` = `rpki.x509.RSA`(`Auto_le` = `cfg.get("irdbd-key")`)
- int `port` = 443
- tuple `rpkid_cert` = `rpki.x509.X509`(`Auto_le` = `cfg.get("rpkid-cert")`)
- `server_cert` = `irdbd_cert`
- tuple `startup_msg` = `cfg.get("startup-message", "")`
- tuple `u` = `urlparse.urlparse(cfg.get("https-url"))`

### 9.2.1 Detailed Description

IR database daemon.

Usage: `python irdbd.py [ { -c | --config } configfile ] [ { -h | --help } ]`

Default configuration file is `irdbd.conf`, override with `--config` option.

\$Id: irdbd.py 2913 2009-12-28 20:55:38Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.2.2 Function Documentation

### 9.2.2.1 def irdbd.handle\_list\_resources(*q\_pdu*, *r\_msg*)

Definition at line 53 of file irdbd.py.

### 9.2.2.2 def irdbd.handle\_list\_roa\_requests(*q\_pdu*, *r\_msg*)

Definition at line 90 of file irdbd.py.

### 9.2.2.3 def irdbd.handler(*query*, *path*, *cb*)

Definition at line 119 of file irdbd.py.

### 9.2.3 Variable Documentation

9.2.3.1 tuple `irdbd.bpki_ta` = `rpki.x509.X509(Auto_ le = cfg.get("bpki-ta"))`

Definition at line 201 of file `irdbd.py`.

9.2.3.2 tuple `irdbd.cfg` = `rpki.config.parser(cfg_ le, "irdbd")`

Definition at line 186 of file `irdbd.py`.

9.2.3.3 `irdbd.cfg_ le` = `"irdbd.conf"`

Definition at line 170 of file `irdbd.py`.

9.2.3.4 tuple `irdbd.client_ta` = `(bpki_ta, rpki_cert)`

Definition at line 217 of file `irdbd.py`.

9.2.3.5 tuple `irdbd.cur` = `db.cursor()`

Definition at line 198 of file `irdbd.py`.

9.2.3.6 tuple `irdbd.db`

Initial value:

```
MySQLdb.connect(user = cfg.get("sql-username"),
                 db    = cfg.get("sql-database"),
                 passwd = cfg.get("sql-password"))
```

Definition at line 194 of file `irdbd.py`.

9.2.3.7 dictionary `irdbd.handle_dispatch`

Initial value:

```
{  
    rpki.left_right.list_resources_elt : handle_list_resources,  
    rpki.left_right.list_roa_requests_elt : handle_list_roa_requests }  
}
```

Definition at line 115 of file irdbd.py.

9.2.3.8 tuple irdbd.handlers = ((u.path, handler),)

Definition at line 220 of file irdbd.py.

9.2.3.9 string irdbd.host = "localhost"

Definition at line 218 of file irdbd.py.

9.2.3.10 tuple irdbd.irdbd\_cert = rpki.x509.X509(Auto\_load =  
 cfg.get("irdbd-cert"))

Definition at line 203 of file irdbd.py.

9.2.3.11 tuple irdbd.irdbd\_key = rpki.x509.RSA( Auto\_load =  
 cfg.get("irdbd-key"))

Definition at line 204 of file irdbd.py.

9.2.3.12 int irdbd.port = 443

Definition at line 219 of file irdbd.py.

9.2.3.13 tuple irdbd.rpkid\_cert = rpki.x509.X509(Auto\_load =  
 cfg.get("rpkid-cert"))

Definition at line 202 of file irdbd.py.

9.2.3.14 `irdbd.server_cert = irdbd_cert,`

Definition at line 216 of `le irdbd.py`.

9.2.3.15 `tuple irdbd.startup_msg = cfg.get("startup-message", "")`

Definition at line 188 of `le irdbd.py`.

9.2.3.16 `tuple irdbd.u = urlparse.urlparse(cfg.get("https-url"))`

Definition at line 206 of `le irdbd.py`.

## 9.3 Package pubd

### Classes

- class `pubd_context`

### Functions

- def `main`

### Variables

- string `cfg_le = "pubd.conf"`
- `profile = False`

### 9.3.1 Detailed Description

RPKI publication engine.

```
Usage: python pubd.py [ { -c | --config } configfile ]
                    [ { -h | --help } ]
                    [ { -p | --profile } outputfile ]
```

Default configuration file is `pubd.conf`, override with `--config` option.

\$Id: pubd.py 2913 2009-12-28 20:55:38Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.3.2 Function Documentation

#### 9.3.2.1 `def pubd.main ()`

Definition at line 172 of `le pubd.py`.

### 9.3.3 Variable Documentation

#### 9.3.3.1 `pubd.cfg_le = "pubd.conf"`

Definition at line 153 of `le pubd.py`.

#### 9.3.3.2 `pubd.pro_le = False`

Definition at line 154 of `le pubd.py`.



## 9.4 Package rootd

### Classes

- class `cms_msg`
- class `issue_pdu`
- class `list_pdu`
- class `message_pdu`
- class `revoke_pdu`
- class `sax_handler`

### Functions

- def `compose_response`
- def `del_subject_cert`
- def `del_subject_pkcs10`
- def `get_root_cert`
- def `get_subject_cert`
- def `get_subject_pkcs10`
- def `issue_subject_cert_maybe`
- def `root_newer_than_subject`
- def `set_subject_cert`
- def `set_subject_pkcs10`
- def `up_down_handler`

### Variables

- tuple `bpki_ta` = `rpki.x509.X509`(`Auto_le` = `cfg.get("bpki-ta")`)
- tuple `cfg` = `rpki.config.parse`(`cfg_le`, "rootd")
- string `cfg_le` = "rootd.conf"
- tuple `child_bpki_cert` = `rpki.x509.X509`(`Auto_le` = `cfg.get("child-bpki-cert")`)
- tuple `client_ta` = (`bpki_ta`, `child_bpki_cert`)
- `handlers` = `up_down_handler`
- `host` = `https_server_host`
- tuple `https_server_host` = `cfg.get("serverhost", "")`
- tuple `https_server_port` = `int(cfg.get("serverport"))`
- `port` = `https_server_port`
- tuple `rootd_bpki_cert` = `rpki.x509.X509`(`Auto_le` = `cfg.get("rootd-bpki-cert")`)
- tuple `rootd_bpki_crl` = `rpki.x509.CRL`(`Auto_le` = `cfg.get("rootd-bpki-crl")`)
- tuple `rootd_bpki_key` = `rpki.x509.RSA`(`Auto_le` = `cfg.get("rootd-bpki-key")`)
- tuple `rpki_base_uri` = `cfg.get("rpki-base-uri", "rsync://" + rpki_class_name + ".invalid/")`

- tuple `rpki_class_name` = `cfg.get("rpki-class-name", "wombat")`
- `rpki_root_cert` = `None`
- tuple `rpki_root_cert_le` = `cfg.get("rpki-root-cert")`
- tuple `rpki_root_cert_uri` = `cfg.get("rpki-root-cert-uri", rpki_base_uri + "Root.cer")`
- tuple `rpki_root_crl` = `cfg.get("rpki-root-crl", "Root.crl")`
- tuple `rpki_root_dir` = `cfg.get("rpki-root-dir")`
- tuple `rpki_root_key` = `rpki.x509.RSA(Auto_le = cfg.get("rpki-root-key"))`
- tuple `rpki_root_manifest` = `cfg.get("rpki-root-manifest", "Root.mnf")`
- tuple `rpki_subject_cert` = `cfg.get("rpki-subject-cert", "Child.cer")`
- tuple `rpki_subject_lifetime` = `rpki.sundial.timedelta.parse(cfg.get("rpki-subject-lifetime", "30d"))`
- tuple `rpki_subject_pkcs10` = `cfg.get("rpki-subject-pkcs10", "Child.pkcs10")`
- tuple `rpki_subject_regen` = `rpki.sundial.timedelta.parse(cfg.get("rpki-subject-regen", rpki_subject_lifetime.convert_to_seconds() / 2))`
- `server_cert` = `rootd_bpki_cert`

#### 9.4.1 Detailed Description

Trivial RPKI up-down protocol root server, for testing. Not suitable for production use. Overrides a bunch of method definitions from the `rpki`. \* classes in order to reuse as much code as possible.

Usage: `python rootd.py [ { -c | --config } configfile ] [ { -h | --help } ]`

Default configuration file is `rootd.conf`, override with `--config` option.

\$Id: rootd.py 2913 2009-12-28 20:55:38Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY

AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

#### 9.4.2 Function Documentation

##### 9.4.2.1 `def rootd.compose_response(msg pkcs10= None)`

Definition at line 175 of file rootd.py.

##### 9.4.2.2 `def rootd.del_subject_cert ()`

Definition at line 72 of file rootd.py.

##### 9.4.2.3 `def rootd.del_subject_pkcs10 ()`

Definition at line 91 of file rootd.py.

##### 9.4.2.4 `def rootd.get_root_cert ()`

Definition at line 48 of file rootd.py.

##### 9.4.2.5 `def rootd.get_subject_cert ()`

Definition at line 56 of file rootd.py.

##### 9.4.2.6 `def rootd.get_subject_pkcs10 ()`

Definition at line 77 of file rootd.py.

9.4.2.7 `def rootd.issue_subject_cert_maybe_new_pkcs10()`

Definition at line 98 of file rootd.py.

9.4.2.8 `def rootd.root_newer_than_subject ()`

Definition at line 53 of file rootd.py.

9.4.2.9 `def rootd.set_subject_cert(cert)`

Definition at line 65 of file rootd.py.

9.4.2.10 `def rootd.set_subject_pkcs10(pkcs10)`

Definition at line 85 of file rootd.py.

9.4.2.11 `def rootd.up_down_handler (query, path, cb)`

Definition at line 238 of file rootd.py.

### 9.4.3 Variable Documentation

9.4.3.1 `tuple rootd.bpk_i_ta = rpki.x509.X509(Auto_ le = cfg.get("bpki-ta"))`

Definition at line 288 of file rootd.py.

9.4.3.2 `tuple rootd.cfg = rpki.config.parser(cfg_ le, "rootd")`

Definition at line 284 of file rootd.py.

9.4.3.3 `rootd.cfg_file = "rootd.conf"`

Definition at line 268 of file `rootd.py`.

9.4.3.4 `tuple rootd.child_bpki_cert = rpki.x509.X509(Auto_load =  
cfg.get("child-bpki-cert"))`

Definition at line 292 of file `rootd.py`.

9.4.3.5 `tuple rootd.client_ta = (bpki_ta, child_bpki_cert)`

Definition at line 316 of file `rootd.py`.

9.4.3.6 `rootd.handlers = up_down_handler)`

Definition at line 319 of file `rootd.py`.

9.4.3.7 `rootd.host = https_server_host,`

Definition at line 317 of file `rootd.py`.

9.4.3.8 `tuple rootd.https_server_host = cfg.get("server-host", "")`

Definition at line 294 of file `rootd.py`.

9.4.3.9 `tuple rootd.https_server_port = int(cfg.get("server-port"))`

Definition at line 295 of file `rootd.py`.

9.4.3.10 `rootd.port = https_server_port,`

Definition at line 318 of file `rootd.py`.

9.4.3.11 `tuple rootd.rootd_bpki_cert = rpki.x509.X509(Auto_load =  
cfg.get("rootd-bpki-cert"))`

Definition at line 290 of file `rootd.py`.

9.4.3.12 `tuple rootd.rootd_bpki_crl = rpki.x509.CRL(Auto_load =  
cfg.get("rootd-bpki-crl"))`

Definition at line 291 of file `rootd.py`.

9.4.3.13 `tuple rootd.rootd_bpki_key = rpki.x509.RSA(Auto_load =  
cfg.get("rootd-bpki-key"))`

Definition at line 289 of file `rootd.py`.

9.4.3.14 `tuple rootd.rpki_base_uri = cfg.get("rpki-base-uri", "rsync:///" +  
rpki_class_name + ".invalid/")`

Definition at line 300 of file `rootd.py`.

9.4.3.15 `tuple rootd.rpki_class_name = cfg.get("rpki-class-name", "wombat")`

Definition at line 297 of file `rootd.py`.

9.4.3.16 `rootd.rpki_root_cert = None`

Definition at line 46 of file `rootd.py`.

```
9.4.3.17 tuple rootd.rpki_root_cert_le = cfg.get("rpki-root-cert")
```

Definition at line 303 of file rootd.py.

```
9.4.3.18 tuple rootd.rpki_root_cert_uri = cfg.get("rpki-root-cert-uri",  
        rpki_base_uri + "Root.cer")
```

Definition at line 304 of file rootd.py.

```
9.4.3.19 tuple rootd.rpki_root_crl = cfg.get("rpki-root-crl", "Root.crl")
```

Definition at line 307 of file rootd.py.

```
9.4.3.20 tuple rootd.rpki_root_dir = cfg.get("rpki-root-dir")
```

Definition at line 299 of file rootd.py.

```
9.4.3.21 tuple rootd.rpki_root_key = rpki.x509.RSA( Auto_le =  
        cfg.get("rpki-root-key"))
```

Definition at line 302 of file rootd.py.

```
9.4.3.22 tuple rootd.rpki_root_manifest = cfg.get("rpki-root-manifest",  
        "Root.mnf")
```

Definition at line 306 of file rootd.py.

```
9.4.3.23 tuple rootd.rpki_subject_cert = cfg.get("rpki-subject-cert",  
        "Child.cer")
```

Definition at line 308 of file rootd.py.

```
9.4.3.24 tuple rootd.rpki_subject_lifetime =
        rpki.sundial.timedelta.parse(cfg.get("rpki-subject-
        lifetime", "30d"))
```

Definition at line 311 of file rootd.py.

```
9.4.3.25 tuple rootd.rpki_subject_pkcs10 = cfg.get("rpki-subject-pkcs10",
        "Child.pkcs10")
```

Definition at line 309 of file rootd.py.

```
9.4.3.26 tuple rootd.rpki_subject_regen =
        rpki.sundial.timedelta.parse(cfg.get("rpki-subject-
        regen", rpki_subject_lifetime.convert_to_seconds() /
        2))
```

Definition at line 312 of file rootd.py.

```
9.4.3.27 rootd.server_cert = rootd_bpki_cert,
```

Definition at line 315 of file rootd.py.

## 9.5 Package rpki

### Packages

- package [async](#)
- package [con g](#)
- package [exceptions](#)
- package [https](#)
- package [ipaddr](#)
- package [left\\_right](#)
- package [log](#)
- package [manifest](#)
- package [oids](#)
- package [publication](#)



- package [relaxng](#)
- package [resource\\_set](#)
- package [roa](#)
- package [rpki\\_engine](#)
- package [sql](#)
- package [sundial](#)
- package [up\\_down](#)
- package [x509](#)
- package [xml\\_utils](#)

## 9.6 Package rpki.async

### Classes

- class [gc\\_summary](#)
- class [iterator](#)
- class [sync\\_wrapper](#)
- class [timer](#)

### Functions

- def [\\_raiseExitNow](#)
- def [defer](#)
- def [event\\_loop](#)
- def [exit\\_event\\_loop](#)
- def [run\\_deferred](#)

### Variables

- list [deferred\\_queue](#) []  
List to hold deferred actions.
- [ExitNow](#) = `asyncore.ExitNow`

### 9.6.1 Detailed Description

Utilities for event-driven programming.

\$Id: async.py 2926 2010-01-04 22:28:34Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any

purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.6.2 Function Documentation

#### 9.6.2.1 `def rpki.async._raiseExitNow (signum, frame) [private]`

Signal handler for `event_loop()`.

Definition at line 264 of `le_async.py`.

#### 9.6.2.2 `def rpki.async.defer (thunk)`

Defer an action until the next pass through the event loop.

Definition at line 245 of `le_async.py`.

#### 9.6.2.3 `def rpki.async.event_loop (catch_signals=(signal.SIGINT, signal.SIGTERM))`

Replacement for `asyncore.loop()`, adding timer and signal support.

Definition at line 268 of `le_async.py`.

#### 9.6.2.4 `def rpki.async.exit_event_loop ()`

Force exit from `event_loop()`.

Definition at line 343 of `le_async.py`.

### 9.6.2.5 def rpki.async.run\_deferred ()

Run deferred actions.

Definition at line 251 of file async.py.

### 9.6.3 Variable Documentation

#### 9.6.3.1 rpki::async::deferred\_queue = []

List to hold deferred actions. We used to do this with `time` queue, but that appears to confuse the garbage collector, and is overengineering for simple deferred actions in any case.

Definition at line 243 of file async.py.

#### 9.6.3.2 rpki::async.ExitNow = asyncore.ExitNow

Definition at line 24 of file async.py.

## 9.7 Package rpki.conf

### Classes

- class `parser`

#### 9.7.1 Detailed Description

Configuration file parsing utilities, layered on top of stock Python ConfigParser module.

\$Id: config.py 2926 2010-01-04 22:28:34Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY

AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.8 Package rpki.exceptions

### Classes

- class [BadClassNameSyntax](#)
- class [BadClientURL](#)
- class [BadContactURL](#)
- class [BadExtension](#)
- class [BadIRDBReply](#)
- class [BadIssueResponse](#)
- class [BadPKCS10](#)
- class [BadPublicationReply](#)
- class [BadQuery](#)
- class [BadSender](#)
- class [BadStatusCode](#)
- class [BadURISyntax](#)
- class [BSCNotFound](#)
- class [BSCNotReady](#)
- class [ChildNotFound](#)
- class [ClassNameMismatch](#)
- class [ClassNameUnknown](#)
- class [ClientNotFound](#)
- class [CMSContentNotSet](#)
- class [CMSCRLNotSet](#)
- class [CMSVerificationFailed](#)
- class [DBConsistencyError](#)
- class [DERObjectConversionError](#)

- classDuplicateObject
- classEmptyPEM
- classEmptyROAPre xList
- classForbiddenURI
- classHandleTranslationError
- classHTTPRequestFailed
- classHTTPSBadVersion
- classHTTPSClientAborted
- classHTTPSUnexpectedState
- classMissingCMSCRL
- classMissingCMSEECert
- classMultipleTLSEECert
- classMustBePre x
- classNoActiveCA
- classNoCoveringCertForROA
- classNoObjectAtURI
- classNotACertificateChain
- classNotFound
- classNotImplementedYet
- classNotInDatabase
- classReceivedTLSCACert
- classRPKI\_Exception
- classServerShuttingDown
- classSKIMismatch
- classSubprocessError
- classTLSValidationError
- classUnexpectedCMSCerts
- classUnexpectedCMSCRLs
- classUnparsableCMSDER
- classUpstreamError
- classWrongEContentType

### 9.8.1 Detailed Description

Exception definitions for RPKI modules.

\$Id: exceptions.py 2907 2009-12-23 20:48:19Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH

REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.9 Package rpki.https

### Classes

- class [http\\_client](#)
- class [http\\_listener](#)
- class [http\\_message](#)
- class [http\\_queue](#)
- class [http\\_request](#)
- class [http\\_response](#)
- class [http\\_server](#)
- class [http\\_stream](#)

### Functions

- def [build\\_https\\_ta\\_cache](#)
- def [client](#)
- def [log\\_method](#)
- def [server](#)

### Variables

- dictionary [client\\_queues](#) = {}
- [debug\\_http](#) = False
- [debug\\_tls\\_certs](#) = False
- tuple [default\\_client\\_timeout](#) = [rpki.sundial.time\\_delta\(minutes = 15\)](#)

- tuple `default_http_version` = (1, 0)
- tuple `default_server_timeout` = rpki.sundial.timeDelta(minutes = 20)
- string `rpki_content_type` = "application/x-rpki"
- bool `want_persistent_client` = False
- bool `want_persistent_server` = False

### 9.9.1 Detailed Description

HTTPS utilities, both client and server.

\$Id: https.py 2902 2009-12-22 21:57:32Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.9.2 Function Documentation

#### 9.9.2.1 `def rpki.https.build_https_ta_cache(certs)`

Package up a collection of certificates into a form suitable for use as a dynamic HTTPS trust anchor set. Precise format of this collection is an internal conspiracy within the `rpki.https` module; at one point it was a `POW.X509Store` object, at the moment it's a Python set, what it will be tomorrow is nobody else's business.

Definition at line 766 of file https.py.

```
9.9.2.2 def rpki.https.client (msg client_key client_cert server_ta url,  
                             callback errback)
```

Open client HTTPS connection, send a message, set up callbacks to handle response.

Definition at line 707 of file https.py.

```
9.9.2.3 def rpki.https.log_method (self, msg logger= rpki.log.debug)
```

Definition at line 169 of file https.py.

```
9.9.2.4 def rpki.https.server (handlers server_key server_cert port, host=  
                             "", client_ta= () , dynamic_https_trust_anchor= None)
```

Run an HTTPS server and wait (forever) for connections.

Definition at line 752 of file https.py.

### 9.9.3 Variable Documentation

```
9.9.3.1 dictionary rpki::https.client_queues = {}
```

Definition at line 705 of file https.py.

```
9.9.3.2 rpki::https.debug_http = False
```

Definition at line 45 of file https.py.

```
9.9.3.3 rpki::https.debug_tls_certs = False
```



Definition at line 48 of file https.py.

```
9.9.3.4 tuple rpki::https.default_client_timeout =  
rpki.sundial.timedelta(minutes = 15)
```

Definition at line 58 of file https.py.

```
9.9.3.5 tuple rpki::https.default_http_version = (1, 0)
```

Definition at line 61 of file https.py.

```
9.9.3.6 tuple rpki::https.default_server_timeout =  
rpki.sundial.timedelta(minutes = 20)
```

Definition at line 59 of file https.py.

```
9.9.3.7 string rpki::https.rpki_content_type = "application/x-rpki"
```

Definition at line 39 of file https.py.

```
9.9.3.8 rpki::https.want_persistent_client = False
```

Definition at line 51 of file https.py.

```
9.9.3.9 rpki::https.want_persistent_server = False
```

Definition at line 52 of file https.py.

## 9.10 Package rpkg.ipaddrs

### Classes

- class [v4addr](#)
- class [v6addr](#)

#### 9.10.1 Detailed Description

Classes to represent IP addresses.

Given some of the other operations we need to perform on them, it's most convenient to represent IP addresses as Python "long" values. The classes in this module just wrap suitable read/write syntax around the underlying "long" type.

These classes also supply a "bits" attribute for use by other code built on these classes; for the most part, IPv6 addresses really are just IPv4 addresses with more bits, so we supply the number of bits once, here, thus avoiding a lot of duplicate code elsewhere.

\$Id: ipaddrs.py 2424 2009-05-11 06:37:32Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.11 Package rpki.left\_right

### Classes

- class [bsc\\_elt](#)
- class [child\\_elt](#)
- class [cms\\_msg](#)
- class [data\\_elt](#)
- class [left\\_right\\_namespace](#)
- class [list\\_published\\_objects\\_elt](#)
- class [list\\_resources\\_elt](#)
- class [list\\_roa\\_requests\\_elt](#)
- class [msg](#)
- class [parent\\_elt](#)
- class [report\\_error\\_elt](#)
- class [repository\\_elt](#)
- class [sax\\_handler](#)
- class [self\\_elt](#)

### Variables

- [enforce\\_strict\\_up\\_down\\_xml\\_send](#) = False

#### 9.11.1 Detailed Description

RPKI "left-right" protocol.

\$Id: left\_right.py 2931 2010-01-06 21:03:14Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.11.2 Variable Documentation

#### 9.11.2.1 `rpki::left_right.enforce_strict_up_down_xml_sender = False`

Definition at line 40 of file `left_right.py`.

## 9.12 Package rpki.log

### Classes

- class `logger`

### Functions

- def `init`
- def `set_trace`
- def `trace`
- def `traceback`

### Variables

- tuple `debug= logger(syslog.LOG_DEBUG)`
- `enable_trace= False`  
Whether call tracing is enabled.
- tuple `error= logger(syslog.LOG_ERR)`
- tuple `info= logger(syslog.LOG_INFO)`
- tuple `note= logger(syslog.LOG_NOTICE)`
- int `pid= 0`
- string `tag= ""`
- `use_syslog= True`  
Whether to use syslog.
- tuple `warn= logger(syslog.LOG_WARNING)`

### 9.12.1 Detailed Description

Logging facilities for RPKI libraries.

\$Id: log.py 2933 2010-01-07 01:00:17Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.12.2 Function Documentation

9.12.2.1 `def rpki.log.init (ident= "rpki" , ags = syslog.LOG_PID , facility = syslog.LOG_DAEMON)`

Initialize logging system.

Definition at line 51 of file log.py.

9.12.2.2 `def rpki.log.set_trace (enable)`

Enable or disable call tracing.

Definition at line 63 of file log.py.

### 9.12.2.3 def rpki.log.trace ()

Execution trace -- where are we now, and whence came we here?

Definition at line 91 of file log.py.

### 9.12.2.4 def rpki.log.traceback ()

Consolidated backtrace facility with a bit of extra info.

Definition at line 100 of file log.py.

## 9.12.3 Variable Documentation

### 9.12.3.1 tuple rpki::log.debug = logger(syslog.LOG\_DEBUG)

Definition at line 89 of file log.py.

### 9.12.3.2 rpki::log::enable\_trace = False

Whether call tracing is enabled.

Definition at line 41 of file log.py.

### 9.12.3.3 tuple rpki::log.error = logger(syslog.LOG\_ERR)

Definition at line 85 of file log.py.

### 9.12.3.4 tuple rpki::log.info = logger(syslog.LOG\_INFO)

Definition at line 88 of file log.py.

9.12.3.5 tuple rpki::log.note = logger(syslog.LOG\_NOTICE)

Definition at line 87 of file log.py.

9.12.3.6 int rpki::log.pid = 0

Definition at line 49 of file log.py.

9.12.3.7 string rpki::log.tag = ""

Definition at line 48 of file log.py.

9.12.3.8 rpki::log::use\_syslog = True

Whether to use syslog.

Definition at line 46 of file log.py.

9.12.3.9 tuple rpki::log.warn = logger(syslog.LOG\_WARNING)

Definition at line 86 of file log.py.

## 9.13 Package rpki.manifest

### Classes

- class [FileAndHash](#)
- class [FilesAndHashes](#)
- class [Manifest](#)

### 9.13.1 Detailed Description

Signed manifests. This is just the ASN.1 encoder, the rest is in rpki.x509 with the rest of the DER\_object code.

Note that rpki.x509.SignedManifest implements the signed manifest; the structures here are just the payload of the CMS eContent field.

\$Id: manifest.py 2424 2009-05-11 06:37:32Z sra \$

Copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.14 Package rpki.oids

### Variables

- tuple `name2oid` = dict((v, k) for k, v in oid2name.items())  
Mapping table of string names to OIDs.
- dictionary `oid2name`  
Mapping table of OIDs to conventional string names.

### 9.14.1 Detailed Description

OID database.

\$Id: oids.py 2424 2009-05-11 06:37:32Z sra \$

Copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.



## 9.14.2 Variable Documentation

9.14.2.1 `rpki::oids::name2oid = dict((v, k) for k, v in oid2name.items())`

Mapping table of string names to OIDs.

Definition at line 58 of file `oids.py`.

9.14.2.2 `rpki::oids::oid2name`

Initial value:

```
{
  (1, 2, 840, 113549, 1, 1, 11) : "sha256WithRSAEncryption",
  (1, 2, 840, 113549, 1, 1, 12) : "sha384WithRSAEncryption",
  (1, 2, 840, 113549, 1, 1, 13) : "sha512WithRSAEncryption",
  (1, 2, 840, 113549, 1, 7, 1) : "id-data",
  (1, 2, 840, 113549, 1, 9, 16) : "id-smime",
  (1, 2, 840, 113549, 1, 9, 16, 1) : "id-ct",
  (1, 2, 840, 113549, 1, 9, 16, 1, 24) : "id-ct-routeOriginAttestation",
  (1, 2, 840, 113549, 1, 9, 16, 1, 26) : "id-ct-rpkiManifest",
  (1, 2, 840, 113549, 1, 9, 16, 1, 28) : "id-ct-xml",
  (1, 3, 6, 1, 5, 5, 7, 1, 1) : "authorityInfoAccess",
  (1, 3, 6, 1, 5, 5, 7, 1, 11) : "subjectInfoAccess",
  (1, 3, 6, 1, 5, 5, 7, 1, 7) : "sbgp-ipAddrBlock",
  (1, 3, 6, 1, 5, 5, 7, 1, 8) : "sbgp-autonomousSysNum",
  (1, 3, 6, 1, 5, 5, 7, 14, 2) : "id-cp-ipAddr-asNumber",
  (1, 3, 6, 1, 5, 5, 7, 48, 2) : "id-ad-calssuers",
  (1, 3, 6, 1, 5, 5, 7, 48, 5) : "id-ad-caRepository",
  (1, 3, 6, 1, 5, 5, 7, 48, 9) : "id-ad-signedObjectRepository",
  (1, 3, 6, 1, 5, 5, 7, 48, 10) : "id-ad-rpkiManifest",
  (1, 3, 6, 1, 5, 5, 7, 48, 11) : "id-ad-signedObject",
  (2, 16, 840, 1, 101, 3, 4, 2, 1) : "id-sha256",
  (2, 5, 29, 14) : "subjectKeyIdentifier",
  (2, 5, 29, 15) : "keyUsage",
  (2, 5, 29, 19) : "basicConstraints",
  (2, 5, 29, 20) : "cRLNumber",
  (2, 5, 29, 31) : "cRLDistributionPoints",
  (2, 5, 29, 32) : "certificatePolicies",
  (2, 5, 29, 35) : "authorityKeyIdentifier",
  (2, 5, 4, 3) : "commonName",
}
```

Mapping table of OIDs to conventional string names.

Definition at line 24 of file `oids.py`.

## 9.15 Package rpki.publication

### Classes

- class [certificate\\_elt](#)
- class [client\\_elt](#)
- class [cms\\_msg](#)
- class [cong\\_elt](#)
- class [control\\_elt](#)
- class [crl\\_elt](#)
- class [manifest\\_elt](#)
- class [msg](#)
- class [publication\\_namespace](#)
- class [publication\\_object\\_elt](#)
- class [report\\_error\\_elt](#)
- class [roa\\_elt](#)
- class [sax\\_handler](#)

### 9.15.1 Detailed Description

RPKI "publication" protocol.

\$Id: publication.py 2935 2010-01-07 17:23:05Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.16 Package rpki.relaxng

### Variables

- tuple [left\\_right](#)  
Parsed RelaxNG [left\\_right](#) schema.
- tuple [publication](#)  
Parsed RelaxNG [publication](#) schema.
- tuple [up\\_down](#)  
Parsed RelaxNG [up\\_down](#) schema.

#### 9.16.1 Variable Documentation

##### 9.16.1.1 rpki::relaxng::left\_right

Parsed RelaxNG [left\\_right](#) schema.

Definition at line 7 of file relaxng.py.

##### 9.16.1.2 rpki::relaxng::publication

Parsed RelaxNG [publication](#) schema.

Definition at line 1171 of file relaxng.py.

##### 9.16.1.3 rpki::relaxng::up\_down

Parsed RelaxNG [up\\_down](#) schema.

Definition at line 917 of file relaxng.py.

## 9.17 Package rpki.resource\_set

### Classes

- class [resource\\_bag](#)

- class `resource_range`
- class `resource_range_as`
- class `resource_range_ip`
- class `resource_range_ipv4`
- class `resource_range_ipv6`
- class `resource_set`
- class `resource_set_as`
- class `resource_set_ip`
- class `resource_set_ipv4`
- class `resource_set_ipv6`
- class `roa_pre_x`
- class `roa_pre_x_ipv4`
- class `roa_pre_x_ipv6`
- class `roa_pre_x_set`
- class `roa_pre_x_set_ipv4`
- class `roa_pre_x_set_ipv6`

#### Functions

- def `_bs2long`
- def `_long2bs`
- def `_rsplit`
- def `test1`
- def `test2`

#### Variables

- string `inherit_token` = "<inherit>"  
Token used to indicate inheritance in read and print syntax.

#### 9.17.1 Detailed Description

Classes dealing with sets of resources.

The basic mechanics of a resource set are the same for any of the resources we handle (ASNs, IPv4 addresses, or IPv6 addresses), so we can provide the same operations on any of them, even though the underlying details vary.

We also provide some basic set operations (union, intersection, etc).

\$Id: resource\_set.py 2776 2009-09-19 03:26:51Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.17.2 Function Documentation

### 9.17.2.1 `def rpki.resource_set._bs2long(s, addrlen, ll) [private]`

Utility function to convert a bitstring (POW.pkix tuple representation) into a Python long.

Definition at line 514 of file resource\_set.py.

### 9.17.2.2 `def rpki.resource_set._long2bs(number, addrlen, pre_xlen = None, strip = None) [private]`

Utility function to convert a Python long into a POW.pkix tuple bitstring. This is a bit complicated because it supports the fiendishly compact encoding used in RFC 3779.

Definition at line 526 of file resource\_set.py.

#### 9.17.2.3 def rpki.resource\_set.\_rsplit (set, that) [private]

Utility function to split a resource range into two resource ranges.

Definition at line 190 of file resource\_set.py.

#### 9.17.2.4 def rpki.resource\_set.test1t( s1, s2)

Definition at line 884 of file resource\_set.py.

#### 9.17.2.5 def rpki.resource\_set.test2t( s1, s2)

Definition at line 917 of file resource\_set.py.

### 9.17.3 Variable Documentation

#### 9.17.3.1 rpki::resource\_set::inherit\_token = "<inherit >"

Token used to indicate inheritance in read and print syntax.

Definition at line 48 of file resource\_set.py.

## 9.18 Package rpki.roa

### Classes

- class [ROAIPAddress](#)
- class [ROAIPAddresses](#)
- class [ROAIPAddressFamilies](#)
- class [ROAIPAddressFamily](#)
- class [RouteOriginAttestation](#)

### 9.18.1 Detailed Description

ROA (Route Origin Authorization).

At the moment this is just the ASN.1 encoder.

This corresponds to draft-ietf-sidr-roa-format, which is a work in progress, so this may need updating later.

\$Id: roa.py 2424 2009-05-11 06:37:32Z sra \$

Copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

draft-ietf-sidr-roa-format-03 2.1.3.2 specifies:

```
RouteOriginAttestation ::= SEQUENCE {
    version [0] INTEGER DEFAULT 0,
    asID ASID,
    ipAddrBlocks SEQUENCE OF ROAIPAddressFamily }
```

```
ASID ::= INTEGER
```

```
ROAIPAddressFamily ::= SEQUENCE {
    addressFamily OCTET STRING (SIZE (2..3)),
    addresses SEQUENCE OF ROAIPAddress }
```

```
ROAIPAddress ::= SEQUENCE {
    address IPAddress,
    maxLength INTEGER OPTIONAL }
```

```
IPAddress ::= BIT STRING
```

## 9.19 Package rpki.rpki\_engine

### Classes

- [classca\\_detail\\_obj](#)
- [classca\\_obj](#)
- [classchild\\_cert\\_obj](#)
- [classpublication\\_queue](#)
- [classrevoked\\_cert\\_obj](#)
- [classroa\\_obj](#)
- [classrpkid\\_context](#)

### 9.19.1 Detailed Description

Global context for rpkiid.

\$Id: rpki\_engine.py 2934 2010-01-07 01:22:04Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.20 Package rpki.sql

### Classes

- [classsession](#)
- [classsql\\_persistent](#)
- [classtemplate](#)

### 9.20.1 Detailed Description

SQL interface code.

\$Id: sql.py 2895 2009-12-21 17:17:55Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above



copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.21 Package rpki.sundial

### Classes

- class [datetime](#)
- class [timedelta](#)

### Functions

- def [\\_cast](#)
- def [now](#)
- def [test](#)

#### 9.21.1 Detailed Description

Unified RPKI date/time handling, based on the standard Python datetime module.

Module name chosen to sidestep a nightmare of import-related errors that occur with the more obvious module names.

List of arithmetic methods that require result casting was derived by inspection of the datetime module, to wit:

```
>>> import datetime
>>> for t in (datetime.datetime, datetime.timedelta):
...     for k in t.__dict__.keys():
```

```
... if k.startswith("__"):
...     print "%s.%s()" % (t.__name__, k)
```

\$Id: sundial.py 2785 2009-09-25 20:21:53Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.21.2 Function Documentation

### 9.21.2.1 def rpki.sundial.\_cast(x) [private]

Cast result of arithmetic operations back into correct subtype.

Definition at line 232 of file sundial.py.

### 9.21.2.2 def rpki.sundial.now()

Get current timestamp.

Definition at line 50 of file sundial.py.

## 9.21.2.3 def rpki.sundial.test(t)

Definition at line 244 of file sundial.py.

## 9.22 Package rpki.up\_down

## Classes

- class [base\\_elt](#)
- class [certificate\\_elt](#)
- class [class\\_elt](#)
- class [class\\_response\\_syntax](#)
- class [cms\\_msg](#)
- class [error\\_response\\_pdu](#)
- class [issue\\_pdu](#)
- class [issue\\_response\\_pdu](#)
- class [list\\_pdu](#)
- class [list\\_response\\_pdu](#)
- class [message\\_pdu](#)
- class [multi\\_uri](#)
- class [revoke\\_pdu](#)
- class [revoke\\_response\\_pdu](#)
- class [revoke\\_syntax](#)
- class [sax\\_handler](#)

## Variables

- dictionary [nsmap](#)= { None : [xmlns](#)}
- string [xmlns](#)= "http://www.apnic.net/specs/rescerts/up-down/"

## 9.22.1 Detailed Description

RPKI "up-down" protocol.

\$Id: up\_down.py 2935 2010-01-07 17:23:05Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH

REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.22.2 Variable Documentation

9.22.2.1 dictionary `rpki::up_down.nsmap` = { None : xmlns }

Definition at line 41 of file `up_down.py`.

9.22.2.2 string `rpki::up_down.xmlns` = "http://www.apnic.net/specs/rescerts/up-down/"

Definition at line 39 of file `up_down.py`.

## 9.23 Package rpki.x509

### Classes

- class [CMS\\_object](#)
- class [CRL](#)
- class [DeadDrop](#)
- class [DER\\_CMS\\_object](#)
- class [DER\\_object](#)
- class [PEM\\_converter](#)
- class [PKCS10](#)
- class [ROA](#)

- class [RSA](#)
- class [RSAPublic](#)
- class [SignedManifest](#)
- class [X509](#)
- class [XML\\_CMS\\_object](#)

## Functions

- def [calculate\\_SKI](#)
- def [POWify\\_OID](#)

### 9.23.1 Detailed Description

One X.509 implementation to rule them all...

...and in the darkness hide the twisty maze of partially overlapping X.509 support packages in Python.

There are several existing packages, none of which do quite what I need, due to age, lack of documentation, specialization, or lack of foresight on somebody's part (perhaps mine). This module attempts to bring together the functionality I need in a way that hides at least some of the nasty details. This involves a lot of format conversion.

\$Id: x509.py 2928 2010-01-05 05:45:35Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM

LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.23.2 Function Documentation

#### 9.23.2.1 def rpki.x509.calculate\_SKI (public\_key\_der)

Calculate the SKI value given the DER representation of a public key, which requires first peeling the ASN.1 wrapper off the key.

Definition at line 51 of file x509.py.

#### 9.23.2.2 def rpki.x509.POWify\_OID (oid)

Utility function to convert tuple form of an OID to the dotted-decimal string form that POW uses.

Definition at line 692 of file x509.py.

## 9.24 Package rpki.xml\_utils

### Classes

- class [base\\_elt](#)
- class [data\\_elt](#)
- class [msg](#)
- class [sax\\_handler](#)
- class [text\\_elt](#)

### 9.24.1 Detailed Description

XML utilities.

\$Id: xml\_utils.py 2836 2009-10-26 22:31:16Z sra \$

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

## 9.25 Package rpkiid

### Functions

- `def main`

### Variables

- `string cfg_le = "rpkiid.conf"`
- `pro le = None`

#### 9.25.1 Detailed Description

RPKI engine daemon. This is still very much a work in progress.

```
Usage: python rpkiid.py [ { -c | --config } configfile ]
                        [ { -h | --help } ]
                        [ { -p | --profile } outputfile ]
```

Default configuration file is `rpkiid.conf`, override with `--config` option.

```
$Id: rpkiid.py 2913 2009-12-28 20:55:38Z sra $
```

Copyright (C) 2009 Internet Systems Consortium ("ISC")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ISC DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ISC BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Portions copyright (C) 2007--2008 American Registry for Internet Numbers ("ARIN")

Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND ARIN DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL ARIN BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

### 9.25.2 Function Documentation

#### 9.25.2.1 def rpkid.main ()

Definition at line 68 of file rpkid.py.

### 9.25.3 Variable Documentation

#### 9.25.3.1 rpkid.cfg\_file = "rpkid.conf"

Definition at line 49 of file rpkid.py.

#### 9.25.3.2 rpkid.pro\_file = None

Definition at line 50 of file rpkid.py.



## 10 Class Documentation

### 10.1 `async_chat` Class Reference

Inherited by [rpki.https.http\\_stream](#)

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

### 10.2 `dispatcher` Class Reference

Inherited by [rpki.https.http\\_listener](#)

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

### 10.3 Exception Class Reference

Inherited by [rpki.exceptions.RPKI\\_Exception](#)

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

### 10.4 `irbe_cli.bsc_elt` Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::left\\_right::bsc\\_elt](#)

#### Public Member Functions

- def [client\\_query\\_signing\\_cert](#)
- def [client\\_query\\_signing\\_cert\\_crl](#)
- def [client\\_reply\\_decode](#)

#### Public Attributes

- [signing\\_cert](#)
- [signing\\_cert\\_crl](#)

### Static Public Attributes

- tuple `excludes` = ("pkcs10\_request",)  
XML attributes and elements that should not be allowed as command line arguments.

#### 10.4.1 Detailed Description

Definition at line 189 of file `irbe_cli.py`.

#### 10.4.2 Member Function Documentation

10.4.2.1 `def irbe_cli.bsc_elt.client_query_signing_cert(self, arg)`

--signing\_cert option.

Definition at line 193 of file `irbe_cli.py`.

10.4.2.2 `def irbe_cli.bsc_elt.client_query_signing_cert_crl(self, arg)`

--signing\_cert\_crl option.

Definition at line 197 of file `irbe_cli.py`.

10.4.2.3 `def irbe_cli.bsc_elt.client_reply_decode(self)`

Reimplemented from [irbe\\_cli.reply\\_elt\\_mixin](#)

Definition at line 201 of file `irbe_cli.py`.

#### 10.4.3 Member Data Documentation

10.4.3.1 `tuple irbe_cli.bsc_elt.excludes = ("pkcs10_request",)[static]`

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from [irbe\\_cli.cmd\\_elt\\_mixin](#)

Definition at line 191 of file irbe\_cli.py.

#### 10.4.3.2 irbe\_cli.bsc\_elt.signing\_cert

Reimplemented from [mpki.left\\_right.bsc\\_elt](#)

Definition at line 195 of file irbe\_cli.py.

#### 10.4.3.3 irbe\_cli.bsc\_elt.signing\_cert\_crl

Reimplemented from [mpki.left\\_right.bsc\\_elt](#)

Definition at line 199 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.5 irbe\_cli.caller Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_call\\_\\_](#)
- [def \\_\\_init\\_\\_](#)

### Public Attributes

- [client\\_cert](#)
- [client\\_key](#)
- [cms\\_class](#)
- [server\\_cert](#)
- [server\\_ta](#)
- [url](#)

#### 10.5.1 Detailed Description

Handle client-side mechanics for left-right and publication protocols.

Definition at line 41 of file irbe\_cli.py.

### 10.5.2 Member Function Documentation

#### 10.5.2.1 def irbe\_cli.caller.\_\_call\_\_(self, cb, eb, msg)

Definition at line 55 of file irbe\_cli.py.

#### 10.5.2.2 def irbe\_cli.caller.\_\_init\_\_(self, cms\_class, client\_key, client\_cert, server\_ta, server\_cert, url)

Definition at line 47 of file irbe\_cli.py.

### 10.5.3 Member Data Documentation

#### 10.5.3.1 irbe\_cli.caller.client\_cert

Definition at line 50 of file irbe\_cli.py.

#### 10.5.3.2 irbe\_cli.caller.client\_key

Definition at line 49 of file irbe\_cli.py.

#### 10.5.3.3 irbe\_cli.caller.cms\_class

Definition at line 48 of file irbe\_cli.py.

#### 10.5.3.4 irbe\_cli.caller.server\_cert

Definition at line 52 of file irbe\_cli.py.

### 10.5.3.5 irbe\_cli.caller.server\_tag

Definition at line 51 of file irbe\_cli.py.

### 10.5.3.6 irbe\_cli.caller.url

Definition at line 53 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.6 irbe\_cli.certificate\_elt Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::publication::certificate\\_elt](#)

### 10.6.1 Detailed Description

Definition at line 246 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.7 irbe\_cli.child\_elt Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::left\\_right::child\\_elt](#)

### 10.7.1 Detailed Description

Definition at line 211 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.8 irbe\_cli.client\_elt Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::publication::client\\_elt](#)

### 10.8.1 Detailed Description

Definition at line 243 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.9 irbe\_cli.cmd\_elt\_mixin Class Reference

Inherits [irbe\\_cli::reply\\_elt\\_mixin](#)

Inherited by [irbe\\_cli.bsc\\_elt](#), [irbe\\_cli.certificate\\_elt](#), [irbe\\_cli.child\\_elt](#), [irbe\\_cli.client\\_elt](#), [irbe\\_cli.config\\_elt](#), [irbe\\_cli.crl\\_elt](#), [irbe\\_cli.list\\_published\\_objects\\_elt](#), [irbe\\_cli.manifest\\_elt](#), [irbe\\_cli.parent\\_elt](#), [irbe\\_cli.repository\\_elt](#), [irbe\\_cli.roa\\_elt](#) and [irbe\\_cli.self\\_elt](#)

### Public Member Functions

- [def client\\_getopt](#)
- [def client\\_query\\_bpki\\_cert](#)
- [def client\\_query\\_bpki\\_cms\\_cert](#)
- [def client\\_query\\_bpki\\_https\\_cert](#)
- [def client\\_query\\_cms\\_glue](#)
- [def client\\_query\\_glue](#)
- [def client\\_query\\_https\\_glue](#)
- [def usage](#)

### Public Attributes

- [bpki\\_cert](#)
- [bpki\\_cms\\_cert](#)
- [bpki\\_cms\\_glue](#)
- [bpki\\_glue](#)
- [bpki\\_https\\_cert](#)
- [bpki\\_https\\_glue](#)

### Static Public Attributes

- tuple [excludes](#) = ()  
XML attributes and elements that should not be allowed as command line arguments.
- [is\\_cmd](#) = True

### 10.9.1 Detailed Description

Protocol mix-in for command line client element PDUs.

Definition at line 105 of file irbe\_cli.py.

### 10.9.2 Member Function Documentation

#### 10.9.2.1 def irbe\_cli.cmd\_elt\_mixin.client\_getopt(self, argv)

Parse options for this class.

Definition at line 129 of file irbe\_cli.py.

#### 10.9.2.2 def irbe\_cli.cmd\_elt\_mixin.client\_query\_bpki\_cert(self, arg)

Special handler for --bpki\_cert option.

Definition at line 146 of file irbe\_cli.py.

#### 10.9.2.3 def irbe\_cli.cmd\_elt\_mixin.client\_query\_bpki\_cms\_cert(self, arg)

Special handler for --bpki\_cms\_cert option.

Definition at line 154 of file irbe\_cli.py.

#### 10.9.2.4 def irbe\_cli.cmd\_elt\_mixin.client\_query\_bpki\_https\_cert(self, arg)

Special handler for --bpki\_https\_cert option.

Definition at line 162 of file irbe\_cli.py.

#### 10.9.2.5 def irbe\_cli.cmd\_elt\_mixin.client\_query\_cms\_glue(self, arg)

Special handler for --bpki\_cms\_glue option.

Definition at line 158 of file irbe\_cli.py.

#### 10.9.2.6 def irbe\_cli.cmd\_elt\_mixin.client\_query\_glue(self, arg)

Special handler for --bpki\_glue option.

Definition at line 150 of file irbe\_cli.py.

#### 10.9.2.7 def irbe\_cli.cmd\_elt\_mixin.client\_query\_https\_glue(self, arg)

Special handler for --bpki\_https\_glue option.

Definition at line 166 of file irbe\_cli.py.

#### 10.9.2.8 def irbe\_cli.cmd\_elt\_mixin.usage(self)

Generate usage message for this PDU.

Definition at line 118 of file irbe\_cli.py.

### 10.9.3 Member Data Documentation

#### 10.9.3.1 irbe\_cli.cmd\_elt\_mixin.bpki\_cert

Definition at line 148 of file irbe\_cli.py.

#### 10.9.3.2 irbe\_cli.cmd\_elt\_mixin.bpki\_cms\_cert

Definition at line 156 of file irbe\_cli.py.



### 10.9.3.3 irbe\_cli.cmd\_elt\_mixin.bpki\_cms\_glue

Definition at line 160 of file irbe\_cli.py.

### 10.9.3.4 irbe\_cli.cmd\_elt\_mixin.bpki\_glue

Definition at line 152 of file irbe\_cli.py.

### 10.9.3.5 irbe\_cli.cmd\_elt\_mixin.bpki\_https\_cert

Definition at line 164 of file irbe\_cli.py.

### 10.9.3.6 irbe\_cli.cmd\_elt\_mixin.bpki\_https\_glue

Definition at line 168 of file irbe\_cli.py.

### 10.9.3.7 irbe\_cli.cmd\_elt\_mixin::excludes = () [static]

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from [irbe\\_cli.bsc\\_elt](#) and [irbe\\_cli.list\\_published\\_objects\\_elt](#)

Definition at line 115 of file irbe\_cli.py.

### 10.9.3.8 irbe\_cli.cmd\_elt\_mixin.is\_cmd = True [static]

Reimplemented from [irbe\\_cli.reply\\_elt\\_mixin](#)

Definition at line 110 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.10 irbe\_cli.cmd\_msg\_mixin Class Reference

Inherits [object](#)

Inherited by [irbe\\_cli.left\\_right\\_msg](#) and [irbe\\_cli.publication\\_msg](#)

### Public Member Functions

- def [usage](#)

#### 10.10.1 Detailed Description

Protocol mix-in for command line client message PDUs.

Definition at line 170 of file [irbe\\_cli.py](#).

#### 10.10.2 Member Function Documentation

##### 10.10.2.1 def irbe\_cli.cmd\_msg\_mixin.usage(s)

Generate usage message for this PDU.

Definition at line 176 of file [irbe\\_cli.py](#).

The documentation for this class was generated from the following file:

- [irbe\\_cli.py](#) (2799)

## 10.11 irbe\_cli.cong\_elt Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::publication::cong\\_elt](#)

### Public Member Functions

- def [client\\_query\\_bpki\\_crl](#)

### Public Attributes

- [bpki\\_crl](#)

### 10.11.1 Detailed Description

Definition at line 237 of file irbe\_cli.py.

### 10.11.2 Member Function Documentation

#### 10.11.2.1 def irbe\_cli.config\_elt.client\_query\_bpki\_crl (self, arg)

Special handler for --bpki\_crl option.

Definition at line 239 of file irbe\_cli.py.

### 10.11.3 Member Data Documentation

#### 10.11.3.1 irbe\_cli.config\_elt.bpki\_crl

Definition at line 241 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.12 irbe\_cli.crl\_elt Class Reference

Inherits [irbe\\_cli.cmd\\_elt\\_mixin](#) and [rpki::publication::crl\\_elt](#)

### 10.12.1 Detailed Description

Definition at line 249 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.13 irbe\_cli.left\_right\_cms\_msg Class Reference

Inherits [rpki::left\\_right::cms\\_msg](#)

## Static Public Attributes

- [saxify](#) = left\_right\_sax\_handler.saxify

## 10.13.1 Detailed Description

Definition at line 232 of file irbe\_cli.py.

## 10.13.2 Member Data Documentation

- 10.13.2.1 [irbe\\_cli.left\\_right\\_cms\\_msg.saxify](#) = left\_right\_sax\_handler.saxify [static]

Reimplemented from [rpki.left\\_right.cms\\_msg](#)

Definition at line 233 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.14 irbe\_cli.left\_right\_msg Class Reference

Inherits [irbe\\_cli::cmd\\_msg\\_mixin](#) and [rpki::left\\_right::msg](#)

## Static Public Attributes

- tuple [pdus](#)  
Dispatch table of PDUs for this protocol.

## 10.14.1 Detailed Description

Definition at line 224 of file irbe\_cli.py.

## 10.14.2 Member Data Documentation

- 10.14.2.1 tuple [irbe\\_cli.left\\_right\\_msg.pdus](#) [static]

Initial value:

```
dict((x.element_name, x)
      for x in (self_elt, bsc_elt, parent_elt, child_elt, repository_elt,
                list_published_objects_elt, report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented from [rpkil.left\\_right.msg](#)

Definition at line 225 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.15 irbe\_cli.left\_right\_sax\_handler Class Reference

Inherits [rpkil.left\\_right.sax\\_handler](#)

Static Public Attributes

- `pdu` = [left\\_right\\_msg](#)

### 10.15.1 Detailed Description

Definition at line 229 of file `irbe_cli.py`.

### 10.15.2 Member Data Documentation

10.15.2.1 `irbe_cli.left_right_sax_handler.pdu = left_right_msg` [static]

Reimplemented from [rpkil.left\\_right.sax\\_handler](#)

Definition at line 230 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.16 irbe\_cli.list\_published\_objects\_elt Class Reference

Inherits [irbe\\_cli.cmd\\_elt\\_mixin](#) and [rpkil.left\\_right.list\\_published\\_objects\\_elt](#)

### Static Public Attributes

- tuple `excludes= ("uri",)`  
XML attributes and elements that should not be allowed as command line arguments.

#### 10.16.1 Detailed Description

Definition at line 217 of file `irbe_cli.py`.

#### 10.16.2 Member Data Documentation

- 10.16.2.1 tuple `irbe_cli.list_published_objects_elt.excludes = ("uri",)`  
[static]

XML attributes and elements that should not be allowed as command line arguments.

Reimplemented from `irbe_cli.cmd_elt_mixin`

Definition at line 219 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- `irbe_cli.py` (2799)

### 10.17 irbe\_cli.manifest\_elt Class Reference

Inherits `irbe_cli::cmd_elt_mixin` and `rpki::publication::manifest_elt`

#### 10.17.1 Detailed Description

Definition at line 252 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- `irbe_cli.py` (2799)

### 10.18 irbe\_cli.parent\_elt Class Reference

Inherits `irbe_cli::cmd_elt_mixin` and `rpki::left_right::parent_elt`

### 10.18.1 Detailed Description

Definition at line 208 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.19 irbe\_cli.publication\_cms\_msg Class Reference

Inherits [rpki::publication::cms\\_msg](#)

### Static Public Attributes

- [saxify](#) = publication\_sax\_handler.saxify

### 10.19.1 Detailed Description

Definition at line 268 of file irbe\_cli.py.

### 10.19.2 Member Data Documentation

10.19.2.1 [irbe\\_cli.publication\\_cms\\_msg.saxify](#) = [publication\\_sax\\_handler.saxify](#)  
[static]

Reimplemented from [rpki.publication.cms\\_msg](#)

Definition at line 269 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.20 irbe\_cli.publication\_msg Class Reference

Inherits [irbe\\_cli::cmd\\_msg\\_mixin](#) and [rpki::publication::msg](#)

### Static Public Attributes

- tuple [pdus](#)  
Dispatch table of PDUs for this protocol.

## 10.20.1 Detailed Description

Definition at line 261 of file irbe\_cli.py.

## 10.20.2 Member Data Documentation

## 10.20.2.1 tuple irbe\_cli.publication\_msg.pdus[static]

Initial value:

```
dict((x.element_name, x)
      for x in (config_elt, client_elt, certificate_elt, crl_elt, manifest_elt, roa_elt, report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented from [rpki.publication.msg](#)

Definition at line 262 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.21 irbe\_cli.publication\_sax\_handler Class Reference

Inherits [rpki::publication::sax\\_handler](#)

Static Public Attributes

- [pdu = publication\\_msg](#)

## 10.21.1 Detailed Description

Definition at line 265 of file irbe\_cli.py.

## 10.21.2 Member Data Documentation

## 10.21.2.1 irbe\_cli.publication\_sax\_handler.pdu = publication\_msg[static]

Reimplemented from [rpki.publication.sax\\_handler](#)

Definition at line 266 of file irbe\_cli.py.



The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.22 irbe\_cli.reply\_elt\_mixin Class Reference

Inherits [object](#)

Inherited by [irbe\\_cli.cmd\\_elt\\_mixin](#), [irbe\\_cli.report\\_error\\_elt](#) and [irbe\\_cli.report\\_error\\_elt](#)

### Public Member Functions

- def [client\\_reply\\_decode](#)
- def [client\\_reply\\_show](#)

### Static Public Attributes

- [is\\_cmd](#)= False

#### 10.22.1 Detailed Description

Protocol mix-in for printout of reply PDUs.

Definition at line 89 of file [irbe\\_cli.py](#).

#### 10.22.2 Member Function Documentation

##### 10.22.2.1 def [irbe\\_cli.reply\\_elt\\_mixin.client\\_reply\\_decode\(self\)](#)

Reimplemented in [irbe\\_cli.bsc\\_elt](#)

Definition at line 96 of file [irbe\\_cli.py](#).

##### 10.22.2.2 def [irbe\\_cli.reply\\_elt\\_mixin.client\\_reply\\_show\(self\)](#)

Definition at line 99 of file [irbe\\_cli.py](#).

### 10.22.3 Member Data Documentation

#### 10.22.3.1 `irbe_cli.reply_elt_mixin.is_cmd = False`[static]

Reimplemented in [irbe\\_cli.cmd\\_elt\\_mixin](#)

Definition at line 94 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py](#) (2799)

## 10.23 `irbe_cli.report_error_elt` Class Reference

Inherits [irbe\\_cli::reply\\_elt\\_mixin](#), [rpki::publication::report\\_error\\_elt](#), [irbe\\_cli::reply\\_elt\\_mixin](#), and [rpki::left\\_right::report\\_error\\_elt](#)

### 10.23.1 Detailed Description

Definition at line 221 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py](#) (2799)

## 10.24 `irbe_cli.repository_elt` Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::left\\_right::repository\\_elt](#)

### 10.24.1 Detailed Description

Definition at line 214 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py](#) (2799)

## 10.25 `irbe_cli.roa_elt` Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::publication::roa\\_elt](#)

### 10.25.1 Detailed Description

Definition at line 255 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.26 irbe\_cli.self\_elt Class Reference

Inherits [irbe\\_cli::cmd\\_elt\\_mixin](#) and [rpki::left\\_right::self\\_elt](#)

### 10.26.1 Detailed Description

Definition at line 186 of file irbe\_cli.py.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.27 irbe\_cli.UsageWrapper Class Reference

Inherits [textwrap::TextWrapper](#)

Public Member Functions

- [def \\_\\_call\\_\\_](#)

### 10.27.1 Detailed Description

Call interface around Python textwrap.TextWrapper class.

Definition at line 78 of file irbe\_cli.py.

### 10.27.2 Member Function Documentation

#### 10.27.2.1 def irbe\_cli.UsageWrapper.\_\_call\_\_(self, args)

Format arguments, with TextWrapper indentation.

Definition at line 83 of file `irbe_cli.py`.

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.28 long Class Reference

Inherited by [rpki.ipaddrs.v4addr](#) and [rpki.ipaddrs.v6addr](#)

The documentation for this class was generated from the following file:

- [ipaddrs.py \(2424\)](#)

## 10.29 object Class Reference

Inherited by [irbe\\_cli.caller](#), [irbe\\_cli.cmd\\_msg\\_mixin](#), [irbe\\_cli.reply\\_elt\\_mixin](#), [pubd.pubd\\_context](#), [rpki.async.gc\\_summary](#), [rpki.async.iterator](#), [rpki.async.sync\\_wrapper](#), [rpki.async.timer](#), [rpki.config.parser](#), [rpki.https.http\\_messenger](#), [rpki.https.http\\_queue](#), [rpki.left\\_right.left\\_right\\_namespace](#), [rpki.log.logger](#), [rpki.publication.publication\\_namespace](#), [rpki.resource\\_set.resource\\_bag](#), [rpki.resource\\_set.resource\\_range](#), [rpki.resource\\_set.roa\\_prefix](#), [rpki.rpki\\_engine.publication\\_queue](#), [rpki.rpki\\_engine.rpkid\\_context](#), [rpki.sql.session](#), [rpki.sql.sql\\_persistent](#), [rpki.sql.template](#), [rpki.up\\_down.base\\_elt](#), [rpki.x509.DeadDrop](#), [rpki.x509.DER\\_object](#), [rpki.x509.PEM\\_converter](#), and [rpki.xml\\_utils.base\\_elt](#)

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.30 pubd.pubd\_context Class Reference

Inherits [object](#)

Public Member Functions

- `def __init__`
- `def build_https_ta_cache`
- `def clear_https_ta_cache`
- `def client_handler`
- `def control_handler`
- `def handler_common`

## Public Attributes

- [bpci\\_ta](#)
- [https\\_server\\_host](#)
- [https\\_server\\_port](#)
- [irbe\\_cert](#)
- [pubd\\_cert](#)
- [pubd\\_key](#)
- [publication\\_base](#)
- [sql](#)

## Static Public Attributes

- tuple [client\\_url\\_regexp](#) = re.compile("/client/([-A-Z0-9\_]+)\$", re.I)
- [https\\_ta\\_cache](#) = None  
HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

## 10.30.1 Detailed Description

A container for various pubd parameters.

Definition at line 46 of file `pubd.py`.

## 10.30.2 Member Function Documentation

## 10.30.2.1 def pubd.pubd\_context.\_\_init\_\_(self, cfg)

Definition at line 51 of file `pubd.py`.

## 10.30.2.2 def pubd.pubd\_context.build\_https\_ta\_cache(self)

Build dynamic TLS trust anchors.

Definition at line 138 of file `pubd.py`.

### 10.30.2.3 def pubd.pubd\_context.clear\_https\_ta\_cache(self)

Clear dynamic TLS trust anchors.

Definition at line 130 of file pubd.py.

### 10.30.2.4 def pubd.pubd\_context.client\_handler(self, query, path, cb)

Process one PDU from a client.

Definition at line 98 of file pubd.py.

### 10.30.2.5 def pubd.pubd\_context.control\_handler(self, query, path, cb)

Process one PDU from the IRBE.

Definition at line 78 of file pubd.py.

### 10.30.2.6 def pubd.pubd\_context.handler\_commons(self, query, client, cb, certs, crl = None)

Common PDU handler code.

Definition at line 65 of file pubd.py.

## 10.30.3 Member Data Documentation

### 10.30.3.1 pubd.pubd\_context.bpki\_ta

Definition at line 55 of file pubd.py.

10.30.3.2 tuple pubd.pubd\_context.client\_url\_regexp =  
re.compile("/client/([-A-Z0-9\_]+)\$", re.I) [static]

Definition at line 96 of file pubd.py.

10.30.3.3 pubd.pubd\_context.https\_server\_host

Definition at line 60 of file pubd.py.

10.30.3.4 pubd.pubd\_context.https\_server\_port

Definition at line 61 of file pubd.py.

10.30.3.5 pubd.pubd\_context.https\_ta\_cache = None [static]

HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

Definition at line 128 of file pubd.py.

10.30.3.6 pubd.pubd\_context.irbe\_cert

Definition at line 56 of file pubd.py.

10.30.3.7 pubd.pubd\_context.pubd\_cert

Definition at line 57 of file pubd.py.

10.30.3.8 pubd.pubd\_context.pubd\_key

Definition at line 58 of file pubd.py.

## 10.30.3.9 pubd.pubd\_context.publication\_base

Definition at line 63 of file pubd.py.

## 10.30.3.10 pubd.pubd\_context.sql

Definition at line 53 of file pubd.py.

The documentation for this class was generated from the following file:

- [pubd.py \(2913\)](#)

## 10.31 datetime Class Reference

Inherited by [rpki.sundial.datetime](#)

The documentation for this class was generated from the following file:

- [sundial.py \(2785\)](#)

## 10.32 timedelta Class Reference

Inherited by [rpki.sundial.timedelta](#)

The documentation for this class was generated from the following file:

- [sundial.py \(2785\)](#)

## 10.33 rootd.cms\_msg Class Reference

Inherits [rpki::up\\_down::cms\\_msg](#)

Static Public Attributes

- [saxify](#) = sax\_handler.saxify

## 10.33.1 Detailed Description

Definition at line 235 of file rootd.py.



### 10.33.2 Member Data Documentation

#### 10.33.2.1 rootd.cms\_msg.saxify = sax\_handler.saxify[static]

Reimplemented from [rpki.up\\_down.cms\\_msg](#)

Definition at line 236 of file rootd.py.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.34 rootd.issue\_pdu Class Reference

Inherits [rpki::up\\_down::issue\\_pdu](#)

Public Member Functions

- [def serve\\_pdu](#)

### 10.34.1 Detailed Description

Definition at line 194 of file rootd.py.

### 10.34.2 Member Function Documentation

#### 10.34.2.1 def rootd.issue\_pdu.serve\_pdu(self, q\_msg r\_msg child, callback, errback)

Serve one issue request PDU.

Reimplemented from [rpki.up\\_down.issue\\_pdu](#)

Definition at line 195 of file rootd.py.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.35 rootd.list\_pdu Class Reference

Inherits [rpki::up\\_down::list\\_pdu](#)

## Public Member Functions

- def [serve\\_pdu](#)

## 10.35.1 Detailed Description

Definition at line 188 of file `rootd.py`.

## 10.35.2 Member Function Documentation

- 10.35.2.1 def `rootd.list_pdu.serve_pdu(self, q_msg r_msg child, callback, errback)`

Serve one "list" PDU.

Reimplemented from [rpki.up\\_down.list\\_pdu](#)

Definition at line 189 of file `rootd.py`.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.36 rootd.message\_pdu Class Reference

Inherits [rpki::up\\_down::message\\_pdu](#)

## Public Member Functions

- def [log\\_query](#)

## Static Public Attributes

- dictionary [name2type](#)
- tuple [type2name](#) = dict((v, k) for k, v in name2type.items())

## 10.36.1 Detailed Description

Definition at line 213 of file `rootd.py`.

### 10.36.2 Member Function Documentation

#### 10.36.2.1 def rootd.message\_pdu.log\_query(self, child)

Log query we're handling.

Reimplemented from [rpki.up\\_down.message\\_pdu](#)

Definition at line 226 of file rootd.py.

### 10.36.3 Member Data Documentation

#### 10.36.3.1 dictionary rootd.message\_pdu.name2type[static]

Initial value:

```
{
    "list"           : list_pdu,
    "list_response"  : rpki.up_down.list_response_pdu,
    "issue"          : issue_pdu,
    "issue_response" : rpki.up_down.issue_response_pdu,
    "revoke"         : revoke_pdu,
    "revoke_response": rpki.up_down.revoke_response_pdu,
    "error_response" : rpki.up_down.error_response_pdu }
```

Reimplemented from [rpki.up\\_down.message\\_pdu](#)

Definition at line 215 of file rootd.py.

#### 10.36.3.2 tuple rootd.message\_pdu.type2name = dict((v, k) for k, v in name2type.items()) [static]

Reimplemented from [rpki.up\\_down.message\\_pdu](#)

Definition at line 224 of file rootd.py.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.37 rootd.revoke\_pdu Class Reference

Inherits [rpki::up\\_down::revoke\\_pdu](#)

## Public Member Functions

- [def serve\\_pdu](#)

### 10.37.1 Detailed Description

Definition at line 201 of file rootd.py.

### 10.37.2 Member Function Documentation

#### 10.37.2.1 def rootd.revoke\_pdu.serve\_pdu(self, q\_msg r\_msg child, cb, eb)

Serve one revoke request PDU.

Reimplemented from [mpki.up\\_down.revoke\\_pdu](#)

Definition at line 202 of file rootd.py.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.38 rootd.sax\_handler Class Reference

Inherits [rpki::up\\_down::sax\\_handler](#)

## Static Public Attributes

- [pdu = message\\_pdu](#)

### 10.38.1 Detailed Description

Definition at line 232 of file rootd.py.

### 10.38.2 Member Data Documentation

#### 10.38.2.1 rootd.sax\_handler.pdu = message\_pdu[static]

Reimplemented from [mpki.up\\_down.sax\\_handler](#)

Definition at line 233 of file rootd.py.

The documentation for this class was generated from the following file:

- [rootd.py \(2913\)](#)

## 10.39 rpkg.async.gc\_summary Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def handler](#)

### Public Attributes

- [interval](#)
- [timer](#)

#### 10.39.1 Detailed Description

Periodic summary of GC state, for tracking down memory bloat.

Definition at line 347 of file async.py.

#### 10.39.2 Member Function Documentation

##### 10.39.2.1 `def rpkg.async.gc_summary.__init__(self, interval)`

Definition at line 352 of file async.py.

##### 10.39.2.2 `def rpkg.async.gc_summary.handler(self)`

Definition at line 359 of file async.py.

### 10.39.3 Member Data Documentation

#### 10.39.3.1 rpki.async.gc\_summary.interval

Definition at line 355 of file `async.py`.

#### 10.39.3.2 rpki.async.gc\_summary.timer

Definition at line 356 of file `async.py`.

The documentation for this class was generated from the following file:

- [async.py \(2926\)](#)

## 10.40 rpki.async.iterator Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_call\\_\\_](#)
- [def \\_\\_init\\_\\_](#)
- [def \\_\\_repr\\_\\_](#)
- [def doit](#)
- [def ignore](#)

### Public Attributes

- [caller\\_function](#)
- [done\\_callback](#)
- [item\\_callback](#)
- [iterator](#)
- [unwind\\_stack](#)

#### 10.40.1 Detailed Description

Iteration construct for event-driven code. Takes three arguments:

- Some kind of iterable object

- A callback to call on each item in the iteration
- A callback to call after the iteration terminates.

The item callback receives two arguments: the callable iterator object and the current value of the iteration. It should call the iterator (or arrange for the iterator to be called) when it is time to continue to the next item in the iteration.

The termination callback receives no arguments.

Definition at line 26 of `le_async.py`.

#### 10.40.2 Member Function Documentation

##### 10.40.2.1 `def rpki.async.iterator.__call__(self)`

Definition at line 64 of `le_async.py`.

##### 10.40.2.2 `def rpki.async.iterator.__init__(self, iterable, item_callback, done_callback, unwind_stack=True)`

Definition at line 45 of `le_async.py`.

##### 10.40.2.3 `def rpki.async.iterator.__repr__(self)`

Definition at line 59 of `le_async.py`.

##### 10.40.2.4 `def rpki.async.iterator.doit(self)`

Definition at line 70 of `le_async.py`.

##### 10.40.2.5 `def rpki.async.iterator.ignore(self, ignored)`

Definition at line 77 of `le_async.py`.

### 10.40.3 Member Data Documentation

#### 10.40.3.1 rpki.async.iterator.caller\_function

Definition at line 48 of file `async.py`.

#### 10.40.3.2 rpki.async.iterator.done\_callback

Definition at line 47 of file `async.py`.

#### 10.40.3.3 rpki.async.iterator.item\_callback

Definition at line 46 of file `async.py`.

#### 10.40.3.4 rpki.async.iterator.iterator

Definition at line 51 of file `async.py`.

#### 10.40.3.5 rpki.async.iterator.unwind\_stack

Definition at line 49 of file `async.py`.

The documentation for this class was generated from the following file:

- [async.py \(2926\)](#)

## 10.41 rpki.async.sync\_wrapper Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_call\\_\\_](#)
- [def \\_\\_init\\_\\_](#)



- def `cb`
- def `eb`

#### Public Attributes

- `func`

#### Static Public Attributes

- `err` = None
- `res` = None

##### 10.41.1 Detailed Description

Synchronous wrapper around asynchronous functions. Running in asynchronous mode at all times makes sense for event-driven daemons, but is kind of tedious for simple scripts, hence this wrapper.

The wrapped function should take at least two arguments: a callback function and an errback function. If any arguments are passed to the wrapper, they will be passed as additional arguments to the wrapped function.

Definition at line 300 of `le_async.py`.

##### 10.41.2 Member Function Documentation

10.41.2.1 `def rpki.async.sync_wrapper.__call__(self, args, kwargs)`

Definition at line 326 of `le_async.py`.

10.41.2.2 `def rpki.async.sync_wrapper.__init__(self, func)`

Definition at line 315 of `le_async.py`.

10.41.2.3 `def rpki.async.sync_wrapper.cb(self, res= None)`

Definition at line 318 of `le_async.py`.

10.41.2.4 def rpki.async.sync\_wrapper.err(self, err)

Definition at line 322 of file async.py.

### 10.41.3 Member Data Documentation

10.41.3.1 rpki.async.sync\_wrapper.err = None[static]

Definition at line 313 of file async.py.

10.41.3.2 rpki.async.sync\_wrapper.func

Definition at line 316 of file async.py.

10.41.3.3 rpki.async.sync\_wrapper.res = None[static]

Definition at line 312 of file async.py.

The documentation for this class was generated from the following file:

- [async.py \(2926\)](#)

## 10.42 rpki.async.timer Class Reference

Inherits [object](#)

### Public Member Functions

- def [\\_\\_cmp\\_\\_](#)
- def [\\_\\_del\\_\\_](#)
- def [\\_\\_init\\_\\_](#)
- def [\\_\\_repr\\_\\_](#)
- def [cancel](#)
- def [clear](#)
- def [errback](#)
- def [handler](#)

- def [is\\_set](#)
- def [runq](#)
- def [seconds\\_until\\_wakeup](#)
- def [set](#)
- def [set\\_errback](#)
- def [set\\_handler](#)
- def [trace](#)

#### Public Attributes

- [errback](#)
- [handler](#)
- [when](#)

#### Static Public Attributes

- [gc\\_debug](#)= False  
Verbose chatter about timers states and garbage collection.
- list [queue](#)= []  
Timer queue, shared by [allmer](#) instances (there can be only one queue).
- [run\\_debug](#)= False  
Verbose chatter about timers being run.

#### 10.42.1 Detailed Description

Timer construct for event-driven code. It can be used in either of two ways:

- As a virtual class, in which case the subclass should provide a `handler()` method to receive the wakeup event when the timer expires; or
- By setting an explicit handler callback, either via the constructor or the `set_handler()` method.

Subclassing is probably more Pythonic, but setting an explicit handler turns out to be very convenient when combined with bound methods to other objects.

Definition at line 80 of `le_async.py`.

### 10.42.2 Member Function Documentation

#### 10.42.2.1 def rpki.async.timer.\_\_cmp\_\_(self, other)

Definition at line 138 of file async.py.

#### 10.42.2.2 def rpki.async.timer.\_\_del\_\_(self)

Definition at line 142 of file async.py.

#### 10.42.2.3 def rpki.async.timer.\_\_init\_\_(self, handler=None, errback=None)

Definition at line 107 of file async.py.

#### 10.42.2.4 def rpki.async.timer.\_\_repr\_\_(self)

Definition at line 204 of file async.py.

#### 10.42.2.5 def rpki.async.timer.cancel(self)

Cancel a timer, if it was set.

Definition at line 145 of file async.py.

#### 10.42.2.6 def rpki.async.timer.clear(cls)

Cancel every timer on the queue. We could just throw away the queue content, but this way we can notify subclasses that provide their own cancel() method.

Definition at line 229 of file async.py.

#### 10.42.2.7 def rpki.async.timer.errback (self, e)

Error callback. May be overridden, or set with `set_errback()`.

Definition at line 176 of `le_async.py`.

#### 10.42.2.8 def rpki.async.timer.handler (self)

Handle a timer that has expired. This must either be overridden by a subclass or set dynamically by `set_handler()`.

Definition at line 159 of `le_async.py`.

#### 10.42.2.9 def rpki.async.timer.is\_set (self)

Test whether this timer is currently set.

Definition at line 155 of `le_async.py`.

#### 10.42.2.10 def rpki.async.timer.runq (cls)

Run the timer queue: for each timer whose call time has passed, pull the timer off the queue and call its `handler()` method.

Definition at line 188 of `le_async.py`.

#### 10.42.2.11 def rpki.async.timer.seconds\_until\_wakeup(s)

Calculate delay until next timer expires, or `None` if no timers are set and we should wait indefinitely. Rounds up to avoid spinning in `select()` or `poll()`. We could calculate fractional seconds in the right units instead, but `select()` and `poll()` don't even take the same units (argh!), and we're not doing anything that hair-triggered, so rounding up is simplest.

Definition at line 208 of `le_async.py`.

#### 10.42.2.12 def rpki.async.timer.set(self, when)

Set a timer. Argument can be a datetime, to specify an absolute time, or a timedelta, to specify an offset time.

Definition at line 123 of file async.py.

#### 10.42.2.13 def rpki.async.timer.set\_errback(self, errback)

Set a timer's errback. Like set\_handler(), for errbacks.

Definition at line 183 of file async.py.

#### 10.42.2.14 def rpki.async.timer.set\_handler(self, handler)

Set timer's expiration handler. This is an alternative to subclassing the timer class, and may be easier to use when integrating timers into other classes (eg, the handler can be a bound method to an object in a class representing a network connection).

Definition at line 166 of file async.py.

#### 10.42.2.15 def rpki.async.timer.trace(self, msg)

Debug logging.

Definition at line 115 of file async.py.

### 10.42.3 Member Data Documentation

#### 10.42.3.1 rpki.async.timer.errback

Definition at line 185 of file async.py.

#### 10.42.3.2 rpki::async.timer::gc\_debug = False [static]

Verbose chatter about timers states and garbage collection.

Definition at line 97 of file `async.py`.

#### 10.42.3.3 rpki.async.timer.handler

Definition at line 174 of file `async.py`.

#### 10.42.3.4 rpki::async.timer::queue = [] [static]

Timer queue, shared by [all timer](#) instances (there can be only one queue).

Definition at line 105 of file `async.py`.

#### 10.42.3.5 rpki::async.timer::run\_debug = False [static]

Verbose chatter about timers being run.

Definition at line 101 of file `async.py`.

#### 10.42.3.6 rpki.async.timer.when

Definition at line 112 of file `async.py`.

The documentation for this class was generated from the following file:

- [async.py \(2926\)](#)

### 10.43 rpki.con g.parser Class Reference

Inherits [object](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [get](#)
- def [getboolean](#)
- def [getint](#)
- def [has\\_option](#)
- def [has\\_section](#)
- def [multiget](#)
- def [set\\_global\\_ags](#)

### Public Attributes

- [cfg](#)
- [default\\_section](#)
- [lename](#)

### Private Member Functions

- def [\\_get\\_wrapper](#)

#### 10.43.1 Detailed Description

Extensions to stock Python ConfigParser:

Read config file and set default section while initializing parser object.

Support for OpenSSL-style subscripted options.

get-methods with default values and default section name.

Definition at line 38 of `le con g.py`.

#### 10.43.2 Member Function Documentation

10.43.2.1 `def rpki.con g.parser.__init__ (self, lename, section= None, allow_missing= False )`

Initialize this parser.

Definition at line 49 of `le con g.py`.



10.43.2.2 `def rpki.config.parser._get_wrapper (self, method section option, default) [private]`

Wrapper method to add default value and default section support to ConfigParser methods.

Definition at line 98 of `le.config.py`.

10.43.2.3 `def rpki.config.parser.get (self, option, default = None, section = None)`

Get an option, perhaps with a default value.

Definition at line 111 of `le.config.py`.

10.43.2.4 `def rpki.config.parser.getboolean (self, option, default = None, section = None)`

Get a boolean option, perhaps with a default value.

Definition at line 117 of `le.config.py`.

10.43.2.5 `def rpki.config.parser.getint (self, option, default = None, section = None)`

Get an integer option, perhaps with a default value.

Definition at line 123 of `le.config.py`.

10.43.2.6 `def rpki.config.parser.has_option (self, option, section = None)`

Test whether an option exists.

Definition at line 70 of `le.config.py`.

#### 10.43.2.7 def rpki.con g.parser.has\_section(self, section)

Test whether a section exists.

Definition at line 63 of file con g.py.

#### 10.43.2.8 def rpki.con g.parser.multiget (self, option, section= None)

Parse OpenSSL-style foo.0, foo.1, ... subscripted options.

Returns a list of values matching the specified option name.

Definition at line 79 of file con g.py.

#### 10.43.2.9 def rpki.con g.parser.set\_global\_ args (self)

Consolidated control for all the little global control flags scattered through the libraries. This isn't a particularly good place for this function to live, but it has to live somewhere and making it a method of the config parser from which it gets all of its data is less silly than the available alternatives.

Definition at line 129 of file con g.py.

### 10.43.3 Member Data Documentation

#### 10.43.3.1 rpki.con g.parser.cfg

Definition at line 55 of file con g.py.

#### 10.43.3.2 rpki.con g.parser.default\_section

Definition at line 61 of file con g.py.

### 10.43.3.3 rpki.config.parser.Length

Definition at line 54 of file config.py.

The documentation for this class was generated from the following file:

- [config.py \(2926\)](#)

## 10.44 rpki.exceptions.BadClassNameSyntax Class Reference

Inherits [rpki.exceptions.RPKI\\_Exception](#)

### 10.44.1 Detailed Description

Illegal syntax for a class\_name.

Definition at line 92 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.45 rpki.exceptions.BadClientURL Class Reference

Inherits [rpki.exceptions.RPKI\\_Exception](#)

### 10.45.1 Detailed Description

URL given to HTTPS client does not match profile.

Definition at line 232 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.46 rpki.exceptions.BadContactURL Class Reference

Inherits [rpki.exceptions.RPKI\\_Exception](#)

### 10.46.1 Detailed Description

Error trying to parse contact URL.

Definition at line 87 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.47 rpki.exceptions.BadExtension Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.47.1 Detailed Description

Forbidden X.509 extension.

Definition at line 242 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.48 rpki.exceptions.BadIRDBReply Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.48.1 Detailed Description

Unexpected reply to IRDB query.

Definition at line 152 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.49 rpki.exceptions.BadIssueResponse Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.49.1 Detailed Description

issue\_response PDU with wrong number of classes or certificates.

Definition at line 97 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.50 rpki.exceptions.BadPKCS10 Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.50.1 Detailed Description

Bad PKCS #10 object.

Definition at line 107 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.51 rpki.exceptions.BadPublicationReply Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.51.1 Detailed Description

Unexpected reply to publication query.

Definition at line 257 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.52 rpki.exceptions.BadQuery Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

#### 10.52.1 Detailed Description

Unexpected protocol query.

Definition at line 55 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

### 10.53 rpki.exceptions.BadSender Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

#### 10.53.1 Detailed Description

Unexpected XML sender value.

Definition at line 127 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

### 10.54 rpki.exceptions.BadStatusCode Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

#### 10.54.1 Detailed Description

Unrecognized protocol status code.

Definition at line 50 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

### 10.55 rpki.exceptions.BadURISyntax Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.55.1 Detailed Description

Illegal syntax for a URI.

Definition at line 45 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.56 rpki.exceptions.BSCNotFound Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.56.1 Detailed Description

Could not find specified BSC in database.

Definition at line 122 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.57 rpki.exceptions.BSCNotReady Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.57.1 Detailed Description

BSC not yet in a usable state, signing\_cert not set.

Definition at line 277 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.58 rpki.exceptions.ChildNotFound Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.58.1 Detailed Description

Could not find specified child in database.

Definition at line 117 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.59 rpki.exceptions.ClassNameMismatch Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.59.1 Detailed Description

class\_name does not match child context.

Definition at line 132 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.60 rpki.exceptions.ClassNameUnknown Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.60.1 Detailed Description

Unknown class\_name.

Definition at line 137 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.61 rpki.exceptions.ClientNotFound Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)



### 10.61.1 Detailed Description

Could not find specified client in database.

Definition at line 237 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.62 rpki.exceptions.CMSContentNotSet Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.62.1 Detailed Description

Inner content of a CMS\_object has not been set. If object is known to be valid, the .extract() method should be able to set the content; otherwise, only the .verify() method (which checks signatures) is safe.

Definition at line 302 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.63 rpki.exceptions.CMSCRLNotSet Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.63.1 Detailed Description

CMS CRL has not been configured.

Definition at line 217 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.64 rpki.exceptions.CMSVerificationFailed Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.64.1 Detailed Description

Verification of a CMS message failed.

Definition at line 66 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.65 rpki.exceptions.DBConsistencyError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.65.1 Detailed Description

Found multiple matches for a database query that shouldn't ever return that.

Definition at line 60 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.66 rpki.exceptions.DERObjectConversionError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.66.1 Detailed Description

Error trying to convert a DER-based object from one representation to another.

Definition at line 76 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.67 rpki.exceptions.DuplicateObject Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.67.1 Detailed Description

Attempt to create an object that already exists.

Definition at line 262 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.68 rpki.exceptions.EmptyPEM Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.68.1 Detailed Description

Couldn't find PEM block to convert.

Definition at line 187 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.69 rpki.exceptions.EmptyROAPrefixList Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.69.1 Detailed Description

Can't create ROA with an empty prefix list.

Definition at line 267 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.70 rpki.exceptions.ForbiddenURI Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.70.1 Detailed Description

Forbidden URI, does not start with correct base URI.

Definition at line 247 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.71 rpki.exceptions.HandleTranslationError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.71.1 Detailed Description

Internal error translating protocol handle -> SQL id.

Definition at line 292 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.72 rpki.exceptions.HTTPRequestFailed Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.72.1 Detailed Description

HTTP request failed.

Definition at line 71 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.73 rpki.exceptions.HTTPSBadVersion Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.73.1 Detailed Description

HTTPS couldn't parse HTTP version.

Definition at line 287 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.74 rpki.exceptions.HTTPSClientAborted Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.74.1 Detailed Description

HTTPS client connection closed while in request-sent state.

Definition at line 252 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.75 rpki.exceptions.HTTPSUnexpectedState Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.75.1 Detailed Description

HTTPS event occurred in an unexpected state.

Definition at line 282 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.76 rpki.exceptions.MissingCMSCRL Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.76.1 Detailed Description

Didn't receive CMS CRL when expecting one.

Definition at line 207 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.77 rpki.exceptions.MissingCMSEECert Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.77.1 Detailed Description

Didn't receive CMS EE cert when expecting one.

Definition at line 202 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.78 rpki.exceptions.MultipleTLSEECert Class Reference

Inherits [rpki::exceptions::TLSValidationError](#)

### 10.78.1 Detailed Description

Received more than one TLS EE certificate.

Definition at line 172 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.79 rpki.exceptions.MustBePrefix Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.79.1 Detailed Description

Resource range cannot be expressed as a prefix.

Definition at line 162 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.80 rpki.exceptions.NoActiveCA Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.80.1 Detailed Description

No active ca\_detail for specified class.

Definition at line 227 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.81 rpki.exceptions.NoCoveringCertForROA Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.81.1 Detailed Description

Couldn't find a covering certificate to generate ROA.

Definition at line 272 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.82 rpki.exceptions.NoObjectAtURI Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.82.1 Detailed Description

No object published at specified URI.

Definition at line 297 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.83 rpki.exceptions.NotACertificateChain Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.83.1 Detailed Description

Certificates don't form a proper chain.

Definition at line 82 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.84 rpki.exceptions.NotFound Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.84.1 Detailed Description

Object not found in database.

Definition at line 157 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.85 rpki.exceptions.NotImplementedYet Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)



### 10.85.1 Detailed Description

Internal error -- not implemented yet.

Definition at line 102 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.86 rpki.exceptions.NotInDatabase Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.86.1 Detailed Description

Lookup failed for an object expected to be in the database.

Definition at line 40 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.87 rpki.exceptions.ReceivedTLSCACert Class Reference

Inherits [rpki::exceptions::TLSValidationError](#)

### 10.87.1 Detailed Description

Received CA certificate via TLS.

Definition at line 177 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.88 rpki.exceptions.RPKI\_Exception Class Reference

Inherits [Exception](#)

Inherited by [rpki.exceptions.BadClassNameSyntax](#), [rpki.exceptions.BadClientURL](#),  
[rpki.exceptions.BadContactURL](#) and [rpki.exceptions.BadExtension](#)

<a href="#">rpki.exceptions.BadIRDBReply</a>	<a href="#">rpki.exceptions.BadIssueResponse</a>
<a href="#">rpki.exceptions.BadPKCS10</a>	<a href="#">rpki.exceptions.BadPublicationReply</a>
<a href="#">rpki.exceptions.BadQuery</a>	<a href="#">rpki.exceptions.BadSender</a>
<a href="#">rpki.exceptions.BadStatusCode</a>	<a href="#">rpki.exceptions.BadURISyntax</a>
<a href="#">rpki.exceptions.BSCNotFound</a>	<a href="#">rpki.exceptions.BSCNotReady</a>
<a href="#">rpki.exceptions.ChildNotFound</a>	<a href="#">rpki.exceptions.ClassNameMismatch</a>
<a href="#">rpki.exceptions.ClassNameUnknown</a>	<a href="#">rpki.exceptions.ClientNotFound</a>
<a href="#">rpki.exceptions.CMSContentNotSet</a>	<a href="#">rpki.exceptions.CMSCRLNotSet</a>
<a href="#">rpki.exceptions.CMSVerificationFailed</a>	<a href="#">rpki.exceptions.DBConsistencyError</a>
<a href="#">rpki.exceptions.DERObjectConversionError</a>	<a href="#">rpki.exceptions.DuplicateObject</a>
<a href="#">rpki.exceptions.EmptyPEM</a>	<a href="#">rpki.exceptions.EmptyROAPre xList</a>
<a href="#">rpki.exceptions.ForbiddenURI</a>	<a href="#">rpki.exceptions.HandleTranslationError</a>
<a href="#">rpki.exceptions.HTTPRequestFailed</a>	<a href="#">rpki.exceptions.HTTPSBadVersion</a>
<a href="#">rpki.exceptions.HTTPSClientAborted</a>	<a href="#">rpki.exceptions.HTTPSUnexpectedState</a>
<a href="#">rpki.exceptions.MissingCMSCRL</a>	<a href="#">rpki.exceptions.MissingCMSEECert</a>
<a href="#">rpki.exceptions.MustBePre x</a>	<a href="#">rpki.exceptions.NoActiveCA</a>
<a href="#">rpki.exceptions.NoCoveringCertForROA</a>	<a href="#">rpki.exceptions.NoObjectAtURI</a>
<a href="#">rpki.exceptions.NotACertificateChain</a>	<a href="#">rpki.exceptions.NotFound</a>
<a href="#">rpki.exceptions.NotImplementedYet</a>	<a href="#">rpki.exceptions.NotInDatabase</a>
<a href="#">rpki.exceptions.ServerShuttingDown</a>	<a href="#">rpki.exceptions.SKIMismatch</a>
<a href="#">rpki.exceptions.SubprocessError</a>	<a href="#">rpki.exceptions.TLSValidationError</a>
<a href="#">rpki.exceptions.UnexpectedCMSCerts</a>	<a href="#">rpki.exceptions.UnexpectedCMSCRLs</a>
<a href="#">rpki.exceptions.UnparsableCMSDER</a>	<a href="#">rpki.exceptions.UpstreamError</a>
<a href="#">rpki.exceptions.WrongContentType</a>	<a href="#">and</a>

### 10.88.1 Detailed Description

Base class for RPKI exceptions.

Definition at line 35 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.89 rpki.exceptions.ServerShuttingDown Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.89.1 Detailed Description

Server is shutting down.

Definition at line 222 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.90 rpki.exceptions.SKIMismatch Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.90.1 Detailed Description

SKI value in response does not match request.

Definition at line 142 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.91 rpki.exceptions.SubprocessError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.91.1 Detailed Description

Subprocess returned unexpected error.

Definition at line 147 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.92 rpki.exceptions.TLSValidationError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

Inherited by [rpki.exceptions.MultipleTLSEECert](#) and [rpki.exceptions.ReceivedTLSCACert](#)

### 10.92.1 Detailed Description

TLS certificate validation error.

Definition at line 167 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.93 rpki.exceptions.UnexpectedCMSCerts Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.93.1 Detailed Description

Received CMS certs when not expecting any.

Definition at line 192 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.94 rpki.exceptions.UnexpectedCMSCRLs Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.94.1 Detailed Description

Received CMS CRLs when not expecting any.

Definition at line 197 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.95 rpki.exceptions.UnparsableCMSDER Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.95.1 Detailed Description

Alleged CMS DER wasn't parsable.

Definition at line 212 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.96 rpki.exceptions.UpstreamError Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.96.1 Detailed Description

Received an error from upstream.

Definition at line 112 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.97 rpki.exceptions.WrongEContentType Class Reference

Inherits [rpki::exceptions::RPKI\\_Exception](#)

### 10.97.1 Detailed Description

Received wrong CMS eContentType.

Definition at line 182 of file exceptions.py.

The documentation for this class was generated from the following file:

- [exceptions.py \(2907\)](#)

## 10.98 rpki.https.http\_client Class Reference

Inherits [rpki::https::http\\_stream](#)

Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def handle\\_close](#)

- def [handle\\_connect](#)
- def [handle\\_error](#)
- def [handle\\_message](#)
- def [handle\\_no\\_content\\_length](#)
- def [handle\\_timeout](#)
- def [send\\_request](#)
- def [set\\_state](#)
- def [start](#)
- def [tls\\_connect](#)

#### Public Attributes

- [cert](#)
- [expect\\_close](#)
- [hostport](#)
- [key](#)
- [queue](#)
- [retry\\_read](#)
- [retry\\_write](#)
- [state](#)
- [ta](#)
- [tls](#)

#### Static Public Attributes

- [parse\\_type](#)= [http\\_response](#)
- [timeout](#)= [default\\_client\\_timeout](#)

#### 10.98.1 Detailed Description

Definition at line 519 of file `https.py`.

#### 10.98.2 Member Function Documentation

- 10.98.2.1 `def rpki.https.http_client.__init__(self, queue, hostport, cert=None, key=None, ta=())`

Definition at line 525 of file `https.py`.

10.98.2.2 def rpki.https.http\_client.handle\_close(self)

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 614 of file https.py.

10.98.2.3 def rpki.https.http\_client.handle\_connect(self)

Definition at line 546 of file https.py.

10.98.2.4 def rpki.https.http\_client.handle\_error(self)

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 629 of file https.py.

10.98.2.5 def rpki.https.http\_client.handle\_messages(self)

Definition at line 587 of file https.py.

10.98.2.6 def rpki.https.http\_client.handle\_no\_content\_length(self)

Definition at line 576 of file https.py.

10.98.2.7 def rpki.https.http\_client.handle\_timeout(self)

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 623 of file https.py.

10.98.2.8 def rpki.https.http\_client.send\_request(self, msg)

Definition at line 579 of file https.py.

10.98.2.9 def rpki.https.http\_client.set\_state(self, state)

Definition at line 572 of file https.py.

10.98.2.10 def rpki.https.http\_client.start(self)

Definition at line 537 of file https.py.

10.98.2.11 def rpki.https.http\_client.tls\_connect(self)

Definition at line 560 of file https.py.

### 10.98.3 Member Data Documentation

10.98.3.1 rpki.https.http\_client.cert

Definition at line 533 of file https.py.

10.98.3.2 rpki.https.http\_client.expect\_close

Definition at line 532 of file https.py.

10.98.3.3 rpki.https.http\_client.hostport

Definition at line 530 of file https.py.

10.98.3.4 rpki.https.http\_client.key

Definition at line 534 of file https.py.



### 10.98.3.5 rpki.https.http\_client.parse\_type = http\_response[static]

Definition at line 521 of file https.py.

### 10.98.3.6 rpki.https.http\_client.queue

Definition at line 529 of file https.py.

### 10.98.3.7 rpki.https.http\_client.retry\_read

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 564 of file https.py.

### 10.98.3.8 rpki.https.http\_client.retry\_write

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 566 of file https.py.

### 10.98.3.9 rpki.https.http\_client.state

Definition at line 531 of file https.py.

### 10.98.3.10 rpki.https.http\_client.ta

Definition at line 535 of file https.py.

### 10.98.3.11 rpki.https.http\_client.timeout = default\_client\_timeout [static]

Definition at line 523 of file https.py.

## 10.98.3.12 rpki.https.http\_client.tls

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 548 of file `https.py`.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.99 rpki.https.http\_listener Class Reference

Inherits [asyncore.dispatcher](#)

## Public Member Functions

- `def __init__`
- `def handle_accept`
- `def handle_error`

## Public Attributes

- `cert`
- `dynamic_ta`
- `handlers`
- `key`
- `ta`

## Static Public Attributes

- `log = log_method`

## 10.99.1 Detailed Description

Definition at line 477 of file `https.py`.

## 10.99.2 Member Function Documentation

10.99.2.1 `def rpki.https.http_listener.__init__(self, handlers, port = 80, host = "", cert = None, key = None, ta = None, dynamic_ta = None)`

Definition at line 481 of file https.py.

10.99.2.2 def rpki.https.http\_listener.handle\_accept(self)

Definition at line 502 of file https.py.

10.99.2.3 def rpki.https.http\_listener.handle\_error(self)

Definition at line 511 of file https.py.

10.99.3 Member Data Documentation

10.99.3.1 rpki.https.http\_listener.cert

Definition at line 485 of file https.py.

10.99.3.2 rpki.https.http\_listener.dynamic\_ta

Definition at line 488 of file https.py.

10.99.3.3 rpki.https.http\_listener.handlers

Definition at line 484 of file https.py.

10.99.3.4 rpki.https.http\_listener.key

Definition at line 486 of file https.py.

10.99.3.5 rpki.https.http\_listener.log = log\_method [static]

Definition at line 479 of file https.py.

## 10.99.3.6 rpk.https.http\_listener.ta

Definition at line 487 of file https.py.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.100 rpk.https.http\_message Class Reference

Inherits [object](#)

Inherited by [rpk.https.http\\_request](#) and [rpk.https.http\\_response](#)

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def \\_\\_str\\_\\_](#)
- [def format](#)
- [def normalize\\_headers](#)
- [def parse\\_from\\_wire](#)
- [def parse\\_version](#)
- [def persistent](#)

## Public Attributes

- [body](#)
- [headers](#)
- [version](#)

## Static Public Attributes

- string [software\\_name](#) = "ISC RPKI library"

## 10.100.1 Detailed Description

Definition at line 63 of file https.py.

## 10.100.2 Member Function Documentation

10.100.2.1 `def rpki.https.http_message.__init__(self, version= None, body= None, headers= None)`

Definition at line 67 of file `https.py`.

10.100.2.2 `def rpki.https.http_message.__str__(self)`

Definition at line 115 of file `https.py`.

10.100.2.3 `def rpki.https.http_message.format(self)`

Definition at line 103 of file `https.py`.

10.100.2.4 `def rpki.https.http_message.normalize_headers(self, headers= None)`

Definition at line 73 of file `https.py`.

10.100.2.5 `def rpki.https.http_message.parse_from_wire(s, headers= None)`

Definition at line 92 of file `https.py`.

10.100.2.6 `def rpki.https.http_message.parse_version(self, version)`

Definition at line 118 of file `https.py`.

10.100.2.7 `def rpki.https.http_message.persistent(self)`

Definition at line 123 of file `https.py`.

### 10.100.3 Member Data Documentation

#### 10.100.3.1 rpki.https.http\_message.body

Definition at line 69 of file `https.py`.

#### 10.100.3.2 rpki.https.http\_message.headers

Definition at line 70 of file `https.py`.

#### 10.100.3.3 string rpki.https.http\_message.software\_name = "ISC RPKI library" [static]

Definition at line 65 of file `https.py`.

#### 10.100.3.4 rpki.https.http\_message.version

Definition at line 68 of file `https.py`.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.101 rpki.https.http\_queue Class Reference

Inherits [object](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [detach](#)
- def [request](#)
- def [restart](#)
- def [return\\_result](#)
- def [send\\_request](#)

### Public Attributes

- [cert](#)
- [client](#)
- [hostport](#)
- [key](#)
- [queue](#)
- [ta](#)

### Static Public Attributes

- [log](#) = `log_method`

#### 10.101.1 Detailed Description

Definition at line 634 of file `https.py`.

#### 10.101.2 Member Function Documentation

10.101.2.1 `def rpki.https.http_queue.__init__(self, hostport, cert=None, key=None, ta=())`

Definition at line 638 of file `https.py`.

10.101.2.2 `def rpki.https.http_queue.detach(self, client)`

Definition at line 673 of file `https.py`.

10.101.2.3 `def rpki.https.http_queue.request(self, request)`

Definition at line 648 of file `https.py`.

10.101.2.4 `def rpki.https.http_queue.restart(self)`

Definition at line 652 of file `https.py`.

10.101.2.5 def rpki.https.http\_queue.return\_result (self, result)

Definition at line 678 of file https.py.

10.101.2.6 def rpki.https.http\_queue.send\_request (self)

Definition at line 669 of file https.py.

10.101.3 Member Data Documentation

10.101.3.1 rpki.https.http\_queue.cert

Definition at line 644 of file https.py.

10.101.3.2 rpki.https.http\_queue.client

Definition at line 642 of file https.py.

10.101.3.3 rpki.https.http\_queue.hostport

Definition at line 641 of file https.py.

10.101.3.4 rpki.https.http\_queue.key

Definition at line 645 of file https.py.

10.101.3.5 rpki.https.http\_queue.log = log\_method[static]

Definition at line 636 of file https.py.



## 10.101.3.6 rpki.https.http\_queue.queue

Definition at line 643 of file `https.py`.

## 10.101.3.7 rpki.https.http\_queue.ta

Definition at line 646 of file `https.py`.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.102 rpki.https.http\_request Class Reference

Inherits [rpki::https::http\\_message](#)

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def format\\_rst\\_line](#)
- [def parse\\_rst\\_line](#)

## Public Attributes

- [callback](#)
- [cmd](#)
- [errback](#)
- [path](#)
- [retried](#)

## 10.102.1 Detailed Description

Definition at line 132 of file `https.py`.

### 10.102.2 Member Function Documentation

10.102.2.1 `def rpki.https.http_request.__init__(self, cmd= None, path= None, version= default_http_version, body= None, callback= None, errback= None, header$`

Definition at line 134 of file `https.py`.

10.102.2.2 `def rpki.https.http_request.format_rst_line (self)`

Definition at line 148 of file `https.py`.

10.102.2.3 `def rpki.https.http_request.parse_rst_line (self, cmd, path, version)`

Definition at line 143 of file `https.py`.

### 10.102.3 Member Data Documentation

10.102.3.1 `rpki.https.http_request.callback`

Definition at line 139 of file `https.py`.

10.102.3.2 `rpki.https.http_request.cmd`

Definition at line 137 of file `https.py`.

10.102.3.3 `rpki.https.http_request.errback`

Definition at line 140 of file `https.py`.

## 10.102.3.4 rpki.https.http\_request.path

Definition at line 138 of file https.py.

## 10.102.3.5 rpki.https.http\_request.retried

Definition at line 141 of file https.py.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.103 rpki.https.http\_response Class Reference

Inherits [rpki::https::http\\_message](#)

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def format\\_rst\\_line](#)
- [def parse\\_rst\\_line](#)

## Public Attributes

- [code](#)
- [reason](#)

## 10.103.1 Detailed Description

Definition at line 152 of file https.py.

## 10.103.2 Member Function Documentation

10.103.2.1 `def rpki.https.http_response.__init__(self, code= None, reason= None, version= default_http_version, body= None, headers= None)`

Definition at line 154 of file https.py.

10.103.2.2 def rpki.https.http\_response.format\_rst\_line (self)

Definition at line 164 of file https.py.

10.103.2.3 def rpki.https.http\_response.parse\_rst\_line (self, version, code, reason)

Definition at line 159 of file https.py.

10.103.3 Member Data Documentation

10.103.3.1 rpki.https.http\_response.code

Definition at line 156 of file https.py.

10.103.3.2 rpki.https.http\_response.reason

Definition at line 157 of file https.py.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

10.104 rpki.https.http\_server Class Reference

Inherits [rpki::https::http\\_stream](#)

Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [nd\\_handler](#)
- def [handle\\_message](#)
- def [handle\\_no\\_content\\_length](#)
- def [send\\_error](#)
- def [send\\_message](#)
- def [send\\_reply](#)
- def [tls\\_accept](#)

### Public Attributes

- [expect\\_close](#)
- [handlers](#)
- [retry\\_read](#)
- [retry\\_write](#)
- [tls](#)

### Static Public Attributes

- [parse\\_type= http\\_request](#)
- [timeout= default\\_server\\_timeout](#)

#### 10.104.1 Detailed Description

Definition at line 381 of file `https.py`.

#### 10.104.2 Member Function Documentation

10.104.2.1 `def rpki.https.http_server.__init__(self, sock, handlers, cert=None, key=None, ta=(), dynamic_ta=None)`

Definition at line 387 of file `https.py`.

10.104.2.2 `def rpki.https.http_server.nd_handler(self, path)`

Helper method to search `self.handlers`.

Definition at line 423 of file `https.py`.

10.104.2.3 `def rpki.https.http_server.handle_message(self)`

Definition at line 432 of file `https.py`.

10.104.2.4 `def rpki.https.http_server.handle_no_content_length(self)`

Definition at line 420 of file `https.py`.

10.104.2.5 `def rpki.https.http_server.send_error(self, code, reason)`

Definition at line 455 of file `https.py`.

10.104.2.6 `def rpki.https.http_server.send_message(self, code, reason="OK",  
body=None)`

Definition at line 461 of file `https.py`.

10.104.2.7 `def rpki.https.http_server.send_reply(self, code, body)`

Definition at line 458 of file `https.py`.

10.104.2.8 `def rpki.https.http_server.tls_accept(self)`

Definition at line 409 of file `https.py`.

10.104.3 Member Data Documentation

10.104.3.1 `rpki.https.http_server.expect_close`

Definition at line 391 of file `https.py`.

10.104.3.2 `rpki.https.http_server.handlers`

Definition at line 389 of file `https.py`.

10.104.3.3 rpki.https.http\_server.parse\_type = http\_request[static]

Definition at line 383 of file https.py.

10.104.3.4 rpki.https.http\_server.retry\_read

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 413 of file https.py.

10.104.3.5 rpki.https.http\_server.retry\_write

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 415 of file https.py.

10.104.3.6 rpki.https.http\_server.timeout = default\_server\_timeout  
[static]

Definition at line 385 of file https.py.

10.104.3.7 rpki.https.http\_server.tls

Reimplemented from [rpki.https.http\\_stream](#)

Definition at line 395 of file https.py.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

10.105 rpki.https.http\_stream Class Reference

Inherits [asyncio::async\\_chat](#)

Inherited by [rpki.https.http\\_client](#) and [rpki.https.http\\_server](#)

### Public Member Functions

- def `__init__`
- def `chunk_body`
- def `chunk_discard_crlf`
- def `chunk_discard_trailer`
- def `chunk_header`
- def `close`
- def `collect_incoming_data`
- def `found_terminator`
- def `get_buffer`
- def `handle_body`
- def `handle_close`
- def `handle_error`
- def `handle_read`
- def `handle_timeout`
- def `handle_write`
- def `initiate_send`
- def `log_cert`
- def `readable`
- def `recv`
- def `restart`
- def `send`
- def `update_timeout`
- def `writable`

### Public Attributes

- `buffer`
- `chunk_handler`
- `msg`
- `timer`

### Static Public Attributes

- `log` = `log_method`
- `retry_read` = `None`
- `retry_write` = `None`
- `tls` = `None`

#### 10.105.1 Detailed Description

Definition at line 174 of file `https.py`.



## 10.105.2 Member Function Documentation

10.105.2.1 `def rpki.https.http_stream.__init__(self, sock= None)`

Definition at line 181 of file `https.py`.

10.105.2.2 `def rpki.https.http_stream.chunk_body(self)`

Definition at line 241 of file `https.py`.

10.105.2.3 `def rpki.https.http_stream.chunk_discard_crlf(self)`

Definition at line 248 of file `https.py`.

10.105.2.4 `def rpki.https.http_stream.chunk_discard_trailer(self)`

Definition at line 254 of file `https.py`.

10.105.2.5 `def rpki.https.http_stream.chunk_header(self)`

Definition at line 231 of file `https.py`.

10.105.2.6 `def rpki.https.http_stream.close(self, force= False )`

Definition at line 356 of file `https.py`.

10.105.2.7 `def rpki.https.http_stream.collect_incoming_data(self, data)`

Buffer the data

Definition at line 202 of file `https.py`.

10.105.2.8 def rpki.https.http\_stream.found\_terminator (self)

Definition at line 214 of file https.py.

10.105.2.9 def rpki.https.http\_stream.get\_buffer (self)

Definition at line 209 of file https.py.

10.105.2.10 def rpki.https.http\_stream.handle\_body (self)

Definition at line 261 of file https.py.

10.105.2.11 def rpki.https.http\_stream.handle\_close (self)

Reimplemented in [rpki.https.http\\_client](#)

Definition at line 280 of file https.py.

10.105.2.12 def rpki.https.http\_stream.handle\_error (self)

Reimplemented in [rpki.https.http\\_client](#)

Definition at line 265 of file https.py.

10.105.2.13 def rpki.https.http\_stream.handle\_read (self)

Definition at line 301 of file https.py.

10.105.2.14 def rpki.https.http\_stream.handle\_timeout (self)

Reimplemented in [rpki.https.http\\_client](#)

Definition at line 276 of file https.py.

10.105.2.15 `def rpkgi.https.http_stream.handle_write (self)`

Definition at line 322 of file `https.py`.

10.105.2.16 `def rpkgi.https.http_stream.initiate_send (self)`

Definition at line 341 of file `https.py`.

10.105.2.17 `def rpkgi.https.http_stream.log_cert (self, tag, x)`

Definition at line 377 of file `https.py`.

10.105.2.18 `def rpkgi.https.http_stream.readable (self)`

Definition at line 295 of file `https.py`.

10.105.2.19 `def rpkgi.https.http_stream.recv (self, buffer_size)`

Definition at line 290 of file `https.py`.

10.105.2.20 `def rpkgi.https.http_stream.restart (self)`

Definition at line 187 of file `https.py`.

10.105.2.21 `def rpkgi.https.http_stream.send (self, data)`

Definition at line 285 of file `https.py`.

10.105.2.22 `def rpki.https.http_stream.update_timeout(self)`

Definition at line 196 of file `https.py`.

10.105.2.23 `def rpki.https.http_stream.writeable(self)`

Definition at line 298 of file `https.py`.

10.105.3 Member Data Documentation

10.105.3.1 `rpki.https.http_stream.buffer`

Definition at line 183 of file `https.py`.

10.105.3.2 `rpki.https.http_stream.chunk_handler`

Definition at line 189 of file `https.py`.

10.105.3.3 `rpki.https.http_stream.log = log_method [static]`

Definition at line 176 of file `https.py`.

10.105.3.4 `rpki.https.http_stream.msg`

Definition at line 221 of file `https.py`.

10.105.3.5 `rpki.https.http_stream.retry_read = None [static]`

Reimplemented in [rpki.https.http\\_server](#) and [rpki.https.http\\_client](#)

Definition at line 178 of file `https.py`.

10.105.3.6 rpki.https.http\_stream.retry\_write = None [static]

Reimplemented in [rpki.https.http\\_server](#) and [rpki.https.http\\_client](#)  
Definition at line 179 of file `https.py`.

10.105.3.7 rpki.https.http\_stream.timer

Definition at line 184 of file `https.py`.

10.105.3.8 rpki.https.http\_stream.tls = None [static]

Reimplemented in [rpki.https.http\\_server](#) and [rpki.https.http\\_client](#)  
Definition at line 177 of file `https.py`.

The documentation for this class was generated from the following file:

- [https.py \(2902\)](#)

## 10.106 rpki.ipaddrs.v4addr Class Reference

Inherits [long](#).

### Public Member Functions

- def [\\_\\_new\\_\\_](#)
- def [\\_\\_str\\_\\_](#)
- def [from\\_bytes](#)
- def [to\\_bytes](#)

### Static Public Attributes

- int [bits](#) = 32

#### 10.106.1 Detailed Description

IPv4 address.

Derived from `long`, but supports IPv4 print syntax.

Definition at line 47 of file ipaddrs.py.

### 10.106.2 Member Function Documentation

#### 10.106.2.1 def rpki.ipaddrs.v4addr.\_\_new\_\_(cls, x)

Construct a v4addr object.

Definition at line 56 of file ipaddrs.py.

#### 10.106.2.2 def rpki.ipaddrs.v4addr.\_\_str\_\_(self)

Convert a v4addr object to string format.

Definition at line 74 of file ipaddrs.py.

#### 10.106.2.3 def rpki.ipaddrs.v4addr.from\_bytes(cls, x)

Convert from a raw byte string to a v4addr object.

Definition at line 70 of file ipaddrs.py.

#### 10.106.2.4 def rpki.ipaddrs.v4addr.to\_bytes(self)

Convert a v4addr object to a raw byte string.

Definition at line 65 of file ipaddrs.py.

### 10.106.3 Member Data Documentation

#### 10.106.3.1 int rpki.ipaddrs.v4addr.bits = 32 [static]

Definition at line 54 of file ipaddrs.py.

The documentation for this class was generated from the following file:

- [ipaddrs.py \(2424\)](#)

## 10.107 rpki.ipaddrs.v6addr Class Reference

Inherits [long](#).

### Public Member Functions

- def [\\_\\_new\\_\\_](#)
- def [\\_\\_str\\_\\_](#)
- def [from\\_bytes](#)
- def [to\\_bytes](#)

### Static Public Attributes

- int [bits](#) = 128

#### 10.107.1 Detailed Description

IPv6 address.

Derived from long, but supports IPv6 print syntax.

Definition at line 78 of file ipaddrs.py.

#### 10.107.2 Member Function Documentation

##### 10.107.2.1 def rpki.ipaddrs.v6addr.\_\_new\_\_(cls, x)

Construct a v6addr object.

Definition at line 87 of file ipaddrs.py.

##### 10.107.2.2 def rpki.ipaddrs.v6addr.\_\_str\_\_(self)

Convert a v6addr object to string format.

Definition at line 104 of file ipaddrs.py.

### 10.107.2.3 def rpki.ipaddrs.v6addr.from\_bytes(cls, x)

Convert from a raw byte string to a v6addr object.

Definition at line 99 of file ipaddrs.py.

### 10.107.2.4 def rpki.ipaddrs.v6addr.to\_bytes(self)

Convert a v6addr object to a raw byte string.

Definition at line 94 of file ipaddrs.py.

## 10.107.3 Member Data Documentation

### 10.107.3.1 int rpki.ipaddrs.v6addr.bits = 128 [static]

Definition at line 85 of file ipaddrs.py.

The documentation for this class was generated from the following file:

- [ipaddrs.py \(2424\)](#)

## 10.108 rpki.left\_right.bsc\_elt Class Reference

Inherits [rpki::left\\_right::data\\_elt](#)

Inherited by [irbe\\_cli.bsc\\_elt](#)

### Public Member Functions

- def [children](#)
- def [parents](#)
- def [repositories](#)
- def [serve\\_pre\\_save\\_hook](#)



## Static Public Attributes

- tuple `attributes` = ("action", "tag", "self\_handle", "bsc\_handle", "key\_type", "hash\_alg", "key\_length")  
XML attributes for this element.
- tuple `booleans` = ("generate\_keypair",)  
Boolean attributes (value "yes" or "no") for this element.
- string `element_name` = "bsc"
- tuple `elements` = ("signing\_cert", "signing\_cert\_crl", "pkcs10\_request")  
XML elements contained by this element.
- tuple `handles` = (("self", self\_elt),)
- `pkcs10_request` = None
- `private_key_id` = None
- `signing_cert` = None
- `signing_cert_crl` = None
- tuple `sql_template`

## 10.108.1 Detailed Description

<bsc/> (Business Signing Context) element.

Definition at line 526 of file `left_right.py`.

## 10.108.2 Member Function Documentation

## 10.108.2.1 def rpki.left\_right.bsc\_elt.children (self)

Fetch all child objects that link to this BSC object.

Definition at line 557 of file `left_right.py`.

## 10.108.2.2 def rpki.left\_right.bsc\_elt.parents (self)

Fetch all parent objects that link to this BSC object.

Definition at line 553 of file `left_right.py`.

### 10.108.2.3 def rpki.left\_right.bsc\_elt.repositories \$self

Fetch all repository objects that link to this BSC object.

Definition at line 549 of file left\_right.py.

### 10.108.2.4 def rpki.left\_right.bsc\_elt.serve\_pre\_save\_hooks(\$self, q\_pdu, r\_pdu, cb, eb)

Extra server actions for bsc\_elt -- handle key generation. For now this only allows RSA with SHA-256.

Reimplemented from [rpki.left\\_right.data\\_elt](#)

Definition at line 561 of file left\_right.py.

## 10.108.3 Member Data Documentation

### 10.108.3.1 tuple rpki.left\_right.bsc\_elt.attributes = ("action", "tag", "self\_handle", "bsc\_handle", "key\_type", "hash\_alg", "key\_length") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 532 of file left\_right.py.

### 10.108.3.2 tuple rpki.left\_right.bsc\_elt.booleans = ("generate\_keypair",) [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 534 of file left\_right.py.

### 10.108.3.3 string rpki.left\_right.bsc\_elt.element\_name = "bsc" [static]

Definition at line 531 of file left\_right.py.

```
10.108.3.4 tuple rpki.left_right.bsc_elt.elements = ("signing_cert",  
            "signing_cert_crl", "pkcs10_request") [static]
```

XML elements contained by this element.

Reimplemented from [mpki.xml\\_utils.base\\_elt](#)

Definition at line 533 of file left\_right.py.

```
10.108.3.5 tuple rpki.left_right.bsc_elt.handles = ("self", self_elt),  
            [static]
```

Reimplemented from [mpki.left\\_right.data\\_elt](#)

Definition at line 542 of file left\_right.py.

```
10.108.3.6 rpki.left_right.bsc_elt.pkcs10_request = None[static]
```

Definition at line 545 of file left\_right.py.

```
10.108.3.7 rpki.left_right.bsc_elt.private_key_id = None [static]
```

Definition at line 544 of file left\_right.py.

```
10.108.3.8 rpki.left_right.bsc_elt.signing_cert = None[static]
```

Reimplemented in [irbe\\_cli.bsc\\_elt](#)

Definition at line 546 of file left\_right.py.

```
10.108.3.9 rpki.left_right.bsc_elt.signing_cert_crl = None[static]
```

Reimplemented in [irbe\\_cli.bsc\\_elt](#)

Definition at line 547 of file left\_right.py.

#### 10.108.3.10 tuple rpki.left\_right.bsc\_elt.sql\_template [static]

Initial value:

```
rpki.sql_template("bsc", "bsc_id", "bsc_handle",
                  "self_id", "hash_alg",
                  ("private_key_id", rpki.x509.RSA),
                  ("pkcs10_request", rpki.x509.PKCS10),
                  ("signing_cert", rpki.x509.X509),
                  ("signing_cert_crl", rpki.x509.CRL))
```

Definition at line 536 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.109 rpki.left\_right.child\_elt Class Reference

Inherits [rpki::left\\_right::data\\_elt](#)

Inherited by [irbe\\_cli.child\\_elt](#)

### Public Member Functions

- def [ca\\_from\\_class\\_name](#)
- def [child\\_certs](#)
- def [endElement](#)
- def [parents](#)
- def [serve\\_destroy\\_hook](#)
- def [serve\\_post\\_save\\_hook](#)
- def [serve\\_up\\_down](#)

### Static Public Attributes

- tuple [attributes](#) = ("action", "tag", [self\\_handle](#), "child\_handle", "bsc\_handle")  
XML attributes for this element.
- tuple [booleans](#) = ("reissue", )  
Boolean attributes (value "yes" or "no") for this element.

- [bpki\\_cert](#)= None
- [bpki\\_glue](#)= None
- [clear\\_https\\_ta\\_cache](#)= False
- [stringelement\\_name](#) "child"
- [tupleelements](#)= ("bpki\_cert", ["bpki\\_glue"](#))  
XML elements contained by this element.
- [tuplehandles](#)= (("self", self\_elt), ("bsc", bsc\_elt))
- [tuplesql\\_template](#)

### 10.109.1 Detailed Description

<child/> element.

Definition at line 802 of file left\_right.py.

### 10.109.2 Member Function Documentation

#### 10.109.2.1 def rpki.left\_right.child\_elt.ca\_from\_class\_names(self, class\_name)

Fetch the CA corresponding to an up-down class\_name.

Definition at line 831 of file left\_right.py.

#### 10.109.2.2 def rpki.left\_right.child\_elt.child\_certs(self, ca\_detail= None, skip= None, unique= False )

Fetch all child\_cert objects that link to this child object.

Definition at line 823 of file left\_right.py.

#### 10.109.2.3 def rpki.left\_right.child\_elt.endElement(self, stack, name, text)

Handle subelements of <child/> element. These require special handling because modifying them invalidates the HTTPS trust anchor cache.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 863 of file left\_right.py.

#### 10.109.2.4 def rpki.left\_right.child\_elt.parents (self)

Fetch all parent objects that link to self object to which this child object links.

Definition at line 827 of file left\_right.py.

#### 10.109.2.5 def rpki.left\_right.child\_elt.serve\_destroy\_hook(self, cb, eb)

Extra server actions when destroying a child\_elt.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 855 of file left\_right.py.

#### 10.109.2.6 def rpki.left\_right.child\_elt.serve\_post\_save\_hook(self, q\_pdu, r\_pdu, cb, eb)

Extra server actions for child\_elt.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 845 of file left\_right.py.

#### 10.109.2.7 def rpki.left\_right.child\_elt.serve\_up\_down(self, query, callback)

Outer layer of server handling for one up-down PDU from this child.

Definition at line 873 of file left\_right.py.

### 10.109.3 Member Data Documentation

#### 10.109.3.1 tuple rpki.left\_right.child\_elt.attributes = ("action", "tag", "self\_handle", "child\_handle", "bsc\_handle") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 808 of file left\_right.py.

10.109.3.2 tuple rpki.left\_right.child\_elt.booleans = ("reissue", ) [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 810 of `le_left_right.py`.

10.109.3.3 rpki.left\_right.child\_elt.bpki\_cert = None [static]

Definition at line 819 of `le_left_right.py`.

10.109.3.4 rpki.left\_right.child\_elt.bpki\_glue = None [static]

Definition at line 820 of `le_left_right.py`.

10.109.3.5 rpki.left\_right.child\_elt.clear\_https\_ta\_cache = False[static]

Definition at line 821 of `le_left_right.py`.

10.109.3.6 string rpki.left\_right.child\_elt.element\_name = "child" [static]

Definition at line 807 of `le_left_right.py`.

10.109.3.7 tuple rpki.left\_right.child\_elt.elements = ("bpki\_cert", "bpki\_glue")  
[static]

XML elements contained by this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 809 of `le_left_right.py`.

10.109.3.8 tuple rpki.left\_right.child\_elt.handles = (("self", self\_elt), ("bsc", bsc\_elt)) [static]

Reimplemented from [rpki.left\\_right.data\\_elt](#)

Definition at line 817 of file left\_right.py.

10.109.3.9 tuple rpki.left\_right.child\_elt.sql\_template [static]

Initial value:

```
rpki.sql.template("child", "child_id", "child_handle",
                  "self_id", "bsc_id",
                  ("bpki_cert", rpki.x509.X509),
                  ("bpki_glue", rpki.x509.X509))
```

Definition at line 812 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.110 rpki.left\_right.cms\_msg Class Reference

Inherits [rpki::x509::XML\\_CMS\\_object](#)

Inherited by [irbe\\_cli.left\\_right cms\\_msg](#)

### Static Public Attributes

- string [encoding](#)= "us-ascii"
- [saxify](#) = sax\_handler.saxify
- [schema](#)= [rpki.relaxng.left\\_right](#)

### 10.110.1 Detailed Description

Class to hold a CMS-signed left-right PDU.

Definition at line 1076 of file left\_right.py.



## 10.110.2 Member Data Documentation

10.110.2.1 `string rpki.left_right.cms_msg.encoding = "us-ascii" [static]`

Definition at line 1081 of file `left_right.py`.

10.110.2.2 `rpki.left_right.cms_msg.saxify = sax_handler.saxify[static]`

Reimplemented in [irbe\\_cli.left\\_right cms\\_msg](#)

Definition at line 1083 of file `left_right.py`.

10.110.2.3 `rpki.left_right.cms_msg.schema = rpki.relaxng.left_right [static]`

Definition at line 1082 of file `left_right.py`.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.111 rpki.left\_right.data\_elt Class Reference

Inherits [rpki::xml\\_utils::data\\_elt](#), [rpki::sql::sql\\_persistent](#), and [rpki::left\\_right::left\\_right\\_namespace](#)

Inherited by [rpki.left\\_right.bsc\\_elt](#), [rpki.left\\_right.child\\_elt](#), [rpki.left\\_right.parent\\_elt](#), [rpki.left\\_right.repository\\_elt](#), and [rpki.left\\_right.self\\_elt](#)

## Public Member Functions

- `def bsc`
- `def make_reply_clone_hook`
- `def self`
- `def serve_fetch_all`
- `def serve_fetch_handle`
- `def serve_fetch_one_maybe`
- `def serve_pre_save_hook`

### Static Public Attributes

- tuple `handles`= ()
- `self_handle`= None
- `self_id`= None

#### 10.111.1 Detailed Description

Virtual class for top-level left-right protocol data elements.

Definition at line 50 of file `left_right.py`.

#### 10.111.2 Member Function Documentation

##### 10.111.2.1 def rpki.left\_right.data\_elt.bsc (self)

Return BSC object to which this object links.

Definition at line 64 of file `left_right.py`.

##### 10.111.2.2 def rpki.left\_right.data\_elt.make\_reply\_clone\_hooks (self, r\_pdu)

Set handles when cloning, including `_id` -> `_handle` translation.

Reimplemented from `rpki.xml_utils.data_elt`

Definition at line 68 of file `left_right.py`.

##### 10.111.2.3 def rpki.left\_right.data\_elt.self (self)

Fetch self object to which this object links.

Definition at line 60 of file `left_right.py`.

## 10.111.2.4 def rpkgi.left\_right.data\_elt.serve\_fetch\_all(self)

Find the objects on which a list method should operate.

Reimplemented in [rpkgi.left\\_right.self\\_elt](#)

Definition at line 99 of file left\_right.py.

## 10.111.2.5 def rpkgi.left\_right.data\_elt.serve\_fetch\_handle(self, gctx, self\_id, handle)

Find an object based on its handle.

Reimplemented in [rpkgi.left\\_right.self\\_elt](#)

Definition at line 84 of file left\_right.py.

## 10.111.2.6 def rpkgi.left\_right.data\_elt.serve\_fetch\_one\_maybe(self)

Find the object on which a get, set, or destroy method should operate, or which would conflict with a create method.

Reimplemented in [rpkgi.left\\_right.self\\_elt](#)

Definition at line 90 of file left\_right.py.

## 10.111.2.7 def rpkgi.left\_right.data\_elt.serve\_pre\_save\_hooks(self, q\_pdu, r\_pdu, cb, eb)

Hook to do \_handle => \_id translation before saving.

self is always the object to be saved to SQL. For create operations, self and q\_pdu are the same object; for set operations, self is the pre-existing object from SQL and q\_pdu is the set request received from the IRBE.

Reimplemented from [rpkgi.xml\\_utils.data\\_elt](#)

Reimplemented in [rpkgi.left\\_right.bsc\\_elt](#)

Definition at line 106 of file left\_right.py.

## 10.111.3 Member Data Documentation

10.111.3.1 tuple `rpki.left_right.data_elt.handles = ()` [static]

Reimplemented in [rpki.left\\_right.self\\_elt](#), [rpki.left\\_right.bsc\\_elt](#), [rpki.left\\_right.repository\\_elt](#), [rpki.left\\_right.parent\\_elt](#), and [rpki.left\\_right.child\\_elt](#)

Definition at line 55 of file `left_right.py`.

10.111.3.2 `rpki.left_right.data_elt.self_handle = None` [static]

Definition at line 58 of file `left_right.py`.

10.111.3.3 `rpki.left_right.data_elt.self_id = None` [static]

Definition at line 57 of file `left_right.py`.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.112 rpki.left\_right.left\_right\_namespace Class Reference

Inherits [object](#)

Inherited by [rpki.left\\_right.data\\_elt](#), [rpki.left\\_right.list\\_published\\_objects\\_elt](#), [rpki.left\\_right.list\\_resources\\_elt](#), [rpki.left\\_right.list\\_roa\\_requests\\_elt](#), [rpki.left\\_right.msg](#) and [rpki.left\\_right.report\\_error\\_elt](#)

Static Public Attributes

- dictionary `nsmap= { None : xmlns }`
- string `xmlns= "http://www.hactrn.net/uris/rpki/left-right-spec/"`

## 10.112.1 Detailed Description

XML namespace parameters for left-right protocol.

Definition at line 42 of file `left_right.py`.

## 10.112.2 Member Data Documentation

10.112.2.1 dictionary `rpki.left_right.left_right_namespace.nsmap = { None : xmlns }` [static]

Definition at line 48 of file `left_right.py`.

10.112.2.2 string `rpki.left_right.left_right_namespace.xmlns = "http://www.hactrn.net/uris/rpki/left-right-spec/"` [static]

Definition at line 47 of file `left_right.py`.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.113 rpki.left\_right.list\_published\_objects\_elt Class Reference

Inherits [rpki::xml\\_utils::text\\_elt](#) and [rpki::left\\_right::left\\_right\\_namespace](#)

Inherited by [irbe\\_cli.list\\_published\\_objects\\_elt](#)

## Public Member Functions

- def [make\\_reply](#)
- def [serve\\_dispatch](#)

## Static Public Attributes

- tuple [attributes](#)= ("self\_handle", "tag", "uri")  
XML attributes for this element.
- string [element\\_name](#)= "list\_published\_objects"
- [obj](#) = None
- string [text\\_attribute](#)= "obj"  
Name of the class attribute that holds the text value.

### 10.113.1 Detailed Description

<list\_published\_objects/> element.

Definition at line 965 of file left\_right.py.

### 10.113.2 Member Function Documentation

#### 10.113.2.1 def rpki.left\_right.list\_published\_objects\_elt.make\_reply(self, uri, obj)

Generate one reply PDU.

Definition at line 992 of file left\_right.py.

#### 10.113.2.2 def rpki.left\_right.list\_published\_objects\_elt.serve\_dispatch(self, r\_msg\_cb, eb)

Handle a <list\_published\_objects/> query. The method name is a misnomer here, there's no action attribute and no dispatch, we just dump every published object for the specified <self/> and return.

Definition at line 976 of file left\_right.py.

### 10.113.3 Member Data Documentation

#### 10.113.3.1 tuple rpki.left\_right.list\_published\_objects\_elt.attributes = ("self\_handle", "tag", "uri") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 971 of file left\_right.py.

#### 10.113.3.2 string rpki.left\_right.list\_published\_objects\_elt.element\_name = "list\_published\_objects" [static]

Definition at line 970 of file left\_right.py.

10.113.3.3 rpki.left\_right.list\_published\_objects\_elt.obj = None [static]

Definition at line 974 of file left\_right.py.

10.113.3.4 string rpki.left\_right.list\_published\_objects\_elt.text\_attribute =  
"obj" [static]

Name of the class attribute that holds the text value.

Reimplemented from [rpki.xml\\_utils.text\\_elt](#)

Definition at line 972 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.114 rpki.left\_right.list\_resources\_elt Class Reference

Inherits [rpki::xml\\_utils::base\\_elt](#) and [rpki::left\\_right::left\\_right\\_namespace](#)

### Public Member Functions

- def [startElement](#)
- def [toXML](#)

### Public Attributes

- [asn](#)
- [ipv4](#)
- [ipv6](#)

### Static Public Attributes

- tuple [attributes](#) = ("self\_handle", "tag", "child\_handle", [valid\\_until](#), "[asn](#)", "[ipv4](#)", "[ipv6](#)")  
XML attributes for this element.
- string [element\\_name](#) = "list\_resources"
- [valid\\_until](#) = None

### 10.114.1 Detailed Description

<list\_resources/> element.

Definition at line 910 of file left\_right.py.

### 10.114.2 Member Function Documentation

#### 10.114.2.1 def rpki.left\_right.list\_resources\_elt.startElement(self, stack, name, attrs)

Handle <list\_resources/> element. This requires special handling due to the data types of some of the attributes.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 919 of file left\_right.py.

#### 10.114.2.2 def rpki.left\_right.list\_resources\_elt.toXML(self)

Generate <list\_resources/> element. This requires special handling due to the data types of some of the attributes.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 935 of file left\_right.py.

### 10.114.3 Member Data Documentation

#### 10.114.3.1 rpki.left\_right.list\_resources\_elt.asn

Definition at line 929 of file left\_right.py.

#### 10.114.3.2 tuple rpki.left\_right.list\_resources\_elt.attributes = ("self\_handle", "tag", "child\_handle", "valid\_until", "asn", "ipv4", "ipv6") [static]

XML attributes for this element.



Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 916 of file left\_right.py.

10.114.3.3 string rpki.left\_right.list\_resources\_elt.element\_name =  
"list\_resources" [static]

Definition at line 915 of file left\_right.py.

10.114.3.4 rpki.left\_right.list\_resources\_elt.ipv4

Definition at line 931 of file left\_right.py.

10.114.3.5 rpki.left\_right.list\_resources\_elt.ipv6

Definition at line 933 of file left\_right.py.

10.114.3.6 rpki.left\_right.list\_resources\_elt.valid\_until = None [static]

Definition at line 917 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.115 rpki.left\_right.list\_roa\_requests\_elt Class Reference

Inherits [rpki.xml\\_utils::base\\_elt](#) and [rpki::left\\_right::left\\_right\\_namespace](#)

### Public Member Functions

- def [startElement](#)

### Public Attributes

- [ipv4](#)

- [ipv6](#)

#### Static Public Attributes

- tuple [attributes](#)= ("self\_handle", "tag", "asn", [ipv4](#), [ipv6](#))  
XML attributes for this element.
- string [element\\_name](#) "list\_roa\_requests"

#### 10.115.1 Detailed Description

<list\_roa\_requests/> element.

Definition at line 945 of file left\_right.py.

#### 10.115.2 Member Function Documentation

10.115.2.1 def rpki.left\_right.list\_roa\_requests\_elt.startElement(self, stack, name, attrs)

Handle <list\_roa\_requests/> element. This requires special handling due to the data types of some of the attributes.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 953 of file left\_right.py.

#### 10.115.3 Member Data Documentation

10.115.3.1 tuple rpki.left\_right.list\_roa\_requests\_elt.attributes = ("self\_handle", "tag", "asn", "ipv4", "ipv6") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 951 of file left\_right.py.

10.115.3.2 string rpki.left\_right.list\_roa\_requests\_elt.element\_name =  
"list\_roa\_requests" [static]

Definition at line 950 of file left\_right.py.

10.115.3.3 rpki.left\_right.list\_roa\_requests\_elt.ipv4

Definition at line 961 of file left\_right.py.

10.115.3.4 rpki.left\_right.list\_roa\_requests\_elt.ipv6

Definition at line 963 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.116 rpki.left\_right.msg Class Reference

Inherits [rpki::xml\\_utils::msg](#) and [rpki::left\\_right::left\\_right\\_namespace](#)

Inherited by [irbe\\_cli.left\\_right\\_msg](#)

### Public Member Functions

- def [serve\\_top\\_level](#)

### Static Public Attributes

- tuple [pdus](#)  
Dispatch table of PDUs for this protocol.
- int [version](#)= 1  
Protocol version.

### 10.116.1 Detailed Description

Left-right PDU.

Definition at line 1023 of file left\_right.py.

### 10.116.2 Member Function Documentation

#### 10.116.2.1 def rpki.left\_right.msg.serve\_top\_level(elf, gctx, cb)

Serve one msg PDU.

Definition at line 1039 of file left\_right.py.

### 10.116.3 Member Data Documentation

#### 10.116.3.1 rpki::left\_right.msg::pdus [static]

Initial value:

```
dict((x.element_name, x)
      for x in (self_elt, child_elt, parent_elt, bsc_elt, repository_elt,
                list_resources_elt, list_roa_requests_elt, list_published
                _objects_elt,
                report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented in [irbe\\_cli.left\\_right\\_msg](#)

Definition at line 1034 of file left\_right.py.

#### 10.116.3.2 rpki::left\_right.msg::version = 1 [static]

Protocol version.

Reimplemented from [rpki.xml\\_utils.msg](#)

Definition at line 1030 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.117 rpki.left\_right.parent\_elt Class Reference

Inherits [rpki::left\\_right::data\\_elt](#)

Inherited by [irbe\\_cli.parent\\_elt](#)

### Public Member Functions

- def [cas](#)
- def [query\\_up\\_down](#)
- def [repository](#)
- def [serve\\_post\\_save\\_hook](#)
- def [serve\\_rekey](#)
- def [serve\\_revoke](#)
- def [serve\\_revoke\\_forgotten](#)

### Static Public Attributes

- tuple [attributes](#)  
XML attributes for this element.
- tuple [booleans](#) = ("rekey", "reissue", "revoke", "revoke\_forgotten")  
Boolean attributes (value "yes" or "no") for this element.
- [bpki\\_cms\\_cert](#) = None
- [bpki\\_cms\\_glue](#) = None
- [bpki\\_https\\_cert](#) = None
- [bpki\\_https\\_glue](#) = None
- string [element\\_name](#) = "parent"
- tuple [elements](#) = ("bpki\_cms\_cert", [bpki\\_cms\\_glue](#), "bpki\_https\_cert", [bpki\\_https\\_glue](#))  
XML elements contained by this element.
- tuple [handles](#) = (("self", self\_elt), ("bsc", bsc\_elt), ("repository", repository\_elt))
- tuple [sql\\_template](#)

### 10.117.1 Detailed Description

<parent/> element.

Definition at line 653 of file left\_right.py.

## 10.117.2 Member Function Documentation

### 10.117.2.1 def rpki.left\_right.parent\_elt.cas (self)

Fetch all CA objects that link to this parent object.

Definition at line 680 of file left\_right.py.

### 10.117.2.2 def rpki.left\_right.parent\_elt.query\_up\_down (self, q\_pdu, cb, eb)

Client code for sending one up-down query PDU to this parent.

Definition at line 756 of file left\_right.py.

### 10.117.2.3 def rpki.left\_right.parent\_elt.repository (self)

Fetch repository object to which this parent object links.

Definition at line 676 of file left\_right.py.

### 10.117.2.4 def rpki.left\_right.parent\_elt.serve\_post\_save\_hooks (self, q\_pdu, r\_pdu, cb, eb)

Extra server actions for parent\_elt.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 684 of file left\_right.py.

### 10.117.2.5 def rpki.left\_right.parent\_elt.serve\_rekey (self, cb, eb)

Handle a left-right rekey action for this parent.

Definition at line 700 of file left\_right.py.

### 10.117.2.6 def rpki.left\_right.parent\_elt.serve\_revoke(self, cb, eb)

Handle a left-right revoke action for this parent.

Definition at line 708 of file left\_right.py.

### 10.117.2.7 def rpki.left\_right.parent\_elt.serve\_revoke\_forgotten(self, cb, eb)

Handle a left-right revoke\_forgotten action for this parent.

This is a bit fiddly: we have to compare the result of an up-down list query with what we have locally and identify the SKIs of any certificates that have gone missing. This should never happen in ordinary operation, but can arise if we have somehow lost a private key, in which case there is nothing more we can do with the issued cert, so we have to clear it. As this really is not supposed to happen, we don't clear it automatically, instead we require an explicit trigger.

Definition at line 716 of file left\_right.py.

## 10.117.3 Member Data Documentation

### 10.117.3.1 tuple rpki.left\_right.parent\_elt.attributes [static]

Initial value:

```
("action", "tag", "self_handle", "parent_handle", "bsc_handle", "repository_handle",
    "peer_contact_uri", "sia_base", "sender_name", "recipient_name")
```

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 659 of file left\_right.py.

### 10.117.3.2 tuple rpki.left\_right.parent\_elt.booleans = ("rekey", "reissue", "revoke", "revoke\_forgotten") [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 662 of file left\_right.py.

10.117.3.3 rpki.left\_right.parent\_elt.bpki\_cms\_cert = None [static]

Definition at line 671 of file left\_right.py.

10.117.3.4 rpki.left\_right.parent\_elt.bpki\_cms\_glue = None [static]

Definition at line 672 of file left\_right.py.

10.117.3.5 rpki.left\_right.parent\_elt.bpki\_https\_cert = None [static]

Definition at line 673 of file left\_right.py.

10.117.3.6 rpki.left\_right.parent\_elt.bpki\_https\_glue = None [static]

Definition at line 674 of file left\_right.py.

10.117.3.7 string rpki.left\_right.parent\_elt.element\_name = "parent"  
[static]

Definition at line 658 of file left\_right.py.

10.117.3.8 tuple rpki.left\_right.parent\_elt.elements = ("bpki\_cms\_cert",  
"bpki\_cms\_glue", "bpki\_https\_cert", "bpki\_https\_glue")  
[static]

XML elements contained by this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 661 of file left\_right.py.



10.117.3.9 tuple `rpki.left_right.parent_elt.handles` = (("self", `self_elt`), ("bsc", `bsc_elt`), ("repository", `repository_elt`)) [static]

Reimplemented from [rpki.left\\_right.data\\_elt](#)

Definition at line 669 of file `left_right.py`.

10.117.3.10 tuple `rpki.left_right.parent_elt.sql_template` [static]

Initial value:

```
rpki.sql.template("parent", "parent_id", "parent_handle",
                  "self_id", "bsc_id", "repository_id",
                  ("bpki_cms_cert", rpki.x509.X509), ("bpki_cms_
glue", rpki.x509.X509),
                  ("bpki_https_cert", rpki.x509.X509), ("bpki_ht
tps_glue", rpki.x509.X509),
                  "peer_contact_uri", "sia_base", "sender_name",
                  "recipient_name")
```

Definition at line 664 of file `left_right.py`.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.118 rpki.left\_right.report\_error\_elt Class Reference

Inherits [rpki::xml\\_utils::text\\_elt](#) and [rpki::left\\_right::left\\_right\\_namespace](#)

Inherited by [irbe\\_cli.report\\_error\\_elt](#)

### Public Member Functions

- [def from\\_exception](#)

### Public Attributes

- [error\\_code](#)
- [self\\_handle](#)
- [tag](#)

## Static Public Attributes

- tuple `attributes`= ("tag", "self\_handle", "error\_code")  
XML attributes for this element.
- string `element_name` "report\_error"
- `error_text`= None
- string `text_attribute`= "error\_text"  
Name of the class attribute that holds the text value.

## 10.118.1 Detailed Description

<report\_error/> element.

Definition at line 1000 of file left\_right.py.

## 10.118.2 Member Function Documentation

- 10.118.2.1 def rpki.left\_right.report\_error\_elt.from\_exception (cls, e, self\_handle= None, tag= None)

Generate a <report\_error/> element from an exception.

Definition at line 1012 of file left\_right.py.

## 10.118.3 Member Data Documentation

- 10.118.3.1 tuple rpki.left\_right.report\_error\_elt.attributes = ("tag", "self\_handle", "error\_code") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 1006 of file left\_right.py.

- 10.118.3.2 string rpki.left\_right.report\_error\_elt.element\_name = "report\_error" [static]

Definition at line 1005 of file left\_right.py.

#### 10.118.3.3 rpki.left\_right.report\_error\_elt.error\_code

Definition at line 1019 of file left\_right.py.

#### 10.118.3.4 rpki.left\_right.report\_error\_elt.error\_text = None [static]

Definition at line 1009 of file left\_right.py.

#### 10.118.3.5 rpki.left\_right.report\_error\_elt.self\_handle

Definition at line 1017 of file left\_right.py.

#### 10.118.3.6 rpki.left\_right.report\_error\_elt.tag

Definition at line 1018 of file left\_right.py.

#### 10.118.3.7 string rpki.left\_right.report\_error\_elt.text\_attribute = "error\_text" [static]

Name of the class attribute that holds the text value.

Reimplemented from [rpki.xml\\_utils.text\\_elt](#)

Definition at line 1007 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

### 10.119 rpki.left\_right.repository\_elt Class Reference

Inherits [rpki::left\\_right::data\\_elt](#)

Inherited by [irbe\\_cli.repository\\_elt](#)

## Public Member Functions

- def [call\\_pubd](#)
- def [default\\_pubd\\_handler](#)
- def [parents](#)

## Static Public Attributes

- tuple [attributes](#)= ("action", "tag", [self\\_handle](#), "repository\_handle", "bsc\_handle", "peer\_contact\_uri")  
XML attributes for this element.
- [bpki\\_cert](#)= None
- [bpki\\_glue](#)= None
- string [element\\_name](#)= "repository"
- tuple [elements](#)= ("bpki\_cert", [bpki\\_glue](#))  
XML elements contained by this element.
- tuple [handles](#)= (("self", self\_elt), ("bsc", bsc\_elt))
- tuple [sql\\_template](#)

## 10.119.1 Detailed Description

<repository/> element.

Definition at line 573 of file `left_right.py`.

## 10.119.2 Member Function Documentation

## 10.119.2.1 def rpki.left\_right.repository\_elt.call\_pubd (self, callback, errback, q\_msg handlers= {} )

Send a message to publication daemon and return the response.

As a convenience, attempting to send an empty message returns immediate success without sending anything.

Handlers is a dict of handler functions to process the response PDUs. If the tag value in the response PDU appears in the dict, the associated handler is called to process the PDU. If no tag matches, `default_pubd_handler()` is called. A handler value of `False` suppresses calling of the default handler.

Definition at line 601 of file `left_right.py`.

### 10.119.2.2 def rpki.left\_right.repository\_elt.default\_pubd\_handler (pdu)

Default handler for publication response PDUs.

Definition at line 595 of file left\_right.py.

### 10.119.2.3 def rpki.left\_right.repository\_elt.parents (self)

Fetch all parent objects that link to this repository object.

Definition at line 590 of file left\_right.py.

## 10.119.3 Member Data Documentation

### 10.119.3.1 tuple rpki.left\_right.repository\_elt.attributes = ("action", "tag", "self\_handle", "repository\_handle", "bsc\_handle", "peer\_contact\_uri") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 579 of file left\_right.py.

### 10.119.3.2 rpki.left\_right.repository\_elt.bpkgi\_cert = None [static]

Definition at line 587 of file left\_right.py.

### 10.119.3.3 rpki.left\_right.repository\_elt.bpkgi\_glue = None [static]

Definition at line 588 of file left\_right.py.

### 10.119.3.4 string rpki.left\_right.repository\_elt.element\_name = "repository" [static]

Definition at line 578 of file left\_right.py.

```
10.119.3.5 tuple rpki.left_right.repository_elt.elements = ("bpki_cert",
    "bpki_glue") [static]
```

XML elements contained by this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 580 of file left\_right.py.

```
10.119.3.6 tuple rpki.left_right.repository_elt.handles = (("self", self_elt),
    ("bsc", bsc_elt)) [static]
```

Reimplemented from [rpki.left\\_right.data\\_elt](#)

Definition at line 585 of file left\_right.py.

```
10.119.3.7 tuple rpki.left_right.repository_elt.sql_template [static]
```

Initial value:

```
rpki.sql.template("repository", "repository_id", "repository_handle",
    "self_id", "bsc_id", "peer_contact_uri",
    ("bpki_cert", rpki.x509.X509), ("bpki_glue", r
    pki.x509.X509))
```

Definition at line 582 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.120 rpki.left\_right.sax\_handler Class Reference

Inherits [rpki.xml\\_utils::sax\\_handler](#)

Inherited by [irbe\\_cli.left\\_right\\_sax\\_handler](#)

Static Public Attributes

- string [name](#)= "msg"

- pdu= msg
- stringversion= "1"

### 10.120.1 Detailed Description

SAX handler for Left-Right protocol.

Definition at line 1067 of file left\_right.py.

### 10.120.2 Member Data Documentation

#### 10.120.2.1 string rpki.left\_right.sax\_handler.name = "msg" [static]

Definition at line 1073 of file left\_right.py.

#### 10.120.2.2 rpki.left\_right.sax\_handler.pdu = msg [static]

Reimplemented in [irbe\\_cli.left\\_right\\_sax\\_handler](#)

Definition at line 1072 of file left\_right.py.

#### 10.120.2.3 string rpki.left\_right.sax\_handler.version = "1" [static]

Definition at line 1074 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.121 rpki.left\_right.self\_elt Class Reference

Inherits [rpki::left\\_right::data\\_elt](#)

Inherited by [irbe\\_cli.self\\_elt](#)

### Public Member Functions

- def [bscs](#)

- def [children](#)
- def [client\\_poll](#)
- def [cron](#)
- def [parents](#)
- def [regenerate\\_crls\\_and\\_manifests](#)
- def [repositories](#)
- def [roas](#)
- def [serve\\_fetch\\_all](#)
- def [serve\\_fetch\\_handle](#)
- def [serve\\_fetch\\_one\\_maybe](#)
- def [serve\\_post\\_save\\_hook](#)
- def [serve\\_publish\\_world\\_now](#)
- def [serve\\_rekey](#)
- def [serve\\_revoke](#)
- def [serve\\_revoke\\_forgotten](#)
- def [serve\\_run\\_now](#)
- def [update\\_children](#)
- def [update\\_roas](#)

#### Static Public Attributes

- tuple [attributes](#) = ("action", "tag", "[self\\_handle](#)", "[crl\\_interval](#)", "[regen\\_margin](#)")  
XML attributes for this element.
- tuple [booleans](#) = ("rekey", "reissue", "revoke", "run\_now", "publish\_world\_now", "revoke\_forgotten")  
Boolean attributes (value "yes" or "no") for this element.
- [bpki\\_cert](#) = None
- [bpki\\_glue](#) = None
- [crl\\_interval](#) = None
- string [element\\_name](#) = "self"
- tuple [elements](#) = ("[bpki\\_cert](#)", "[bpki\\_glue](#)")  
XML elements contained by this element.
- tuple [handles](#) = ()
- [regen\\_margin](#) = None
- tuple [sql\\_template](#)
- [use\\_hsm](#) = False



### 10.121.1 Detailed Description

<self/> element.

Definition at line 124 of file left\_right.py.

### 10.121.2 Member Function Documentation

#### 10.121.2.1 def rpki.left\_right.self\_elt.bscs(self)

Fetch all BSC objects that link to this self object.

Definition at line 145 of file left\_right.py.

#### 10.121.2.2 def rpki.left\_right.self\_elt.children(self)

Fetch all child objects that link to this self object.

Definition at line 157 of file left\_right.py.

#### 10.121.2.3 def rpki.left\_right.self\_elt.client\_poll(self, callback)

Run the regular client poll cycle with each of this self's parents in turn.

Definition at line 302 of file left\_right.py.

#### 10.121.2.4 def rpki.left\_right.self\_elt.cron(self, cb)

Periodic tasks.

Definition at line 274 of file left\_right.py.

### 10.121.2.5 def rpki.left\_right.self\_elt.parents (self)

Fetch all parent objects that link to this self object.

Definition at line 153 of file left\_right.py.

### 10.121.2.6 def rpki.left\_right.self\_elt.regenerate\_crls\_and\_manifests (self, cb)

Generate new CRLs and manifests as necessary for all of this self's CAs. Extracting nextUpdate from a manifest is hard at the moment due to implementation silliness, so for now we generate a new manifest whenever we generate a new CRL

This method also cleans up tombstones left behind by revoked ca\_detail objects, since we're walking through the relevant portions of the database anyway.

Definition at line 428 of file left\_right.py.

### 10.121.2.7 def rpki.left\_right.self\_elt.repositories (self)

Fetch all repository objects that link to this self object.

Definition at line 149 of file left\_right.py.

### 10.121.2.8 def rpki.left\_right.self\_elt.roas (self)

Fetch all ROA objects that link to this self object.

Definition at line 161 of file left\_right.py.

### 10.121.2.9 def rpki.left\_right.self\_elt.serve\_fetch\_all (self)

Find the self objects upon which a list action should operate. This is different from the list action for all other objects, where list only works within a given self\_id context.

Reimplemented from [mpki.left\\_right.data\\_elt](#)

Definition at line 266 of file left\_right.py.

```
10.121.2.10 def rpkgi.left_right.self_elt.serve_fetch_handled(s, gctx, self_id,
                  self_handle)
```

Find a self object based on its self\_handle.

Reimplemented from [mpki.left\\_right.data\\_elt](#)

Definition at line 260 of file left\_right.py.

```
10.121.2.11 def rpkgi.left_right.self_elt.serve_fetch_one_maybe(self)
```

Find the self object upon which a get, set, or destroy action should operate, or which would conflict with a create method.

Reimplemented from [mpki.left\\_right.data\\_elt](#)

Definition at line 252 of file left\_right.py.

```
10.121.2.12 def rpkgi.left_right.self_elt.serve_post_save_hooks(self, q_pdu,
                  r_pdu, cb, eb)
```

Extra server actions for self\_elt.

Reimplemented from [mpki.xml\\_utils.data\\_elt](#)

Definition at line 165 of file left\_right.py.

```
10.121.2.13 def rpkgi.left_right.self_elt.serve_publish_world_now(self, cb, eb)
```

Handle a left-right publish\_world\_now action for this self.

The publication stuff needs refactoring, right now publication is interleaved with local operations in a way that forces far too many bounces through the task system for any complex update. The whole thing ought to be rewritten to queue up outgoing publication

PDUs and only send them when we're all done or when we need to force publication at a particular point in a multi-phase operation.

Once that reorganization has been done, this method should be rewritten to reuse the low-level publish() methods that each object will have...but we're not there yet. So, for now, we just do this via brute force. Think of it as a trial version to see whether we've identified everything that needs to be republished for this operation.

Definition at line 213 of file left\_right.py.

10.121.2.14 def rpki.left\_right.self\_elt.serve\_rekey(self, cb, eb)

Handle a left-right rekey action for this self.

Definition at line 186 of file left\_right.py.

10.121.2.15 def rpki.left\_right.self\_elt.serve\_revokes(self, cb, eb)

Handle a left-right revoke action for this self.

Definition at line 195 of file left\_right.py.

10.121.2.16 def rpki.left\_right.self\_elt.serve\_revoke\_forgotten(self, cb, eb)

Handle a left-right revoke\_forgotten action for this self.

Definition at line 204 of file left\_right.py.

10.121.2.17 def rpki.left\_right.self\_elt.serve\_run\_now(self, cb, eb)

Handle a left-right run\_now action for this self.

Definition at line 245 of file left\_right.py.

10.121.2.18 `def rpki.left_right.self_elt.update_children(self, cb)`

Check for updated IRDB data for all of this self's children and issue new certs as necessary. Must handle changes both in resources and in expiration date.

Definition at line 361 of file `left_right.py`.

10.121.2.19 `def rpki.left_right.self_elt.update_roas(self, cb)`

Generate or update ROAs for this self.

Definition at line 470 of file `left_right.py`.

### 10.121.3 Member Data Documentation

10.121.3.1 `tuple rpki.left_right.self_elt.attributes = ("action", "tag", "self_handle", "crl_interval", "regen_margin") [static]`

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 130 of file `left_right.py`.

10.121.3.2 `tuple rpki.left_right.self_elt.booleans = ("rekey", "reissue", "revoke", "run_now", "publish_world_now", "revoke_forgotten") [static]`

Boolean attributes (value "yes" or "no") for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 132 of file `left_right.py`.

10.121.3.3 `rpki.left_right.self_elt.bpkcert = None [static]`

Definition at line 142 of file `left_right.py`.

10.121.3.4 rpki.left\_right.self\_elt.bpki\_glue = None [static]

Definition at line 143 of file left\_right.py.

10.121.3.5 rpki.left\_right.self\_elt.crl\_interval = None [static]

Definition at line 140 of file left\_right.py.

10.121.3.6 string rpki.left\_right.self\_elt.element\_name = "self" [static]

Definition at line 129 of file left\_right.py.

10.121.3.7 tuple rpki.left\_right.self\_elt.elements = ("bpki\_cert", "bpki\_glue")  
[static]

XML elements contained by this element.

Reimplemented from [mpki.xml\\_utils.base\\_elt](#)

Definition at line 131 of file left\_right.py.

10.121.3.8 tuple rpki.left\_right.self\_elt.handles = () [static]

Reimplemented from [mpki.left\\_right.data\\_elt](#)

Definition at line 137 of file left\_right.py.

10.121.3.9 rpki.left\_right.self\_elt.regen\_margin = None [static]

Definition at line 141 of file left\_right.py.

10.121.3.10 tuple rpki.left\_right.self\_elt.sql\_template [static]

Initial value:

```
rpki.sql.template("self", "self_id", "self_handle",
                  "use_hsm", "crl_interval", "regen_margin",
                  ("bpki_cert", rpki.x509.X509), ("bpki_glue", r
                  pki.x509.X509))
```

Definition at line 134 of file left\_right.py.

10.121.3.11 rpki.left\_right.self\_elt.use\_hsm = False[static]

Definition at line 139 of file left\_right.py.

The documentation for this class was generated from the following file:

- [left\\_right.py \(2931\)](#)

## 10.122 rpki.log.logger Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_call\\_\\_](#)
- [def \\_\\_init\\_\\_](#)

### Public Attributes

- [priority](#)

### 10.122.1 Detailed Description

Closure for logging.

Definition at line 71 of file log.py.

### 10.122.2 Member Function Documentation

10.122.2.1 def rpki.log.logger.\_\_call\_\_(self, message)

Definition at line 79 of file log.py.

10.122.2.2 def rpki.log.logger.\_\_init\_\_(self, priority)

Definition at line 76 of file log.py.

### 10.122.3 Member Data Documentation

10.122.3.1 rpki.log.logger.priority

Definition at line 77 of file log.py.

The documentation for this class was generated from the following file:

- [log.py \(2933\)](#)

## 10.123 rpki.manifest.FileAndHash Class Reference

Inherits [Sequence](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)

### Public Attributes

- [le](#)
- [hash](#)

### 10.123.1 Detailed Description

Definition at line 27 of file manifest.py.

### 10.123.2 Member Function Documentation

10.123.2.1 def rpki.manifest.FileAndHash.\_\_init\_\_(self, optional=0, default="")

Definition at line 28 of file manifest.py.



### 10.123.3 Member Data Documentation

#### 10.123.3.1 rpki.manifest.FileAndHash. le

Definition at line 29 of le manifest.py.

#### 10.123.3.2 rpki.manifest.FileAndHash.hash

Definition at line 30 of le manifest.py.

The documentation for this class was generated from the following le:

- [manifest.py \(2424\)](#)

## 10.124 rpki.manifest.FilesAndHashes Class Reference

Inherits [SequenceOf](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)

#### 10.124.1 Detailed Description

Definition at line 34 of le manifest.py.

#### 10.124.2 Member Function Documentation

##### 10.124.2.1 `def rpki.manifest.FilesAndHashes.__init__(self, optional=0, default="")`

Definition at line 35 of le manifest.py.

The documentation for this class was generated from the following le:

- [manifest.py \(2424\)](#)

## 10.125 rpki.manifest.Manifest Class Reference

Inherits [Sequence](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)

### Public Attributes

- [explicitVersion](#)
- [leHashAlg](#)
- [leList](#)
- [manifestNumber](#)
- [nextUpdate](#)
- [thisUpdate](#)
- [version](#)

#### 10.125.1 Detailed Description

Definition at line 38 of `le manifest.py`.

#### 10.125.2 Member Function Documentation

10.125.2.1 `def rpki.manifest.Manifest.__init__(self, optional = 0, default = " ")`

Definition at line 39 of `le manifest.py`.

#### 10.125.3 Member Data Documentation

10.125.3.1 `rpki.manifest.Manifest.explicitVersion`

Definition at line 41 of `le manifest.py`.

10.125.3.2 `rpki.manifest.Manifest.leHashAlg`

Definition at line 45 of `le manifest.py`.

## 10.125.3.3 rpki.manifest.Manifest.leList

Definition at line 46 of le\_manifest.py.

## 10.125.3.4 rpki.manifest.Manifest.manifestNumber

Definition at line 42 of le\_manifest.py.

## 10.125.3.5 rpki.manifest.Manifest.nextUpdate

Definition at line 44 of le\_manifest.py.

## 10.125.3.6 rpki.manifest.Manifest.thisUpdate

Definition at line 43 of le\_manifest.py.

## 10.125.3.7 rpki.manifest.Manifest.version

Definition at line 40 of le\_manifest.py.

The documentation for this class was generated from the following file:

- [manifest.py \(2424\)](#)

## 10.126 rpki.publication.certificate\_elt Class Reference

Inherits [rpki::publication::publication\\_object\\_elt](#)

Inherited by [irbe\\_cli.certificate\\_elt](#)

## Static Public Attributes

- [string element\\_name](#) = "certificate"
- [payload\\_type](#) = [rpki.x509.X509](#)

### 10.126.1 Detailed Description

<certificate/> element.

Definition at line 286 of file publication.py.

### 10.126.2 Member Data Documentation

10.126.2.1 string rpki.publication.certificate\_elt.element\_name = "certificate"  
[static]

Definition at line 291 of file publication.py.

10.126.2.2 rpki.publication.certificate\_elt.payload\_type = rpki.x509.X509  
[static]

Reimplemented from [rpki.publication.publication\\_object\\_elt](#)

Definition at line 292 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.127 rpki.publication.client\_elt Class Reference

Inherits [rpki::publication::control\\_elt](#)

Inherited by [irbe\\_cli.client\\_elt](#)

### Public Member Functions

- def [check\\_allowed\\_uri](#)
- def [endElement](#)
- def [serve\\_fetch\\_all](#)
- def [serve\\_fetch\\_one\\_maybe](#)
- def [serve\\_post\\_save\\_hook](#)

## Static Public Attributes

- tuple `attributes`= ("action", "tag", "client\_handle", `base_uri`)  
XML attributes for this element.
- `base_uri`= None
- `bpki_cert`= None
- `bpki_glue`= None
- `clear_https_ta_cache`= False
- string `element_name` "client"
- tuple `elements`= ("bpki\_cert", `bpki_glue`)  
XML elements contained by this element.
- tuple `sql_template`= `rpki.sql.template`("client", "client\_id", "client\_handle",  
"base\_uri", ("bpki\_cert", `rpki.x509.X509`), ("bpki\_glue", `rpki.x509.X509`))

## 10.127.1 Detailed Description

<client/> element.

Definition at line 113 of `publication.py`.

## 10.127.2 Member Function Documentation

10.127.2.1 `def rpki.publication.client_elt.check_allowed_uri(self, uri)`

Definition at line 160 of `publication.py`.

10.127.2.2 `def rpki.publication.client_elt.endElement(self, stack, name, text)`

Handle subelements of <client/> element. These require special handling because modifying them invalidates the HTTPS trust anchor cache.

Reimplemented from `rpki.xml_utils.data_elt`

Definition at line 130 of `publication.py`.

## 10.127.2.3 def rpki.publication.client\_elt.serve\_fetch\_all(self)

Find client objects on which a list method should operate.

Definition at line 156 of file publication.py.

## 10.127.2.4 def rpki.publication.client\_elt.serve\_fetch\_one\_maybe(self)

Find the client object on which a get, set, or destroy method should operate, or which would conflict with a create method.

Definition at line 149 of file publication.py.

## 10.127.2.5 def rpki.publication.client\_elt.serve\_post\_save\_hooks(self, q\_pdu, r\_pdu, cb, eb)

Extra server actions for client\_elt.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 140 of file publication.py.

## 10.127.3 Member Data Documentation

## 10.127.3.1 tuple rpki.publication.client\_elt.attributes = ("action", "tag", "client\_handle", "base\_uri") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 119 of file publication.py.

## 10.127.3.2 rpki.publication.client\_elt.base\_uri = None [static]

Definition at line 124 of file publication.py.

10.127.3.3 rpki.publication.client\_elt.bpki\_cert = None [static]

Definition at line 125 of file publication.py.

10.127.3.4 rpki.publication.client\_elt.bpki\_glue = None [static]

Definition at line 126 of file publication.py.

10.127.3.5 rpki.publication.client\_elt.clear\_https\_ta\_cache = False [static]

Definition at line 128 of file publication.py.

10.127.3.6 string rpki.publication.client\_elt.element\_name = "client"  
[static]

Definition at line 118 of file publication.py.

10.127.3.7 tuple rpki.publication.client\_elt.elements = ("bpki\_cert",  
"bpki\_glue") [static]

XML elements contained by this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 120 of file publication.py.

10.127.3.8 tuple rpki.publication.client\_elt.sql\_template =  
rpki.sql.template("client", "client\_id", "client\_handle", "base\_uri",  
("bpki\_cert", rpki.x509.X509), ("bpki\_glue", rpki.x509.X509))  
[static]

Definition at line 122 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.128 rpki.publication.cms\_msg Class Reference

Inherits [rpki::x509::XML\\_CMS\\_object](#)

Inherited by [irbe\\_cli.publication\\_cms\\_msg](#)

### Static Public Attributes

- string [encoding](#) = "us-ascii"
- [saxify](#) = sax\_handler.saxify
- [schema](#) = [rpki.relaxng.publication](#)

### 10.128.1 Detailed Description

Class to hold a CMS-signed publication PDU.

Definition at line 414 of [le publication.py](#).

### 10.128.2 Member Data Documentation

#### 10.128.2.1 string rpki.publication.cms\_msg.encoding = "us-ascii" [static]

Definition at line 419 of [le publication.py](#).

#### 10.128.2.2 rpki.publication.cms\_msg.saxify = sax\_handler.saxify[static]

Reimplemented in [irbe\\_cli.publication\\_cms\\_msg](#)

Definition at line 421 of [le publication.py](#).

#### 10.128.2.3 rpki.publication.cms\_msg.schema = rpki.relaxng.publication [static]

Definition at line 420 of [le publication.py](#).

The documentation for this class was generated from the following [le](#):



- [publication.py \(2935\)](#)

## 10.129 rpki.publication.con g\_elt Class Reference

Inherits [rpki::publication::control\\_elt](#)

Inherited by [rbe\\_cli.con g\\_elt](#)

### Public Member Functions

- def [fetch](#)
- def [serve\\_fetch\\_one\\_maybe](#)
- def [serve\\_set](#)
- def [startElement](#)

### Public Attributes

- [con g\\_id](#)

### Static Public Attributes

- tuple [attributes](#)= ("action", "tag")  
XML attributes for this element.
- string [element\\_name](#) "con g"
- tuple [elements](#)= ("bpki\_crl",)  
XML elements contained by this element.
- tuple [sql\\_template](#) = [rpki.sql.template](#)("con g", " [con g\\_id](#)", ("bpki\_crl",  
rpki.x509.CRL))
- int [wired\\_in\\_con g\\_id](#)= 1

#### 10.129.1 Detailed Description

<config/> element. This is a little weird because there should never be more than one row in the SQL config table, but we have to put the BPKI CRL somewhere and SQL is the least bad place available.

So we reuse a lot of the SQL machinery, but we nail config\_id at 1, we don't expose it in the XML protocol, and we only support the get and set actions.

Definition at line 61 of file [publication.py](#).

## 10.129.2 Member Function Documentation

### 10.129.2.1 def rpki.publication.config\_elt.fetch(cls, gctx)

Fetch the config object from SQL. This requires special handling because of the weird way we treat config\_id.

Definition at line 89 of file publication.py.

### 10.129.2.2 def rpki.publication.config\_elt.serve\_fetch\_one\_maybe(self)

Find the config object on which a get or set method should operate.

Definition at line 106 of file publication.py.

### 10.129.2.3 def rpki.publication.config\_elt.serve\_set(self, r\_msg cb, eb)

Handle a set action. This requires special handling because config doesn't support the create method.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 96 of file publication.py.

### 10.129.2.4 def rpki.publication.config\_elt.startElement(self, stack, name, attrs)

StartElement() handler for config object. This requires special handling because of the weird way we treat config\_id.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 80 of file publication.py.

### 10.129.3 Member Data Documentation

10.129.3.1 tuple rpki.publication.con g\_elt.attributes = ("action", "tag")  
[static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 72 of file publication.py.

10.129.3.2 rpki.publication.con g\_elt.con g\_id

Definition at line 86 of file publication.py.

10.129.3.3 string rpki.publication.con g\_elt.element\_name = "con g"  
[static]

Definition at line 73 of file publication.py.

10.129.3.4 tuple rpki.publication.con g\_elt.elements = ("bpki\_crl",)  
[static]

XML elements contained by this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 74 of file publication.py.

10.129.3.5 tuple rpki.publication.con g\_elt.sql\_template =  
rpki.sql.template("con g", "con g\_id", ("bpki\_crl",  
rpki.x509.CRL)) [static]

Definition at line 76 of file publication.py.

10.129.3.6 int rpki.publication.control\_elt.wired\_in\_control\_id = 1 [static]

Definition at line 78 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.130 rpki.publication.control\_elt Class Reference

Inherits [rpki::xml\\_utils::data\\_elt](#) [rpki::sql::sql\\_persistent](#) and [rpki::publication::publication\\_namespace](#)

Inherited by [rpki.publication.client\\_elt](#) and [rpki.publication.control\\_elt](#)

### Public Member Functions

- def [serve\\_dispatch](#)

#### 10.130.1 Detailed Description

Virtual class for control channel objects.

Definition at line 47 of file publication.py.

#### 10.130.2 Member Function Documentation

10.130.2.1 def rpki.publication.control\_elt.serve\_dispatch(self, r\_msg\_cb, eb)

Action dispatch handler. This needs special handling because we need to make sure that this PDU arrived via the control channel.

Reimplemented from [rpki.xml\\_utils.data\\_elt](#)

Definition at line 52 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.131 rpki.publication.crl\_elt Class Reference

Inherits [rpki::publication::publication\\_object\\_elt](#)

Inherited by [irbe\\_cli.crl\\_elt](#)

### Static Public Attributes

- string [element\\_name](#) = "crl"
- [payload\\_type](#) = [rpki.x509.CRL](#)

### 10.131.1 Detailed Description

<crl/> element.

Definition at line 294 of file `publication.py`.

### 10.131.2 Member Data Documentation

10.131.2.1 string `rpki.publication.crl_elt.element_name = "crl"` [static]

Definition at line 299 of file `publication.py`.

10.131.2.2 `rpki.publication.crl_elt.payload_type = rpki.x509.CRL` [static]

Reimplemented from [rpki.publication.publication\\_object\\_elt](#)

Definition at line 300 of file `publication.py`.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.132 rpki.publication.manifest\_elt Class Reference

Inherits [rpki::publication::publication\\_object\\_elt](#)

Inherited by [irbe\\_cli.manifest\\_elt](#)

### Static Public Attributes

- `string` `element_name` = "manifest"
- `payload_type` = `rpki.x509.SignedManifest`

#### 10.132.1 Detailed Description

<manifest/> element.

Definition at line 302 of file `publication.py`.

#### 10.132.2 Member Data Documentation

10.132.2.1 `string` `rpki.publication.manifest_elt.element_name` = "manifest"  
[static]

Definition at line 307 of file `publication.py`.

10.132.2.2 `rpki.publication.manifest_elt.payload_type` =  
`rpki.x509.SignedManifest` [static]

Reimplemented from `rpki.publication.publication_object_elt`

Definition at line 308 of file `publication.py`.

The documentation for this class was generated from the following file:

- `publication.py` (2935)

### 10.133 rpki.publication.msg Class Reference

Inherits `rpki.xml_utils::msg` and `rpki::publication::publication_namespace`

Inherited by `irbe_cli.publication_msg`

### Public Member Functions

- `def` `serve_top_level`

## Static Public Attributes

- tuple [pdus](#)  
Dispatch table of PDUs for this protocol.
- int [version](#) = 1  
Protocol version.

## 10.133.1 Detailed Description

Publication PDU.

Definition at line 361 of file `publication.py`.

## 10.133.2 Member Function Documentation

10.133.2.1 `def rpki.publication.msg.serve_top_level(self, gctx, client, cb)`

Serve one msg PDU.

Definition at line 375 of file `publication.py`.

## 10.133.3 Member Data Documentation

10.133.3.1 `rpki::publication.msg::pdus` [static]

Initial value:

```
dict((x.element_name, x)
      for x in (config_elt, client_elt, certificate_elt, crl_elt, manifest_elt, roa_elt, report_error_elt))
```

Dispatch table of PDUs for this protocol.

Reimplemented in [irbe\\_cli.publication\\_msg](#)

Definition at line 372 of file `publication.py`.

10.133.3.2 `rpki::publication.msg::version` = 1 [static]

Protocol version.

Reimplemented from [rpki.xml\\_utils.msg](#)

Definition at line 368 of file `publication.py`.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.134 rpki.publication.publication\_namespace Class Reference

Inherits [object](#)

Inherited by [rpki.publication.control\\_elt](#), [rpki.publication.msg](#), [rpki.publication.publication\\_object\\_elt](#) and [rpki.publication.report\\_error\\_elt](#)

Static Public Attributes

- dictionary `nsmap` = { None : [xmlns](#) }
- string `xmlns` = "http://www.hactrn.net/uris/rpki/publication-spec/"

### 10.134.1 Detailed Description

XML namespace parameters for publication protocol.

Definition at line 39 of file `publication.py`.

### 10.134.2 Member Data Documentation

10.134.2.1 dictionary `rpki.publication.publication_namespace.nsmap` = { None : `xmlns` } [static]

Definition at line 45 of file `publication.py`.

10.134.2.2 string `rpki.publication.publication_namespace.xmlns` = "http://www.hactrn.net/uris/rpki/publication-spec/" [static]

Definition at line 44 of file `publication.py`.

The documentation for this class was generated from the following file:



- [publication.py \(2935\)](#)

## 10.135 rpki.publication.publication\_object\_elt Class Reference

Inherits [rpki.xml\\_utils::base\\_elt](#) and [rpki::publication::publication\\_namespace](#)

Inherited by [rpki.publication.certificate\\_elt](#) [rpki.publication.crl\\_elt](#)  
[rpki.publication.manifest\\_elt](#) and [rpki.publication.roa\\_elt](#)

### Public Member Functions

- def [endElement](#)
- def [make\\_publish](#)
- def [make\\_withdraw](#)
- def [raise\\_if\\_error](#)
- def [serve\\_dispatch](#)
- def [serve\\_publish](#)
- def [serve\\_withdraw](#)
- def [toXML](#)
- def [uri\\_to\\_lename](#)

### Static Public Attributes

- tuple [attributes](#)= ("action", "tag", "client\_handle", "uri")  
XML attributes for this element.
- [payload](#)= None
- [payload\\_type](#)= None

#### 10.135.1 Detailed Description

Virtual class for publishable objects. These have very similar syntax, differences lie in underlying datatype and methods. XML methods are a little different from the pattern used for objects that support the create/set/get/list/destroy actions, but publishable objects don't go in SQL either so these classes would be different in any case.

Definition at line 164 of file [publication.py](#).

## 10.135.2 Member Function Documentation

### 10.135.2.1 `def rpki.publication.publication_object_elt.endElement(self, stack, name, text)`

Handle a publishable element element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 178 of file `publication.py`.

### 10.135.2.2 `def rpki.publication.publication_object_elt.make_publish(cls, uri, obj, tag=None)`

Construct a publication PDU.

Definition at line 265 of file `publication.py`.

### 10.135.2.3 `def rpki.publication.publication_object_elt.make_withdraw(cls, uri, obj, tag=None)`

Construct a withdrawal PDU.

Definition at line 273 of file `publication.py`.

### 10.135.2.4 `def rpki.publication.publication_object_elt.raise_if_error(self)`

No-op, since this is not a `<report_error/>` PDU.

Definition at line 280 of file `publication.py`.

### 10.135.2.5 `def rpki.publication.publication_object_elt.serve_dispatch(self, r_msg_cb, eb)`

Action dispatch handler.

Definition at line 196 of file `publication.py`.

#### 10.135.2.6 def rpki.publication.publication\_object\_elt.serve\_publish(self)

Publish an object.

Definition at line 221 of file publication.py.

#### 10.135.2.7 def rpki.publication.publication\_object\_elt.serve\_withdraw(self)

Withdraw an object.

Definition at line 236 of file publication.py.

#### 10.135.2.8 def rpki.publication.publication\_object\_elt.toXML(self)

Generate XML element for publishable object.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 187 of file publication.py.

#### 10.135.2.9 def rpki.publication.publication\_object\_elt.uri\_to\_filename(self)

Convert a URI to a local filename.

Definition at line 250 of file publication.py.

### 10.135.3 Member Data Documentation

#### 10.135.3.1 tuple rpki.publication.publication\_object\_elt.attributes = ("action", "tag", "client\_handle", "uri") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 174 of file publication.py.

10.135.3.2 rpki.publication.publication\_object\_elt.payload = None [static]

Definition at line 176 of file publication.py.

10.135.3.3 rpki.publication.publication\_object\_elt.payload\_type = None [static]

Reimplemented in [rpki.publication.certificate\\_elt](#), [rpki.publication.crl\\_elt](#), [rpki.publication.manifest\\_elt](#) and [rpki.publication.roa\\_elt](#)

Definition at line 175 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.136 rpki.publication.report\_error\_elt Class Reference

Inherits [rpki.xml\\_utils::text\\_elt](#) and [rpki::publication::publication\\_namespace](#)

Inherited by [irbe\\_cli.report\\_error\\_elt](#)

### Public Member Functions

- [def \\_\\_str\\_\\_](#)
- [def from\\_exception](#)
- [def raise\\_if\\_error](#)

### Public Attributes

- [error\\_code](#)
- [tag](#)

### Static Public Attributes

- tuple [attributes](#) = ("tag", "[error\\_code](#)")  
XML attributes for this element.
- string [element\\_name](#) = "report\_error"
- [error\\_text](#) = None

- string `text_attribute` = "error\_text"  
Name of the class attribute that holds the text value.

### 10.136.1 Detailed Description

<report\_error/> element.

Definition at line 320 of file publication.py.

### 10.136.2 Member Function Documentation

#### 10.136.2.1 def rpki.publication.report\_error\_elt.\_\_str\_\_ (self)

Convert a base\_elt object to string format.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 342 of file publication.py.

#### 10.136.2.2 def rpki.publication.report\_error\_elt.from\_exception (cls, e, tag = None)

Generate a <report\_error/> element from an exception.

Definition at line 332 of file publication.py.

#### 10.136.2.3 def rpki.publication.report\_error\_elt.raise\_if\_error (self)

Raise exception associated with this <report\_error/> PDU.

Definition at line 351 of file publication.py.

### 10.136.3 Member Data Documentation

#### 10.136.3.1 tuple rpki.publication.report\_error\_elt.attributes = ("tag", "error\_code") [static]

XML attributes for this element.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 326 of file publication.py.

```
10.136.3.2 string rpki.publication.report_error_elt.element_name =  
            "report_error" [static]
```

Definition at line 325 of file publication.py.

```
10.136.3.3 rpki.publication.report_error_elt.error_code
```

Definition at line 338 of file publication.py.

```
10.136.3.4 rpki.publication.report_error_elt.error_text = None [static]
```

Definition at line 329 of file publication.py.

```
10.136.3.5 rpki.publication.report_error_elt.tag
```

Definition at line 337 of file publication.py.

```
10.136.3.6 string rpki.publication.report_error_elt.text_attribute =  
            "error_text" [static]
```

Name of the class attribute that holds the text value.

Reimplemented from [rpki.xml\\_utils.text\\_elt](#)

Definition at line 327 of file publication.py.

The documentation for this class was generated from the following file:

- [publication.py \(2935\)](#)

## 10.137 rpki.publication.roa\_elt Class Reference

Inherits [rpki::publication::publication\\_object\\_elt](#)

Inherited by [irbe\\_cli.roa\\_elt](#)

### Static Public Attributes

- string [element\\_name](#) = "roa"
- [payload\\_type](#) = [rpki.x509.ROA](#)

#### 10.137.1 Detailed Description

<roa/> element.

Definition at line 310 of file `publication.py`.

#### 10.137.2 Member Data Documentation

10.137.2.1 string `rpki.publication.roa_elt.element_name = "roa"` [static]

Definition at line 315 of file `publication.py`.

10.137.2.2 `rpki.publication.roa_elt.payload_type = rpki.x509.ROA`  
[static]

Reimplemented from [rpki.publication.publication\\_object\\_elt](#)

Definition at line 316 of file `publication.py`.

The documentation for this class was generated from the following file:

- [publication.py](#) (2935)

## 10.138 rpki.publication.sax\_handler Class Reference

Inherits [rpki::xml\\_utils::sax\\_handler](#)

Inherited by [irbe\\_cli.publication\\_sax\\_handler](#)

### Static Public Attributes

- string [name](#)= "msg"
- [pdu](#)= [msg](#)
- string [version](#)= "1"

#### 10.138.1 Detailed Description

SAX handler for publication protocol.

Definition at line 405 of file `publication.py`.

#### 10.138.2 Member Data Documentation

##### 10.138.2.1 string `rpki.publication.sax_handler.name` = "msg" [static]

Definition at line 411 of file `publication.py`.

##### 10.138.2.2 `rpki.publication.sax_handler.pdu` = `msg` [static]

Reimplemented in [irbe\\_cli.publication\\_sax\\_handler](#)

Definition at line 410 of file `publication.py`.

##### 10.138.2.3 string `rpki.publication.sax_handler.version` = "1" [static]

Definition at line 412 of file `publication.py`.

The documentation for this class was generated from the following file:

- [publication.py](#) (2935)

### 10.139 rpki.resource\_set.resource\_bag Class Reference

Inherits [object](#)



## Public Member Functions

- [def \\_\\_eq\\_\\_](#)
- [def \\_\\_init\\_\\_](#)
- [def \\_\\_ne\\_\\_](#)
- [def \\_\\_str\\_\\_](#)
- [def empty](#)
- [def from\\_rfc3779\\_tuples](#)
- [def intersection](#)
- [def oversized](#)
- [def undersized](#)
- [def union](#)

## Public Attributes

- [asn](#)  
Set of Autonomous System Number resources.
- [v4](#)  
Set of IPv4 resources.
- [v6](#)  
Set of IPv6 resources.
- [valid\\_until](#)  
Expiration date of resources, for setting certificate notAfter field.

### 10.139.1 Detailed Description

Container to simplify passing around the usual triple of ASN, IPv4, and IPv6 resource sets.

Definition at line 547 of file resource\_set.py.

### 10.139.2 Member Function Documentation

#### 10.139.2.1 [def rpki.resource\\_set.resource\\_bag.\\_\\_eq\\_\\_\(self, other\)](#)

Definition at line 615 of file resource\_set.py.

10.139.2.2 `def rpki.resource_set.resource_bag.__init__(self, asn=None, v4=None, v6=None, valid_until=None)`

Definition at line 565 of `le resource_set.py`.

10.139.2.3 `def rpki.resource_set.resource_bag.__ne__(self, other)`

Definition at line 621 of `le resource_set.py`.

10.139.2.4 `def rpki.resource_set.resource_bag.__str__(self)`

Definition at line 644 of `le resource_set.py`.

10.139.2.5 `def rpki.resource_set.resource_bag.empty(self)`

True iff all resource sets in this bag are empty.

Definition at line 611 of `le resource_set.py`.

10.139.2.6 `def rpki.resource_set.resource_bag.from_rfc3779_tuples(self, exts)`

Build a resource\_bag from intermediate form generated by RFC 3779 ASN.1 decoder.

Definition at line 588 of `le resource_set.py`.

10.139.2.7 `def rpki.resource_set.resource_bag.intersection(self, other)`

Compute intersection with another resource\_bag. valid\_until attribute (if any) inherits from self.

Definition at line 624 of `le resource_set.py`.

10.139.2.8 `def rpki.resource_set.resource_bag.oversized(self, other)`

True iff self is oversized with respect to other.

Definition at line 571 of file resource\_set.py.

10.139.2.9 `def rpki.resource_set.resource_bag.undersized(self, other)`

True iff self is undersized with respect to other.

Definition at line 579 of file resource\_set.py.

10.139.2.10 `def rpki.resource_set.resource_bag.union(self, other)`

Compute union with another resource\_bag. valid\_until attribute (if any) inherits from self.

Definition at line 634 of file resource\_set.py.

### 10.139.3 Member Data Documentation

10.139.3.1 `rpki::resource_set.resource_bag::asn`

Set of Autonomous System Number resources.

Definition at line 566 of file resource\_set.py.

10.139.3.2 `rpki::resource_set.resource_bag::v4`

Set of IPv4 resources.

Definition at line 567 of file resource\_set.py.

## 10.139.3.3 rpki::resource\_set.resource\_bag::v6

Set of IPv6 resources.

Definition at line 568 of file resource\_set.py.

## 10.139.3.4 rpki::resource\_set.resource\_bag::valid\_until

Expiration date of resources, for setting certificate notAfter field.

Definition at line 569 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.140 rpki.resource\_set.resource\_range Class Reference

Inherits [object](#)

Inherited by [rpki.resource\\_set.resource\\_range\\_and](#) and [rpki.resource\\_set.resource\\_range\\_ip](#)

## Public Member Functions

- [def \\_\\_cmp\\_\\_](#)
- [def \\_\\_init\\_\\_](#)

## Public Attributes

- [max](#)
- [min](#)

## 10.140.1 Detailed Description

Generic resource range type. Assumes underlying type is some kind of integer.

This is a virtual class. You probably don't want to use this type directly.

Definition at line 50 of file resource\_set.py.

## 10.140.2 Member Function Documentation

### 10.140.2.1 `def rpki.resource_set.resource_range.__cmp__(self, other)`

Compare two `resource_range` objects.

Definition at line 67 of `le resource_set.py`.

### 10.140.2.2 `def rpki.resource_set.resource_range.__init__(self, min, max)`

Initialize and sanity check a `resource_range`.

Definition at line 59 of `le resource_set.py`.

## 10.140.3 Member Data Documentation

### 10.140.3.1 `rpki.resource_set.resource_range.max`

Definition at line 65 of `le resource_set.py`.

### 10.140.3.2 `rpki.resource_set.resource_range.min`

Reimplemented in [rpki.resource\\_set.resource\\_range\\_as](#)

Definition at line 64 of `le resource_set.py`.

The documentation for this class was generated from the following `le`:

- [resource\\_set.py \(2776\)](#)

## 10.141 `rpki.resource_set.resource_range_as` Class Reference

Inherits [rpki::resource\\_set::resource\\_range](#)

### Public Member Functions

- `def __str__`
- `def to_rfc3779_tuple`

## Public Attributes

- [min](#)

## Static Public Attributes

- [datum\\_type = long](#)  
Type of underlying data (min and max).

### 10.141.1 Detailed Description

Range of Autonomous System Numbers.

Denotes a single ASN by a range whose min and max values are identical.

Definition at line 78 of file resource\_set.py.

### 10.141.2 Member Function Documentation

#### 10.141.2.1 def rpki.resource\_set.resource\_range\_as.\_\_str\_\_(self)

Convert a resource\_range\_as to string format.

Definition at line 91 of file resource\_set.py.

#### 10.141.2.2 def rpki.resource\_set.resource\_range\_as.to\_rfc3779\_tuple(self)

Convert a resource\_range\_as to tuple format for RFC 3779 ASN.1 encoding.

Definition at line 100 of file resource\_set.py.

### 10.141.3 Member Data Documentation

#### 10.141.3.1 rpki::resource\_set.resource\_range\_as::datum\_type = long [static]

Type of underlying data (min and max).

Definition at line 89 of file resource\_set.py.

#### 10.141.3.2 rpki.resource\_set.resource\_range\_as.min

Reimplemented from [rpki.resource\\_set.resource\\_range](#)

Definition at line 95 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

### 10.142 rpki.resource\_set.resource\_range\_ip Class Reference

Inherits [rpki::resource\\_set::resource\\_range](#)

Inherited by [rpki.resource\\_set.resource\\_range\\_ip](#) and [rpki.resource\\_set.resource\\_range\\_ipv6](#)

#### Public Member Functions

- [def \\_\\_str\\_\\_](#)
- [def make\\_prefix](#)
- [def to\\_rfc3779\\_tuple](#)

#### Private Member Functions

- [def \\_prefixlen](#)

#### 10.142.1 Detailed Description

Range of (generic) IP addresses.

Prefixes are converted to ranges on input, and ranges that can be represented as prefixes are written as prefixes on output.

This is a virtual class. You probably don't want to use it directly.

Definition at line 109 of file resource\_set.py.

## 10.142.2 Member Function Documentation

### 10.142.2.1 def rpki.resource\_set.resource\_range\_ip.\_\_str\_\_(self)

Convert a resource\_range\_ip to string format.

Definition at line 137 of file resource\_set.py.

### 10.142.2.2 def rpki.resource\_set.resource\_range\_ip.\_prefixlen(self) [private]

Determine whether a resource\_range\_ip can be expressed as a prefix.

Definition at line 120 of file resource\_set.py.

### 10.142.2.3 def rpki.resource\_set.resource\_range\_ip.make\_prefix(self, prefix, prefixlen)

Construct a resource range corresponding to a prefix.

Definition at line 160 of file resource\_set.py.

### 10.142.2.4 def rpki.resource\_set.resource\_range\_ip.to\_rfc3779\_tuple(self)

Convert a resource\_range\_ip to tuple format for RFC 3779 ASN.1 encoding.

Definition at line 147 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.143 rpki.resource\_set.resource\_range\_ipv4 Class Reference

Inherits [rpki::resource\\_set::resource\\_range\\_ip](#)



### Static Public Attributes

- [datum\\_type= rpki.ipaddrs.v4addr](#)  
Type of underlying data (min and max).

#### 10.143.1 Detailed Description

Range of IPv4 addresses.

Definition at line 170 of file resource\_set.py.

#### 10.143.2 Member Data Documentation

10.143.2.1 `rpki::resource_set.resource_range_ipv4::datum_type = rpki.ipaddrs.v4addr` [static]

Type of underlying data (min and max).

Definition at line 178 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

### 10.144 rpki.resource\_set.resource\_range\_ipv6 Class Reference

Inherits [rpki::resource\\_set::resource\\_range\\_ip](#)

### Static Public Attributes

- [datum\\_type= rpki.ipaddrs.v6addr](#)  
Type of underlying data (min and max).

#### 10.144.1 Detailed Description

Range of IPv6 addresses.

Definition at line 180 of file resource\_set.py.

### 10.144.2 Member Data Documentation

#### 10.144.2.1 rpki::resource\_set.resource\_range\_ipv6::datum\_type = rpki.ipaddrs.v6addr [static]

Type of underlying data (min and max).

Definition at line 188 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

### 10.145 rpki.resource\_set.resource\_set Class Reference

Inherits list.

Inherited by [rpki.resource\\_set.resource\\_set](#) and [rpki.resource\\_set.resource\\_set\\_ip](#).

#### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [\\_\\_str\\_\\_](#)
- def [contains](#)
- def [difference](#)
- def [from\\_sql](#)
- def [intersection](#)
- def [issubset](#)
- def [issuperset](#)
- def [symmetric\\_difference](#)
- def [union](#)

#### Static Public Attributes

- [inherit](#) = False  
Boolean indicating whether this [resource\\_set](#) uses RFC 3779 inheritance.

#### Private Member Functions

- def [\\_comm](#)

### 10.145.1 Detailed Description

Generic resource set, a list subclass containing resource ranges.

This is a virtual class. You probably don't want to use it directly.

Definition at line 206 of file resource\_set.py.

### 10.145.2 Member Function Documentation

#### 10.145.2.1 def rpki.resource\_set.resource\_set.\_\_init\_\_(self, ini = None)

Initialize a resource\_set.

Definition at line 219 of file resource\_set.py.

#### 10.145.2.2 def rpki.resource\_set.resource\_set.\_\_str\_\_(self)

Convert a resource\_set to string format.

Definition at line 246 of file resource\_set.py.

#### 10.145.2.3 def rpki.resource\_set.resource\_set.comm(self, other) [private]

Like comm(1), sort of.

Returns a tuple of three resource sets: resources only in self, resources only in other, and resources in both. Used (not very efficiently) as the basis for most set operations on resource sets.

Definition at line 255 of file resource\_set.py.

#### 10.145.2.4 def rpki.resource\_set.resource\_set.contains(self, item)

Set membership test for resource sets.

Definition at line 332 of file resource\_set.py.

#### 10.145.2.5 def rpki.resource\_set.resource\_set.difference(self, other)

Set difference for resource sets.

Definition at line 323 of file resource\_set.py.

#### 10.145.2.6 def rpki.resource\_set.resource\_set.from\_sql(sql, query, args=None)

Create resource set from an SQL query.

sql is an object that supports execute() and fetchall() methods like a DB API 2.0 cursor object.

query is an SQL query that returns a sequence of (min, max) pairs.

Definition at line 369 of file resource\_set.py.

#### 10.145.2.7 def rpki.resource\_set.resource\_set.intersection(self, other)

Set intersection for resource sets.

Definition at line 319 of file resource\_set.py.

#### 10.145.2.8 def rpki.resource\_set.resource\_set.issubset(self, other)

Test whether self is a subset (possibly improper) of other.

Definition at line 355 of file resource\_set.py.

#### 10.145.2.9 def rpki.resource\_set.resource\_set.issuperset(self, other)

Test whether self is a superset (possibly improper) of other.

Definition at line 364 of file resource\_set.py.

10.145.2.10 `def rpki.resource_set.resource_set.symmetric_difference(self, other)`

Set symmetric difference (XOR) for resource sets.

Definition at line 327 of file `resource_set.py`.

10.145.2.11 `def rpki.resource_set.resource_set.union(self, other)`

Set union for resource sets.

Definition at line 288 of file `resource_set.py`.

### 10.145.3 Member Data Documentation

10.145.3.1 `rpki::resource_set.resource_set::inherit = False`[\[static\]](#)

Boolean indicating whether this `resource_set` uses RFC 3779 inheritance.

Reimplemented in `rpki.resource_set.resource_set_and` and `rpki.resource_set.resource_set_ip`

Definition at line 217 of file `resource_set.py`.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.146 rpki.resource\_set.resource\_set\_as Class Reference

Inherits `rpki::resource_set::resource_set`

### Public Member Functions

- `def parse_rfc3779_tuple`
- `def parse_str`
- `def to_rfc3779_tuple`

## Public Attributes

- [inherit](#)  
Boolean indicating whether this [resource\\_set](#) uses RFC 3779 inheritance.

## Static Public Attributes

- [range\\_type](#) = [resource\\_range\\_as](#)  
Type of range underlying this type of [resource\\_set](#)

## 10.146.1 Detailed Description

Autonomous System Number resource set.

Definition at line 384 of file `resource_set.py`.

## 10.146.2 Member Function Documentation

10.146.2.1 `def rpki.resource_set.resource_set_as.parse_rfc3779_tuple(self, x)`

Parse ASN resource from tuple format generated by RFC 3779 ASN.1 decoder.

Definition at line 404 of file `resource_set.py`.

10.146.2.2 `def rpki.resource_set.resource_set_as.parse_set(self, x)`

Parse ASN resource sets from text (eg, XML attributes).

Definition at line 394 of file `resource_set.py`.

10.146.2.3 `def rpki.resource_set.resource_set_as.to_rfc3779_tuple(self)`

Convert ASN resource set into tuple format used for RFC 3779 ASN.1 encoding.

Definition at line 422 of file `resource_set.py`.

## 10.146.3 Member Data Documentation

## 10.146.3.1 rpki.resource\_set.resource\_set\_as.inherit

Boolean indicating whether this [resource\\_set](#) uses RFC 3779 inheritance.

Reimplemented from [rpki.resource\\_set.resource\\_set](#)

Definition at line 420 of file `resource_set.py`.

## 10.146.3.2 rpki.resource\_set.resource\_set\_as::range\_type = resource\_range\_as [static]

Type of range underlying this type of [resource\\_set](#)

Definition at line 392 of file `resource_set.py`.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.147 rpki.resource\_set.resource\_set\_ip Class Reference

Inherits [rpki.resource\\_set.resource\\_set](#)

Inherited by [rpki.resource\\_set.resource\\_set\\_ip](#) and [rpki.resource\\_set.resource\\_set\\_ipv6](#).

## Public Member Functions

- def [parse\\_rfc3779\\_tuple](#)
- def [parse\\_str](#)
- def [to\\_rfc3779\\_tuple](#)

## Public Attributes

- [inherit](#)

Boolean indicating whether this [resource\\_set](#) uses RFC 3779 inheritance.

### 10.147.1 Detailed Description

(Generic) IP address resource set.

This is a virtual class. You probably don't want to use it directly.

Definition at line 434 of file resource\_set.py.

### 10.147.2 Member Function Documentation

#### 10.147.2.1 def rpki.resource\_set.resource\_set\_ip.parse\_rfc3779\_tuple(self, x)

Parse IP address resource sets from tuple format generated by RFC 3779 ASN.1 decoder.

Definition at line 454 of file resource\_set.py.

#### 10.147.2.2 def rpki.resource\_set.resource\_set\_ip.parse\_str(self, x)

Parse IP address resource sets from text (eg, XML attributes).

Definition at line 442 of file resource\_set.py.

#### 10.147.2.3 def rpki.resource\_set.resource\_set\_ip.to\_rfc3779\_tuple(self)

Convert IP resource set into tuple format used by RFC 3779 ASN.1 encoder.

Definition at line 472 of file resource\_set.py.

### 10.147.3 Member Data Documentation

#### 10.147.3.1 rpki.resource\_set.resource\_set\_ip.inherit

Boolean indicating whether this resource\_set uses RFC 3779 inheritance.

Reimplemented from [rpki.resource\\_set.resource\\_set](#)



Definition at line 470 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.148 rpki.resource\_set.resource\_set\_ipv4 Class Reference

Inherits [rpki::resource\\_set::resource\\_set\\_ip](#)

### Static Public Attributes

- `string a = "\x00\x01"`  
Address Family Identifier value for IPv4.
- `range_type = resource_range_ipv4`  
Type of range underlying this type of [resource\\_set](#)

### 10.148.1 Detailed Description

IPv4 address resource set.

Definition at line 484 of file resource\_set.py.

### 10.148.2 Member Data Documentation

10.148.2.1 `rpki::resource_set.resource_set_ipv4::a = "\x00\x01" [static]`

Address Family Identifier value for IPv4.

Definition at line 497 of file resource\_set.py.

10.148.2.2 `rpki::resource_set.resource_set_ipv4::range_type = resource_range_ipv4 [static]`

Type of range underlying this type of [resource\\_set](#)

Definition at line 492 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.149 rpki.resource\_set.resource\_set\_ipv6 Class Reference

Inherits [rpki::resource\\_set::resource\\_set\\_ip](#)

### Static Public Attributes

- string `a` = "\x00\x02"  
Address Family Identifier value for IPv6.
- `range_type` = [resource\\_range\\_ipv6](#)  
Type of range underlying this type of [resource\\_set](#)

### 10.149.1 Detailed Description

IPv6 address resource set.

Definition at line 499 of file `resource_set.py`.

### 10.149.2 Member Data Documentation

10.149.2.1 `rpki::resource_set.resource_set_ipv6::a = "\x00\x02"` [static]

Address Family Identifier value for IPv6.

Definition at line 512 of file `resource_set.py`.

10.149.2.2 `rpki::resource_set.resource_set_ipv6::range_type = resource_range_ipv6` [static]

Type of range underlying this type of [resource\\_set](#)

Definition at line 507 of file `resource_set.py`.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.150 rpki.resource\_set.roa\_pre x Class Reference

Inherits [object](#)

Inherited by [rpki.resource\\_set.roa\\_pre x\\_ipv4](#) and [rpki.resource\\_set.roa\\_pre x\\_ipv6](#)

### Public Member Functions

- [def \\_\\_cmp\\_\\_](#)
- [def \\_\\_init\\_\\_](#)
- [def \\_\\_str\\_\\_](#)
- [def max](#)
- [def min](#)
- [def to\\_resource\\_range](#)
- [def to\\_roa\\_tuple](#)

### Public Attributes

- [max\\_pre\\_xlen](#)  
Maximum pre x length.
- [pre\\_x](#)  
The pre x itself, an IP address with bits beyond the pre x length zeroed.
- [pre\\_xlen](#)  
(Minimum) pre x length.

#### 10.150.1 Detailed Description

ROA prefix. This is similar to the `resource_range_ip` class, but differs in that it only represents prefixes, never ranges, and includes the maximum prefix length as an additional value.

This is a virtual class, you probably don't want to use it directly.

Definition at line 666 of file `resource_set.py`.

#### 10.150.2 Member Function Documentation

##### 10.150.2.1 `def rpki.resource_set.roa_pre x.__cmp__(self, other)`

Compare two ROA prefix objects. Comparison is based on prefix, prefixlen, and max\_prefixlen, in that order.

Definition at line 697 of file resource\_set.py.

```
10.150.2.2 def rpki.resource_set.roa_prefix.__init__(self, prefix, prefixlen,
max_prefixlen = None)
```

Initialize a ROA prefix. max\_prefixlen is optional and defaults to prefixlen. max\_prefixlen must not be smaller than prefixlen.

Definition at line 685 of file resource\_set.py.

```
10.150.2.3 def rpki.resource_set.roa_prefix.__str__(self)
```

Convert a ROA prefix to string format.

Definition at line 710 of file resource\_set.py.

```
10.150.2.4 def rpki.resource_set.roa_prefix.max(self)
```

Return highest address covered by prefix.

Definition at line 731 of file resource\_set.py.

```
10.150.2.5 def rpki.resource_set.roa_prefix.min(self)
```

Return lowest address covered by prefix.

Definition at line 727 of file resource\_set.py.

```
10.150.2.6 def rpki.resource_set.roa_prefix.to_resource_ranges(self)
```

Convert this ROA prefix to the equivalent resource\_range\_ip object. This is an irreversible transformation because it loses the max\_prefixlen attribute, nothing we can do about that.

Definition at line 719 of file resource\_set.py.

10.150.2.7 def rpki.resource\_set.roa\_prefix.to\_roa\_tuple(self)

Convert a resource\_range\_ip to tuple format for ROA ASN.1 encoding.

Definition at line 738 of file resource\_set.py.

### 10.150.3 Member Data Documentation

10.150.3.1 rpki::resource\_set.roa\_prefix::max\_prefixlen

Maximum prefix length.

Definition at line 695 of file resource\_set.py.

10.150.3.2 rpki::resource\_set.roa\_prefix::prefix

The prefix itself, an IP address with bits beyond the prefix length zeroed.

Definition at line 693 of file resource\_set.py.

10.150.3.3 rpki::resource\_set.roa\_prefix::prefixlen

(Minimum) prefix length.

Definition at line 694 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.151 rpki.resource\_set.roa\_prefix\_ipv4 Class Reference

Inherits [rpki::resource\\_set::roa\\_prefix](#)

## Static Public Attributes

- [range\\_type= resource\\_range\\_ipv4](#)  
Type of corresponding [resource\\_range\\_ip](#)

## 10.151.1 Detailed Description

IPv4 ROA prefix.

Definition at line 746 of file resource\_set.py.

## 10.151.2 Member Data Documentation

10.151.2.1 `rpki::resource_set.roa_prefix_ipv4::range_type = resource_range_ipv4 [static]`

Type of corresponding [resource\\_range\\_ip](#)

Definition at line 754 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.152 rpki.resource\_set.roa\_prefix\_ipv6 Class Reference

Inherits [rpki::resource\\_set::roa\\_prefix](#).

## Static Public Attributes

- [range\\_type= resource\\_range\\_ipv6](#)  
Type of corresponding [resource\\_range\\_ip](#)

## 10.152.1 Detailed Description

IPv6 ROA prefix.

Definition at line 756 of file resource\_set.py.

## 10.152.2 Member Data Documentation

### 10.152.2.1 rpki::resource\_set.roa\_prefix\_ipv6::range\_type = resource\_range\_ipv6 [static]

Type of corresponding [resource\\_range\\_ip](#)

Definition at line 764 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.153 rpki.resource\_set.roa\_prefix\_set Class Reference

Inherits list.

Inherited by [rpki.resource\\_set.roa\\_prefix\\_set\\_ipv4](#) and [rpki.resource\\_set.roa\\_prefix\\_set\\_ipv6](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [\\_\\_str\\_\\_](#)
- def [from\\_sql](#)
- def [parse\\_str](#)
- def [to\\_resource\\_set](#)
- def [to\\_roa\\_tuple](#)

### 10.153.1 Detailed Description

Set of ROA prefixes, analogous to the resource\_set\_ip class.

Definition at line 766 of file resource\_set.py.

### 10.153.2 Member Function Documentation

#### 10.153.2.1 def rpki.resource\_set.roa\_prefix\_set.\_\_init\_\_(self, ini = None)

Initialize a ROA prefix set.

Definition at line 771 of file resource\_set.py.

## 10.153.2.2 def rpki.resource\_set.roa\_prefix\_set.\_\_str\_\_(self)

Convert a ROA prefix set to string format.

Definition at line 791 of file resource\_set.py.

## 10.153.2.3 def rpki.resource\_set.roa\_prefix\_set.from\_sql(sql, query, args = None)

Create ROA prefix set from an SQL query.

sql is an object that supports execute() and fetchall() methods like a DB API 2.0 cursor object.

query is an SQL query that returns a sequence of (prefix, prefixlen, max\_prefixlen) triples.

Definition at line 825 of file resource\_set.py.

## 10.153.2.4 def rpki.resource\_set.roa\_prefix\_set.parse\_text(self, x)

Parse ROA prefix from text (eg, an XML attribute).

Definition at line 795 of file resource\_set.py.

## 10.153.2.5 def rpki.resource\_set.roa\_prefix\_set.to\_resource\_set(self)

Convert a ROA prefix set to a resource set. This is an irreversible transformation. We have to compute a union here because ROA prefix sets can include overlaps, while RFC 3779 resource sets cannot. This is ugly, and there is almost certainly a more efficient way to do this, but start by getting the output right before worrying about making it fast or pretty.

Definition at line 807 of file resource\_set.py.



## 10.153.2.6 def rpki.resource\_set.roa\_prefix\_set.to\_roa\_tuples(self)

Convert ROA prefix set into tuple format used by ROA ASN.1 encoder. This is a variation on the format used in RFC 3779.

Definition at line 840 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.154 rpki.resource\_set.roa\_prefix\_set\_ipv4 Class Reference

Inherits [rpki::resource\\_set::roa\\_prefix\\_set](#)

## Static Public Attributes

- [prefix\\_type = roa\\_prefix\\_ipv4](#)  
Type of underlying [roa\\_prefix](#).
- [resource\\_set\\_type = resource\\_set\\_ipv4](#)  
Type of corresponding [resource\\_set](#) class.

## 10.154.1 Detailed Description

Set of IPv4 ROA prefixes.

Definition at line 850 of file resource\_set.py.

## 10.154.2 Member Data Documentation

10.154.2.1 [rpki::resource\\_set.roa\\_prefix\\_set\\_ipv4::prefix\\_type = roa\\_prefix\\_ipv4](#) [static]

Type of underlying [roa\\_prefix](#).

Definition at line 858 of file resource\_set.py.

10.154.2.2 rpki::resource\_set.roa\_pre\_x\_set\_ipv4::resource\_set\_type = resource\_set\_ipv4 [static]

Type of corresponding [resource\\_set\\_ip](#) class.

Definition at line 863 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.155 rpki.resource\_set.roa\_pre\_x\_set\_ipv6 Class Reference

Inherits [rpki::resource\\_set::roa\\_pre\\_x\\_set](#)

### Static Public Attributes

- [pre\\_x\\_type = roa\\_pre\\_x\\_ipv6](#)  
Type of underlying [roa\\_pre\\_x](#).
- [resource\\_set\\_type = resource\\_set\\_ipv6](#)  
Type of corresponding [resource\\_set\\_ip](#) class.

### 10.155.1 Detailed Description

Set of IPv6 ROA prefixes.

Definition at line 865 of file resource\_set.py.

### 10.155.2 Member Data Documentation

10.155.2.1 rpki::resource\_set.roa\_pre\_x\_set\_ipv6::pre\_x\_type = roa\_pre\_x\_ipv6 [static]

Type of underlying [roa\\_pre\\_x](#).

Definition at line 873 of file resource\_set.py.

10.155.2.2 rpki::resource\_set.roa\_pre x\_set\_ipv6::resource\_set\_type =  
resource\_set\_ipv6 [static]

Type of corresponding [resource\\_set\\_ip](#) class.

Definition at line 878 of file resource\_set.py.

The documentation for this class was generated from the following file:

- [resource\\_set.py \(2776\)](#)

## 10.156 rpki.roa.ROAIPAddress Class Reference

Inherits [Sequence](#)

Public Member Functions

- [def \\_\\_init\\_\\_](#)

Public Attributes

- [address](#)
- [maxLength](#)

### 10.156.1 Detailed Description

Definition at line 47 of file roa.py.

### 10.156.2 Member Function Documentation

10.156.2.1 `def rpki.roa.ROAIPAddress.__init__(self, optional=0, default="")`

Definition at line 48 of file roa.py.

### 10.156.3 Member Data Documentation

10.156.3.1 `rpki.roa.ROAIPAddress.address`

Definition at line 49 of file roa.py.

## 10.156.3.2 rpki.roa.ROAIPAddress.maxLength

Definition at line 50 of file roa.py.

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.157 rpki.roa.ROAIPAddresses Class Reference

Inherits [SequenceOf](#)

Public Member Functions

- [def \\_\\_init\\_\\_](#)

## 10.157.1 Detailed Description

Definition at line 54 of file roa.py.

## 10.157.2 Member Function Documentation

10.157.2.1 `def rpki.roa.ROAIPAddresses.__init__(self, optional=0, default=`  
 `)`

Definition at line 55 of file roa.py.

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.158 rpki.roa.ROAIPAddressFamilies Class Reference

Inherits [SequenceOf](#)

Public Member Functions

- [def \\_\\_init\\_\\_](#)

### 10.158.1 Detailed Description

Definition at line 65 of file roa.py.

### 10.158.2 Member Function Documentation

10.158.2.1 def rpki.roa.ROAIPAddressFamilies.\_\_init\_\_(self, optional = 0, default = " ")

Definition at line 66 of file roa.py.

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.159 rpki.roa.ROAIPAddressFamily Class Reference

Inherits [Sequence](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)

### Public Attributes

- [addresses](#)
- [addressFamily](#)

### 10.159.1 Detailed Description

Definition at line 58 of file roa.py.

### 10.159.2 Member Function Documentation

10.159.2.1 def rpki.roa.ROAIPAddressFamily.\_\_init\_\_(self, optional = 0, default = " ")

Definition at line 59 of file roa.py.

### 10.159.3 Member Data Documentation

#### 10.159.3.1 rpki.roa.ROAIPAddressFamily.addresses

Definition at line 61 of file roa.py.

#### 10.159.3.2 rpki.roa.ROAIPAddressFamily.addressFamily

Definition at line 60 of file roa.py.

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.160 rpki.roa.RouteOriginAttestation Class Reference

Inherits [Sequence](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)

### Public Attributes

- [asID](#)
- [explicitVersion](#)
- [ipAddrBlocks](#)
- [version](#)

### 10.160.1 Detailed Description

Definition at line 69 of file roa.py.

### 10.160.2 Member Function Documentation

#### 10.160.2.1 `def rpki.roa.RouteOriginAttestation.__init__(self, optional = 0, default = "")`

Definition at line 70 of file roa.py.

### 10.160.3 Member Data Documentation

#### 10.160.3.1 rpki.roa.RouteOriginAttestation.asID

Definition at line 73 of file roa.py.

#### 10.160.3.2 rpki.roa.RouteOriginAttestation.explicitVersion

Definition at line 72 of file roa.py.

#### 10.160.3.3 rpki.roa.RouteOriginAttestation.ipAddrBlocks

Definition at line 74 of file roa.py.

#### 10.160.3.4 rpki.roa.RouteOriginAttestation.version

Definition at line 71 of file roa.py.

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.161 rpki.rpki\_engine.ca\_detail\_obj Class Reference

Inherits [rpki::sql::sql\\_persistent](#)

### Public Member Functions

- def [activate](#)
- def [ca](#)
- def [child\\_certs](#)
- def [create](#)
- def [crl\\_published\\_callback](#)

- def [crl\\_uri](#)
- def [crl\\_uri\\_tail](#)
- def [delete](#)
- def [generate\\_crl](#)
- def [generate\\_manifest](#)
- def [generate\\_manifest\\_cert](#)
- def [issue](#)
- def [issue\\_ee](#)
- def [manifest\\_published\\_callback](#)
- def [manifest\\_uri](#)
- def [revoke](#)
- def [revoked\\_certs](#)
- def [roas](#)
- def [sql\\_decode](#)
- def [update](#)

#### Public Attributes

- [ca\\_cert\\_uri](#)
- [ca\\_id](#)
- [gctx](#)
- [latest\\_crl](#)
- [latest\\_manifest](#)
- [latest\\_manifest\\_cert](#)
- [manifest\\_private\\_key\\_id](#)
- [manifest\\_public\\_key](#)
- [nextUpdate](#)
- [private\\_key\\_id](#)
- [public\\_key](#)
- [state](#)

#### Static Public Attributes

- [crl\\_published](#) = None
- [latest\\_ca\\_cert](#) = None
- [manifest\\_published](#) = None
- tuple [sql\\_template](#)

#### 10.161.1 Detailed Description

Internal CA detail object.

Definition at line 563 of file `rpki_engine.py`.



## 10.161.2 Member Function Documentation

10.161.2.1 `def rpki.rpki_engine.ca_detail_obj.activate(self, ca, cert, uri, callback, errback, predecessor=None)`

Activate this ca\_detail.

Definition at line 625 of file rpki\_engine.py.

10.161.2.2 `def rpki.rpki_engine.ca_detail_obj.ca(self)`

Fetch CA object to which this ca\_detail links.

Definition at line 597 of file rpki\_engine.py.

10.161.2.3 `def rpki.rpki_engine.ca_detail_obj.child_certs(self, child = None, ski = None, unique = False )`

Fetch all child\_cert objects that link to this ca\_detail.

Definition at line 601 of file rpki\_engine.py.

10.161.2.4 `def rpki.rpki_engine.ca_detail_obj.create(self, ca)`

Create a new ca\_detail object for a specified CA.

Definition at line 763 of file rpki\_engine.py.

10.161.2.5 `def rpki.rpki_engine.ca_detail_obj.crl_published_callback(self, pdu)`

Check result of CRL publication.

Definition at line 886 of file rpki\_engine.py.

### 10.161.2.6 def rpki.rpki\_engine.ca\_detail\_obj.crl\_uri (self, ca)

Return publication URI for this ca\_detail's CRL.

Definition at line 613 of file rpki\_engine.py.

### 10.161.2.7 def rpki.rpki\_engine.ca\_detail\_obj.crl\_uri\_tail (self)

Return tail (filename portion) of publication URI for this ca\_detail's CRL.

Definition at line 617 of file rpki\_engine.py.

### 10.161.2.8 def rpki.rpki\_engine.ca\_detail\_obj.delete(self, ca, publisher, allow\_failure = False )

Delete this ca\_detail and all of the certs it issued.

If allow\_failure is true, we clean up as much as we can but don't raise an exception.

Definition at line 650 of file rpki\_engine.py.

### 10.161.2.9 def rpki.rpki\_engine.ca\_detail\_obj.generate\_crl(self, publisher, nextUpdate= None)

Generate a new CRL for this ca\_detail. At the moment this is unconditional, that is, it is up to the caller to decide whether a new CRL is needed.

Definition at line 850 of file rpki\_engine.py.

### 10.161.2.10 def rpki.rpki\_engine.ca\_detail\_obj.generate\_manifest(self, publisher, nextUpdate= None)

Generate a new manifest for this ca\_detail.

Definition at line 894 of file rpki\_engine.py.

10.161.2.11 `def rpki.rpki_engine.ca_detail_obj.generate_manifest_cert(self, ca)`

Generate a new manifest certificate for this ca\_detail.

Definition at line 798 of `rpki_engine.py`.

10.161.2.12 `def rpki.rpki_engine.ca_detail_obj.issue(self, ca, child, subject_key sia, resources publisher, child_cert= None)`

Issue a new certificate to a child. Optional child\_cert argument specifies an existing child\_cert object to update in place; if not specified, we create a new one. Returns the child\_cert object containing the newly issued cert.

Definition at line 810 of `rpki_engine.py`.

10.161.2.13 `def rpki.rpki_engine.ca_detail_obj.issue_ee(self, ca, resources subject_key sia= None)`

Issue a new EE certificate.

Definition at line 781 of `rpki_engine.py`.

10.161.2.14 `def rpki.rpki_engine.ca_detail_obj.manifest_published_callback (self, pdu)`

Check result of manifest publication.

Definition at line 928 of `rpki_engine.py`.

10.161.2.15 `def rpki.rpki_engine.ca_detail_obj.manifest_uri(self, ca)`

Return publication URI for this ca\_detail's manifest.

Definition at line 621 of `rpki_engine.py`.

### 10.161.2.16 def rpki.rpki\_engine.ca\_detail\_obj.revokeself, cb, eb)

Request revocation of all certificates whose SKI matches the key for this ca\_detail.

Tasks:

- Request revocation of old keypair by parent.
- Revoke all child certs issued by the old keypair.
- Generate a final CRL, signed with the old keypair, listing all the revoked certs, with a next CRL time after the last cert or CRL signed by the old keypair will have expired.
- Generate a corresponding final manifest.
- Destroy old keypairs.
- Leave final CRL and manifest in place until their nextupdate time has passed.

Definition at line 674 of file rpki\_engine.py.

### 10.161.2.17 def rpki.rpki\_engine.ca\_detail\_obj.revoked\_certsself)

Fetch all revoked\_cert objects that link to this ca\_detail.

Definition at line 605 of file rpki\_engine.py.

### 10.161.2.18 def rpki.rpki\_engine.ca\_detail\_obj.roasself)

Fetch all ROA objects that link to this ca\_detail.

Definition at line 609 of file rpki\_engine.py.

### 10.161.2.19 def rpki.rpki\_engine.ca\_detail\_obj.sql\_decode(self, vals)

Extra assertions for SQL decode of a ca\_detail\_obj.

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 589 of file rpki\_engine.py.

10.161.2.20 `def rpki.rpki_engine.ca_detail_obj.update(self, parent, ca, rc, sia_uri_changed, old_resources, callback, errback)`

Need to get a new certificate for this ca\_detail and perhaps frob children of this ca\_detail.

Definition at line 738 of `le rpki_engine.py`.

### 10.161.3 Member Data Documentation

10.161.3.1 `rpki.rpki_engine.ca_detail_obj.ca_cert_uri`

Definition at line 633 of `le rpki_engine.py`.

10.161.3.2 `rpki.rpki_engine.ca_detail_obj.ca_id`

Definition at line 769 of `le rpki_engine.py`.

10.161.3.3 `rpki.rpki_engine.ca_detail_obj.crl_published = None[static]`

Definition at line 585 of `le rpki_engine.py`.

10.161.3.4 `rpki.rpki_engine.ca_detail_obj.gctx`

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 768 of `le rpki_engine.py`.

10.161.3.5 `rpki.rpki_engine.ca_detail_obj.latest_ca_cert = None[static]`

Definition at line 587 of `le rpki_engine.py`.

### 10.161.3.6 rpki.rpki\_engine.ca\_detail\_obj.latest\_crl

Definition at line 873 of file rpki\_engine.py.

### 10.161.3.7 rpki.rpki\_engine.ca\_detail\_obj.latest\_manifest

Definition at line 914 of file rpki\_engine.py.

### 10.161.3.8 rpki.rpki\_engine.ca\_detail\_obj.latest\_manifest\_cert

Definition at line 731 of file rpki\_engine.py.

### 10.161.3.9 rpki.rpki\_engine.ca\_detail\_obj.manifest\_private\_key\_id

Definition at line 729 of file rpki\_engine.py.

### 10.161.3.10 rpki.rpki\_engine.ca\_detail\_obj.manifest\_public\_key

Definition at line 730 of file rpki\_engine.py.

### 10.161.3.11 rpki.rpki\_engine.ca\_detail\_obj.manifest\_published = None [static]

Definition at line 586 of file rpki\_engine.py.

### 10.161.3.12 rpki.rpki\_engine.ca\_detail\_obj.nextUpdate

Definition at line 707 of file rpki\_engine.py.

## 10.161.3.13 rpki.rpki\_engine.ca\_detail\_obj.private\_key\_id

Definition at line 728 of file rpki\_engine.py.

## 10.161.3.14 rpki.rpki\_engine.ca\_detail\_obj.public\_key

Definition at line 773 of file rpki\_engine.py.

## 10.161.3.15 tuple rpki.rpki\_engine.ca\_detail\_obj.sql\_template[static]

Initial value:

```
rpki.sql.template(
    "ca_detail",
    "ca_detail_id",
    ("private_key_id", rpki.x509.RSA),
    ("public_key", rpki.x509.RSAPublic),
    ("latest_ca_cert", rpki.x509.X509),
    ("manifest_private_key_id", rpki.x509.RSA),
    ("manifest_public_key", rpki.x509.RSAPublic),
    ("latest_manifest_cert", rpki.x509.X509),
    ("latest_manifest", rpki.x509.SignedManifest),
    ("latest_crl", rpki.x509.CRL),
    ("crl_published", rpki.sundial.datetime),
    ("manifest_published", rpki.sundial.datetime),
    "state",
    "ca_cert_uri",
    "ca_id")
```

Definition at line 568 of file rpki\_engine.py.

## 10.161.3.16 rpki.rpki\_engine.ca\_detail\_obj.state

Definition at line 635 of file rpki\_engine.py.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.162 rpki.rpki\_engine.ca\_obj Class Reference

Inherits [rpki::sql::sql\\_persistent](#)

### Public Member Functions

- def [ca\\_details](#)
- def [check\\_for\\_updates](#)
- def [construct\\_sia\\_uri](#)
- def [create](#)
- def [delete](#)
- def [fetch\\_active](#)
- def [fetch\\_deprecated](#)
- def [fetch\\_issue\\_response\\_candidates](#)
- def [fetch\\_pending](#)
- def [fetch\\_revoked](#)
- def [next\\_crl\\_number](#)
- def [next\\_manifest\\_number](#)
- def [next\\_serial\\_number](#)
- def [parent](#)
- def [rekey](#)
- def [revoke](#)

### Public Attributes

- [gctx](#)
- [parent\\_id](#)
- [parent\\_resource\\_class](#)
- [sia\\_uri](#)

### Static Public Attributes

- int [last\\_crl\\_sn](#) = 0
- int [last\\_issued\\_sn](#) = 0
- int [last\\_manifest\\_sn](#) = 0
- tuple [sql\\_template](#)

#### 10.162.1 Detailed Description

Internal CA object.

Definition at line 309 of file `rpki_engine.py`.



## 10.162.2 Member Function Documentation

### 10.162.2.1 def rpki.rpki\_engine.ca\_obj.ca\_detailss(elf)

Fetch all ca\_detail objects that link to this CA object.

Definition at line 331 of file rpki\_engine.py.

### 10.162.2.2 def rpki.rpki\_engine.ca\_obj.check\_for\_updates(elf, parent, rc, cb, eb)

Parent has signaled continued existence of a resource class we already knew about, so we need to check for an updated certificate, changes in resource coverage, revocation and reissue with the same key, etc.

Definition at line 372 of file rpki\_engine.py.

### 10.162.2.3 def rpki.rpki\_engine.ca\_obj.construct\_sia\_uri(elf, parent, rc)

Construct the sia\_uri value for this CA given configured information and the parent's up-down protocol list\_response PDU.

Definition at line 359 of file rpki\_engine.py.

### 10.162.2.4 def rpki.rpki\_engine.ca\_obj.create\_cls(parent, rc, cb, eb)

Parent has signaled existence of a new resource class, so we need to create and set up a corresponding CA object.

Definition at line 452 of file rpki\_engine.py.

### 10.162.2.5 def rpki.rpki\_engine.ca\_obj.delete(elf, parent, callback)

The list of current resource classes received from parent does not include the class corresponding to this CA, so we need to delete it (and its little dog too...).

All certs published by this CA are now invalid, so need to withdraw them, the CRL, and the manifest from the repository, delete all child\_cert and ca\_detail records associated with this CA, then finally delete this CA itself.

Definition at line 476 of file rpki\_engine.py.

10.162.2.6 def rpki.rpki\_engine.ca\_obj.fetch\_active(self)

Fetch the active ca\_detail for this CA, if any.

Definition at line 339 of file rpki\_engine.py.

10.162.2.7 def rpki.rpki\_engine.ca\_obj.fetch\_deprecated(self)

Fetch deprecated ca\_details for this CA, if any.

Definition at line 343 of file rpki\_engine.py.

10.162.2.8 def rpki.rpki\_engine.ca\_obj.fetch\_issue\_response\_candidates(self)

Fetch ca\_details which are candidates for consideration when processing an up-down issue\_response PDU.

Definition at line 351 of file rpki\_engine.py.

10.162.2.9 def rpki.rpki\_engine.ca\_obj.fetch\_pending(self)

Fetch the pending ca\_details for this CA, if any.

Definition at line 335 of file rpki\_engine.py.

#### 10.162.2.10 def rpkirpki\_engine.ca\_obj.fetch\_revoked(self)

Fetch revoked ca\_details for this CA, if any.

Definition at line 347 of file rpkirpki\_engine.py.

#### 10.162.2.11 def rpkirpki\_engine.ca\_obj.next\_crl\_number(self)

Allocate a CRL serial number.

Definition at line 518 of file rpkirpki\_engine.py.

#### 10.162.2.12 def rpkirpki\_engine.ca\_obj.next\_manifest\_numbers(self)

Allocate a manifest serial number.

Definition at line 510 of file rpkirpki\_engine.py.

#### 10.162.2.13 def rpkirpki\_engine.ca\_obj.next\_serial\_numbers(self)

Allocate a certificate serial number.

Definition at line 502 of file rpkirpki\_engine.py.

#### 10.162.2.14 def rpkirpki\_engine.ca\_obj.parent(self)

Fetch parent object to which this CA object links.

Definition at line 327 of file rpkirpki\_engine.py.

10.162.2.15 `def rpki.rpki_engine.ca_obj.rekey(self, cb, eb)`

Initiate a rekey operation for this ca. Generate a new keypair. Request cert from parent using new keypair. Mark result as our active ca\_detail. Reissue all child certs issued by this ca using the new ca\_detail.

Definition at line 526 of `le rpki_engine.py`.

10.162.2.16 `def rpki.rpki_engine.ca_obj.revoke(self, cb, eb)`

Revoke deprecated ca\_detail objects associated with this ca.

Definition at line 551 of `le rpki_engine.py`.

### 10.162.3 Member Data Documentation

10.162.3.1 `rpki.rpki_engine.ca_obj.gctx`

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 459 of `le rpki_engine.py`.

10.162.3.2 `int rpki.rpki_engine.ca_obj.last_crl_sn = 0 [static]`

Definition at line 323 of `le rpki_engine.py`.

10.162.3.3 `int rpki.rpki_engine.ca_obj.last_issued_sn = 0 [static]`

Definition at line 324 of `le rpki_engine.py`.

10.162.3.4 `int rpki.rpki_engine.ca_obj.last_manifest_sn = 0 [static]`

Definition at line 325 of `le rpki_engine.py`.

## 10.162.3.5 rpki.rpki\_engine.ca\_obj.parent\_id

Definition at line 460 of file rpki\_engine.py.

## 10.162.3.6 rpki.rpki\_engine.ca\_obj.parent\_resource\_class

Definition at line 461 of file rpki\_engine.py.

## 10.162.3.7 rpki.rpki\_engine.ca\_obj.sia\_uri

Definition at line 383 of file rpki\_engine.py.

## 10.162.3.8 tuple rpki.rpki\_engine.ca\_obj.sql\_template[static]

Initial value:

```
rpki.sql.template(  
    "ca",  
    "ca_id",  
    "last_crl_sn",  
    ("next_crl_update", rpki.sundial.datetime),  
    "last_issued_sn", "last_manifest_sn",  
    ("next_manifest_update", rpki.sundial.datetime),  
    "sia_uri", "parent_id", "parent_resource_class")
```

Definition at line 314 of file rpki\_engine.py.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.163 rpki.rpki\_engine.child\_cert\_obj Class Reference

Inherits [rpki::sql::sql\\_persistent](#)

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [ca\\_detail](#)
- def [child](#)

- def [fetch](#)
- def [published\\_callback](#)
- def [reissue](#)
- def [revoke](#)
- def [uri](#)
- def [uri\\_tail](#)

#### Public Attributes

- [ca\\_detail\\_id](#)
- [cert](#)
- [child\\_id](#)
- [gctx](#)
- [published](#)

#### Static Public Attributes

- tuple [sql\\_template](#)

#### 10.163.1 Detailed Description

Certificate that has been issued to a child.

Definition at line 937 of file `rpki_engine.py`.

#### 10.163.2 Member Function Documentation

10.163.2.1 `def rpki.rpki_engine.child_cert_obj.__init__(self, gctx = None, child_id = None, ca_detail_id = None, cert = None)`

Initialize a `child_cert_obj`.

Definition at line 951 of file `rpki_engine.py`.

10.163.2.2 `def rpki.rpki_engine.child_cert_obj.ca_detail(self)`

Fetch `ca_detail` object to which this `child_cert` object links.

Definition at line 968 of file `rpki_engine.py`.

### 10.163.2.3 def rpki.rpki\_engine.child\_cert\_obj.child (self)

Fetch child object to which this child\_cert object links.

Definition at line 964 of file rpki\_engine.py.

### 10.163.2.4 def rpki.rpki\_engine.child\_cert\_obj.fetch (cls, gctx= None, child = None, ca\_detail= None, ski = None, unique= False )

Fetch all child\_cert objects matching a particular set of parameters. This is a wrapper to consolidate various queries that would otherwise be inline SQL WHERE expressions. In most cases code calls this indirectly, through methods in other classes.

Definition at line 1049 of file rpki\_engine.py.

### 10.163.2.5 def rpki.rpki\_engine.child\_cert\_obj.published\_callback (self, pdu)

Publication callback: check result and mark published.

Definition at line 1081 of file rpki\_engine.py.

### 10.163.2.6 def rpki.rpki\_engine.child\_cert\_obj.reissue (self, ca\_detail, publisher, resources= None, sia= None)

Reissue an existing child cert, reusing the public key. If the child cert we would generate is identical to the one we already have, we just return the one we already have. If we have to revoke the old child cert when generating the new one, we have to generate a new child\_cert\_obj, so calling code that needs the updated child\_cert\_obj must use the return value from this method.

Definition at line 992 of file rpki\_engine.py.

### 10.163.2.7 def rpki.rpki\_engine.child\_cert\_obj.revoke (self, publisher)

Revoke a child cert.

Definition at line 980 of file rpki\_engine.py.

### 10.163.2.8 def rpki.rpki\_engine.child\_cert\_obj.uri (self, ca)

Return the publication URI for this child\_cert.

Definition at line 976 of file rpki\_engine.py.

### 10.163.2.9 def rpki.rpki\_engine.child\_cert\_obj.uri\_tail (self)

Return the tail (filename) portion of the URI for this child\_cert.

Definition at line 972 of file rpki\_engine.py.

## 10.163.3 Member Data Documentation

### 10.163.3.1 rpki.rpki\_engine.child\_cert\_obj.ca\_detail\_id

Definition at line 958 of file rpki\_engine.py.

### 10.163.3.2 rpki.rpki\_engine.child\_cert\_obj.cert

Definition at line 959 of file rpki\_engine.py.

### 10.163.3.3 rpki.rpki\_engine.child\_cert\_obj.child\_id

Definition at line 957 of file rpki\_engine.py.

### 10.163.3.4 rpki.rpki\_engine.child\_cert\_obj.gctx

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 956 of file rpki\_engine.py.



## 10.163.3.5 rpki.rpki\_engine.child\_cert\_obj.published

Definition at line 960 of file rpki\_engine.py.

## 10.163.3.6 tuple rpki.rpki\_engine.child\_cert\_obj.sql\_template [static]

Initial value:

```
rpki.sql.template(  
    "child_cert",  
    "child_cert_id",  
    ("cert", rpki.x509.X509),  
    "child_id",  
    "ca_detail_id",  
    "ski",  
    ("published", rpki.sundial.datetime))
```

Definition at line 942 of file rpki\_engine.py.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.164 rpki.rpki\_engine.publication\_queue Class Reference

Inherits [object](#)

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [call\\_pubd](#)
- def [publish](#)
- def [withdraw](#)

## Public Attributes

- [handlers](#)
- [msgs](#)
- [repositories](#)
- [uris](#)

## Static Public Attributes

- [replace](#)= True

## Private Member Functions

- [def \\_add](#)

### 10.164.1 Detailed Description

Utility to simplify publication from within rpkiid.

General idea here is to accumulate a collection of objects to be published, in one or more repositories, each potentially with its own completion callback. Eventually we want to publish everything we've accumulated, at which point we need to iterate over the collection and do `repository.call_pubd()` for each repository.

Definition at line 1367 of file `rpki_engine.py`.

### 10.164.2 Member Function Documentation

#### 10.164.2.1 `def rpki.rpki_engine.publication_queue.__init__(self)`

Definition at line 1380 of file `rpki_engine.py`.

#### 10.164.2.2 `def rpki.rpki_engine.publication_queue._add(self, cls, uri, obj, repository handler, withdraw) [private]`

Definition at line 1387 of file `rpki_engine.py`.

#### 10.164.2.3 `def rpki.rpki_engine.publication_queue.call_pubd(self, cb, eb)`

Definition at line 1410 of file `rpki_engine.py`.

#### 10.164.2.4 `def rpki.rpki_engine.publication_queue.publish(self, cls, uri, obj, repository handler=None)`

Definition at line 1404 of file `rpki_engine.py`.

10.164.2.5 `def rpki.rpki_engine.publication_queue.withdraw (self, cls, uri, obj, repository, handler = None)`

Definition at line 1407 of file `rpki_engine.py`.

### 10.164.3 Member Data Documentation

10.164.3.1 `rpki.rpki_engine.publication_queue.handlers`

Definition at line 1383 of file `rpki_engine.py`.

10.164.3.2 `rpki.rpki_engine.publication_queue.msgs`

Definition at line 1382 of file `rpki_engine.py`.

10.164.3.3 `rpki.rpki_engine.publication_queue.replace = True[static]`

Definition at line 1378 of file `rpki_engine.py`.

10.164.3.4 `rpki.rpki_engine.publication_queue.repositories`

Definition at line 1381 of file `rpki_engine.py`.

10.164.3.5 `rpki.rpki_engine.publication_queue.uris`

Definition at line 1385 of file `rpki_engine.py`.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.165 rpki.rpki\_engine.revoked\_cert\_obj Class Reference

Inherits [rpki::sql::sql\\_persistent](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [ca\\_detail](#)
- def [revoke](#)

### Public Attributes

- [ca\\_detail\\_id](#)
- [expires](#)
- [gctx](#)
- [revoked](#)
- [serial](#)

### Static Public Attributes

- tuple [sql\\_template](#)

#### 10.165.1 Detailed Description

Tombstone for a revoked certificate.

Definition at line 1089 of file `rpki_engine.py`.

#### 10.165.2 Member Function Documentation

10.165.2.1 def `rpki.rpki_engine.revoked_cert_obj.__init__(self, gctx=None, serial=None, revoked=None, expires=None, ca_detail_id=None)`

Initialize a `revoked_cert_obj`.

Definition at line 1102 of file `rpki_engine.py`.

### 10.165.2.2 def rpki.rpki\_engine.revoked\_cert\_obj.ca\_detail(self)

Fetch ca\_detail object to which this revoked\_cert\_obj links.

Definition at line 1113 of file rpki\_engine.py.

### 10.165.2.3 def rpki.rpki\_engine.revoked\_cert\_obj.revoke(self, cert, ca\_detail)

Revoke a certificate.

Definition at line 1118 of file rpki\_engine.py.

## 10.165.3 Member Data Documentation

### 10.165.3.1 rpki.rpki\_engine.revoked\_cert\_obj.ca\_detail\_id

Definition at line 1109 of file rpki\_engine.py.

### 10.165.3.2 rpki.rpki\_engine.revoked\_cert\_obj.expires

Definition at line 1108 of file rpki\_engine.py.

### 10.165.3.3 rpki.rpki\_engine.revoked\_cert\_obj.gctx

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 1105 of file rpki\_engine.py.

### 10.165.3.4 rpki.rpki\_engine.revoked\_cert\_obj.revoked

Definition at line 1107 of file rpki\_engine.py.

## 10.165.3.5 rpki.rpki\_engine.revoked\_cert\_obj.serial

Definition at line 1106 of file rpki\_engine.py.

## 10.165.3.6 tuple rpki.rpki\_engine.revoked\_cert\_obj.sql\_template[static]

Initial value:

```
rpki.sql.template(  
    "revoked_cert",  
    "revoked_cert_id",  
    "serial",  
    "ca_detail_id",  
    ("revoked", rpki.sundial.datetime),  
    ("expires", rpki.sundial.datetime))
```

Definition at line 1094 of file rpki\_engine.py.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.166 rpki.rpki\_engine.roa\_obj Class Reference

Inherits [rpki::sql::sql\\_persistent](#)

## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [ca\\_detail](#)
- def [generate](#)
- def [published\\_callback](#)
- def [regenerate](#)
- def [revoke](#)
- def [self](#)
- def [sql\\_delete\\_hook](#)
- def [sql\\_fetch\\_hook](#)
- def [sql\\_insert\\_hook](#)
- def [update](#)
- def [uri](#)
- def [uri\\_tail](#)

### Public Attributes

- [asn](#)
- [gctx](#)
- [ipv4](#)
- [ipv6](#)
- [self\\_id](#)

### Static Public Attributes

- [ca\\_detail\\_id](#)= None
- [cert](#)= None
- [published](#)= None
- [roa](#)= None
- tuple [sql\\_template](#)

#### 10.166.1 Detailed Description

Route Origin Authorization.

Definition at line 1129 of file `rpki_engine.py`.

#### 10.166.2 Member Function Documentation

10.166.2.1 `def rpki.rpki_engine.roa_obj.__init__(self, gctx = None, self_id = None, asn = None, ipv4 = None, ipv6 = None)`

Definition at line 1195 of file `rpki_engine.py`.

10.166.2.2 `def rpki.rpki_engine.roa_obj.ca_detail(self)`

Fetch `ca_detail` object to which this `roa_obj` links.

Definition at line 1155 of file `rpki_engine.py`.

### 10.166.2.3 def rpki.rpki\_engine.roa\_obj.generate(self, publisher)

Generate a ROA.

At present this does not support ROAs with multiple signatures (neither does the current CMS code).

At present we have no way of performing a direct lookup from a desired set of resources to a covering certificate, so we have to search. This could be quite slow if we have a lot of active ca\_detail objects. Punt on the issue for now, revisit if profiling shows this as a hotspot.

Once we have the right covering certificate, we generate the ROA payload, generate a new EE certificate, use the EE certificate to sign the ROA payload, publish the result, then throw away the private key for the EE cert, all per the ROA specification. This implies that generating a lot of ROAs will tend to thrash /dev/random, but there is not much we can do about that.

Definition at line 1238 of file rpki\_engine.py.

### 10.166.2.4 def rpki.rpki\_engine.roa\_obj.published\_callback(self, pdu)

Check publication result.

Definition at line 1304 of file rpki\_engine.py.

### 10.166.2.5 def rpki.rpki\_engine.roa\_obj.regenerate(self, publisher)

Reissue ROA associated with this roa\_obj.

Definition at line 1344 of file rpki\_engine.py.

### 10.166.2.6 def rpki.rpki\_engine.roa\_obj.revoke(self, publisher, regenerate=False, allow\_failure=False)

Withdraw ROA associated with this roa\_obj.

In order to preserve make-before-break properties without



duplicating code, this method also handles generating a replacement ROA when requested.

If `allow_failure` is set, failing to withdraw the ROA will not be considered an error.

Definition at line 1312 of `le rpki_engine.py`.

10.166.2.7 `def rpki.rpki_engine.roa_obj.self(self)`

Fetch self object to which this `roa_obj` links.

Definition at line 1149 of `le rpki_engine.py`.

10.166.2.8 `def rpki.rpki_engine.roa_obj.sql_delete_hooks(self)`

Extra SQL delete actions for `roa_obj` -- handle prefix lists.

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 1189 of `le rpki_engine.py`.

10.166.2.9 `def rpki.rpki_engine.roa_obj.sql_fetch_hook(self)`

Extra SQL fetch actions for `roa_obj` -- handle prefix lists.

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 1161 of `le rpki_engine.py`.

10.166.2.10 `def rpki.rpki_engine.roa_obj.sql_insert_hook(self)`

Extra SQL insert actions for `roa_obj` -- handle prefix lists.

Reimplemented from [rpki.sql.sql\\_persistent](#)

Definition at line 1175 of `le rpki_engine.py`.

### 10.166.2.11 def rpki.rpki\_engine.roa\_obj.update(self, publisher)

Bring this roa\_obj's ROA up to date if necessary.

Definition at line 1208 of file rpki\_engine.py.

### 10.166.2.12 def rpki.rpki\_engine.roa\_obj.uri(self, key= None)

Return the publication URI for this roa\_obj's ROA.

Definition at line 1353 of file rpki\_engine.py.

### 10.166.2.13 def rpki.rpki\_engine.roa\_obj.uri\_tail(self, key= None)

Return the tail (filename portion) of the publication URI for this roa\_obj's ROA.

Definition at line 1359 of file rpki\_engine.py.

## 10.166.3 Member Data Documentation

### 10.166.3.1 rpki.rpki\_engine.roa\_obj.asn

Definition at line 1199 of file rpki\_engine.py.

### 10.166.3.2 rpki.rpki\_engine.roa\_obj.ca\_detail\_id = None [static]

Definition at line 1144 of file rpki\_engine.py.

### 10.166.3.3 rpki.rpki\_engine.roa\_obj.cert = None [static]

Definition at line 1145 of file rpki\_engine.py.

#### 10.166.3.4 rpki.rpki\_engine.roa\_obj.gctx

Reimplemented from [rpki.sql.sql\\_persistent](#)  
Definition at line 1197 of file `rpki_engine.py`.

#### 10.166.3.5 rpki.rpki\_engine.roa\_obj.ipv4

Definition at line 1200 of file `rpki_engine.py`.

#### 10.166.3.6 rpki.rpki\_engine.roa\_obj.ipv6

Definition at line 1201 of file `rpki_engine.py`.

#### 10.166.3.7 rpki.rpki\_engine.roa\_obj.published = None [static]

Definition at line 1147 of file `rpki_engine.py`.

#### 10.166.3.8 rpki.rpki\_engine.roa\_obj.roa = None [static]

Definition at line 1146 of file `rpki_engine.py`.

#### 10.166.3.9 rpki.rpki\_engine.roa\_obj.self\_id

Definition at line 1198 of file `rpki_engine.py`.

#### 10.166.3.10 tuple rpki.rpki\_engine.roa\_obj.sql\_template [static]

Initial value:

```
rpki.sql.template(  
    "roa",  
    "roa_id",  
    "ca_detail_id",
```

```
"self_id",  
"asn",  
("roa", rpki.x509.ROA),  
("cert", rpki.x509.X509),  
("published", rpki.sundial.datetime))
```

Definition at line 1134 of file `rpki_engine.py`.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.167 rpki.rpki\_engine.rpkid\_context Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def build\\_https\\_ta\\_cache](#)
- [def checkpoint](#)
- [def clear\\_https\\_ta\\_cache](#)
- [def cron](#)
- [def cronjob\\_handler](#)
- [def irdb\\_query](#)
- [def irdb\\_query\\_child\\_resources](#)
- [def irdb\\_query\\_roa\\_requests](#)
- [def left\\_right\\_handler](#)
- [def start\\_cron](#)
- [def up\\_down\\_handler](#)

### Public Attributes

- [bpci\\_ta](#)
- [cron\\_keepalive](#)
- [cron\\_period](#)
- [cron\\_timeout](#)
- [cron\\_timer](#)
- [https\\_server\\_host](#)
- [https\\_server\\_port](#)
- [initial\\_delay](#)
- [irbe\\_cert](#)
- [irdb\\_cert](#)

- [irdb\\_url](#)
- [publication\\_kludge\\_base](#)
- [rpkid\\_cert](#)
- [rpkid\\_key](#)
- [sql](#)
- [use\\_internal\\_cron](#)

#### Static Public Attributes

- [https\\_ta\\_cache](#) None  
HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.
- tuple [up\\_down\\_url\\_regexp](#) = re.compile("/up-down/([-A-Z0-9\_]+)/([-A-Z0-9\_+])\$/", re.I)

#### 10.167.1 Detailed Description

A container for various global rpki parameters.

Definition at line 39 of file `rpki_engine.py`.

#### 10.167.2 Member Function Documentation

##### 10.167.2.1 def rpki.rpki\_engine.rpkid\_context.\_\_init\_\_(self, cfg)

Definition at line 44 of file `rpki_engine.py`.

##### 10.167.2.2 def rpki.rpki\_engine.rpkid\_context.build\_https\_ta\_cache(self)

Build dynamic TLS trust anchors.

Definition at line 289 of file `rpki_engine.py`.

##### 10.167.2.3 def rpki.rpki\_engine.rpkid\_context.checkpoint(self)

Record that we were still alive when we got here, by resetting keepalive timer.

Definition at line 200 of file `rpki_engine.py`.

#### 10.167.2.4 def rpki.rpki\_engine.rpkid\_context.clear\_https\_ta\_caches(self)

Clear dynamic TLS trust anchors.

Definition at line 280 of file rpki\_engine.py.

#### 10.167.2.5 def rpki.rpki\_engine.rpkid\_context.cron(self, cb = None)

Periodic tasks.

Definition at line 208 of file rpki\_engine.py.

#### 10.167.2.6 def rpki.rpki\_engine.rpkid\_context.cronjob\_handler(self, query, path, cb)

External trigger for periodic tasks. This is somewhat obsolete now that we have internal timers, but the test framework still uses it.

Definition at line 264 of file rpki\_engine.py.

#### 10.167.2.7 def rpki.rpki\_engine.rpkid\_context.irdb\_query(self, q\_pdu, callback, errback)

Perform an IRDB callback query.

Definition at line 86 of file rpki\_engine.py.

#### 10.167.2.8 def rpki.rpki\_engine.rpkid\_context.irdb\_query\_child\_resources(self, self\_handle, child\_handle, callback, errback)

Ask IRDB about a child's resources.

Definition at line 112 of file rpki\_engine.py.

10.167.2.9 `def rpki.rpki_engine.rpkid_context.irdb_query_roa_requests(self, self_handle callback, errback)`

Ask IRDB about self's ROA requests.

Definition at line 134 of file `rpki_engine.py`.

10.167.2.10 `def rpki.rpki_engine.rpkid_context.left_right_handler(self, query, path, cb)`

Process one left-right PDU.

Definition at line 146 of file `rpki_engine.py`.

10.167.2.11 `def rpki.rpki_engine.rpkid_context.start_cron(self)`

Start clock for rpkid's internal cron process.

Definition at line 73 of file `rpki_engine.py`.

10.167.2.12 `def rpki.rpki_engine.rpkid_context.up_down_handler(self, query, path, cb)`

Process one up-down PDU.

Definition at line 172 of file `rpki_engine.py`.

### 10.167.3 Member Data Documentation

10.167.3.1 `rpki.rpki_engine.rpkid_context.bpkid_ta`

Definition at line 48 of file `rpki_engine.py`.

### 10.167.3.2 rpki.rpki\_engine.rpkid\_context.cron\_keepalive

Definition at line 68 of file rpki\_engine.py.

### 10.167.3.3 rpki.rpki\_engine.rpkid\_context.cron\_period

Definition at line 67 of file rpki\_engine.py.

### 10.167.3.4 rpki.rpki\_engine.rpkid\_context.cron\_timeout

Definition at line 71 of file rpki\_engine.py.

### 10.167.3.5 rpki.rpki\_engine.rpkid\_context.cron\_timer

Definition at line 79 of file rpki\_engine.py.

### 10.167.3.6 rpki.rpki\_engine.rpkid\_context.https\_server\_host

Definition at line 56 of file rpki\_engine.py.

### 10.167.3.7 rpki.rpki\_engine.rpkid\_context.https\_server\_port

Definition at line 57 of file rpki\_engine.py.

### 10.167.3.8 rpki::rpki\_engine.rpkid\_context::https\_ta\_cache = None [static]

HTTPS trust anchor cache, to avoid regenerating it for every TLS connection.

Definition at line 278 of file rpki\_engine.py.



## 10.167.3.9 rpki.rpki\_engine.rpkid\_context.initial\_delay

Definition at line 63 of file rpki\_engine.py.

## 10.167.3.10 rpki.rpki\_engine.rpkid\_context.irbe\_cert

Definition at line 50 of file rpki\_engine.py.

## 10.167.3.11 rpki.rpki\_engine.rpkid\_context.irdb\_cert

Definition at line 49 of file rpki\_engine.py.

## 10.167.3.12 rpki.rpki\_engine.rpkid\_context.irdb\_url

Definition at line 54 of file rpki\_engine.py.

## 10.167.3.13 rpki.rpki\_engine.rpkid\_context.publication\_kludge\_base

Definition at line 59 of file rpki\_engine.py.

## 10.167.3.14 rpki.rpki\_engine.rpkid\_context.rpkid\_cert

Definition at line 51 of file rpki\_engine.py.

## 10.167.3.15 rpki.rpki\_engine.rpkid\_context.rpkid\_key

Definition at line 52 of file rpki\_engine.py.

## 10.167.3.16 rpki.rpki\_engine.rpkid\_context.sql

Definition at line 46 of file `rpki_engine.py`.

```
10.167.3.17 tuple rpki.rpki_engine.rpkid_context.up_down_url_regexp =  
            re.compile("/up-down/([-A-Z0-9_]+)/([-A-Z0-9_]+)$", re.I)  
            [static]
```

Definition at line 170 of file `rpki_engine.py`.

## 10.167.3.18 rpki.rpki\_engine.rpkid\_context.use\_internal\_cron

Definition at line 61 of file `rpki_engine.py`.

The documentation for this class was generated from the following file:

- [rpki\\_engine.py \(2934\)](#)

## 10.168 rpki.sql.session Class Reference

Inherits [object](#)

## Public Member Functions

- def `__init__`
- def [assert\\_pristine](#)
- def [cache\\_clear](#)
- def [close](#)
- def [connect](#)
- def [execute](#)
- def [executemany](#)
- def [fetchall](#)
- def [lastrowid](#)
- def [ping](#)
- def [sweep](#)

### Public Attributes

- [cache](#)
- [cur](#)
- [database](#)
- [db](#)
- [dirty](#)
- [password](#)
- [username](#)

### Private Member Functions

- [def \\_wrap\\_execute](#)

### Static Private Attributes

- [\\_exceptions\\_enabled](#)False

#### 10.168.1 Detailed Description

SQL session layer.

Definition at line 50 of file sql.py.

#### 10.168.2 Member Function Documentation

##### 10.168.2.1 def rpki.sql.session.\_\_init\_\_(self, cfg)

Definition at line 57 of file sql.py.

##### 10.168.2.2 def rpki.sql.session.\_wrap\_execute(self, func, query, args) [private]

Definition at line 88 of file sql.py.

### 10.168.2.3 def rpki.sql.session.assert\_pristine(self)

Assert that there are no dirty objects in the cache.

Definition at line 112 of file sql.py.

### 10.168.2.4 def rpki.sql.session.cache\_clear(self)

Clear the object cache.

Definition at line 108 of file sql.py.

### 10.168.2.5 def rpki.sql.session.close(self)

Definition at line 77 of file sql.py.

### 10.168.2.6 def rpki.sql.session.connect(self)

Definition at line 72 of file sql.py.

### 10.168.2.7 def rpki.sql.session.execute(self, query, args= None)

Definition at line 96 of file sql.py.

### 10.168.2.8 def rpki.sql.session.executemany(self, query, args)

Definition at line 99 of file sql.py.

### 10.168.2.9 def rpki.sql.session.fetchall(self)

Definition at line 102 of file sql.py.

10.168.2.10 `def rpki.sql.session.lastrowids(self)`

Definition at line 105 of `le sql.py`.

10.168.2.11 `def rpki.sql.session.pings(self)`

Definition at line 85 of `le sql.py`.

10.168.2.12 `def rpki.sql.session.sweep(self)`

Write any dirty objects out to SQL.

Definition at line 116 of `le sql.py`.

10.168.3 Member Data Documentation

10.168.3.1 `rpki.sql.session._exceptions_enabled = False`  
[static, private]

Definition at line 55 of `le sql.py`.

10.168.3.2 `rpki.sql.session.cache`

Definition at line 67 of `le sql.py`.

10.168.3.3 `rpki.sql.session.cur`

Definition at line 74 of `le sql.py`.

10.168.3.4 `rpki.sql.session.database`

Definition at line 64 of file sql.py.

#### 10.168.3.5 rpki.sql.session.db

Definition at line 73 of file sql.py.

#### 10.168.3.6 rpki.sql.session.dirty

Definition at line 68 of file sql.py.

#### 10.168.3.7 rpki.sql.session.password

Definition at line 65 of file sql.py.

#### 10.168.3.8 rpki.sql.session.username

Definition at line 63 of file sql.py.

The documentation for this class was generated from the following file:

- [sql.py \(2895\)](#)

### 10.169 rpki.sql.sql\_persistent Class Reference

Inherits [object](#)

Inherited by [rpki.left\\_right.data\\_engine](#), [rpki.publication.control\\_engine](#), [rpki.rpki\\_engine.ca\\_detail\\_obj](#), [rpki.rpki\\_engine.ca\\_obj](#), [rpki.rpki\\_engine.child\\_cert\\_obj](#), [rpki.rpki\\_engine.revoked\\_cert\\_obj](#), and [rpki.rpki\\_engine.roa\\_obj](#)

Public Member Functions

- def [sql\\_decode](#)
- def [sql\\_delete](#)
- def [sql\\_delete\\_hook](#)
- def [sql\\_encode](#)

- def [sql\\_fetch](#)
- def [sql\\_fetch\\_all](#)
- def [sql\\_fetch\\_hook](#)
- def [sql\\_fetch\\_where](#)
- def [sql\\_fetch\\_where1](#)
- def [sql\\_init](#)
- def [sql\\_insert\\_hook](#)
- def [sql\\_is\\_dirty](#)
- def [sql\\_mark\\_clean](#)
- def [sql\\_mark\\_deleted](#)
- def [sql\\_mark\\_dirty](#)
- def [sql\\_store](#)
- def [sql\\_update\\_hook](#)

#### Public Attributes

- [gctx](#)

#### Static Public Attributes

- [sql\\_debug](#)= False  
Enable logging of SQL actions.
- [sql\\_deleted](#)= False  
Whether our cached copy of this [object](#) has been deleted.
- [sql\\_in\\_db](#)= False  
Whether this [object](#) is already in SQL or not.

#### 10.169.1 Detailed Description

Mixin for persistent class that needs to be stored in SQL.

Definition at line 152 of file `sql.py`.

#### 10.169.2 Member Function Documentation

10.169.2.1 `def rpki.sql.sql_persistent.sql_decode(self, vals)`

Initialize an object with values returned by `self.sql_fetch()`.  
 This is a default version that assumes a one-to-one mapping  
 between column names in SQL and attribute names in Python. If you  
 need something fancier, override this.

Reimplemented in [rpki.rpki\\_engine.ca\\_detail\\_obj](#)

Definition at line 322 of `le sql.py`.

10.169.2.2 `def rpki.sql.sql_persistent.sql_delete(self)`

Delete this object from SQL.

Definition at line 293 of `le sql.py`.

10.169.2.3 `def rpki.sql.sql_persistent.sql_delete_hook(self)`

Customization hook.

Reimplemented in [rpki.rpki\\_engine.roa\\_obj](#)

Definition at line 348 of `le sql.py`.

10.169.2.4 `def rpki.sql.sql_persistent.sql_encode(self)`

Convert object attributes into a dict for use with canned SQL  
 queries. This is a default version that assumes a one-to-one  
 mapping between column names in SQL and attribute names in Python.  
 If you need something fancier, override this.

Definition at line 309 of `le sql.py`.

10.169.2.5 `def rpki.sql.sql_persistent.sql_fetch(self, gctx, id)`

Fetch one object from SQL, based on its primary key.

Since in this one case we know that the primary index is also the  
 cache key, we check for a cache hit directly in the hope of  
 bypassing the SQL lookup entirely.



This method is usually called via a one-line class-specific wrapper. As a convenience, we also accept an id of None, and just return None in this case.

Definition at line 173 of file sql.py.

10.169.2.6 def rpki.sql.sql\_persistent.sql\_fetch\_all(s, gctx)

Fetch all objects of this type from SQL.

Definition at line 211 of file sql.py.

10.169.2.7 def rpki.sql.sql\_persistent.sql\_fetch\_hooks(self)

Customization hook.

Reimplemented in [rpki.rpki\\_engine.roa\\_obj](#)

Definition at line 335 of file sql.py.

10.169.2.8 def rpki.sql.sql\_persistent.sql\_fetch\_where(s, gctx, where, args=None, also\_from=None)

Fetch objects of this type matching an arbitrary SQL WHERE expression.

Definition at line 216 of file sql.py.

10.169.2.9 def rpki.sql.sql\_persistent.sql\_fetch\_where(s, gctx, where, args=None, also\_from=None)

Fetch one object from SQL, based on an arbitrary SQL WHERE expression.

Definition at line 196 of file sql.py.

10.169.2.10 `def rpki.sql.sql_persistent.sql_init(cls, gctx, row, key)`

Initialize one Python object from the result of a SQL query.

Definition at line 243 of file `sql.py`.

10.169.2.11 `def rpki.sql.sql_persistent.sql_insert_hooks(self)`

Customization hook.

Reimplemented in [rpki.rpki\\_engine.roa\\_obj](#)

Definition at line 339 of file `sql.py`.

10.169.2.12 `def rpki.sql.sql_persistent.sql_is_dirty(self)`

Query whether this object needs to be written back to SQL.

Definition at line 263 of file `sql.py`.

10.169.2.13 `def rpki.sql.sql_persistent.sql_mark_clean(self)`

Mark this object as not needing to be written back to SQL.

Definition at line 259 of file `sql.py`.

10.169.2.14 `def rpki.sql.sql_persistent.sql_mark_deleted(self)`

Mark this object as needing to be deleted in SQL.

Definition at line 267 of file `sql.py`.

10.169.2.15 `def rpki.sql.sql_persistent.sql_mark_dirty(self)`

Mark this object as needing to be written back to SQL.

Definition at line 255 of `le sql.py`.

10.169.2.16 `def rpki.sql.sql_persistent.sql_store(self)`

Store this object to SQL.

Definition at line 271 of `le sql.py`.

10.169.2.17 `def rpki.sql.sql_persistent.sql_update_hooks(self)`

Customization hook.

Definition at line 343 of `le sql.py`.

### 10.169.3 Member Data Documentation

10.169.3.1 `rpki.sql.sql_persistent.gctx`

Reimplemented in [rpki.rpki\\_engine.ca\\_obj](#) [rpki.rpki\\_engine.ca\\_detail\\_obj](#) [rpki.rpki\\_engine.child\\_cert\\_obj](#) [rpki.rpki\\_engine.revoked\\_cert\\_obj](#) and [rpki.rpki\\_engine.roa\\_obj](#)

Definition at line 248 of `le sql.py`.

10.169.3.2 `rpki::sql.sql_persistent::sql_debug = False[static]`

Enable logging of SQL actions.

Definition at line 170 of `le sql.py`.

10.169.3.3 rpki::sql.sql\_persistent::sql\_deleted = False[static]

Whether our cached copy of this [object](#) has been deleted.

Definition at line 165 of file sql.py.

10.169.3.4 rpki::sql.sql\_persistent::sql\_in\_db = False[static]

Whether this [object](#) is already in SQL or not.

Definition at line 160 of file sql.py.

The documentation for this class was generated from the following file:

- [sql.py \(2895\)](#)

## 10.170 rpki.sql.template Class Reference

Inherits [object](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)

### Public Attributes

- [columns](#)
- [delete](#)
- [index](#)
- [insert](#)
- [map](#)
- [select](#)
- [table](#)
- [update](#)

### 10.170.1 Detailed Description

SQL template generator.

Definition at line 128 of file sql.py.

## 10.170.2 Member Function Documentation

### 10.170.2.1 def rpki.sql.template.\_\_init\_\_(self, table\_name, index\_column, data\_column)

Build a SQL template.

Definition at line 133 of file sql.py.

## 10.170.3 Member Data Documentation

### 10.170.3.1 rpki.sql.template.columns

Definition at line 140 of file sql.py.

### 10.170.3.2 rpki.sql.template.delete

Definition at line 150 of file sql.py.

### 10.170.3.3 rpki.sql.template.index

Definition at line 139 of file sql.py.

### 10.170.3.4 rpki.sql.template.insert

Definition at line 143 of file sql.py.

### 10.170.3.5 rpki.sql.template.map

Definition at line 141 of file sql.py.

## 10.170.3.6 rpki.sql.template.select

Definition at line 142 of file sql.py.

## 10.170.3.7 rpki.sql.template.table

Definition at line 138 of file sql.py.

## 10.170.3.8 rpki.sql.template.update

Definition at line 146 of file sql.py.

The documentation for this class was generated from the following file:

- [sql.py \(2895\)](#)

## 10.171 rpki.sundial.datetime Class Reference

Inherits [pydatetime::datetime](#)

## Public Member Functions

- [def \\_\\_add\\_\\_](#)
- [def \\_\\_radd\\_\\_](#)
- [def \\_\\_rsub\\_\\_](#)
- [def \\_\\_str\\_\\_](#)
- [def \\_\\_sub\\_\\_](#)
- [def earlier](#)
- [def from\\_sql](#)
- [def fromASN1tuple](#)
- [def fromdatetime](#)
- [def fromGeneralizedTime](#)
- [def fromUTCtime](#)
- [def fromXMLtime](#)
- [def later](#)
- [def to\\_sql](#)
- [def toASN1tuple](#)
- [def toGeneralizedTime](#)

- def [totimestamp](#)
- def [toUTCTime](#)
- def [toXMLtime](#)

#### Static Public Attributes

- tuple [PKIX\\_threshold](#)= pydatetime.datetime(2050, 1, 1)  
Threshold specified in RFC 3280 for switchover from UTCTime to GeneralizedTime.

#### 10.171.1 Detailed Description

RPKI extensions to standard datetime.datetime class. All work here is in UTC, so we use naive datetime objects.

Definition at line 54 of file sundial.py.

#### 10.171.2 Member Function Documentation

##### 10.171.2.1 def rpki.sundial.datetime.\_\_add\_\_(x, y)

Definition at line 163 of file sundial.py.

##### 10.171.2.2 def rpki.sundial.datetime.\_\_radd\_\_(x, y)

Definition at line 164 of file sundial.py.

##### 10.171.2.3 def rpki.sundial.datetime.\_\_rsub\_\_(x, y)

Definition at line 165 of file sundial.py.

##### 10.171.2.4 def rpki.sundial.datetime.\_\_str\_\_(self)

Definition at line 124 of file sundial.py.

10.171.2.5 def rpki.sundial.datetime.\_\_sub\_\_(x, y)

Definition at line 166 of file sundial.py.

10.171.2.6 def rpki.sundial.datetime.earlier(self, other)

Return the earlier of two timestamps.

Definition at line 159 of file sundial.py.

10.171.2.7 def rpki.sundial.datetime.from\_sql(cls, x)

Convert from SQL storage format.

Definition at line 136 of file sundial.py.

10.171.2.8 def rpki.sundial.datetime.fromASN1tuple(cls, x)

Convert from ASN.1 tuple representation.

Definition at line 86 of file sundial.py.

10.171.2.9 def rpki.sundial.datetime.fromdatetime(cls, x)

Convert a datetime.datetime object into this subclass. This is whacky due to the weird constructors for datetime.

Definition at line 128 of file sundial.py.

10.171.2.10 def rpki.sundial.datetime.fromGeneralizedTime(cls, x)

Convert from ASN.1 GeneralizedTime.

Definition at line 77 of file sundial.py.



10.171.2.11 def rpki.sundial.datetime.fromUTCTime(cls, x)

Convert from ASN.1 UTCTime.

Definition at line 68 of file sundial.py.

10.171.2.12 def rpki.sundial.datetime.fromXMLtime(cls, x)

Convert from XML time representation.

Definition at line 111 of file sundial.py.

10.171.2.13 def rpki.sundial.datetime.later(self, other)

Return the later of two timestamps.

Definition at line 155 of file sundial.py.

10.171.2.14 def rpki.sundial.datetime.to\_sql(self)

Convert to SQL storage format.

There's something whacky going on in the MySQLdb module, it throws range errors when storing a derived type into a DATETIME column. Investigate some day, but for now brute force this by copying the relevant fields into a datetime.datetime for MySQLdb's consumption.

Definition at line 140 of file sundial.py.

10.171.2.15 def rpki.sundial.datetime.toASN1tuple(self)

Convert to ASN.1 tuple representation.

Definition at line 101 of file sundial.py.

#### 10.171.2.16 def rpki.sundial.datetime.toGeneralizedTime(self)

Convert to ASN.1 GeneralizedTime.

Definition at line 81 of file sundial.py.

#### 10.171.2.17 def rpki.sundial.datetime.timestamp(self)

Convert to seconds from epoch (like time.time()). Conversion method is a bit silly, but avoids time module timezone whackiness.

Definition at line 60 of file sundial.py.

#### 10.171.2.18 def rpki.sundial.datetime.toUTCTime(self)

Convert to ASN.1 UTCTime.

Definition at line 72 of file sundial.py.

#### 10.171.2.19 def rpki.sundial.datetime.toXMLtime(self)

Convert to XML time representation.

Definition at line 120 of file sundial.py.

### 10.171.3 Member Data Documentation

#### 10.171.3.1 rpki.sundial.datetime.PKIX\_threshold = pydatetime.datetime(2050, 1, 1) [static]

Threshold specified in RFC 3280 for switchover from UTCTime to GeneralizedTime.

Definition at line 99 of file sundial.py.

The documentation for this class was generated from the following file:

- [sundial.py \(2785\)](#)

## 10.172 rpki.sundial.timedelta Class Reference

Inherits [pydatetime::timedelta](#)

### Public Member Functions

- def [\\_\\_abs\\_\\_](#)
- def [\\_\\_add\\_\\_](#)
- def [\\_\\_div\\_\\_](#)
- def [\\_\\_oordiv\\_\\_](#)
- def [\\_\\_mul\\_\\_](#)
- def [\\_\\_neg\\_\\_](#)
- def [\\_\\_pos\\_\\_](#)
- def [\\_\\_radd\\_\\_](#)
- def [\\_\\_rdiv\\_\\_](#)
- def [\\_\\_r oordiv\\_\\_](#)
- def [\\_\\_rmul\\_\\_](#)
- def [\\_\\_rsub\\_\\_](#)
- def [\\_\\_sub\\_\\_](#)
- def [convert\\_to\\_seconds](#)
- def [fromtimedelta](#)
- def [parse](#)

### Static Public Attributes

- tuple [regexp](#)  
Hideously ugly regular expression to parse the complex text form.

#### 10.172.1 Detailed Description

Timedelta with text parsing. This accepts two input formats:

- A simple integer, indicating a number of seconds.
- A string of the form "wD xH yM zS" where w, x, y, and z are integers and D, H, M, and S indicate days, hours, minutes, and seconds. All of the fields are optional, but at least one must be specified. Eg, "3D4H" means "three days plus four hours".

Definition at line 168 of file sundial.py.

### 10.172.2 Member Function Documentation

#### 10.172.2.1 def rpkg.sundial.timedelta.\_\_abs\_\_(x)

Definition at line 218 of file sundial.py.

#### 10.172.2.2 def rpkg.sundial.timedelta.\_\_add\_\_(x, y)

Definition at line 219 of file sundial.py.

#### 10.172.2.3 def rpkg.sundial.timedelta.\_\_div\_\_(x, y)

Definition at line 220 of file sundial.py.

#### 10.172.2.4 def rpkg.sundial.timedelta.\_\_floordiv\_\_(x, y)

Definition at line 221 of file sundial.py.

#### 10.172.2.5 def rpkg.sundial.timedelta.\_\_mul\_\_(x, y)

Definition at line 222 of file sundial.py.

#### 10.172.2.6 def rpkg.sundial.timedelta.\_\_neg\_\_(x)

Definition at line 223 of file sundial.py.

#### 10.172.2.7 def rpkg.sundial.timedelta.\_\_pos\_\_(x)

Definition at line 224 of file sundial.py.

10.172.2.8 def rpkgi.sundial.timedelta.\_\_radd\_\_(x, y)

Definition at line 225 of file sundial.py.

10.172.2.9 def rpkgi.sundial.timedelta.\_\_rdiv\_\_(x, y)

Definition at line 226 of file sundial.py.

10.172.2.10 def rpkgi.sundial.timedelta.\_\_rmoddiv\_\_(x, y)

Definition at line 227 of file sundial.py.

10.172.2.11 def rpkgi.sundial.timedelta.\_\_rmul\_\_(x, y)

Definition at line 228 of file sundial.py.

10.172.2.12 def rpkgi.sundial.timedelta.\_\_rsub\_\_(x, y)

Definition at line 229 of file sundial.py.

10.172.2.13 def rpkgi.sundial.timedelta.\_\_sub\_\_(x, y)

Definition at line 230 of file sundial.py.

10.172.2.14 def rpkgi.sundial.timedelta.convert\_to\_seconds(self)

Convert a timedelta interval to seconds.

Definition at line 209 of file sundial.py.

10.172.2.15 def rpkgi.sundial.timedelta.fromtimedelta (cls, x)

Convert a datetime.timedelta object into this subclass.

Definition at line 214 of file sundial.py.

10.172.2.16 def rpkgi.sundial.timedelta.parse (cls, arg)

Parse text into a timedelta object.

Definition at line 194 of file sundial.py.

### 10.172.3 Member Data Documentation

10.172.3.1 rpkgi.sundial.timedelta::regexp [static]

Initial value:

```
re.compile("\s* ".join(("^",
                        "(?: (?P<days> \d+ ) D )?",
                        "(?: (?P<hours> \d+ ) H )?",
                        "(?: (?P<minutes> \d+ ) M )?",
                        "(?: (?P<seconds> \d+ ) S )?",
                        "$"),
                    re.I))
```

Hideously ugly regular expression to parse the complex text form. Tags are intended for use with re.MatchObject.groupdict() and map directly to the keywords expected by the [timedelta](#) constructor.

Definition at line 185 of file sundial.py.

The documentation for this class was generated from the following file:

- [sundial.py \(2785\)](#)

## 10.173 rpkgi.up\_down.base\_elt Class Reference

Inherits [object](#)

Inherited by [rpki.up\\_down.certificate\\_elt](#) [rpki.up\\_down.class\\_elt](#) [rpki.up\\_down.class\\_response\\_syntax](#) [rpki.up\\_down.error\\_response\\_pdu](#) [rpki.up\\_down.issue\\_pdu](#) [rpki.up\\_down.list\\_pdu](#) [rpki.up\\_down.message\\_pdu](#) and [rpki.up\\_down.revoke\\_syntax](#)

## Public Member Functions

- def [check\\_response](#)
- def [endElement](#)
- def [make\\_b64elt](#)
- def [make\\_elt](#)
- def [serve\\_pdu](#)
- def [startElement](#)

## 10.173.1 Detailed Description

Generic PDU object.

Virtual class, just provides some default methods.

Definition at line 43 of `le up_down.py`.

## 10.173.2 Member Function Documentation

## 10.173.2.1 def rpki.up\_down.base\_elt.check\_response(self)

Placeholder for response checking.

Reimplemented in [rpki.up\\_down.issue\\_response\\_pdu](#) and [rpki.up\\_down.error\\_response\\_pdu](#)

Definition at line 91 of `le up_down.py`.

## 10.173.2.2 def rpki.up\_down.base\_elt.endElement(self, stack, name, text)

Ignore endElement() if there's no specific handler.

If we don't need to do anything else, just pop the stack.

Reimplemented in [rpki.up\\_down.certificate\\_elt](#), [rpki.up\\_down.class\\_elt](#), [rpki.up\\_down.issue\\_pdu](#) and [rpki.up\\_down.error\\_response\\_pdu](#)

Definition at line 59 of `le up_down.py`.

10.173.2.3 `def rpki.up_down.base_elt.make_b64_elt(self, elt, name, value=None)`

Construct a sub-element with Base64 text content.

Definition at line 78 of `le up_down.py`.

10.173.2.4 `def rpki.up_down.base_elt.make_elt(self, name, attrs)`

Construct a element, copying over a set of attributes.

Definition at line 67 of `le up_down.py`.

10.173.2.5 `def rpki.up_down.base_elt.serve_pdu(self, q_msg, r_msg, child, callback, errback)`

Default PDU handler to catch unexpected types.

Reimplemented in [rpki.up\\_down.list\\_pdu](#), [rpki.up\\_down.issue\\_pdu](#), [rpki.up\\_down.revoke\\_pdu](#), [rootd.list\\_pdu](#), [rootd.issue\\_pdu](#) and [rootd.revoke\\_pdu](#)

Definition at line 87 of `le up_down.py`.

10.173.2.6 `def rpki.up_down.base_elt.startElements(self, stack, name, attrs)`

Ignore `startElement()` if there's no specific handler.

Some elements have no attributes and we only care about their text content.

Reimplemented in [rpki.up\\_down.certificate\\_elt](#), [rpki.up\\_down.class\\_elt](#), [rpki.up\\_down.class\\_response\\_syntax](#), [rpki.up\\_down.issue\\_pdu](#), [rpki.up\\_down.revoke\\_syntax](#) and [rpki.up\\_down.message\\_pdu](#)

Definition at line 50 of `le up_down.py`.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)



## 10.174 rpki.up\_down.certificate\_elt Class Reference

Inherits [rpki.up\\_down.base\\_elt](#)

### Public Member Functions

- def [endElement](#)
- def [startElement](#)
- def [toXML](#)

### Public Attributes

- [cert](#)
- [cert\\_url](#)
- [req\\_resource\\_set\\_as](#)
- [req\\_resource\\_set\\_ipv4](#)
- [req\\_resource\\_set\\_ipv6](#)

#### 10.174.1 Detailed Description

Up-Down protocol representation of an issued certificate.

Definition at line 128 of file `up_down.py`.

#### 10.174.2 Member Function Documentation

##### 10.174.2.1 def rpki.up\_down.certificate\_elt.endElement (self, stack, name, text)

Handle text content of a `<certificate/>` element.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 143 of file `up_down.py`.

##### 10.174.2.2 def rpki.up\_down.certificate\_elt.startElement (self, stack, name, attrs)

Handle attributes of `<certificate/>` element.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 133 of file up\_down.py.

10.174.2.3 def rpki.up\_down.certificate\_elt.toXML (self)

Generate a <certificate/> element.

Definition at line 151 of file up\_down.py.

10.174.3 Member Data Documentation

10.174.3.1 rpki.up\_down.certificate\_elt.cert

Definition at line 148 of file up\_down.py.

10.174.3.2 rpki.up\_down.certificate\_elt.cert\_url

Definition at line 138 of file up\_down.py.

10.174.3.3 rpki.up\_down.certificate\_elt.req\_resource\_set\_as

Definition at line 139 of file up\_down.py.

10.174.3.4 rpki.up\_down.certificate\_elt.req\_resource\_set\_ipv4

Definition at line 140 of file up\_down.py.

10.174.3.5 rpki.up\_down.certificate\_elt.req\_resource\_set\_ipv6

Definition at line 141 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.175 rpki.up\_down.class\_elt Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def endElement](#)
- [def from\\_resource\\_bag](#)
- [def startElement](#)
- [def to\\_resource\\_bag](#)
- [def toXML](#)

### Public Attributes

- [cert\\_url](#)
- [certs](#)
- [class\\_name](#)
- [resource\\_set\\_as](#)
- [resource\\_set\\_ipv4](#)
- [resource\\_set\\_ipv6](#)
- [resource\\_set\\_notafter](#)
- [suggested\\_sia\\_head](#)

### Static Public Attributes

- [issuer](#)= None

#### 10.175.1 Detailed Description

Up-Down protocol representation of a resource class.

Definition at line 160 of file `up_down.py`.

## 10.175.2 Member Function Documentation

### 10.175.2.1 def rpki.up\_down.class\_elt.\_\_init\_\_(self)

Initialize class\_elt.

Definition at line 167 of file up\_down.py.

### 10.175.2.2 def rpki.up\_down.class\_elt.endElements(self, stack, name, text)

Handle <class/> elements and their children.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 191 of file up\_down.py.

### 10.175.2.3 def rpki.up\_down.class\_elt.from\_resource\_bag(self, bag)

Set resources of this class element from a resource\_bag.

Definition at line 222 of file up\_down.py.

### 10.175.2.4 def rpki.up\_down.class\_elt.startElements(self, stack, name, attrs)

Handle <class/> elements and their children.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 172 of file up\_down.py.

### 10.175.2.5 def rpki.up\_down.class\_elt.to\_resource\_bag(self)

Build a resource\_bag from from this <class/> element.

Definition at line 213 of file up\_down.py.

### 10.175.2.6 def rpki.up\_down.class\_elt.toXML (self)

Generate a <class/> element.

Definition at line 201 of file up\_down.py.

## 10.175.3 Member Data Documentation

### 10.175.3.1 rpki.up\_down.class\_elt.cert\_url

Definition at line 184 of file up\_down.py.

### 10.175.3.2 rpki.up\_down.class\_elt.certs

Definition at line 170 of file up\_down.py.

### 10.175.3.3 rpki.up\_down.class\_elt.class\_name

Definition at line 183 of file up\_down.py.

### 10.175.3.4 rpki.up\_down.class\_elt.issuer = None[static]

Definition at line 165 of file up\_down.py.

### 10.175.3.5 rpki.up\_down.class\_elt.resource\_set\_as

Definition at line 186 of file up\_down.py.

### 10.175.3.6 rpki.up\_down.class\_elt.resource\_set\_ipv4

Definition at line 187 of file up\_down.py.

## 10.175.3.7 rpki.up\_down.class\_elt.resource\_set\_ipv6

Definition at line 188 of file up\_down.py.

## 10.175.3.8 rpki.up\_down.class\_elt.resource\_set\_notafter

Definition at line 189 of file up\_down.py.

## 10.175.3.9 rpki.up\_down.class\_elt.suggested\_sia\_head

Definition at line 185 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.176 rpki.up\_down.class\_response\_syntax Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

Inherited by [rpki.up\\_down.issue\\_response\\_pdu](#) and [rpki.up\\_down.list\\_response\\_pdu](#)

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def startElement](#)
- [def toXML](#)

## Public Attributes

- [classes](#)

## 10.176.1 Detailed Description

Syntax for Up-Down protocol "list\_response" and "issue\_response" PDUs.

Definition at line 284 of file up\_down.py.

## 10.176.2 Member Function Documentation

### 10.176.2.1 def rpki.up\_down.class\_response\_syntax.\_\_init\_\_(self)

Initialize class\_response\_syntax.

Definition at line 289 of file up\_down.py.

### 10.176.2.2 def rpki.up\_down.class\_response\_syntax.startElement(self, stack, name, attrs)

Handle "list\_response" and "issue\_response" PDUs.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 296 of file up\_down.py.

### 10.176.2.3 def rpki.up\_down.class\_response\_syntax.toXMLs(self)

Generate payload of "list\_response" and "issue\_response" PDUs.

Definition at line 306 of file up\_down.py.

## 10.176.3 Member Data Documentation

### 10.176.3.1 rpki.up\_down.class\_response\_syntax.classes

Definition at line 294 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.177 rpki.up\_down.cms\_msg Class Reference

Inherits [rpki::x509::XML\\_CMS\\_object](#)

Inherited by [rootd.cms\\_msg](#)

### Static Public Attributes

- `stringencoding= "UTF-8"`
- `saxify= sax_handler.saxify`
- `schema= rpki.relaxng.up_down`

#### 10.177.1 Detailed Description

Class to hold a CMS-signed up-down PDU.

Definition at line 682 of file `up_down.py`.

#### 10.177.2 Member Data Documentation

10.177.2.1 `string rpki.up_down.cms_msg.encoding = "UTF-8" [static]`

Definition at line 687 of file `up_down.py`.

10.177.2.2 `rpki.up_down.cms_msg.saxify = sax_handler.saxify [static]`

Reimplemented in `mootd.cms_msg`

Definition at line 689 of file `up_down.py`.

10.177.2.3 `rpki.up_down.cms_msg.schema = rpki.relaxng.up_down [static]`

Definition at line 688 of file `up_down.py`.

The documentation for this class was generated from the following file:

- `up_down.py (2935)`

### 10.178 rpki.up\_down.error\_response\_pdu Class Reference

Inherits `rpki::up_down::base_elt`



## Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [check\\_response](#)
- def [endElement](#)
- def [toXML](#)

## Public Attributes

- [description](#)
- [status](#)

## Static Public Attributes

- dictionary [codes](#)
- dictionary [exceptions](#)

## 10.178.1 Detailed Description

Up-Down protocol "error\_response" PDU.

Definition at line 502 of file up\_down.py.

## 10.178.2 Member Function Documentation

10.178.2.1 def rpki.up\_down.error\_response\_pdu.\_\_init\_\_(self, exception=None)

Initialize an error\_response PDU from an exception object.

Definition at line 521 of file up\_down.py.

10.178.2.2 def rpki.up\_down.error\_response\_pdu.check\_response(self)

Handle an error response. For now, just raise an exception, perhaps figure out something more clever to do later.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 561 of file up\_down.py.

10.178.2.3 def rpki.up\_down.error\_response\_pdu.endElements(~~self~~, stack  
name, text)

Handle "error\_response" PDU.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 530 of file up\_down.py.

10.178.2.4 def rpki.up\_down.error\_response\_pdu.toXML(~~self~~)

Generate payload of "error\_response" PDU.

Definition at line 546 of file up\_down.py.

### 10.178.3 Member Data Documentation

10.178.3.1 dictionary rpki.up\_down.error\_response\_pdu.codes[static]

Initial value:

```
{
    1101 : "Already processing request",
    1102 : "Version number error",
    1103 : "Unrecognised request type",
    1201 : "Request - no such resource class",
    1202 : "Request - no resources allocated in resource class",
    1203 : "Request - badly formed certificate request",
    1301 : "Revoke - no such resource class",
    1302 : "Revoke - no such key",
    2001 : "Internal Server Error - Request not performed" }
```

Definition at line 507 of file up\_down.py.

10.178.3.2 rpki.up\_down.error\_response\_pdu.description

Definition at line 528 of file up\_down.py.

10.178.3.3 dictionary rpki.up\_down.error\_response\_pdu.exceptions  
[static]

Initial value:

```
{  
    rpki.exceptions.NoActiveCA : 1202 }  
}
```

Definition at line 518 of file up\_down.py.

#### 10.178.3.4 rpki.up\_down.error\_response\_pdu.status

Definition at line 527 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

### 10.179 rpki.up\_down.issue\_pdu Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

Inherited by [rootd.issue\\_pdu](#)

#### Public Member Functions

- def [endElement](#)
- def [query](#)
- def [serve\\_pdu](#)
- def [startElement](#)
- def [toXML](#)

#### Public Attributes

- [class\\_name](#)
- [pkcs10](#)
- [req\\_resource\\_set\\_as](#)
- [req\\_resource\\_set\\_ipv4](#)
- [req\\_resource\\_set\\_ipv6](#)

#### 10.179.1 Detailed Description

Up-Down protocol "issue" PDU.

Definition at line 316 of file up\_down.py.

## 10.179.2 Member Function Documentation

10.179.2.1 `def rpkι.up_down.issue_pdu.endElements(εlf, stack, name, text)`

Handle "issue" PDU.

Reimplemented from [rpkι.up\\_down.base\\_elt](#)

Definition at line 331 of `le up_down.py`.

10.179.2.2 `def rpkι.up_down.issue_pdu.query(εls, parent, ca, ca_detail, callback, errback)`

Send an "issue" request to parent associated with ca.

Definition at line 417 of `le up_down.py`.

10.179.2.3 `def rpkι.up_down.issue_pdu.serve_pdu(εlf, q_msg, r_msg, child, callback, errback)`

Serve one issue request PDU.

Reimplemented from [rpkι.up\\_down.base\\_elt](#)

Reimplemented in [mootd.issue\\_pdu](#)

Definition at line 348 of `le up_down.py`.

10.179.2.4 `def rpkι.up_down.issue_pdu.startElements(εlf, stack, name, attrs)`

Handle "issue" PDU.

Reimplemented from [rpkι.up\\_down.base\\_elt](#)

Definition at line 321 of `le up_down.py`.

### 10.179.2.5 def rpki.up\_down.issue\_pdu.toXML (§self)

Generate payload of "issue" PDU.

Definition at line 339 of file up\_down.py.

## 10.179.3 Member Data Documentation

### 10.179.3.1 rpki.up\_down.issue\_pdu.class\_name

Definition at line 326 of file up\_down.py.

### 10.179.3.2 rpki.up\_down.issue\_pdu.pkcs10

Definition at line 336 of file up\_down.py.

### 10.179.3.3 rpki.up\_down.issue\_pdu.req\_resource\_set\_as

Definition at line 327 of file up\_down.py.

### 10.179.3.4 rpki.up\_down.issue\_pdu.req\_resource\_set\_ipv4

Definition at line 328 of file up\_down.py.

### 10.179.3.5 rpki.up\_down.issue\_pdu.req\_resource\_set\_ipv6

Definition at line 329 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.180 rpki.up\_down.issue\_response\_pdu Class Reference

Inherits [rpki::up\\_down::class\\_response\\_syntax](#)

### Public Member Functions

- def [check\\_response](#)

#### 10.180.1 Detailed Description

Up-Down protocol "issue\_response" PDU.

Definition at line 429 of file `up_down.py`.

#### 10.180.2 Member Function Documentation

##### 10.180.2.1 def rpki.up\_down.issue\_response\_pdu.check\_response()

Check whether this looks like a reasonable issue\_response PDU.  
XML schema should be tighter for this response.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 434 of file `up_down.py`.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.181 rpki.up\_down.list\_pdu Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

Inherited by [rootd.list\\_pdu](#)

### Public Member Functions

- def [query](#)
- def [serve\\_pdu](#)
- def [toXML](#)

### 10.181.1 Detailed Description

Up-Down protocol "list" PDU.

Definition at line 231 of file up\_down.py.

### 10.181.2 Member Function Documentation

#### 10.181.2.1 def rpki.up\_down.list\_pdu.query (cls, parent, cb, eb)

Send a "list" query to parent.

Definition at line 273 of file up\_down.py.

#### 10.181.2.2 def rpki.up\_down.list\_pdu.serve\_pdu (self, q\_msg, r\_msg, child, callback, errback)

Serve one "list" PDU.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Reimplemented in [mootd.list\\_pdu](#)

Definition at line 240 of file up\_down.py.

#### 10.181.2.3 def rpki.up\_down.list\_pdu.toXML (self)

Generate (empty) payload of "list" PDU.

Definition at line 236 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.182 rpki.up\_down.list\_response\_pdu Class Reference

Inherits [rpki.up\\_down::class\\_response\\_syntax](#)

### 10.182.1 Detailed Description

Up-Down protocol "list\_response" PDU.

Definition at line 310 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.183 rpki.up\_down.message\_pdu Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

Inherited by [rootd.message\\_pdu](#)

### Public Member Functions

- def [\\_\\_str\\_\\_](#)
- def [log\\_query](#)
- def [make\\_query](#)
- def [serve\\_error](#)
- def [serve\\_top\\_level](#)
- def [startElement](#)
- def [toXML](#)

### Public Attributes

- [payload](#)
- [recipient](#)
- [sender](#)
- [type](#)
- [version](#)

### Static Public Attributes

- dictionary [name2type](#)
- tuple [type2name](#)= dict((v, k) for k, v in name2type.items())
- int [version](#)= 1



### 10.183.1 Detailed Description

Up-Down protocol message wrapper PDU.

Definition at line 568 of file up\_down.py.

### 10.183.2 Member Function Documentation

#### 10.183.2.1 def rpki.up\_down.message\_pdu.\_\_str\_\_(self)

Convert a message PDU to a string.

Definition at line 610 of file up\_down.py.

#### 10.183.2.2 def rpki.up\_down.message\_pdu.log\_query(self, child)

Log query we're handling. Separate method so rootd can override.

Reimplemented in [rootd.message\\_pdu](#)

Definition at line 639 of file up\_down.py.

#### 10.183.2.3 def rpki.up\_down.message\_pdu.make\_query(self, payload sender, recipient)

Construct one message PDU.

Definition at line 657 of file up\_down.py.

#### 10.183.2.4 def rpki.up\_down.message\_pdu.serve\_error(self, exception)

Generate an error\_response message PDU.

Definition at line 645 of file up\_down.py.

10.183.2.5 `def rpki.up_down.message_pdu.serve_top_level(self, child, callback)`

Serve one message request PDU.

Definition at line 614 of `le up_down.py`.

10.183.2.6 `def rpki.up_down.message_pdu.startElement(self, stack, name, attrs)`

Handle message PDU.

Payload of the `<message/>` element varies depending on the "type" attribute, so after some basic checks we have to instantiate the right class object to handle whatever kind of PDU this is.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 594 of `le up_down.py`.

10.183.2.7 `def rpki.up_down.message_pdu.toXMLs(elf)`

Generate payload of message PDU.

Definition at line 586 of `le up_down.py`.

### 10.183.3 Member Data Documentation

10.183.3.1 dictionary `rpki.up_down.message_pdu.name2type`[\[static\]](#)

Initial value:

```
{
    "list"           : list_pdu,
    "list_response"  : list_response_pdu,
    "issue"          : issue_pdu,
    "issue_response" : issue_response_pdu,
    "revoke"         : revoke_pdu,
    "revoke_response": revoke_response_pdu,
    "error_response" : error_response_pdu }
```

Reimplemented in [mootd.message\\_pdu](#)

Definition at line 575 of `le up_down.py`.

### 10.183.3.2 rpki.up\_down.message\_pdu.payload

Definition at line 607 of file up\_down.py.

### 10.183.3.3 rpki.up\_down.message\_pdu.recipient

Definition at line 605 of file up\_down.py.

### 10.183.3.4 rpki.up\_down.message\_pdu.sender

Definition at line 604 of file up\_down.py.

### 10.183.3.5 rpki.up\_down.message\_pdu.type

Definition at line 606 of file up\_down.py.

### 10.183.3.6 tuple rpki.up\_down.message\_pdu.type2name = dict((v, k) for k, v in name2type.items()) [static]

Reimplemented in [mootd.message\\_pdu](#)

Definition at line 584 of file up\_down.py.

### 10.183.3.7 rpki.up\_down.message\_pdu.version

Definition at line 603 of file up\_down.py.

### 10.183.3.8 int rpki.up\_down.message\_pdu.version = 1 [static]

Definition at line 573 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.184 rpki.up\_down.multi\_uri Class Reference

Inherits list.

### Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def \\_\\_str\\_\\_](#)
- [def rsync](#)

### 10.184.1 Detailed Description

Container for a set of URIs.

Definition at line 95 of file `up_down.py`.

### 10.184.2 Member Function Documentation

#### 10.184.2.1 `def rpki.up_down.multi_uri.__init__(self, ini)`

Initialize a set of URIs, which includes basic some syntax checking.

Definition at line 100 of file `up_down.py`.

#### 10.184.2.2 `def rpki.up_down.multi_uri.__str__(self)`

Convert a `multi_uri` back to a string representation.

Definition at line 115 of file `up_down.py`.

#### 10.184.2.3 `def rpki.up_down.multi_uri.rsync(self)`

Find first `rsync://...` URI in `self`.

Definition at line 119 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.185 rpki.up\_down.revoke\_pdu Class Reference

Inherits [rpki::up\\_down::revoke\\_syntax](#)

Inherited by [rootd.revoke\\_pdu](#)

### Public Member Functions

- def [get\\_SKI](#)
- def [query](#)
- def [serve\\_pdu](#)

### Public Attributes

- [class\\_name](#)
- [ski](#)

### 10.185.1 Detailed Description

Up-Down protocol "revoke" PDU.

Definition at line 456 of file up\_down.py.

### 10.185.2 Member Function Documentation

#### 10.185.2.1 def rpki.up\_down.revoke\_pdu.get\_SKI(self)

Convert g(SKI) encoding from PDU back to raw SKI.

Definition at line 461 of file up\_down.py.

10.185.2.2 def rpki.up\_down.revoke\_pdu.query(self, ca, gski, cb, eb)

Send a "revoke" request for certificate(s) named by gski to parent associated with ca.

Definition at line 485 of file up\_down.py.

10.185.2.3 def rpki.up\_down.revoke\_pdu.serve\_pdu(self, q\_msg, r\_msg, child, cb, eb)

Serve one revoke request PDU.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Reimplemented in [mootd.revoke\\_pdu](#)

Definition at line 465 of file up\_down.py.

### 10.185.3 Member Data Documentation

10.185.3.1 rpki.up\_down.revoke\_pdu.class\_name

Reimplemented from [rpki.up\\_down.revoke\\_syntax](#)

Definition at line 491 of file up\_down.py.

10.185.3.2 rpki.up\_down.revoke\_pdu.ski

Reimplemented from [rpki.up\\_down.revoke\\_syntax](#)

Definition at line 492 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.186 rpki.up\_down.revoke\_response\_pdu Class Reference

Inherits [rpki::up\\_down::revoke\\_syntax](#)

### 10.186.1 Detailed Description

Up-Down protocol "revoke\_response" PDU.

Definition at line 495 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.187 rpki.up\_down.revoke\_syntax Class Reference

Inherits [rpki::up\\_down::base\\_elt](#)

Inherited by [rpki.up\\_down.revoke\\_pdu](#) and [rpki.up\\_down.revoke\\_response\\_pdu](#)

### Public Member Functions

- [def startElement](#)
- [def toXML](#)

### Public Attributes

- [class\\_name](#)
- [ski](#)

### 10.187.1 Detailed Description

Syntax for Up-Down protocol "revoke" and "revoke\_response" PDUs.

Definition at line 442 of file up\_down.py.

### 10.187.2 Member Function Documentation

10.187.2.1 `def rpki.up_down.revoke_syntax.startElement(self, stack, name, attrs)`

Handle "revoke" PDU.

Reimplemented from [rpki.up\\_down.base\\_elt](#)

Definition at line 447 of file up\_down.py.

### 10.187.2.2 def rpki.up\_down.revoke\_syntax.toXML (self)

Generate payload of "revoke" PDU.

Definition at line 452 of file up\_down.py.

### 10.187.3 Member Data Documentation

#### 10.187.3.1 rpki.up\_down.revoke\_syntax.class\_name

Reimplemented in [rpki.up\\_down.revoke\\_pdu](#)

Definition at line 449 of file up\_down.py.

#### 10.187.3.2 rpki.up\_down.revoke\_syntax.ski

Reimplemented in [rpki.up\\_down.revoke\\_pdu](#)

Definition at line 450 of file up\_down.py.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.188 rpki.up\_down.sax\_handler Class Reference

Inherits [rpki::xml\\_utils::sax\\_handler](#)

Inherited by [rootd.sax\\_handler](#)

### Static Public Attributes

- string [name](#)= "message"
- pdu= [message\\_pdu](#)
- string [version](#)= "1"

### 10.188.1 Detailed Description

SAX handler for Up-Down protocol.

Definition at line 673 of file up\_down.py.



## 10.188.2 Member Data Documentation

10.188.2.1 `string rpki.up_down.sax_handler.name = "message"` [static]

Definition at line 679 of file `up_down.py`.

10.188.2.2 `rpki.up_down.sax_handler.pdu = message_pd` [static]

Reimplemented in [mootd.sax\\_handler](#)

Definition at line 678 of file `up_down.py`.

10.188.2.3 `string rpki.up_down.sax_handler.version = "1"` [static]

Definition at line 680 of file `up_down.py`.

The documentation for this class was generated from the following file:

- [up\\_down.py \(2935\)](#)

## 10.189 rpki.x509.CMS\_object Class Reference

Inherits [rpki::x509::DER\\_object](#)

Inherited by [rpki.x509.DER\\_CMS\\_object](#) and [rpki.x509.XML\\_CMS\\_object](#)

### Public Member Functions

- def [extract](#)
- def [get\\_content](#)
- def [get\\_DER](#)
- def [get\\_POW](#)
- def [set\\_content](#)
- def [sign](#)
- def [verify](#)

## Public Attributes

- `content`
- `DER`  
DER value of this `object`
- `POW`

## Static Public Attributes

- `debug_cms_certs` `False`  
Set this to True to log a lot of chatter about CMS certificates.
- `dump_on_verify_failure` `True`  
Set this to True to get dumpasn1 dumps of ASN.1 on CMS verify failures.
- `tuple_econtent_oid` `POWify_OID("id-data")`
- `tuple_formats` `("DER", "POW")`  
Formats supported in this `object`
- `tuple_other_clear` `("content",)`  
Other attributes that self.clear() should whack.
- `tuple_pem_converter` `PEM_converter("CMS")`  
PEM converter for this `object`
- `print_on_der_error` `True`  
Set this to True to log alleged DER when we have trouble parsing it, in case it's really a Perl backtrace or something.
- `require_crls` `False`  
Set this to False to make CMS CRLs optional in the cases where we would otherwise require them.

## 10.189.1 Detailed Description

Class to hold a CMS-wrapped object.

CMS-wrapped objects are a little different from the other DER\_object types because the signed object is CMS wrapping inner content that's also ASN.1, and due to our current minimal support for CMS we can't just handle this as a pretty composite object. So, for now anyway, a CMS\_object is the outer CMS wrapped object so that the usual DER and PEM operations do the obvious things, and the inner content is handle via separate methods.

Definition at line 702 of file x509.py.

## 10.189.2 Member Function Documentation

### 10.189.2.1 def rpki.x509.CMS\_object.extract(self)

Extract and store inner content from CMS wrapper without verifying the CMS.

DANGER WILL ROBINSON!!!

Do not use this method on unvalidated data. Use the verify() method instead.

If you don't understand this warning, don't use this method.

Definition at line 853 of file x509.py.

### 10.189.2.2 def rpki.x509.CMS\_object.get\_contents(self)

Get the inner content of this CMS\_object.

Definition at line 764 of file x509.py.

### 10.189.2.3 def rpki.x509.CMS\_object.get\_DER(self)

Get the DER value of this CMS\_object.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 743 of file x509.py.

### 10.189.2.4 def rpki.x509.CMS\_object.get\_POW(self)

Get the POW value of this CMS\_object.

Definition at line 755 of file x509.py.

10.189.2.5 `def rpki.x509.CMS_object.set_contents(self, content)`

Set the (inner) content of this CMS\_object, clearing the wrapper.

Definition at line 772 of file x509.py.

10.189.2.6 `def rpki.x509.CMS_object.sign(self, keypair, certs, crls = None, no_certs= False )`

Sign and wrap inner content.

Definition at line 881 of file x509.py.

10.189.2.7 `def rpki.x509.CMS_object.verify(self, ta)`

Verify CMS wrapper and store inner content.

Definition at line 779 of file x509.py.

### 10.189.3 Member Data Documentation

10.189.3.1 `rpki.x509.CMS_object.content`

Reimplemented in [rpki.x509.DER\\_CMS\\_object](#) and [rpki.x509.XML\\_CMS\\_object](#)

Definition at line 777 of file x509.py.

10.189.3.2 `rpki.x509.CMS_object::debug_cms_certs = False`[\[static\]](#)

Set this to True to [log](#) a lot of chatter about CMS certificates.

Definition at line 728 of file x509.py.

### 10.189.3.3 rpki.x509.CMS\_object.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 751 of file x509.py.

10.189.3.4 `rpki.x509.CMS_object.dump_on_verify_failure = True`  
[static]

Set this to True to get dumpasn1 dumps of ASN.1 on CMS verify failures.

Definition at line 723 of file x509.py.

10.189.3.5 `tuple rpki.x509.CMS_object.econtent_oid =`  
`POWify_OID("id-data")` [static]

Reimplemented in [rpki.x509.SignedManifest](#), [rpki.x509.ROA](#), and [rpki.x509.XML\\_CMS\\_object](#)

Definition at line 717 of file x509.py.

10.189.3.6 `tuple rpki.x509.CMS_object.formats = ("DER", "POW")`  
[static]

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 715 of file x509.py.

10.189.3.7 `tuple rpki.x509.CMS_object.other_clear = ("content",)` [static]

Other attributes that self.clear() should whack.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 716 of file x509.py.

10.189.3.8 tuple rpki.x509.CMS\_object.pem\_converter =  
PEM\_converter("CMS") [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Reimplemented in [rpki.x509.SignedManifest](#) and [rpki.x509.ROA](#)

Definition at line 718 of file x509.py.

10.189.3.9 rpki.x509.CMS\_object.POW

Definition at line 761 of file x509.py.

10.189.3.10 rpki::x509.CMS\_object::print\_on\_der\_error = True [static]

Set this to True to [log](#) alleged DER when we have trouble parsing it, in case it's really a Perl backtrace or something.

Definition at line 741 of file x509.py.

10.189.3.11 rpki::x509.CMS\_object::require\_crls = False [static]

Set this to False to make CMS CRLs optional in the cases where we would otherwise require them. Some day this option should go away and CRLs should be unconditionally mandatory in such cases.

Definition at line 735 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

10.190 rpki.x509.CRL Class Reference

Inherits [rpki::x509::DER\\_object](#)

## Public Member Functions

- def [generate](#)
- def [get\\_DER](#)
- def [get\\_POW](#)
- def [get\\_POWpkix](#)
- def [getIssuer](#)
- def [getNextUpdate](#)
- def [getThisUpdate](#)

## Public Attributes

- [DER](#)  
DER value of this [object](#)
- [POW](#)
- [POWpkix](#)

## Static Public Attributes

- tuple [formats](#)= ("DER", "[POW](#)", "[POWpkix](#)")  
Formats supported in this [object](#)
- tuple [pem\\_converter](#)= [PEM\\_convert](#)("X509 CRL")  
PEM converter for this [object](#)

## 10.190.1 Detailed Description

Class to hold a Certificate Revocation List.

Definition at line 1107 of file x509.py.

## 10.190.2 Member Function Documentation

10.190.2.1 def rpki.x509.CRL.generate(cls, keypair, issuer, serial, thisUpdate, nextUpdate, revokedCertificates, version=1, digestType="sha256WithRSAEncryption")

Generate a new CRL.

Definition at line 1163 of file x509.py.

### 10.190.2.2 def rpki.x509.CRL.get\_DER(\$self)

Get the DER value of this CRL.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 1115 of file x509.py.

### 10.190.2.3 def rpki.x509.CRL.get\_POW(\$self)

Get the POW value of this CRL.

Definition at line 1130 of file x509.py.

### 10.190.2.4 def rpki.x509.CRL.get\_POWpkix(\$self)

Get the POW.pkix value of this CRL.

Definition at line 1139 of file x509.py.

### 10.190.2.5 def rpki.x509.CRL.getIssuer(\$self)

Get issuer value of this CRL.

Definition at line 1158 of file x509.py.

### 10.190.2.6 def rpki.x509.CRL.getNextUpdate(\$self)

Get nextUpdate value from this CRL.

Definition at line 1154 of file x509.py.



10.190.2.7 def rpki.x509.CRL.getThisUpdate \$elf)

Get thisUpdate value from this CRL.

Definition at line 1150 of file x509.py.

### 10.190.3 Member Data Documentation

10.190.3.1 rpki.x509.CRL.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 1123 of file x509.py.

10.190.3.2 tuple rpki.x509.CRL.formats = ("DER", "POW", "POWpkix")  
[static]

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 1112 of file x509.py.

10.190.3.3 tuple rpki.x509.CRL.pem\_converter = PEM\_converter("X509  
CRL") [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 1113 of file x509.py.

10.190.3.4 rpki.x509.CRL.POW

Definition at line 1136 of file x509.py.

## 10.190.3.5 rpki.x509.CRL.POWpkix

Definition at line 1147 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.191 rpki.x509.DeadDrop Class Reference

Inherits [object](#)

## Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def dump](#)

## Public Attributes

- [maildir](#)
- [pid](#)

## 10.191.1 Detailed Description

Dead-drop utility for storing copies of CMS messages for debugging or audit. At the moment this uses Maildir mailbox format, as it has approximately the right properties and a number of useful tools for manipulating it already exist.

Definition at line 1002 of file x509.py.

## 10.191.2 Member Function Documentation

## 10.191.2.1 def rpki.x509.DeadDrop.\_\_init\_\_(self, name)

Definition at line 1010 of file x509.py.

10.191.2.2 def rpki.x509.DeadDrop.dump(\$self, obj)

Definition at line 1014 of file x509.py.

### 10.191.3 Member Data Documentation

10.191.3.1 rpki.x509.DeadDrop.maildir

Definition at line 1011 of file x509.py.

10.191.3.2 rpki.x509.DeadDrop.pid

Definition at line 1012 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.192 rpki.x509.DER\_CMS\_object Class Reference

Inherits [rpki::x509::CMS\\_object](#)

Inherited by [rpki.x509.ROA](#), and [rpki.x509.SignedManifest](#)

### Public Member Functions

- def [decode](#)
- def [encode](#)

### Public Attributes

- [content](#)

### 10.192.1 Detailed Description

Class to hold CMS objects with DER-based content.

Definition at line 917 of file x509.py.

## 10.192.2 Member Function Documentation

## 10.192.2.1 def rpki.x509.DER\_CMS\_object.decode(self, der)

Decode DER and set inner content.

Definition at line 926 of file x509.py.

## 10.192.2.2 def rpki.x509.DER\_CMS\_object.encode(self)

Encode inner content for signing.

Definition at line 922 of file x509.py.

## 10.192.3 Member Data Documentation

## 10.192.3.1 rpki.x509.DER\_CMS\_object.content

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 932 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.193 rpki.x509.DER\_object Class Reference

Inherits [object](#)

Inherited by [rpki.x509.CMS\\_object](#), [rpki.x509.CRL](#), [rpki.x509.PKCS10](#), [rpki.x509.RSA](#), [rpki.x509.RSAPublicKey](#) and [rpki.x509.X509](#)

## Public Member Functions

- def [\\_\\_cmp\\_\\_](#)
- def [\\_\\_init\\_\\_](#)
- def [clear](#)
- def [dumpasn1](#)

- def `empty`
- def `from_sql`
- def `gAKI`
- def `get_3779resources`
- def `get_AIA`
- def `get_AKI`
- def `get_Base64`
- def `get_basicConstraints`
- def `get_DER`
- def `get_PEM`
- def `get_SIA`
- def `get_SKI`
- def `gSKI`
- def `hAKI`
- def `hSKI`
- def `is_CA`
- def `set`
- def `to_sql`

#### Public Attributes

- `DER`  
DER value of this `object`

#### Static Public Attributes

- tuple `formats= ("DER",)`  
Formats supported in this `object`
- tuple `other_clear= ()`  
Other attributes that self.clear() should whack.
- `pem_converter= None`  
PEM converter for this `object`

#### 10.193.1 Detailed Description

Virtual class to hold a generic DER object.

Definition at line 105 of file `x509.py`.

### 10.193.2 Member Function Documentation

#### 10.193.2.1 def rpki.x509.DER\_object.\_\_cmp\_\_(self, other)

Compare two DER-encoded objects.

Definition at line 200 of file x509.py.

#### 10.193.2.2 def rpki.x509.DER\_object.\_\_init\_\_(self, kw)

Initialize a DER\_object.

Definition at line 138 of file x509.py.

#### 10.193.2.3 def rpki.x509.DER\_object.clear(self)

Make this object empty.

Definition at line 131 of file x509.py.

#### 10.193.2.4 def rpki.x509.DER\_object.dumpasn1(self)

Pretty print an ASN.1 DER object using cryptlib dumpasn1 tool.  
Use a temporary file rather than popen4() because dumpasn1 uses  
seek() when decoding ASN.1 content nested in OCTET STRING values.

Definition at line 308 of file x509.py.

#### 10.193.2.5 def rpki.x509.DER\_object.empty(self)

Test whether this object is empty.

Definition at line 122 of file x509.py.

#### 10.193.2.6 def rpki.x509.DER\_object.from\_sql(cls, x)

Convert from SQL storage format.

Definition at line 300 of file x509.py.

#### 10.193.2.7 def rpki.x509.DER\_object.gAKI(self)

Calculate g(AKI) for this object. Only work for subclasses that implement get\_AKI().

Definition at line 236 of file x509.py.

#### 10.193.2.8 def rpki.x509.DER\_object.get\_3779resources(self)

Get RFC 3779 resources as rpki.resource\_set objects. Only works for subclasses that support getExtensions().

Definition at line 287 of file x509.py.

#### 10.193.2.9 def rpki.x509.DER\_object.get\_AIA(self)

Get the SIA extension from this object. Only works for subclasses that support getExtension().

Definition at line 265 of file x509.py.

#### 10.193.2.10 def rpki.x509.DER\_object.get\_AKI(self)

Get the AKI extension from this object. Only works for subclasses that support getExtension().

Definition at line 243 of file x509.py.

10.193.2.11 `def rpki.x509.DER_object.get_Base64(self)`

Get the Base64 encoding of the DER value of this object.

Definition at line 192 of file x509.py.

10.193.2.12 `def rpki.x509.DER_object.get_basicConstraints(self)`

Get the basicConstraints extension from this object. Only works for subclasses that support `getExtension()`.

Definition at line 272 of file x509.py.

10.193.2.13 `def rpki.x509.DER_object.get_DER(self)`

Get the DER value of this object.

Subclasses will almost certainly override this method.

Reimplemented in [rpki.x509.X509](#), [rpki.x509.PKCS10](#), [rpki.x509.RSA](#),  
[rpki.x509.RSAPublicKey](#), [rpki.x509.CMS\\_object](#) and [rpki.x509.CRL](#)

Definition at line 181 of file x509.py.

10.193.2.14 `def rpki.x509.DER_object.get_PEM(self)`

Get the PEM representation of this object.

Definition at line 196 of file x509.py.

10.193.2.15 `def rpki.x509.DER_object.get_SIA(self)`

Get the SIA extension from this object. Only works for subclasses that support `getExtension()`.

Definition at line 258 of file x509.py.



#### 10.193.2.16 def rpki.x509.DER\_object.get\_SKI(self)

Get the SKI extension from this object. Only works for subclasses that support getExtension().

Reimplemented in [rpki.x509.RSA](#) and [rpki.x509.RSAPublic](#)

Definition at line 251 of file x509.py.

#### 10.193.2.17 def rpki.x509.DER\_object.gSKI(self)

Calculate g(SKI) for this object. Only work for subclasses that implement get\_SKI().

Definition at line 221 of file x509.py.

#### 10.193.2.18 def rpki.x509.DER\_object.hAKI(self)

Return hexadecimal string representation of AKI for this object. Only work for subclasses that implement get\_AKI().

Definition at line 228 of file x509.py.

#### 10.193.2.19 def rpki.x509.DER\_object.hSKI(self)

Return hexadecimal string representation of SKI for this object. Only work for subclasses that implement get\_SKI().

Definition at line 213 of file x509.py.

#### 10.193.2.20 def rpki.x509.DER\_object.is\_CA(self)

Return True if and only if object has the basicConstraints extension and its cA value is true.

Definition at line 279 of file x509.py.

## 10.193.2.21 def rpki.x509.DER\_object.set(self, kw)

Set this object by setting one of its known formats.

This method only allows one to set one format at a time. Subsequent calls will clear the object first. The point of all this is to let the object's internal converters handle mustering the object into whatever format you need at the moment.

Definition at line 146 of file x509.py.

## 10.193.2.22 def rpki.x509.DER\_object.to\_sql(self)

Convert to SQL storage format.

Definition at line 304 of file x509.py.

## 10.193.3 Member Data Documentation

## 10.193.3.1 rpki.x509.DER\_object.DER

DER value of this object

Reimplemented in [rpki.x509.X509](#), [rpki.x509.PKCS10](#), [rpki.x509.RSA](#), [rpki.x509.RSAPublicKey](#), [rpki.x509.CMS\\_object](#) and [rpki.x509.CRL](#)

Definition at line 164 of file x509.py.

## 10.193.3.2 tuple rpki.x509.DER\_object.formats = ("DER",) [static]

Formats supported in this object

Reimplemented in [rpki.x509.X509](#), [rpki.x509.PKCS10](#), [rpki.x509.RSA](#), [rpki.x509.RSAPublicKey](#), [rpki.x509.CMS\\_object](#) and [rpki.x509.CRL](#)

Definition at line 111 of file x509.py.

## 10.193.3.3 tuple rpki.x509.DER\_object.other\_clear = () [static]

Other attributes that self.clear() should whack.

Reimplemented in [rpki.x509.CMS\\_object](#)

Definition at line 117 of file x509.py.

10.193.3.4 rpki.x509.DER\_object.pem\_converter = None[static]

PEM converter for this [object](#)

Reimplemented in [rpki.x509.X509](#), [rpki.x509.PKCS10](#), [rpki.x509.RSA](#),  
[rpki.x509.RSAPublic](#), [rpki.x509.CMS\\_object](#), [rpki.x509.SignedManifest](#),  
[rpki.x509.ROA](#), and [rpki.x509.CRL](#)

Definition at line 114 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.194 rpki.x509.PEM\_converter Class Reference

Inherits [object](#)

### Public Member Functions

- def [\\_\\_init\\_\\_](#)
- def [looks\\_like\\_PEM](#)
- def [to\\_DER](#)
- def [to\\_PEM](#)

### Public Attributes

- [b](#)
- [e](#)

### 10.194.1 Detailed Description

Convert between DER and PEM encodings for various kinds of ASN.1 data.

Definition at line 62 of file x509.py.

## 10.194.2 Member Function Documentation

### 10.194.2.1 def rpki.x509.PEM\_converter.\_\_init\_\_(self, kind)

Initialize PEM\_converter.

Definition at line 67 of file x509.py.

### 10.194.2.2 def rpki.x509.PEM\_converter.looks\_like\_PEM(self, text)

Guess whether text looks like a PEM encoding.

Definition at line 74 of file x509.py.

### 10.194.2.3 def rpki.x509.PEM\_converter.to\_DER(self, pem)

Convert from PEM to DER.

Definition at line 81 of file x509.py.

### 10.194.2.4 def rpki.x509.PEM\_converter.to\_PEM(self, der)

Convert from DER to PEM.

Definition at line 94 of file x509.py.

## 10.194.3 Member Data Documentation

### 10.194.3.1 rpki.x509.PEM\_converter.b

Definition at line 71 of file x509.py.

## 10.194.3.2 rpki.x509.PEM\_converter.e

Definition at line 72 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.195 rpki.x509.PKCS10 Class Reference

Inherits [rpki::x509::DER\\_object](#)

## Public Member Functions

- def [check\\_valid\\_rpki](#)
- def [create](#)
- def [create\\_ca](#)
- def [get\\_DER](#)
- def [get\\_POWpkix](#)
- def [getPublicKey](#)

## Public Attributes

- [DER](#)  
DER value of this [object](#)
- [POWpkix](#)

## Static Public Attributes

- tuple [formats](#)= ("DER", "[POWpkix](#)")  
Formats supported in this [object](#)
- tuple [pem\\_converter](#)= [PEM\\_converter](#)("CERTIFICATE REQUEST")  
PEM converter for this [object](#)

## 10.195.1 Detailed Description

Class to hold a PKCS #10 request.

Definition at line 501 of file x509.py.

## 10.195.2 Member Function Documentation

### 10.195.2.1 def rpki.x509.PKCS10.check\_valid\_rpki(self)

Check this certification request to see whether it's a valid request for an RPKI certificate. This is broken out of the up-down protocol code because it's somewhat involved and the up-down code doesn't need to know the details.

Throws an exception if the request isn't valid, so if this method returns at all, the request is ok.

Definition at line 536 of file x509.py.

### 10.195.2.2 def rpki.x509.PKCS10.create(self, keypair, exts= None)

Create a new request for a given keypair, including given extensions.

Definition at line 596 of file x509.py.

### 10.195.2.3 def rpki.x509.PKCS10.create\_csr(self, keypair, sia= None)

Create a new request for a given keypair, including given SIA value.

Definition at line 583 of file x509.py.

### 10.195.2.4 def rpki.x509.PKCS10.get\_DER(self)

Get the DER value of this certification request.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 509 of file x509.py.

### 10.195.2.5 def rpki.x509.PKCS10.get\_POWpkix(self)

Get the POW.pkix value of this certification request.

Definition at line 521 of file x509.py.

### 10.195.2.6 def rpki.x509.PKCS10.getPublicKeys(self)

Extract the public key from this certification request.

Definition at line 532 of file x509.py.

## 10.195.3 Member Data Documentation

### 10.195.3.1 rpki.x509.PKCS10.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 517 of file x509.py.

### 10.195.3.2 tuple rpki.x509.PKCS10.formats = ("DER", "POWpkix") [static]

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 506 of file x509.py.

### 10.195.3.3 tuple rpki.x509.PKCS10.pem\_converter = PEM\_converter("CERTIFICATE REQUEST") [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 507 of file x509.py.

### 10.195.3.4 rpki.x509.PKCS10.POWpkix

Definition at line 529 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.196 rpki.x509.ROA Class Reference

Inherits [rpki::x509::DER\\_CMS\\_object](#)

### Public Member Functions

- `def` [build](#)

### Static Public Attributes

- `content_class` [= rpki.roa.RouteOriginAttestation](#)
- `tuple` [econtent\\_oid](#) [= POWify\\_OID\("id-ct-routeOriginAttestation"\)](#)
- `tuple` [pem\\_converter](#) [= PEM\\_converter\("ROUTE ORIGIN ATTESTATION"\)](#)  
 PEM converter for this [object](#)

### 10.196.1 Detailed Description

Class to hold a signed ROA.

Definition at line 974 of file `x509.py`.

### 10.196.2 Member Function Documentation

10.196.2.1 `def rpki.x509.ROA.build(cls, asn, ipv4, ipv6, keypair, certs, version=0)`

Build a ROA.

Definition at line 984 of file `x509.py`.

### 10.196.3 Member Data Documentation

10.196.3.1 `rpki.x509.ROA.content_class = rpki.roa.RouteOriginAttestation`  
`[static]`

Definition at line 980 of file `x509.py`.



10.196.3.2 tuple rpki.x509.ROA.econtent\_oid = POWify\_OID("id-ct-routeOriginAttestation") [static]

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 981 of file x509.py.

10.196.3.3 tuple rpki.x509.ROA.pem\_converter = PEM\_converter("ROUTE ORIGIN ATTESTATION") [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 979 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.197 rpki.x509.RSA Class Reference

Inherits [rpki::x509::DER\\_object](#)

### Public Member Functions

- def [generate](#)
- def [get\\_DER](#)
- def [get\\_POW](#)
- def [get\\_public\\_DER](#)
- def [get\\_RSAPublic](#)
- def [get\\_SKI](#)

### Public Attributes

- [DER](#)  
DER value of this [object](#)
- [POW](#)

### Static Public Attributes

- tuple `formats`= ("DER", "POW")  
Formats supported in this [object](#)
- tuple `pem_converter`= `PEM_converter`("RSA PRIVATE KEY")  
PEM converter for this [object](#)

### 10.197.1 Detailed Description

Class to hold an RSA key pair.

Definition at line 610 of file `x509.py`.

### 10.197.2 Member Function Documentation

#### 10.197.2.1 `def rpki.x509.RSA.generated(s, keylength= 2048 )`

Generate a new keypair.

Definition at line 640 of file `x509.py`.

#### 10.197.2.2 `def rpki.x509.RSA.get_DER(self)`

Get the DER value of this keypair.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 618 of file `x509.py`.

#### 10.197.2.3 `def rpki.x509.RSA.get_POW(self)`

Get the POW value of this keypair.

Definition at line 630 of file `x509.py`.

#### 10.197.2.4 def rpki.x509.RSA.get\_public\_DER([self](#))

Get the DER encoding of the public key from this keypair.

Definition at line 647 of file x509.py.

#### 10.197.2.5 def rpki.x509.RSA.get\_RSAPublic([self](#))

Convert the public key of this keypair into a RSAPublic object.

Definition at line 655 of file x509.py.

#### 10.197.2.6 def rpki.x509.RSA.get\_SKI([self](#))

Calculate the SKI of this keypair.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 651 of file x509.py.

### 10.197.3 Member Data Documentation

#### 10.197.3.1 rpki.x509.RSA.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 626 of file x509.py.

#### 10.197.3.2 tuple rpki.x509.RSA.formats = ("DER", "POW") [static]

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 615 of file x509.py.

10.197.3.3 tuple rpki.x509.RSA.pem\_converter = PEM\_converter("RSA  
PRIVATE KEY") [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 616 of file x509.py.

10.197.3.4 rpki.x509.RSA.POW

Definition at line 636 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.198 rpki.x509.RSAPublic Class Reference

Inherits [rpki::x509::DER\\_object](#)

### Public Member Functions

- def [get\\_DER](#)
- def [get\\_POW](#)
- def [get\\_SKI](#)

### Public Attributes

- [DER](#)  
DER value of this [object](#)
- [POW](#)

### Static Public Attributes

- tuple [formats](#)= ("DER", "[POW](#)")  
Formats supported in this [object](#)
- tuple [pem\\_converter](#)= [PEM\\_converter](#)("RSA PUBLIC KEY")

PEM converter for this [object](#)

### 10.198.1 Detailed Description

Class to hold an RSA public key.

Definition at line 659 of file x509.py.

### 10.198.2 Member Function Documentation

#### 10.198.2.1 def rpki.x509.RSAPublic.get\_DER(self)

Get the DER value of this public key.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 667 of file x509.py.

#### 10.198.2.2 def rpki.x509.RSAPublic.get\_POW(self)

Get the POW value of this public key.

Definition at line 679 of file x509.py.

#### 10.198.2.3 def rpki.x509.RSAPublic.get\_SKI(self)

Calculate the SKI of this public key.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 688 of file x509.py.

### 10.198.3 Member Data Documentation

#### 10.198.3.1 rpki.x509.RSAPublic.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 675 of file x509.py.

```
10.198.3.2 tuple rpki.x509.RSAPublic.formats = ("DER", "POW")
          [static]
```

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 664 of file x509.py.

```
10.198.3.3 tuple rpki.x509.RSAPublic.pem_converter = PEM_converter("RSA
          PUBLIC KEY") [static]
```

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 665 of file x509.py.

```
10.198.3.4 rpki.x509.RSAPublic.POW
```

Definition at line 685 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.199 rpki.x509.SignedManifest Class Reference

Inherits [rpki.x509.DER\\_CMS\\_object](#)

### Public Member Functions

- def [build](#)
- def [getNextUpdate](#)
- def [getThisUpdate](#)

### Static Public Attributes

- `content_class` `rpki.manifest.Manifest`
- tuple `content_oid` `POWify_OID("id-ct-rpkiManifest")`
- tuple `pem_converter` `PEM_converter("RPKI MANIFEST")`  
 PEM converter for this object

### 10.199.1 Detailed Description

Class to hold a signed manifest.

Definition at line 934 of file `x509.py`.

### 10.199.2 Member Function Documentation

10.199.2.1 `def rpki.x509.SignedManifest.build(cls, serial, thisUpdate, nextUpdate, names_and_objskeypair, certs, version=0)`

Build a signed manifest.

Definition at line 952 of file `x509.py`.

10.199.2.2 `def rpki.x509.SignedManifest.getNextUpdates(self)`

Get nextUpdate value from this manifest.

Definition at line 947 of file `x509.py`.

10.199.2.3 `def rpki.x509.SignedManifest.getThisUpdates(self)`

Get thisUpdate value from this manifest.

Definition at line 943 of file `x509.py`.

### 10.199.3 Member Data Documentation

10.199.3.1 `rpki.x509.SignedManifest.content_class = rpki.manifest.Manifest`  
[static]

Definition at line 940 of file `x509.py`.

10.199.3.2 `tuple rpki.x509.SignedManifest.econtent_oid =`  
`POWify_OID("id-ct-rpkiManifest")` [static]

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 941 of file `x509.py`.

10.199.3.3 `tuple rpki.x509.SignedManifest.pem_converter =`  
`PEM_converter("RPKI MANIFEST")` [static]

PEM converter for this [object](#)

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 939 of file `x509.py`.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.200 rpki.x509.X509 Class Reference

Inherits [rpki::x509::DER\\_object](#)

### Public Member Functions

- `def` [cross\\_certify](#)
- `def` [expired](#)
- `def` [get\\_DER](#)
- `def` [get\\_POW](#)
- `def` [get\\_POWpkix](#)
- `def` [getIssuer](#)
- `def` [getNotAfter](#)



- def [getNotBefore](#)
- def [getPublicKey](#)
- def [getSerial](#)
- def [getSubject](#)
- def [issue](#)
- def [normalize\\_chain](#)

#### Public Attributes

- [DER](#)  
DER value of this [object](#)
- [POW](#)
- [POWpkix](#)

#### Static Public Attributes

- tuple [formats](#)= ("DER", "[POW](#)", "[POWpkix](#)")  
Formats supported in this [object](#)
- tuple [pem\\_converter](#)= [PEM\\_converter](#)("CERTIFICATE")  
PEM converter for this [object](#)

### 10.200.1 Detailed Description

X.509 certificates.

This class is designed to hold all the different representations of X.509 certs we're using and convert between them. X.509 support in Python a nasty maze of half-cooked stuff (except perhaps for cryptlib, which is just different). Users of this module should not have to care about this implementation nightmare.

Definition at line 327 of file `x509.py`.

### 10.200.2 Member Function Documentation

- 10.200.2.1 def `rpki.x509.X509.cross_certify(self, keypair, source_cert serial, notAfter, now = None, pathLenConstraint= 0)`

Issue a certificate with values taking from an existing certificate.  
This is used to construct some kinds of BPKI certificates.

Definition at line 459 of file x509.py.

10.200.2.2 def rpki.x509.X509.expired(self)

Test whether this certificate has expired.

Definition at line 400 of file x509.py.

10.200.2.3 def rpki.x509.X509.get\_DER(self)

Get the DER value of this certificate.

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 341 of file x509.py.

10.200.2.4 def rpki.x509.X509.get\_POW(self)

Get the POW value of this certificate.

Definition at line 356 of file x509.py.

10.200.2.5 def rpki.x509.X509.get\_POWpkix(self)

Get the POW.pkix value of this certificate.

Definition at line 365 of file x509.py.

10.200.2.6 def rpki.x509.X509.getIssuers(self)

Get the issuer of this certificate.

Definition at line 376 of file x509.py.

10.200.2.7 `def rpki.x509.X509.getNotAfter(self)`

Get the expiration time of this certificate.

Definition at line 388 of file x509.py.

10.200.2.8 `def rpki.x509.X509.getNotBefore(self)`

Get the inception time of this certificate.

Definition at line 384 of file x509.py.

10.200.2.9 `def rpki.x509.X509.getPublicKey(self)`

Extract the public key from this certificate.

Definition at line 396 of file x509.py.

10.200.2.10 `def rpki.x509.X509.getSerial(self)`

Get the serial number of this certificate.

Definition at line 392 of file x509.py.

10.200.2.11 `def rpki.x509.X509.getSubject(self)`

Get the subject of this certificate.

Definition at line 380 of file x509.py.

```
10.200.2.12 def rpki.x509.X509.issue(self, keypair, subject_key serial, sia,
    aia, crldp, notAfter, cn = None, resources= None, is_ca= True )
```

Issue a certificate.

Definition at line 404 of file x509.py.

```
10.200.2.13 def rpki.x509.X509.normalize_chain(chain)
```

Normalize a chain of certificates into a tuple of X509 objects.  
Given all the glue certificates needed for BPKI cross certification, it's easiest to allow sloppy arguments to the HTTPS and CMS validation methods and provide a single method that normalizes the allowed cases. So this method allows X509, None, lists, and tuples, and returns a tuple of X509 objects.

Definition at line 488 of file x509.py.

### 10.200.3 Member Data Documentation

#### 10.200.3.1 rpki.x509.X509.DER

DER value of this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 349 of file x509.py.

```
10.200.3.2 tuple rpki.x509.X509.formats = ("DER", "POW", "POWpkix")
    [static]
```

Formats supported in this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 338 of file x509.py.

```
10.200.3.3 tuple rpki.x509.X509.pem_converter =
    PEM_converter("CERTIFICATE") [static]
```

PEM converter for this [object](#)

Reimplemented from [rpki.x509.DER\\_object](#)

Definition at line 339 of file x509.py.

#### 10.200.3.4 rpki.x509.X509.POW

Definition at line 362 of file x509.py.

#### 10.200.3.5 rpki.x509.X509.POWpkix

Definition at line 373 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

### 10.201 rpki.x509.XML\_CMS\_object Class Reference

Inherits [rpki::x509::CMS\\_object](#)

Inherited by [rpki.left\\_right.cms\\_msg](#) [rpki.publication.cms\\_msg](#) and [rpki.up\\_down.cms\\_msg](#)

#### Public Member Functions

- def [decode](#)
- def [dump\\_to\\_disk](#)
- def [encode](#)
- def [pretty\\_print\\_content](#)
- def [schema\\_check](#)
- def [unwrap](#)
- def [wrap](#)

#### Public Attributes

- [content](#)

### Static Public Attributes

- `dump_inbound_cms` None  
If set, we write all inbound XML-CMS PDUs to disk, for debugging.
- `dump_outbound_cms` None  
If set, we write all outbound XML-CMS PDUs to disk, for debugging.
- `tuplecontent_oid` POWify\_OID("id-ct-xml")

### 10.201.1 Detailed Description

Class to hold CMS-wrapped XML protocol data.

Definition at line 1025 of file x509.py.

### 10.201.2 Member Function Documentation

#### 10.201.2.1 def rpki.x509.XML\_CMS\_object.decode(self, xml)

Decode XML and set inner content.

Definition at line 1048 of file x509.py.

#### 10.201.2.2 def rpki.x509.XML\_CMS\_object.dump\_to\_disk(self, prefix)

Write DER of current message to disk, for debugging.

Definition at line 1066 of file x509.py.

#### 10.201.2.3 def rpki.x509.XML\_CMS\_object.encode(self)

Encode inner content for signing.

Definition at line 1044 of file x509.py.

#### 10.201.2.4 def rpki.x509.XML\_CMS\_object.pretty\_print\_content (self)

Pretty print XML content of this message.

Definition at line 1052 of file x509.py.

#### 10.201.2.5 def rpki.x509.XML\_CMS\_object.schema\_checks(self)

Handle XML RelaxNG schema check.

Definition at line 1056 of file x509.py.

#### 10.201.2.6 def rpki.x509.XML\_CMS\_object.unwrap (cls, der, ta, pretty\_print = False )

Unwrap a CMS-wrapped XML PDU and return Python objects.

Definition at line 1092 of file x509.py.

#### 10.201.2.7 def rpki.x509.XML\_CMS\_object.wrap (cls, msg, keypair, certs, crls = None, pretty\_print= False )

Build a CMS-wrapped XML PDU and return its DER encoding.

Definition at line 1075 of file x509.py.

### 10.201.3 Member Data Documentation

#### 10.201.3.1 rpki.x509.XML\_CMS\_object.content

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 1050 of file x509.py.

10.201.3.2 rpki::x509.XML\_CMS\_object::dump\_inbound\_cms = None  
[static]

If set, we write all inbound XML-CMS PDUs to disk, for debugging. If set, value should be [aDeadDropobject](#)

Definition at line 1042 of file x509.py.

10.201.3.3 rpki::x509.XML\_CMS\_object::dump\_outbound\_cms = None  
[static]

If set, we write all outbound XML-CMS PDUs to disk, for debugging. If set, value should be [aDeadDropobject](#)

Definition at line 1036 of file x509.py.

10.201.3.4 tuple rpki.x509.XML\_CMS\_object.econtent\_oid =  
POWify\_OID("id-ct-xml") [static]

Reimplemented from [rpki.x509.CMS\\_object](#)

Definition at line 1030 of file x509.py.

The documentation for this class was generated from the following file:

- [x509.py \(2928\)](#)

## 10.202 rpki.xml\_utils.base\_elt Class Reference

Inherits [object](#)

Inherited by [rpki.left\\_right.list\\_resources\\_elt](#) [rpki.left\\_right.list\\_roa\\_requests\\_elt](#) [rpki.publication.publication\\_object\\_elt](#) [rpki.xml\\_utils.data\\_elt](#) and [rpki.xml\\_utils.text\\_elt](#)

### Public Member Functions

- def [\\_\\_str\\_\\_](#)
- def [endElement](#)
- def [make\\_b64elt](#)
- def [make\\_elt](#)



- def [make\\_pdu](#)
- def [read\\_attrs](#)
- def [startElement](#)
- def [toXML](#)

#### Static Public Attributes

- tuple [attributes](#)= ()  
XML attributes for this element.
- tuple [booleans](#)= ()  
Boolean attributes (value "yes" or "no") for this element.
- tuple [elements](#)= ()  
XML elements contained by this element.

#### 10.202.1 Detailed Description

Virtual base class for XML message elements. The left-right and publication protocols use this. At least for now, the up-down protocol does not, due to different design assumptions.

Definition at line 126 of file `xml_utils.py`.

#### 10.202.2 Member Function Documentation

##### 10.202.2.1 def rpki.xml\_utils.base\_elt.\_\_str\_\_(self)

Convert a `base_elt` object to string format.

Reimplemented in [rpki.publication.report\\_error\\_elt](#)

Definition at line 201 of file `xml_utils.py`.

##### 10.202.2.2 def rpki.xml\_utils.base\_elt.endElements(self, stack, name, text)

Default `endElement()` handler: just pop the stack.

Reimplemented in [rpki.left\\_right.child\\_elt](#), [rpki.publication.client\\_elt](#), [rpki.publication.publication\\_object\\_elt](#), [rpki.xml\\_utils.text\\_elt](#) and [rpki.xml\\_utils.data\\_elt](#)

Definition at line 153 of file xml\_utils.py.

```
10.202.2.3 def rpki.xml_utils.base_elt.make_b64_elt(self, elt, name, value=
           None)
```

Constructor for Base64-encoded subelement.

Definition at line 192 of file xml\_utils.py.

```
10.202.2.4 def rpki.xml_utils.base_elt.make_elt(self)
```

XML element constructor.

Definition at line 178 of file xml\_utils.py.

```
10.202.2.5 def rpki.xml_utils.base_elt.make_pdu(self, kargs)
```

Generic PDU constructor.

Definition at line 208 of file xml\_utils.py.

```
10.202.2.6 def rpki.xml_utils.base_elt.read_attrs(self, attrs)
```

Template-driven attribute reader.

Definition at line 166 of file xml\_utils.py.

```
10.202.2.7 def rpki.xml_utils.base_elt.startElement(self, stack, name, attrs)
```

Default startElement() handler: just process attributes.

Reimplemented in [rpki.left\\_right.list\\_resources\\_elt](#), [rpki.left\\_right.list\\_roa\\_requests\\_elt](#), and [rpki.publication.cong\\_elt](#)

Definition at line 145 of file `xml_utils.py`.

#### 10.202.2.8 def rpki.xml\_utils.base\_elt.toXML (self)

Default toXML() element generator.

Reimplemented in [rpki.left\\_right.list\\_resources\\_elt](#), [rpki.publication.publication\\_object\\_elt](#), [rpki.xml\\_utils.text\\_elt](#), and [rpki.xml\\_utils.data\\_elt](#)

Definition at line 160 of file `xml_utils.py`.

### 10.202.3 Member Data Documentation

#### 10.202.3.1 rpki::xml\_utils.base\_elt::attributes = () [static]

XML attributes for this element.

Reimplemented in [rpki.left\\_right.self\\_elt](#), [rpki.left\\_right.bsc\\_elt](#), [rpki.left\\_right.repository\\_elt](#), [rpki.left\\_right.parent\\_elt](#), [rpki.left\\_right.child\\_elt](#), [rpki.left\\_right.list\\_resources\\_elt](#), [rpki.left\\_right.list\\_roa\\_requests\\_elt](#), [rpki.left\\_right.list\\_published\\_objects\\_elt](#), [rpki.left\\_right.report\\_error\\_elt](#), [rpki.publication.cong\\_elt](#), [rpki.publication.client\\_elt](#), [rpki.publication.publication\\_object\\_elt](#) and [rpki.publication.report\\_error\\_elt](#)

Definition at line 135 of file `xml_utils.py`.

#### 10.202.3.2 rpki::xml\_utils.base\_elt::booleans = () [static]

Boolean attributes (value "yes" or "no") for this element.

Reimplemented in [rpki.left\\_right.self\\_elt](#), [rpki.left\\_right.bsc\\_elt](#), [rpki.left\\_right.parent\\_elt](#) and [rpki.left\\_right.child\\_elt](#)

Definition at line 143 of file `xml_utils.py`.

#### 10.202.3.3 rpki::xml\_utils.base\_elt::elements = () [static]

XML elements contained by this element.

Reimplemented in [rpki.left\\_right.self\\_elt](#), [rpki.left\\_right.bsc\\_elt](#), [rpki.left\\_right.repository\\_elt](#), [rpki.left\\_right.parent\\_elt](#), [rpki.left\\_right.child\\_elt](#), [rpki.publication.config\\_elt](#) and [rpki.publication.client\\_elt](#)

Definition at line 139 of file `xml_utils.py`.

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 10.203 rpki.xml\_utils.data\_elt Class Reference

Inherits [rpki.xml\\_utils::base\\_elt](#)

Inherited by [rpki.left\\_right.data\\_elt](#) and [rpki.publication.control\\_elt](#)

### Public Member Functions

- [def endElement](#)
- [def make\\_reply](#)
- [def make\\_reply\\_clone\\_hook](#)
- [def serve\\_create](#)
- [def serve\\_destroy](#)
- [def serve\\_destroy\\_hook](#)
- [def serve\\_dispatch](#)
- [def serve\\_fetch\\_one](#)
- [def serve\\_get](#)
- [def serve\\_list](#)
- [def serve\\_post\\_save\\_hook](#)
- [def serve\\_pre\\_save\\_hook](#)
- [def serve\\_set](#)
- [def toXML](#)
- [def unimplemented\\_control](#)

### 10.203.1 Detailed Description

Virtual base class for PDUs that map to SQL objects. These objects all implement the create/set/get/list/destroy action attribute.

Definition at line 243 of file `xml_utils.py`.

## 10.203.2 Member Function Documentation

### 10.203.2.1 def rpki.xml\_utils.data\_elt.endElement(self, stack, name, text)

Default endElement handler for SQL-based objects. This assumes that sub-elements are Base64-encoded using the sql\_template mechanism.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Reimplemented in [rpki.left\\_right.child\\_elt](#) and [rpki.publication.client\\_elt](#)

Definition at line 249 of file xml\_utils.py.

### 10.203.2.2 def rpki.xml\_utils.data\_elt.make\_reply(self, r\_pdu = None)

Construct a reply PDU.

Definition at line 275 of file xml\_utils.py.

### 10.203.2.3 def rpki.xml\_utils.data\_elt.make\_reply\_clone\_hooks(self, r\_pdu)

Overridable hook.

Reimplemented in [rpki.left\\_right.data\\_elt](#)

Definition at line 292 of file xml\_utils.py.

### 10.203.2.4 def rpki.xml\_utils.data\_elt.serve\_create(self, r\_msg cb, eb)

Handle a create action.

Definition at line 314 of file xml\_utils.py.

### 10.203.2.5 def rpki.xml\_utils.data\_elt.serve\_destroy(self, r\_msg cb, eb)

Handle a destroy action.

Definition at line 384 of file xml\_utils.py.

10.203.2.6 def rpki.xml\_utils.data\_elt.serve\_destroy\_hooks(self, cb, eb)

Overridable hook.

Reimplemented in [rpki.left\\_right.child\\_elt](#)

Definition at line 378 of file xml\_utils.py.

10.203.2.7 def rpki.xml\_utils.data\_elt.serve\_dispatch(self, r\_msg cb, eb)

Action dispatch handler.

Reimplemented in [rpki.publication.control\\_elt](#)

Definition at line 395 of file xml\_utils.py.

10.203.2.8 def rpki.xml\_utils.data\_elt.serve\_fetch\_one(self)

Find the object on which a get, set, or destroy method should operate.

Definition at line 296 of file xml\_utils.py.

10.203.2.9 def rpki.xml\_utils.data\_elt.serve\_get(self, r\_msg cb, eb)

Handle a get action.

Definition at line 360 of file xml\_utils.py.

10.203.2.10 def rpki.xml\_utils.data\_elt.serve\_list(self, r\_msg cb, eb)

Handle a list action for non-self objects.

Definition at line 369 of file xml\_utils.py.

10.203.2.11 `def rpkg.xml_utils.data_elt.serve_post_save_hook(self, q_pdu, r_pdu, cb, eb)`

Overridable hook.

Reimplemented in [rpki.left\\_right.self\\_elt](#), [rpki.left\\_right.parent\\_elt](#), [rpki.left\\_right.child\\_elt](#), and [rpki.publication.client\\_elt](#)

Definition at line 310 of `le_xml_utils.py`.

10.203.2.12 `def rpkg.xml_utils.data_elt.serve_pre_save_hook(self, q_pdu, r_pdu, cb, eb)`

Overridable hook.

Reimplemented in [rpki.left\\_right.data\\_elt](#) and [rpki.left\\_right.bsc\\_elt](#)

Definition at line 306 of `le_xml_utils.py`.

10.203.2.13 `def rpkg.xml_utils.data_elt.serve_set(self, r_msg, cb, eb)`

Handle a set action.

Reimplemented in [rpki.publication.config\\_elt](#)

Definition at line 337 of `le_xml_utils.py`.

10.203.2.14 `def rpkg.xml_utils.data_elt.toXML (self)`

Default element generator for SQL-based objects. This assumes that sub-elements are Base64-encoded DER objects.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 263 of `le_xml_utils.py`.

10.203.2.15 def rpki.xml\_utils.data\_elt.unimplemented\_control(self, controls)

Uniform handling for unimplemented control operations.

Definition at line 408 of file xml\_utils.py.

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 10.204 rpki.xml\_utils.msg Class Reference

Inherits list.

Inherited by [rpki.left\\_right.msg](#) and [rpki.publication.msg](#)

### Public Member Functions

- def [\\_\\_str\\_\\_](#)
- def [endElement](#)
- def [is\\_query](#)
- def [is\\_reply](#)
- def [query](#)
- def [reply](#)
- def [startElement](#)
- def [toXML](#)

### Public Attributes

- [type](#)
- [version](#)

### 10.204.1 Detailed Description

Generic top-level PDU.

Definition at line 416 of file xml\_utils.py.



## 10.204.2 Member Function Documentation

### 10.204.2.1 def rpki.xml\_utils.msg.\_\_str\_\_(self)

Convert msg object to string.

Definition at line 442 of file xml\_utils.py.

### 10.204.2.2 def rpki.xml\_utils.msg.endElement(self, stack, name, text)

Handle top-level PDU.

Definition at line 434 of file xml\_utils.py.

### 10.204.2.3 def rpki.xml\_utils.msg.is\_query(self)

Is this msg a query?

Definition at line 468 of file xml\_utils.py.

### 10.204.2.4 def rpki.xml\_utils.msg.is\_reply(self)

Is this msg a reply?

Definition at line 472 of file xml\_utils.py.

### 10.204.2.5 def rpki.xml\_utils.msg.query(cls, args)

Create a query PDU.

Definition at line 455 of file xml\_utils.py.

### 10.204.2.6 def rpki.xml\_utils.msg.reply (cls, args)

Create a reply PDU.

Definition at line 462 of file xml\_utils.py.

### 10.204.2.7 def rpki.xml\_utils.msg.startElement (self, stack, name, attrs)

Handle top-level PDU.

Definition at line 421 of file xml\_utils.py.

### 10.204.2.8 def rpki.xml\_utils.msg.toXML (self)

Generate top-level PDU.

Definition at line 446 of file xml\_utils.py.

## 10.204.3 Member Data Documentation

### 10.204.3.1 rpki.xml\_utils.msg.type

Definition at line 427 of file xml\_utils.py.

### 10.204.3.2 rpki.xml\_utils.msg.version

Reimplemented in [rpki.left\\_right.msg](#) and [rpki.publication.msg](#)

Definition at line 426 of file xml\_utils.py.

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 10.205 rpki.xml\_utils.sax\_handler Class Reference

Inherits [xml::sax::handler::ContentHandler](#)

Inherited by [rpki.left\\_right.sax\\_handler](#), [rpki.publication.sax\\_handler](#), and [rpki.up\\_down.sax\\_handler](#)

### Public Member Functions

- [def \\_\\_init\\_\\_](#)
- [def characters](#)
- [def create\\_top\\_level](#)
- [def endElement](#)
- [def endElementNS](#)
- [def saxify](#)
- [def startElement](#)
- [def startElementNS](#)

### Public Attributes

- [result](#)
- [stack](#)
- [text](#)

### 10.205.1 Detailed Description

SAX handler for RPKI protocols.

This class provides some basic amenities for parsing protocol XML of the kind we use in the RPKI protocols, including whacking all the protocol element text into US-ASCII, simplifying accumulation of text fields, and hiding some of the fun relating to XML namespaces.

General assumption: by the time this parsing code gets invoked, the XML has already passed RelaxNG validation, so we only have to check for errors that the schema can't catch, and we don't have to play as many XML namespace games.

Definition at line 38 of file `xml_utils.py`.

### 10.205.2 Member Function Documentation

#### 10.205.2.1 `def rpki.xml_utils.sax_handler.__init__(self)`

Initialize SAX handler.

Definition at line 53 of file xml\_utils.py.

10.205.2.2 def rpki.xml\_utils.sax\_handler.characters(self, content)

Accumulate a chunk of element content (text).

Definition at line 69 of file xml\_utils.py.

10.205.2.3 def rpki.xml\_utils.sax\_handler.create\_top\_level(self, name, attrs)

Handle top-level PDU for this protocol.

Definition at line 119 of file xml\_utils.py.

10.205.2.4 def rpki.xml\_utils.sax\_handler.endElement(self, name)

Handle endElement() events. Mostly this means handling any accumulated element text.

Definition at line 101 of file xml\_utils.py.

10.205.2.5 def rpki.xml\_utils.sax\_handler.endElementNS(self, name, qname)

Redirect endElementNS() events to endElement().

Definition at line 65 of file xml\_utils.py.

10.205.2.6 def rpki.xml\_utils.sax\_handler.saxify(cls, elt)

Create a one-off SAX parser, parse an ETree, return the result.

Definition at line 111 of file xml\_utils.py.

### 10.205.2.7 def rpki.xml\_utils.sax\_handler.startElement(self, name, attrs)

Handle startElement() events.

We maintain a stack of nested elements under construction so that we can feed events directly to the current element rather than having to pass them through all the nesting elements.

If the stack is empty, this event is for the outermost element, so we call a virtual method to create the corresponding object and that's the object we'll be returning as our final result.

Definition at line 73 of file xml\_utils.py.

### 10.205.2.8 def rpki.xml\_utils.sax\_handler.startElementNS(self, name, qname, attrs)

Redirect startElementNS() events to startElement().

Definition at line 61 of file xml\_utils.py.

## 10.205.3 Member Data Documentation

### 10.205.3.1 rpki.xml\_utils.sax\_handler.result

Definition at line 97 of file xml\_utils.py.

### 10.205.3.2 rpki.xml\_utils.sax\_handler.stack

Definition at line 59 of file xml\_utils.py.

### 10.205.3.3 rpki.xml\_utils.sax\_handler.text

Definition at line 58 of file xml\_utils.py.

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 10.206 rpki.xml\_utils.text\_elt Class Reference

Inherits [rpki::xml\\_utils::base\\_elt](#)

Inherited by [rpki.left\\_right.list\\_published\\_objects\\_elt](#), [rpki.left\\_right.report\\_error\\_elt](#) and [rpki.publication.report\\_error\\_elt](#)

### Public Member Functions

- def [endElement](#)
- def [toXML](#)

### Static Public Attributes

- [text\\_attribute](#) = None  
Name of the class attribute that holds the text value.

#### 10.206.1 Detailed Description

Virtual base class for XML message elements that contain text.

Definition at line 219 of file `xml_utils.py`.

#### 10.206.2 Member Function Documentation

10.206.2.1 def `rpki.xml_utils.text_elt.endElement(self, stack, name, text)`

Extract text from parsed XML.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 228 of file `xml_utils.py`.

10.206.2.2 def `rpki.xml_utils.text_elt.toXML(self)`

Insert text into generated XML.

Reimplemented from [rpki.xml\\_utils.base\\_elt](#)

Definition at line 235 of file `xml_utils.py`.

## 10.206.3 Member Data Documentation

10.206.3.1 `rpki::xml_utils.text_elt::text_attribute = None` [static]

Name of the class attribute that holds the text value.

Reimplemented in [rpki.left\\_right.list\\_published\\_objects\\_elt](#), [rpki.left\\_right.report\\_error\\_elt](#) and [rpki.publication.report\\_error\\_elt](#)

Definition at line 226 of file `xml_utils.py`.

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 10.207 Sequence Class Reference

Inherited by [rpki.manifest.FileAndHash](#), [rpki.manifest.Manifest](#), [rpki.roa.ROAIPAddress](#), [rpki.roa.ROAIPAddressFamily](#) and [rpki.roa.RouteOriginAttestation](#)

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.208 SequenceOf Class Reference

Inherited by [rpki.manifest.FilesAndHashes](#), [rpki.roa.ROAIPAddresses](#) and [rpki.roa.ROAIPAddressFamilies](#)

The documentation for this class was generated from the following file:

- [roa.py \(2424\)](#)

## 10.209 TextWrapper Class Reference

Inherited by [irbe\\_cli.UsageWrapper](#)

The documentation for this class was generated from the following file:

- [irbe\\_cli.py \(2799\)](#)

## 10.210 ContentHandler Class Reference

Inherited by [rpki.xml\\_utils.sax\\_handler](#)

The documentation for this class was generated from the following file:

- [xml\\_utils.py \(2836\)](#)

## 11 File Documentation

### 11.1 \_\_init\_\_.py File Reference

Packages

- package [rpki](#)

### 11.2 async.py File Reference

Classes

- class [rpki.async.gc\\_summary](#)
- class [rpki.async.iterator](#)
- class [rpki.async.sync\\_wrapper](#)
- class [rpki.async.timer](#)

Packages

- package [rpki.async](#)

Functions

- def [rpki::async.\\_raiseExitNow](#)
- def [rpki::async.defer](#)
- def [rpki::async.event\\_loop](#)
- def [rpki::async.exit\\_event\\_loop](#)
- def [rpki::async.run\\_deferred](#)

Variables

- list [rpki::async.deferred\\_queue](#)  
List to hold deferred actions.



- `rpki::async.ExitNow` = `asyncore.ExitNow`

## 11.3 con g.py File Reference

### Classes

- class `rpki.con g.parser`

### Packages

- package `rpki.con g`

## 11.4 exceptions.py File Reference

### Classes

- class `rpki.exceptions.BadClassNameSyntax`
- class `rpki.exceptions.BadClientURL`
- class `rpki.exceptions.BadContactURL`
- class `rpki.exceptions.BadExtension`
- class `rpki.exceptions.BadIRDBReply`
- class `rpki.exceptions.BadIssueResponse`
- class `rpki.exceptions.BadPKCS10`
- class `rpki.exceptions.BadPublicationReply`
- class `rpki.exceptions.BadQuery`
- class `rpki.exceptions.BadSender`
- class `rpki.exceptions.BadStatusCode`
- class `rpki.exceptions.BadURISyntax`
- class `rpki.exceptions.BSCNotFound`
- class `rpki.exceptions.BSCNotReady`
- class `rpki.exceptions.ChildNotFound`
- class `rpki.exceptions.ClassNameMismatch`
- class `rpki.exceptions.ClassNameUnknown`
- class `rpki.exceptions.ClientNotFound`
- class `rpki.exceptions.CMSContentNotSet`
- class `rpki.exceptions.CMSCRLNotSet`
- class `rpki.exceptions.CMSVerificationFailed`
- class `rpki.exceptions.DBConsistencyError`
- class `rpki.exceptions.DEROBJECTConversionError`
- class `rpki.exceptions.DuplicateObject`
- class `rpki.exceptions.EmptyPEM`

- class [rpki.exceptions.EmptyROAPre xList](#)
- class [rpki.exceptions.ForbiddenURI](#)
- class [rpki.exceptions.HandleTranslationError](#)
- class [rpki.exceptions.HTTPRequestFailed](#)
- class [rpki.exceptions.HTTPSBadVersion](#)
- class [rpki.exceptions.HTTPSClientAborted](#)
- class [rpki.exceptions.HTTPSUnexpectedState](#)
- class [rpki.exceptions.MissingCMSCRL](#)
- class [rpki.exceptions.MissingCMSEECert](#)
- class [rpki.exceptions.MultipleTLSEECert](#)
- class [rpki.exceptions.MustBePre x](#)
- class [rpki.exceptions.NoActiveCA](#)
- class [rpki.exceptions.NoCoveringCertForROA](#)
- class [rpki.exceptions.NoObjectAtURI](#)
- class [rpki.exceptions.NotACertificateChain](#)
- class [rpki.exceptions.NotFound](#)
- class [rpki.exceptions.NotImplementedYet](#)
- class [rpki.exceptions.NotInDatabase](#)
- class [rpki.exceptions.ReceivedTLSCACert](#)
- class [rpki.exceptions.RPKI\\_Exception](#)
- class [rpki.exceptions.ServerShuttingDown](#)
- class [rpki.exceptions.SKIMismatch](#)
- class [rpki.exceptions.SubprocessError](#)
- class [rpki.exceptions.TLSValidationError](#)
- class [rpki.exceptions.UnexpectedCMSCerts](#)
- class [rpki.exceptions.UnexpectedCMSCRLs](#)
- class [rpki.exceptions.UnparsableCMSDER](#)
- class [rpki.exceptions.UpstreamError](#)
- class [rpki.exceptions.WrongEContentType](#)

#### Packages

- package [rpki.exceptions](#)

## 11.5 https.py File Reference

#### Classes

- class [rpki.https.http\\_client](#)
- class [rpki.https.http\\_listener](#)
- class [rpki.https.http\\_message](#)
- class [rpki.https.http\\_queue](#)

- class [rpki.https.http\\_request](#)
- class [rpki.https.http\\_response](#)
- class [rpki.https.http\\_server](#)
- class [rpki.https.http\\_stream](#)

#### Packages

- package [rpki.https](#)

#### Functions

- def [rpki::https.build\\_https\\_ta\\_cache](#)
- def [rpki::https.client](#)
- def [rpki::https.log\\_method](#)
- def [rpki::https.server](#)

#### Variables

- dictionary [rpki::https.client\\_queues](#) {}
- [rpki::https.debug\\_http](#) = False
- [rpki::https.debug\\_tls\\_certs](#) = False
- tuple [rpki::https.default\\_client\\_timeout](#) = [rpki.sundial.timedelta\(minutes = 15\)](#)
- tuple [rpki::https.default\\_http\\_version](#) = (1, 0)
- tuple [rpki::https.default\\_server\\_timeout](#) = [rpki.sundial.timedelta\(minutes = 20\)](#)
- string [rpki::https.rpki\\_content\\_type](#) = "application/x-rpki"
- [rpki::https.want\\_persistent\\_client](#) = False
- [rpki::https.want\\_persistent\\_server](#) = False

## 11.6 ipaddrs.py File Reference

#### Classes

- class [rpki.ipaddrs.v4addr](#)
- class [rpki.ipaddrs.v6addr](#)

#### Packages

- package [rpki.ipaddrs](#)

## 11.7 irbe\_cli.py File Reference

### Classes

- class [irbe\\_cli.bsc\\_elt](#)
- class [irbe\\_cli.caller](#)
- class [irbe\\_cli.certificate\\_elt](#)
- class [irbe\\_cli.child\\_elt](#)
- class [irbe\\_cli.client\\_elt](#)
- class [irbe\\_cli.cmd\\_elt\\_mixin](#)
- class [irbe\\_cli.cmd\\_msg\\_mixin](#)
- class [irbe\\_cli.config\\_elt](#)
- class [irbe\\_cli.crl\\_elt](#)
- class [irbe\\_cli.left\\_right\\_cms\\_msg](#)
- class [irbe\\_cli.left\\_right\\_msg](#)
- class [irbe\\_cli.left\\_right\\_sax\\_handler](#)
- class [irbe\\_cli.list\\_published\\_objects\\_elt](#)
- class [irbe\\_cli.manifest\\_elt](#)
- class [irbe\\_cli.parent\\_elt](#)
- class [irbe\\_cli.publication\\_cms\\_msg](#)
- class [irbe\\_cli.publication\\_msg](#)
- class [irbe\\_cli.publication\\_sax\\_handler](#)
- class [irbe\\_cli.reply\\_elt\\_mixin](#)
- class [irbe\\_cli.report\\_error\\_elt](#)
- class [irbe\\_cli.report\\_error\\_elt](#)
- class [irbe\\_cli.repository\\_elt](#)
- class [irbe\\_cli.roa\\_elt](#)
- class [irbe\\_cli.self\\_elt](#)
- class [irbe\\_cli.UsageWrapper](#)

### Packages

- package [irbe\\_cli](#)

### Functions

- def [irbe\\_cli.usage](#)

## Variables

- list `irbe_cli.argv`= sys.argv[1:]
- tuple `irbe_cli.call_pubd`
- tuple `irbe_cli.call_rpkid`
- tuple `irbe_cli.cfg`= `rpki.config.parse`(`cfg_le`, "irbe\_cli")
- string `irbe_cli.cfg_le` = "irbe.conf"
- `irbe_cli.pem_out`= None
- `irbe_cli.q_msg`= `q_msg_left_right`
- tuple `irbe_cli.q_msg_left_right`= `left_right_msg.query`()
- tuple `irbe_cli.q_msg_publication`= `publication_msg.query`()
- list `irbe_cli.q_pdu`= `left_right_msg.pdus`[argv[0]]
- list `irbe_cli.top_opts`= ["con g=", "help", "pem\_out=", "quiet", "verbose"]
- tuple `irbe_cli.usage_ll`= `UsageWrapper`(`subsequent_indent`="4")
- `irbe_cli.verbose`= True

## 11.8 irdbd.py File Reference

## Packages

- package `irdbd`

## Functions

- def `irdbd.handle_list_resources`
- def `irdbd.handle_list_roa_requests`
- def `irdbd.handler`

## Variables

- tuple `irdbd.bpki_ta`= `rpki.x509.X509`(`Auto_le` = `cfg.get`("bpki-ta"))
- tuple `irdbd.cfg`= `rpki.config.parse`(`cfg_le`, "irdbd")
- string `irdbd.cfg_le` = "irdbd.conf"
- tuple `irdbd.client_ta`= (`bpki_ta`, `rpkid_cert`)
- tuple `irdbd.cur`= `db.cursor`()
- tuple `irdbd.db`
- dictionary `irdbd.handle_dispatch`
- tuple `irdbd.handlers`= ((`u.path`, `handler`),)
- string `irdbd.host`= "localhost"
- tuple `irdbd.irdbd_cert`= `rpki.x509.X509`(`Auto_le` = `cfg.get`("irdbd-cert"))
- tuple `irdbd.irdbd_key`= `rpki.x509.RSA`(`Auto_le` = `cfg.get`("irdbd-key"))
- int `irdbd.port`= 443

- tuple `irdbd.rpkid_cert` = `rpki.x509.X509`(Auto\_ le = `cfg.get("rpkid-cert")`)
- `irdbd.server_cert` = `irdbd_cert`,
- tuple `irdbd.startup_msg` = `cfg.get("startup-message", "")`
- tuple `irdbd.u` = `urlparse.urlparse(cfg.get("https-url"))`

## 11.9 left\_right.py File Reference

### Classes

- class `rpki.left_right.bsc_elt`
- class `rpki.left_right.child_elt`
- class `rpki.left_right.cms_msg`
- class `rpki.left_right.data_elt`
- class `rpki.left_right.left_right_namespace`
- class `rpki.left_right.list_published_objects_elt`
- class `rpki.left_right.list_resources_elt`
- class `rpki.left_right.list_roa_requests_elt`
- class `rpki.left_right.msg`
- class `rpki.left_right.parent_elt`
- class `rpki.left_right.report_error_elt`
- class `rpki.left_right.repository_elt`
- class `rpki.left_right.sax_handler`
- class `rpki.left_right.self_elt`

### Packages

- package `rpki.left_right`

### Variables

- `rpki::left_right.enforce_strict_up_down_xml_send` = `False`

## 11.10 log.py File Reference

### Classes

- class `rpki.log.logger`

### Packages

- package `rpki.log`

### Functions

- def `rpki::log.init`
- def `rpki::log.set_trace`
- def `rpki::log.trace`
- def `rpki::log.traceback`

### Variables

- tuple `rpki::log.debug`= `logger(syslog.LOG_DEBUG)`
- `rpki::log.enable_trace` False  
Whether call tracing is enabled.
- tuple `rpki::log.error`= `logger(syslog.LOG_ERR)`
- tuple `rpki::log.info`= `logger(syslog.LOG_INFO)`
- tuple `rpki::log.note`= `logger(syslog.LOG_NOTICE)`
- int `rpki::log.pid`= 0
- string `rpki::log.tag`= ""
- `rpki::log.use_syslog` True  
Whether to use syslog.
- tuple `rpki::log.warn`= `logger(syslog.LOG_WARNING)`

## 11.11 manifest.py File Reference

### Classes

- class `rpki.manifest.FileAndHash`
- class `rpki.manifest.FilesAndHashes`
- class `rpki.manifest.Manifest`

### Packages

- package `rpki.manifest`

## 11.12 oids.py File Reference

### Packages

- package `rpki.oids`

## Variables

- tuple `rpki::oids.name2oid` = dict((v, k) for k, v in oid2name.items())  
Mapping table of string names to OIDs.
- dictionary `rpki::oids.oid2name`  
Mapping table of OIDs to conventional string names.

## 11.13 pubd.py File Reference

## Classes

- class `pubd.pubd_context`

## Packages

- package `pubd`

## Functions

- def `pubd.main`

## Variables

- string `pubd.cfg_le` = "pubd.conf"
- `pubd.pro le` = False

## 11.14 publication.py File Reference

## Classes

- class `rpki.publication.certificate_elt`
- class `rpki.publication.client_elt`
- class `rpki.publication.cms_msg`
- class `rpki.publication.cong_elt`
- class `rpki.publication.control_elt`
- class `rpki.publication.crl_elt`
- class `rpki.publication.manifest_elt`
- class `rpki.publication.msg`
- class `rpki.publication.publication_namespace`



- class [rpki.publication.publication\\_object\\_elt](#)
- class [rpki.publication.report\\_error\\_elt](#)
- class [rpki.publication.roa\\_elt](#)
- class [rpki.publication.sax\\_handler](#)

#### Packages

- package [rpki.publication](#)

## 11.15 relaxng.py File Reference

#### Packages

- package [rpki.relaxng](#)

#### Variables

- tuple [rpki::relaxng.left\\_right](#)  
Parsed RelaxNG [left\\_right](#) schema.
- tuple [rpki::relaxng.publication](#)  
Parsed RelaxNG [publication](#) schema.
- tuple [rpki::relaxng.up\\_down](#)  
Parsed RelaxNG [up\\_down](#) schema.

## 11.16 resource\_set.py File Reference

#### Classes

- class [rpki.resource\\_set.resource\\_bag](#)
- class [rpki.resource\\_set.resource\\_range](#)
- class [rpki.resource\\_set.resource\\_range\\_as](#)
- class [rpki.resource\\_set.resource\\_range\\_ip](#)
- class [rpki.resource\\_set.resource\\_range\\_ipv4](#)
- class [rpki.resource\\_set.resource\\_range\\_ipv6](#)
- class [rpki.resource\\_set.resource\\_set](#)
- class [rpki.resource\\_set.resource\\_set\\_as](#)
- class [rpki.resource\\_set.resource\\_set\\_ip](#)
- class [rpki.resource\\_set.resource\\_set\\_ipv4](#)

- class [rpki.resource\\_set.resource\\_set\\_ipv6](#)
- class [rpki.resource\\_set.roa\\_pre\\_x](#)
- class [rpki.resource\\_set.roa\\_pre\\_x\\_ipv4](#)
- class [rpki.resource\\_set.roa\\_pre\\_x\\_ipv6](#)
- class [rpki.resource\\_set.roa\\_pre\\_x\\_set](#)
- class [rpki.resource\\_set.roa\\_pre\\_x\\_set\\_ipv4](#)
- class [rpki.resource\\_set.roa\\_pre\\_x\\_set\\_ipv6](#)

#### Packages

- package [rpki.resource\\_set](#)

#### Functions

- def [rpki::resource\\_set.\\_bs2long](#)
- def [rpki::resource\\_set.\\_long2bs](#)
- def [rpki::resource\\_set.\\_rsplit](#)
- def [rpki::resource\\_set.test1](#)
- def [rpki::resource\\_set.test2](#)

#### Variables

- string [rpki::resource\\_set.inherit\\_token](#) "<inherit>"  
Token used to indicate inheritance in read and print syntax.

## 11.17 roa.py File Reference

#### Classes

- class [rpki.roa.ROAIPAddress](#)
- class [rpki.roa.ROAIPAddresses](#)
- class [rpki.roa.ROAIPAddressFamilies](#)
- class [rpki.roa.ROAIPAddressFamily](#)
- class [rpki.roa.RouteOriginAttestation](#)

#### Packages

- package [rpki.roa](#)

## 11.18 rootd.py File Reference

### Classes

- class [rootd.cms\\_msg](#)
- class [rootd.issue\\_pdu](#)
- class [rootd.list\\_pdu](#)
- class [rootd.message\\_pdu](#)
- class [rootd.revoke\\_pdu](#)
- class [rootd.sax\\_handler](#)

### Packages

- package [rootd](#)

### Functions

- def [rootd.compose\\_response](#)
- def [rootd.del\\_subject\\_cert](#)
- def [rootd.del\\_subject\\_pkcs10](#)
- def [rootd.get\\_root\\_cert](#)
- def [rootd.get\\_subject\\_cert](#)
- def [rootd.get\\_subject\\_pkcs10](#)
- def [rootd.issue\\_subject\\_cert\\_maybe](#)
- def [rootd.root\\_newer\\_than\\_subject](#)
- def [rootd.set\\_subject\\_cert](#)
- def [rootd.set\\_subject\\_pkcs10](#)
- def [rootd.up\\_down\\_handler](#)

### Variables

- tuple [rootd.bpki\\_ta](#) = [rpki.x509.X509](#)(Auto\_ le = [cfg.get](#)("bpki-ta"))
- tuple [rootd.cfg](#) = [rpki.config.parse](#)([cfg\\_ le](#), "rootd")
- string [rootd.cfg\\_ le](#) = "rootd.conf"
- tuple [rootd.child\\_bpki\\_cert](#) = [rpki.x509.X509](#)(Auto\_ le = [cfg.get](#)("child-bpki-cert"))
- tuple [rootd.client\\_ta](#) = ([bpki\\_ta](#), [child\\_bpki\\_cert](#))
- [rootd.handlers](#) = [up\\_down\\_handler](#)
- [rootd.host](#) = [https\\_server\\_host](#),
- tuple [rootd.https\\_server\\_host](#) = [cfg.get](#)("server-host", "")
- tuple [rootd.https\\_server\\_port](#) = [int](#)([cfg.get](#)("server-port"))
- [rootd.port](#) = [https\\_server\\_port](#),

- tuple `rootd.rootd_bpki_cert` = `rpki.x509.X509`(Auto\_le = `cfg.get("rootd-bpki-cert")`)
- tuple `rootd.rootd_bpki_crl` = `rpki.x509.CRL`(Auto\_le = `cfg.get("rootd-bpki-crl")`)
- tuple `rootd.rootd_bpki_key` = `rpki.x509.RSA`(Auto\_le = `cfg.get("rootd-bpki-key")`)
- tuple `rootd.rpki_base_uri` = `cfg.get("rpki-base-uri", "rsync:///" + rpki_class_name + ".invalid/")`
- tuple `rootd.rpki_class_name` = `cfg.get("rpki-class-name", "wombat")`
- `rootd.rpki_root_cert` = None
- tuple `rootd.rpki_root_cert_le` = `cfg.get("rpki-root-cert")`
- tuple `rootd.rpki_root_cert_uri` = `cfg.get("rpki-root-cert-uri", rpki_base_uri + "Root.cer")`
- tuple `rootd.rpki_root_crl` = `cfg.get("rpki-root-crl", "Root.crl")`
- tuple `rootd.rpki_root_dir` = `cfg.get("rpki-root-dir")`
- tuple `rootd.rpki_root_key` = `rpki.x509.RSA`(Auto\_le = `cfg.get("rpki-root-key")`)
- tuple `rootd.rpki_root_manifest` = `cfg.get("rpki-root-manifest", "Root.mnf")`
- tuple `rootd.rpki_subject_cert` = `cfg.get("rpki-subject-cert", "Child.cer")`
- tuple `rootd.rpki_subject_lifetime` = `rpki.sundial.timedelta.parse(cfg.get("rpki-subject-lifetime", "30d"))`
- tuple `rootd.rpki_subject_pkcs10` = `cfg.get("rpki-subject-pkcs10", "Child.pkcs10")`
- tuple `rootd.rpki_subject_regen` = `rpki.sundial.timedelta.parse(cfg.get("rpki-subject-regen", rpki_subject_lifetime.convert_to_seconds() / 2))`
- `rootd.server_cert` = `rootd_bpki_cert`,

## 11.19 rpki\_engine.py File Reference

### Classes

- class `rpki.rpki_engine.ca_detail_obj`
- class `rpki.rpki_engine.ca_obj`
- class `rpki.rpki_engine.child_cert_obj`
- class `rpki.rpki_engine.publication_queue`
- class `rpki.rpki_engine.revoked_cert_obj`
- class `rpki.rpki_engine.roa_obj`
- class `rpki.rpki_engine.rpkid_context`

### Packages

- package `rpki.rpki_engine`

## 11.20 rpkid.py File Reference

### Packages

- package [rpkid](#)

### Functions

- def [rpkid.main](#)

### Variables

- string [rpkid.cfg\\_le](#) = "rpkid.conf"
- [rpkid.pro le](#) = None

## 11.21 sql.py File Reference

### Classes

- class [rpk.sql.session](#)
- class [rpk.sql.sql\\_persistent](#)
- class [rpk.sql.template](#)

### Packages

- package [rpk.sql](#)

## 11.22 sundial.py File Reference

### Classes

- class [rpk.sundial.datetime](#)
- class [rpk.sundial.timedelta](#)

### Packages

- package [rpk.sundial](#)

## Functions

- def `rpki::sundial._cast`
- def `rpki::sundial.now`
- def `rpki::sundial.test`

## 11.23 up\_down.py File Reference

## Classes

- class `rpki.up_down.base_elt`
- class `rpki.up_down.certificate_elt`
- class `rpki.up_down.class_elt`
- class `rpki.up_down.class_response_syntax`
- class `rpki.up_down.cms_msg`
- class `rpki.up_down.error_response_pdu`
- class `rpki.up_down.issue_pdu`
- class `rpki.up_down.issue_response_pdu`
- class `rpki.up_down.list_pdu`
- class `rpki.up_down.list_response_pdu`
- class `rpki.up_down.message_pdu`
- class `rpki.up_down.multi_uri`
- class `rpki.up_down.revoke_pdu`
- class `rpki.up_down.revoke_response_pdu`
- class `rpki.up_down.revoke_syntax`
- class `rpki.up_down.sax_handler`

## Packages

- package `rpki.up_down`

## Variables

- dictionary `rpki::up_down.nsmap` { None : xmlns }
- string `rpki::up_down.xmlns` = "http://www.apnic.net/specs/rescerts/up-down/"

## 11.24 x509.py File Reference

## Classes

- class `rpki.x509.CMS_object`
- class `rpki.x509.CRL`

- class [rpki.x509.DeadDrop](#)
- class [rpki.x509.DER\\_CMS\\_object](#)
- class [rpki.x509.DER\\_object](#)
- class [rpki.x509.PEM\\_converter](#)
- class [rpki.x509.PKCS10](#)
- class [rpki.x509.ROA](#)
- class [rpki.x509.RSA](#)
- class [rpki.x509.RSAPublic](#)
- class [rpki.x509.SignedManifest](#)
- class [rpki.x509.X509](#)
- class [rpki.x509.XML\\_CMS\\_object](#)

#### Packages

- package [rpki.x509](#)

#### Functions

- def [rpki::x509.calculate\\_SKI](#)
- def [rpki::x509.POWify\\_OID](#)

## 11.25 xml\_utils.py File Reference

#### Classes

- class [rpki.xml\\_utils.base\\_elt](#)
- class [rpki.xml\\_utils.data\\_elt](#)
- class [rpki.xml\\_utils.msg](#)
- class [rpki.xml\\_utils.sax\\_handler](#)
- class [rpki.xml\\_utils.text\\_elt](#)

#### Packages

- package [rpki.xml\\_utils](#)

## Index

\_\_abs\_\_  
    rpki::sundial::timedelta [330](#)

\_\_add\_\_  
    rpki::sundial::datetime [325](#)  
    rpki::sundial::timedelta [330](#)

\_\_call\_\_  
    irbe\_cli::caller, [98](#)  
    irbe\_cli::UsageWrapper, [113](#)  
    rpki::async::iterator, [125](#)  
    rpki::async::sync\_wrapper, [127](#)  
    rpki::log::logger, [221](#)

\_\_cmp\_\_  
    rpki::async::timer, [130](#)  
    rpki::resource\_set::resource\_range,  
        [251](#)  
    rpki::resource\_set::roa\_pre\_x, [265](#)  
    rpki::x509::DER\_object, [372](#)

\_\_del\_\_  
    rpki::async::timer, [130](#)

\_\_div\_\_  
    rpki::sundial::timedelta [330](#)

\_\_eq\_\_  
    rpki::resource\_set::resource\_bag,  
        [247](#)

\_\_oordiv\_\_  
    rpki::sundial::timedelta [330](#)

\_\_init\_\_  
    irbe\_cli::caller, [98](#)  
    pubd::pubd\_context, [115](#)  
    rpki::async::gc\_summary, [123](#)  
    rpki::async::iterator, [125](#)  
    rpki::async::sync\_wrapper, [127](#)  
    rpki::async::timer, [130](#)  
    rpki::con\_g::parser, [134](#)  
    rpki::https::http\_client, [156](#)  
    rpki::https::http\_listener, [160](#)  
    rpki::https::http\_message, [163](#)  
    rpki::https::http\_queue, [165](#)  
    rpki::https::http\_request, [168](#)  
    rpki::https::http\_response, [169](#)  
    rpki::https::http\_server, [171](#)  
    rpki::https::http\_stream, [175](#)  
    rpki::log::logger, [221](#)  
    rpki::manifest::FileAndHash, [222](#)  
    rpki::manifest::FilesAndHashes, [223](#)  
    rpki::manifest::Manifest, [224](#)  
    rpki::resource\_set::resource\_bag,  
        [247](#)  
    rpki::resource\_set::resource\_range,  
        [251](#)  
    rpki::resource\_set::resource\_set, [257](#)  
    rpki::resource\_set::roa\_pre\_x, [266](#)  
    rpki::resource\_set::roa\_pre\_x\_set,  
        [269](#)  
    rpki::roa::ROAIPAddress, [273](#)  
    rpki::roa::ROAIPAddresses, [274](#)  
    rpki::roa::ROAIPAddressFamilies,  
        [275](#)  
    rpki::roa::ROAIPAddressFamily,  
        [275](#)  
    rpki::roa::RouteOriginAttestation,  
        [276](#)  
    rpki::rpki\_engine::child\_cert\_obj,  
        [292](#)  
    rpki::rpki\_engine::publication\_  
        queue, [296](#)  
    rpki::rpki\_engine::revoked\_cert\_obj,  
        [298](#)  
    rpki::rpki\_engine::roa\_obj, [301](#)  
    rpki::rpki\_engine::rpkid\_context,  
        [307](#)  
    rpki::sql::session, [313](#)  
    rpki::sql::template, [323](#)  
    rpki::up\_down::class\_elt, [338](#)  
    rpki::up\_down::class\_response\_  
        syntax, [341](#)  
    rpki::up\_down::error\_response\_pdu,  
        [343](#)  
    rpki::up\_down::multi\_uri, [354](#)  
    rpki::x509::DeadDrop, [368](#)  
    rpki::x509::DER\_object, [372](#)  
    rpki::x509::PEM\_convert, [378](#)  
    rpki::xml\_utils::sax\_handler, [409](#)  
\_\_init\_\_.py(2937), [414](#)



---

- \_\_mul\_\_
  - rpki::sundial::timedelta [330](#)
- \_\_ne\_\_
  - rpki::resource\_set::resource\_bag, [248](#)
- \_\_neg\_\_
  - rpki::sundial::timedelta [330](#)
- \_\_new\_\_
  - rpki::ipaddrs::v4addr, [180](#)
  - rpki::ipaddrs::v6addr, [181](#)
- \_\_pos\_\_
  - rpki::sundial::timedelta [330](#)
- \_\_radd\_\_
  - rpki::sundial::datetime [325](#)
  - rpki::sundial::timedelta [330](#)
- \_\_rdiv\_\_
  - rpki::sundial::timedelta [331](#)
- \_\_repr\_\_
  - rpki::async::iterator, [125](#)
  - rpki::async::timer, [130](#)
- \_\_r oordiv\_\_
  - rpki::sundial::timedelta [331](#)
- \_\_rmul\_\_
  - rpki::sundial::timedelta [331](#)
- \_\_rsub\_\_
  - rpki::sundial::datetime [325](#)
  - rpki::sundial::timedelta [331](#)
- \_\_str\_\_
  - rpki::https::http\_message, [163](#)
  - rpki::ipaddrs::v4addr, [180](#)
  - rpki::ipaddrs::v6addr, [181](#)
  - rpki::publication::report\_error\_elt, [243](#)
  - rpki::resource\_set::resource\_bag, [248](#)
  - rpki::resource\_set::resource\_range\_addresses, [252](#)
  - rpki::resource\_set::resource\_range\_ip, [254](#)
  - rpki::resource\_set::resource\_set, [267](#)
  - rpki::resource\_set::roa\_pre, [266](#)
  - rpki::resource\_set::roa\_pre\_x\_set, [269](#)
  - rpki::sundial::datetime [325](#)
  - rpki::up\_down::message\_packet, [351](#)
  - rpki::up\_down::multi\_uri, [354](#)
  - rpki::xml\_utils::base\_elt, [399](#)
  - rpki::xml\_utils::msg, [407](#)
- \_\_sub\_\_
  - rpki::sundial::datetime [325](#)
  - rpki::sundial::timedelta [331](#)
- \_add
  - rpki::rpki\_engine::publication\_queue, [296](#)
- \_bs2long
  - rpki::resource\_set, [83](#)
- \_cast
  - rpki::sundial, [88](#)
- \_comm
  - rpki::resource\_set::resource\_set, [267](#)
- \_exceptions\_enabled
  - rpki::sql::session, [315](#)
- \_get\_wrapper
  - rpki::con g::parser, [134](#)
- \_long2bs
  - rpki::resource\_set, [83](#)
- \_pre\_xlen
  - rpki::resource\_set::resource\_range\_ip, [254](#)
- \_raiseExitNow
  - rpki::async, [64](#)
- \_rsplit
  - rpki::resource\_set, [83](#)
- \_wrap\_execute
  - rpki::sql::session, [313](#)
- activate
  - rpki::rpki\_engine::ca\_detail\_obj, [279](#)
- address
  - rpki::roa::ROAIPAddress, [273](#)
- addresses
  - rpki::roa::ROAIPAddressFamily, [276](#)
- addressFamily
  - rpki::roa::ROAIPAddressFamily, [276](#)
- a
  - rpki::resource\_set::resource\_set\_ip4, [263](#)
  - rpki::resource\_set::resource\_set\_ip6, [264](#)

- argv
  - irbe\_cli, [47](#)
- asID
  - rpki::roa::RouteOriginAttestation, [277](#)
- asn
  - rpki::left\_right::list\_resources\_elt, [198](#)
  - rpki::resource\_set::resource\_bag, [249](#)
  - rpki::rpki\_engine::roa\_obj, [304](#)
- assert\_pristine
  - rpki::sql::session, [313](#)
- async.py(2926), [414](#)
- asynchat::async\_chat, [35](#)
- asyncore::dispatcher, [95](#)
- attributes
  - rpki::left\_right::bsc\_elt, [184](#)
  - rpki::left\_right::child\_elt, [188](#)
  - rpki::left\_right::list\_published\_objects\_elt, [196](#)
  - rpki::left\_right::list\_resources\_elt, [198](#)
  - rpki::left\_right::list\_roa\_requests\_elt, [200](#)
  - rpki::left\_right::parent\_elt, [205](#)
  - rpki::left\_right::report\_error\_elt, [208](#)
  - rpki::left\_right::repository\_elt, [211](#)
  - rpki::left\_right::self\_elt, [219](#)
  - rpki::publication::client\_elt, [228](#)
  - rpki::publication::con\_g\_elt, [233](#)
  - rpki::publication::publication\_object\_elt, [241](#)
  - rpki::publication::report\_error\_elt, [243](#)
  - rpki::xml\_utils::base\_elt, [401](#)
- b
  - rpki::x509::PEM\_convert, [378](#)
- base\_uri
  - rpki::publication::client\_elt, [228](#)
- bits
  - rpki::ipaddrs::v4addr, [180](#)
  - rpki::ipaddrs::v6addr, [182](#)
- body
  - rpki::https::http\_message, [464](#)
- booleans
  - rpki::left\_right::bsc\_elt, [184](#)
  - rpki::left\_right::child\_elt, [188](#)
  - rpki::left\_right::parent\_elt, [205](#)
  - rpki::left\_right::self\_elt, [219](#)
  - rpki::xml\_utils::base\_elt, [401](#)
- bpki\_cert
  - irbe\_cli::cmd\_elt\_mixin, [102](#)
  - rpki::left\_right::child\_elt, [189](#)
  - rpki::left\_right::repository\_elt, [211](#)
  - rpki::left\_right::self\_elt, [219](#)
  - rpki::publication::client\_elt, [228](#)
- bpki\_cms\_cert
  - irbe\_cli::cmd\_elt\_mixin, [102](#)
  - rpki::left\_right::parent\_elt, [205](#)
- bpki\_cms\_glue
  - irbe\_cli::cmd\_elt\_mixin, [102](#)
  - rpki::left\_right::parent\_elt, [206](#)
- bpki\_crl
  - irbe\_cli::con\_g\_elt, [105](#)
- bpki\_glue
  - irbe\_cli::cmd\_elt\_mixin, [103](#)
  - rpki::left\_right::child\_elt, [189](#)
  - rpki::left\_right::repository\_elt, [211](#)
  - rpki::left\_right::self\_elt, [219](#)
  - rpki::publication::client\_elt, [229](#)
- bpki\_https\_cert
  - irbe\_cli::cmd\_elt\_mixin, [103](#)
  - rpki::left\_right::parent\_elt, [206](#)
- bpki\_https\_glue
  - irbe\_cli::cmd\_elt\_mixin, [103](#)
  - rpki::left\_right::parent\_elt, [206](#)
- bpki\_ta
  - irbdb, [51](#)
  - pubd::pubd\_context, [116](#)
  - rootd, [58](#)
  - rpki::rpki\_engine::rpkid\_context, [309](#)
- bsc
  - rpki::left\_right::data\_elt, [192](#)
- bscs
  - rpki::left\_right::self\_elt, [215](#)
- buffer
  - rpki::https::http\_stream, [178](#)
- build
  - rpki::x509::ROA, [382](#)

- rpki::x509::SignedManifest, 389
- build\_https\_ta\_cache
  - pubd::pubd\_context, 15
  - rpki::https, 69
  - rpki::rpki\_engine::rpkid\_context, 307
- ca
  - rpki::rpki\_engine::ca\_detail\_obj, 279
- ca\_cert\_uri
  - rpki::rpki\_engine::ca\_detail\_obj, 283
- ca\_detail
  - rpki::rpki\_engine::child\_cert\_obj, 292
  - rpki::rpki\_engine::revoked\_cert\_obj, 298
  - rpki::rpki\_engine::roa\_obj, 301
- ca\_detail\_id
  - rpki::rpki\_engine::child\_cert\_obj, 294
  - rpki::rpki\_engine::revoked\_cert\_obj, 299
  - rpki::rpki\_engine::roa\_obj, 304
- ca\_details
  - rpki::rpki\_engine::ca\_obj, 287
- ca\_from\_class\_name
  - rpki::left\_right::child\_elt, 187
- ca\_id
  - rpki::rpki\_engine::ca\_detail\_obj, 283
- cache
  - rpki::sql::session, 315
- cache\_clear
  - rpki::sql::session, 314
- calculate\_SKI
  - rpki::x509, 92
- call\_pubd
  - irbe\_cli, 47
  - rpki::left\_right::repository\_elt, 210
  - rpki::rpki\_engine::publication\_queue, 296
- call\_rpkid
  - irbe\_cli, 47
- callback
  - rpki::https::http\_request, 168
- caller\_function
  - rpki::async::iterator, 126
- cancel
  - rpki::async::timer, 130
- cas
  - rpki::left\_right::parent\_elt, 204
- cb
  - rpki::async::sync\_wrapper, 127
- cert
  - rpki::https::http\_client, 158
  - rpki::https::http\_listener, 161
  - rpki::https::http\_queue, 166
  - rpki::rpki\_engine::child\_cert\_obj, 294
  - rpki::rpki\_engine::roa\_obj, 304
  - rpki::up\_down::certificate\_elt, 336
- cert\_url
  - rpki::up\_down::certificate\_elt, 336
  - rpki::up\_down::class\_elt, 339
- certs
  - rpki::up\_down::class\_elt, 339
- irbe\_cli, 47
- irdbd, 51
- rootd, 58
- rpki::config::parser, 136
- cfg\_le
  - irbe\_cli, 47
  - irdbd, 51
  - pubd, 54
  - rootd, 58
  - rpkid, 94
- characters
  - rpki::xml\_utils::sax\_handler, 410
- check\_allowed\_uri
  - rpki::publication::client\_elt, 227
- check\_for\_updates
  - rpki::rpki\_engine::ca\_obj, 287
- check\_response
  - rpki::up\_down::base\_elt, 333
  - rpki::up\_down::error\_response\_pdu, 343
  - rpki::up\_down::issue\_response\_pdu, 348
- check\_valid\_rpkid

- rpki::x509::PKCS10,380
- checkpoint
  - rpki::rpki\_engine::rpkid\_context,307
- child
  - rpki::rpki\_engine::child\_cert\_obj,292
- child\_bpki\_cert
  - rootd,59
- child\_certs
  - rpki::left\_right::child\_elt,187
  - rpki::rpki\_engine::ca\_detail\_obj,279
- child\_id
  - rpki::rpki\_engine::child\_cert\_obj,294
- children
  - rpki::left\_right::bsc\_elt,183
  - rpki::left\_right::self\_elt,215
- chunk\_body
  - rpki::https::http\_stream,175
- chunk\_discard\_crlf
  - rpki::https::http\_stream,175
- chunk\_discard\_trailer
  - rpki::https::http\_stream,175
- chunk\_handler
  - rpki::https::http\_stream,178
- chunk\_header
  - rpki::https::http\_stream,175
- class\_name
  - rpki::up\_down::class\_elt,339
  - rpki::up\_down::issue\_pdu,347
  - rpki::up\_down::revoke\_pdu,356
  - rpki::up\_down::revoke\_syntax,358
- classes
  - rpki::up\_down::class\_response\_syntax,341
- clear
  - rpki::async::timer,130
  - rpki::x509::DER\_object,372
- clear\_https\_ta\_cache
  - pubd::pubd\_context,115
  - rpki::left\_right::child\_elt,189
  - rpki::publication::client\_elt,229
  - rpki::rpki\_engine::rpkid\_context,307
- client
  - rpki::https,70
  - rpki::https::http\_queue,166
- client\_cert
  - irbe\_cli::caller,98
- client\_getopt
  - irbe\_cli::cmd\_elt\_mixin,101
- client\_handler
  - pubd::pubd\_context,116
- client\_key
  - irbe\_cli::caller,98
- client\_poll
  - rpki::left\_right::self\_elt,215
- client\_query\_bpki\_cert
  - irbe\_cli::cmd\_elt\_mixin,101
- client\_query\_bpki\_cms\_cert
  - irbe\_cli::cmd\_elt\_mixin,101
- client\_query\_bpki\_crl
  - irbe\_cli::con g\_elt,105
- client\_query\_bpki\_https\_cert
  - irbe\_cli::cmd\_elt\_mixin,101
- client\_query\_cms\_glue
  - irbe\_cli::cmd\_elt\_mixin,101
- client\_query\_glue
  - irbe\_cli::cmd\_elt\_mixin,102
- client\_query\_https\_glue
  - irbe\_cli::cmd\_elt\_mixin,102
- client\_query\_signing\_cert
  - irbe\_cli::bsc\_elt,96
- client\_query\_signing\_cert\_crl
  - irbe\_cli::bsc\_elt,96
- client\_queues
  - rpki::https,70
- client\_reply\_decode
  - irbe\_cli::bsc\_elt,96
  - irbe\_cli::reply\_elt\_mixin,111
- client\_reply\_show
  - irbe\_cli::reply\_elt\_mixin,111
- client\_ta
  - irdbd,51
  - rootd,59
- client\_url\_regexp
  - pubd::pubd\_context,116
- close
  - rpki::https::http\_stream,175
  - rpki::sql::session,314

- cmd
  - rpki::https::http\_request, [168](#)
- cms\_class
  - irbe\_cli::caller, [98](#)
- code
  - rpki::https::http\_response, [470](#)
- codes
  - rpki::up\_down::error\_response\_pdu, [344](#)
- collect\_incoming\_data
  - rpki::https::http\_stream, [175](#)
- columns
  - rpki::sql::template, [323](#)
- compose\_response
  - rootd, [57](#)
- con g.py(2926), [415](#)
- con g\_id
  - rpki::publication::con g\_elt, [233](#)
- connect
  - rpki::sql::session, [314](#)
- construct\_sia\_uri
  - rpki::rpki\_engine::ca\_obj, [287](#)
- contains
  - rpki::resource\_set::resource\_set, [317](#)
- content
  - rpki::x509::CMS\_object, [362](#)
  - rpki::x509::DER\_CMS\_object, [370](#)
  - rpki::x509::XML\_CMS\_object, [397](#)
- content\_class
  - rpki::x509::ROA, [382](#)
  - rpki::x509::SignedManifest, [390](#)
- control\_handler
  - pubd::pubd\_context, [116](#)
- convert\_to\_seconds
  - rpki::sundial::timedelta, [331](#)
- create
  - rpki::rpki\_engine::ca\_detail\_obj, [279](#)
  - rpki::rpki\_engine::ca\_obj, [287](#)
  - rpki::x509::PKCS10, [380](#)
- create\_ca
  - rpki::x509::PKCS10, [380](#)
- create\_top\_level
  - rpki::xml\_utils::sax\_handler, [410](#)
- crl\_interval
  - rpki::left\_right::self\_elt, [220](#)
- crl\_published
  - rpki::rpki\_engine::ca\_detail\_obj, [283](#)
- crl\_published\_callback
  - rpki::rpki\_engine::ca\_detail\_obj, [279](#)
- crl\_uri
  - rpki::rpki\_engine::ca\_detail\_obj, [279](#)
- crl\_uri\_tail
  - rpki::rpki\_engine::ca\_detail\_obj, [280](#)
- cron
  - rpki::left\_right::self\_elt, [215](#)
  - rpki::rpki\_engine::rpkid\_context, [308](#)
- cron\_keepalive
  - rpki::rpki\_engine::rpkid\_context, [309](#)
- cron\_period
  - rpki::rpki\_engine::rpkid\_context, [310](#)
- cron\_timeout
  - rpki::rpki\_engine::rpkid\_context, [310](#)
- cron\_timer
  - rpki::rpki\_engine::rpkid\_context, [310](#)
- cronjob\_handler
  - rpki::rpki\_engine::rpkid\_context, [308](#)
- cross\_certify
  - rpki::x509::X509, [391](#)
- cur
  - irbdb, [51](#)
  - rpki::sql::session, [315](#)
- database
  - rpki::sql::session, [315](#)
- datum\_type
  - rpki::resource\_set::resource\_range\_as, [252](#)
  - rpki::resource\_set::resource\_range\_ipv4, [255](#)
  - rpki::resource\_set::resource\_range\_ipv6, [256](#)

- db
  - irdbd, [51](#)
  - rpki::sql::session, [316](#)
- debug
  - rpki::log, [76](#)
- debug\_cms\_certs
  - rpki::x509::CMS\_object, [362](#)
- debug\_http
  - rpki::https, [70](#)
- debug\_tls\_certs
  - rpki::https, [70](#)
- decode
  - rpki::x509::DER\_CMS\_object, [370](#)
  - rpki::x509::XML\_CMS\_object, [396](#)
- default\_client\_timeout
  - rpki::https, [71](#)
- default\_http\_version
  - rpki::https, [71](#)
- default\_pubd\_handler
  - rpki::left\_right::repository\_elt, [210](#)
- default\_section
  - rpki::con g::parser, [136](#)
- default\_server\_timeout
  - rpki::https, [71](#)
- defer
  - rpki::async, [64](#)
- deferred\_queue
  - rpki::async, [65](#)
- del\_subject\_cert
  - rootd, [57](#)
- del\_subject\_pkcs10
  - rootd, [57](#)
- delete
  - rpki::rpki\_engine::ca\_detail\_obj, [280](#)
  - rpki::rpki\_engine::ca\_obj, [287](#)
  - rpki::sql::template, [323](#)
- DER
  - rpki::x509::CMS\_object, [362](#)
  - rpki::x509::CRL, [367](#)
  - rpki::x509::DER\_object, [376](#)
  - rpki::x509::PKCS10, [381](#)
  - rpki::x509::RSA, [385](#)
  - rpki::x509::RSAPublic, [387](#)
  - rpki::x509::X509, [394](#)
- description
  - rpki::up\_down::error\_response\_pdu, [344](#)
- detach
  - rpki::https::http\_queue, [165](#)
- difference
  - rpki::resource\_set::resource\_set, [257](#)
- dirty
  - rpki::sql::session, [316](#)
- doit
  - rpki::async::iterator, [125](#)
- done\_callback
  - rpki::async::iterator, [126](#)
- dump
  - rpki::x509::DeadDrop, [368](#)
- dump\_inbound\_cms
  - rpki::x509::XML\_CMS\_object, [397](#)
- dump\_on\_verify\_failure
  - rpki::x509::CMS\_object, [363](#)
- dump\_outbound\_cms
  - rpki::x509::XML\_CMS\_object, [398](#)
- dump\_to\_disk
  - rpki::x509::XML\_CMS\_object, [396](#)
- dumpasn1
  - rpki::x509::DER\_object, [372](#)
- dynamic\_ta
  - rpki::https::http\_listener, [161](#)
- e
  - rpki::x509::PEM\_convert, [378](#)
- earlier
  - rpki::sundial::datetime, [326](#)
- eb
  - rpki::async::sync\_wrapper, [127](#)
- econtent\_oid
  - rpki::x509::CMS\_object, [363](#)
  - rpki::x509::ROA, [382](#)
  - rpki::x509::SignedManifest, [390](#)
  - rpki::x509::XML\_CMS\_object, [398](#)
- element\_name
  - rpki::left\_right::bsc\_elt, [184](#)
  - rpki::left\_right::child\_elt, [189](#)
  - rpki::left\_right::list\_published\_objects\_elt, [196](#)
  - rpki::left\_right::list\_resources\_elt, [199](#)

- rpki::left\_right::list\_roa\_requests\_ -  
elt, 200
- rpki::left\_right::parent\_elt 206
- rpki::left\_right::report\_error\_elt 208
- rpki::left\_right::repository\_elt 211
- rpki::left\_right::self\_elt 220
- rpki::publication::certificate\_elt 226
- rpki::publication::client\_elt 229
- rpki::publication::cong\_elt 233
- rpki::publication::crl\_elt 235
- rpki::publication::manifest\_elt 236
- rpki::publication::report\_error\_elt,  
244
- rpki::publication::roa\_elt 245
- elements
  - rpki::left\_right::bsc\_elt 185
  - rpki::left\_right::child\_elt 189
  - rpki::left\_right::parent\_elt 206
  - rpki::left\_right::repository\_elt 212
  - rpki::left\_right::self\_elt 220
  - rpki::publication::client\_elt 229
  - rpki::publication::cong\_elt 233
  - rpki::xml\_utils::base\_elt 401
- empty
  - rpki::resource\_set::resource\_bag,  
248
  - rpki::x509::DER\_object 372
- enable\_trace
  - rpki::log, 76
- encode
  - rpki::x509::DER\_CMS\_object 370
  - rpki::x509::XML\_CMS\_object 396
- encoding
  - rpki::left\_right::cms\_msg 191
  - rpki::publication::cms\_msg 230
  - rpki::up\_down::cms\_msg 342
- endElement
  - rpki::left\_right::child\_elt 187
  - rpki::publication::client\_elt 227
  - rpki::publication::publication\_ -  
object\_elt 240
  - rpki::up\_down::base\_elt 333
  - rpki::up\_down::certificate\_elt 335
  - rpki::up\_down::class\_elt 338
  - rpki::up\_down::error\_response\_pdu,  
343
  - rpki::up\_down::issue\_pdu 346
  - rpki::xml\_utils::base\_elt 399
  - rpki::xml\_utils::data\_elt 403
  - rpki::xml\_utils::msg 407
  - rpki::xml\_utils::sax\_handler 410
  - rpki::xml\_utils::text\_elt 412
- endElementNS
  - rpki::xml\_utils::sax\_handler 410
- enforce\_strict\_up\_down\_xml\_sender
  - rpki::left\_right, 74
- err
  - rpki::async::sync\_wrapper 28
- errback
  - rpki::async::timer, 130, 132
  - rpki::https::http\_request 168
- error
  - rpki::log, 76
- error\_code
  - rpki::left\_right::report\_error\_elt 209
  - rpki::publication::report\_error\_elt,  
244
- error\_text
  - rpki::left\_right::report\_error\_elt 209
  - rpki::publication::report\_error\_elt,  
244
- event\_loop
  - rpki::async, 64
- Exception, 95
- exceptions
  - rpki::up\_down::error\_response\_pdu,  
344
- exceptions.py(2907), 115
- excludes
  - irbe\_cli::bsc\_elt 96
  - irbe\_cli::cmd\_elt\_mixin, 103
  - irbe\_cli::list\_published\_objects\_elt,  
108
- execute
  - rpki::sql::session 314
- executemany
  - rpki::sql::session 314
- exit\_event\_loop
  - rpki::async, 64
- ExitNow
  - rpki::async, 65
- expect\_close

- rpki::https::http\_client,158
- rpki::https::http\_server,172
- expired
  - rpki::x509::X509,392
- expires
  - rpki::rpki\_engine::revoked\_cert\_obj,299
- explicitVersion
  - rpki::manifest::Manifest,224
  - rpki::roa::RouteOriginAttestation,277
- extract
  - rpki::x509::CMS\_object,361
- fetch
  - rpki::publication::cong\_elt,232
  - rpki::rpki\_engine::child\_cert\_obj,293
- fetch\_active
  - rpki::rpki\_engine::ca\_obj,288
- fetch\_deprecated
  - rpki::rpki\_engine::ca\_obj,288
- fetch\_issue\_response\_candidates
  - rpki::rpki\_engine::ca\_obj,288
- fetch\_pending
  - rpki::rpki\_engine::ca\_obj,288
- fetch\_revoked
  - rpki::rpki\_engine::ca\_obj,288
- fetchall
  - rpki::sql::session,314
- le
  - rpki::manifest::FileAndHash,223
- leHashAlg
  - rpki::manifest::Manifest,224
- leList
  - rpki::manifest::Manifest,224
- lename
  - rpki::cong::parser,136
- nd\_handler
  - rpki::https::http\_server,171
- format
  - rpki::https::http\_message,463
- format\_rst\_line
  - rpki::https::http\_request,168
  - rpki::https::http\_response,469
- formats
  - rpki::x509::CMS\_object,363
  - rpki::x509::CRL,367
  - rpki::x509::DER\_object,376
  - rpki::x509::PKCS10,381
  - rpki::x509::RSA,385
  - rpki::x509::RSAPublic,388
  - rpki::x509::X509,394
- found\_terminator
  - rpki::https::http\_stream,175
- from\_bytes
  - rpki::ipaddr::v4addr,180
  - rpki::ipaddr::v6addr,181
- from\_exception
  - rpki::left\_right::report\_error\_elt,208
  - rpki::publication::report\_error\_elt,243
- from\_resource\_bag
  - rpki::up\_down::class\_elt,338
- from\_rfc3779\_tuples
  - rpki::resource\_set::resource\_bag,248
- from\_sql
  - rpki::resource\_set::resource\_set,268
  - rpki::resource\_set::roa\_pre\_x\_set,270
  - rpki::sundial::datetime,326
  - rpki::x509::DER\_object,372
- fromASN1tuple
  - rpki::sundial::datetime,326
- fromdatetime
  - rpki::sundial::datetime,326
- fromGeneralizedTime
  - rpki::sundial::datetime,326
- fromtimedelta
  - rpki::sundial::timedelta,331
- fromUTCtime
  - rpki::sundial::datetime,326
- fromXMLtime
  - rpki::sundial::datetime,327
- func
  - rpki::async::sync\_wrapper,28
- gAKI
  - rpki::x509::DER\_object,373
- gc\_debug
  - rpki::async::timer,132



gctx  
 rpki::rpki\_engine::ca\_detail\_obj,  
   283  
 rpki::rpki\_engine::ca\_obj,290  
 rpki::rpki\_engine::child\_cert\_obj,  
   294  
 rpki::rpki\_engine::revoked\_cert\_obj,  
   299  
 rpki::rpki\_engine::roa\_obj,304  
 rpki::sql::sql\_persisten,321  
generate  
 rpki::rpki\_engine::roa\_obj,301  
 rpki::x509::CRL,365  
 rpki::x509::RSA,384  
generate\_crl  
 rpki::rpki\_engine::ca\_detail\_obj,  
   280  
generate\_manifest  
 rpki::rpki\_engine::ca\_detail\_obj,  
   280  
generate\_manifest\_cert  
 rpki::rpki\_engine::ca\_detail\_obj,  
   280  
get  
 rpki::con g::parser,135  
get\_377resources  
 rpki::x509::DER\_object,373  
get\_AIA  
 rpki::x509::DER\_object,373  
get\_AKI  
 rpki::x509::DER\_object,373  
get\_Base64  
 rpki::x509::DER\_object,373  
get\_basicConstraints  
 rpki::x509::DER\_object,374  
get\_buffer  
 rpki::https::http\_stream,176  
get\_content  
 rpki::x509::CMS\_object,361  
get\_DER  
 rpki::x509::CMS\_object,361  
 rpki::x509::CRL,365  
 rpki::x509::DER\_object,374  
 rpki::x509::PKCS10,380  
 rpki::x509::RSA,384  
 rpki::x509::RSAPublic,387  
 rpki::x509::X509,392  
get\_PEM  
 rpki::x509::DER\_object,374  
get\_POW  
 rpki::x509::CMS\_object,361  
 rpki::x509::CRL,366  
 rpki::x509::RSA,384  
 rpki::x509::RSAPublic,387  
 rpki::x509::X509,392  
get\_POWpkix  
 rpki::x509::CRL,366  
 rpki::x509::PKCS10,380  
 rpki::x509::X509,392  
get\_public\_DER  
 rpki::x509::RSA,384  
get\_root\_cert  
 rootd,57  
get\_RSAPublic  
 rpki::x509::RSA,385  
get\_SIA  
 rpki::x509::DER\_object,374  
get\_SKI  
 rpki::up\_down::revoke\_pdu,355  
 rpki::x509::DER\_object,374  
 rpki::x509::RSA,385  
 rpki::x509::RSAPublic,387  
get\_subject\_cert  
 rootd,57  
get\_subject\_pkcs10  
 rootd,57  
getboolean  
 rpki::con g::parser,135  
getint  
 rpki::con g::parser,135  
getIssuer  
 rpki::x509::CRL,366  
 rpki::x509::X509,392  
getNextUpdate  
 rpki::x509::CRL,366  
 rpki::x509::SignedManifest,389  
getNotAfter  
 rpki::x509::X509,392  
getNotBefore  
 rpki::x509::X509,393  
getPublicKey  
 rpki::x509::PKCS10,380

- rpki::x509::X509,393
- getSerial
  - rpki::x509::X509,393
- getSubject
  - rpki::x509::X509,393
- getThisUpdate
  - rpki::x509::CRL,366
  - rpki::x509::SignedManifest,389
- gSKI
  - rpki::x509::DER\_object,375
- hAKI
  - rpki::x509::DER\_object,375
- handle\_accept
  - rpki::https::http\_listener,161
- handle\_body
  - rpki::https::http\_stream,176
- handle\_close
  - rpki::https::http\_client,156
  - rpki::https::http\_stream,176
- handle\_connect
  - rpki::https::http\_client,157
- handle\_dispatch
  - irdbd,51
- handle\_error
  - rpki::https::http\_client,157
  - rpki::https::http\_listener,161
  - rpki::https::http\_stream,176
- handle\_list\_resources
  - irdbd,50
- handle\_list\_roa\_requests
  - irdbd,50
- handle\_message
  - rpki::https::http\_client,157
  - rpki::https::http\_server,171
- handle\_no\_content\_length
  - rpki::https::http\_client,157
  - rpki::https::http\_server,171
- handle\_read
  - rpki::https::http\_stream,176
- handle\_timeout
  - rpki::https::http\_client,157
  - rpki::https::http\_stream,176
- handle\_write
  - rpki::https::http\_stream,176
- handler
  - irdbd,50
  - rpki::async::gc\_summary,123
  - rpki::async::timer,131, 133
- handler\_common
  - pubd::pubd\_context,116
- handlers
  - irdbd,52
  - rootd,59
  - rpki::https::http\_listener,161
  - rpki::https::http\_server,172
  - rpki::rpki\_engine::publication\_queue,297
- handles
  - rpki::left\_right::bsc\_elt,185
  - rpki::left\_right::child\_elt,189
  - rpki::left\_right::data\_elt,194
  - rpki::left\_right::parent\_elt,206
  - rpki::left\_right::repository\_elt,212
  - rpki::left\_right::self\_elt,220
- has\_option
  - rpki::con g::parser,135
- has\_section
  - rpki::con g::parser,135
- hash
  - rpki::manifest::FileAndHash,223
- headers
  - rpki::https::http\_message,164
- host
  - irdbd,52
  - rootd,59
- hostport
  - rpki::https::http\_client,158
  - rpki::https::http\_queue,166
- hSKI
  - rpki::x509::DER\_object,375
- https.py(2902),416
- https\_server\_host
  - pubd::pubd\_context,117
  - rootd,59
  - rpki::rpki\_engine::rpkid\_context,310
- https\_server\_port
  - pubd::pubd\_context,117
  - rootd,59
  - rpki::rpki\_engine::rpkid\_context,310

---

[https\\_ta\\_cache](#)  
     [pubd::pubd\\_context](#), [17](#)  
     [rpki::rpki\\_engine::rpkid\\_context](#),  
         [310](#)  
[ignore](#)  
     [rpki::async::iterator](#), [125](#)  
[index](#)  
     [rpki::sql::template](#), [323](#)  
[info](#)  
     [rpki::log](#), [76](#)  
[inherit](#)  
     [rpki::resource\\_set::resource\\_set](#), [259](#)  
     [rpki::resource\\_set::resource\\_set\\_as](#),  
         [261](#)  
     [rpki::resource\\_set::resource\\_set\\_ip](#),  
         [262](#)  
[inherit\\_token](#)  
     [rpki::resource\\_set](#), [84](#)  
[init](#)  
     [rpki::log](#), [75](#)  
[initial\\_delay](#)  
     [rpki::rpki\\_engine::rpkid\\_context](#),  
         [310](#)  
[initiate\\_send](#)  
     [rpki::https::http\\_stream](#), [177](#)  
[insert](#)  
     [rpki::sql::template](#), [323](#)  
[intersection](#)  
     [rpki::resource\\_set::resource\\_bag](#),  
         [248](#)  
     [rpki::resource\\_set::resource\\_set](#), [258](#)  
[interval](#)  
     [rpki::async::gc\\_summary](#), [124](#)  
[ipAddrBlocks](#)  
     [rpki::roa::RouteOriginAttestation](#),  
         [277](#)  
[ipaddrs.py\(2424\)](#), [417](#)  
[ipv4](#)  
     [rpki::left\\_right::list\\_resources\\_elt](#),  
         [199](#)  
     [rpki::left\\_right::list\\_roa\\_requests\\_-](#)  
         [elt](#), [201](#)  
     [rpki::rpki\\_engine::roa\\_obj](#), [305](#)  
[ipv6](#)  
     [rpki::left\\_right::list\\_resources\\_elt](#),  
         [199](#)  
     [rpki::left\\_right::list\\_roa\\_requests\\_-](#)  
         [elt](#), [201](#)  
     [rpki::rpki\\_engine::roa\\_obj](#), [305](#)  
[irbe\\_cert](#)  
     [pubd::pubd\\_context](#), [17](#)  
     [rpki::rpki\\_engine::rpkid\\_context](#),  
         [311](#)  
[irbe\\_cli](#), [45](#)  
     [argv](#), [47](#)  
     [call\\_pubd](#), [47](#)  
     [call\\_rpkid](#), [47](#)  
     [cfg](#), [47](#)  
     [cfg\\_le](#), [47](#)  
     [pem\\_out](#), [47](#)  
     [q\\_msg](#), [48](#)  
     [q\\_msg\\_left\\_right](#), [48](#)  
     [q\\_msg\\_publication](#), [48](#)  
     [q\\_pdu](#), [48](#)  
     [top\\_opts](#), [48](#)  
     [usage](#), [46](#)  
     [usage\\_ll](#), [48](#)  
     [verbose](#), [48](#)  
[irbe\\_cli.py\(2799\)](#), [418](#)  
[irbe\\_cli::bsc\\_elt](#), [95](#)  
     [client\\_query\\_signing\\_cert](#), [96](#)  
     [client\\_query\\_signing\\_cert\\_cr](#), [96](#)  
     [client\\_reply\\_decode](#), [96](#)  
     [excludes](#), [96](#)  
     [signing\\_cert](#), [97](#)  
     [signing\\_cert\\_cr](#), [97](#)  
[irbe\\_cli::caller](#), [97](#)  
     [\\_\\_call\\_\\_](#), [98](#)  
     [\\_\\_init\\_\\_](#), [98](#)  
     [client\\_cert](#), [98](#)  
     [client\\_key](#), [98](#)  
     [cms\\_class](#), [98](#)  
     [server\\_cert](#), [98](#)  
     [server\\_ta](#), [98](#)  
     [url](#), [99](#)  
[irbe\\_cli::certicate\\_elt](#), [99](#)  
[irbe\\_cli::child\\_elt](#), [99](#)  
[irbe\\_cli::client\\_elt](#), [99](#)  
[irbe\\_cli::cmd\\_elt\\_mixin](#), [100](#)  
     [bpki\\_cert](#), [102](#)

- bpki\_cms\_cert, 102
- bpki\_cms\_glue, 102
- bpki\_glue, 103
- bpki\_https\_cert, 103
- bpki\_https\_glue, 103
- client\_getopt, 101
- client\_query\_bpki\_cert, 101
- client\_query\_bpki\_cms\_cert, 101
- client\_query\_bpki\_https\_cert, 101
- client\_query\_cms\_glue, 101
- client\_query\_glue, 102
- client\_query\_https\_glue, 102
- excludes, 103
- is\_cmd, 103
- usage, 102
- irbe\_cli::cmd\_msg\_mixin, 104
- usage, 104
- irbe\_cli::config\_elt, 104
- bpki\_crl, 105
- client\_query\_bpki\_crl, 105
- irbe\_cli::crl\_elt, 105
- irbe\_cli::left\_right\_cms\_msg, 105
- saxify, 106
- irbe\_cli::left\_right\_msg, 106
- pdu, 106
- irbe\_cli::left\_right\_sax\_handler, 107
- pdu, 107
- irbe\_cli::list\_published\_objects\_elt, 107
- excludes, 108
- irbe\_cli::manifest\_elt, 108
- irbe\_cli::parent\_elt, 108
- irbe\_cli::publication\_cms\_msg, 109
- saxify, 109
- irbe\_cli::publication\_msg, 109
- pdu, 110
- irbe\_cli::publication\_sax\_handler, 110
- pdu, 110
- irbe\_cli::reply\_elt\_mixin, 111
- client\_reply\_decode, 111
- client\_reply\_show, 111
- is\_cmd, 112
- irbe\_cli::report\_error\_elt, 112
- irbe\_cli::repository\_elt, 112
- irbe\_cli::roa\_elt, 112
- irbe\_cli::self\_elt, 113
- irbe\_cli::UsageWrapper, 113
- \_\_call\_\_, 113
- irdb\_cert
  - rpki::rpki\_engine::rpkid\_context, 311
- irdb\_query
  - rpki::rpki\_engine::rpkid\_context, 308
- irdb\_query\_child\_resources
  - rpki::rpki\_engine::rpkid\_context, 308
- irdb\_query\_roa\_requests
  - rpki::rpki\_engine::rpkid\_context, 308
- irdb\_url
  - rpki::rpki\_engine::rpkid\_context, 311
- irdbd, 49
- bpki\_ta, 51
- cfg, 51
- cfg\_le, 51
- client\_ta, 51
- cur, 51
- db, 51
- handle\_dispatch, 51
- handle\_list\_resource, 50
- handle\_list\_roa\_request, 50
- handler, 50
- handlers, 52
- host, 52
- irdbd\_cert, 52
- irdbd\_key, 52
- port, 52
- rpkid\_cert, 52
- server\_cert, 52
- startup\_msg, 53
- u, 53
- irdbd.py(2913), 419
- irdbd\_cert
  - irdbd, 52
- irdbd\_key
  - irdbd, 52
- is\_CA
  - rpki::x509::DER\_object, 375
- is\_cmd
  - irbe\_cli::cmd\_elt\_mixin, 103
  - irbe\_cli::reply\_elt\_mixin, 112

- is\_query
  - rpki::xml\_utils::msg, [407](#)
- is\_reply
  - rpki::xml\_utils::msg, [407](#)
- is\_set
  - rpki::async::timer, [131](#)
- issubset
  - rpki::resource\_set::resource\_set, [268](#)
- issue
  - rpki::rpki\_engine::ca\_detail\_obj, [281](#)
  - rpki::x509::X509, [393](#)
- issue\_ee
  - rpki::rpki\_engine::ca\_detail\_obj, [281](#)
- issue\_subject\_cert\_maybe
  - rootd, [57](#)
- issuer
  - rpki::up\_down::class\_elt, [339](#)
- issuperset
  - rpki::resource\_set::resource\_set, [268](#)
- item\_callback
  - rpki::async::iterator, [126](#)
- iterator
  - rpki::async::iterator, [126](#)
- key
  - rpki::https::http\_client, [158](#)
  - rpki::https::http\_listener, [161](#)
  - rpki::https::http\_queue, [166](#)
- last\_crl\_sn
  - rpki::rpki\_engine::ca\_obj, [290](#)
- last\_issued\_sn
  - rpki::rpki\_engine::ca\_obj, [290](#)
- last\_manifest\_sn
  - rpki::rpki\_engine::ca\_obj, [290](#)
- lastrowid
  - rpki::sql::session, [314](#)
- later
  - rpki::sundial::datetime, [327](#)
- latest\_ca\_cert
  - rpki::rpki\_engine::ca\_detail\_obj, [283](#)
- latest\_crl
  - rpki::rpki\_engine::ca\_detail\_obj, [283](#)
- latest\_manifest
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- latest\_manifest\_cert
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- left\_right
  - rpki::relaxng, [81](#)
- left\_right.py(2931), [420](#)
- left\_right\_handler
  - rpki::rpki\_engine::rpkid\_context, [309](#)
- log
  - rpki::https::http\_listener, [161](#)
  - rpki::https::http\_queue, [166](#)
  - rpki::https::http\_stream, [178](#)
- log.py(2933), [420](#)
- log\_cert
  - rpki::https::http\_stream, [177](#)
- log\_method
  - rpki::https, [70](#)
- log\_query
  - rootd::message\_pdu, [121](#)
  - rpki::up\_down::message\_pdu, [151](#)
- long, [114](#)
- looks\_like\_PEM
  - rpki::x509::PEM\_convert, [378](#)
- maildir
  - rpki::x509::DeadDrop, [369](#)
- main
  - pubd, [54](#)
  - rpkid, [94](#)
- make\_b64elt
  - rpki::up\_down::base\_elt, [333](#)
  - rpki::xml\_utils::base\_elt, [400](#)
- make\_elt
  - rpki::up\_down::base\_elt, [334](#)
  - rpki::xml\_utils::base\_elt, [400](#)
- make\_pdu
  - rpki::xml\_utils::base\_elt, [400](#)
- make\_pre\_x
  - rpki::resource\_set::resource\_range\_ip, [254](#)

- make\_publish
  - rpki::publication::publication\_ - object\_elt, [240](#)
- make\_query
  - rpki::up\_down::message\_pd, [351](#)
- make\_reply
  - rpki::left\_right::list\_published\_ - objects\_elt, [196](#)
  - rpki::xml\_utils::data\_elt, [403](#)
- make\_reply\_clone\_hook
  - rpki::left\_right::data\_elt, [192](#)
  - rpki::xml\_utils::data\_elt, [403](#)
- make\_withdraw
  - rpki::publication::publication\_ - object\_elt, [240](#)
- manifest.py(2424), [421](#)
- manifest\_private\_key\_id
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- manifest\_public\_key
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- manifest\_published
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- manifest\_published\_callback
  - rpki::rpki\_engine::ca\_detail\_obj, [281](#)
- manifest\_uri
  - rpki::rpki\_engine::ca\_detail\_obj, [281](#)
- manifestNumber
  - rpki::manifest::Manifest, [225](#)
- map
  - rpki::sql::template, [323](#)
- max
  - rpki::resource\_set::resource\_range, now, [251](#)
  - rpki::resource\_set::roa\_pre, [266](#)
- max\_pre\_xlen
  - rpki::resource\_set::roa\_pre, [267](#)
- maxLength
  - rpki::roa::ROAIPAddress, [273](#)
- min
  - rpki::resource\_set::resource\_range, obj, [251](#)
- rpki::resource\_set::resource\_range\_ - as, [253](#)
- rpki::resource\_set::roa\_pre, [266](#)
- msg
  - rpki::https::http\_stream, [178](#)
- msgs
  - rpki::rpki\_engine::publication\_ - queue, [297](#)
- multiget
  - rpki::con g::parser, [136](#)
- name
  - rpki::left\_right::sax\_handle, [213](#)
  - rpki::publication::sax\_handle, [246](#)
  - rpki::up\_down::sax\_handle, [359](#)
- name2oid
  - rpki::oids, [79](#)
- name2type
  - rootd::message\_pd, [421](#)
  - rpki::up\_down::message\_pd, [352](#)
- next\_crl\_number
  - rpki::rpki\_engine::ca\_obj, [289](#)
- next\_manifest\_number
  - rpki::rpki\_engine::ca\_obj, [289](#)
- next\_serial\_number
  - rpki::rpki\_engine::ca\_obj, [289](#)
- nextUpdate
  - rpki::manifest::Manifest, [225](#)
  - rpki::rpki\_engine::ca\_detail\_obj, [284](#)
- normalize\_chain
  - rpki::x509::X509, [394](#)
- normalize\_headers
  - rpki::https::http\_message, [463](#)
- note
  - rpki::log, [76](#)
- now
  - rpki::sundial, [88](#)
- nsmmap
  - rpki::left\_right::left\_right\_ - namespace, [195](#)
  - rpki::publication::publication\_ - namespace, [238](#)
  - rpki::up\_down, [90](#)

- rpki::left\_right::list\_published\_ - objects\_elt, [196](#)
- object, [114](#)
- oid2name
  - rpki::oids, [79](#)
- oids.py(2424), [421](#)
- other\_clear
  - rpki::x509::CMS\_object, [363](#)
  - rpki::x509::DER\_object, [376](#)
- oversized
  - rpki::resource\_set::resource\_bag, [248](#)
- parent
  - rpki::rpki\_engine::ca\_ob, [289](#)
- parent\_id
  - rpki::rpki\_engine::ca\_ob, [290](#)
- parent\_resource\_class
  - rpki::rpki\_engine::ca\_ob, [291](#)
- parents
  - rpki::left\_right::bsc\_elt, [183](#)
  - rpki::left\_right::child\_elt, [187](#)
  - rpki::left\_right::repository\_elt, [211](#)
  - rpki::left\_right::self\_elt, [215](#)
- parse
  - rpki::sundial::timedelta, [332](#)
- parse\_rst\_line
  - rpki::https::http\_request, [168](#)
  - rpki::https::http\_response, [170](#)
- parse\_from\_wire
  - rpki::https::http\_message, [163](#)
- parse\_rfc3779\_tuple
  - rpki::resource\_set::resource\_set\_as, [260](#)
  - rpki::resource\_set::resource\_set\_ip, [262](#)
- parse\_str
  - rpki::resource\_set::resource\_set\_as, [260](#)
  - rpki::resource\_set::resource\_set\_ip, [262](#)
  - rpki::resource\_set::roa\_pre x\_set, [270](#)
- parse\_type
  - rpki::https::http\_client, [158](#)
  - rpki::https::http\_server, [172](#)
- parse\_version
  - rpki::https::http\_message, [163](#)
- password
  - rpki::sql::session, [316](#)
- path
  - rpki::https::http\_request, [168](#)
- payload
  - rpki::publication::publication\_ - object\_elt, [241](#)
  - rpki::up\_down::message\_pdu, [162](#)
- payload\_type
  - rpki::publication::certificate\_elt, [226](#)
  - rpki::publication::crl\_elt, [235](#)
  - rpki::publication::manifest\_elt, [236](#)
  - rpki::publication::publication\_ - object\_elt, [242](#)
  - rpki::publication::roa\_elt, [245](#)
- pdu
  - irbe\_cli::left\_right\_sax\_handler, [107](#)
  - irbe\_cli::publication\_sax\_handler, [110](#)
  - rootd::sax\_handler, [122](#)
  - rpki::left\_right::sax\_handler, [213](#)
  - rpki::publication::sax\_handler, [246](#)
  - rpki::up\_down::sax\_handler, [159](#)
- pdu\_s
  - irbe\_cli::left\_right\_msg, [106](#)
  - irbe\_cli::publication\_msg, [110](#)
  - rpki::left\_right::msg, [202](#)
  - rpki::publication::msg, [237](#)
- pem\_converter
  - rpki::x509::CMS\_object, [363](#)
  - rpki::x509::CRL, [367](#)
  - rpki::x509::DER\_object, [377](#)
  - rpki::x509::PKCS10, [381](#)
  - rpki::x509::ROA, [383](#)
  - rpki::x509::RSA, [385](#)
  - rpki::x509::RSAPublic, [388](#)
  - rpki::x509::SignedManifest, [390](#)
  - rpki::x509::X509, [394](#)
- pem\_out
  - irbe\_cli, [47](#)
- persistent
  - rpki::https::http\_message, [163](#)
- pid
  - rpki::log, [77](#)

- rpki::x509::DeadDrop [369](#)
- ping
  - rpki::sql::session [315](#)
- pkcs10
  - rpki::up\_down::issue\_pdu [347](#)
- pkcs10\_request
  - rpki::left\_right::bsc\_elt [185](#)
- PKIX\_threshold
  - rpki::sundial::datetime [328](#)
- port
  - irdbd, [52](#)
  - rootd, [59](#)
- POW
  - rpki::x509::CMS\_object [364](#)
  - rpki::x509::CRL, [367](#)
  - rpki::x509::RSA, [386](#)
  - rpki::x509::RSAPublic, [388](#)
  - rpki::x509::X509, [395](#)
- POWify\_OID
  - rpki::x509, [92](#)
- POWpkix
  - rpki::x509::CRL, [367](#)
  - rpki::x509::PKCS10, [381](#)
  - rpki::x509::X509, [395](#)
- pre x
  - rpki::resource\_set::roa\_pre [267](#)
- pre x\_type
  - rpki::resource\_set::roa\_pre x\_set -  
ipv4, [271](#)
  - rpki::resource\_set::roa\_pre x\_set -  
ipv6, [272](#)
- pre xlen
  - rpki::resource\_set::roa\_pre [267](#)
- pretty\_print\_content
  - rpki::x509::XML\_CMS\_object [396](#)
- print\_on\_der\_error
  - rpki::x509::CMS\_object [364](#)
- priority
  - rpki::log::logger, [222](#)
- private\_key\_id
  - rpki::left\_right::bsc\_elt, [185](#)
  - rpki::rpki\_engine::ca\_detail\_obj,  
[284](#)
- pro le
  - pubd, [54](#)
  - rpkid, [94](#)
- pubd, [53](#)
  - cfg\_ le, [54](#)
  - main, [54](#)
  - pro le, [54](#)
- pubd.py(2913), [422](#)
- pubd::pubd\_context, [114](#)
  - \_\_init\_\_, [115](#)
  - bpki\_ta, [116](#)
  - build\_https\_ta\_cache, [15](#)
  - clear\_https\_ta\_cache, [15](#)
  - client\_handler, [116](#)
  - client\_url\_regexp, [116](#)
  - control\_handler, [116](#)
  - handler\_common, [116](#)
  - https\_server\_host, [17](#)
  - https\_server\_port, [17](#)
  - https\_ta\_cache, [17](#)
  - irbe\_cert, [117](#)
  - pubd\_cert, [117](#)
  - pubd\_key, [117](#)
  - publication\_base, [17](#)
  - sql, [118](#)
- pubd\_cert
  - pubd::pubd\_context, [117](#)
- pubd\_key
  - pubd::pubd\_context, [117](#)
- public\_key
  - rpki::rpki\_engine::ca\_detail\_obj,  
[285](#)
- publication
  - rpki::relaxng, [81](#)
- publication.py(2935), [422](#)
- publication\_base
  - pubd::pubd\_context, [117](#)
- publication\_kludge\_base
  - rpki::rpki\_engine::rpkid\_context,  
[311](#)
- publish
  - rpki::rpki\_engine::publication\_  
queue, [296](#)
- published
  - rpki::rpki\_engine::child\_cert\_obj,  
[294](#)
  - rpki::rpki\_engine::roa\_obj, [305](#)
- published\_callback



- rpki::rpki\_engine::child\_cert\_obj, 293
- rpki::rpki\_engine::roa\_obj, 302
- pydatetime::datetime, 18
- pydatetime::timedelta, 18
- q\_msg
  - irbe\_cli, 48
- q\_msg\_left\_right
  - irbe\_cli, 48
- q\_msg\_publication
  - irbe\_cli, 48
- q\_pdu
  - irbe\_cli, 48
- query
  - rpki::up\_down::issue\_pdu, 346
  - rpki::up\_down::list\_pdu, 349
  - rpki::up\_down::revoke\_pdu, 355
  - rpki::xml\_utils::msg, 407
- query\_up\_down
  - rpki::left\_right::parent\_elt, 204
- queue
  - rpki::async::timer, 133
  - rpki::https::http\_client, 159
  - rpki::https::http\_queue, 166
- raise\_if\_error
  - rpki::publication::publication\_object\_elt, 240
  - rpki::publication::report\_error\_elt, 243
- range\_type
  - rpki::resource\_set::resource\_set\_as, 261
  - rpki::resource\_set::resource\_set\_ipv4, 263
  - rpki::resource\_set::resource\_set\_ipv6, 264
  - rpki::resource\_set::roa\_pre\_x\_ipv4, 268
  - rpki::resource\_set::roa\_pre\_x\_ipv6, 269
- read\_attrs
  - rpki::xml\_utils::base\_elt, 400
- readable
  - rpki::https::http\_stream, 177
- reason
  - rpki::https::http\_response, 470
- recipient
  - rpki::up\_down::message\_pdu, 363
- recv
  - rpki::https::http\_stream, 177
- regen\_margin
  - rpki::left\_right::self\_elt, 220
- regenerate
  - rpki::rpki\_engine::roa\_obj, 302
- regenerate\_crls\_and\_manifests
  - rpki::left\_right::self\_elt, 216
- regexp
  - rpki::sundial::timedelta, 332
- reissue
  - rpki::rpki\_engine::child\_cert\_obj, 293
- rekey
  - rpki::rpki\_engine::ca\_obj, 289
- relaxng.py(2876), 423
- replace
  - rpki::rpki\_engine::publication\_queue, 297
- reply
  - rpki::xml\_utils::msg, 407
- repositories
  - rpki::left\_right::bsc\_elt, 183
  - rpki::left\_right::self\_elt, 216
  - rpki::rpki\_engine::publication\_queue, 297
- repository
  - rpki::left\_right::parent\_elt, 204
- req\_resource\_set\_as
  - rpki::up\_down::certificate\_elt, 336
  - rpki::up\_down::issue\_pdu, 347
- req\_resource\_set\_ipv4
  - rpki::up\_down::certificate\_elt, 336
  - rpki::up\_down::issue\_pdu, 347
- req\_resource\_set\_ipv6
  - rpki::up\_down::certificate\_elt, 336
  - rpki::up\_down::issue\_pdu, 347
- request
  - rpki::https::http\_queue, 165
- require\_crls
  - rpki::x509::CMS\_object, 364
- res

---

- rpki::async::sync\_wrapper [128](#)
- resource\_set.py(2776) [423](#)
- resource\_set\_as
  - rpki::up\_down::class\_el [839](#)
- resource\_set\_ipv4
  - rpki::up\_down::class\_el [839](#)
- resource\_set\_ipv6
  - rpki::up\_down::class\_el [839](#)
- resource\_set\_notafter
  - rpki::up\_down::class\_el [840](#)
- resource\_set\_type
  - rpki::resource\_set::roa\_pre\_x\_set\_-
    - ipv4, [271](#)
  - rpki::resource\_set::roa\_pre\_x\_set\_-
    - ipv6, [272](#)
- restart
  - rpki::https::http\_queue [65](#)
  - rpki::https::http\_stream [177](#)
- result
  - rpki::xml\_utils::sax\_handle [411](#)
- retried
  - rpki::https::http\_request [169](#)
- retry\_read
  - rpki::https::http\_client [159](#)
  - rpki::https::http\_server [173](#)
  - rpki::https::http\_stream [178](#)
- retry\_write
  - rpki::https::http\_client [159](#)
  - rpki::https::http\_server [173](#)
  - rpki::https::http\_stream [178](#)
- return\_result
  - rpki::https::http\_queue [65](#)
- revoke
  - rpki::rpki\_engine::ca\_detail\_obj,
    - [281](#)
  - rpki::rpki\_engine::ca\_obj [290](#)
  - rpki::rpki\_engine::child\_cert\_obj,
    - [293](#)
  - rpki::rpki\_engine::revoked\_cert\_obj,
    - [299](#)
  - rpki::rpki\_engine::roa\_obj [302](#)
- revoked
  - rpki::rpki\_engine::revoked\_cert\_obj,
    - [299](#)
- revoked\_certs
  - rpki::rpki\_engine::ca\_detail\_obj,
    - [282](#)
- roa
  - rpki::rpki\_engine::roa\_obj [305](#)
- roa.py(2424) [424](#)
- roas
  - rpki::left\_right::self\_elt [216](#)
  - rpki::rpki\_engine::ca\_detail\_obj,
    - [282](#)
- root\_newer\_than\_subject
  - rootd, [58](#)
- rootd, [55](#)
  - bpki\_ta, [58](#)
  - cfg, [58](#)
  - cfg\_le, [58](#)
  - child\_bpki\_cert, [59](#)
  - client\_ta, [59](#)
  - compose\_response, [57](#)
  - del\_subject\_cert, [57](#)
  - del\_subject\_pkcs10, [57](#)
  - get\_root\_cert, [57](#)
  - get\_subject\_cert, [57](#)
  - get\_subject\_pkcs10, [57](#)
  - handlers, [59](#)
  - host, [59](#)
  - https\_server\_host, [59](#)
  - https\_server\_port, [59](#)
  - issue\_subject\_cert\_maybe, [57](#)
  - port, [59](#)
  - root\_newer\_than\_subject, [58](#)
  - rootd\_bpki\_cert, [60](#)
  - rootd\_bpki\_crl, [60](#)
  - rootd\_bpki\_key, [60](#)
  - rpki\_base\_uri, [60](#)
  - rpki\_class\_name, [60](#)
  - rpki\_root\_cert, [60](#)
  - rpki\_root\_cert\_le, [60](#)
  - rpki\_root\_cert\_uri, [61](#)
  - rpki\_root\_crl, [61](#)
  - rpki\_root\_dir, [61](#)
  - rpki\_root\_key, [61](#)
  - rpki\_root\_manifest, [61](#)
  - rpki\_subject\_cert, [61](#)
  - rpki\_subject\_lifetime, [61](#)
  - rpki\_subject\_pkcs10, [62](#)
  - rpki\_subject\_reger, [62](#)

- server\_cert, 62
- set\_subject\_cert, 58
- set\_subject\_pkcs1, 68
- up\_down\_handler, 58
- rootd.py(2913), 425
- rootd::cms\_msg, 18
- saxify, 119
- rootd::issue\_pdu, 19
- serve\_pdu, 19
- rootd::list\_pdu, 19
- serve\_pdu, 120
- rootd::message\_pdu, 20
- log\_query, 121
- name2type, 121
- type2name, 121
- rootd::revoke\_pdu, 21
- serve\_pdu, 122
- rootd::sax\_handler, 22
- pdu, 122
- rootd\_bpki\_cert
- rootd, 60
- rootd\_bpki\_crl
- rootd, 60
- rootd\_bpki\_key
- rootd, 60
- rpki, 62
- rpki.async, 63
- rpki.config, 65
- rpki.exceptions, 66
- rpki.https, 68
- rpki.ipaddrs, 72
- rpki.left\_right, 73
- rpki.log, 74
- rpki.manifest, 77
- rpki.oids, 78
- rpki.publication, 80
- rpki.relaxng, 81
- rpki.resource\_set, 81
- rpki.roa, 84
- rpki.rpki\_engine, 85
- rpki.sql, 86
- rpki.sundial, 87
- rpki.up\_down, 89
- rpki.x509, 90
- rpki.xml\_utils, 92
- rpki::async
- \_raiseExitNow, 64
- defer, 64
- deferred\_queue, 65
- event\_loop, 64
- exit\_event\_loop, 64
- ExitNow, 65
- run\_deferred, 64
- rpki::async::gc\_summary, 123
- \_\_init\_\_, 123
- handler, 123
- interval, 124
- timer, 124
- rpki::async::iterator, 124
- \_\_call\_\_, 125
- \_\_init\_\_, 125
- \_\_repr\_\_, 125
- caller\_function, 126
- doit, 125
- done\_callback, 126
- ignore, 125
- item\_callback, 126
- iterator, 126
- unwind\_stack, 126
- rpki::async::sync\_wrapper, 126
- \_\_call\_\_, 127
- \_\_init\_\_, 127
- cb, 127
- eb, 127
- err, 128
- func, 128
- res, 128
- rpki::async::timer, 128
- \_\_cmp\_\_, 130
- \_\_del\_\_, 130
- \_\_init\_\_, 130
- \_\_repr\_\_, 130
- cancel, 130
- clear, 130
- errback, 130, 132
- gc\_debug, 132
- handler, 131, 133
- is\_set, 131
- queue, 133
- run\_debug, 133
- runq, 131
- seconds\_until\_wakeup, 131

- set, 131
- set\_errback, 132
- set\_handler, 132
- trace, 132
- when, 133
- rpki::con g::parser, 133
- \_\_init\_\_, 134
- \_get\_wrapper, 134
- cfg, 136
- default\_section, 136
- lename, 136
- get, 135
- getboolean, 135
- getint, 135
- has\_option, 135
- has\_section, 135
- multiget, 136
- set\_global\_ags, 136
- rpki::exceptions::BadClassNameSyntax, 137
- rpki::exceptions::BadClientURL, 137
- rpki::exceptions::BadContactURL, 137
- rpki::exceptions::BadExtension, 138
- rpki::exceptions::BadIRDBReply, 138
- rpki::exceptions::BadIssueResponse, 138
- rpki::exceptions::BadPKCS10, 139
- rpki::exceptions::BadPublicationReply, 139
- rpki::exceptions::BadQuery, 139
- rpki::exceptions::BadSender, 140
- rpki::exceptions::BadStatusCode, 140
- rpki::exceptions::BadURISyntax, 140
- rpki::exceptions::BSCNotFound, 141
- rpki::exceptions::BSCNotReady, 141
- rpki::exceptions::ChildNotFound, 141
- rpki::exceptions::ClassNameMismatch, 142
- rpki::exceptions::ClassNameUnknown, 142
- rpki::exceptions::ClientNotFound, 142
- rpki::exceptions::CMSContentNotSet, 143
- rpki::exceptions::CMSCRLNotSet, 143
- rpki::exceptions::CMSVerificationFailed, 143
- rpki::exceptions::DBConsistencyError, 144
- rpki::exceptions::DERObjectConversionError, 144
- rpki::exceptions::DuplicateObject, 144
- rpki::exceptions::EmptyPEM, 145
- rpki::exceptions::EmptyROAPre xList, 145
- rpki::exceptions::ForbiddenURI, 145
- rpki::exceptions::HandleTranslationError, 146
- rpki::exceptions::HTTPRequestFailed, 146
- rpki::exceptions::HTTPSBadVersion, 146
- rpki::exceptions::HTTPSCClientAborted, 147
- rpki::exceptions::HTTPSUnexpectedState, 147
- rpki::exceptions::MissingCMSCRL, 147
- rpki::exceptions::MissingCMSEECert, 148
- rpki::exceptions::MultipleTLSEECert, 148
- rpki::exceptions::MustBePre x, 148
- rpki::exceptions::NoActiveCA, 149
- rpki::exceptions::NoCoveringCertForROA, 149
- rpki::exceptions::NoObjectAtURI, 149
- rpki::exceptions::NotACertificateChain, 150
- rpki::exceptions::NotFound, 150
- rpki::exceptions::NotImplementedYet, 150
- rpki::exceptions::NotInDatabase, 151
- rpki::exceptions::ReceivedTLSCACert, 151
- rpki::exceptions::RPKI\_Exception, 151
- rpki::exceptions::ServerShuttingDown, 152
- rpki::exceptions::SKIMismatch, 153
- rpki::exceptions::SubprocessError, 153
- rpki::exceptions::TLSValidationError, 153
- rpki::exceptions::UnexpectedCMSCerts, 154

- rpki::exceptions::UnexpectedCMSCRLs, 154
- rpki::exceptions::UnparsableCMSDER, 154
- rpki::exceptions::UpstreamError, 155
- rpki::exceptions::WrongContentType, 155
- rpki::https
  - build\_https\_ta\_cache, 69
  - client, 70
  - client\_queues, 70
  - debug\_http, 70
  - debug\_tls\_certs, 70
  - default\_client\_timeout, 71
  - default\_http\_version, 71
  - default\_server\_timeout, 71
  - log\_method, 70
  - rpki\_content\_type, 71
  - server, 70
  - want\_persistent\_client, 71
  - want\_persistent\_server, 71
- rpki::https::http\_client, 155
  - \_\_init\_\_, 156
  - cert, 158
  - expect\_close, 158
  - handle\_close, 156
  - handle\_connect, 157
  - handle\_error, 157
  - handle\_message, 157
  - handle\_no\_content\_length, 157
  - handle\_timeout, 157
  - hostport, 158
  - key, 158
  - parse\_type, 158
  - queue, 159
  - retry\_read, 159
  - retry\_write, 159
  - send\_request, 157
  - set\_state, 157
  - start, 158
  - state, 159
  - ta, 159
  - timeout, 159
  - tls, 159
  - tls\_connect, 158
- rpki::https::http\_listener, 160
  - \_\_init\_\_, 160
  - cert, 161
  - dynamic\_ta, 161
  - handle\_accept, 161
  - handle\_error, 161
  - handlers, 161
  - key, 161
  - log, 161
  - ta, 161
- rpki::https::http\_message, 162
  - \_\_init\_\_, 163
  - \_\_str\_\_, 163
  - body, 164
  - format, 163
  - headers, 164
  - normalize\_headers, 163
  - parse\_from\_wire, 163
  - parse\_version, 163
  - persistent, 163
  - software\_name, 164
  - version, 164
- rpki::https::http\_queue, 164
  - \_\_init\_\_, 165
  - cert, 166
  - client, 166
  - detach, 165
  - hostport, 166
  - key, 166
  - log, 166
  - queue, 166
  - request, 165
  - restart, 165
  - return\_result, 165
  - send\_request, 166
  - ta, 167
- rpki::https::http\_request, 167
  - \_\_init\_\_, 168
  - callback, 168
  - cmd, 168
  - errback, 168
  - format\_rst\_line, 168
  - parse\_rst\_line, 168
  - path, 168
  - retried, 169
- rpki::https::http\_response, 169
  - \_\_init\_\_, 169

- code,170
- format\_rst\_line,169
- parse\_rst\_line,170
- reason,170
- rpki::https::http\_server,170
  - \_\_init\_\_,171
  - expect\_close,172
  - nd\_handler,171
  - handle\_message,171
  - handle\_no\_content\_length,171
  - handlers,172
  - parse\_type,172
  - retry\_read,173
  - retry\_write,173
  - send\_error,172
  - send\_message,172
  - send\_reply,172
  - timeout,173
  - tls,173
  - tls\_accept,172
- rpki::https::http\_stream,173
  - \_\_init\_\_,175
  - buffer,178
  - chunk\_body,175
  - chunk\_discard\_crlf,175
  - chunk\_discard\_trailer,175
  - chunk\_handler,178
  - chunk\_header,175
  - close,175
  - collect\_incoming\_data,175
  - found\_terminator,175
  - get\_buffer,176
  - handle\_body,176
  - handle\_close,176
  - handle\_error,176
  - handle\_read,176
  - handle\_timeout,176
  - handle\_write,176
  - initiate\_send,177
  - log,178
  - log\_cert,177
  - msg,178
  - readable,177
  - recv,177
  - restart,177
  - retry\_read,178
  - retry\_write,178
  - send,177
  - timer,179
  - tls,179
  - update\_timeout,177
  - writeable,178
- rpki::ipaddr::v4addr,179
  - \_\_new\_\_,180
  - \_\_str\_\_,180
  - bits,180
  - from\_bytes,180
  - to\_bytes,180
- rpki::ipaddr::v6addr,181
  - \_\_new\_\_,181
  - \_\_str\_\_,181
  - bits,182
  - from\_bytes,181
  - to\_bytes,182
- rpki::left\_right
  - enforce\_strict\_up\_down\_xml\_sender,74
- rpki::left\_right::bsc\_elt,182
  - attributes,184
  - booleans,184
  - children,183
  - element\_name,184
  - elements,185
  - handles,185
  - parents,183
  - pkcs10\_request,185
  - private\_key\_id,185
  - repositories,183
  - serve\_pre\_save\_hook,184
  - signing\_cert,185
  - signing\_cert\_crl,185
  - sql\_template,186
- rpki::left\_right::child\_elt,186
  - attributes,188
  - booleans,188
  - bpki\_cert,189
  - bpki\_glue,189
  - ca\_from\_class\_name,187
  - child\_certs,187
  - clear\_https\_ta\_cache,189
  - element\_name,189
  - elements,189

- endElement, 187
- handles, 189
- parents, 187
- serve\_destroy\_hook, 188
- serve\_post\_save\_hook, 188
- serve\_up\_down, 188
- sql\_template, 190
- rpki::left\_right::cms\_msg, 190
  - encoding, 191
  - saxify, 191
  - schema, 191
- rpki::left\_right::data\_elt, 191
  - bsc, 192
  - handles, 194
  - make\_reply\_clone\_hook, 192
  - self, 192
  - self\_handle, 194
  - self\_id, 194
  - serve\_fetch\_all, 192
  - serve\_fetch\_handle, 193
  - serve\_fetch\_one\_maybe, 193
  - serve\_pre\_save\_hook, 193
- rpki::left\_right::left\_right\_namespace, 194
  - nsmmap, 195
  - xmlns, 195
- rpki::left\_right::list\_published\_objects\_elt, 195
  - attributes, 196
  - element\_name, 196
  - make\_reply, 196
  - obj, 196
  - serve\_dispatch, 196
  - text\_attribute, 197
- rpki::left\_right::list\_resources\_elt, 197
  - asn, 198
  - attributes, 198
  - element\_name, 199
  - ipv4, 199
  - ipv6, 199
  - startElement, 198
  - toXML, 198
  - valid\_until, 199
- rpki::left\_right::list\_roa\_requests\_elt, 199
  - attributes, 200
  - element\_name, 200
  - ipv4, 201
  - ipv6, 201
  - startElement, 200
- rpki::left\_right::msg, 201
  - pdus, 202
  - serve\_top\_level, 202
  - version, 202
- rpki::left\_right::parent\_elt, 203
  - attributes, 205
  - booleans, 205
  - bpki\_cms\_cert, 205
  - bpki\_cms\_glue, 206
  - bpki\_https\_cert, 206
  - bpki\_https\_glue, 206
  - cas, 204
  - element\_name, 206
  - elements, 206
  - handles, 206
  - query\_up\_down, 204
  - repository, 204
  - serve\_post\_save\_hook, 204
  - serve\_rekey, 204
  - serve\_revoke, 204
  - serve\_revoke\_forgotten, 205
  - sql\_template, 207
- rpki::left\_right::report\_error\_elt, 207
  - attributes, 208
  - element\_name, 208
  - error\_code, 209
  - error\_text, 209
  - from\_exception, 208
  - self\_handle, 209
  - tag, 209
  - text\_attribute, 209
- rpki::left\_right::repository\_elt, 209
  - attributes, 211
  - bpki\_cert, 211
  - bpki\_glue, 211
  - call\_pubd, 210
  - default\_pubd\_handle, 210
  - element\_name, 211
  - elements, 212
  - handles, 212
  - parents, 211
  - sql\_template, 212
- rpki::left\_right::sax\_handle, 212

- name,213
- pdu,213
- version,213
- rpki::left\_right::self\_elt,213
  - attributes,219
  - booleans,219
  - bpki\_cert,219
  - bpki\_glue,219
  - bscs,215
  - children,215
  - client\_poll,215
  - crl\_interval,220
  - cron,215
  - element\_name,220
  - elements,220
  - handles,220
  - parents,215
  - regen\_margin,220
  - regenerate\_crls\_and\_manifests,216
  - repositories,216
  - roas,216
  - serve\_fetch\_all,216
  - serve\_fetch\_handle,217
  - serve\_fetch\_one\_maybe,217
  - serve\_post\_save\_hook,217
  - serve\_publish\_world\_now,217
  - serve\_rekey,218
  - serve\_revoke,218
  - serve\_revoke\_forgetting,218
  - serve\_run\_now,218
  - sql\_template,220
  - update\_children,218
  - update\_roas,219
  - use\_hsm,221
- rpki::log
  - debug,76
  - enable\_trace,76
  - error,76
  - info,76
  - init,75
  - note,76
  - pid,77
  - set\_trace,75
  - tag,77
  - trace,75
  - traceback,76
  - use\_syslog,77
  - warn,77
- rpki::log::logger,221
  - \_\_call\_\_,221
  - \_\_init\_\_,221
  - priority,222
- rpki::manifest::FileAndHash,222
  - \_\_init\_\_,222
  - le,223
  - hash,223
- rpki::manifest::FilesAndHashes,223
  - \_\_init\_\_,223
- rpki::manifest::Manifest,224
  - \_\_init\_\_,224
  - explicitVersion,224
  - leHashAlg,224
  - leList,224
  - manifestNumber,225
  - nextUpdate,225
  - thisUpdate,225
  - version,225
- rpki::oids
  - name2oid,79
  - oid2name,79
- rpki::publication::certificate\_elt,225
  - element\_name,226
  - payload\_type,226
- rpki::publication::client\_elt,226
  - attributes,228
  - base\_uri,228
  - bpki\_cert,228
  - bpki\_glue,229
  - check\_allowed\_uri,227
  - clear\_https\_traffic\_cache,229
  - element\_name,229
  - elements,229
  - endElement,227
  - serve\_fetch\_all,227
  - serve\_fetch\_one\_maybe,228
  - serve\_post\_save\_hook,228
  - sql\_template,229
- rpki::publication::cms\_msg,230
  - encoding,230
  - saxify,230
  - schema,230
- rpki::publication::content\_elt,231



- attributes [233](#)
- con g\_id, [233](#)
- element\_name [233](#)
- elements [233](#)
- fetch, [232](#)
- serve\_fetch\_one\_maybe, [232](#)
- serve\_set [232](#)
- sql\_template [233](#)
- startElement [232](#)
- wired\_in\_con g\_id, [233](#)
- rpki::publication::control\_elt [234](#)
  - serve\_dispatch [234](#)
- rpki::publication::crl\_elt [235](#)
  - element\_name [235](#)
  - payload\_type [235](#)
- rpki::publication::manifest\_elt [235](#)
  - element\_name [236](#)
  - payload\_type [236](#)
- rpki::publication::msg [236](#)
  - pdus, [237](#)
  - serve\_top\_level [237](#)
  - version, [237](#)
- rpki::publication::publication\_ -
  - namespace [238](#)
  - nsmmap [238](#)
  - xmlns, [238](#)
- rpki::publication::publication\_object\_elt, [239](#)
  - attributes [241](#)
  - endElement [240](#)
  - make\_publish [240](#)
  - make\_withdraw [240](#)
  - payload, [241](#)
  - payload\_type [242](#)
  - raise\_if\_error [240](#)
  - serve\_dispatch [240](#)
  - serve\_publish [240](#)
  - serve\_withdraw [241](#)
  - toXML, [241](#)
  - uri\_to\_ lename, [241](#)
- rpki::publication::report\_error\_elt [242](#)
  - \_\_str\_\_ [243](#)
  - attributes [243](#)
  - element\_name [244](#)
  - error\_code [244](#)
  - error\_text, [244](#)
  - from\_exception [243](#)
  - raise\_if\_error [243](#)
  - tag, [244](#)
  - text\_attribute [244](#)
- rpki::publication::roa\_elt [245](#)
  - element\_name [245](#)
  - payload\_type [245](#)
- rpki::publication::sax\_handle [245](#)
  - name, [246](#)
  - pdu, [246](#)
  - version, [246](#)
- rpki::relaxng
  - left\_right, [81](#)
  - publication, [81](#)
  - up\_down, [81](#)
- rpki::resource\_set
  - \_bs2long [83](#)
  - \_long2bs [83](#)
  - \_rsplit, [83](#)
  - inherit\_token, [84](#)
  - test1, [84](#)
  - test2, [84](#)
- rpki::resource\_set::resource\_base [246](#)
  - \_\_eq\_\_ [247](#)
  - \_\_init\_\_, [247](#)
  - \_\_ne\_\_ [248](#)
  - \_\_str\_\_ [248](#)
  - asn, [249](#)
  - empty, [248](#)
  - from\_rfc3779\_tuples [248](#)
  - intersection [248](#)
  - oversized [248](#)
  - undersized [249](#)
  - union, [249](#)
  - v4, [249](#)
  - v6, [249](#)
  - valid\_until, [250](#)
- rpki::resource\_set::resource\_range [250](#)
  - \_\_cmp\_\_ [251](#)
  - \_\_init\_\_, [251](#)
  - max, [251](#)
  - min, [251](#)
- rpki::resource\_set::resource\_range\_as, [251](#)
  - \_\_str\_\_ [252](#)
  - datum\_type [252](#)

min, 253  
 to\_rfc3779\_tuple, 252  
 rpki::resource\_set::resource\_range\_ip, 253  
     \_\_str\_\_, 254  
     \_pre\_xlen, 254  
     make\_pre\_x, 254  
     to\_rfc3779\_tuple, 254  
 rpki::resource\_set::resource\_range\_ipv4, 254  
     datum\_type, 255  
 rpki::resource\_set::resource\_range\_ipv6, 255  
     datum\_type, 256  
 rpki::resource\_set::resource\_set, 256  
     \_\_init\_\_, 257  
     \_\_str\_\_, 257  
     \_\_comm\_\_, 257  
     contains, 257  
     difference, 257  
     from\_sql, 258  
     inherit, 259  
     intersection, 258  
     issubset, 258  
     issuperset, 258  
     symmetric\_difference, 258  
     union, 259  
 rpki::resource\_set::resource\_set\_ip, 259  
     inherit, 261  
     parse\_rfc3779\_tuple, 260  
     parse\_str, 260  
     range\_type, 261  
     to\_rfc3779\_tuple, 260  
 rpki::resource\_set::resource\_set\_ip, 261  
     inherit, 262  
     parse\_rfc3779\_tuple, 262  
     parse\_str, 262  
     to\_rfc3779\_tuple, 262  
 rpki::resource\_set::resource\_set\_ipv4, 263  
     a, 263  
     range\_type, 263  
 rpki::resource\_set::resource\_set\_ipv6, 264  
     a, 264  
     range\_type, 264  
 rpki::resource\_set::roa\_pre, 265  
     \_\_cmp\_\_, 265  
     \_\_init\_\_, 266  
     \_\_str\_\_, 266  
     max, 266  
     max\_pre\_xlen, 267  
     min, 266  
     pre\_x, 267  
     pre\_xlen, 267  
     to\_resource\_range, 266  
     to\_roa\_tuple, 267  
 rpki::resource\_set::roa\_pre\_x\_ipv4, 267  
     range\_type, 268  
 rpki::resource\_set::roa\_pre\_x\_ipv6, 268  
     range\_type, 269  
 rpki::resource\_set::roa\_pre\_x\_set, 269  
     \_\_init\_\_, 269  
     \_\_str\_\_, 269  
     from\_sql, 270  
     parse\_str, 270  
     to\_resource\_set, 270  
     to\_roa\_tuple, 270  
 rpki::resource\_set::roa\_pre\_x\_set\_ipv4, 271  
     pre\_x\_type, 271  
     resource\_set\_type, 271  
 rpki::resource\_set::roa\_pre\_x\_set\_ipv6, 272  
     pre\_x\_type, 272  
     resource\_set\_type, 272  
 rpki::roa::ROAIPAddress, 273  
     \_\_init\_\_, 273  
     address, 273  
     maxLength, 273  
 rpki::roa::ROAIPAddresses, 274  
     \_\_init\_\_, 274  
 rpki::roa::ROAIPAddressFamilies, 274  
     \_\_init\_\_, 275  
 rpki::roa::ROAIPAddressFamily, 275  
     \_\_init\_\_, 275  
     addresses, 276  
     addressFamily, 276  
 rpki::roa::RouteOriginAttestation, 276  
     \_\_init\_\_, 276  
     asID, 277  
     explicitVersion, 277

- ipAddrBlocks, 277
- version, 277
- rpki::rpki\_engine::ca\_detail\_obj, 277
  - activate, 279
  - ca, 279
  - ca\_cert\_uri, 283
  - ca\_id, 283
  - child\_certs, 279
  - create, 279
  - crl\_published, 283
  - crl\_published\_callback, 279
  - crl\_uri, 279
  - crl\_uri\_tail, 280
  - delete, 280
  - gctx, 283
  - generate\_crl, 280
  - generate\_manifest, 280
  - generate\_manifest\_cert, 280
  - issue, 281
  - issue\_ee, 281
  - latest\_ca\_cert, 283
  - latest\_crl, 283
  - latest\_manifest, 284
  - latest\_manifest\_cert, 284
  - manifest\_private\_key\_id, 284
  - manifest\_public\_key, 284
  - manifest\_published, 284
  - manifest\_published\_callback, 281
  - manifest\_uri, 281
  - nextUpdate, 284
  - private\_key\_id, 284
  - public\_key, 285
  - revoke, 281
  - revoked\_certs, 282
  - roas, 282
  - sql\_decode, 282
  - sql\_template, 285
  - state, 285
  - update, 282
- rpki::rpki\_engine::ca\_obj, 285
  - ca\_details, 287
  - check\_for\_updates, 287
  - construct\_sia\_uri, 287
  - create, 287
  - delete, 287
  - fetch\_active, 288
  - fetch\_deprecated, 288
  - fetch\_issue\_response\_candidates, 288
  - fetch\_pending, 288
  - fetch\_revoked, 288
  - gctx, 290
  - last\_crl\_sn, 290
  - last\_issued\_sn, 290
  - last\_manifest\_sn, 290
  - next\_crl\_number, 289
  - next\_manifest\_number, 289
  - next\_serial\_number, 289
  - parent, 289
  - parent\_id, 290
  - parent\_resource\_class, 291
  - rekey, 289
  - revoke, 290
  - sia\_uri, 291
  - sql\_template, 291
- rpki::rpki\_engine::child\_cert\_obj, 291
  - \_\_init\_\_, 292
  - ca\_detail, 292
  - ca\_detail\_id, 294
  - cert, 294
  - child, 292
  - child\_id, 294
  - fetch, 293
  - gctx, 294
  - published, 294
  - published\_callback, 293
  - reissue, 293
  - revoke, 293
  - sql\_template, 295
  - uri, 293
  - uri\_tail, 294
- rpki::rpki\_engine::publication\_queue, 295
  - \_\_init\_\_, 296
  - \_add, 296
  - call\_pubd, 296
  - handlers, 297
  - msgs, 297
  - publish, 296
  - replace, 297
  - repositories, 297
  - uris, 297

- withdraw, 296
- rpki::rpki\_engine::revoked\_cert\_obj, 298
  - \_\_init\_\_, 298
  - ca\_detail, 298
  - ca\_detail\_id, 299
  - expires, 299
  - gctx, 299
  - revoke, 299
  - revoked, 299
  - serial, 299
  - sql\_template, 300
- rpki::rpki\_engine::roa\_obj, 300
  - \_\_init\_\_, 301
  - asn, 304
  - ca\_detail, 301
  - ca\_detail\_id, 304
  - cert, 304
  - gctx, 304
  - generate, 301
  - ipv4, 305
  - ipv6, 305
  - published, 305
  - published\_callback, 302
  - regenerate, 302
  - revoke, 302
  - roa, 305
  - self, 303
  - self\_id, 305
  - sql\_delete\_hook, 303
  - sql\_fetch\_hook, 303
  - sql\_insert\_hook, 303
  - sql\_template, 305
  - update, 303
  - uri, 304
  - uri\_tail, 304
- rpki::rpki\_engine::rpki\_context, 306
  - \_\_init\_\_, 307
  - bpki\_ta, 309
  - build\_https\_ta\_cache, 307
  - checkpoint, 307
  - clear\_https\_ta\_cache, 307
  - cron, 308
  - cron\_keepalive, 309
  - cron\_period, 310
  - cron\_timeout, 310
  - cron\_timer, 310
  - cronjob\_handler, 308
  - https\_server\_host, 310
  - https\_server\_port, 310
  - https\_ta\_cache, 310
  - initial\_delay, 310
  - irbe\_cert, 311
  - irdb\_cert, 311
  - irdb\_query, 308
  - irdb\_query\_child\_resource, 308
  - irdb\_query\_roa\_request, 308
  - irdb\_url, 311
  - left\_right\_handler, 309
  - publication\_kludge\_base, 311
  - rpkiid\_cert, 311
  - rpkiid\_key, 311
  - sql, 311
  - start\_cron, 309
  - up\_down\_handler, 309
  - up\_down\_url\_regex, 312
  - use\_internal\_cron, 312
- rpki::sql::session, 312
  - \_\_init\_\_, 313
  - \_exceptions\_enabled, 315
  - \_wrap\_execute, 313
  - assert\_pristine, 313
  - cache, 315
  - cache\_clear, 314
  - close, 314
  - connect, 314
  - cur, 315
  - database, 315
  - db, 316
  - dirty, 316
  - execute, 314
  - executemany, 314
  - fetchall, 314
  - lastrowid, 314
  - password, 316
  - ping, 315
  - sweep, 315
  - username, 316
- rpki::sql::sql\_persistent, 316
  - gctx, 321
  - sql\_debug, 321
  - sql\_decode, 317
  - sql\_delete, 318

- sql\_delete\_hook, 318
- sql\_deleted, 321
- sql\_encode, 318
- sql\_fetch, 318
- sql\_fetch\_all, 319
- sql\_fetch\_hook, 319
- sql\_fetch\_where, 319
- sql\_fetch\_where1, 319
- sql\_in\_db, 322
- sql\_init, 319
- sql\_insert\_hook, 320
- sql\_is\_dirty, 320
- sql\_mark\_clean, 320
- sql\_mark\_deleted, 320
- sql\_mark\_dirty, 320
- sql\_store, 321
- sql\_update\_hook, 321
- rpki::sql::template, 322
  - \_\_init\_\_, 323
  - columns, 323
  - delete, 323
  - index, 323
  - insert, 323
  - map, 323
  - select, 323
  - table, 324
  - update, 324
- rpki::sundial
  - \_cast, 88
  - now, 88
  - test, 88
- rpki::sundial::datetime, 324
  - \_\_add\_\_, 325
  - \_\_radd\_\_, 325
  - \_\_rsub\_\_, 325
  - \_\_str\_\_, 325
  - \_\_sub\_\_, 325
  - earlier, 326
  - from\_sql, 326
  - fromASN1tuple, 326
  - fromdatetime, 326
  - fromGeneralizedTime, 326
  - fromUTCTime, 326
  - fromXMLtime, 327
  - later, 327
  - PKIX\_threshold, 328
  - to\_sql, 327
  - toASN1tuple, 327
  - toGeneralizedTime, 327
  - totimestamp, 328
  - toUTCTime, 328
  - toXMLtime, 328
- rpki::sundial::timedelta, 329
  - \_\_abs\_\_, 330
  - \_\_add\_\_, 330
  - \_\_div\_\_, 330
  - \_\_oordiv\_\_, 330
  - \_\_mul\_\_, 330
  - \_\_neg\_\_, 330
  - \_\_pos\_\_, 330
  - \_\_radd\_\_, 330
  - \_\_rdiv\_\_, 331
  - \_\_r oordiv\_\_, 331
  - \_\_rmul\_\_, 331
  - \_\_rsub\_\_, 331
  - \_\_sub\_\_, 331
  - convert\_to\_second, 331
  - fromtimedelta, 331
  - parse, 332
  - regex, 332
- rpki::up\_down
  - nsmmap, 90
  - xmlns, 90
- rpki::up\_down::base\_elt, 332
  - check\_response, 333
  - endElement, 333
  - make\_b64elt, 333
  - make\_elt, 334
  - serve\_pdu, 334
  - startElement, 334
- rpki::up\_down::certificate\_elt, 335
  - cert, 336
  - cert\_url, 336
  - endElement, 335
  - req\_resource\_set, 336
  - req\_resource\_set\_ip, 336
  - req\_resource\_set\_ip, 336
  - startElement, 335
  - toXML, 336
- rpki::up\_down::class\_elt, 337
  - \_\_init\_\_, 338
  - cert\_url, 339

- certs, [339](#)
- class\_name, [339](#)
- endElement, [338](#)
- from\_resource\_bag, [338](#)
- issuer, [339](#)
- resource\_set\_a, [339](#)
- resource\_set\_ipv4, [339](#)
- resource\_set\_ipv6, [339](#)
- resource\_set\_notafter, [340](#)
- startElement, [338](#)
- suggested\_sia\_header, [340](#)
- to\_resource\_bag, [338](#)
- toXML, [338](#)
- rpki::up\_down::class\_response\_syntax, [340](#)
  - \_\_init\_\_, [341](#)
  - classes, [341](#)
  - startElement, [341](#)
  - toXML, [341](#)
- rpki::up\_down::cms\_msg, [341](#)
  - encoding, [342](#)
  - saxify, [342](#)
  - schema, [342](#)
- rpki::up\_down::error\_response\_pdu, [342](#)
  - \_\_init\_\_, [343](#)
  - check\_response, [343](#)
  - codes, [344](#)
  - description, [344](#)
  - endElement, [343](#)
  - exceptions, [344](#)
  - status, [345](#)
  - toXML, [344](#)
- rpki::up\_down::issue\_pdu, [345](#)
  - class\_name, [347](#)
  - endElement, [346](#)
  - pkcs10, [347](#)
  - query, [346](#)
  - req\_resource\_set\_a, [347](#)
  - req\_resource\_set\_ipv4, [347](#)
  - req\_resource\_set\_ipv6, [347](#)
  - serve\_pdu, [346](#)
  - startElement, [346](#)
  - toXML, [346](#)
- rpki::up\_down::issue\_response\_pdu, [348](#)
  - check\_response, [348](#)
- rpki::up\_down::list\_pdu, [348](#)
  - query, [349](#)
  - serve\_pdu, [349](#)
  - toXML, [349](#)
- rpki::up\_down::list\_response\_pdu, [349](#)
- rpki::up\_down::message\_pdu, [350](#)
  - \_\_str\_\_, [351](#)
  - log\_query, [351](#)
  - make\_query, [351](#)
  - name2type, [352](#)
  - payload, [352](#)
  - recipient, [353](#)
  - sender, [353](#)
  - serve\_error, [351](#)
  - serve\_top\_level, [351](#)
  - startElement, [352](#)
  - toXML, [352](#)
  - type, [353](#)
  - type2name, [353](#)
  - version, [353](#)
- rpki::up\_down::multi\_uri, [354](#)
  - \_\_init\_\_, [354](#)
  - \_\_str\_\_, [354](#)
  - rsync, [354](#)
- rpki::up\_down::revoke\_pdu, [355](#)
  - class\_name, [356](#)
  - get\_SKI, [355](#)
  - query, [355](#)
  - serve\_pdu, [356](#)
  - ski, [356](#)
- rpki::up\_down::revoke\_response\_pdu, [356](#)
- rpki::up\_down::revoke\_syntax, [357](#)
  - class\_name, [358](#)
  - ski, [358](#)
  - startElement, [357](#)
  - toXML, [357](#)
- rpki::up\_down::sax\_handler, [358](#)
  - name, [359](#)
  - pdu, [359](#)
  - version, [359](#)
- rpki::x509
  - calculate\_SKI, [92](#)
  - POWify\_OID, [92](#)
- rpki::x509::CMS\_object, [359](#)
  - content, [362](#)
  - debug\_cms\_cert, [362](#)

- DER, 362
- dump\_on\_verify\_failure, 363
- econtent\_oid, 363
- extract, 361
- formats, 363
- get\_content, 361
- get\_DER, 361
- get\_POW, 361
- other\_clear, 363
- pem\_converter, 363
- POW, 364
- print\_on\_der\_error, 364
- require\_crls, 364
- set\_content, 361
- sign, 362
- verify, 362
- rpki::x509::CRL, 364
  - DER, 367
  - formats, 367
  - generate, 365
  - get\_DER, 365
  - get\_POW, 366
  - get\_POWpkix, 366
  - getIssuer, 366
  - getNextUpdate, 366
  - getThisUpdate, 366
  - pem\_converter, 367
  - POW, 367
  - POWpkix, 367
- rpki::x509::DeadDrop, 368
  - \_\_init\_\_, 368
  - dump, 368
  - maildir, 369
  - pid, 369
- rpki::x509::DER\_CMS\_object, 369
  - content, 370
  - decode, 370
  - encode, 370
- rpki::x509::DER\_object, 370
  - \_\_cmp\_\_, 372
  - \_\_init\_\_, 372
  - clear, 372
  - DER, 376
  - dumpasn1, 372
  - empty, 372
  - formats, 376
  - from\_sql, 372
  - gAKI, 373
  - get\_3779resource, 373
  - get\_AIA, 373
  - get\_AKI, 373
  - get\_Base64, 373
  - get\_basicConstraint, 374
  - get\_DER, 374
  - get\_PEM, 374
  - get\_SIA, 374
  - get\_SKI, 374
  - gSKI, 375
  - hAKI, 375
  - hSKI, 375
  - is\_CA, 375
  - other\_clear, 376
  - pem\_converter, 377
  - set, 375
  - to\_sql, 376
- rpki::x509::PEM\_converter, 377
  - \_\_init\_\_, 378
  - b, 378
  - e, 378
  - looks\_like\_PEM, 378
  - to\_DER, 378
  - to\_PEM, 378
- rpki::x509::PKCS10, 379
  - check\_valid\_rpki, 380
  - create, 380
  - create\_ca, 380
  - DER, 381
  - formats, 381
  - get\_DER, 380
  - get\_POWpkix, 380
  - getPublicKey, 380
  - pem\_converter, 381
  - POWpkix, 381
- rpki::x509::ROA, 382
  - build, 382
  - content\_class, 382
  - econtent\_oid, 382
  - pem\_converter, 383
- rpki::x509::RSA, 383
  - DER, 385
  - formats, 385
  - generate, 384

- get\_DER,384
- get\_POW,384
- get\_public\_DER,384
- get\_RSAPublic,385
- get\_SKI,385
- pem\_converter,385
- POW,386
- rpki::x509::RSAPublic,386
  - DER,387
  - formats,388
  - get\_DER,387
  - get\_POW,387
  - get\_SKI,387
  - pem\_converter,388
  - POW,388
- rpki::x509::SignedManifest,388
  - build,389
  - content\_class,390
  - econtent\_oid,390
  - getNextUpdate,389
  - getThisUpdate,389
  - pem\_converter,390
- rpki::x509::X509,390
  - cross\_certify,391
  - DER,394
  - expired,392
  - formats,394
  - get\_DER,392
  - get\_POW,392
  - get\_POWpkix,392
  - getIssuer,392
  - getNotAfter,392
  - getNotBefore,393
  - getPublicKey,393
  - getSerial,393
  - getSubject,393
  - issue,393
  - normalize\_chain,394
  - pem\_converter,394
  - POW,395
  - POWpkix,395
- rpki::x509::XML\_CMS\_object,395
  - content,397
  - decode,396
  - dump\_inbound\_cms,397
  - dump\_outbound\_cms,398
  - dump\_to\_disk,396
  - econtent\_oid,398
  - encode,396
  - pretty\_print\_content,396
  - schema\_check,397
  - unwrap,397
  - wrap,397
- rpki::xml\_utils::base\_elt,398
  - \_\_str\_\_,399
  - attributes,401
  - booleans,401
  - elements,401
  - endElement,399
  - make\_b64elt,400
  - make\_elt,400
  - make\_pdu,400
  - read\_attrs,400
  - startElement,400
  - toXML,401
- rpki::xml\_utils::data\_elt,402
  - endElement,403
  - make\_reply,403
  - make\_reply\_clone\_hook,403
  - serve\_create,403
  - serve\_destroy,403
  - serve\_destroy\_hook,403
  - serve\_dispatch,404
  - serve\_fetch\_one,404
  - serve\_get,404
  - serve\_list,404
  - serve\_post\_save\_hook,404
  - serve\_pre\_save\_hook,405
  - serve\_set,405
  - toXML,405
  - unimplemented\_control,405
- rpki::xml\_utils::msg,406
  - \_\_str\_\_,407
  - endElement,407
  - is\_query,407
  - is\_reply,407
  - query,407
  - reply,407
  - startElement,408
  - toXML,408
  - type,408
  - version,408



- rpki::xml\_utils::sax\_handler [409](#)
  - \_\_init\_\_, [409](#)
  - characters, [410](#)
  - create\_top\_level, [410](#)
  - endElement, [410](#)
  - endElementNS, [410](#)
  - result, [411](#)
  - saxify, [410](#)
  - stack, [411](#)
  - startElement, [410](#)
  - startElementNS, [411](#)
  - text, [411](#)
- rpki::xml\_utils::text\_elt, [412](#)
  - endElement, [412](#)
  - text\_attribute, [413](#)
  - toXML, [412](#)
- rpki\_base\_uri
  - rootd, [60](#)
- rpki\_class\_name
  - rootd, [60](#)
- rpki\_content\_type
  - rpki::https, [71](#)
- rpki\_engine.py(2934), [426](#)
- rpki\_root\_cert
  - rootd, [60](#)
- rpki\_root\_cert\_le
  - rootd, [60](#)
- rpki\_root\_cert\_uri
  - rootd, [61](#)
- rpki\_root\_crl
  - rootd, [61](#)
- rpki\_root\_dir
  - rootd, [61](#)
- rpki\_root\_key
  - rootd, [61](#)
- rpki\_root\_manifest
  - rootd, [61](#)
- rpki\_subject\_cert
  - rootd, [61](#)
- rpki\_subject\_lifetime
  - rootd, [61](#)
- rpki\_subject\_pkcs10
  - rootd, [62](#)
- rpki\_subject\_regen
  - rootd, [62](#)
- rpkid, [93](#)
  - cfg\_le, [94](#)
  - main, [94](#)
  - pro le, [94](#)
- rpkid.py(2913), [427](#)
- rpkid\_cert
  - irdbd, [52](#)
  - rpki::rpki\_engine::rpkid\_context, [311](#)
- rpkid\_key
  - rpki::rpki\_engine::rpkid\_context, [311](#)
- rsync
  - rpki::up\_down::multi\_uri, [354](#)
- run\_debug
  - rpki::async::timer, [133](#)
- run\_deferred
  - rpki::async, [64](#)
- runq
  - rpki::async::timer, [131](#)
- saxify
  - irbe\_cli::left\_right\_cms\_msg, [106](#)
  - irbe\_cli::publication\_cms\_msg, [109](#)
  - rootd::cms\_msg, [19](#)
  - rpki::left\_right::cms\_msg, [191](#)
  - rpki::publication::cms\_msg, [230](#)
  - rpki::up\_down::cms\_msg, [42](#)
  - rpki::xml\_utils::sax\_handler, [410](#)
- schema
  - rpki::left\_right::cms\_msg, [191](#)
  - rpki::publication::cms\_msg, [230](#)
  - rpki::up\_down::cms\_msg, [42](#)
- schema\_check
  - rpki::x509::XML\_CMS\_object, [397](#)
- seconds\_until\_wakeup
  - rpki::async::timer, [131](#)
- select
  - rpki::sql::template, [323](#)
- self
  - rpki::left\_right::data\_elt, [192](#)
  - rpki::rpki\_engine::roa\_obj, [303](#)
- self\_handle
  - rpki::left\_right::data\_elt, [194](#)
  - rpki::left\_right::report\_error\_elt, [209](#)
- self\_id
  - rpki::left\_right::data\_elt, [194](#)

- rpki::rpki\_engine::roa\_obj, 305
- send
  - rpki::https::http\_stream, 177
- send\_error
  - rpki::https::http\_server, 172
- send\_message
  - rpki::https::http\_server, 172
- send\_reply
  - rpki::https::http\_server, 172
- send\_request
  - rpki::https::http\_client, 157
  - rpki::https::http\_queue, 166
- sender
  - rpki::up\_down::message\_pdu, 353
- Sequence, 413
- SequenceOf, 413
- serial
  - rpki::rpki\_engine::revoked\_cert\_obj, 299
- serve\_create
  - rpki::xml\_utils::data\_elt, 403
- serve\_destroy
  - rpki::xml\_utils::data\_elt, 403
- serve\_destroy\_hook
  - rpki::left\_right::child\_elt, 188
  - rpki::xml\_utils::data\_elt, 403
- serve\_dispatch
  - rpki::left\_right::list\_published\_objects\_elt, 196
  - rpki::publication::control\_elt, 234
  - rpki::publication::publication\_object\_elt, 240
  - rpki::xml\_utils::data\_elt, 404
- serve\_error
  - rpki::up\_down::message\_pdu, 351
- serve\_fetch\_all
  - rpki::left\_right::data\_elt, 192
  - rpki::left\_right::self\_elt, 216
  - rpki::publication::client\_elt, 227
- serve\_fetch\_handle
  - rpki::left\_right::data\_elt, 193
  - rpki::left\_right::self\_elt, 217
- serve\_fetch\_one
  - rpki::xml\_utils::data\_elt, 404
- serve\_fetch\_one\_maybe
  - rpki::left\_right::data\_elt, 193
- rpki::left\_right::self\_elt, 217
- rpki::publication::client\_elt, 228
- rpki::publication::control\_elt, 232
- serve\_get
  - rpki::xml\_utils::data\_elt, 404
- serve\_list
  - rpki::xml\_utils::data\_elt, 404
- serve\_pdu
  - rootd::issue\_pdu, 119
  - rootd::list\_pdu, 120
  - rootd::revoke\_pdu, 122
  - rpki::up\_down::base\_elt, 334
  - rpki::up\_down::issue\_pdu, 346
  - rpki::up\_down::list\_pdu, 349
  - rpki::up\_down::revoke\_pdu, 356
- serve\_post\_save\_hook
  - rpki::left\_right::child\_elt, 188
  - rpki::left\_right::parent\_elt, 204
  - rpki::left\_right::self\_elt, 217
  - rpki::publication::client\_elt, 228
  - rpki::xml\_utils::data\_elt, 404
- serve\_pre\_save\_hook
  - rpki::left\_right::bsc\_elt, 184
  - rpki::left\_right::data\_elt, 193
  - rpki::xml\_utils::data\_elt, 405
- serve\_publish
  - rpki::publication::publication\_object\_elt, 240
- serve\_publish\_world\_now
  - rpki::left\_right::self\_elt, 217
- serve\_rekey
  - rpki::left\_right::parent\_elt, 204
  - rpki::left\_right::self\_elt, 218
- serve\_revoke
  - rpki::left\_right::parent\_elt, 204
  - rpki::left\_right::self\_elt, 218
- serve\_revoke\_forgotten
  - rpki::left\_right::parent\_elt, 205
  - rpki::left\_right::self\_elt, 218
- serve\_run\_now
  - rpki::left\_right::self\_elt, 218
- serve\_set
  - rpki::publication::control\_elt, 232
  - rpki::xml\_utils::data\_elt, 405
- serve\_top\_level
  - rpki::left\_right::msg, 202

rpki::publication::msg [237](#)  
 rpki::up\_down::message\_pdu [351](#)  
 serve\_up\_down  
   rpki::left\_right::child\_elt [188](#)  
 serve\_withdraw  
   rpki::publication::publication\_  
     object\_elt [241](#)  
 server  
   rpki::https [70](#)  
 server\_cert  
   irbe\_cli::caller [98](#)  
   irdbd [52](#)  
   rootd [62](#)  
 server\_ta  
   irbe\_cli::caller [98](#)  
 set  
   rpki::async::timer [131](#)  
   rpki::x509::DER\_object [375](#)  
 set\_content  
   rpki::x509::CMS\_object [361](#)  
 set\_errback  
   rpki::async::timer [132](#)  
 set\_global\_ags  
   rpki::con\_g::parser [136](#)  
 set\_handler  
   rpki::async::timer [132](#)  
 set\_state  
   rpki::https::http\_client [157](#)  
 set\_subject\_cert  
   rootd [58](#)  
 set\_subject\_pkcs10  
   rootd [58](#)  
 set\_trace  
   rpki::log [75](#)  
 sia\_uri  
   rpki::rpki\_engine::ca\_obj [291](#)  
 sign  
   rpki::x509::CMS\_object [362](#)  
 signing\_cert  
   irbe\_cli::bsc\_elt [97](#)  
   rpki::left\_right::bsc\_elt [185](#)  
 signing\_cert\_crl  
   irbe\_cli::bsc\_elt [97](#)  
   rpki::left\_right::bsc\_elt [185](#)  
 ski  
   rpki::up\_down::revoke\_pdu [356](#)  
   rpki::up\_down::revoke\_syntax [358](#)  
 software\_name  
   rpki::https::http\_message [464](#)  
 sql  
   pubd::pubd\_context [118](#)  
   rpki::rpki\_engine::rpkid\_context,  
     [311](#)  
   sql.py(2895) [427](#)  
   sql\_debug  
     rpki::sql::sql\_persisten [821](#)  
   sql\_decode  
     rpki::rpki\_engine::ca\_detail\_obj,  
       [282](#)  
     rpki::sql::sql\_persisten [817](#)  
   sql\_delete  
     rpki::sql::sql\_persisten [818](#)  
   sql\_delete\_hook  
     rpki::rpki\_engine::roa\_obj [303](#)  
     rpki::sql::sql\_persisten [818](#)  
   sql\_deleted  
     rpki::sql::sql\_persisten [821](#)  
   sql\_encode  
     rpki::sql::sql\_persisten [818](#)  
   sql\_fetch  
     rpki::sql::sql\_persisten [818](#)  
   sql\_fetch\_all  
     rpki::sql::sql\_persisten [819](#)  
   sql\_fetch\_hook  
     rpki::rpki\_engine::roa\_obj [303](#)  
     rpki::sql::sql\_persisten [819](#)  
   sql\_fetch\_where  
     rpki::sql::sql\_persisten [819](#)  
   sql\_fetch\_where1  
     rpki::sql::sql\_persisten [819](#)  
   sql\_in\_db  
     rpki::sql::sql\_persisten [822](#)  
   sql\_init  
     rpki::sql::sql\_persisten [819](#)  
   sql\_insert\_hook  
     rpki::rpki\_engine::roa\_obj [303](#)  
     rpki::sql::sql\_persisten [820](#)  
   sql\_is\_dirty  
     rpki::sql::sql\_persisten [820](#)  
   sql\_mark\_clean  
     rpki::sql::sql\_persisten [820](#)  
   sql\_mark\_deleted

- rpki::sql::sql\_persisten**820**
- sql\_mark\_dirty
  - rpki::sql::sql\_persisten**820**
- sql\_store
  - rpki::sql::sql\_persisten**821**
- sql\_template
  - rpki::left\_right::bsc\_elt**186**
  - rpki::left\_right::child\_elt**190**
  - rpki::left\_right::parent\_elt**207**
  - rpki::left\_right::repository\_elt**212**
  - rpki::left\_right::self\_elt**220**
  - rpki::publication::client\_elt**229**
  - rpki::publication::con g\_elt**233**
  - rpki::rpki\_engine::ca\_detail\_obj, **285**
  - rpki::rpki\_engine::ca\_obj**291**
  - rpki::rpki\_engine::child\_cert\_obj, **295**
  - rpki::rpki\_engine::revoked\_cert\_obj, **300**
  - rpki::rpki\_engine::roa\_obj**305**
- sql\_update\_hook
  - rpki::sql::sql\_persisten**821**
- stack
  - rpki::xml\_utils::sax\_handler**411**
- start
  - rpki::https::http\_client**158**
- start\_cron
  - rpki::rpki\_engine::rpkid\_context, **309**
- startElement
  - rpki::left\_right::list\_resources\_elt, **198**
  - rpki::left\_right::list\_roa\_requests\_ - elt, **200**
  - rpki::publication::con g\_elt**232**
  - rpki::up\_down::base\_elt**334**
  - rpki::up\_down::certi cate\_elt**335**
  - rpki::up\_down::class\_elt**338**
  - rpki::up\_down::class\_response\_ - syntax,**341**
  - rpki::up\_down::issue\_pdu**346**
  - rpki::up\_down::message\_pdu**352**
  - rpki::up\_down::revoke\_synta**357**
  - rpki::xml\_utils::base\_elt**400**
  - rpki::xml\_utils::msg**408**
  - rpki::xml\_utils::sax\_handler**410**
- startElementNS
  - rpki::xml\_utils::sax\_handler**411**
- startup\_msg
  - irdbd, **53**
- state
  - rpki::https::http\_client**159**
  - rpki::rpki\_engine::ca\_detail\_obj, **285**
- status
  - rpki::up\_down::error\_response\_pdu, **345**
- suggested\_sia\_head
  - rpki::up\_down::class\_elt**340**
- sundial.py(2785)**427**
- sweep
  - rpki::sql::session**315**
- symmetric\_difference
  - rpki::resource\_set::resource\_ **318**
- ta
  - rpki::https::http\_client**159**
  - rpki::https::http\_listener**161**
  - rpki::https::http\_queue**167**
- table
  - rpki::sql::template**324**
- tag
  - rpki::left\_right::report\_error\_elt**209**
  - rpki::log, **77**
  - rpki::publication::report\_error\_elt, **244**
- test
  - rpki::sundial,**88**
- test1
  - rpki::resource\_se**84**
- test2
  - rpki::resource\_se**84**
- text
  - rpki::xml\_utils::sax\_handler**411**
- text\_attribute
  - rpki::left\_right::list\_published\_ - objects\_elt,**197**
  - rpki::left\_right::report\_error\_elt**209**
  - rpki::publication::report\_error\_elt, **244**
  - rpki::xml\_utils::text\_elt**413**

- textwrap::TextWrapper [413](#)
- thisUpdate
  - rpki::manifest::Manifest [225](#)
- timeout
  - rpki::https::http\_client [159](#)
  - rpki::https::http\_server [173](#)
- timer
  - rpki::async::gc\_summary [124](#)
  - rpki::https::http\_stream [179](#)
- tls
  - rpki::https::http\_client [159](#)
  - rpki::https::http\_server [173](#)
  - rpki::https::http\_stream [179](#)
- tls\_accept
  - rpki::https::http\_server [172](#)
- tls\_connect
  - rpki::https::http\_client [158](#)
- to\_bytes
  - rpki::ipaddr::v4addr [180](#)
  - rpki::ipaddr::v6addr [182](#)
- to\_DER
  - rpki::x509::PEM\_convert [378](#)
- to\_PEM
  - rpki::x509::PEM\_convert [378](#)
- to\_resource\_bag
  - rpki::up\_down::class\_elt [338](#)
- to\_resource\_range
  - rpki::resource\_set::roa\_pre [266](#)
- to\_resource\_set
  - rpki::resource\_set::roa\_pre x\_set, [270](#)
- to\_rfc3779\_tuple
  - rpki::resource\_set::resource\_range\_trace
    - as, [252](#)
  - rpki::resource\_set::resource\_range\_ -
    - ip, [254](#)
  - rpki::resource\_set::resource\_set\_as, [260](#)
  - rpki::resource\_set::resource\_set\_ip, [262](#)
- to\_roa\_tuple
  - rpki::resource\_set::roa\_pre [267](#)
  - rpki::resource\_set::roa\_pre x\_set, [270](#)
- to\_sql
  - rpki::sundial::datetime [327](#)
- rpki::x509::DER\_object [376](#)
- toASN1tuple
  - rpki::sundial::datetime [327](#)
- toGeneralizedTime
  - rpki::sundial::datetime [327](#)
- top\_opts
  - irbe\_cli, [48](#)
- totimestamp
  - rpki::sundial::datetime [328](#)
- toUTCTime
  - rpki::sundial::datetime [328](#)
- toXML
  - rpki::left\_right::list\_resources\_elt, [198](#)
  - rpki::publication::publication\_ -
    - object\_elt, [241](#)
  - rpki::up\_down::certi cate\_elt, [336](#)
  - rpki::up\_down::class\_elt, [338](#)
  - rpki::up\_down::class\_response\_ -
    - syntax, [341](#)
  - rpki::up\_down::error\_response\_pdu, [344](#)
  - rpki::up\_down::issue\_pdu, [346](#)
  - rpki::up\_down::list\_pdu, [349](#)
  - rpki::up\_down::message\_pdu, [352](#)
  - rpki::up\_down::revoke\_syntax, [357](#)
  - rpki::xml\_utils::base\_elt, [401](#)
  - rpki::xml\_utils::data\_elt, [405](#)
  - rpki::xml\_utils::msg, [408](#)
  - rpki::xml\_utils::text\_elt, [412](#)
- toXMLtime
  - rpki::sundial::datetime [328](#)
- rpki::async::timer, [132](#)
- rpki::log, [75](#)
- traceback
  - rpki::log, [76](#)
- type
  - rpki::up\_down::message\_pdu, [353](#)
  - rpki::xml\_utils::msg, [408](#)
- type2name
  - rootd::message\_pdu, [421](#)
  - rpki::up\_down::message\_pdu, [353](#)
- u
  - irbdb, [53](#)

- undersized
  - rpki::resource\_set::resource\_bag, 249
- unimplemented\_control
  - rpki::xml\_utils::data\_elt, 405
- union
  - rpki::resource\_set::resource\_bag, 249
  - rpki::resource\_set::resource\_set, 249
- unwind\_stack
  - rpki::async::iterator, 126
- unwrap
  - rpki::x509::XML\_CMS\_object, 397
- up\_down
  - rpki::relaxng, 81
- up\_down.py(2935), 428
- up\_down\_handler
  - rootd, 58
  - rpki::rpki\_engine::rpkid\_context, 309
- up\_down\_url\_regexp
  - rpki::rpki\_engine::rpkid\_context, 312
- update
  - rpki::rpki\_engine::ca\_detail\_obj, 282
  - rpki::rpki\_engine::roa\_obj, 303
  - rpki::sql::template, 324
- update\_children
  - rpki::left\_right::self\_elt, 218
- update\_roas
  - rpki::left\_right::self\_elt, 219
- update\_timeout
  - rpki::https::http\_stream, 177
- uri
  - rpki::rpki\_engine::child\_cert\_obj, 293
  - rpki::rpki\_engine::roa\_obj, 304
- uri\_tail
  - rpki::rpki\_engine::child\_cert\_obj, 294
  - rpki::rpki\_engine::roa\_obj, 304
- uri\_to\_lename
  - rpki::publication::publication\_object\_elt, 241
- uris
  - rpki::rpki\_engine::publication\_queue, 297
- url
  - irbe\_cli::caller, 99
- usage
  - irbe\_cli, 46
  - irbe\_cli::cmd\_elt\_mixin, 102
  - irbe\_cli::cmd\_msg\_mixin, 104
- usage\_ll
  - irbe\_cli, 48
- use\_hsm
  - rpki::left\_right::self\_elt, 221
- use\_internal\_cron
  - rpki::rpki\_engine::rpkid\_context, 312
- use\_syslog
  - rpki::log, 77
- username
  - rpki::sql::session, 316
- v4
  - rpki::resource\_set::resource\_bag, 249
- v6
  - rpki::resource\_set::resource\_bag, 249
- valid\_until
  - rpki::left\_right::list\_resources\_elt, 199
  - rpki::resource\_set::resource\_bag, 250
- verbose
  - irbe\_cli, 48
- verify
  - rpki::x509::CMS\_object, 362
- version
  - rpki::https::http\_message, 464
  - rpki::left\_right::msg, 202
  - rpki::left\_right::sax\_handle, 213
  - rpki::manifest::Manifest, 225
  - rpki::publication::msg, 237
  - rpki::publication::sax\_handle, 246
  - rpki::roa::RouteOriginAttestation, 277
  - rpki::up\_down::message\_pool, 353
  - rpki::up\_down::sax\_handle, 359

- rpki::xml\_utils::msg, [408](#)
- want\_persistent\_client
  - rpki::https, [71](#)
- want\_persistent\_server
  - rpki::https, [71](#)
- warn
  - rpki::log, [77](#)
- when
  - rpki::async::timer, [133](#)
- wired\_in\_con\_g\_id
  - rpki::publication::con\_g\_elt, [233](#)
- withdraw
  - rpki::rpki\_engine::publication\_  
queue, [296](#)
- wrap
  - rpki::x509::XML\_CMS\_object, [397](#)
- writable
  - rpki::https::http\_stream, [178](#)
- x509.py(2928), [428](#)
- xml::sax::handler::ContentHandler, [414](#)
- xml\_utils.py(2836), [429](#)
- xmlns
  - rpki::left\_right::left\_right\_  
namespace, [195](#)
  - rpki::publication::publication\_  
namespace, [238](#)
  - rpki::up\_down, [90](#)