

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Aditya Prakash

University of Warwick, UK

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Problem: Given a parity automaton A , decide if A is HD.

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Problem: Given a parity automaton A , decide if A is HD.

Lower bound:

Solving parity games
 $\text{NP} \cap \text{coNP}$, $n^{\Theta(\log d)}$
Kuperberg, Skrzypczak '15

Upper bound:

$\Theta(n)$
 n

Henzinger, Piterman '06

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Problem: Given a parity automaton A , decide if A is HD.

Lower bound:

Solving parity games
 $\text{NP} \cap \text{coNP}$, $n^{\Theta(\log d)}$
Kuperberg, Skrzypczak '15

2-token conjecture



$\text{PSPACE}, 2^{3d} \cdot \text{Poly}(n)$

Upper bound:

$n^{\Theta(n)}$

Henzinger, Piterman '06

Joint work with

Karoliina Lehtinen

Aix-Marseille Université,
France

To appear in STOC 2025

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18


A is history-deterministic



Eve wins the 2-token game on A

Parity Automaton

Alphabet = { a, b }




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a...

Run: \emptyset




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $p \xrightarrow{b:1} p$




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} q$




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} q \xrightarrow{b:1} \perp$




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} q \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp$




Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \dots$



Parity Automaton


Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \dots$

Run2: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:1} \text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \dots$



Parity Automaton

Alphabet = {a, b}


Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \dots$

Run2: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:1} \text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \dots$

A run is accepting if the least priority occurring only often is even



Parity Automaton

Alphabet = {a, b}


Input: infinite word

b a b a a a a a a...

Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \dots$ (Rejecting because 1 is odd)

Run2: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:1} \text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \dots$ (Accepting because 0 is even)

A run is accepting if the least priority occurring only often is even



Parity Automaton

Alphabet = {a, b}

Input: infinite word

b a b a a a a a a...


Run: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{b:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \perp \xrightarrow{a:1} \dots$ (Rejecting because 1 is odd)

Run2: $\text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:1} \text{p} \xrightarrow{b:1} \text{p} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \text{q} \xrightarrow{a:0} \dots$ (Accepting because 0 is even)


A run is accepting if the least priority occurring only often is even

A word is accepting if there is an accepting run on it.

Language: Set of accepting words



Parity Automaton




A run is accepting if the least priority occurring only often is even.

A word is accepting if there is an accepting run on it.

Language : Set of accepting words

Parity Automaton




A run is accepting if the least priority occurring only often is even.
↓
Infinitely many 0's

A word is accepting if there is an accepting run on it.

Language : Set of accepting words

Parity Automaton



A run is accepting if the least priority occurring \Downarrow often is even.
Infinitely many 0's

A word is accepting if there is an accepting run on it.

Language : Set of accepting words


$$L(A) = \{ \text{Words that contain finitely many } b \text{'s} \}$$

Parity-Index Hierarchy

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$


Parity-Index Hierarchy

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$



Parity-Index Hierarchy

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$



Priority 1 transitions
Occur finitely often
or
Eventually, only priority 2
transitions occur

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

History Determinism: b/w nondeterminism and
determinism

History Determinism: b/w nondeterminism and determinism

Runs can be constructed 'on-the fly',
without knowing the entire word

History Determinism: b/w nondeterminism and determinism


Runs can be constructed 'on-the fly',
without knowing the entire word such that,
if word is in the language then the constructed run is accepting.

History Determinism: b/w nondeterminism and determinism

Runs can be constructed 'on-the fly',
without knowing the entire word such that,
if word is in the language then the constructed run is accepting.

Non-example:


A:



$L(A) = \{ \text{Words that contain finitely many } b's \}$

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$



HD game

Adam


Eve \circled{p}

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$

Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}



HD game

Adam

Eve \textcircled{p}


More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$

Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}

In round i , when Eve's token is at \textcircled{q}_i :



HD game

Adam

Eve \textcircled{p}

More precisely: Eve wins the HD game


Automaton A : HD game on $\{a, b\}$

Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}

In round i , when Eve's token is at q_i :

1. Adam selects a_i



HD game

Adam a
Eve \textcircled{p}

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at $\textcolor{blue}{p}$

In round i , when Eve's token is at q_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game

Adam a

Eve $p \xrightarrow{a:0} q$

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}


In round i , when Eve's token is at \textcircled{q}_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game



More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}

In round i , when Eve's token is at \textcircled{q}_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game

Adam a b

Eve $\textcircled{p} \xrightarrow{a:0} \textcircled{q} \xrightarrow{b:1} \perp$

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at \textcircled{p}

In round i , when Eve's token is at q_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game

Adam a b

Eve $\textcircled{p} \xrightarrow{a:0} \textcircled{q} \xrightarrow{b:1} \perp \rightarrow \dots$

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at $\rightarrow p$

In round i , when Eve's token is at q_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game

Adam a b

Eve $p \xrightarrow{a:0} q \xrightarrow{b:1} \perp \rightarrow \dots$

In the limit: Adam builds a word w , Eve builds a run ρ on that word.

More precisely: Eve wins the HD game

Automaton A : HD game on $\{a, b\}$


Players: Eve, Adam

Starts with an Eve's token at $\textcolor{blue}{p}$

In round i , when Eve's token is at q_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i : c_i} q_{i+1}$



HD game

Adam a b

Eve $\textcolor{blue}{p} \xrightarrow{a:0} q \xrightarrow{b:1} \perp \rightarrow \dots$

In the limit: Adam builds a word w , Eve builds a run P on that word.

Eve's winning condition: if $w \in L(A)$, then P is accepting.

More precisely: Eve wins the HD game

Automaton A : HD game on \sqrt{A}


Players: Eve, Adam

Starts with an Eve's token at $\rightarrow p$

In round i , when Eve's token is at q_i :

1. Adam selects a_i

2. Eve selects $q_i \xrightarrow{a_i:c_i} q_{i+1}$



HD game

Adam a b

Eve $p \xrightarrow{a:0} q \xrightarrow{b:1} \perp \rightarrow \dots$

In the limit: Adam builds a word w , Eve builds a run P on that word.

Eve's winning condition: if $w \in L(A)$, then P is accepting.


A is HD \iff Eve has a winning strategy.

Quick Note on Games


For games in this talk: either Eve has a winning strategy
or Adam has a winning strategy.

If Player has a winning strategy in \mathcal{G}
then Player wins \mathcal{G} .

Non-example (of HD automata)



Non-example (of HD automata)




$L(A) = \{ \text{words that contain finitely many } b's \}$

Adam's winning strategy in the HD game:

1. Select a 's until Eve's token moves to $\rightarrow q$

(if her token stays in p , then her run is rejecting but $aaa\dots \in L(A)$)

Non-example (of HD automata)



$L(A) = \{ \text{words that contain finitely many } b's \}$

Adam's winning strategy in the HD game:

1. Select a 's until Eve's token moves to $\rightarrow q$

(if her token stays in p , then her run is rejecting but $aaa\dots \in L(A)$)

2. When Eve's token moves to $\rightarrow q$, Adam plays b $aaa\dots$

Adam's word $aa\dots a b a a a\dots \in L(A)$, and Eve's run is rejecting.

Example 0

Example 0

Deterministic parity automata

The example: coBüchi automaton

[Kuperberg, Skrzypczak '15]


Alphabet $\Sigma = \{\sqsubset, \times, \sqsupseteq\}$

The example: coBüchi automaton

[Kuperberg, Skrzypczak '15]

Alphabet $\Sigma = \{ \begin{smallmatrix} \cdot & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \cdot & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \cdot & \cdot \\ \cdot & \cdot \end{smallmatrix} \}$

Words are graphs:




The example: coBüchi automaton


[Kuperberg, Skrzypczak '15]

Alphabet $\Sigma = \{ \begin{smallmatrix} \cdot & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \times & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \cdot & \times \\ \cdot & \cdot \end{smallmatrix} \}$

Words are graphs:



Run is accepting if it contains
finitely many 1's.




The example: coBüchi automaton


[Kuperberg, Skrzypczak '15]

Alphabet $\Sigma = \{ \cdot\cdot, \text{X}, \text{--} \}$

Words are graphs:



Run is accepting if it contains
finitely many 1's.




The example: coBüchi automaton


[Kuperberg, Skrzypczak '15]

Alphabet $\Sigma = \{ \begin{smallmatrix} \cdot & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \times & \cdot \\ \cdot & \cdot \end{smallmatrix}, \begin{smallmatrix} \times & \cdot \\ \cdot & \cdot \end{smallmatrix} \}$

Words are graphs:



Run is accepting if it contains
finitely many 1's.




The example: coBüchi automaton


[Kuperberg, Skrzypczak '15]

Alphabet $\Sigma = \{\equiv, \times, \leq\}$

Words are graphs:



Run is accepting if it contains
finitely many 1's.



The example: coBüchi automaton

[Kuperberg, Skrzypczak '15]


Alphabet $\Sigma = \{ \begin{smallmatrix} \cdot & \cdot \\ \equiv & \equiv \end{smallmatrix}, \begin{smallmatrix} \cdot & \cdot \\ \times & \times \end{smallmatrix}, \begin{smallmatrix} \cdot & \cdot \\ \equiv & \times \end{smallmatrix} \}$

Words are graphs:



Run is accepting if it contains
finitely many 1's.

Language = ?




The example: coBüchi automaton

[Kuperberg, Skrzypczak '15]


Alphabet $\Sigma = \{\cdot\cdot, \times\cdot, \cdot\times\}$

Words are graphs:





Run is accepting if it contains
finitely many 1's.

Language = { Graphs that contain a path
of infinite length }





This automaton is HD!

Eve's strategy in the HD game:





This automaton is HD!

Eve's strategy in the HD game:




This automaton is HD!

Eve's strategy in the HD game:




This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with
the longest unbroken path.




This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with
the longest unbroken path.




This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with
the longest unbroken path.




This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with
the longest unbroken path.




This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with the longest unbroken path.



This automaton is HD!

Eve's strategy in the HD game:




At $\rightarrow \circ$, pick the state with the longest unbroken path.

Recall Eve's winning condition:

If Adam's word is in $L(A)$, then

Eve's run is accepting.




Language = { Graphs with an ∞ paths }

This automaton is HD!

This idea will appear again!

Eve's strategy in the HD game:




At $\rightarrow \circlearrowleft$, pick the state with the longest unbroken path.

Recall Eve's winning condition:

If Adam's word is in $L(A)$, then

Eve's run is accepting.



Language = { Graphs with an ∞ paths }

Why HD automata?

* Good-for-games:

2-player game \mathcal{G} with winning condition as $L(A)$.

If A is HD, then \mathcal{G} and $\mathcal{G} \times A$ have the same-winner.

(Useful for reactive synthesis)

Why HD automata?

- * Good-for-games:
 - 2-player game \mathcal{G} with winning condition as $L(A)$.
If A is HD, then \mathcal{G} and $\mathcal{G} \times A$ have the same-winner.
(Useful for reactive synthesis)
- * Exponentially more succinct [Kuberberg, Skrzypczak '15]

Why HD automata?

- * Good-for-games:
 - 2-player game \mathcal{G} with winning condition as $L(A)$.
If A is HD, then \mathcal{G} and $\mathcal{G} \times A$ have the same-winner.
(Useful for reactive synthesis)
- * Exponentially more succinct [Kuberberg, Skrzypczak '15]
- * Inclusion is easy: Quasi-polynomial time [Prakash, FoSSaCS'24]

Why HD automata?

- * Good-for-games:
 - 2-player game \mathcal{G} with winning condition as $L(A)$.
If A is HD, then \mathcal{G} and $\mathcal{G} \times A$ have the same-winner.
(Useful for reactive synthesis)
- * Exponentially more succinct [Kuberberg, Skrzypczak '15]
- * Inclusion is easy: Quasi-polynomial time [Prakash, FoSSaCS '24]
- * Provides canonical representation for ω -regular languages [Ehlers, Schewe '22], [Abu Radi, Kupferman '20]

Recognising HD parity automaton

Problem. Given a parity automaton, decide if it is HD.

Recognising HD parity automaton

Problem. Given a parity automaton, decide if it is HD.

Winning condition in the HD game on A :

If Adam's word is in $L(A)$, then Eve's run is accepting.

Recognising HD parity automaton

Problem. Given a parity automaton, decide if it is HD.

Winning condition in the HD game on A :

If Adam's word is in $L(A)$, then Eve's run is accepting.

Directly solving HD games takes $n^{\Theta(n)}$ time.

Henzinger, Piterman'06

Recognising HD parity automaton

Problem. Given a parity automaton, decide if it is HD.

Winning condition in the HD game on A :

If Adam's word is in $L(A)$, then Eve's run is accepting.


Directly solving HD games takes $n^{\Theta(n)}$ time.

Henzinger, Piterman'06

Alternate approach: Easily-solvable games with the same winner


History of recognising HD parity automata

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$



History of recognising HD parity automata

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$




Kuperberg, Skrzypczak'15.

Polynomial-time algorithm for coBüchi

History of recognising HD parity automata

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$



Kuberberg, Skrzypczak'15.

Polynomial-time algorithm for coBüchi


Bagnol, Kuberberg'18.

Büchi automata.

Use 2-token game

History of recognising HD parity automata

$[i, j]$ automata: priorities in $\{i, i+1, \dots, j\}$



Kuperberg, Skrzypczak'15.

Polynomial-time algorithm for coBüchi

Bagnol, Kuperberg'18.

Büchi automata.

Use 2-token game

Boker, Kuperberg, Lehtinen, Skrzypczak'20

co Büchi automata

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18


A is history-deterministic



Eve wins the 2-token game on A

The 2-token game

Automaton A: the 2-token game on A




The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and

two of Adam's tokens at $\rightarrow p$



2-token game

Adam

Eve p

Adam p

Adam p


The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and

two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :



2-token game

Adam

Eve p

Adam p

Adam p

The 2-token game

Automaton A: the 2-token game on A


Starts with an Eve's token and

two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i

and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :



2-token game

Adam a

Eve p

Adam p

Adam p

The 2-token game

Automaton A: the 2-token game on A


Starts with an Eve's token and

two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i

2. Eve selects $q_i \xrightarrow{a_i : c_i} q_{i+1}$



2-token game

Adam a

Eve $p \xrightarrow{a:0} q$

Adam p

Adam p

The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and


two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :

2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \xrightarrow{a_i: c_i} p_{i+1}^1$, $p_i^2 \xrightarrow{a_i: c_i} p_{i+1}^2$



2-token game

Adam a

Eve $p \xrightarrow{a:0} q$

Adam $p \xrightarrow{a:0} q$

Adam $p \xrightarrow{a:1} p$

The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and


two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :

2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \xrightarrow{a_i: 1} p_{i+1}^1$, $p_i^2 \xrightarrow{a_i: 1} p_{i+1}^2$



2-token game

Adam a b

Eve $p \xrightarrow{a:0} q$

Adam $p \xrightarrow{a:0} q$

Adam $p \xrightarrow{a:1} p$

The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and


two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i
 and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :

2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \xrightarrow{a_i: 1} p_{i+1}^1$, $p_i^2 \xrightarrow{a_i: 1} p_{i+1}^2$



2-token game

Adam a b

Eve p -- a:0 --> q -- b:1 --> l

Adam p -- a:0 --> q

Adam p -- a:1 --> p

The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and


two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :

2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \rightarrow p_{i+1}^1$, $p_i^2 \rightarrow p_{i+1}^2$



2-token game

Adam a b



The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and


two of Adam's tokens at $\rightarrow p$

In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :

2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \rightarrow p_{i+1}^1$, $p_i^2 \rightarrow p_{i+1}^2$



2-token game

Adam a b

Eve $p \xrightarrow{a:0} q \xrightarrow{b:1} l \rightarrow \dots$

Adam $p \xrightarrow{a:0} q \xrightarrow{b:1} l \rightarrow \dots$

Adam $p \xrightarrow{a:1} p \xrightarrow{b:0} q \rightarrow \dots$

The 2-token game

Automaton A: the 2-token game on A

Starts with an Eve's token and

two of Adam's tokens at $\rightarrow p$


In round i , when Eve's token is at q_i and Adam's tokens are at p_i^1 and p_i^2 :

1. Adam selects a letter a_i :


2. Eve selects $q_i \xrightarrow{a_i: c_i} q_{i+1}$

3. Adam selects $p_i^1 \rightarrow p_{i+1}^1, p_i^2 \rightarrow p_{i+1}^2$

Eve's winning condition: if either of Adam's runs are accepting
then Eve's run is accepting.



2-token game



HD game vs. 2-token game

Winning condition in HD game:

if *Adam*'s word is in LCA) then *Eve*'s run is accepting.

Winning condition in 2-token game:

if either of *Adam*'s runs are accepting then *Eve*'s run is accepting.

HD game vs. 2-token game

Winning condition in HD game:

if Adam's word is in LCA) then Eve's run is accepting.

Winning condition in 2-token game:

if either of Adam's runs are accepting then Eve's run is accepting.

Observation.

If A is HD then Eve wins the 2-token game on A.

Proof. Use Eve's winning strategy in the HD game to play in the 2-token

2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Why 2 tokens?

Why 2 tokens?

* 2 tokens are plenty!

Lemma. If Eve wins the 2-token game on A
then Eve wins the k-token game on A for all $k \geq 1$.
Bagnol, Kuperberg '18

Why 2 tokens?

* 2 tokens are plenty!

Lemma. If Eve wins the 2-token game on A
then Eve wins the k-token game on A for all $k \geq 1$.
Bagnol, Kuperberg'18

Proof. If Eve wins 2-token game then Eve wins 3-token game.

Why 2 tokens?


* 2 tokens are plenty!

Lemma.

Bagnol, Kuperberg'18

If Eve wins the 2-token game on A
then Eve wins the k-token game on A for all $k \geq 1$.

Proof. If Eve wins 2-token game then Eve wins 3-token game.



2-Token Conjecture. For every parity automaton A ,

Bagnol, Kuperberg '18

A is history-deterministic



Eve wins the 2-token game on A

Lemma.

Bagnol, Kuperberg '18

If Eve wins the 2-token game on A
then Eve wins the k -token game on A for all $k \geq 1$.

Theorem. For every Büchi or coBüchi automaton A ,

Bagnol, Kuperberg'18

Boker, Kuperberg,
Lehtinen, Skrzypczak'20

Eve wins the 2-token game on $A \Rightarrow A$ is history-deterministic.

Theorem. For every Büchi or coBüchi automaton A ,

Bagnol, Kuperberg'18

Boker, Kuperberg,
Lehtinen, Skrzypczak'20

Eve wins the 2-token game on $A \Rightarrow A$ is history-deterministic.

Proof sketch. Suppose, towards a contradiction, that

1. Eve wins the 2-token game.
2. Adam wins the HD game.

Theorem. For every Büchi or coBüchi automaton A ,

Bagnol, Kuperberg'18

Boker, Kuperberg,
Lehtinen, Skrzypczak'20

Eve wins the 2-token game on $A \Rightarrow A$ is history-deterministic.

Proof sketch. Suppose, towards a contradiction, that

1. Eve wins the 2-token game.



2. Adam wins the HD game.

A has nice properties

Theorem. For every Büchi or coBüchi automaton A ,

Bagnol, Kuperberg '18

Boker, Kuperberg,
Lehtinen, Skrzypczak '20

Eve wins the 2-token game on $A \Rightarrow A$ is history-deterministic.


Proof sketch. Suppose, towards a contradiction, that

1. Eve wins the 2-token game.



2. Adam wins the HD game.

A has nice properties



Adam wins the k -token game on A ,

where $k = 2^{2^n}$

Just 1 token

Theorem. For every Büchi or coBüchi automaton A ,
if Eve wins the 1-token game from everywhere on A
then A is HD.

Just 1 token

Theorem. For every Büchi or coBüchi automaton A ,
if Eve wins the 1-token game from everywhere on A
then A is HD.

Corollary

Theorem. For every Büchi or coBüchi automaton A ,

Bagnol, Kuperberg'18

Boker, Kuperberg,
Lehtinen, Skrzypczak'20

Eve wins the 2-token game on $A \Rightarrow A$ is history-deterministic.

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof sketch.

CoBüchi automata
or $[1,2]$ automata

Automaton A

Büchi automata
or $[0,1]$ automata

Automaton A

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof sketch.

CoBüchi automata
or $[1,2]$ automata

Automaton A

{ Modify

A has safe-coverage.

Büchi automata
or $[0,1]$ automata

Automaton A

{ Modify

A has reach-covering.

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof sketch.

CoBüchi automata
or $[1,2]$ automata

Automaton A

{ Modify

A has safe-coverage.

↓ Prove

A is HD

Büchi automata
or $[0,1]$ automata

Automaton A

{ Modify

A has reach-covering.

↓ Prove

A is HD.

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof sketch.

CoBüchi automata
or $[1,2]$ automata

Automaton A

{ Modify
↓

A has safe-coverage.

↓ Prove

A is HD

Büchi automata
or $[0,1]$ automata

Automaton A

{ Modify
↓

A has reach-covering.


↓ Prove

A is HD.

Safety automata: simpler coBüchi automata


Safety automata: simpler coBüchi automata

All transitions of priority 1 are on a rejecting sink state.



Safety automata: simpler coBüchi automata

All transitions of priority 1 are on a rejecting sink state.



Theorem
Löding'12

For every safety automaton A ,
Eve wins the 1-token game on A





A is determinisable-by-pruning $\Leftrightarrow A$ is HD.

Safe approximation

CoBüchi automaton A  Safety automaton $A_{>1}$



Safe approximation

CoBüchi automaton A  Safety automaton $A_{>1}$



Safe approximation

CoBüchi automaton A  Safety automaton $A_{>1}$




Safe coverage for a coBüchi automaton.*

There are states p , such that Eve wins 1-token game from p in $A_{>1}$.

Safe approximation

CoBüchi automaton A  Safety automaton $A_{>1}$



Safe coverage for a coBüchi automaton.*



There are states p , such that Eve wins 1-token game

from p in $A_{>1}$.

$(A_{>1}, p)$ is HD

Safe approximation

CoBüchi automaton A  Safety automaton $A_{>1}$



Safe coverage for a coBüchi automaton.*

There are states p , such that Eve wins 1-token game

from p in $A_{>1}$.

$(A_{>1}, p)$ is HD

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof.

CoBüchi automata
or $[1,2]$ automata

Automaton A

{ Modify

A has safe-coverage.

Prove

A is HD

Büchi automata
or $[0,1]$ automata

Automaton A

{ Modify

A has reach-covering.

Prove

A is HD.

[Acharya, Jurdziński, me, ICALP'24]

Büchi coBüchi
Safety Reachability


```
graph LR; Büchi <--> coBüchi; Safety <--> Reachability;
```

\vdots \vdots
 $[0, 4]$ $[1, 5]$

$[0, 3]$ $[1, 4]$

$[0, 2]$ $[1, 3]$

$[0, 1]$ $[1, 2]$
Büchi coBüchi
Safety Reachability



Even-to-odd

2-token conjecture


for $[0, K]$ automata



2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage



Even-to-odd

2-token conjecture


for $[0, K]$ automata



2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage



Odd-to-even

2-token conjecture

for $[1, K]$ automata



2-token conjecture

for $[0, K]$ automata

Reach double
covering

2-Token Theorem. For every parity automaton A ,

A is history-deterministic



Eve wins the 2-token game on A

2-Token Theorem. For every parity automaton A ,

A is history-deterministic



Eve wins the 2-token game on A

Problem. Given a parity automaton, decide if it is HD.

Upper bound:

PSPACE,

$2^{3d} \cdot \text{Poly}(n)$

2-Token Theorem. For every parity automaton A ,

A is history-deterministic



Eve wins the 2-token game on A

Problem. Given a parity automaton, decide if it is HD.

Lower bound:

NP-hard

[P, FoSSaCS'24]
me :)

Upper bound:

PSPACE,

$2^{3d} \cdot \text{Poly}(n)$

Even-to-odd

2-token conjecture


for $[0, K]$ automata



2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage



Odd-to-even

2-token conjecture

for $[1, K]$ automata



2-token conjecture

for $[0, K]$ automata

Reach double
covering

Rest of this
talk!

Theorem: Every coBüchi automaton on which Eve wins
the 1-token game from everywhere is HD.

Theorem: Every coBüchi automaton on which Eve wins the 1-token game from everywhere is HD.


Proof. CoBüchi automaton

A



Modify

A has safe coverage



Prove

A is HD.

Token game from different states

For an automaton A and states q, p, r :

$G_2(q; p, r)$ in A : 2-token game where Eve's token starts at q , Adam's tokens start at p and r .

Token game from different states

For an automaton A and states q, p, r :

$G_2(q; p, r)$ in A : 2-token game where Eve's token starts at q , Adam's tokens start at p and r .

$G_1(q; p)$ in A : 1-token game where Eve's token starts at q , Adam's token starts at p .

Token game from different states

For an automaton A and states q, p, r :

$G_2(q; p, r)$ in A : 2-token game where Eve's token starts at q , Adam's tokens start at p and r .

$G_1(q; p)$ in A : 1-token game where Eve's token starts at q , Adam's token starts at p .

Winning condition: If any of Adam's run is accepting then Eve's run is accepting.


Observation: Gr1 transitivity

Lemma: If Eve wins $\text{Gr1}(p; q)$ and $\text{Gr1}(q; r)$ in A ,
then Eve wins $\text{Gr1}(p; r)$ in A .

Observation: Gr1 transitivity

Lemma: If Eve wins $\text{Gr1}(p; q)$ and $\text{Gr1}(q; r)$ in A ,
then Eve wins $\text{Gr1}(p; r)$ in A .

Proof.




Weak coreachability

Weak coreachability

Automaton A: p and q are **coreachable** in A if


there is a finite word u , such that



Weak coreachability

Automaton A: p and q are **coreachable** in A if

there is a finite word u , such that




Weak coreachability: Transitive closure of coreachability.

Weak coreachability


Automaton A: p and q are **coreachable** in A if

there is a finite word u , such that



Weak coreachability: Transitive closure of coreachability.


p and q are weakly coreachable in A if $\exists p_0, p_1, \dots, p_k$ s.t.



Weak coreachability

Automaton A: p and q are **coreachable** in A if


there is a finite word u , such that



Equivalence relation
↑

Weak coreachability: Transitive closure of coreachability.


p and q are weakly coreachable in A if $\exists p_0, p_1, \dots, p_k$ s.t.



Weak coreachability

Automaton A: p and q are **coreachable** in A if


there is a finite word u , such that



Equivalence relation
↑

Weak coreachability: Transitive closure of coreachability.

p and q are weakly coreachable in A if $\exists p_0, p_1, \dots, p_k$ s.t.




$$(p, q) \in WCR(A)$$

$$p \in WCR(A, q)$$


Weak coreachability

Automaton A and a finite word u .



Weak coreachability

Automaton A and a finite word u .



$CR(A, u)$

$WCR(A, u)$

Winning token games from everywhere

Eve wins 1-token game from everywhere in A

if she wins $G^1(p; q)$ for all $(p, q) \in CR(A)$

Winning token games from everywhere

Eve wins 1-token game from everywhere in A

if she wins $G \sqsupseteq (\textcolor{blue}{p}; q)$ for all $(\textcolor{blue}{p}, q) \in \text{CR}(A)$
 $\text{WCR}(A)$.

Recall: $G \sqsupseteq$ is transitive

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that, Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$.

Theorem: Every coBüchi automaton on which Eve wins the 1-token game from everywhere is HD.


Proof. CoBüchi automaton

A



Modify

A has safe coverage



Prove

A is HD.

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that, Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$.

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that,

Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$.

$$q_0 \ b_0 \ b_1 \ b_2 \dots$$

$\swarrow \searrow$

$$\text{Gr1}(b_2; b_1)$$

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that,

Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$.


q b_0 b_1 b_2 $\dots b \dots b \dots$
 \ /
 $\text{Gr1}(b_2; b_1)$

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that,

Eve wins $G_1(b; q)$ in $A_{\geq 1}$

and Eve wins $G_1(b; b)$ in $A_{\geq 1}$.



Recall: G_1 is transitive

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that,

Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$

and Eve wins $\text{Gr1}(b; b)$ in $A_{\geq 1}$.



$(A_{\geq 1}, b)$ is determinable-by-pruning.

Safe coverage

Defn. A coBüchi automaton A has safe coverage if for all q , there is $b \in \text{WCR}(A, q)$ such that,

Eve wins $\text{Gr1}(b; q)$ in $A_{\geq 1}$

and Eve wins $\text{Gr1}(b; b)$ in $A_{\geq 1}$.



$(A_{\geq 1}, b)$ is determinable-by-pruning.

Safe-deterministic states:

States b , such that Eve wins $\text{Gr1}(b; b)$ in $A_{\geq 1}$.

Lemma. If a coBüchi automaton A has safe coverage and Eve wins 1-token game from everywhere in A then A is HD.

Proof. In the HD game on A , Adam builds a word w .


$$w = a_0 \quad a_1 \quad a_2 \quad a_3 \quad \dots$$

Safe coverage

For each $q \exists b \in WCR(A, q)$ s.t. Eve wins $G_1(b; q)$ in $A_{>1}$ and $(A_{>1}, b)$ is DBP.

Lemma. If a coBüchi automaton A has safe coverage and Eve wins 1-token game from everywhere in A then A is HD.

Proof. In the HD game on A , Adam builds a word w . Eve build a DAG D_w in her memory as follows:




Safe coverage

For each $q \exists b \in WCR(A, q)$ s.t.
Eve wins $G_1(b; q)$ in $A_{>1}$
and $(A_{>1}, b)$ is DBP.

Lemma. If a coBüchi automaton A has safe coverage and Eve wins 1-token game from everywhere in A then A is HD.

Proof. In the HD game on A , Adam builds a word w . Eve build a DAG D_w in her memory as follows:




Safe coverage

For each $q \exists b \in WCR(A, q)$ s.t. Eve wins $G_1(b; q)$ in $A_{>1}$ and $(A_{>1}, b)$ is DBP.

Proof. In the HD game on A , Adam builds a word w .
Eve build a DAG D_w in her memory as follows:

$$w = a_0 \ a_1 \ a_2 \ a_3 \ \dots$$



deterministic transitions of
priority 2 in $A_{\geq 1}$.


States b in $WCR(A, a_0 a_1)$

that are safe deterministic

Claim: If w is in $L(A)$, then D_w contains an infinite path.

Proof. Eve builds a run in the HD game using D_w .

$\omega = a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ \dots$



Recall:


Eve wins 1-token game from everywhere

Proof. Eve builds a run in the HD game using D_w .

$\omega = a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ \dots$

Eve's token

D_w



Recall:


Eve wins 1-token game from everywhere

Proof. Eve builds a run in the HD game using D_w .

$\omega = a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ \dots$

Eve's token

D_w



Find a state with the longest unbroken path

Recall:


Eve wins 1-token game from everywhere

Proof. Eve builds a run in the HD game using D_w .

$\omega = a_0 \ a_1 \ a_2 \ a_3 \ a_4$

Eve's token

D_w



Find a state with the longest unbroken path

Recall:


Eve wins 1-token game from everywhere

Proof. Eve builds a run in the HD game using D_w .

$\omega = a_0 \ a_1 \ a_2 \ a_3 \ a_4$

Eve's token

D_w



Find a state with the longest unbroken path

Recall:

Eve wins 1-token game from everywhere


Proof. Eve builds a run in the HD game using D_w .

$w = a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ \dots$

Eve's token

Play G1 against

D_w



Find a state with the longest unbroken path

Recall:


Eve wins 1-token game from everywhere

Proof. Eve builds a run in the HD game using D_w .

$w = a_0 \ a_1 \ a_2 \ a_3 \ a_4 \ a_5 \ \dots$

Eve's token

D_w



Find a state with the longest unbroken path

w in $L(A) \Rightarrow D_w$ contains an ∞ path



Eve's run is accepting.

Recall:

Eve wins 1-token game from everywhere

Lemma. If a coBüchi automaton A has safe coverage and Eve wins 1-token game from everywhere in A then A is HD.

Theorem. For every Büchi or coBüchi automaton A ,

if Eve wins the 1-token game from everywhere on A
then A is HD.

Proof sketch.

CoBüchi automata
or $[1,2]$ automata

Automaton A

{ Modify

A has safe-coverage.

↓ Prove

A is HD

Büchi automata
or $[0,1]$ automata

Automaton A

{ Modify

A has reach-covering.

↓ Prove

A is HD.

Büchi automata: reach covering

Reach covering.

For each $q, \exists b \in WCR(A, q)$ s.t.

Eve wins $G_1(q; b)$ in $A_{\geq 0}$.

Büchi automata: reach covering

For coBüchi automata: safe coverage

Reach covering.

For each $q, \exists b \in WCR(A, q)$ s.t.

Eve wins $G_1(q; b)$ in $A_{>0}$.

Safe coverage

For each $q, \exists b \in WCR(A, q)$ s.t.

Eve wins $G_1(b; q)$ in $A_{>1}$.

Büchi automata $\rightarrow [0, 1]$ automata

Even-to-odd

2-token conjecture


for $[0, K]$ automata



2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage



Odd-to-even

2-token conjecture

for $[1, K]$ automata



2-token conjecture

for $[0, K]$ automata

Even-to-odd

2-token conjecture

for $[0, K]$ automata



2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage

For each $q_i \exists b \in WCR(A, q_i)$ s.t.

Eve wins $G_2(b; q_i, q_i)$ in $A_{>1}$.

Odd-to-even


2-token conjecture

for $[1, K]$ automata



2-token conjecture

for $[0, K]$ automata



Even-to-odd

2-token conjecture

for $[0, K]$ automata




2-token conjecture

for $[1, K+2]$ automata

Safe double
coverage

For each $q_i \exists b \in WCR(A, q_i)$ s.t.

Eve wins $G_2(b; q_i, q_i)$ in $A_{>1}$.



Odd-to-even

2-token conjecture

for $[1, K]$ automata



2-token conjecture

for $[0, K]$ automata

Reach double
covering

For each $q_i \exists b \in WCR(A, q_i)$ s.t.

Eve wins $G_2(q_i; b, b)$ in $A_{>0}$.

2-Token Theorem. For every parity automaton A ,

A is history-deterministic



Eve wins the 2-token game on A

Problem. Given a parity automaton, decide if it is HD.

Lower bound:

NP-hard

Upper bound:

PSPACE,

$2^{3d} \cdot \text{Poly}(n)$

Find these results in:

History-Deterministic Parity automata: Games, Complexity,
and the 2-Token Theorem , on arxiv

Open Problems

Given a parity automaton, decide if it is HD.

Lower bound:

NP-hard

Upper bound:

PSPACE

Open Topic

- * Resolving Nondeterminism in Automata with Randomness,
with Tom A. Henzinger and K. S. Thejaswini

Open Topic

* Resolving Nondeterminism in Automata with Randomness,
with Tom A. Henzinger and K. S. Thejaswini

Conjecture: Every HD Parity automata can be efficiently transformed into one where Eve almost surely wins the HD game using positional memoryless strategy.
(True for co Büchi HD automata)

Open Problem.

- * Does the 2-token conjecture hold for infinite-state systems with parity / ω -regular acceptance condition?
E.g. timed automata, pushdown automata

Open Problem.

- * Does the 2-token conjecture hold for infinite-state systems with parity / ω -regular acceptance condition?
E.g. timed automata, pushdown automata

Theorem: There is an infinite state coBüchi automaton A s.t.,
Eve wins 2-token game on A but A is not HD.

2-Token Theorem. For every parity automaton A ,

Thanks!
:)

A is history-deterministic



Eve wins the 2-token game on A

Problem. Given a parity automaton, decide if it is HD.

Lower bound:

NP-hard

Upper bound:

PSPACE,

$2^{3d} \cdot \text{Poly}(n)$

