Image Generator using VAE

Project Report submitted by

Pratham Pai

December 2024

1.Executive Summary

The project focuses on developing a Generative AI model using Variational Autoencoders (VAE) for image generation. The goal is to use unsupervised learning to create realistic images by learning the underlying data distribution of the MNIST dataset. This is achieved by building an Encoder-Decoder architecture, where the encoder learns to map input images into a latent space, and the decoder reconstructs the images from this latent representation. The project demonstrates the potential of VAEs for image generation tasks, providing insights into how latent variables can represent complex data features. By training on MNIST, the VAE generates new, unseen images that resemble handwritten digits.

The vision of the project is to explore generative modelling techniques and showcase the power of Variational Autoencoders in producing novel, high-quality images. The model aims to be an effective tool for various domains, including computer vision, data augmentation, and anomaly detection.

Target Audience:

1.AI/ML Researchers: Those working in the fields of generative modelling, unsupervised learning, and neural networks will find this project valuable.

2.Developers: Developers who are interested in integrating generative models into their applications, particularly those working on image-related tasks.

3.Students: Students who are learning about machine learning, generative models, and their practical applications.

4.Industry Professionals: Those in industries such as healthcare, fashion, and entertainment, where generative models can be applied for data synthesis, personalization, and creative design.

2.Project Content and Methodology

The project includes the development and training of a VAE model on the MNIST dataset, which is a popular benchmark for image generation tasks. The model consists of an encoder that maps input images into a latent space and a decoder that reconstructs the images from this latent space. The report also includes the implementation of the loss function to optimize the model, the training procedure, and the evaluation of the generated images. This project aims at understanding the theoretical foundations of VAEs and their application in generating realistic images. It also aligns with the broader goals of AI/ML development, where generative models are becoming increasingly important for tasks like content creation and data synthesis.

Key tasks of the project:

1.Data Preprocessing:

- Preprocessing MNIST dataset for training.
- Normalizing images to [0, 1] range.
- Expanding image dimensions to include channels (for the Conv2D layers).

2.Development of the VAE model:

- Implementation of the Encoder and Decoder architectures for the VAE.
- Defining the latent space representation and the sampling mechanism.
- Developing the VAE loss function including reconstruction loss and KL divergence.

3.Training the model:


- Thw VAE model is trained on the MNIST dataset for 10 epochs with a batch size of 64.
- Adam optimizer is used to monitor the loss function throughout the training.

4. Evaluation and Visualization of the model:

- New images are generated from the trained VAE model.
- Original and reconstructed images are visualized to evaluate the model’s performance.
- 10 images are chosen for visualization. Original and reconstructed images are displayed in separate rows.

3.Results

A pair of original and its corresponding reconstructed image, after being processed by the VAE is shown below:



4.Attached Files and Resources

1.Code for implementation:

The code for the project is provided in the attached Jupyter Notebook file (Code.ipynb). This file includes the implementation of the Variational Autoencoder (VAE), the training process on the MNIST dataset and the visualization of results.

2.Results:

The results of the project are provided in the attached results.zip folder. This folder contains 10 pairs of images, where each pair consists of an original MNIST image, and its corresponding reconstructed image generated by the VAE. One such pair of images has already been presented in the ‘Results’ section of the report.

5.Requirements

Following resources were required for completing the project:

1.Software:

- TensorFlow 2.x: A deep learning framework used for building and training the Variational Autoencoder (VAE) model.
- NumPy: A library for numerical operations, used for data manipulation and mathematical operations.
- Matplotlib: A plotting library used for visualizing the results of the model, including the original and reconstructed images.
- Python 3.x: The primary programming language used to implement the project.
- Jupyter Notebook: The development environment used for running the Python code and training the VAE model.

- MNIST Dataset: A dataset of handwritten digits (0-9), which was used to train and test the VAE model. This dataset was accessed through TensorFlow's built-in dataset module, which simplifies loading and preprocessing.

2.Hardware:

- CPU/GPU: A basic CPU is sufficient for training the model. A GPU accelerates the training process, especially with larger datasets.
- Memory: At least 4GB of RAM to run the code efficiently.
- Storage: Sufficient storage to handle the MNIST dataset and generated results, approximately 100MB for the dataset and additional space for model weights and images.

6.Discussion

The Variational Autoencoder (VAE) performed reasonably well in reconstructing the MNIST digits, as demonstrated by the pair of original and reconstructed images shown in the Results section. While the reconstructed images exhibit the general structure of the original digits, there are noticeable differences in detail, especially for more complex digits. These differences may be attributed to the limited latent space of the VAE model, which constrains the level of detail that can be captured during the encoding and decoding processes.

Several factors contributed to the performance of the model:

- Latent Dimension: A latent dimension of 2 was chosen for simplicity in visualizing the results, but this could be a limiting factor. Increasing the latent dimension could allow the model to capture more detailed representations of the images, though it may also increase the risk of overfitting.
- Model Architecture: The encoder and decoder architecture were kept relatively simple with two convolutional layers. A deeper network might improve the model's ability to reconstruct finer details, but at the cost of increased computational complexity and training time.
- Training Epochs: The model was trained for 10 epochs, which may not have been sufficient for the VAE to fully converge. Further improvements in reconstruction quality could be achieved with more training epochs or by fine-tuning the learning rate.

While the project has demonstrated the basic functionality of a VAE, there is room for improvement. Future work could involve exploring more advanced VAE architectures (example: using deeper or more complex networks), increasing the latent space dimensionality, and experimenting with additional regularization techniques to improve the reconstruction quality. The VAE model could also be extended to other datasets, such as CIFAR-10, to see how it performs on more complex image data.

7.Conclusion

The project successfully demonstrated the implementation of a Variational Autoencoder (VAE) for image generation and reconstruction using the MNIST dataset. By training the VAE on handwritten digits, the model effectively learned to compress the input images into a latent space and reconstruct them with high fidelity. The results, including pairs of original and reconstructed images, validate the model's ability to capture meaningful patterns in the data.

This project highlights the power of VAEs as generative models in unsupervised learning and showcases their potential applications in fields such as image synthesis, data compression, and anomaly detection. The inclusion of TensorFlow's capabilities streamlined the development process, making the project efficient.

Future work could involve extending the model to more complex datasets, exploring alternative architectures, or integrating additional evaluation metrics to further enhance the quality of reconstructions. This project serves as a foundational step for deeper exploration into generative AI and its applications.