



Institut national de la statistique
et des études économiques

Mesurer pour comprendre

R and JDemetra+ 3.0: A new toolbox around seasonal adjustment and time series analysis

ALAIN QUARTIER-LA-TENTE

Insee

Scientific Session: Time series and longitudinal data analysis

06/11/2022

Contents

1. Introduction


2. Utility packages

3. Seasonal adjustment packages


4. Other packages

5. Conclusion



JDemetra+ ?

- JDemetra+ is an open source software (build on ) officially recommended by Eurostat for seasonal adjustment (SA)




JDemetra+ ?

- JDemetra+ is an open source software (build on ) officially recommended by Eurostat for seasonal adjustment (SA)
- Implements the two leading SA methods X-13ARIMA and TRAMO-SEATS with a nice graphical interface





Introduction (1)

- In March 2019, RJDemetra was published on CRAN:
 - only  package that enables to use TRAMO-SEATS
 - faster than existing  packages on seasonal adjustment
 - enables to interact with JDemetra+ “workspaces” used in production






Introduction (1)

- In March 2019, RJDemetra was published on CRAN:
 - only  package that enables to use TRAMO-SEATS
 - faster than existing  packages on seasonal adjustment
 - enables to interact with JDemetra+ “workspaces” used in production
- Other  packages around SA
 - `stats::stl()` and `forecast::mstl()` for (M)STL: not recommended because they cannot perform calendar adjustment
 - `seasonal` and `x12`: interface to X-13-ARIMA-SEATS US Census Bureau binaries

Introduction (1)

- In March 2019, RJDemetra was published on CRAN:
 - only  package that enables to use TRAMO-SEATS
 - faster than existing  packages on seasonal adjustment
 - enables to interact with JDemetra+ “workspaces” used in production
- Other  packages around SA
 - `stats::stl()` and `forecast::mstl()` for (M)STL: not recommended because they cannot perform calendar adjustment
 - `seasonal` and `x12`: interface to X-13-ARIMA-SEATS US Census Bureau binaries
- With the development of JDemetra+ 3.0, more than 13  packages are being developed! Not only on seasonal adjustment!

Introduction (1)


- In March 2019, RJDemetra was published on CRAN:
 - only  package that enables to use TRAMO-SEATS
 - faster than existing  packages on seasonal adjustment
 - enables to interact with JDemetra+ “workspaces” used in production
- Other  packages around SA
 - `stats::stl()` and `forecast::mstl()` for (M)STL: not recommended because they cannot perform calendar adjustment
 - `seasonal` and `x12`: interface to X-13-ARIMA-SEATS US Census Bureau binaries
- With the development of JDemetra+ 3.0, more than 13  packages are being developed! Not only on seasonal adjustment!
- They require Java  ≥ 17 (see for example installation manual of RJDemetra:
<https://github.com/jdemetra/rjdemetra/wiki/Installation-manual>)

Introduction (2)

They are all available in GitHub, currently:

```
# install.packages("remotes")
remotes::install_github("palatej/rjd3toolkit")
remotes::install_github("palatej/rjd3modelling")
remotes::install_github("palatej/rjd3sa")
remotes::install_github("palatej/rjd3arima")
remotes::install_github("palatej/rjd3x13")
remotes::install_github("palatej/rjd3tramoseats")
remotes::install_github("palatej/rjdemetra3")
remotes::install_github("palatej/rjdfilters")
remotes::install_github("palatej/rjd3sts")
remotes::install_github("palatej/rjd3highfreq")
remotes::install_github("palatej/rjd3stl")
remotes::install_github("palatej/rjd3bench")
remotes::install_github("AQLT/ggdemetra3")
```

Introduction (3)



And it's just the beginning! (might change in the future)

Contents

1. Introduction

2. Utility packages

2.1 rjd3toolkit

2.2 rjd3modelling

2.3 rjd3sa


3. Seasonal adjustment packages

4. Other packages

5. Conclusion

rjd3toolkit

Contains several utility functions used in other rjd packages and several functions to perform tests:

- Normality tests: Bowman-Shenton (`bowmanshenton()`), Doornik-Hansen (`doornikhansen()`), Jarque-Bera (`jarquebera()`, with more parameters than `tseries::jarque.bera.test()`)
-  Runs tests (randomness of data): mean or the median (`testofruns()`) or up and down runs test (`testofupdownruns()`)
- autocorrelation functions (usual, inverse, partial)
- `aggregate()` to aggregate a time serie to a higher frequency


rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`



rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`
-  create outliers regressors (AO, LS, TC, SO, Ramp, intervention variables), calendar related regressors (stock, leap year, periodic dummies and contrasts, trigonometric variables) -> to be added quadratic ramps



rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`
-  create outliers regressors (AO, LS, TC, SO, Ramp, intervention variables), calendar related regressors (stock, leap year, periodic dummies and contrasts, trigonometric variables) -> to be added quadratic ramps
-  Range-mean regression test (to choose log transformation), Canova-Hansen (`td.ch()`) and trading-days f-test (`td.f()`)



rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`
-  create outliers regressors (AO, LS, TC, SO, Ramp, intervention variables), calendar related regressors (stock, leap year, periodic dummies and contrasts, trigonometric variables) -> to be added quadratic ramps
-  Range-mean regression test (to choose log transformation), Canova-Hansen (`td.ch()`) and trading-days f-test (`td.f()`)
- manipulation of ARIMA models (generation, sum, decomposition, estimation)



rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`
-  create outliers regressors (AO, LS, TC, SO, Ramp, intervention variables), calendar related regressors (stock, leap year, periodic dummies and contrasts, trigonometric variables) -> to be added quadratic ramps
-  Range-mean regression test (to choose log transformation), Canova-Hansen (`td.ch()`) and trading-days f-test (`td.f()`)
- manipulation of ARIMA models (generation, sum, decomposition, estimation)
- functions to stationarise your series `do.stationary()`, `differences()`, `differencing.fast()`

rjd3modelling



- create user-defined calendar and trading-days regressors:
`calendar.new()` (create a new calendar), `calendar.holiday()` (add a specific holiday, e.g. christmas), `calendar.easter()` (easter related day) and `calendar.fixedday()`
-  create outliers regressors (AO, LS, TC, SO, Ramp, intervention variables), calendar related regressors (stock, leap year, periodic dummies and contrasts, trigonometric variables) -> to be added quadratic ramps
-  Range-mean regression test (to choose log transformation), Canova-Hansen (`td.ch()`) and trading-days f-test (`td.f()`)
- manipulation of ARIMA models (generation, sum, decomposition, estimation)
- functions to stationarise your series `do.stationary()`, `differences()`, `differencing.fast()`
- specification functions for `rjd3x13` and `rjd3tramoseats`

Example of a specific calendar (1)

```
library(rjd3modelling)
fr_cal <- calendar.new()
calendar.holiday(fr_cal, "NEWYEAR")
calendar.holiday(fr_cal, "EASTERMONDAY")
calendar.holiday(fr_cal, "MAYDAY")
calendar.fixedday(fr_cal, month = 5, day = 8,
                  start = "1953-03-20")
# calendar.holiday(fr_cal, "WHITMONDAY") # Equivalent to:
calendar.easter(fr_cal, offset = 61)

calendar.fixedday(fr_cal, month = 7, day = 14)
# calendar.holiday(fr_cal, "ASSUMPTION")
calendar.easter(fr_cal, offset = 61)
calendar.holiday(fr_cal, "ALLSAINTSDAY")
calendar.holiday(fr_cal, "ARMISTICE")
calendar.holiday(fr_cal, "CHRISTMAS")
```

Example of a specific calendar (2)

Use `holidays()` to get the days of the holidays and `htd()` to get the trading days regressors

```
holidays(fr_cal, "2020-12-24", 10, single = TRUE)
```

```
##           [,1]  
## 2020-12-24    0  
## 2020-12-25    1  
## 2020-12-26    0  
## 2020-12-27    0  
## 2020-12-28    0  
## 2020-12-29    0  
## 2020-12-30    0  
## 2020-12-31    0  
## 2021-01-01    1  
## 2021-01-02    0
```

Example of a specific calendar (3)


```
s <- ts(0, start = 2020, end = c(2020, 11), frequency = 12)
# Trading-days regressors (each day has a different effect, sunday as contrasts)
td_reg <- htd(fr_cal, s = s, groups = c(1, 2, 3, 4, 5, 6, 0))
# Working-days regressors (Monday = ... = Friday; Saturday = Sunday = contrasts)
wd_reg <- htd(fr_cal, s = s, groups = c(1, 1, 1, 1, 1, 0, 0))
# Monday = ... = Friday; Saturday; Sunday = contrasts
wd_reg <- htd(fr_cal, s = s, groups = c(1, 1, 1, 1, 1, 2, 0))
wd_reg
```

```
##           group-1    group-2
## Jan 2020  2.0000000  0.0000000
## Feb 2020  0.0000000  1.0000000
## Mar 2020 -1.7809251 -0.7968209
## Apr 2020  0.7809251 -0.2031791
## May 2020 -3.1554920  0.4740847
## Jun 2020  5.1554920  0.5259153
## Jul 2020  2.0000000  0.0000000
## Aug 2020 -4.0000000  0.0000000
## Sep 2020  2.0000000  0.0000000
## Oct 2020  2.0000000  1.0000000
## Nov 2020  0.0000000  0.0000000
```

Example of outliers (1)



```
s <- ts(0, start = 2000, end = 2005, frequency = 12)
ao <- ao.variable(s = s, date = "2001-03-01")
ls <- ls.variable(s = s, date = "2001-01-01")
tc <- tc.variable(s = s, date = "2001-01-01", rate = 0.7)
so <- so.variable(s = s, date = "2003-05-01")
ramp <- ramp.variable(s = s, range = c("2001-01-01", "2001-12-01"))
plot(ts.union(ao, ls, tc, so, ramp), plot.type = "single",
     col = c("red", "lightgreen", "orange", "blue", "black"))
```

Example of outliers (2)





Benchmark of ARIMA estimations

More than 20 times faster in median!



rjd3sa (1)

Seasonality tests:

- Canova-Hansen (`seasonality.canovahansen()`)
-  X-12 combined test (`seasonality.combined()`)
- F-test on seasonal dummies (`seasonality.f()`)
- Friedman Seasonality Test (`seasonality.friedman()`)
- Kruskal-Wallis Seasonality Test (`seasonality.kruskalwallis()`)
-  Periodogram Seasonality Test (`seasonality.periodogram()`)
- QS Seasonality Test (`seasonality.qs()`)

rjd3sa (2)



Always correct the trend and remove the mean before seasonality tests:

```
library(rjd3sa)
y <- diff(rjd3toolkit::ABS$X0.2.09.10.M, 1); y <- y - mean(y)
# Or:
y <- rjd3modelling::differences(rjd3toolkit::ABS$X0.2.09.10.M)
seasonality.f(y)
```

```
## Value: 378.9234
```

```
## P-Value: 0.0000
```

```
seasonality.friedman(y)
```

```
## Value: 298.2529
```

```
## P-Value: 0.0000
```

```
seasonality.kruskalwallis(y)
```

```
## Value: 319.9801
```

```
## P-Value: 0.0000
```

```
seasonality.combined(y)
```

```
## $seasonality
```

```
## [1] "PRESENT"
```

```
##
```

Contents

1. Introduction

2. Utility packages

3. Seasonal adjustment packages

3.1 rjd3arima

3.2 rjd3x13 and rjd3tramoseats

3.3 rjd3tramoseats

3.4 rjdemetra3

3.5 rjd3highfreq and rjd3stl

4. Other packages

5. Conclusion

rjd3arima

rjd3arima is devoted to formatting the output of Arima related results

Common functions

In RJDemetra you have **one function** to set the specification (regarima_spec_x13(), regarima_spec_tramo(), x13_spec() and tramoseats_spec()) now one function for each part of the specification

Common functions


In RJDemetra you have **one function** to set the specification (`regarima_spec_x13()`, `regarima_spec_tramo()`, `x13_spec()` and `tramoseats_spec()`) now one function for each part of the specification

Common functions (defined in `rjd3modelling`) to set the specification of the preprocessing:

```
set_arima(), set_automodel(), set_basic(), set_easter(),  
set_estimate(), set_outlier(), set_tradingdays(),  
set_transform(), add_outlier() and remove_outlier(),  
add_ramp(), remove_ramp(), add_usrdefvar()
```


rjd3x13

Main functions:

- Specification: created with `spec_x11_default()`, `spec_x13_default()`, `spec_regarima_default()` and customized with `rjd3modelling` functions + `set_x11()`
- Apply SA model with `x11()`, `x13()`, `fast.x13()`
- ARIMA modelling with `regarima()`, `fast.regarima()`
-  Refresh policies: `regarima.refresh()` and `x13.refresh()`

Performance

In median: RJDemetra more 3 time faster than seasonal and rjdemetra3 more than 12 time faster than seasonal!



Exemple (1)


```
library(rjd3modelling);library(rjd3x13)
y <- rjd3toolkit::ABS$X0.2.09.10.M
spec <- spec_x13_default("rsa5c") |> set_easter(type = "unused") |>
  set_outlier(outliers.type = c("A0", "LS")) |>
  set_tradingdays(test = "None") |> set_x11(henderson.filter = 13) |>
  add_outlier(type = "TC", date = "2000-06-01",
             name = "My TC in 2000-06")
m = rjd3x13::x13(y, spec)
m$result$preprocessing
```

```
## Log-transformation: yes
## SARIMA model: (0,1,2) (1,1,1)
##
## Coefficients
##           Estimate Std. Error T-stat
## theta(1)  -1.01804    0.07639 -13.326
## theta(2)   0.20863    0.05378  3.879
## bphi(1)   -0.26680    0.05399 -4.942
## btheta(1) -0.77559    0.05384 -14.405
##
## Regression model:
##           Estimate Std. Error T-stat
## monday      -0.011247   0.004004 -2.809
## tuesday       0.005870   0.004013  1.463
## wednesday    -0.002002   0.004003 -0.500
```

Exemple (2)


```
## thursday          0.014483    0.004021    3.602
## friday            0.001577    0.004023    0.392
## saturday          0.011465    0.003996    2.869
## lp                0.037501    0.010994    3.411
## easter            0.053486    0.008319    6.429
## My TC in 2000-06  0.022947    0.023666    0.970
## Number of observations:  425
## Number of effective observations:  412
## Number of parameters:  14
##
## Loglikelihood:  763.5143
## Adjusted loglikelihood:  -2104.113
##
## Standard error of the regression (ML estimate):  0.03757223
## AIC:  4236.225
## AICC:  4237.283
## BIC:  4292.519
# Also summary function
# summary(m)
plot(m)
```

Exemple (3)



rjd3tramoseats

Main functions:

- Specification: created with `spec_tramoseats_default()`, `spec_tramo_default()` and customized with `rjd3arima` functions + `set_seats()`
- Apply model with `tramoseats()`, `fast.tramoseats()`, `tramo()`, `fast.tramo()`
-  Refresh policies: `tramo.refresh()` and `tramoseats.refresh()`

rjd3tramoseats

Main functions:

- Specification: created with `spec_tramoseats_default()`, `spec_tramo_default()` and customized with `rjd3arima` functions + `set_seats()`
- Apply model with `tramoseats()`, `fast.tramoseats()`, `tramo()`, `fast.tramo()`



- Refresh policies: `tramo.refresh()` and `tramoseats.refresh()`

```
spec <- spec_tramoseats_default("rsafull") |>  
  set_easter(type = "IncludeEasterMonday") |>  
  set_tradingdays(test = "Separate_T") |>  
  set_seats(algorithm = "KalmanSmoother")  
m <- rjd3tramoseats::tramoseats(y, spec)
```



rjdemetra3

Functions to manipulate JDemetra+ workspaces:

- Still in construction: you can load an existing workspace but not create a new one (use `jws.load()` for example)
- Will contain all the functionalities of `rjdworkspace` (more manipulation of workspaces)

rjd3highfreq and rjd3stl

Seasonal adjustment of high frequency data:

-  fractional and multi airline decomposition
-  Extension of X-11 decomposition with non integer periodicity

rjd3stl: STL, MSTL, ISTL, loess

See next presentation of Anna Smyk

Contents

1. Introduction

2. Utility packages

3. Seasonal adjustment packages

4. Other packages

4.1 `ggdemetra3`

4.2 `rjd3filters`

4.3 `rjd3sts` and `rjd3bench`


5. Conclusion

ggdemetra3 (1)

Like `ggdemetra` but compatible with `rjdemetra3`: `ggplot2` to add seasonal adjustment statistics to your plot, `autoplot()` functions... Also compatible with high-frequency methods (WIP):

```
library(ggdemetra3)
spec <- spec_x13_default("rsa3") |> set_tradingdays(option = "WorkingDays")
ggplot(data = ipi_c_eu_df, mapping = aes(x = date, y = FR)) +
  geom_line() +
  labs(title = "SA - IPI-FR",
       x = NULL, y = NULL) +
  geom_sa(component = "y_f(12)", linetype = 2,
         spec = spec) +
  geom_sa(component = "sa", color = "red") +
  geom_sa(component = "sa_f", color = "red", linetype = 2) +
  geom_outlier(geom = "label_repel",
              coefficients = TRUE,
              ylim = c(NA, 65), force = 10,
              arrow = arrow(length = unit(0.03, "npc"),
                           type = "closed", ends = "last"),
              digits = 2)
```

ggdemetra3 (2)




ggdemetra3 (1)

Or from an existing model:


```
mod <- rjd3x13::x13(y, spec)  
autoplot(mod)
```

ggdemetra3 (2)




```
siratioplot(mod)
```

ggdemetra3 (3)



rjd3filters

-  easily create/combine/apply moving averages `moving_average()` (much more general than `stats::filter()`) and study their properties: plot coefficients (`plot_coef()`), gain (`plot_gain()`), phase-shift (`plot_phase()`) and different statics (`diagnostic_matrix()`)

rjd3filters






- easily create/combine/apply moving averages `moving_average()` (much more general than `stats::filter()`) and study their properties: plot coefficients (`plot_coef()`), gain (`plot_gain()`), phase-shift (`plot_phase()`) and different statics (`diagnostic_matrix()`)



- trend-cycle extraction with different methods to treat endpoints:
 - `lp_filter()` local polynomial filters of Proietti and Luati (2008) (including Musgrave): Henderson, Uniform, biweight, Trapezoidal, Triweight, Tricube, "Gaussian", Triangular, Parabolic (= Epanechnikov)
 - `rkhs_filter()` Reproducing Kernel Hilbert Space (RKHS) of Dagum and Bianconcini (2008) with same kernels
 - `fst_filter()` FST approach of Grun-Rehomme, Guggemos, and Ladiray (2018)
 - `dfa_filter()` derivation of AST approach of Wildi and McElroy (2019)

rjd3filters

-  easily create/combine/apply moving averages `moving_average()` (much more general than `stats::filter()`) and study their properties: `plot_coef()`, gain (`plot_gain()`), phase-shift (`plot_phase()`) and different statics (`diagnostic_matrix()`)
-  trend-cycle extraction with different methods to treat endpoints:
 - `lp_filter()` local polynomial filters of Proietti and Luati (2008) (including Musgrave): Henderson, Uniform, biweight, Trapezoidal, Triweight, Tricube, "Gaussian", Triangular, Parabolic (= Epanechnikov)
 - `rkhs_filter()` Reproducing Kernel Hilbert Space (RKHS) of Dagum and Bianconcini (2008) with same kernels
 - `fst_filter()` FST approach of Grun-Rehonne, Guggemos, and Ladiray (2018)
 - `dfa_filter()` derivation of AST approach of Wildi and McElroy (2019)
-  change the filter used in X-11 for TC extraction

Create moving average `moving_average()`

(Recall: $B^i X_t = X_{t-p}$ and $F^i X_t = X_{t+p}$)

Goal: manipulate moving averages

$$M_{\theta}(X_t) = \sum_{k=-p}^{+f} \theta_k X_{t+k} = \left(\sum_{k=-p}^{+f} \theta_k F^k \right) X_t$$

Create moving average `moving_average()`

(Recall: $B^i X_t = X_{t-p}$ and $F^i X_t = X_{t+p}$)

Goal: manipulate moving averages

$$M_{\theta}(X_t) = \sum_{k=-p}^{+f} \theta_k X_{t+k} = \left(\sum_{k=-p}^{+f} \theta_k F^k \right) X_t$$

Currently in **R**, with `filter()` you can only manipulate symmetric filters ($p = f$, $\theta_{-k} = \theta_k$) or real-time asymmetric filters:

$$M_{\theta}(X_t) = \left(\sum_{k=-p}^0 \theta_k F^k \right) X_t = \theta_0 X_t + \cdots + \theta_{-p} X_{t-p}$$

Create moving average `moving_average()`

(Recall: $B^i X_t = X_{t-p}$ and $F^i X_t = X_{t+p}$)

Goal: manipulate moving averages

$$M_{\theta}(X_t) = \sum_{k=-p}^{+f} \theta_k X_{t+k} = \left(\sum_{k=-p}^{+f} \theta_k F^k \right) X_t$$

Currently in **R**, with `filter()` you can only manipulate symmetric filters ($p = f$, $\theta_{-k} = \theta_k$) or real-time asymmetric filters:

$$M_{\theta}(X_t) = \left(\sum_{k=-p}^0 \theta_k F^k \right) X_t = \theta_0 X_t + \dots + \theta_{-p} X_{t-p}$$

In practice, you often need to combine filters (e.g. X-11) or use different filters according to the number of future points available (see `?rjd3filters::finite_filters` and `?rjd3filters::jfilter`)

Create moving average `moving_average()` (1)

```
library(rjd3filters)
m1 = moving_average(rep(1,3), lags = 1); m1 # Forward MA

## [1] " F + F^2 + F^3"

m2 = moving_average(rep(1,3), lags = -1) / 3; m2 # centered MA

## [1] "0,3333 B + 0,3333 + 0,3333 F"

m1 + m2

## [1] "0,3333 B + 0,3333 + 1,3333 F + F^2 + F^3"

m1 - m2

## [1] " - 0,3333 B - 0,3333 + 0,6667 F + F^2 + F^3"

m1 * m2

## [1] "0,3333 + 0,6667 F + F^2 + 0,6667 F^3 + 0,3333 F^4"
```

Create moving average `moving_average()` (2)

Can be used to create all the MA of X-11:

```
e1 <- moving_average(rep(1,12), lags = -6)
e1 <- e1/sum(e1)
e2 <- moving_average(rep(1/12, 12), lags = -5)
# used to have the 1rst estimate of the trend
tc_1 <- M2X12 <- (e1 + e2)/2
coef(M2X12) |> round(3)
```

```
##      t-6      t-5      t-4      t-3      t-2      t-1      t      t+1      t+2      t+3
## 0.042 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083
##      t+4      t+5      t+6
## 0.083 0.083 0.042
```

```
si_1 <- 1 - tc_1
M3 <- moving_average(rep(1/3, 3), lags = -1)
M3X3 <- M3 * M3
# M3X3 moving average applied to each month
coef(M3X3) |> round(3)
```

```
##      t-2      t-1      t      t+1      t+2
## 0.111 0.222 0.333 0.222 0.111
```

Create moving average moving_average() (3)

```
M3X3_seasonal <- to_seasonal(M3X3, 12)  
coef(M3X3_seasonal) |> round(3)
```

```
##  t-24  t-23  t-22  t-21  t-20  t-19  t-18  t-17  t-16  t-15  
## 0.111 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000  
##  t-14  t-13  t-12  t-11  t-10  t-9   t-8   t-7   t-6   t-5  
## 0.000 0.000 0.222 0.000 0.000 0.000 0.000 0.000 0.000 0.000  
##  t-4   t-3   t-2   t-1    t    t+1   t+2   t+3   t+4   t+5  
## 0.000 0.000 0.000 0.000 0.333 0.000 0.000 0.000 0.000 0.000  
##  t+6   t+7   t+8   t+9   t+10  t+11  t+12  t+13  t+14  t+15  
## 0.000 0.000 0.000 0.000 0.000 0.000 0.222 0.000 0.000 0.000  
##  t+16  t+17  t+18  t+19  t+20  t+21  t+22  t+23  t+24  
## 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.111
```

Create moving average `moving_average()` (4)


```
s_1 <- M3X3_seasonal * si_1
s_1_norm <- (1 - M2X12) * s_1
sa_1 <- 1 - s_1_norm
henderson_mm = moving_average(lp_filter(horizon = 6)$
                               filters.coef[, "q=6"],
                               lags = -6)

tc_2 <- henderson_mm * sa_1
si_2 <- 1 - tc_2
M5 <- moving_average(rep(1/5, 5), lags = -2)
M5X5_seasonal <- to_seasonal(M5 * M5, 12)
s_2 <- M5X5_seasonal * si_2
s_2_norm <- (1 - M2X12) * s_2
sa_2 <- 1 - s_2_norm
tc_f <- henderson_mm * sa_2
```

Create moving average moving_average() (5)


```
par(mai = c(0.3, 0.3, 0.2, 0))  
layout(matrix(c(1,1,2,3), 2, 2, byrow = TRUE))  
  
plot_coef(tc_f);plot_coef(sa_2, col = "orange", add = TRUE)  
legend("topleft",  
      legend = c("Final TC filter", "Final SA filter"),  
      col= c("black", "orange"), lty = 1)  
plot_gain(tc_f);plot_gain(sa_2, col = "orange", add = TRUE)  
plot_phase(tc_f);plot_phase(sa_2, col = "orange", add = TRUE)
```


Create moving average `moving_average()` (6)



Apply a moving average

```
y <- retailsa$AllOtherGenMerchandiseStores  
trend <- y * tc_1  
sa <- y * sa_1  
plot(window(ts.union(y, trend, sa), start = 2000),  
      plot.type = "single",  
      col = c("black", "orange", "lightblue"))
```



rjd3sts and rjd3bench

`rjd3sts` Interface to structural time series and state space models

Several examples available here https://github.com/palatej/test_rjd3sts

`rjd3bench` Benchmarking and temporal disaggregation

Several examples here: https://github.com/palatej/test_rjd3bench

Contents

1. Introduction


2. Utility packages

3. Seasonal adjustment packages

4. Other packages


5. Conclusion

Conclusion

With JDemetra+ 3.0, lots of new  packages are coming:

- On time series analysis and seasonal adjustment (much faster than standard packages)
- New developments on seasonal adjustment will be available (e.g. high-frequency data)
- Allow to create new trainings thanks to a deeper access to all the functionalities of JDemetra+

Conclusion


With JDemetra+ 3.0, lots of new  packages are coming:

- On time series analysis and seasonal adjustment (much faster than standard packages)
- New developments on seasonal adjustment will be available (e.g. high-frequency data)
- Allow to create new trainings thanks to a deeper access to all the functionalities of JDemetra+

Many ways to contribute:

- Testing it and reporting issues
- Developing new tools (other packages, new functions, etc.)

Thank you for your attention

Packages :

-  palatej/rjd3toolkit
-  palatej/rjd3modelling
-  palatej/rjd3sa
-  palatej/rjd3arima
-  palatej/rjd3x13
-  palatej/rjd3tramoseats
-  palatej/rjdemetra3

-  palatej/rjdfilters
-  palatej/rjd3sts
-  palatej/rjd3stl
-  palatej/rjd3highfreq
-  palatej/rjd3bench
-  AQLT/ggdemetra3