Good Data or Leaked Data?

Do Aggregate Privacy Checks Hide Risk to Outlier Records in Synthetic Tabular Data?

Megha Chaudhari and Austin Qi

Course Research Project — Progress Report

Response to Proposal Feedback

The proposal feedback asked for a novel research question rather than a literature review alone. We have narrowed the project to one question that the papers we reviewed do not answer directly, and that we can test with our own experiment:

> *When a synthetic dataset passes the aggregate privacy check that generator papers commonly report, are outlier records in the training data still exposed at a much higher rate than typical records?*

Generator papers such as TabDDPM [3] summarize privacy with a single dataset-level number based on the distance to the closest record (DCR). Stadler et al. [6] show with targeted attacks that outliers are the records most at risk. No paper we reviewed checks whether the commonly reported aggregate check would reveal that risk. If it does not, a dataset can look safe on paper while its most identifiable people are exposed. The literature review is still part of the project, but it now serves this question: it explains which checks are reported and why they might miss record-level risk.

We test two hypotheses:

- **H1.** For a given generator, a simple membership inference attack succeeds more often on outlier records than on typical records.
- **H2.** The aggregate DCR check does not reveal this gap: generators can look close to the ideal value while outliers remain more exposed.

Progress on the Literature Review

We have organized the evaluation measures in our six papers into the four groups from the proposal: statistical similarity, predictive utility, privacy-risk checks, and formal privacy guarantees. All six papers report some form of similarity or utility. Table 1 shows the two privacy groups, which our research question depends on.

Two observations motivate our question. First, three of the six papers (SDV, CTGAN, Herurkar et al.) report no privacy-risk check; Herurkar et al. list DCR among existing metrics but do not apply it. Second, where a check is reported, it compares the training set with a held-out set as a whole. TabDDPM reports DCR, and RCGAN concludes that its model does not memorize because reconstruction errors (Kolmogorov–Smirnov test) and an MMD three-sample test do not differ significantly between training and test data. Only the dedicated privacy paper [6] looks at individual records. It finds outliers most exposed and explicitly argues against privacy evaluations based on similarity metrics, but its attacks train many shadow generative models per target, which is too costly to be routine in generator papers. Our experiment asks whether the cheap aggregate check is enough.

Paper	Privacy-risk check	Formal privacy guarantee
SDV [1]	–	–
CTGAN [2]	–	–
TabDDPM [3]	distance to closest record (DCR)	–
RCGAN [4]	train-vs-test memorization tests	differentially private training
Herurkar et al. [5]	– (DCR mentioned, not applied)	–
Stadler et al. [6]	membership and attribute inference attacks	differentially private generators

Table 1: Privacy evaluations reported by each paper. "–" means not tested, not unsafe. Rows for RCGAN, Herurkar et al. and Stadler et al. are checked against the full texts; the others are based on our reading so far and will be re-verified for the final report.

Experimental Setup

We use UCI Adult (45,222 complete rows). For each of three random seeds we split it into a training set (5,000 rows) used to fit the generators, a holdout set (5,000 rows) never seen by them, a test set (10,000 rows) for utility, and a reference set (the remaining rows) used only to define outliers. Each generator produces 5,000 synthetic rows. We compare the Gaussian copula [1], CTGAN [2] and TVAE [2] (300 epochs, `sdv` library), a SMOTE-style interpolation baseline in the spirit of the TabDDPM comparison [3], and a "copy" reference that resamples training rows directly.

- **Utility:** train a gradient-boosting classifier on synthetic data, test on real test data (TSTR), and report F1 for the `>50K` class.
- **Aggregate privacy check:** for each synthetic record, find its closest real record and ask whether it lies in the training set or the holdout set. The share closer to training is the *DCR share*; 0.5 means no sign of copying.
- **Record-level risk:** a simple membership inference attack scores each real record by its distance to the closest synthetic record. We report the fraction of training members identified at a 1% false-positive rate (TPR), separately for typical records and outliers.
- **Outliers:** the 10% of training and holdout records with the largest mean distance to their 10 nearest neighbors in the reference set.

Distances use standardized numeric features and one-hot categorical features, with scaling fit on the training data only.

Preliminary Results

	TSTR F1	DCR share	Members identified at 1% FPR	
Generator		(0.5 = ideal)	Typical	Outliers
Real data (reference)	0.685	–	–	–
Copy (reference)	0.668	1.000	0.635	0.629
Interpolation (SMOTE-style)	0.663	0.929	0.185	0.436
CTGAN	0.599	0.506	0.011	0.009
TVAE	0.586	0.520	0.010	0.013
Gaussian copula	0.083	0.517	0.010	0.017

Table 2: Mean over three seeds. Random guessing identifies 1% of members at 1% FPR.




Figure 1: Members identified by the attack at a 1% false-positive rate, typical vs. outlier records (mean ± 1 s.d. over three seeds).

H1 holds for interpolation, not for the deep generators. The SMOTE-style baseline exposes outliers at more than twice the rate of typical records (43.6% vs. 18.5%, Figure 1), consistent across all three seeds. Interpolating between a rare record and its nearest neighbor produces points that sit close to that rare record and to few others. CTGAN and TVAE show no measurable leakage with our attack, for outliers or typical records, while keeping most of the real-data utility (F1 0.60 and 0.59 vs. 0.69).

In this setting the aggregate check is not misleading. The interpolation baseline that leaks also fails the DCR check clearly (0.93), and the generators that pass it (0.51–0.52) show no leakage. So the natural experiment alone cannot answer H2: no generator here leaks only its outliers.

A controlled test supports H2. To test H2 directly, we adapt the approach Herurkar et al. [5] use for fidelity metrics: inject a known defect and check whether the metric responds. We start from TVAE output and replace a small number of synthetic rows with near-copies of randomly chosen outlier training records (numeric features jittered by 5% of a standard deviation, so none is an exact duplicate). This simulates a generator that memorizes only its rarest records. Figure 2 shows the result:

- With 50 planted rows (1% of the synthetic data), the attack identifies 11.0% of outlier members, up from 1.3% with none planted. The DCR share moves only from 0.520 to 0.524, and the exact-duplicate check finds nothing.
- Even with 250 planted rows, about half of all outlier members (50.8%) are identified, yet the DCR share (0.545) stays inside the range we observed for the unaltered generators (0.46–0.56).
- The attack's overall success rate barely moves either (1.0% to 1.4%). An average over all records hides the risk as well as the DCR check does.

Takeaway so far. A dataset can pass the dataset-level check that generator papers report while exposing a large share of its outliers. The check is only informative when leakage is widespread, as with interpolation. This suggests that privacy evaluations should report attack success on outliers (or another high-risk subgroup) separately, not only an average.

Remaining Work and Timeline

- **Week 4 (current):** Done: data pipeline, five generators, utility and privacy measures, the planted-leakage test, three random seeds. Next: check that the outlier definition is not driving




Figure 2: Planting near-copies of outlier training records into TVAE output (mean ± 1 s.d. over three seeds). (a) The aggregate DCR share stays within the range seen for unaltered generators (gray band). (b) The share of outlier members identified rises roughly linearly, while the overall rate stays near 1%.

the result by repeating with a second definition (isolation forest) and a 5% cut-off.

- **Week 5:** Add one stronger attack that uses all synthetic neighbors rather than the single closest record, and a second dataset if time allows. Write the full report.
- **Week 6:** Write the checklist (now including a record-level check for outliers), revise, and finalize the notebook.

Challenges and Changes

- The Gaussian copula produced poor utility on Adult (Table 2), so it is mainly a low-utility, low-leakage reference point. We will report this rather than tune it to look better.
- Our attack and DCR both depend on how features are encoded and scaled. We fix the encoding on real training data only and document it in the code; results with other encodings may differ.
- One dataset and three seeds limit how far the results generalize. The planted test shows that the aggregate check *can* miss concentrated leakage. It does not show that real generators leak this way; CTGAN and TVAE did not in our runs. We will present it in those terms.
- Our attack is deliberately simple. Stronger attacks [6] might find leakage in CTGAN or TVAE that ours does not, so "no measurable leakage" means "none found by this attack".

Code and results are in our course repository under `synthetic_privacy_project/`.

References

[1] N. Patki et al. The Synthetic Data Vault. IEEE DSAA, 2016.
[2] L. Xu et al. Modeling Tabular Data using Conditional GAN. NeurIPS, 2019.
[3] A. Kotelnikov et al. TabDDPM: Modelling Tabular Data with Diffusion Models. ICML, 2023.
[4] C. Esteban et al. Real-valued (Medical) Time Series Generation with Recurrent Conditional GANs. arXiv:1706.02633, 2017.
[5] D. Herurkar et al. Evaluating Generative Models for Tabular Data: Novel Metrics and Benchmarking. arXiv:2504.20900, 2025.
[6] T. Stadler et al. Synthetic Data – Anonymisation Groundhog Day. USENIX Security, 2022.