














AWS 3-TIER APPLICATION DEPLOY



Prerequisites

-  AWS Account
-  Basic knowledge of Linux

List of AWS services

-  Amazon CloudFront
-  Amazon Route 53
-  Amazon EC2
-  Amazon Autoscaling
-  Amazon Certificate Manager
-  Amazon Backup service
-  Amazon RDS
-  Amazon VPC
-  Amazon WAF
-  Amazon CloudWatch

Plan of Execution


-  What is three-tier architecture

- 🏠 The architecture of the project
- 🚀 A step-by-step guide with screenshots
- ☐ Testing
- ☐ Resource cleanup
- ☐ conclusion

😞 What is Three-tier architecture

Three-tier architecture is a software architecture pattern that separates an application into three layers.

- ◆ Presentation layer ➡ handles user interaction
- ◆ Application layer(backend logic) ➡ processes business logic and data processing
- ◆ Data layer (database) ➡ manages data storage and retrieval




Each layer has distinct responsibilities, allowing for modularity, scalability, and maintainability. This architecture promotes the separation of concerns and facilitates easy updates or modifications to specific layers without impacting others.

🏠 Architecture of the Project

Let's see the architecture of today's project. we are going to follow a goal-driven approach that helps us to put in minimum effort and gain lots of results. it's very important to understand what we are going to build and to understand you can follow the below architecture. I request you please go through it once. it helps you a lot while building this project.

I have spent hours creating this below animated architecture and if you liked it please like my blog and follow me on [LinkedIn](#).



Architecture design without animation [here](#)

🚀 A Step-by-step guide

we are following a **Warm standby Disaster recovery strategy** so we are going to utilize two regions during our deployment. **us-east-1** AKA North Virginia as **primary** and **us-west-2** AKA Oregon as secondary or DR.

◆ VPC

firstly we are going to set up VPC in both regions to isolate our resources from the internet. The below image contained all the subnets, their IP range, and their uses. you can use your own VPC setup if you have a better idea. and if you are a beginner, please create VPC as I have shown below.

| VPC | 172.20.0.0/16 | | | |
|-----------------------------|-------------------------|-----------------|-------------------------|-----------------|
| Availability zone | us-east-1a / us-west-2a | | us-east-1b / us-west-2b | |
| uses | name of the subnet | subnet ip range | name of the subnet | subnet ip range |
| ALB frontend ALB backend | pub-sub-1a | 172.20.1.0/24 | pub-sub-2b | 172.20.2.0/24 |
| Web servers | pri-sub-3a | 172.20.3.0/24 | pri-sub-4b | 172.20.4.0/24 |
| App servers | pri-sub-5a | 172.20.5.0/24 | pri-sub-6b | 172.20.6.0/24 |
| Databases | pri-sub-7a | 172.20.7.0/24 | pri-sub-8b | 172.20.8.0/24 |

please log in to your AWS Account and type VPC in the AWS console. and click on VPC service.



click on Your VPC's button on the left and then click on Create VPC the button on the top right corner of the page



here we can see the form where we can fill the configuration of VPC. please enter the name that you want to keep and the IPV4 CIDR block. in my case CIDE block is 172.20.0.0/16.

Create VPC

A VPC is an isolated portion of the AWS network, administered by AWS Identity and Access Management (IAM).

VPC settings

Requirements to create: info
Create only the VPC, or select the VPC and create subnets and resources.

☒ VPC only ☐ VPC and subnets

Learning - optional
Create this VPC with a list of names for your subnets.

IPv4 CIDR block info
☒ IPv4 CIDR block ☐ IPv6 CIDR block ☐ IPv4 and IPv6 CIDR block

IPv4 CIDR

IPv4 CIDR block info
☒ New IPv4 CIDR block ☐ IPv4 address from IPv4 CIDR block ☐ Amazon-provided IPv4 CIDR block ☐ IPv4 CIDR block from my

Subnets info
Default

Tags
Assign a list of tags to your VPC. Tags are key-value pairs that help you organize your AWS resources. For more information, see the AWS IAM documentation.

Key ☒ **Value** ☒ **Remove**

Maximum 50 tags per VPC

now click on the subnet button which is located on the left side and then click on the Create subnet button on the top right corner of the page.

Subnets

Filter by VPC:

Virtual private cloud
☒ VPCs ☐ Subnets

| Name | Subnet ID | State | VPC | IPv4 CIDR | IPv6 CIDR | Available IPv4 addresses | Availability Zone | Availability Zone ID | Network Interface |
|-----------|-----------|-----------|--------|---------------|-----------|--------------------------|-------------------|----------------------|-------------------|
| subnet-1a | vpc-1a | Available | vpc-1a | 172.20.0.0/16 | | 4095 | us-east-1a | us-east-1a | eni-1a |
| subnet-1b | vpc-1b | Available | vpc-1b | 172.21.0.0/16 | | 4095 | us-east-1b | us-east-1b | eni-1b |
| subnet-1c | vpc-1c | Available | vpc-1c | 172.22.0.0/16 | | 4095 | us-east-1c | us-east-1c | eni-1c |
| subnet-1d | vpc-1d | Available | vpc-1d | 172.23.0.0/16 | | 4095 | us-east-1d | us-east-1d | eni-1d |
| subnet-1e | vpc-1e | Available | vpc-1e | 172.24.0.0/16 | | 4095 | us-east-1e | us-east-1e | eni-1e |
| subnet-1f | vpc-1f | Available | vpc-1f | 172.25.0.0/16 | | 4095 | us-east-1f | us-east-1f | eni-1f |

please remove the default VPC ID and choose the VPC ID that we have just created in the VPC ID field. and click on the Add Subnet button at the bottom.

Create subnet

VPC
VPC ID:

Associated VPC CIDRs
IPv4 CIDR: 172.20.0.0/16

Subnet settings
Specify the VPC ID and the availability zone for the subnet.

now we need to configure our subnets. Again you can use the VPC configuration image that I shared earlier on the blog to get the IP range and to know which subnet will be used for what purpose. we are going to create a total of 8 subnets of which 2 of them are public and the rest of 6 subnets are private. you can create a subnet as I have shown in the below image. after adding all the subnets click on Create subnet button.

Associated VPC CIDRs

VPC CIDRs
172.20.0.0/16

Subnet settings
Specify the VPC CIDR block and availability zone for the subnet.

Subnet 1 of 2

Subnet name
pub-sub-1a

Availability zone
us-east-1b (us-east-1b) (us-east-1b)

CIDR block
172.20.1.0/24

Tags - optional

Key
Name

Value
pub-sub-1a

Subnet 2 of 2

Subnet name
pub-sub-1b

Availability zone
us-east-1c (us-east-1c) (us-east-1c)

CIDR block
172.20.2.0/24

Tags - optional

Key
Name

Value
pub-sub-1a

Add new subnet

after the successful creation of all 8 subnets, they look like this. you can verify with my subnets.

| Name | Subnet ID | State | VPC | IPv4 CIDR | IPv6 CIDR | Available IPv4 addresses | Availability Zone | Network ID |
|------------|------------------------|-----------|----------------------|---------------|-----------|--------------------------|-------------------|----------------------|
| pub-sub-1a | subnet-03a7d770b3e0a91 | Available | vpc-04411d969779d9f1 | 172.20.1.0/24 | --- | 251 | us-east-1b | vpc-04411d969779d9f1 |
| pub-sub-1b | subnet-03a7d770b3e0a92 | Available | vpc-04411d969779d9f1 | 172.20.2.0/24 | --- | 251 | us-east-1c | vpc-04411d969779d9f1 |
| pub-sub-2a | subnet-03a7d770b3e0a93 | Available | vpc-04411d969779d9f1 | 172.20.3.0/24 | --- | 251 | us-east-1a | vpc-04411d969779d9f1 |
| pub-sub-2b | subnet-03a7d770b3e0a94 | Available | vpc-04411d969779d9f1 | 172.20.4.0/24 | --- | 251 | us-east-1b | vpc-04411d969779d9f1 |
| pub-sub-3a | subnet-03a7d770b3e0a95 | Available | vpc-04411d969779d9f1 | 172.20.5.0/24 | --- | 251 | us-east-1c | vpc-04411d969779d9f1 |
| pub-sub-3b | subnet-03a7d770b3e0a96 | Available | vpc-04411d969779d9f1 | 172.20.6.0/24 | --- | 251 | us-east-1a | vpc-04411d969779d9f1 |
| pub-sub-4a | subnet-03a7d770b3e0a97 | Available | vpc-04411d969779d9f1 | 172.20.7.0/24 | --- | 251 | us-east-1b | vpc-04411d969779d9f1 |
| pub-sub-4b | subnet-03a7d770b3e0a98 | Available | vpc-04411d969779d9f1 | 172.20.8.0/24 | --- | 251 | us-east-1c | vpc-04411d969779d9f1 |

now we are going to create Internet Gateway also known as **IGW**. it is responsible for communication between VPC, VPC's public subnet with the Internet. without IGW we won't be able to communicate with the Internet. so let's create that. click on the internet gateways button at the left panel. and then click on the Create Internet gateways button on the top right corner of the page.

Internet gateways (1/1) sub

Internet gateways

Create Internet gateway

| Name | Internet gateway ID | State | VPC ID | Domain |
|-----------|---------------------|-----------|----------------------|---------------|
| vpc-igw-1 | igw-03a7d770b3e0a91 | Available | vpc-04411d969779d9f1 | 172.20.0.0/16 |

give any name you wanna give to IGW. and click on Create Internet gateway button.

Create internet gateway

Internet gateway settings

Name:

Tags & options

Key: Value

Key: Value:

after creating an internet gateway we need to attach it with VPC to use it. for that click on the Action button. here you can see the drop-down list. please select the option Attach to VPC.

Internet gateway details

igw-004957e309e7a0e3a / IGW-three-tier-app

Actions

Attach to VPC

Attach to VPC


please select VPC that we have created just now from the Available VPC list. and then click on the Attach Internet gateway button.

Attach to VPC


Available VPCs

vpc-0442354668779a0f


Now we need to create a NAT gateway. NAT gateway is responsible to connect resources that are in the private subnet to communicate with the internet. all the resources which will be there in a private subnet will communicate to the internet through the NAT gateway. we will keep the NAT gateway in the public subnet so that it can access the internet. NAT gateway is a chargeable resource. so you will be charged by AWS as long as you keep it up. Now to create a NAT gateway click on the NAT gateways button on the left panel of the web page. and then click on the Create NAT gateways button in the top right corner of the page.



give any name you want to give to the NAT gateway. but be cautious with selecting a subnet. **You have to select one of the Public subnets among the two. either pub-sub-1a or pub-sub-2b.** then click on the Allocate Elastic IP button to allocate Elastic IP. and then click on the Create NAT gateways button. NAT gateways creation takes 2-4 minutes.



Now we need to have a route table to handle traffic for public subnet and private subnet and for that, we need to create a Route table. we are going to create two route tables one for the public subnet and another one for the private subnet. first, we are going to create RT for the public subnet. so click on the Route table button which you can see on the left panel. and click on the Create Route table button on the top corner of the page.



give a name to your RT such as Pub-RT. please give a name that is appropriate for resources then it will be easy to organize the things. make sure you select the correct VPC. and then click on the create route table.

VPC > Route tables > Create route table

Create route table [Help](#)

Amazon Route 53 lets you associate the subnets within your VPC, the internet, and your VPN connections.

Route table settings

Name: R01R01
 (Click on the top of the input field to select from the suggestions)

VPC: **vpc-0a220349d770af770af** (This VPC uses VPC)

Tags

Assign a label to your resources on AWS to organize them logically, such as by region, and to optimize costs. You can tag resources from the console or using the AWS CLI.

Key: Name Value: ap01-us-east-1


let's create RT for the private subnet.

The screenshot shows the 'Create route table' page in the AWS IAM console. The 'Route table settings' section has 'Name' set to 'rt-1' and 'VPC' set to 'vpc-044550a3b37396af7 (us-east-1) vpc'. The 'Tags' section has 'Key' as 'Name' and 'Value' as 'rt-1'. A yellow box highlights the 'Create route table' button at the bottom right. A yellow arrow points from the 'Create route table' button to the 'VPC' dropdown menu.


Now, we need to do some association with both RTs so select **Pub-RT** and click on the Routes tab at the bottom and then click on the edit route button.

The screenshot shows the AWS IAM console's 'Route tables' page. The 'Route tables' table lists three route tables. The 'pub-RT' row is highlighted with a yellow box and labeled '1'. The 'Route' tab is selected for the 'pub-RT' route table, and the 'Routes' table is shown below. The 'Routes' table has one entry, '122.20.0.0/24', which is highlighted with a yellow box and labeled '2'. The 'Add routes' button is highlighted with a yellow box and labeled '3'.


click on the Add Route button. and select 0.0.0.0/0 in the destination field. and then click on the Target field. As soon as you click on the Target field one drop-down will open and here you have to select Internet gateway, shown in the below image.




here you can see the IGW that we created earlier. select that IGW and click the save changes button.




keep Pub-RT selected and click on the Subnet associations tab next to the Routes tab. and then click on the Edit subnet associations. as shown in the below image.




now select both public subnets. **pub-sub-1a** and **pub-sub-2b**. and click on the save associations button.




now we have to do the same thing for the Pri-RT as well. but there is one slight change. let me show you. Please select Pri-RT and click on the Routes tab at the bottom of the page.




Here please select 0.0.0.0/0 in the destination field and click on the target. As soon as you click on the target you will see the drop-down list. Please select NAT gateway from the drop-down list. As shown in the below image.




select the NAT gateway that we have just created. and click on the save changes button.



keep Pri-RT selected and click on the subnet associations tab at the bottom next to the Routes tab. And then click on the Edit route associations button.




Here you can see the same situation as we saw before. But here we are going to select all the 6 private subnets. And then click on the save association button.




Before we move ahead I want to change the settings of VPC and two public subnets. So just click on the Your VPC button on the left panel and select VPC that we have created and click on the action button and there you will see the drop-down menu. Select the Edit VPC setting button. As shown in the image.




And here please enable **Enable DNS hostname** checkbox by clicking on it. and then click on the Save button



Please go to the subnet page and select the public subnet and click on the action button and then choose the Edit subnet setting button from the drop-down list.



Here you have to mark right on **Enable public assign public IPV4 address**. And then click on the save button



And here we are done with VPC configuration in the primary region. In my case **us-east-1 (N.Virginia)**. But we have to do the same setup in the secondary region as well. As you know I am going to use the **us-west-2 (Oregon)** as my second region AKA Oregon.


Your task is to set up VPC in the secondary region. All the setup is completely similar. You just have to change the region. And please do VPC set up in the secondary region.

I hope you did the setup. Now let's move ahead


◆ Security Groups (SG)

Security groups are very essential part of the infrastructure. Because it can secure the resources in the cloud. SGs are a kind of firewall that allow or block incoming and outgoing traffic. SGs are applied to the resources like ALB, ec2, rds, etc. One resource can have more than one SG.


So let's first understand. How SG will be used in our architecture and how we are going to apply that. Please see the below image you will get all the ideas. Which resource depends on what. And what are the port numbers we need to allow etc..



To create SG, click on the security groups tab on the left panel and here you will see the Security Groups button. Note that SGs are specific with VPC. So we can't use SG which is created in a different VPC. So when you create SG please make sure that you choose the right VPC. click on the create security button on the top right corner.



We will create our first SG for **bastion-jump-server**. Give any name and description you want but please remove the default VPC and add VPC that we have just created. Then click on the Add rule button in inbound rules. And add SSH rule and add your IP in the destination. Please don't do anything with the outbound rule if you don't have a good understanding. And then click on the create security group button.



Now let's create SG for the **ALB-frontend**. Again steps are similar but add the rule HTTP AND HTTPS from anywhere on the internet because both ALB are internet facing. But please select the right VPC.

Create security group [info](#)

A security group exists on a virtual network. It controls inbound and outbound traffic. To create a new security group, complete the fields below.

Basic details

Security group name [info](#)

Security group description [info](#)

VPC [info](#)

Inbound rules

| Type info | Protocol info | Port range info | Source info | Description optional info |
|---------------------------|-------------------------------|---------------------------------|-----------------------------|---|
| HTTP | TCP | 80 | Anywhere-IPv4 | |
| HTTPS | TCP | 443 | Anywhere-IPv4 | |

[Add rule](#)

Outbound rules

| Type info | Protocol info | Port range info | Destination info | Description optional info |
|---------------------------|-------------------------------|---------------------------------|----------------------------------|---|
| All traffic | Any | Any | Anywhere | |

[Add rule](#)

Tags - optional

Key Value [optional](#) ☒ [Remove](#)

[Add new tag](#)

[Cancel](#) [Create security group](#)

Create SG for **ALB-backend**. ALB-backend is also internet-facing. Again allow HTTP and HTTPS from anywhere.

Create security group [info](#)

A security group exists on a virtual network. It controls inbound and outbound traffic. To create a new security group, complete the fields below.

Basic details

Security group name [info](#)

Security group description [info](#)

VPC [info](#)

Inbound rules

| Type info | Protocol info | Port range info | Source info | Description optional info |
|---------------------------|-------------------------------|---------------------------------|-----------------------------|---|
| HTTP | TCP | 80 | Anywhere-IPv4 | |
| HTTPS | TCP | 443 | Anywhere-IPv4 | |

[Add rule](#)

Outbound rules

| Type info | Protocol info | Port range info | Destination info | Description optional info |
|---------------------------|-------------------------------|---------------------------------|----------------------------------|---|
| All traffic | Any | Any | Anywhere | |

[Add rule](#)

Tags - optional

Key Value [optional](#) ☒ [Remove](#)

[Add new tag](#)

[Cancel](#) [Create security group](#)

create SG for frontend servers. Our frontend server will be in a private subnet so add the HTTP rule and select the source as **ALB-frontend-sg**. So only ALB-frontend can access the frontend server on port 80. You have to add one more rule SSH allows from **bastion-jump-server-sg**. So that the bastion host can log in to web servers.

Create security group [info](#)

A security group acts as a virtual firewall for your instance to control inbound and outbound traffic. To create a new security group, complete the following steps.

Basic details

Security group name: 1

Description: 2

VPC: 3

Inbound rules

| Type | Protocol | Port range | Source | Description (optional) |
|------|----------|------------|------------------|------------------------|
| HTTP | TCP | 80 | 0.0.0.0/0 | |
| TCP | TCP | 80 | sg-0421d6d7716d7 | |

Outbound rules

| Type | Protocol | Port range | Destination | Description (optional) |
|-------------|----------|------------|-------------|------------------------|
| All traffic | TCP | 0.0.0.0/0 | 0.0.0.0/0 | |

Tags - optional

Key: Value:

Let's create SG for the backend server. Again steps are completely similar to **frontend-sg**. You have to allow port 80 from **ALB-backend-sg** so that only **ALB-backend** can request to the backend server and add the rule SSH allows from **bastion-jump-server-sg**. So that the bastion host can log in to backend servers.

Create security group [info](#)

A security group acts as a virtual firewall for your instance to control inbound and outbound traffic. To create a new security group, complete the following steps.

Basic details

Security group name: 1

Description: 2

VPC: 3

Inbound rules

| Type | Protocol | Port range | Source | Description (optional) |
|------|----------|------------|------------------|------------------------|
| HTTP | TCP | 80 | sg-0421d6d7716d7 | |
| SSH | TCP | 22 | sg-0421d6d7716d7 | |

Outbound rules

| Type | Protocol | Port range | Destination | Description (optional) |
|-------------|----------|------------|-------------|------------------------|
| All traffic | TCP | 0.0.0.0/0 | 0.0.0.0/0 | |

Tags - optional


Key: Value:

Lastly, we are going to create SG for RDS instance. Allow port 3306 MySQL/Aurora from **backend-sg** so that only the backend server will be able to access it. and no one else can access our database.


And here our SG setups are complete now. Your task is to do the complete same setup for the secondary region. In my case, it is **Oregon (us-west-2)**.

◆ RDS and Route 53


Now we are going to set up a database for our application. And for that, we are going to utilize the RDS service of AWS. So let's head over to the RDS dashboard. Just search RDS in the AWS console. And click on the service.




Now first we need to set up a subnet group. It specifies in which subnet and Availability zone our database instance will be created. So click on the subnet group button on the left panel. And click on the button Create database subnet group which is in the middle of the web page.




Here we can configure our VPC, subnet, and availability zone. Give any name to your subnet but make sure you select the correct VPC. and select **Az-us-east-1a** and **us-east-2b**. According to the architecture that I have shown you, our database will be in private subnet **pri-sub-7a** and **pri-sub-8b**. so please select as I have shown in the below figure. And then click on the create button.



Note: we need to create a subnet group in the **Oregon** region as well. All the configuration is similar to the above. just need to change the Availability zone **us-west-2a** and **us-west-2b**



Now come to the **N.virginia** region and here we are going to create a database. So click on the database button on the left panel and then click on the created database button.



On this page, we can configure our database. Select stander create because I'm going to show you each and every step. select MySQL in the engine option because our application runs on MySQL database. If your app runs on other engines you can select that one. Furthermore, you can select the engine version my application is compatible with MySQL version. But you can select according to the developer guild.

Create database

Choose a database creation method

- ☒ Standard create: Use part of the configuration template, including one for availability, security, backups, and maintenance.
- ☐ Easy restore: Use a recommended template for restoring a database from a backup.

Engine options

Engine type

- ☐ Aurora (MySQL, Compatible)
- ☐ Aurora (PostgreSQL, Compatible)
- ☒ MySQL
- ☐ MariaDB
- ☐ PostgreSQL
- ☐ Oracle
- ☐ Microsoft SQL Server

Database

☒ MySQL, Community

Engine version

MySQL 8.0.32

MySQL

MySQL is the most popular open source database in the world. MySQL, and its fork MariaDB, offers the rich features of the MySQL Community Edition with the flexibility to easily scale compute resources or storage capacity for your database.

- Supports database size up to 64 TiB.
- Supports General Purpose, Memory Optimized, and Burstable Performance Instance classes.
- Supports automated backup and point-in-time recovery.
- Supports up to 15 Read Replicas per instance, within a single Region or 5 read replicas cross-region.

Scroll down, and select Dev/test as template. If you select the free tier then you won't be able to deploy RDS in a multi-availability zone. Select Multi-AZ DB instance from availability and durability option. In settings give any name to your database. In the credential setting give the username of the database in the Master username field and give the password in the Master password field. And then confirm the password below. Please do remember your username and password.

Templates

Choose a template to use when you create your database.

- ☐ Production: Use a template for high availability and high database performance.
- ☒ Dev/Test: This template is intended for development and testing of a production database.
- ☐ Free tier: Use this template for a free tier database.

Availability and durability

Deployment options

The deployment option determines how your database is deployed and how it is scaled.

- ☐ Multi-AZ DB Instance: Deploy your database in two Availability Zones for high availability.
- ☒ Single-AZ DB Instance: Deploy your database in one Availability Zone.

Settings

DB instance identifier

The DB instance identifier is the name of your database instance. It must be unique across all database instances in your AWS Region.

Master username

Enter a username for the master user of your database instance.

Master password

Enter a password for the master user of your database instance.

Again scroll down, select Burstable class in the instance setting and select the instance type. Actually, it depends on your application uses. But for learning purposes, I am selecting t3.micro. now in storage type select General purpose(GP2) and allocate 22 GiB for database. Please uncheck the auto-scaling option to keep our costs low. And In the connectivity option please select the option according below screenshot.

In VPC, select VPC that we created earlier and in DB subnet group select the group that we just created, In the public access option please select No, choose existing security, and select security group **book-rds-db**.

Scroll down, click on Additional Configuration, and in the database option give the name **test** because we need a database with the name of the **test** in the application. Enable Automated Backup. Note: you have to enable automated backup otherwise you won't be able to create a read replica of the RDS instance.

Database authentication

Database authentication options

☒ Password authentication
 Authentication using database passwords

☐ Password and SSL database authentication
 Authentication using database passwords and SSL certificates (through SSL/TLS)

☐ Password and Federated Authentication
 Connect a database to various user name tables authentication with federated authentication

Monitoring

Monitoring

Enable federated monitoring

Enabling federated monitoring enables you to set up monitoring for various different parameters with respect to the DB.

Granularity

hourly

Monitoring role

default

Enabling a new database with auto backup to ensure the database is always up to date.

Additional configuration

Configure options, on a per database basis, to enable or disable various DB parameters. Use the options to enable or disable parameters.

Database options

Use of database name

yes

DB parameter group

default_mysql56

Options group

default_mysql56

Backup

Enable automated backup

Enabling a backup is a key aspect of your database.

This is note that automated backup is currently supported for InnoDB storage engine only. If you are using MyISAM, refer to backup here.

Backup retention period

7


MySQL

MySQL is the most popular open source database in the world. MySQL and MSS offer the core features of the MySQL community edition with the flexibility to easily scale, integrate, replicate or manage security for your database.

- Supports database size up to 64 TB.
- Supports InnoDB, MyISAM, Memory, Columnstore and Federated Performance Schema engines.
- Supports a structured backup and recovery solution.
- Supports up to 128GB database per instance, with a single region or a multi-region configuration.


Scroll down, mark on enable encryption checkbox to make the database bit more secure, and click on Create database button below.

[illegible]



Note: RDS take 15-20 minute because it creates a database and then take a snapshot. So please have patience and wait for it to be ready.

After your database is completely ready and you see the status Available then select the database and click on the Action button. There you can see the drop-down list. Please click on created read-replica.



This page is similar to creating a database. In the AWS region select the region where you want to create the read replica. In my case, It is **Oregon (us-west-2)**. Give a name to your read replica, and select all the necessary configurations that we did before while creating the database. For your reference, I have shown everything in the below images.

Amazon RDS

Dashboard
Performance insights
Query Editor
Performance insights
Snapshots
Export to Amazon S3
Automated backups
Recent instances
Reset

Subnet groups
Parameter groups
Option groups
Custom engine versions

Events
Event categories

Recommendations
Certificate authority

Next > Back < Create new read replica

Create read replica

You are creating a replica DB instance from a source DB instance. This new DB instance will have the same DB instance ID, security groups and VPC parameter group.

Settings

Replica source
Select a database instance

Read replica

DB instance identifier
DB instance identifier. This is the unique identifier for the instance. This parameter is stored in a database with ID, instance, region, and availability zone.

Read replica

Instance configuration

Read replica instance configuration is inherited from the source instance. You can modify the configuration for the read replica.

DB instance class [Info](#)

☐ General purpose (includes MySQL)

☐ Memory optimized (includes MySQL)

☒ Burstable shared (includes MySQL)

db.r5.large

☐ Include provisioned IOPS

AWS Region

Destination Region
The region in which the read replica is created.

US East (Oregon)

Storage

Storage type [Info](#)

Provisioned IOPS (SSD)

Allocated storage [Info](#)

100

The allocated storage is 100 GB and the provisioned IOPS is 1,000 IOPS.

[Provisioning best practices for Amazon RDS](#) (PDF) to help you get the most out of your Amazon RDS instances. Learn more [AWS](#)

Amazon RDS

Dashboard
Performance insights
Query Editor
Performance insights
Snapshots
Export to Amazon S3
Automated backups
Recent instances
Reset

Subnet groups
Parameter groups
Option groups
Custom engine versions

Events
Event categories

Recommendations
Certificate authority

Storage autoscaling [Info](#)

☐ Enable storage autoscaling
Enabling this feature will allow the storage to increase after the specified threshold is reached.

Availability

Database configurations [Info](#)

The following configurations are inherited from the source instance.

☐ Multi-AZ DB instance

☒ Multi-AZ DB instance

☐ Single DB instance

Connectivity

Network type [Info](#)

To use Amazon RDS, you must specify a network type. Amazon RDS supports two network types: VPC and EC2-Classic.

☒ VPC

☐ EC2-Classic

Subnet group [Info](#)

Choose the VPC subnet group. The DB instance group will be created in the VPC subnet group.

Read replica

Public access

☐ Publicly accessible
The instance will be accessible to the Internet. Amazon RDS instances are not publicly accessible by default. Amazon RDS instances are not publicly accessible by default.

☒ Not publicly accessible
The instance will not be accessible to the Internet. Amazon RDS instances are not publicly accessible by default.

Enabling VPC security groups

Choose VPC security groups

Default VPC



Additional configuration

Database port [Info](#)


Port on which the database is accessible.

3306


Database authentication



Once you click on the button create replica . It will start creating that.



You can check your read replica on the specified region's RDS dashboard. So let me head over to **Oregon** and show you the read replica.




Note: we can't write anything into a read replica. It is just read-only database. So when a disaster happens we just have to promote read replica so that it becomes the primary database in that region.

Now we are going to utilize route 53 service and create two private hosted zone. One for **north Virginia(us-east-1)** and another one for **Oregon region (us-west-2)** with the same name. you may think Why Two hosted zone with the same name? don't worry I will answer it later. So head over to Route 53. Type route 53 in the AWS console. And click on the service.



Firstly, we are gonna create a hosted zone for **us-east-1**. Click on the Hosted Zones button on the left panel and click on the created hosted zone button on the top right corner.

Create a hosted zone



Give any domain name because anyhow it will be private hosted zone but it would be great if you give the name same as mine (**rds.com**). Please select the private hosted zone and Select the region. In my case, it is **us-east-1**. And then select VPC ID. Make sure you select VPC that we created earlier. Because this hosted zone will resolve the record only in specified VPC. and then click on the Create hosted zone.

Create hosted zone

Hosted zone configuration

Domain name:

Description:

Type: ☒ Private hosted zone

VPCs to associate with the hosted zone

Add VPC

Tags

Create hosted zone

Now we are going to create a Record that points to our RDS instance which is in **us-east-1**. So click on create record button on the top right corner.

Hosted zone details

Records (2)

| Name | Type | Routing policy | Alias | Value/Route traffic to |
|---------|------|----------------|-------|-----------------------------|
| rds.com | A | Simple | | us-east-1 rds.amazonaws.com |
| rds.com | A | Simple | | us-east-1 rds.amazonaws.com |

Create record

Select simple routing,

Here type book in the record name field. In the record type select CNAME. In the value field paste **endpoint of the RDS which is in us-east-1**. Then click on the defined record button.

Quick create record [Switch to wizard](#)

▼ **Record 1** Delete

Record name [Info](#) .rds.com

Record type [Info](#) CNAME – Routes traffic to another domain name and to some AWS reso...

Value [Info](#)

Enter multiple values on separate lines.

TTL (seconds) [Info](#) 1m 1h 1d

Routing policy [Info](#) Simple routing

Recommended values: 60 to 172800 (two days)

Add another record

Cancel Create records

Now we are going to create a new hosted zone with the same name. but for **disaster recovery region** and that is **us-west-2 (Oregon)**. While creating hosted zone please keep in mind that you need to choose the **us-west-2** region and select VPC that you have created in the **the us-west-2** region. Again you can utilize the below image for reference

Create hosted zone

Hosted zone configuration

Zone name [Info](#)

Zone type [Info](#) Public hosted zone

Region [Info](#) us-west-2

VPCs to associate with the hosted zone [Info](#)

☒ Associate VPCs that you associate with a private hosted zone. You must select the Amazon VPC settings: us-west-2 us-west-2 us-west-2

☐ Public hosted zone

☒ Private hosted zone

Tags

Add tag

Create hosted zone

Our next step is to set up a **simple record** that points to the **read replica** (database) which is in the **us-west-2 (Oregon)**. So select the hosted zone that was created for **us-west-2** and defined a simple record in that. Everything is the same as we defined the record in the us-east-1 hosted zone.

▼ Record 1 Delete

Record name [Info](#) .rds.com

Record type [Info](#) CNAME – Routes traffic to another domain name and to some AWS reso...

☐ Alias

Value [Info](#)

Enter multiple values on separate lines.

TTL (seconds) [Info](#) 1m 1h 1d

Routing policy [Info](#) Simple routing

Recommended values: 60 to 172800 (two days)

Add another record

After successfully completing the above steps your Route 53 console look like this.

[Route 53](#) > Hosted zones

Hosted zones (4) Refresh View details Edit Delete Create hosted zone

Automatic mode is the current search behavior optimized for best filter results. [To change modes go to settings.](#)

< 1 > Settings

| | Hosted zone name | Type | Create... | Record ... | Descrip... | Hosted... |
|-----------------------|------------------------------|---------|-----------|------------|------------|-----------|
| <input type="radio"/> | rds.com | Private | Route 53 | 3 | us-east-1 | Z059978 |
| <input type="radio"/> | rds.com | Private | Route 53 | 3 | us-west -2 | Z055657 |
| <input type="radio"/> | narni.co.in | Public | Route 53 | 3 | - | Z073563 |
| <input type="radio"/> | vardhan.live | Public | Route 53 | 5 | - | Z035076 |

You may think that We can connect two regions and VPC in one hosted zone then why two private hosted zone with the same name? And the answer is Endpoint of both databases will be different and we can't implement a health check coz we attached a security group that allow traffic from **3306 port from only backend SG**. So route 53 can't check the health of databases and because of that we can't implement a Failover record here but we will do that with the application server (backend-server).

And here we successfully completed our RDS setup. Let's go ahead and explore more services

◆ Certificate Manager


As you saw in previous screenshots, I have the domain name [ankitjodhani.club](#) in Route 53. Now I am going to use this domain name to create subdomains such as [api.ankitjodhani.club](#) and that will resolve **ALB-backend DNS**. Furthermore, we need an SSL certificate so that we can make the connection secure.

Note: we are going to create certificates in both regions us-east-1 and us-west-2.


So let's head over to ACM (AWS certificate manager). Type certificate manager in the AWS console search bar. And click on the service.



Now click on the list certificates button on the left panel and then click on the request certificate on the top right corner.



Select the option Request the public certificate and click on the next button.



In the domain name field please type ***.Your_Domain_Name.xyz** in my case it is ***.vardhan.live** DON'T DO ANY TYPO. In the validation method select DNS validation and click on the request certificate.

Provide one or more domain names for your certificate.

*.vardhan.live

[Add another name to this certificate](#)

You can add additional names to this certificate. For example, if you're requesting a certificate for "www.example.com", you might want to add the name "example.com" so that customers can reach your site by either name.

Select a method for validating domain ownership.


- ☒ **DNS validation - recommended**
Choose this option if you are authorized to modify the DNS configuration for the domains in your certificate request.
- ☐ **Email validation**
Choose this option if you do not have permission or cannot obtain permission to modify the DNS configuration for the domains in your certificate request.

Key algorithm [Info](#)

The screenshot shows the AWS IAM console 'Certificates' page. At the top, there's a message about pending validation. Below it, a table lists certificates. One certificate is highlighted with a yellow box. Annotations with yellow boxes and arrows point to various elements on the page:

- Status:** Pending validation
- Certificate ID:** b9-4c47-8f0a-95cc5374a3cf
- Certificate name:** b9-4c47-8f0a-95cc5374a3cf
- Certificate type:** User
- Certificate details:** Certificate ID, Certificate name, Certificate type, Certificate status
- Certificate status:** Pending validation
- Certificate details:** Certificate ID, Certificate name, Certificate type, Certificate status
- Certificate details:** Certificate ID, Certificate name, Certificate type, Certificate status

And in just a few minutes you will see the status issued.



Note: I created a certificate in N.virginia(us-east-1) but you need to do the same thing for the Oregon region(us-west-2).

◆ Application Load balancer(ALB) and Route 53

Now it's time to set up an Application load balancer. We need two load balancers, one point to the backend server, and another point to the frontend server.


Note: I am doing setup in N.virginia (us-east-1)but you have to do the same setup for Oregon (us-west-2) or whatever region you have chosen.

Type ec2 in the AWS console. and click on the EC2 service.



Note: before we created ALB we need to create a Target group(TG). So first we will create TG for ALB-frontend and then create TG for ALB-backend.

Click the target group button on the bottom of the left panel. And click on the create target group button in the middle of the page.



Here we can configure our TG. Select the instance in the target type. You can give any name to TG but try to give some relevant name such as **ALB-frontend-TG**

because we are creating TG for ALB-frontend. In the VPC section select VPC that we created earlier.

Basic configuration

Choose target type

- ☒ Instances
- ☐ IP addresses
- ☐ Lambda Function
- ☐ Application Load Balancer

Target group name

ALB frontend TG

VPC

my-aws-2020-07-10-123456789012-us-east-1

Protocol version

- ☒ HTTP
- ☐ HTTPS
- ☐ GREY

Health checks

Health check protocol

HTTP

Keep everything as it is, scroll down, and click on the Next button.

Advanced health check settings

Health check path

/

Health threshold

5

Timeout

10 seconds

Unhealthy threshold

3

Success ratio


2/3

Attributes


Tags - optional

Next

Click on the create target group button.



Let's create TG for **ALB-backend**. Click on the create target group button. Select the target type Instance. Again give some meaning full name such as **ALB-backend-TG**. Select VPC that we have created.



Scroll down and click on the next button.

Health check type

Healthiness threshold

Health check type

Healthiness threshold

Timeout

Interval

Success codes

Attributes

Tags - optional

Next

And click on the created target group. That's it.


Register targets

Available instances


Targets

Create target group

So we have two TG. **ALB-frontend-TG** and **ALB-backend-TG**.




Now let's associate these TG with the load balancer. So click on the Load Balancer button at the bottom of the left panel and click on the create load balancer button. First, we will create ALB for frontend.



Choose Application load balancer and click on create button.



here we can configure our ALB. First, give the relevant name to ALB such as **ALB-frontend**. Select the internet-facing option. In Network mapping select VPC that we have created. Select both availability zone **us-east-1a** and **us-east-2b**. and select subnet **pub-sub-1a** and **pub-sub-2b** respectively.



Select security group **ALB-frontend-sg**. This SG we have created for ALB-frontend. In the listener part select TG that we have just created **ALB-frontend-TG**.

Listeners and routing

Listener: HTTP 80

Protocol: HTTP Port: 80 Default action: Forward

Target group: ALB-Forward-TG


Create target group

Scroll down and click on the create load balancer button.


Summary

Create load balancer

Now, lets create ALB for backend. Again choose Application load balancer option and click on the create button.




Select Internet facing option. And select VPC that we have created.




Select both availability zone **us-east-1a** and **us-east-2b**. and select subnet **pub-sub-1a** and **pub-sub2b**. select security group **ALB-backend-sg** that we created for ALB-backend. And in the listener part select TG that we just created **ALB-backend-TG**.



Scroll down as click on the Created Load balancer button



Now we have two load balancers, **ALB-frontend** and **ALB-backend**. But we need to add one more listener in **ALB-backend**. So click on ALB-backend.



So here we successfully completed the ALB setup for the **N.virginia region (us-east-1)**, and your task is to set up the same ALB for the **Oregon region (us-west-2)**.



I hope that you completed the given task.


Same process do for frontend loadbalancer in both regions to add another listener rule that is https for security.

◆ EC2


Now we are going to create a temporary frontend and backend server to do all the required setup, take snapshots and create Machine images from it. So that we can utilize it in the launch template. It is a long process so bear with me.

Note: we are doing this setup in the us-east-1 region and we don't have to do this in the us-west-2 because we are going to leverage AWS backup service and copy it in the us-west-2 region.


First, click on the instance button and then click on the Launch Instance button on the top right corner.




First, we are going to set up a frontend server. Give a name to your instance (**temp-frontent-server**). Select Ubuntu as the operating system. Choose the instance type as t2.micro. click on Create key pair if you don't have it.



If you are creating key pair make sure you select .PEM file format as I have shown in the below image. Because we are going to use Git bash to do the login NOT putty and give any name to your key. And save it somewhere safe location on your computer.



Here we are doing a temporary setup so we don't use our OWN VPC. we can use the default VPC given by AWS. In short, keep the Network setting as it is. In the firewall setting select all the fields as I shown in the below image to keep things simple. And lastly, click on the Advance details option.



Scroll down to the bottom of the page, here we can see one text box with the name USER DATA. Here in this text box, you can write your bash script file and that will be executed during the launch of the instance. I have given the bash script below. so please copy that script and paste it here. And lastly, click on the launch instance button.

```
#!/bin/bash
```

```
sudo apt update -y
```

```
sudo apt install apache2 -y
```

```
curl -fsSL https://deb.nodesource.com/setup_18.x | sudo -E bash - &&\nsudo apt-get install -y nodejs -y
```


```
sudo apt update -y
```

```
sudo npm install -g corepack -y
```


```
corepack enable
```

```
corepack prepare yarn@stable --activate --yes
```


```
sudo yarn global add pm2
```



we have successfully launched **temp-frontend-server**. so now let's launch a temporary backend server. give a name to your instance (**temp-backend-server**). select ubuntu as the operating system. And select t2.micro as instance type. Here we don't have to create a new key, we can utilize the previous key that we have created while launching the frontend instance.



In the network setting, we don't have to change anything just select whatever I have shown below image to keep things simple. And lastly please click on the advance details option.



Scroll down to the bottom of the page, and copy the bash script that I have given below. and paste it in the USER-DATA text box. This bash scripting installs some packages so that we don't have to install them manually. And click on the launch instance.

```
#!/bin/bash
```

```
sudo apt update -y
```

```
curl -fsSL https://deb.nodesource.com/setup_18.x | sudo -E bash - &&\nsudo apt-get install -y nodejs -y
```


```
sudo apt update -y
```

```
sudo npm install -g corepack -y
```

```
corepack enable
```

```
corepack prepare yarn@stable --activate --yes
```


```
sudo yarn global add pm2
```




Please wait for 5-8 minutes so that the instance comes in a running state. and then we will utilize instances for further steps.

Select **temp-frontent-server**. and copy the IP address of the instance. Now open Gitbash where you have downloaded your YOUR_KEY.pem file. And type the command.

`ssh -i<name_of_key>.pem ubuntu@<Public_IP_add_of_Instance>`




It will prompt you for your permission just type yes




Now you are successfully logged your remote **temp-front-end-server**. now our first task is to clone my git repo.


■




Go inside the directory.
 cd /2nd10WeeksofCloudOps
 cd /client
 or
 cd 2nd10WeeksofCloudOps/client



Now, we need to change just one line in our frontend application that is built in React. So type the command
`vim src/pages/config.js`




The above command opens the file in a text editor. Now press I the button on your keyboard to edit the file. In this file, we have to change `API_BASE_URL`. So remove whatever is present in the `API_BASE_URL` variable.



And add <https://api.vardhan.live>, In my case I have added this URL but in your case it is different. This means you need to use your OWN domain name. so your API_BASE_URL should be like `https://api.<YOUR_DOMAIN_NAME>.XYZ` I hope it makes sense. After updating the variable press ESC key on your keyboard and then type :wq and hit the Enter button.

API_BASE_URL = `https://api.vardhan.live`




```
aws
Services
Search [Alt+S]
EC2 VPC S3 IAM Route 53 RDS Lambda CloudWatch Secrets Manager CloudFront Amazon Redshift

// const API_BASE_URL = "http://localhost:8800";
const API_BASE_URL = "https://api.vardhan.live";
export default API_BASE_URL;
```

After making these changes our frontend of the application will send all the API calls on the domain name <https://narni.co.in> And lastly, that will point to our backend server.


Now type the command `npm install` in the terminal to install all the required packages.

npm install




Type the command `npm run build` to create the optimize static pages.

npm run build




Now you have one more folder in the directory called build. You can verify that by typing `ls` command




Now type the very essential command `sudo cp -r build/* /var/www/html/`
`sudo cp -r build/* /var/www/html`

The above command takes all the static files from the build folder and stores them in `/var/www/html` so that Apache can serve them.



Here our temp-front-end-server configuration is completed. Now let's set up the temp-backend-server. So select the temp-backend-server and copy the IP address of the instance. Again please open Git bash in the same directory where your stored key.pem file. And type the below command
 ssh -iname_of_your_key>.pem ubuntu@<Public_IP_add>



We are successfully logged in inside the backend server. first, we will clone the repo.

■ git clone <https://github.com/CloudTechDevOps/2nd10WeeksofCloudOps-main.git>

```
aws
Services
Search
[Alt+S]
EC2 VPC S3 IAM Route 53 RDS Lambda CloudWatch Secrets Manager CloudFront Amazon Redshift Elastic Kubernetes Service CloudFormation
buntu@ip-172-20-1-141:~$
buntu@ip-172-20-1-141:~$
buntu@ip-172-20-1-141:~$
buntu@ip-172-20-1-141:~$
buntu@ip-172-20-1-141:~$ git clone https://github.com/vardhan1228/2nd10WeeksofCloudOps.git
```


go inside the 2nd10WeeksofCloudOps/backend

cd /2nd10WeeksofCloudOps

cd /backend


or

cd 2nd10WeeksofCloudOps/backend




Here we are going to create one file with the name .env

vim .env





Press the I button on your keyboard. And copy the code given below and paste the snippet into the code editor. This code contains information about the RDS instance. Please change your username and password according to whatever you kept while creating a database. And then click on the ESC button and type :wq and hit the enter button





Now type the below commands in terminal

```
npm install
npm install dotenv
```

Now, let's start the backend server. (*very IMP*)
sudo pm2 start index.js --name "backendApi"



you can verify that by typing the command


sudo pm2 list

Yeah!!! 😊 Successfully completed our backend server configuration. You can close the terminal


But before we end this section we need to do a few more steps. We have to create Machine images of these servers so that we can create a launch template. *these steps are optional because anyhow we will take a backup from the AWS backup*

service and that will do the same thing. but that takes time. so it would be better if you follow the steps.

So please select temp-frontend-server and click on the Action button in the top right corner. One drop-down menu will open. You have to select the images and template option and that will give one more drop-down menu from which we need to click on create image button.



Give the name you your image (**img-frontend-server**). just deselect that delete on the termination button and click on the create image button.



You have to do the same thing for the temp-backend-server as well. I have shown you each and every step in the below images.





After a couple of minutes (10-15) you can see those images. Click on the AMIs button on the left panel and you can see both images here.




Note: Again we did the above setup in us-east-1 and we don't have to do this setup for us-west-2 we will leverage aws backup service or copy ami from one region to another region to copy these machine images in us-west-2.


◆ Launch Template

Take note that we need to create a launch template in both regions primary and disaster recovery (secondary) **us-east-1** and **us-west-2**. And now we have machine images in both regions.

First I will create a launch template in **N.virginia (us-east-1)**. So click on the launch template button on the left panel and click on the create launch template button.



Give the name to your launch template such as template-frontend-server as we are creating a launch template for frontend-server. let's give the version 1 in the version field. Here we need to select AMI so click on My AMIs tab and select the option owned by me. So now it will show you all the images that are present in your current region. If you are following the blog from starting then you will have a total of 4 images in **N.virginia**. coz two we created manually and two were created by backup service. Here you have to select the image that contains the frontend application. Either you can select the manual or the one created by the backup service. both are okay coz it contains the same data. Select instance type t2.micro



Scroll down, attach the key pair, and in the network setting just select the security group that we created for the frontend server. in my case the name **SG is frontend-sg**. And click on the advance details section at the bottom of the page.

we successfully created a launch template for the frontend-server. now let's create a launch template for the backend server.

Give a name to your launch template (template-backend-server). Give version 1 in the version field, but make you select the correct AMI that holding your backend application. And Select an instance type t2.micro

Launch template name:

Version:

Amazon Machine Image (AMI):

Instance type:

Storage: Standard

Summary

Template name: template-backend-server

Version: 1

Amazon Machine Image (AMI): ami-0a4b73a5d9a2d02

Instance type: t2.micro

Storage: Standard

Warning: You have selected a template that is not a valid launch template. Please check the template name and version.

Select the key pair, and in the network setting just select the security group that we have created for the backend server. in my case name of the SG is **backend-sg**. And click on the advance details section at the bottom.

Key pair (login):

Network settings:

Security group:

Storage (volumes):

Resource tags:

Advanced details:

Summary

Template name: template-backend-server

Version: 1

Amazon Machine Image (AMI): ami-0a4b73a5d9a2d02

Instance type: t2.micro

Storage: Standard

Warning: You have selected a template that is not a valid launch template. Please check the template name and version.

Scroll down to the bottom, and in the USER-DATA text box paste the code that I have given below. And then click on the Create launch template button.

```
#!/bin/bash
```

```
sudo apt update -y
```


```
sleep 150
```

```
sudo pm2 startup
```

```
sudo env PATH=$PATH:/usr/bin /usr/local/share/.config/yarn/global/node_modules/pm2/bin/pm2 startup  
systemd -u ubuntu --hp /home/ubuntu
```

```
sudo systemctl start pm2-root
```

```
sudo systemctl enable pm2-root
```



We have created two launch templates, template-frontend-server and template-backend-server in **N.virginia**.

Note: Your task is to set up two launch templates in the **Oregon** region (disaster recovery region). Everything is completely similar just you have to change AMIs. Please select the correct AMI for the frontend and backend. If you have difficulties finding AMIs you can compare the instance_id with temp-frontend-server and temp-backend-server. this will definitely help you.

I hope you did the task, Now we can terminate those temp-servers to save the bills.


◆ Auto scaling group (ASG)

The auto-scaling group is the functionality of EC2 service that launches instances depending on your network traffic or CPU utilization or parameter that you set. It launches instances from the launch template.


Note: we need to set up an Auto Scaling group in both regions **us-east-1 (N.virginia)**

and **us-west-2 (Oregon, Disaster recovery region)**. First, we are going to set up ASG in **us-east-1**.

Click on the Auto scaling groups button which is located at the bottom of the left panel. And then click on the Create auto scaling group button.



Give a name to your ASG. E.g ASG-frontend . And select the launch template that we have created for frontend (e.g template-frontend-server) in the launch template field. And click on the next button.



In the network field, you have to choose VPC that we created earlier. And in AZs and subnet field choose pri-sub-3a and pri-sub-4b. these subnets we have created for frontend servers. And click on the next button.

Choose instance launch options

For more information, see [AWS Auto Scaling documentation](#).

Network

For most applications, you can use multiple Availability Zones and an Elastic Load Balancing load balancer to distribute your instances across the region. The default VPC and default subnets are available for use in most regions.

VPC: **vpc-1a234567890123456789012345678901**

Availability Zones and subnets: **us-east-1a** **us-east-1b**

Instance type requirements

| Instance type | Version | Description |
|---------------|---------|-------------|
| t2.micro | Default | Default |

Next

On this page we need to attach ASG with ALB so select the Attach existing ALB option and select TG that we have created for frontend e.g ALB-frontend-TG. And then scroll down and click on the NEXT button

Load balancing

Use the options below to attach your Auto Scaling group to an existing load balancer, or to create a new load balancer.

☐ Create a new load balancer

☒ Attach to an existing load balancer

☐ Attach to an existing load balancer

Attach to an existing load balancer

Select the load balancer that you want to attach to your Auto Scaling group.

Attach to an existing load balancer

Select load balancer: **alb-1a234567890123456789012345678901**

Next

Here you can set the capacity and scaling policy but I'm keeping 1,1,1 to save cost but in real projects, it depends on the traffic. Click on the NEXT->next->next-> and create ASG button.

Configure Auto Scaling group - optional [View](#)

Set the desired minimum and maximum capacity of your Auto Scaling group. You can optionally add a scaling policy to dynamically scale the number of instances in the group.

Group size - optional [View](#)

Specify the size of the Auto Scaling group by changing the desired capacity. You can also specify minimum and maximum capacity limits. Note desired capacity must be within the link range.

Desired capacity
1

Minimum capacity
1

Maximum capacity
1

Scaling policies - optional

Choose whether to use a scaling policy to dynamically adjust your Auto Scaling group to meet changes in demand. [View](#)

☐ Target tracking scaling policy
Choose a target tracking policy to use for this scaling policy to add and remove capacity as needed to achieve your objective.

☒ None

Instance scale-in protection - optional

Instance scale-in protection
Protection scale-in protection prevents your instances from being terminated from outside by default.

☐ Enable instance scale-in protection

Cancel Skip to review Previous **Next**

1. choose

2. click next review create ASG

Let's set up ASG for the backend.

2. click

Give a name to your ASG. E.g ASG-backend. And select the launch template that we have created for the backend (e.g.template-backend-server) in the launch template field. And click on the next button.

The screenshot shows the AWS Management Console interface for creating an Auto Scaling group. The page is titled "Choose launch template or configuration" and includes a sidebar with navigation options like "Name", "Launch template", "Launch configuration", "Launch profile", "Launch policy", "Launch permissions", "Launch logs", "Next", and "Review". The main content area has two tabs: "Launch template" (selected) and "Switch to launch configurations". Under the "Launch template" tab, there is a section for "Launch template" with a dropdown menu showing "Default (Amazon Linux 2)". A yellow box highlights this section, and a yellow arrow points to it with the text "1. select". Below this, there is a "Next" button at the bottom right, which is also highlighted with a yellow box and a yellow arrow pointing to it with the text "2. click".

In the network field, you have to choose VPC that we created earlier. And in AZ and subnet field choose pri-sub-5a and pri-sub-6b. these subnets we have created for backend servers. And click on the next button.

Choose Instance Launch Options

Choose the VPC, network Availability Zones, and subnets that you want to use for your Amazon EC2 instances, and customize the instance type and platform details.

Network

For most applications, you can use multiple Availability Zones and an Amazon EC2 instance to spread your instances across the zone. The default VPC and default subnets are available for getting started quickly.

Choose the VPC that defines the virtual address space for your Amazon EC2 instances.

Availability Zones and subnets

Amazon EC2 instances are distributed across multiple Availability Zones for high availability. Choose the Availability Zones and subnets that you want to use for your Amazon EC2 instances.

Instance type requirements

Choose the instance type and platform details that you want to use for your Amazon EC2 instances.

Launch template: t3.xlarge (Amazon EC2)

Instance type: t3.xlarge

Control Skip to review Previous **Next**

On this page we need to attach ASG with ALB so select the Attach existing ALB option and select TG that we have created for the backend e.g ALB-backend-TG. And then scroll down and click on the NEXT button.

Load balancing

Use the options below to attach your Auto Scaling group to an existing load balancer, or to a new load balancer that you create.

☐ Create a new load balancer

☒ Attach to an existing load balancer

☐ Attach to a Classic Load Balancer

Attach to an existing load balancer

Select the load balancer that you want to attach to your Auto Scaling group.

Existing load balancer target group

Only one target group can be attached to a load balancer. Choose the target group that you want to attach to your Auto Scaling group.

VPC Lattice integration options

To improve network performance and scalability, integrate your Auto Scaling group with VPC Lattice. VPC Lattice provides a managed service for connecting microservices across Availability Zones and regions.

Health checks


Health checks monitor the health of your instances. When you use multiple health checks, all are used until all are successful. If any are unsuccessful, the instance is marked as unhealthy.

EC2 health checks

Amazon EC2 health checks monitor the health of your instances. When you use multiple health checks, all are used until all are successful. If any are unsuccessful, the instance is marked as unhealthy.

Next

Here you can set the capacity and scaling policy but I'm keeping 1,1,1 to save cost but in real projects, it depends on the traffic. Click on the NEXT->next->next-> and create ASG button.



Now, We have two ASGs, ASG-frontend will launch frontend servers and ASG-backend will launch backend servers. we have successfully set up ASG in the **N.virginia region** and we need to do the same setup in the **Oregon region (Disaster recovery region)**.

So your task is to set up ASGs in the **Oregon region (Disaster recovery region)**.

I hope you successfully completed the given task.


Now before we go further one more thing we need to do. We need to initialize our database and need to create some tables. But we can't access the RDS instance or backend server directly coz they are in a private subnet and the security group won't let us login into it. So we need to launch an instance in the same VPC but in the public subnet that instance is called bastion host or jump-server. And through that instance, we will log in to the backend server, and from the backend server we will initialize our database.

Now before we go further one more thing we need to do. We need to initialize our database and need to create some tables. But we can't access the RDS instance or backend server directly coz they are in a private subnet and the security group won't let us login into it. So we need to launch an instance in the same VPC but in the public subnet that instance is called bastion host or jump-server. And through that instance, we will log in to the backend server, and from the backend server we will initialize our database.


Click on the instance button on the left panel and click on the launch instance button in the top right corner. *Please terminate those **temp-servers** if you haven't*



Give a name to the instance (bastion-jump-server). Select Ubuntu as OS, instance type t2.micro, and select Key pair. In all the instance and launch template we have used only **one key** so it will be easy to login in any instance. And then click on the Edit button of the Network setting.




In the network setting select VPC that we have created and in the subnet select pub-sub-1a, you can select any public subnet from the VPC. and then select security group. We already have a security group with the name bastion-jump-server-sg and click on the launch instance.




Once the instance becomes healthy, we can SSH into it. so select the instance and copy its public IP. Open Git bash or terminal in which folder your key.pem file is present and hit the below command.

```
scp -i<name_of_your_key>.pem<name_of_your_key>.pem
ubuntu@<Public_IP_add_of_instance>:/home/ubuntu/key.pem
```



The above command will copy our login secret key file into the bastion host. Now type the below command to login into the Bastion host. And copy the public IP of the Bastion host.

```
ssh -i<name_of_your_key>.pem ubuntu@<Public_IP_add_of_instance>
```



We are successfully logged in inside the bastion host.




Hit the below command to change the permission of the key.pem file
 chmod 400 key.pem



Now we want login into the backend server so select backend server and copy its private IP address. You can identify the backend server by the security group attached to the instance.

Type the below command to log in to the backend server.

ssh -ikey.pem ubuntu@<Private_IP_add_backend_server>



Now we are logged in inside the backend server it mens auto scaling server backend instance. just go into 2nd10WeeksofCloudOps/backend directory
`cd 2nd10WeeksofCloudOps/backend`



We need to install one package type below the command
`sudo apt install mysql-server -y`



And type the below command to initialize the database.

`mysql -h book.rds.com -u <user_name_of_rds> -p<password_of_rds> test <test.sql`

if above one not work

connctet to your database by using

`mysql -h book.rds.com -u <user_name_of_rds> -p<password_of_rds>`


`mysql -h book.rds.com -u admin -psrivardhan ---- this is my url`

create database test;

exit

agin giver first command in project backend directory.

`mysql -h book.rds.com -u <user_name_of_rds> -p<password_of_rds> test <test.sql`



Now you can close the terminal.


◆ Route 53

Amazon Route 53 is a highly available and scalable Domain Name System (DNS) web service.


If you try to access the web app using ALB-frontendDNS then you won't see the website in functional mode because our frontend or loaded static pages try to call the API from your browser on the domain name `https://api.<Your_Domain_name>.xyz`
In my case, <https://api.vardhan.live> And that record we didn't add yet in our domain name. so let's do that.

We are going to set up a Health check in route 53. So route 53 checks the health of the backend servers and if it is unhealthy (hits by disaster) then it will transfer the traffic to another region's (**disaster recovery region, Oregon**) backend server.


Head over to route 53 service. And click on the health check button on the left panel.



Click on the create health check button.



On this page, we can configure our Health check. Give a name to your health check, and select the endpoint to monitor it. select HTTP and in the Domain name field give the DNS of the ALB-backend which is in US-EAST-1 because **us-east-1 is our primary region**. And fill in all the details as I have shown you in the below image. And then click on the next button.




Our health check is set up successfully. it takes a few minutes to show whether our specified resource is healthy or not.



In the next few minutes, it starts showing you the health of the ALB-backend (backend-servers).



Now let's create a record in our domain name. click on the hosted zone and select your public hosted zone or your domain. I already have one. And click on the Create record button in the top right corner.



Select failover record. And click on the next button.

Here in the record name field write api so that our record name becomes api.<Your_Domain_name>.xyz in my case, it is api.vardhan.live . in the record type field select “A” and then click on the define failover record button.

Record name [Info](#) .vardhan.live

Record type [Info](#) A - Routes traffic to an IPv4 address and some AWS resources

Keep blank to create a record for the root domain.

☒ Alias

Route traffic to [Info](#)

Alias to Application and Classic Load Balancer

US East (N. Virginia)

×

Use: "dualstack.ALB-backend-579315607.us-east-1.elb.amazonaws.com"

[dualstack.ALB-backend-579315607.us-east-1.elb.amazonaws.com](#)

dualstack.ALB-frontend-1428066899.us-east-1.elb.amazonaws.com

one failover record of each type:

Primary

Health check ID [Info](#) × ↺

Evaluate target health ☒ Yes

Record ID [Info](#)

Firstly Select Alias to application and classic Load balancer from the drop-down list, secondly, select us-east-1 as a region. And in the below drop-down list select DNS of the ALB-backend. As you know that **us-east-1 is our primary region** so select primary in failover type. And in the health check ID select the health check that we have created just now. And click on the Define failover record button. Follow the below image for more clarity.

Record name [Info](#) .vardhan.live

Record type [Info](#) A - Routes traffic to an IPv4 address and some AWS resources

Keep blank to create a record for the root domain.

☒ Alias

Route traffic to [Info](#)

Alias to Application and Classic Load Balancer

US East (N. Virginia)

×

Use: "dualstack.ALB-backend-579315607.us-east-1.elb.amazonaws.com"

[dualstack.ALB-backend-579315607.us-east-1.elb.amazonaws.com](#)

dualstack.ALB-frontend-1428066899.us-east-1.elb.amazonaws.com

one failover record of each type:

Primary

Health check ID [Info](#) × ↺

Evaluate target health ☒ Yes

Record ID [Info](#)

Click on create record button.

Now we need to set up one more failover record with the same domain name but for a secondary region. Firstly Select Alias to application and classic Load balancer from the drop-down list, secondly, select us-west-2 as the region. And in the below drop-down list select the DNS of the ALB-backend. As you know that **us-west-2 is our secondary region** so select secondary in failover type. **Make sure you don't select**

anything in health check ID. And click on the Define failover record button. Follow the below image for more clarity. For second region

Record name: rdl .wardhan.live

Record type: A - Routes traffic to an IPv4 address and some AWS resources

Route traffic to: Alias to Application and Classic Load Balancer

US West (Oregon)

Q: dualstack.alb-backend-1061937887.us-west-2.elb.amazonaws.com

Routing policy: Failover

Failover record type: Secondary

Health check ID - optional: Choose health check

Record ID: US West load balancer

don't select any keep empty for second region

So we have two failover type records with same name but one is pointing to the backend load balancer which is in **us-east-1 region** and the second one is pointing to the backend load balancer of the **secondary region Oregon(us-west-2)**.

| Record name | Record type | Routing policy | Failover record type | Health check ID | Record ID |
|-------------|-------------|----------------|----------------------|-----------------|-------------------------|
| rdl | A | Failover | Primary | | us-east-1 load balancer |
| rdl | A | Failover | Secondary | | us-west-2 load balancer |

Now it's time to access our website so take the DNS of the **frontend load balancer** (ALB-frontend) and paste it into the browser. I am sure that you will see the website in fully functional mode. You can add and remove books.

aws&devops by VEERA nareshit

Gamer of throne

Fire folks

this is an amazing book to read when you are free

fire folks is ming blowing book to read it will blow your mind

\$2343.2

\$2342.3

Delete


Update

But there are some more improvements that we can do. So let's see those.

◆ CloudFront

AWS CloudFront is a CDN service provided and fully managed by AWS. By utilizing CloudFront we can do the caching of our website at every edge location of the world. The user of the website faces less latency and gets high performance.


let's create Cloudfront distribution for our website. Head over to CloudFront.




Click on the distribution button on the left panel and then click on the create distribution button on top right corner.



In the origin name field select ALB-frontend (**us-east-1 primary region**). Select Match Viewer in the protocol field. And scroll down



In viewer policy select Redirect **HTTP to HTTPS** and allow all the methods. But please make sure that you select CachingDisabled and in cache policy and select AllViewer in origin request policy.



Click on the add item button and add an alternative domain name (frontend.vardhan.live) and select the certificate that we have created in the Custom SSL certificate field.

☐ Enable security protections

Keep your application secure from the most common web threats and security vulnerabilities using AWS WAF. Blocked requests are stopped before they reach your web servers.

☒ Do not enable security protections

Select this option if your application does not need security protections from AWS WAF.

Settings

Price class [Info](#)

Choose the price class associated with the maximum price that you want to pay.

- ☒ Use all edge locations (best performance)
- ☐ Use only North America and Europe
- ☐ Use North America, Europe, Asia, Middle East, and Africa

Alternate domain name (CNAME) - *optional*

Add the custom domain names that you use in URLs for the files served by this distribution.

To add a list of alternative domain names, use the [bulk editor](#).

Scroll down and click button create distribution.

Add the custom domain names that you use in URLs for the files served by this distribution.

frontend.vardhan.live

Remove

Add item

i To add a list of alternative domain names, use the [bulk editor](#).

Custom SSL certificate - *optional*

Associate a certificate from AWS Certificate Manager. The certificate must be in the US East (N. Virginia) Region (us-east-1).

*.vardhan.live (66cd563a-3e6a-4254-8f50-3db5b1a836d1) ▼



✓ *.vardhan.live [Request certificate](#)

Legacy clients support - \$600/month prorated charge applies. Most customers do not need this.
CloudFront allocates dedicated IP addresses at each CloudFront edge location to serve your content over HTTPS.

☐ Enabled

Security policy

The security policy determines the SSL or TLS protocol and the specific ciphers that CloudFront uses for HTTPS connections with viewers (clients).

☒ TLSv1.2_2021 (recommended)

☐ TLSv1.2_2019

☐ TLSv1.2_2018

☐ TLSv1.1_2016

☐ TLSv1_2016

☐ TLSv1

Supported HTTP versions

Add support for additional HTTP versions. HTTP/1.0 and HTTP/1.1 are supported by default.

☒ HTTP/2

☐ HTTP/3

Default root object - *optional*

The object (file name) to return when a viewer requests the root URL (/) instead of a specific object.

Standard logging

Get logs of viewer requests delivered to an Amazon S3 bucket.

☒ Off

☐ On

IPv6

☐ Off


☒ On

Description - *optional*


Cancel

Create distribution

Now, click on the distribution that we have created just now and click on the Origin tab. Here you need to select create origin the button in the top right corner.




Click on the origin domain field and select the ALB-frontend(**us-west-2 secondary region**), select math view in protocol and the rest of the parameters are all the same so click on the create origin button.



So now we have two Origins one is points to ALB-frontend which is in us-east-1 and the second one is pointing to ALB-frontend which is in the secondary region Oregon (us-west-2). Now click on the create origin group button.



Here, In the Origins field select the first origin that is associated with us-east-1 and click on the add button. And again click on the origin field and select the origin that is associated with us-west-2 and click on the add button. Give any name to the origin group (frontend_failover_handler) and select all the failover criteria as I have shown in the below image. Hit the button created origin group.




Now, click on the behavior tab. And select the behavior and click on the edit button.




Here we need to change the origin and origin group. Select the origin group that we have just created (frontend_failover_handler). Scroll down and click on the save button.



We need to wait till the distribution become available. It takes around 5-8 minutes. And then we can access our website through the DNS name generated by CloudFront. But we want to access the web app custom domain name. so again head over to Route 53 and select your public hosted zone. or your domain name hosted zone. and click on create record button.



Select simple record, and click on the button defined record. In the record name, add name threetier so our domain name becomes threetier.<Your_Domain_name>.XYZ, in my case, it is threetier.ankitjodhani.club. Select record type "A". Select Alias to CloudFront distribution from the drop-down list in value/route traffic to field. And select the distribution that we have created just now. Lastly, hit the define simple record button. Route 53 takes sometime around 5-10 minutes to route traffic on the newly created record so please wait.



Now, let's check the final endpoint. Please hit the record name that you have set up. In my case that is <https://frontend.vardhan.live>. I am sure you can see the website in running state. We are almost done before we taste our application one small service but very essential service we want to utilize and that is WAF.


◆ AWS WAF (Web application firewall)

AWS WAF is a web application firewall that helps protect apps and APIs against bots and exploits that consume resources.


Search WAF in the AWS console, and click on the service.




Click on the Web ACLs on the left panel and then click the button which is in the middle Create Web ACL.




Give some meaning full name to the ACL list, in resource type select the AWS CloudFront distribution. And then click on the Add AWS resource button and add the CloudFront distribution that we have just created.




Here, hit the add rule button on top and click Add manage rule group.




Over here we can add the rules to protect our web app front attackers. You can read the description and add the rules that suit your application security. Scroll down and save it.





Select default action Allow and hit the next button and that's it. we secured web application. You can see Web ACLs in the list.




□ Testing


It's time to test our architecture. Let's see if it works as we expected. **Can we call it Resilient architecture? Did we implement the Warm Standby strategy properly?**

We are going to do manual failover by changing the rules of the security group of the ALB-frontend and ALB-backend. To make our frontend server and backend server inaccessible from the internet in **US-EAST-1 region**. So we can create a situation like a disaster.


First let's do a modification in ALB-frontend-sg.




Select ALB-frontend-sg. Click on the edit inbound rule. And remove all the HTTP and HTTPS rules from it. after doing this our CloudFront distribution won't be able to access this **ALB-frontend** and it have to route traffic to another region (**us-west-2**)ALB-frontend.



let's do a modification in ALB-backend-sg.




Select ALB-backend-sg. Click on the edit inbound rule. And remove all the HTTP and HTTPS rules from it. after doing this route 53 will find it unhealthy and it have to route traffic to another region (us-west-2) ALB-backend.



So let's see if CloudFront and Route 53 are routing traffic to a secondary region's server. Take the domain name and try pasting it into the browser.


If we can see the website in fully functional mode, it means we have properly set up and configured our architecture.

Note: Please wait for at least 10 minutes so that Route 53 can identify the unhealthy resource. CloudFront takes 60 to 90 seconds for every request to route traffic. So, please don't drop the website immediately.




Yeahhh!! 🐼 We Did it.

Our architecture working as we designed. But you can see that you can't add a book here. And it is because of read-replica. Read replica allows only read-only operation. We need to promote read-replica which is in the DR **region(us-west-2)**. so that it becomes a database instance. And that allow read and write both operation.




I know it is taking a long time to open the website. But we can improve that by changing some configurations in CloudFront. Click on the origin tab. Select the first origin and click on the edit button.



Click on the additional settings tab. And decrease the number. So that CloudFront won't wait too long for a response.



Now, if you try again you will feel very less latency compared to the previous one.



□ Resource cleanup

◆ CloudFront

- disabled (takes a lot of time)
- delete

◆ RDS

- RDS instance or read replica delete in both regions (takes a lot of time)
- snapshot

◆ Route 53

- Delete both private hosted zone (rds.com)
- Delete all three records in the public hosted zone

◆ EC2

- Delete ASG in both regions
- Terminate Bastion host from us-east-1
- Delete ALB in both regions
- Delete TG from both regions
- Delete the Launch template from both regions
- Deregister AMIs which are created manually

◆ ACM

- Delete the certificate if you don't need it

◆ Backup services

- Delete resources from the backup vault in both regions
- Delete backup vault from N.virginia
- Delete Assign resources in the backup plan
- Delete backup plan

◆ VPC

- Delete NAT gateways from both regions (takes around 5 minutes)

- Release the Elastic IP
- Delete VPC in both regions (17 resources will be deleted on one click)

◆ WAF

- Remove Web ACLs from WAF

□ Conclusion

In conclusion, the three-tier architecture implemented in our system ensures robustness and resiliency in the face of disasters or regional failures. With Route 53 and CloudFront handling DNS routing and failover mechanisms, our system can seamlessly switch to a secondary region, guaranteeing uninterrupted website availability. The use of Application Load Balancers and the RDS database further enhances scalability and reliability in processing user requests and storing data.