

Introduction

console.log()

The `console.log()` method is used to log or print messages to the console. It can also be used to print objects and other info.

```
console.log('Hi there!');  
// Prints: Hi there!
```

JavaScript

JavaScript is a programming language that powers the dynamic behavior on most websites. Alongside HTML and CSS, it is a core technology that makes the web run.

Methods

Methods return information about an object, and are called by appending an instance with a period `.`, the method name, and parentheses.

```
// Returns a number between 0 and 1  
Math.random();
```

Libraries

Libraries contain methods that can be called by appending the library name with a period `.`, the method name, and a set of parentheses.

```
Math.random();  
// 🙌 Math is the library
```

Numbers

Numbers are a primitive data type. They include the set of all integers and floating point numbers.

```
let amount = 6;  
let price = 4.99;
```

String .length

The `.length` property of a string returns the number of characters that make up the string.

```
let message = 'good nite';  
console.log(message.length);  
// Prints: 9  
  
console.log('howdy'.length);  
// Prints: 5
```

Data Instances

When a new piece of data is introduced into a JavaScript program, the program keeps track of it in an instance of that data type. An instance is an individual case of a data type.

Booleans

Booleans are a primitive data type. They can be either `true` or `false`.

Math.random()

The `Math.random()` function returns a floating-point, random number in the range from 0 (inclusive) up to but not including 1.

Math.floor()

The `Math.floor()` function returns the largest integer less than or equal to the given number.

Single Line Comments

In JavaScript, single-line comments are created with two consecutive forward slashes `//`.

Null

Null is a primitive data type. It represents the intentional absence of value. In code, it is represented as `null`.

Strings

Strings are a primitive data type. They are any grouping of characters (letters, spaces, numbers, or symbols) surrounded by single quotes `'` or double quotes `"`.

Arithmetic Operators

JavaScript supports arithmetic operators for:

- `+` addition
- `-` subtraction
- `*` multiplication
- `/` division
- `%` modulo

```
let lateToWork = true;
```

```
console.log(Math.random());  
// Prints: 0 - 0.9
```

```
console.log(Math.floor(5.95));  
// Prints: 5
```

```
// This line will denote a comment
```

```
let x = null;
```

```
let single = 'Wheres my bandit hat?';  
let double = "Wheres my bandit hat?";
```

```
// Addition  
5 + 5  
// Subtraction  
10 - 5  
// Multiplication  
5 * 10  
// Division  
10 / 5  
// Modulo  
10 % 5
```

Multi-line Comments

In JavaScript, multi-line comments are created by surrounding the lines with `/*` at the beginning and `*/` at the end. Comments are good ways for a variety of reasons like explaining a code block or indicating some hints, etc.

```
/*
The below configuration must be
changed before deployment.
*/

let baseUrl =
'localhost/taxwebapp/country';
```

Assignment Operators

An assignment operator assigns a value to its left operand based on the value of its right operand. Here are some of them:

- `+=` addition assignment
- `-=` subtraction assignment
- `*=` multiplication assignment
- `/=` division assignment

```
let number = 100;

// Both statements will add 10
number = number + 10;
number += 10;

console.log(number);
// Prints: 120
```

String Interpolation

String interpolation is the process of evaluating string literals containing one or more placeholders (expressions, variables, etc).

It can be performed using template literals: `text` `${expression}` `text`.

```
let age = 7;

// String concatenation
'Tommy is ' + age + ' years old.';

// String interpolation
`Tommy is ${age} years old.`;
```

Variables

Variables are used whenever there's a need to store a piece of data. A variable contains data that can be used in the program elsewhere. Using variables also ensures code re-usability since it can be used to replace the same value in multiple places.

```
const currency = '$';
let userIncome = 85000;

console.log(currency + userIncome + '
is more than the average income.');
```

// Prints: \$85000 is more than the average income.

Undefined

`undefined` is a primitive JavaScript value that represents lack of defined value. Variables that are declared but not initialized to a value will have the value `undefined`.

```
var a;

console.log(a);
// Prints: undefined
```

Declaring Variables

To declare a variable in JavaScript, any of these three keywords can be used along with a variable name:

- **var** is used in pre-ES6 versions of JavaScript.
- **let** is the preferred way to declare a variable when it can be reassigned.
- **const** is the preferred way to declare a variable with a constant value.

```
var age;  
let weight;  
const numberOfFingers = 20;
```

Template Literals

Template literals are strings that allow embedded expressions, `${expression}`. While regular strings use single `'` or double `"` quotes, template literals use backticks instead.

```
let name = "Codecademy";  
console.log(`Hello, ${name}`);  
// Prints: Hello, Codecademy  
  
console.log(`Billy is ${6+8} years  
old.`)  
// Prints: Billy is 14 years old.
```

let Keyword

let creates a local variable in JavaScript & can be re-assigned. Initialization during the declaration of a **let** variable is optional. A **let** variable will contain **undefined** if nothing is assigned to it.

```
let count;  
console.log(count); // Prints:  
undefined  
count = 10;  
console.log(count); // Prints: 10
```

const Keyword

A constant variable can be declared using the keyword **const**. It must have an assignment. Any attempt of re-assigning a **const** variable will result in JavaScript runtime error.

```
const numberOfColumns = 4;  
numberOfColumns = 8;  
// TypeError: Assignment to constant  
variable.
```

String Concatenation

In JavaScript, multiple strings can be concatenated together using the `+` operator. In the example, multiple strings and variables containing string values have been concatenated. After execution of the code block, the **displayText** variable will contain the concatenated string.

```
let service = 'credit card';  
let month = 'May 30th';  
let displayText = 'Your ' + service  
+ ' bill is due on ' + month + '.';  
  
console.log(displayText);  
// Prints: Your credit card bill is  
due on May 30th.
```