

Branch : CSE & IT

Programming in C Recursion -2

DPP-04
[NAT]

1. Consider the following function:

```
int func(int a)
{
    static int b=1;
    b=b+a;
    if((b%a)%2!=0) return a+func(b+a);
    return b-a;
}
```

The value returned by func(5) is _____.

[MCQ]

2. Consider the following function:

```
void func(int n)
{
    if(n>0){
        func(n-1);
        printf("%d\t", n);
    }
    printf("%d\t", n-1);
}
```

The output printed by func(2) is-

- (a) -1 1 0 2 1 (b) -1 1 0 2 1 2
(c) -1 1 0 2 -2 1 (d) -1 1 0 2 1

[NAT]

3. Consider the following function:

```
int func(int n)
{
    if(n>0){
        return func(n/2)+func(n/4)+1;
    }
    return n+1;
}
```

The value returned by func(6) is _____

[NAT]

4. Consider the following function:

```
int func(int n)
{
    if(n>0){
        return 3*func(n/4)+1;
    }
    return n;
}
```

The value returned by func(24) is _____.

[NAT]

5. Consider the following function:

```
int func(int n)
{
    static int k=0;
    if(n>0){
        k++;
        return 2*func(n/2)+k;
    }
    return n+k--;
}
```

The value returned by func(8) is _____.

[MCQ]

6. Consider the following function:

```
int func(int n, int i)
{
    if(n==0) return 0;
    else if(n%2){
        return func(n/2, 2*i)+i;
    }else return func(n/2, 2*i)-i;
}
```

The value returned by func(14, 1) is-

- (a) 1 (b) 13
(c) 15 (d) 0

[MCQ]

7. Consider the following function:

```
int func(int n)
{
    static int i=0;
    if(n/2){
        i--;
        return func(n/2)+i;
    }else return i;
}
```

The value returned by func(7) is-

- (a) -6
- (b) -12
- (c) -18
- (d) -21

[MCQ]

8. Consider the following function:

```
void display()
{
    static int i;
    if(i<=printf("GATE24")){
        i=i+2;
        display();
    }
}

int main()
{
    int i=0;
    for(i=0;i<3;i++)
        display();
    return 0;
}
```

The number of times printf() executed is-

- (a) 6
- (b) 5
- (c) 7
- (d) 9

Answer Key

1. (11)
2. (d)
3. (9)
4. (13)

5. (109)
6. (b)
7. (a)
8. (c)



Hints and Solutions

1. (11)

```
func(5):
    static int b=1; //static b is initialized to 1.
    b=b+a; //b=1+5=6
    if((b%a)%2!=0) //(6%5)%2!=0 is TRUE
    Line 1: return a+func(b+a); // return 5+func(6+5);
    func(11) is called. Returns 5+6 i.e 11.
    Line 2: return b-a;

func(11):
    static int b=1; //static b is initialized to 1.
    b=b+a; //b=6+11=17
    if((b%a)%2!=0) //(17%11)%2!=0 is FALSE
    Line 1: return a+func(b+a);
    Line 2: return b-a; // return (17-11) i.e 6 to Line 1
    of func(5);
```

2. (d)

```
func(2):
    2>0 True
    func(1) is called.
    printf("%d\t", n); // 2 is printed.
    printf("%d\t", n-1); //1 is printed.
```

```
func(1):
    1>0 True
    func(0) is called.
    printf("%d\t", n); // 1 is printed.
    printf("%d\t", n-1); //0 is printed.
```

```
func(0):
    0>0 is FALSE
    printf("%d\t", n-1); //-1 is printed.
    Output: -1 1 0 2 1
```

3. (9)

```
func(6):
    if(n>0){ //6>0 is TRUE
    1. return func(n/2)+func(n/4)+1; //return
    func(3)+func(1)+1; return 5+3+1=9;
    }
```

```
func(3):
    if(n>0){ //3>0 is TRUE
    1. return func(n/2)+func(n/4)+1; //return
    func(1)+func(0)+1; return 3+1+1=5;
    }
```

```
func(1):
    if(n>0){ //3>0 is TRUE
    1. return func(n/2)+func(n/4)+1; //return
    func(0)+func(0)+1; //return 3;
    }
```

```
func(0):
    return 1;
```

4. (13)

```
func(24):
    if(n>0){ //24>0 is TRUE
    return 3*func(n/4)+1; //func(6) is called.
    Returns 3*4+1; Returns 13.
    }
```

```
func(6):
    if(n>0){ //6>0 is TRUE
    return 3*func(n/4)+1; //func(1) is called.
    Returns 3*1+1; returns 4;
    }
```

```
func(1):
    if(n>0){ //1>0 is TRUE
    return 3*func(n/4)+1; //func(0) is called.
    Returns 1;
    }
```

```
func(0):
    return 0;
```

5. (109)

```
func(8):
    static int k=0;
    if(n>0){//8>0 is TRUE
        k++; //static k is incremented to 1.
        return 2*func(n/2)+k;//func(4) is called.
        Returns (2*53+3) i.e 109
    }
```

```
func(4):
    static int k=0;
    if(n>0){//4>0 is TRUE
        k++; //static k is incremented to 2.
        return 2*func(n/2)+k;//func(2) is called.
        Returns (2*25+3) i.e 53
    }
```

```
func(2):
    static int k=0;
    if(n>0){//2>0 is TRUE
        k++; //static k is incremented to 3.
        return 2*func(n/2)+k;//func(1) is called.
        Returns (2*11+3) i.e 25
    }
```

```
func(1):
    static int k=0;
    if(n>0){//1>0 is TRUE
        k++; //static k is incremented to 4.
        return 2*func(n/2)+k;//func(0) is called.
        Returns(2*4+3) i.e 11
    }
```

f(0) returns (0+4). Static k is decremented to 3.

6. (b)

```
func(14, 1):
    14%2 is 0, so else part is executed.
    return func(7, 2)-1;// Returns 14-1 i.e 13.
```

```
func(7,2):
    7%2 is 1, so else if part is executed.
    return func(3, 4)+2; //Returns 12+2 i.e 14 to
    func(14, 1)
```

```
func(3,4):
    3%2 is 1, so else if part is executed.
    return func(1, 8)+4; //Returns 8+4 i.e 12 to func(7, 2)
```

```
func(1,8):
    1%2 is 1, so else if part is executed.
    return func(0, 16)+8; //fun(0,16) returns 0
    //Returns 8 to func(3, 4)
```

7. (a)

```
func(7):
    static int i=0;
    if(n/2){//7/2= 3 is TRUE
        i--;//static i is decremented to -1
        return func(n/2)+i; //func(3) is called. func(7)
        returns -4-2 i.e -6
    }else return i;
```

```
func(3):
    static int i=0;
    if(n/2){//3/2= 1 is TRUE
        i--;//static i is decremented to -2
        return func(n/2)+i; //func(1) is called. func(1)
        returns -2. func(3) returns -2-2 i.e -4
    }else return i;
```

8. (c)

```
For i=0 in main():
    display():
        static int i;/i=0
        if(i<=printf("GATE24")){//i<=6; printf() executed
            i=i+2;//i=2
            display();
        }
```

```
display():
    static int i;
    if(i<=printf("GATE24")){//2<=6; printf() executed
        i=i+2;//i=4
        display();
    }
```

```
display():
    static int i;
    if(i<=printf("GATE24")){//4<=6; printf() executed
        i=i+2;//i=6
        display();
    }
```

```

display():
    static int i;
    if(i<=printf("GATE24")){//6<=6; printf() executed
        i=i+2;//i=8
        display();
    }
display():
    static int i;
    if(i<=printf("GATE24")){//8<=6 is FALSE but
        printf() executed
        i=i+2;
        display();
    }

```

For i=1 in main:

```

display():
    static int i;
    if(i<=printf("GATE24")){//8<=6 is FALSE but
        printf() executed
        i=i+2;
        display();
    }

```

For i=2 in main():

```

display():
    static int i;
    if(i<=printf("GATE24")){//8<=6 is FALSE but
        printf() executed
        i=i+2;
        display();
    }

```

Total number of times printf() executed is 7.



For more questions, kindly visit the library section: Link for app: <https://physicswallah.live/tabs/tabs/library-tab>

For more questions, kindly visit the library section: Link for web: <https://links.physicswallah.live/vyJw>

Any issue with DPP, please report by clicking here- <https://forms.gle/t2SzQVvQcs638c4r5>



PW Mobile APP: <https://play.google.com/store/apps/details?id=xyz.pencil.physicswala>

For PW Website: <https://www.physicswallah.live/contact-us>