NAME: Aravindan S G REG NO: 230701031

EX N0:14

MongoDB Queries for Restaurants and Movies Collections

Restaurants Collection Queries

```
1. Find restaurants that don't serve 'American' or 'Chinese' or whose names start with 'Wil':
   db.restaurants.find({
   $or: [
     { cuisine: { $nin: ["American", "Chinese"] } },
    { name: { $regex: /^Wil/, $options: 'i' } }
   ]
 }, { restaurant_id: 1, name: 1, borough: 1, cuisine: 1 });
2. Find restaurants with a grade of 'A' and score 11 on '2014-08-11':
 db.restaurants.find({
   "grades": { $elemMatch: { "grade": "A", "score": 11, "date": ISODate("2014-08-11T00:00:00Z") }
} }, { restaurant id: 1, name: 1, grades: 1 });
3. Find restaurants where the 2nd element of grades contains a grade 'A' and score 9 on
   '20140811':
 db.restaurants.find({
   "grades.1.grade": "A",
   "grades.1.score": 9,
   "grades.1.date": ISODate("2014-08-11T00:00:00Z")
 }, { restaurant_id: 1, name: 1, grades: 1 });
4. Find restaurants where the 2nd element of `coord` array contains a value more than 42 and up
   to 52:
 db.restaurants.find({
   "address.coord.1":{$gt: 42, $lte: 52}
 }, { restaurant_id: 1, name: 1, address: 1, "address.coord": 1 });
```

```
5. Arrange restaurant names in ascending order with all columns:
 db.restaurants.find().sort({ name: 1});
6. Arrange restaurant names in descending order with all columns:
 db.restaurants.find().sort({ name: -1});
7. Arrange cuisine in ascending order and borough in descending order:
 db.restaurants.find().sort({ cuisine: 1, borough: -1 });
8. Check if all addresses contain the street field:
 db.restaurants.find({"address.street":{$exists:true}});
9. Select all documents where the `coord` field value is of type Double:
 db.restaurants.find({"address.coord":{$type:"double"}});
10. Find restaurants where score is divisible by 7: db.restaurants.find({
    "grades": { $elemMatch: { "score": { $mod: [7, 0] } } }
  }, { restaurant_id: 1, name: 1, grades: 1 });
11. Find restaurants where name contains 'mon':
  db.restaurants.find({
                           name:{
$regex: "mon", $options: "i" }
  }, { name: 1, borough: 1, "address.coord": 1, cuisine: 1});
12. Find restaurants where name starts with 'Mad':
  db.restaurants.find({
                           name: { $regex:
"^Mad", $options: "i" }
  }, { name: 1, borough: 1, "address.coord": 1, cuisine: 1});
```

```
13. Find restaurants with at least one grade with a score less than 5: db.restaurants.find({
   "grades": { $elemMatch: { "score": { $lt: 5 } } }
  });
14. Find restaurants with at least one grade with a score less than 5 and located in Manhattan:
  db.restaurants.find({
   "grades": { $elemMatch: { "score": { $lt: 5 } } },
borough: "Manhattan"
  });
15. Find restaurants with at least one grade with a score less than 5 in Manhattan or Brooklyn:
  db.restaurants.find({
   "grades": { $elemMatch: { "score": { $lt: 5 } } },
borough: { $in: ["Manhattan", "Brooklyn"] }
  });
16. Find restaurants with at least one grade with a score less than 5 in Manhattan or Brooklyn and
   not American cuisine: db.restaurants.find({
   "grades": { $elemMatch: { "score": { $lt: 5 } } },
borough: { $in: ["Manhattan", "Brooklyn"] }, cuisine: {
$ne: "American" }
  });
17. Find restaurants with at least one grade with a score less than 5 in Manhattan or Brooklyn and
   not American or Chinese cuisine:
  db.restaurants.find({
    "grades":{ $elemMatch:{ "score":{ $lt:5}}},
borough: { $in: ["Manhattan", "Brooklyn"] }, cuisine: {
$nin:["American", "Chinese"] }
  });
18. Find restaurants with grades having a score of 2 and a score of 6:
```

```
db.restaurants.find({      grades: { $all: [{ $elemMatch: { score: 2 } }, {
$elemMatch:{ score: 6 } }] }
 });
19. Find restaurants with grades having a score of 2 and a score of 6 in Manhattan:
  db.restaurants.find({ grades: { $all: [{ $elemMatch: { score: 2 } }, {
$elemMatch:{ score: 6 } }] }, borough: "Manhattan"
 });
20. Find restaurants with grades having a score of 2 and a score of 6 in Manhattan or Brooklyn:
  db.restaurants.find({ grades: { $all: [{ $elemMatch: { score: 2 } }, {
$elemMatch:{score:6}}]}, borough:{$in:["Manhattan","Brooklyn"]}
 });
21. Find restaurants with grades having a score of 2 and a score of 6 in Manhattan or Brooklyn and
   not American cuisine: db.restaurants.find({ grades: { $all: [{ $elemMatch: { score: 2 }}, {
   $elemMatch:{score:6}}]}, borough:{$in:["Manhattan", "Brooklyn"]}, cuisine:{$ne:
   "American" }
 });
22. Find restaurants with grades having a score of 2 and a score of 6 in Manhattan or Brooklyn and
   not American or Chinese cuisine:
  db.restaurants.find({     grades: { $all: [{ $elemMatch: { score: 2 } }, {
$elemMatch:{ score: 6 } }] }, borough:{ $in: ["Manhattan", "Brooklyn"]
}, cuisine: { $nin: ["American", "Chinese"] }
 });
23. Find restaurants with a grade of 2 or a grade of 6: db.restaurants.find({
   $or: [{"grades.score": 2}, { "grades.score": 6}]
 });
Movies Collection Queries
```

```
1. Find movies released in 1893:
 db.movies.find({
year: 1893
 });
2. Find movies with runtime greater than 120 minutes:
 db.movies.find({
runtime: { $gt: 120 }
 });
3. Find movies with genre 'Short':
 db.movies.find({
genres: "Short"
 });
4. Find movies directed by 'William K.L. Dickson': db.movies.find({ directors: "William K.L.
  Dickson"
 });
5) Find movies released in the USA:
db.movies.find({
countries: "USA"
});
6. Find movies released in the USA:
 db.movies.find({
countries: "USA"
 });
7. Find movies rated as 'UNRATED':
 db.movies.find({
rated: "UNRATED"
 });
```

```
8. Find movies with more than 1000 votes on IMDb:
 db.movies.find({
   "imdb.votes": { $gt: 1000 }
 });
9. Find movies with IMDb rating higher than 7: db.movies.find({
                                                                        "imdb.rating": { $gt: 7 }
 });
10. Find movies with viewer rating higher than 4 on Tomatoes:
  db.movies.find({
    "tomatoes.viewer.rating": { $gt: 4 }
  });
11. Find movies that have received an award:
  db.movies.find({
    "awards.wins": { $gt: 0 }
  });
12. Find movies with at least one nomination:
  db.movies.find({
    "awards.nominations": { $gt: 0 }
  }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, awards: 1, year: 1, genres: 1,
runtime: 1, cast: 1, countries: 1 });
13. Find movies with cast including 'Charles Kayser': db.movies.find({ cast: "Charles Kayser"
  }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, awards: 1, year: 1, genres: 1,
runtime: 1, cast: 1, countries: 1 });
14. Find movies released on May 9, 1893:
  db.movies.find({
                       released:
ISODate("1893-05-09T00:00:00Z")
  }, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, countries: 1 });
```

```
15. Find movies with 'scene' in the title: db.movies.find({ title: { $regex: "scene", $options: "i" }
}, { title: 1, languages: 1, released: 1, directors: 1, writers: 1, countries: 1 });
```