

## MODULE PRACTICE

### Recursive Step in Recursive Function

```
def countdown(value):  
    if value <= 0:  
        print("done")  
    else:  
        print(value)  
        countdown(value-1) #recursive step
```

A recursive function should have a **recursive step** which calls the recursive function with some input that brings it closer to its base case. In the example, the recursive step is the call to `countdown()` with a decremented value.

### Big-O Runtime for Recursive Functions

The big-O runtime for a recursive function is equivalent to the number of recursive function calls. This value varies depending on the complexity of the algorithm of the recursive function. For example, a recursive function of input  $N$  that is called  $N$  times will have a runtime of  $O(N)$ . On the other hand, a recursive function of input  $N$  that calls itself twice per function may have a runtime of  $O(2^N)$ .


### **Weak Base Case in Recursive Function**

A recursive function with a weak base case will not have a condition that will stop the function from recursing, causing the function to run indefinitely. When this happens, the call stack will overflow and the program will generate a *stack overflow* error.

### **Execution Context of a Recursive Function**

An execution context of a recursive function is the set of arguments to the recursive function call. Programming languages use execution contexts to manage recursive functions.

## A Call Stack Calculating 4!




We want to calculate 4!

## Call Stack in Recursive Function

8/12

A Call Stack Calculating 4!



Calculating 4!

4th call

Programming languages use a facility called a **call stack** to manage the invocation of recursive functions. Like a stack, a call stack for a recursive function calls the last function in its stack when the **base case** is met.

## Base Case of a Recursive Function

```
function countdown(value)
  if value is negative or zero
    print "done"
  otherwise if value is greater than zero
    print value
    call countdown with (value-1)
```

A recursive function should have a base case with a condition that stops the function from recursing indefinitely. In the example, the base case is a condition evaluating a negative or zero value to be true.

## What is Recursion

Recursion is a strategy for solving problems by defining the problem in terms of itself. A recursive function consists of two basic parts: the base case and the recursive step.