

HULK

Rafael A. Sanchez Martinez
University of Havana
Group: C-113



Figure 1: Havana University Language for Kompilers

1 Introduction

Welcome to the user manual of HULK, the programming language of the University of Havana. This manual is divided into 5 sections, each one dedicated to a part of the interpreter. The first section explains how to install the interpreter, the second section explains how to use the interpreter, the third section explains how to use the lexical analyzer, the fourth section explains how to use the syntax analyzer and the fifth section Explains how to use the expression evaluator.

1.1 Start

- To start using the interpreter, you must download the source code of the interpreter from the project's github repository. Once the source code has been downloaded, the project must be run using the 'dotnet run' command from a terminal open in the project folder.
- Another option is to run the script which will take care of everything
- See previous report in https://github.com/ARKye03/mini_kompiler.git

1.2 Summary

HULK (Havana University Language for Compilers) is an educational, type-safe, object-oriented and incremental programming language, designed for the Introduction to Compilers course of the Computer Science degree at the University of Havana.

A simple 'Hola Mundo' in HULK looks like this:

```
print('Hola mundo')
```

From a bird's eye view, HULK is an object-oriented programming language, with simple inheritance, polymorphism, and class-level encapsulation. Additionally, in HULK it is possible to define global functions outside the scope of all classes. It is also possible to define a single global expression that constitutes the entry point to the program.

Most syntactic constructs in HULK are expressions, including conditional statements and loops. HULK is a statically typed language with optional type inference, meaning that some (or all) parts of a program can be annotated with types and the compiler will check all operations for consistency.

But, in this case, since it is a project for 1st year students, it is a bit simplified. In this case, let's say, we have a one-line interpreter, which allow us, to evaluate expressions like:

- Like I said above, `print("Hello World")`
 - Which is equivalent to `print("Hello" + "World")`
 - And `print("Hello" @ "World")`
- All basics 'instructions' can handle simple math expressions like:
 - `"2 ± 5;"` — `"147.6 ± -63;"`
 - `"8 × 2;"` — `"200 ÷ 3;"`
 - `"264;"` — `"sqrt(3969)"` → `"√3969"` — `"log(2, 10);"`

- Mathematical functions:

Sin(x): Returns the sine of x, where x is in radians. Example: Sin(0) returns 0.

Cos(x): Returns the cosine of x, where x is in radians. Example: Cos(0) returns 1.

Tan(x): Returns the tangent of x, where x is in radians. Example: Tan(0) returns 0.

Log(x): Returns the natural logarithm (base 10) of x. Example: Log(1) returns 0.

Ln(x): Returns the natural logarithm (base e) of x. Example: Ln(1) returns 0.

Sqrt(x): Returns the square root of x. Example: Sqrt(4) returns 2.

Abs(x): Returns the absolute value of x. Example: Abs(-5) returns 5.

Pow(x, y): Returns x raised to the power of y. Example: Pow(2, 3) returns 8.

Exp(x): Returns e raised to the power of x. Example: Exp(1) returns approximately 2.71828.

Floor(x): Returns the largest integer less than or equal to x. Example: Floor(1.5) returns 1.

Ceil(x): Returns the smallest integer greater than or equal to x. Example: Ceil(1.5) returns 2.

Round(x): Rounds x to the nearest integer. Example: Round(1.5) returns 2.

Rand(min, max): Returns a random integer between min (inclusive) and max (exclusive). Example: Rand(10, 20) returns a random number between 10 and 20.

- And thats pretty much it $\wedge \times \wedge$

- Evaluable expressions are:

- Printing:

This expression keyword receives another expressions as argument, and evaluates it, and print the returned value

print(55); shows 55 — *print*("Kitty"); shows Kitty

- Variables:

This one, contains two important keywords, "LetKeyword" and "InKeyword".

A basic let-in expression is: "let < var_name > in < statement >"

Example: "let x = $(63 \pm 109)^2$ in *print*(x); "

- Conditions:

Basic and classic conditions:

if (condition) < do_if_true > else < do_if_false >

"if (1024 % 2 == 0) *print*("Even") else *print*("Odd"); "

- Functions:

- * Declare functions:

To declare functions simple do:

function *function_name*(arguments) => < statement >;

Example: function Pow(*x*, *y*) => x^y ;

This can be used like:

"let number = Pow(2, 5) in *print*(number); "

- Note: A statement is basically another instruction or expression.

- Some expressions can be:
 1. `print("Hello World");`
 2. `print((((1 + 2)3) * 4) / 5);`
 3. `print(sin(2 * PI)2 + cos(3 * PI / log(4, 64)));`
 4. `function tan(x) => sin(x) / cos(x);`
 5. `let x = $PI/2$ in print(tan(x));`
 6. `let number = 42, text = "The meaning of life is" in print(text @ number);`
 `– let number = 42 in (let text = "The meaning of life is" in (print(text @ number)));`
 7. `print(7 + (let $x = 2$ in $x * x$));`
 8. `let a = 42 in if (a % 2 == 0) print("Even") else print("odd");`
 9. `let a = 42 in print(if (a % 2 == 0) "even" else "odd");`
 10. `function fib(n) => if ($n > 1$) fib($n - 1$) + fib($n - 2$) else 1;`
- And on and on, use your imagination, except if you are my programming teacher, please don't get creative, I beg you.

2 Lexer

2.1 Lexer Summary

A Lexer, also known as a lexical analyzer, tokenizer, or scanner, is a program or function that breaks down input code into a sequence of tokens. These tokens are meaningful units of code.

In the process of parsing programming languages, this task is traditionally split up into two phases: the lexing stage and the parsing stage. The lexer's job is simpler than the parser's. It turns the meaningless string into a flat list of things like “number literal”, “string literal”, “identifier”, or “operator”. It can also recognize reserved identifiers (“keywords”) and discard whitespace.

The output of the lexer is used as the input for the parser. The parser then has the much harder job of turning the stream of “tokens” produced by the lexer into a parse tree representing the structure of the parsed language. This separation allows the lexer to do its job well and for the parser to work on a simpler, more meaningful input than the raw text.

More info about:

- What's a Lexer
- The Lexer - ACCU
- Extra blog

2.2 Now, my Lexer

First I've defined some simple Token types in this “enum”:

```
public enum TokenType
{
    FLinq, //Link token for function declaration
    ComparisonOperator,
    Number, // Number
    StringLiteral, // Literally a string
    FunctionDeclaration, // Well, deprecated
    LetKeyword,
    IfKeyword,
    ElseKeyword,
    PrintKeyword,
    InKeyword,
    FunctionKeyword,
    Operator, // '+', '-', '*', '/', '^', '='...
    Punctuation, // '(', ')', '&', ','
    Identifier, //Used for variables name and functions value
    EOL, //';'
    EOF, //Not yet
    Semicolon, //Idk man/woman
    Separator // '@', and in a future, "||", "&&"...
}
```

Basically, my Tokens, have a few properties:

```
public TokenType type; // From enum
public string value; // Text of the token
public int line; // Line position, currently 1, always
public int column; // Column position
```

Note: ToString override is there to test tokens only.

Some functions of my lexer

- `advance()`: One char to the right.
- `skip_whitespace()`: Jumps to next non-blank char.
- `peek()`: Takes a look to next token, without taking it.
- `unget_token()`: Drops next token, to use it later.
- Some Token functions. Take a summary along the code itself

The main function

The `get_next_token()` not that simple C# method that tokenizes a source code string for a programming language interpreter. This method reads characters from the source code and categorizes them into different types of tokens like operators, punctuation, keywords, etc.

If you're asking for an explanation of this code, here's a brief overview:

- The `'get_next_token'` method is used to get the next token from the source code.
- It first checks if there are any tokens already read and not processed. If so, it returns the first one and removes it from the list.
- If there are no pre-read tokens, it starts reading the source code character by character.
- Depending on the current character, it categorizes it into a token type (like operator, punctuation, keyword, etc.) and returns a new token of that type.
- It also handles multi-character tokens like `'=>'`, `'=='`, `'<='`, `'>='`, and `'!= '`.
- If it encounters a newline character (`'\n'`), it increments the line count and resets the column count.
- If it encounters an unrecognized character, it prints an error message.
- If it reaches the end of the source code, it returns an EOF (end-of-file) token.

The `'function_declaration()'`: used to parse a function declaration in the source code of a programming language. Here's a brief overview of what it does:

- It first checks if the next token is a function keyword and then expects an identifier (the function name).
- It reads the function name by appending all the non-whitespace characters.
- It then checks for an opening parenthesis `'('` to start the function parameters list.
- It reads all the parameters of the function, separated by commas `','`, and adds them to a list.
- It then expects a `'=> '` token, which presumably indicates the start of the function body.
- It reads all the tokens of the function body until it encounters a semicolon `';'` or an EOF (end-of-file) token, indicating the end of the function body.
- Finally, it returns a `'FunctionToken'` that represents the function declaration, including its name, parameters, and body. Note: This `'Token'`, turns to `'DFunction'`.

3 Interpreter

3.1 Parser

A parser is a program or a component of a program that analyzes a string of symbols according to a set of rules. A parser can be used for different purposes, such as understanding natural language, processing computer languages, or parsing data structures. A parser typically breaks down the input into smaller units called tokens, and then assigns them to categories based on their syntax and semantics. A parser may also produce a representation of the input, such as a parse tree or an abstract syntax tree, that shows the hierarchical structure and the relationships between the tokens.

3.2 My Parser

In my case, I handle, 2 types of ‘expressions’, basic statements, and return expressions, the first ones, generally are used to print values, second ones to handle complex operations, you won’t even notice them, there are a third type of expression, that derives from the return expressions, used only on declared functions.

My parsing life starts with the `Run()` function, used to parse and execute a series of statements in the source code of a programming language. This is an overview:

- It first gets the next token from the lexer, using ‘main’ lexer function above explained.
- If the token is a `PrintKeyword`, it expects an opening parenthesis ‘(’, evaluates the expression inside the parenthesis, checks for a closing parenthesis ‘)’, and then prints the result of the evaluated expression.
- If the token is a `LetKeyword`, it calls the `assignment()` method to process the assignment of values to variables.
- If the token is an `IfKeyword`, it calls the `Conditional()` method to process the conditional instruction.

Some Statements must be processed, for that there is `statement()`:

- Basically does the same as `Run()`, but with extras
- If the token is an ‘Identifier’ or ‘Number’, it does nothing.
- If the token is an ‘EOF’ (end-of-file), it returns from the method.
- If the token is not recognized, it prints an error message.
- Finally, it checks if there is a semicolon (end-of-line ‘EOL’ token) and either advances to the next statement or returns the token to the lexer to be analyzed in the next iteration.

Let-In expressions are handled with `assignment()` method:

- It first gets the next token from the lexer, which should be an identifier (the variable name).
- It then expects an equals ‘=’ operator.
- It evaluates the expression on the right side of the equals operator to get the assigned value.
- It assigns the value to the variable in the variables dictionary.
- It then checks if there is a comma, indicating another assignment statement, and recursively calls `assignment()` if there is. If there is no comma, it expects an in keyword. Finally, it calls the `statement()` method to execute the next statement.

Basic conditional statements, processed by Conditional():

- It first gets the next token from the lexer, which should be an opening parenthesis ‘(’.
- It then evaluates the left-hand side of the comparison, expects a comparison operator, and evaluates the right-hand side of the comparison.
- It checks for a closing parenthesis ‘)’.
- It then performs the comparison operation based on the comparison operator and stores the result.
- If the comparison result is true, it calls the statement() method to execute the next statement.
- If the comparison result is false, it skips to the else part of the if-else statement and executes the statement there.
- If there is no else part, it prints an error message.

Note: RConditional() and RConditional(List|Token| tokens), are simple variations of Conditional(), used on return expressions and functions return expressions respectively.

3.3 Recursive Descent Parser

The jewel in the crown revolves around these functions, they are what allow everything to flow as well as my programming skills allow.

- expression()
 - It first evaluates a term.
 - It then enters a loop where it gets the next token from the lexer and checks if it’s an operator.
 - If the operator is @, it evaluates the next term and concatenates it with the left-hand side.
 - If the operator is + or -, it evaluates the next term and performs the binary operation with the left-hand side and the operator.
 - If the token is not an operator, it returns the token to the lexer and returns the left-hand side as the result of the expression.
- term()
 - It first evaluates a power.
 - It then enters a loop where it gets the next token from the lexer and checks if it’s a multiplication, division, or modulo operator.
 - If the token is not one of these operators, it returns the token to the lexer and returns the left-hand side as the result of the term.
 - If the token is one of these operators, it evaluates the next power and performs the binary operation with the left-hand side and the operator.
- power()
 - It first evaluates a primary expression.
 - It then enters a loop where it gets the next token from the lexer and checks if it’s a power operator ^.
 - If the token is not a power operator, it returns the token to the lexer and returns the left-hand side as the result of the power expression.
 - If the token is a power operator, it evaluates the next primary expression and performs the binary operation with the left-hand side and the operator.

- `primary()`
 - It first gets the next token from the lexer.
 - It checks if the token is a function call, and if so, it parses the arguments and calls the function.
 - If the token is a number, it returns the number.
 - If the token is a string literal, it returns the string.
 - If the token is an identifier, it returns the value of the variable with that name.
 - If the token is an opening parenthesis `(`, it evaluates the expression inside the parentheses.
 - If the token is a `let` keyword, it parses a `let-in` expression.
 - If the token is an `if` keyword, it parses an `if-else` expression.
 - If the token is a minus operator `-`, it negates the next number.
 - If the token is none of the above, it prints an error message.

Note: These functions each have an overload specifically designed to handle expressions within functions. Check `fnizer.cs`

The function that performs Binary Operations on two operands. Simple overview:

- It first checks if the operator token is indeed an operator.
- If the operator is `+`, it adds the operands if they are both floats or concatenates them if they are both strings.
- If the operator is `-`, it subtracts the operands if they are both floats.
- If the operator is `@`, it concatenates the operands if they are both strings.
- If the operator is `*`, it multiplies the operands if they are both floats.
- If the operator is `;`, it raises the left operand to the power of the right operand if they are both floats.
- If the operator is `/`, it divides the left operand by the right operand if they are both floats.
- If the operator is
- If the operator is none of the above, it prints an error message.
- If the token is not an operator, it prints an error message.

An extra encapsulation is `ConcatenateValues()`:

- If both operands are strings, it concatenates them.
- If one of the operands is a string, it converts the other operand to a string and then concatenates them.
- If neither operand is a string, it tries to add them if they are both floats.
- If the operands cannot be concatenated or added, it prints an error message.

4 Introduction

This is the report of my compiler project. The compiler is written in C++ and

5 Introduction

This is the report of my compiler project. The compiler is written in C++ and