## mbed TLS Introduction

## **ARM**

Simon Butcher
Principal Security Engineer
mbed TLS Tech Lead

Silicon Partner Workshop - Wyboston Lakes March 2017

Confidential © ARM 2017

## Agenda

- What is mbed TLS?
- History of mbed TLS
- Why mbed TLS?
- Applications and Use Cases
- Why trust mbed TLS?
- Features Supported by Hardware Features
- Indicative Code Sizes
- Workshop Outcomes




#### What is mbed TLS?

- Open Source
  - Available under GPL and Apache licenses
  - Contributions actively encouraged from the community
- Self-contained small footprint SSL/TLS library
  - Suitable for embedded and constrained devices, PCs, and servers
  - Highly configurable to reduce footprint to suit required features
- Cryptography library
  - Suitable for use on its own or with the TLS library
- Mature
  - Around for several years, trusted and proven (and subject of many research papers)
  - Strong track record of maintenance and support
  - Ongoing support for previous releases 1.3 and 2.1(LTS)



#### mbed TLS as a Product

- mbed TLS is a product in itself, with its own:
  - Customers
  - Releases (independent of mbed OS)
  - Website
  - Support forum
  - Knowledgebase
  - Security Advisories
  - Bug Bounty





## History of mbed TLS

- Created in 2006 as XySSL, by Christophe Devine, the Security Researcher famous for Aircrack
- Maintenance passed to Paul Bakker in 2008, who founded OffSpark, renaming it to PolarSSL
- Purchased by ARM in November 2014, and renamed to mbed TLS



Christophe Devine (Image courtesy SoldierX)






## Why mbed TLS?



- Leveraging established standards, best practice
- Fully-fledged SSL / TLS / DTLS Library
- Developer friendly: Clean API and documentation
- High assurance: Extensive testing
- Practical: Flexible, small footprint

Transport Security	Symmetric Encryption	Public Key Algorithms	Hash Algorithms	Random Number Generation	X.509 Certificate Handling
TLS/DTL S	AES, 3DES, DES, Blowfish, ARC4, Camellia, XTEA	ECDHE, ECDSA, FFDHE, RSA, FFDH, ECDH	MD2, MD4, MD5, SHA-I, SHA-2, RIPEMD-160	Entropy pool, CTR_DRBG, HMAC_DRBG	<b>√</b>



#### Many Possible Use Cases

- Secure communications
  - TLS/DTLS and as a cryptographic library for Thread
- Authentication cryptographic signing and verification
  - Image verification for secure boot or authenticating patches for update
- Provisioning
  - Remote configuration and secure deployment
- Persistent and volatile data protection
  - Protecting on-device data



#### mbed TLS Core Features

- Client and Server support of SSL v3,TLS v1.0/v1.1/v1.2, DTLS v1.0/v1.2
- Key exchange methods
  - RSA, FFDHE-RSA, ECDHE-RSA, ECDH-RSA, ECDHE-ECDSA
  - Pre-shared keys FFDHE-PSK, ECDHE-PSK, RSA-PSK, PSK (no public key)
- NIST Suite B Compliance
- Crypto Algorithms
  - AES, Blowfish, 3DES, DES, ARC4, Camellia, XTEA
  - Modes ECB, CBC, CFB, CTR, GCM, CCM
  - Hash MD2, MD4, MD5, SHA-1, SHA-224, SHA-256, SHA-384, SHA-512, RIPEMD-160
  - ECC NIST, Koblitz, Brainpool curves and Curve25519
  - MAC HMAC, CMAC
- X.509 reading/writing and validation PEM/DER formats



#### How we handle security defects

- Security Researchers and academics occasionally report defects/vulnerabilities
- Such defects or vulnerabilities may not be immediately exploitable
- Significant defects can lead to CVE codes and security advisories
- Security updates and advisories are issued when necessary

#### Dismantling real-world ECC with Horizontal and Vertical Template Attacks

Margaux Dugardin<sup>1,2</sup>, Louiza Papachristodoulou<sup>3</sup>, Zakaria Najm<sup>1</sup>, Lejla Batina<sup>3</sup>, Jean-Luc Danger<sup>1</sup>, Sylvain Guilley<sup>1</sup>, Jean-Christophe Courrège<sup>2</sup>, and

<sup>1</sup> TELECOM ParisTech, COMELEC, 46 rue Barrault, 75014 Paris, France firstname.lastname@telecom-paristech.fr

<sup>2</sup> Thales Communications & Security, CESTI, 3 avenue de l'Europe, 31000 Toulouse, France

<sup>3</sup> Radboud University Nijmegen, Digital Security Group, P.O. Box 9010, 6500 GI Nijmegen, The Netherlands

lejla@cs.ru.nl, louiza@cryptologio.org

Abstract. Recent side-channel attacks on elliptic curve algorithms have shown that the security of these cryptosystems is a matter of serious concern. The development of techniques in the area of Template Attacks makes it feasible to extract a 256-bit secret key with only 257 traces. This paper enhances the applicability of this attack by exploiting both the horizontal leakage of the carry propagation during the finite field multiplication, and the vertical leakage of the input data. As a further contribution, our method provides detection and auto-correction of possible errors that may occur during the key recovery. These enhancements come at the cost of extra traces, while still providing a practical attack. Finally, we show that the elliptic curve technology developed in PolarSSL running on a ARM STM32F4 platform is completely vulnerable, when



## Features Supported by HW Feature

Entropy Support	Network	Available Features
X	X	<ul> <li>Some cryptographic primitives</li> <li>No key generation</li> <li>Authentication, not secure communications</li> </ul>
	X	<ul><li>All cryptographic primitives</li><li>Key generation</li><li>Secure communication, but not TLS</li></ul>
		<ul><li>All cryptographic primitives</li><li>Key generation</li><li>Full TLS/DTLS Support</li></ul>



## Typical Code Size Figures for mbed TLS 2.4.2

Estimated code size (flash/ROM) figures for current development version of mbed TLS 2.4.2

Configuration Profile*	Code Size (approx)
mbed TLS Default	248kb
mbed OS 5.4.1 default	I70kb
Thread	58kb
NIST Suite B	80kb
Pre-shared Key	28kb



<sup>\*</sup> arm-none-eabi-gcc 5.3. I used to obtain figures with flag -Os.

# Workshop Agenda for mbed TLS

#### Targets for the workshop

- Understand of how to integrate entropy sources
- Understand of how to integrate hardware acceleration support into mbed TLS
- Be able to test and benchmark mbed TLS performance with your hardware
- Know how to contribute code changes to mbed TLS
- Know what is expected of contributed code to be accepted



#### Feedback welcome

- Hardware accelerators come in many different shapes
- mbed TLS API for acceleration and extension is not fixed!
- Feedback on how the API can be adjusted to fit *your* hardware is more than welcome!



# Questions?

