Jason

Strength S, S_y, S_u

inherent property
of the object
geometry, material

Stress
property of object
state and location
$\sigma, \tau \rightarrow$ shear stress
$\hookrightarrow$ normal

Factor of Safety

The yield strength of hot rolled steel is 220 Mpa.

Design ~~Sel~~ Factor

$$n_d = \frac{\text{loss-of-function param}}{\text{max allowable param}}$$

If the load that will cause failure is between 90 and 110 lbs and you'd like a design factor of 2, what is the max allowable load?

A. 45 lbs
B. 50 lbs
C. 55 lbs

Factor of Safety

$$n_d = \frac{\text{Yield Strength}}{\text{max stress}} = \frac{S_y}{\sigma_{max}}$$

Table A–17

Preferred Sizes and Renard (R-Series) Numbers (When a choice can be made, use one of these sizes; however, not all parts or items are available in all the sizes shown in the table.)

Fraction of Inches

$\frac{1}{64}$, $\frac{1}{32}$, $\frac{1}{16}$, $\frac{3}{32}$, $\frac{1}{8}$, $\frac{5}{32}$, $\frac{3}{16}$, $\frac{1}{4}$, $\frac{5}{16}$, $\frac{3}{8}$, $\frac{7}{16}$, $\frac{1}{2}$, $\frac{9}{16}$, $\frac{5}{8}$, $\frac{11}{16}$, $\frac{3}{4}$, $\frac{7}{8}$, 1, $1\frac{1}{4}$, $1\frac{1}{2}$, $1\frac{3}{4}$, 2, $2\frac{1}{4}$, $2\frac{1}{2}$, $2\frac{3}{4}$, 3, $3\frac{1}{4}$, $3\frac{1}{2}$, $3\frac{3}{4}$, 4, $4\frac{1}{4}$, $4\frac{1}{2}$, $4\frac{3}{4}$, 5, $5\frac{1}{4}$, $5\frac{1}{2}$, $5\frac{3}{4}$, 6, $6\frac{1}{2}$, 7, $7\frac{1}{2}$, 8, $8\frac{1}{2}$, 9, $9\frac{1}{2}$, 10, $10\frac{1}{2}$, 11, $11\frac{1}{2}$, 12, $12\frac{1}{2}$, 13, $13\frac{1}{2}$, 14, $14\frac{1}{2}$, 15, $15\frac{1}{2}$, 16, $16\frac{1}{2}$, 17, $17\frac{1}{2}$, 18, $18\frac{1}{2}$, 19, $19\frac{1}{2}$, 20

Decimal Inches

0.010, 0.012, 0.016, 0.020, 0.025, 0.032, 0.040, 0.05, 0.06, 0.08, 0.10, 0.12, 0.16, 0.20, 0.24, 0.30, 0.40, 0.50, 0.60, 0.80, 1.00, 1.20, 1.40, 1.60, 1.80, 2.0, 2.4, 2.6, 2.8, 3.0, 3.2, 3.4, 3.6, 3.8, 4.0, 4.2, 4.4, 4.6, 4.8, 5.0, 5.2, 5.4, 5.6, 5.8, 6.0, 7.0, 7.5, 8.5, 9.0, 9.5, 10.0, 10.5, 11.0, 11.5, 12.0, 12.5, 13.0, 13.5, 14.0, 14.5, 15.0, 15.5, 16.0, 16.5, 17.0, 17.5, 18.0, 18.5, 19.0, 19.5, 20

Millimeters

0.05, 0.06, 0.08, 0.10, 0.12, 0.16, 0.20, 0.25, 0.30, 0.40, 0.50, 0.60, 0.70, 0.80, 0.90, 1.0, 1.1, 1.2, 1.4, 1.5, 1.6, 1.8, 2.0, 2.2, 2.5, 2.8, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0, 6.5, 7.0, 8.0, 9.0, 10, 11, 12, 14, 16, 18, 20, 22, 25, 28, 30, 32, 35, 40, 45, 50, 60, 80, 100, 120, 140, 160, 180, 200, 250, 300

Renard Numbers*

1st choice, R5: 1, 1.6, 2.5, 4, 6.3, 10

2d choice, R10: 1.25, 2, 3.15, 5, 8

3d choice, R20: 1.12, 1.4, 1.8, 2.24, 2.8, 3.55, 4.5, 5.6, 7.1, 9

4th choice, R40: 1.06, 1.18, 1.32, 1.5, 1.7, 1.9, 2.12, 2.36, 2.65, 3, 3.35, 3.75, 4.25, 4.75, 5.3, 6, 6.7, 7.5, 8.5, 9.5

*May be multiplied or divided by powers of 10.

5

A square cross section rod is loaded axially with a static load of 1000±10 lbs. The strength of the material is 25 kpsi and the desired design factor is 4. Determine the minimum width of the square cross section. Then select a preferred fractional inch size from Table A-17 and report the factor of safety.

$$\sigma_{max} = \frac{P_{max}}{A} = \frac{P_{max}}{w^2}$$

$$n_d = \frac{S}{\sigma_{max}} \Rightarrow \sigma_{max} = \frac{S}{n_d}$$

$$w^2 \sigma_{max} = P_{max}$$

$$w^2 = \frac{P_{max}\, n_d}{S}$$

$$w = \sqrt{\frac{P_{max}\, n_d}{S}}$$

6

$$w = \sqrt{\frac{(1010\ \text{lbs})(4)}{(25E3\ \text{psi})}}$$

$w = 0.40\ldots''$

$\frac{7}{16} \Rightarrow 0.4375''$

Factor of Safety

$w_n = 0.4375''$

$$n_d = \frac{S}{\sigma_{max}} = \boxed{\frac{S\, w_n^2}{P_{max}}}$$